

Attachment K
Outside Laboratory Environmental Test Report

Report Date: 10 January 2003

Customer P.O.: 53756 & Rev. 1 through 7

Test Period: 16 September through 11 December 2002

Security Classification: NA

TEST REPORT

FOR

ENVIRONMENTAL TESTING OF THE MODEL NUMBER SRB-406

SURVIVAL RESCUE BEACON (RAFT MOUNTED)

TESTING PERFORMED BY:


FOR:

QUALTEST, INC.
5325 Old Winter Garden Road
Orlando, Florida 32811-1520


DME CORPORATION
6830 Northwest 16th Terracc
Ft. Lauderdale, FL 33309

Website: www.qualtest.com

TEST REPORT PREPARED BY:


Mary Webb, Technical Documentation Specialist

APPROVED BY:


Todd Scarborough, General Manager

QUALITY ASSURANCE:



Mike McCord, Quality Assurance Manager

being duly sworn, deposes and says that the information contained in this report is the result of complete and carefully conducted tests and is to the best of his knowledge true and correct in all respects. Subscribed and sworn to before me,

"CQA Performed IAW One Book"

Not Required

Bill Kennedy, DCM Orlando QAS, S1002A


Susan Kingdon Fields, Notary Public in and for the State of Florida at large, this

22nd day of January, 2003.

State of Florida, County of Orange

Susan Kingdon Fields



My Commission CC885948

Expires August 24, 2003

Qualtest shall have no liability for damages of any kind to person or property, including special or consequential damages, covered by this report. This test report shall not be reproduced except in full, without the written approval of Qualtest.

REPORT REVISION RECORD

REVISION DESCRIPTION OF CHANGE

INITIAL RELEASE

TABLE OF CONTENTS

<u>TITLE</u>	<u>PAGE</u>
FOREWORD	4
SECTION 1	4
LOW TEMPERATURE ACTIVATION TEST SUMMARY	4
1-1 TEST HARDWARE	4
2-1 TEST REQUIREMENTS	4
3-1 TEST SETUP	4
4-1 TEST DESCRIPTION	4
5-1 TEST RESULTS	4
Figure 1-1. Test setup for low temperature activation	4
SECTION 2	4
HIGH TEMPERATURE ACTIVATION TEST SUMMARY	4
1-2 TEST HARDWARE	4
2-2 TEST REQUIREMENTS	4
3-2 TEST SETUP	4
4-2 TEST DESCRIPTION	4
5-2 TEST RESULTS	4
SECTION 3	4
HIGH TEMPERATURE ACTIVATION (RETEST) TEST SUMMARY	4
1-3 TEST HARDWARE	4
2-3 TEST REQUIREMENTS	4
3-3 TEST SETUP	4
4-3 TEST DESCRIPTION	4
5-3 TEST RESULTS	4
SECTION 4	4
ALTITUDE TEST SUMMARY	4
1-4 TEST HARDWARE	4
2-4 TEST REQUIREMENTS	4
3-4 TEST SETUP	4
4-4 TEST DESCRIPTION	4
5-4 TEST RESULTS	4
Figure 1-4. Test setup for altitude.	4
SECTION 5	4
DECOMPRESSION TEST SUMMARY	4
1-5 TEST HARDWARE	4
2-5 TEST REQUIREMENTS	4
3-5 TEST SETUP	4
4-5 TEST DESCRIPTION	4
5-5 TEST RESULTS	4
SECTION 6	4
OVERPRESSURE TEST SUMMARY	4
1-6 TEST HARDWARE	4
2-6 TEST REQUIREMENTS	4

3-6 TEST SETUP	4
4-6 TEST DESCRIPTION.....	4
5-6 TEST RESULTS	4
SECTION 7.....	4
SINUSOIDAL VIBRATION TEST SUMMARY	4
1-7 TEST HARDWARE	4
2-7 TEST REQUIREMENTS.....	4
3-7 TEST SETUP	4
4-7 TEST DESCRIPTION.....	4
5-7 TEST RESULTS	4
Figure 1-7. Test setup for vertical-axis sinusoidal vibration.	4
Figure 2-7. Test setup for longitudinal-axis sinusoidal vibration.....	4
Figure 3-7. Test setup for lateral-axis sinusoidal vibration.....	4
SECTION 8.....	4
SINUSOIDAL VIBRATION (RETEST) TEST SUMMARY	4
1-8 TEST HARDWARE	4
2-8 TEST REQUIREMENTS.....	4
3-8 TEST SETUP	4
4-8 TEST DESCRIPTION.....	4
5-8 TEST RESULTS	4
Figure 1-8. Test setup for vertical-axis sinusoidal vibration (retest) without monitor accelerometer.	4
Figure 2-8. Test setup for longitudinal-axis sinusoidal vibration.....	4
Figure 3-8. Test setup for lateral-axis sinusoidal vibration (retest).....	4
Figure 4-8. Test setup for vertical-axis sinusoidal upswing with monitor accelerometer.	4
SECTION 9.....	4
HUMIDITY TEST SUMMARY	4
1-9 TEST HARDWARE	4
2-9 TEST REQUIREMENTS.....	4
3-9 TEST SETUP	4
4-9 TEST DESCRIPTION.....	4
5-9 TEST RESULTS	4
Figure 1-9. Test setup for humidity.	4
SECTION 10.....	4
SPRAY PROOF TEST SUMMARY	4
1-10 TEST HARDWARE	4
2-10 TEST REQUIREMENTS.....	4
3-10 TEST SETUP	4
4-10 TEST DESCRIPTION.....	4
5-10 TEST RESULTS	4
Figure 1-10. Overall test setup for face 1 spray proof.	4
Figure 2-10. Test setup for face 1 spray proof.....	4
Figure 3-10. Test setup for face 2 spray proof.....	4
Figure 4-10. Test setup for face 3 spray proof.....	4
Figure 5-10. Test setup for face 4 spray proof.....	4
Figure 6-10. Test setup for face 5 spray proof.....	4
Figure 7-10. Test setup for face 6 spray proof.....	4

SECTION 11	4
SPRAY PROOF (RETEST) TEST SUMMARY	4
1-11 TEST HARDWARE	4
2-11 TEST REQUIREMENTS	4
3-11 TEST SETUP	4
4-11 TEST DESCRIPTION	4
5-11 TEST RESULTS	4
Figure 1-11. Typical test setup for face 1 spray proof.	4
Figure 2-11. Typical test setup for face 1 spray proof.	4
Figure 3-11. Typical test setup for face 2 spray proof.	4
Figure 4-11. Typical test setup for face 3 spray proof.	4
Figure 5-11. Typical test setup for face 4 spray proof.	4
Figure 6-11. Typical test setup for face 5 spray proof.	4
Figure 7-11. Typical test setup for face 6 spray proof.	4
SECTION 12	4
IMMERSION TEST SUMMARY	4
1-12 TEST HARDWARE	4
2-12 TEST REQUIREMENTS	4
3-12 TEST SETUP	4
4-12 TEST DESCRIPTION	4
5-12 TEST RESULTS	4
Figure 1-12. Test setup for immersion dryout.	4
SECTION 13	4
SAND AND DUST TEST SUMMARY	4
1-13 TEST HARDWARE	4
2-13 TEST REQUIREMENTS	4
3-13 TEST SETUP	4
4-13 TEST DESCRIPTION	4
5-13 TEST RESULTS	4
Figure 1-13. Test setup for first-aspect sand and dust.	4
Figure 2-13. Test setup for second-aspect sand and dust.	4
Figure 3-13. Test setup for third-aspect sand and dust.	4
Figure 4-13. Test setup for fourth-aspect sand and dust.	4
Figure 5-13. Test setup for fifth-aspect sand and dust.	4
Figure 6-13. Test setup for sixth-aspect sand and dust.	4
SECTION 14	4
SALT SPRAY TEST SUMMARY	4
1-14 TEST HARDWARE	4
2-14 TEST REQUIREMENTS	4
3-14 TEST SETUP	4
4-14 TEST DESCRIPTION	4
5-14 TEST RESULTS	4
Figure 1-14. Test setup for salt spray.	4
Figure 2-14. Test setup for salt spray.	4
SECTION 15	4
OPERATIONAL SHOCK TEST SUMMARY	4

1-15 TEST HARDWARE	4
2-15 TEST REQUIREMENTS.....	4
3-15 TEST SETUP	4
4-15 TEST DESCRIPTION.....	4
5-15 TEST RESULTS	4
Figure 1-15. Test setup for longitudinal-axis operational shock.....	4
Figure 2-15. Test setup for lateral-axis operational shock.....	4
Figure 3-15. Test setup for vertical-axis operational shock.....	4
SECTION 16.....	4
CRASHWORTHINESS SHOCK TEST SUMMARY.....	4
1-16 TEST HARDWARE	4
2-16 TEST REQUIREMENTS.....	4
3-16 TEST SETUP	4
4-16 TEST DESCRIPTION.....	4
5-16 TEST RESULTS	4
Figure 1-16. Test setup for lateral-axis crashworthiness shock.....	4
Figure 2-16. Typical test setup for vertical and longitudinal-axis crashworthiness shock.....	4
SECTION 17.....	4
SALT SPRAY (RETEST) TEST SUMMARY	4
1-17 TEST HARDWARE	4
2-17 TEST REQUIREMENTS.....	4
3-17 TEST SETUP	4
4-17 TEST DESCRIPTION.....	4
5-17 TEST RESULTS	4
Figure 1-17. Test setup for salt spray retest 1.....	4
Figure 2-17. Test setup for salt spray retest 1.....	4
Figure 3-17. Corrosion following salt spray retest 1.....	4
Figure 4-17. Corrosion following salt spray retest 1.....	4
Figure 5-17. Corrosion following salt spray retest 1.....	4
Figure 6-17. Corrosion following salt spray retest 1.....	4
SECTION 18.....	4
POST-CRASH IMMERSION TEST SUMMARY	4
1-18 TEST HARDWARE	4
2-18 TEST REQUIREMENTS.....	4
3-18 TEST SETUP	4
4-18 TEST DESCRIPTION.....	4
5-18 TEST RESULTS	4
Figure 1-18. Test setup for post crash immersion.....	4

This laboratory maintains A2LA accreditation to ISO/IEC 17025 for the specific tests listed in A2LA Certificate #1805.01 and meets the relevant quality systems requirements of ISO 9001:1994. The test results included in this report, however, are not covered by this accreditation.

FOREWORD

The objective of this test program was to subject customer provided test hardware to environmental simulation in compliance with customer stated specifications, including any authorized modifications, deviations or concessions to the original requirements. Test hardware consisted of items identified in the appropriate sections of this report. In addition to test hardware identification, each section contains information that describes the associated test setup and performance, and the resulting data. Qualtest measuring instruments used in testing were calibrated according to the requirements of ANSI/NCSL Z540-1-1994 and are NIST traceable. Calibration records are on file and available for inspection by request. Because the test methods are well established and are qualitative or semi-quantitative in nature, Qualtest does not apply measurement uncertainty unless obligated by contract. Measured value related to the corresponding accuracy requirement is used to decide whether a test meets the requirements of the specification. Any test hardware operational setups and resulting evaluations or inspections performed by the customer are not included in this report, unless they were explicitly requested. While observations and/or specification compliance statements may be reported, no interpretations or opinions regarding customer product performance are intended. Unless otherwise indicated in the appropriate report section, all contract obligations were met and the test objective achieved.