

© Radiated Emission Measurement Results

PASSED.

Date of Test : Sep. 15, 2004 Temperature : 24°C

EUT : Fan-Light Remote Controller
(Transmitter) Humidity : 65%

Test Position : EUT on Stand

Emission Frequency MHz	Antenna Factor dB/m	Cable Loss dB	Meter Reading Horizontal dBμV	Emission Level Horizontal dBμV/m	Limits dBμV/m	Margin dB
------------------------------	---------------------------	---------------------	-------------------------------------	--	------------------	--------------

Fundamental Freq. (Quasi-Peak Value)

304.300	14.87	3.90	54.37	73.14	74.94	1.80
---------	-------	------	-------	-------	-------	------

Emission Frequency MHz	Antenna Factor dB/m	Cable Loss dB	Meter Reading Vertical dBμV	Emission Level Vertical dBμV/m	Limits dBμV/m	Margin dB
------------------------------	---------------------------	---------------------	-----------------------------------	--------------------------------------	------------------	--------------

Fundamental Freq. (Quasi-Peak Value)

304.300	15.17	3.90	39.49	58.56	74.94	16.38
---------	-------	------	-------	-------	-------	-------

Remarks : Emission Level = Antenna Factor + Cable Loss + Meter Reading.

Date of Test : Sep. 15, 2004 Temperature : 24°C

EUT : Fan-Light Remote Controller
(Transmitter) Humidity : 65%

Test Position : EUT on Side

Emission Frequency MHz	Antenna Factor dB/m	Cable Loss dB	Meter Reading Horizontal dBμV	Emission Level Horizontal dBμV/m	Limits dBμV/m	Margin dB
------------------------------	---------------------------	---------------------	-------------------------------------	--	------------------	--------------

Fundamental Freq. (Quasi-Peak Value)

304.300	14.87	3.90	54.07	72.84	74.94	2.10
---------	-------	------	-------	-------	-------	------

Emission Frequency MHz	Antenna Factor dB/m	Cable Loss dB	Meter Reading Vertical dBμV	Emission Level Vertical dBμV/m	Limits dBμV/m	Margin dB
------------------------------	---------------------------	---------------------	-----------------------------------	--------------------------------------	------------------	--------------

Fundamental Freq. (Quasi-Peak Value)

304.300	15.17	3.90	40.26	59.33	74.94	15.61
---------	-------	------	-------	-------	-------	-------

Remarks : Emission Level = Antenna Factor + Cable Loss + Meter Reading.

Date of Test : Sep. 15, 2004 Temperature : 24°C

EUT : Fan-Light Remote Controller
(Transmitter) Humidity : 65%

Test Position : EUT on Lying

Emission Frequency MHz	Antenna Factor dB/m	Cable Loss dB	Meter Reading Horizontal dBμV	Emission Level Horizontal dBμV/m	Limits dBμV/m	Margin dB

Fundamental Freq. (Quasi-Peak Value)						
304.300	14.87	3.90	54.45	73.22	74.94	1.72

Emission Frequency MHz	Antenna Factor dB/m	Cable Loss dB	Meter Reading Vertical dBμV	Emission Level Vertical dBμV/m	Limits dBμV/m	Margin dB

Fundamental Freq. (Quasi-Peak Value)						
304.300	15.17	3.90	38.21	57.28	74.94	17.66

Remarks : Emission Level = Antenna Factor + Cable Loss + Meter Reading.

© Radiated Emission Measurement Results

PASSED. All emissions not reported below are too low against the prescribed limits.

Date of Test : Sep. 10, 2004 Temperature : 25°C

EUT : Fan-Light Remote Controller
(Transmitter) Humidity : 67%

Test Position : EUT on Stand

Emission Frequency MHz	Antenna Factor dB/m	Cable Loss dB	Meter Reading Horizontal dBμV	Emission Level Horizontal dBμV/m	Limits dBμV/m	Margin dB

Spurious / Harmonic Freq. (Below 1000MHz, Quasi-Peak Value)						
58.080	13.43	1.60	5.20	20.23	40.00	19.77
91.830	16.08	2.00	7.16	25.24	43.50	18.26
101.280	17.17	2.10	7.10	26.37	43.50	17.13
160.680	20.82	2.70	3.90	27.42	43.50	16.08
608.400	21.47	6.20	13.98	41.65	46.00	4.35
912.500	24.98	7.40	3.54	35.92	46.00	10.08

Emission Frequency MHz	Antenna Factor dB/m	Cable Loss dB	Meter Reading Vertical dBμV	Emission Level Vertical dBμV/m	Limits dBμV/m	Margin dB

Spurious / Harmonic Freq. (Below 1000MHz, Quasi-Peak Value)						
46.740	17.09	1.40	7.14	25.63	40.00	14.37
62.130	13.37	1.60	9.31	24.28	40.00	15.72
93.990	17.01	2.00	3.40	22.41	43.50	21.09
129.090	18.43	2.40	5.54	26.37	43.50	17.13
131.790	18.94	2.40	5.75	27.09	43.50	16.41
144.480	20.94	2.60	3.57	27.11	43.50	16.39
608.400	21.68	6.20	14.78	42.66	46.00	3.34
912.500	25.69	7.40	4.53	37.62	46.00	8.38

- Remarks :
1. Emission Level = Antenna Factor + Cable Loss + Meter Reading.
 2. Measurement was up to 10th harmonics (~5.5GHz), but the emission levels were too low against the official limit and not report.

Date of Test : Sep. 10, 2004 Temperature : 25°C

EUT : Fan-Light Remote Controller
(Transmitter) Humidity : 67%

Test Position : EUT on Side

Emission Frequency MHz	Antenna Factor dB/m	Cable Loss dB	Meter Reading Horizontal dBμV	Emission Level Horizontal dBμV/m	Limits dBμV/m	Margin dB

Spurious / Harmonic Freq. (Below 1000MHz, Quasi-Peak Value)						
91.830	16.08	2.00	7.15	25.23	43.50	18.27
162.030	20.85	2.70	4.78	28.33	43.50	15.17
174.990	21.13	2.85	3.84	27.82	43.50	15.68
203.340	22.01	3.10	4.69	29.80	43.50	13.70
274.080	25.19	3.70	2.46	31.35	46.00	14.65
608.400	21.47	6.20	14.70	42.37	46.00	3.63
912.500	24.98	7.40	0.91	33.29	46.00	12.71

Emission Frequency MHz	Antenna Factor dB/m	Cable Loss dB	Meter Reading Vertical dBμV	Emission Level Vertical dBμV/m	Limits dBμV/m	Margin dB

Spurious / Harmonic Freq. (Below 1000MHz, Quasi-Peak Value)						
52.140	15.42	1.50	4.70	21.62	40.00	18.38
99.930	17.62	2.10	2.59	22.31	43.50	21.19
131.790	18.94	2.40	5.20	26.54	43.50	16.96
151.500	21.87	2.60	1.83	26.30	43.50	17.20
247.080	24.78	3.50	1.54	29.82	46.00	16.18
608.400	21.68	6.20	15.64	43.52	46.00	2.48
912.500	25.69	7.40	3.21	36.30	46.00	9.70

Remarks : 1. Emission Level = Antenna Factor + Cable Loss + Meter Reading.
2. Measurement was up to 10th harmonics (~5.5GHz), but the emission levels were too low against the official limit and not report.

