

Maximum Permissive Exposure

FCC ID: KUJCE10718

Product Name: Ceiling Fan Remote Controller

Model No: JY1126W

1. According to FCC CFR 47 §1.1310, the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b).

Table 1 Limits for Maximum Permissible Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits For Occupational / Control Exposures (f = frequency)				
30-300	61.4	0.163	1.0	6
300-1500	...	...	f/300	6
1500-100,000	...	...	5.0	6
(B) Limits For General Population / Uncontrolled Exposure (f = frequency)				
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

Chungear Industrial Co., Ltd declares that the product described above has been evaluated and found to comply with the RF exposure limits for humans, as specified based on ANSI/FCC recommendation.

Based on safety distance (r) **20cm**, the antenna gain (G) is **1.521Numerical**, and the highest power output (P) is **299.916mW**, the power density (S) is **0.090753mW/cm²**.

RF Exposure Calculations:

$$S = (P * G) / (4 * \pi * r^2) \text{ or } r = \sqrt{(P * G) / (4 * \pi * S)}$$

Where :

Based on safety distance (r)=	20 cm
Highest Power Output (P)=	24.77 dBm = 299.916 mW
Antenna Gain (G)=	1.82 dBi = 1.521 Numerical
MPE (S) = (P*G) / (4*π*r ²) =	= (299.916*1.521)/(4*π*20²)= 0.090753 mW/cm²

Sincerely Yours,



Mr. Ben Cheng

Manager

AUDIX Technology Corporation