



Test report No:
NIE: 60825RRF.002A1

Test report

USA FCC Part 15.249, 15.209

CANADA RSS-210, RSS-Gen

Radio Frequency Devices. Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz, and 5725 - 5850 MHz.

(*) Identification of item tested	Hearing Aid
(*) Trademark	Phonak
(*) Model and /or type reference tested	Phonak Virto M90-312 Right
Other identification of the product	HW version: 063-0498-01 FW version: 068-1310-000000 FCC ID: KWC-INR IC: 2262A-INR
(*) Features	Bluetooth, Bluetooth LE, Flora, DM
Applicant	SONOVA USA INC. 4520 Weaver Parkway 60555 Warrenville, IL, USA
Test method requested, standard	USA FCC Part 15.249 10-1-17 Edition: Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz, 5725 - 5875 MHz, and 24.0 – 24.25 GHz. USA FCC Part 15.209 10-1-17 Edition: Radiated emission limits; general requirements. CANADA RSS-210 Issue 9 (August 2016). CANADA RSS-Gen Issue 5 (April 2018). ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.
Summary	IN COMPLIANCE
Approved by (name / position & signature)	Rafael López Martín EMC Consumer & RF Lab. Manager 
Date of issue	2020-02-05
Report template No	FDT08_22 (*) "Data provided by the client"

RAFAEL LÓPEZ
MARTÍN
2020.02.05
10:52:46
+01'00'

Competences and guarantees	3
General Conditions	3
Uncertainty	3
Data provided by the client.....	3
Usage of samples	4
Test sample description	4
Identification of the client.....	5
Testing period and place.....	5
Document history	5
Environmental conditions	6
Remarks and comments	7
Testing verdicts.....	8
Summary	8
Appendix A: Test results. Bluetooth Low Energy.....	10
Appendix B: Test results. Bluetooth Basic Rate	31
Appendix C: Test results. Proprietary protocol DM.....	52
Appendix D: Test results. Proprietary protocol Flora	73

Competences and guarantees

DEKRA Testing and Certification S.A.U. is a testing laboratory accredited by the National Accreditation Body (ENAC -Entidad Nacional de Acreditación), to perform the tests indicated in the Certificate No. 51/LE 147.

DEKRA Testing and Certification is a FCC-recognized accredited testing laboratory with appropriate scope of accreditation that include testing performed in this test report.

DEKRA Testing and Certification S.A.U. is a laboratory with a measurement site in compliance with the requirements of RSS 212, Issue 1 (Provisional) and has been added to the list of filed sites of the Canadian Certification and Engineering Bureau. Reference File Number: ISED 4621A-4.

In order to assure the traceability to other national and international laboratories, DEKRA Testing and Certification S.A.U. has a calibration and maintenance program for its measurement equipment.

DEKRA Testing and Certification S.A.U. guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Testing and Certification S.A.U. at the time of performance of the test.

DEKRA Testing and Certification S.A.U. is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Testing and Certification S.A.U.

General Conditions

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Testing and Certification S.A.U.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Testing and Certification S.A.U. and the Accreditation Bodies.

Uncertainty

Uncertainty (factor $k=2$) was calculated according to the DEKRA Testing and Certification S.A.U. internal document PODT000.

Data provided by the client

The following data has been provided by the client:

1. Information relating to the description of the sample ("Identification of the item tested", "Trademark", "Model and/or type reference tested").
2. The sample consists of a Hearing aid.

DEKRA Testing and Certification S.A.U. declines any responsibility with respect to the information provided by the client and that may affect the validity of results.

Usage of samples

Samples undergoing test have been selected by: The client.

- Sample S/01 is composed of the following elements:

Control N°	Description	Model	Serial N°	Reception
60825/025	Hearing aid	Phonak Virto M90-312 Right	---	2019-07-23

Sample S/01 has undergone the following test(s): All CONDUCTED tests indicated in Appendixes A, B, C and D.

- Sample S/02 is composed of the following elements:

Control N°	Description	Model	Serial N°	Reception
60825/014	Hearing aid	Phonak Virto M90-312 Right	---	2019-07-23

Sample S/02 has undergone the following test(s): All RADIATED tests indicated in Appendixes A, B, C and D.

Test sample description

Ports..... :	Port name and description		Cable			
			Specified max length [m]	Attached during test	Shielded	Coupled to patient ⁽³⁾
	N/A			☐	☐	☐
				☐	☐	☐
Supplementary information to the ports..... :						
Rated power supply	Voltage and Frequency		Reference poles			
			L1	L2	L3	N
	☐	AC:	☐	☐	☐	☐
	☒	DC: 1.4V Zinc Air Battery				
Rated Power	--					
Clock frequencies	--					
Other parameters..... :	--					
Software version	068-1310-000000					
Hardware version..... :	063-0498-01					

Dimensions in cm (W x H x D).....:			
Mounting position.....:	☐	Table top equipment	
	☐	Wall/Ceiling mounted equipment	
	☐	Floor standing equipment	
	☐	Hand-held equipment	
	☒	Other: Hearing Aid	
Modules/parts	Module/parts of test item	Type	Manufacturer
	--		
Accessories (not part of the test item)	Description	Type	Manufacturer
	--		
Documents as provided by the applicant.....:	Description	File name	Issue date
	--		

⁽³⁾ Only for Medical Equipment

Identification of the client

SONOVA AG
Laubisruetistrasse 28
8712 Staefa, Switzerland

Testing period and place

Test Location	DEKRA Testing and Certification S.A.U.
Date (start)	2019-08-07
Date (finish)	2019-09-05

Document history

Report number	Date	Description
60825RRF.002	2019-10-11	First release
60825RRF.002A1	2020-02-05	First modification: correction of FCC ID on front page. This modification test report cancels and replaces the test report 60825RRF.002

Environmental conditions

In the control chamber, the following limits were not exceeded during the test:

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 75 %

In the semianechoic chamber, the following limits were not exceeded during the test.

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 75 %
Air pressure	Min. = 860 mbar Max. = 1060 mbar

In the chamber for conducted measurements, the following limits were not exceeded during the test:

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 35 %
Air pressure	Min. = 860 mbar Max. = 1060 mbar

Remarks and comments

The tests have been performed by the technical personnel: Miguel Ángel Torres and Jose Gabriel Pendon.

Used instrumentation:

Conducted Measurements:

	Last Calibration	Due Calibration
1. Signal and Spectrum Analyzer 10Hz – 40GHz ROHDE AND SCHWARZ FSV40	2018/02	2020/02

Radiated Measurements:

	Last Calibration	Due Calibration
1. Semianechoic Absorber Lined Chamber ETS FACT3 200STP	N.A.	N.A.
2. EMI Test Receiver ROHDE AND SCHWARZ ESR7	2018/10	2020/10
3. BiconicalLog antenna ETS LINDGREN 3142E	2017/09	2020/09
4. RF Pre-amplifier 40 dB, 10 MHz-6 GHz BONN ELEKTRONIK BLNA 0160-01N	2019/02	2020/08
5. Signal and Spectrum Analyzer ROHDE AND SCHWARZ FSV40	2018/02	2020/02
6. RF Pre-amplifier, 30 dB ,1-18 GHz BONN ELEKTRONIK BLMA 0118-3A	2019/04	2020/04
7. Broadband Horn antenna 1-18 GHz SCHWARZBECK BBHA 9120 D	2018/01	2021/01
8. RF Pre-amplifier 30 dB, 18 GHz-40 GHz BONN ELEKTRONIK BLMA 1840-1M	2019/02	2021/02
8. RF pre-amplifier 18-40 GHz NARDA JS44-18004000-33-8P	02/2019	02/2020
9. Broadband Horn antenna 18-40 GHz SCHWARZBECK BBHA 9170	2018/07	2021/07

Testing verdicts

Not applicable:	N/A
Pass:	P
Fail:	F
Not measured:	N/M

Summary

1. Bluetooth Low Energy

FCC PART 15 PARAGRAPH / RSS-210			
Requirement – Test case		Verdict	Remark
Section 15.249 Subclause (a) / RSS-210 B.10. (a)	Field strength of fundamental and harmonic emissions	P	
Section 15.249 Subclause (d) / RSS-210 B.10. (b)	Emissions radiated outside of the specific frequency bands	P	
<u>Supplementary information and remarks:</u> None.			

2. Bluetooth Basic Rate

FCC PART 15 PARAGRAPH / RSS-210			
Requirement – Test case		Verdict	Remark
Section 15.249 Subclause (a) / RSS-210 B.10. (a)	Field strength of fundamental and harmonic emissions	P	
Section 15.249 Subclause (d) / RSS-210 B.10. (b)	Emissions radiated outside of the specific frequency bands	P	
<u>Supplementary information and remarks:</u> None.			

3. Proprietary protocol DM 2.4 GHz

FCC PART 15 PARAGRAPH / RSS-210			
Requirement – Test case		Verdict	Remark
Section 15.249 Subclause (a) / RSS-210 B.10. (a)	Field strength of fundamental and harmonic emissions	P	
Section 15.249 Subclause (d) / RSS-210 B.10. (b)	Emissions radiated outside of the specific frequency bands	P	
<u>Supplementary information and remarks:</u> None.			

4. Proprietary protocol Flora 2.4 GHz

FCC PART 15 PARAGRAPH / RSS-210			
Requirement – Test case		Verdict	Remark
Section 15.249 Subclause (a) / RSS-210 B.10. (a)	Field strength of fundamental and harmonic emissions	P	
Section 15.249 Subclause (d) / RSS-210 B.10. (b)	Emissions radiated outside of the specific frequency bands	P	
<u>Supplementary information and remarks:</u> None.			

Appendix A: Test results. Bluetooth Low Energy

TEST CONDITIONS	12
Occupied Bandwidth	14
Section 15.249 Subclause (a) / RSS-210 B.10. (a) Field strength of fundamental and harmonics emissions	16
Section 15.249 Subclause (d) / RSS-210 B.10. (b) Emissions radiated outside of the specific frequency bands	19

TEST CONDITIONS

POWER SUPPLY (V):

V nominal: 1.4 Vdc
Type of power supply: DC voltage from battery.
Type of antenna: Internal antenna.
Declared antenna gain: - 7 dBi

TEST FREQUENCIES:

Low Channel: 2402 MHz
Middle Channel: 2440 MHz
High Channel: 2480 MHz

CONDUCTED MEASUREMENTS

The equipment under test was set up in a shielded room and it is connected to the spectrum analyser using a low loss RF cable. The reading of the spectrum analyser is corrected taking into account the cable loss.



RADIATED MEASUREMENTS


All radiated tests were performed in a semi-anechoic chamber. The measurement antenna is situated at a distance of 3 m for the frequency range 30 MHz-1000 MHz (30 MHz-1000 MHz Bilog antenna) and at a distance of 1m for the frequency range 1 GHz-26 GHz (1 GHz-18 GHz Double ridge horn antenna and 18 GHz-40 GHz horn antenna).

For radiated emissions in the range 1 GHz-26 GHz that is performed at a distance closer than the specified distance, an inverse proportionality factor of 20 dB per decade is used to normalize the measured data for determining compliance.


The equipment under test was set up on a non-conductive platform above the ground plane and the situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

Radiated measurements setup $f < 1$ GHz:



Radiated measurements setup $f > 1$ GHz:




Occupied Bandwidth


RESULTS:

	Low Channel 2402 MHz	Middle Channel 2440 MHz	High Channel 2480 MHz
99% Bandwidth (MHz)	1.030	1.050	1.065
Measurement Uncertainty (kHz)	<±5.00		

- Low Channel:



- Middle Channel:



- High Channel:



Section 15.249 Subclause (a) / RSS-210 B.10. (a) Field strength of fundamental and harmonics emissions

SPECIFICATION:

The field strength of emissions from intentional radiators shall comply with the following

Fundamental frequency (MHz)	Field strength of fundamental (mV/m)	Field strength (dBμV/m)	Measurement distance (m)
902 - 928	50	93.98	3
2400 – 2483.5	50	93.98	3
5725 - 5875	50	93.98	3
24000-24250	250	107.96	3


For frequencies above 1000 MHz, the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

RESULTS:


	Low Channel 2402 MHz	Middle Channel 2440 MHz	High Channel 2480 MHz
Average Field Strength (dBμV/m)	84.93	84.36	81.01
Peak Field Strength (dBμV/m)	88.01	87.47	84.14
Measurement Uncertainty (dB)	<±3.05		

Verdict: PASS


- Low Channel:



- Middle Channel:



- High Channel:



Section 15.249 Subclause (d) / RSS-210 B.10. (b) Emissions radiated outside of the specific frequency bands

SPECIFICATION:

The field strength of harmonics from intentional radiators shall comply with the following

Fundamental frequency (MHz)	Field strength of harmonics ($\mu\text{V/m}$)	Field strength of harmonics ($\text{dB}\mu\text{V/m}$)	Measurement distance (m)
902 - 928	500	54	3
2400 – 2483.5	500	54	3
5725 - 5875	500	54	3
24000-24250	2500	67.96	3

Emissions radiated outside of the specific frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of fundamental or to the general radiated emission limits specified in section 15.209:

Frequency Range (MHz)	Field strength ($\mu\text{V/m}$)	Field strength ($\text{dB}\mu\text{V/m}$)	Measurement distance (m)
0.009-0.490	$2400/F(\text{kHz})$	-	300
0.490-1.705	$24000/F(\text{kHz})$	-	30
1.705 - 30.0	30	-	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
960 - 25000	500	54	3

Whichever is the lesser attenuation.

RESULTS:

The situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

All tests were performed in a semi-anechoic chamber at a distance of 3 m for the frequency range 30 MHz-1000 MHz and at distance of 1m for the frequency range 1 GHz-26 GHz.

The field strength is calculated by adding correction factor to the measured level from the spectrum analyzer. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

Frequency range 30 MHz - 1 GHz.

The spurious signals detected do not depend on the operating channel.

No spurious emissions were found at less than 20 dB of the limit.

Frequency range 1 - 26 GHz.

The results in the next tables show the maximum measured levels in the 1-26 GHz range including the restricted bands 2.31-2.39 GHz and 2.4835-2.5 GHz (see next plots).

Spurious signals with peak levels above the average limit (54 dB μ V/m at 3 m) are measured with average detector for checking compliance with the average limit.

- Low Channel (2402 MHz):

Spurious frequency (GHz)	Detector	Emission Level (dB μ V/m)	Polarization	Measurement Uncertainty (dB)
2.38964	Peak	55.14	H	< $\pm$ 3.70
	Average	40.23		< $\pm$ 3.70
4.80437	Peak	42.56	V	< $\pm$ 3.70
7.20537	Peak	43.36	H	< $\pm$ 3.70

- Middle Channel (2440 MHz):

Spurious frequency (GHz)	Detector	Emission Level (dB μ V/m)	Polarization	Measurement Uncertainty (dB)
4.87950	Peak	47.76	V	< $\pm$ 3.70


- High Channel (2480 MHz):

Spurious frequency (GHz)	Detector	Emission Level (dB μ V/m)	Polarization	Measurement Uncertainty (dB)
2.48352	Peak	61.85	H	< $\pm$ 3.70
	Average	41.01		< $\pm$ 3.70
4.95977	Peak	47.88	V	< $\pm$ 3.70

Verdict: PASS


FREQUENCY RANGE 30 MHz - 1 GHz

The spurious signals detected do not depend on the operating channel, so this plot is valid for Low, Middle and High Channels.




FREQUENCY RANGE 1 - 3 GHz

- Low Channel:




The peak shown in the plot above the limit is the carrier frequency.

- Middle Channel:



The peak shown in the plot above the limit is the carrier frequency.


- High Channel:




The peak shown in the plot above the limit is the carrier frequency.

FREQUENCY RANGE 3 - 17 GHz


- Low Channel:



- Middle Channel:




- High Channel:




FREQUENCY RANGE 17 - 26 GHz

The spurious signals detected do not depend on the operating channel, so this plot is valid for Low, Middle and High Channels.




FREQUENCY RANGE 2.31 - 2.39 GHz


- Low Channel:



- Middle Channel:




- High Channel:




FREQUENCY RANGE 2.4835 - 2.5 GHz.


- Low Channel:



- Middle Channel:



- High Channel:



Appendix B: Test results. Bluetooth Basic Rate

TEST CONDITIONS	33
Occupied Bandwidth	35
Section 15.249 Subclause (a) / RSS-210 B.10. (a) Field strength of fundamental and harmonics emissions	37
Section 15.249 Subclause (d) / RSS-210 B.10. (b) Emissions radiated outside of the specific frequency bands	40

TEST CONDITIONS

POWER SUPPLY (V):

V nominal: 1.4 Vdc
Type of power supply: DC voltage from battery.
Type of antenna: Internal antenna.
Declared antenna gain: - 7 dBi

TEST FREQUENCIES:

Low Channel: 2402 MHz
Middle Channel: 2441 MHz
High Channel: 2480 MHz

CONDUCTED MEASUREMENTS

The equipment under test was set up in a shielded room and it is connected to the spectrum analyser using a low loss RF cable. The reading of the spectrum analyser is corrected taking into account the cable loss.



RADIATED MEASUREMENTS


All radiated tests were performed in a semi-anechoic chamber. The measurement antenna is situated at a distance of 3 m for the frequency range 30 MHz-1000 MHz (30 MHz-1000 MHz Bilog antenna) and at a distance of 1m for the frequency range 1 GHz-26 GHz (1 GHz-18 GHz Double ridge horn antenna and 18 GHz-40 GHz horn antenna).

For radiated emissions in the range 1 GHz-26 GHz that is performed at a distance closer than the specified distance, an inverse proportionality factor of 20 dB per decade is used to normalize the measured data for determining compliance.


The equipment under test was set up on a non-conductive platform above the ground plane and the situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

Radiated measurements setup $f < 1$ GHz:



Radiated measurements setup $f > 1$ GHz:




Occupied Bandwidth


RESULTS:

	Low Channel 2402 MHz	Middle Channel 2441 MHz	High Channel 2480 MHz
99% Bandwidth (MHz)	0.978	0.978	0.981
Measurement Uncertainty (kHz)	<±5.00		


- Low Channel:



- Middle Channel:



- High Channel:



Section 15.249 Subclause (a) / RSS-210 B.10. (a) Field strength of fundamental and harmonics emissions

SPECIFICATION:

The field strength of emissions from intentional radiators shall comply with the following

Fundamental frequency (MHz)	Field strength of fundamental (mV/m)	Field strength (dBµV/m)	Measurement distance (m)
902 - 928	50	93.98	3
2400 – 2483.5	50	93.98	3
5725 - 5875	50	93.98	3
24000-24250	250	107.96	3


For frequencies above 1000 MHz, the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

RESULTS:


	Low Channel 2402 MHz	Middle Channel 2441 MHz	High Channel 2480 MHz
Average Field Strength (dBµV/m)	87.77	85.98	83.57
Peak Field Strength (dBµV/m)	87.95	86.2	83.86
Measurement Uncertainty (dB)	<±3.05		

Verdict: PASS


- Low Channel:



- Middle Channel:



- High Channel:



Section 15.249 Subclause (d) / RSS-210 B.10. (b) Emissions radiated outside of the specific frequency bands

SPECIFICATION:

The field strength of harmonics from intentional radiators shall comply with the following

Fundamental frequency (MHz)	Field strength of harmonics ($\mu\text{V/m}$)	Field strength of harmonics ($\text{dB}\mu\text{V/m}$)	Measurement distance (m)
902 - 928	500	54	3
2400 – 2483.5	500	54	3
5725 - 5875	500	54	3
24000-24250	2500	67.96	3

Emissions radiated outside of the specific frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of fundamental or to the general radiated emission limits specified in section 15.209:

Frequency Range (MHz)	Field strength ($\mu\text{V/m}$)	Field strength ($\text{dB}\mu\text{V/m}$)	Measurement distance (m)
0.009-0.490	$2400/F(\text{kHz})$	-	300
0.490-1.705	$24000/F(\text{kHz})$	-	30
1.705 - 30.0	30	-	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
960 - 25000	500	54	3

Whichever is the lesser attenuation.

RESULTS:

The situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

All tests were performed in a semi-anechoic chamber at a distance of 3 m for the frequency range 30 MHz-1000 MHz and at distance of 1m for the frequency range 1 GHz-26 GHz.

The field strength is calculated by adding correction factor to the measured level from the spectrum analyzer. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

Frequency range 30 MHz - 1 GHz.

The spurious signals detected do not depend on the operating channel.

No spurious emissions were found at less than 20 dB of the limit.

Frequency range 1 - 26 GHz.

The results in the next tables show the maximum measured levels in the 1-26 GHz range including the restricted bands 2.31-2.39 GHz and 2.4835-2.5 GHz (see next plots).

Spurious signals with peak levels above the average limit (54 dB μ V/m at 3 m) are measured with average detector for checking compliance with the average limit.

- Low Channel (2402 MHz):

Spurious frequency (GHz)	Detector	Emission Level (dB μ V/m)	Polarization	Measurement Uncertainty (dB)
4.8039	Peak	45.56	H	< $\pm$ 3.70
7.20583	Peak	43.17	V	< $\pm$ 3.70

- Middle Channel (2441 MHz):

Spurious frequency (GHz)	Detector	Emission Level (dB μ V/m)	Polarization	Measurement Uncertainty (dB)
4.88183	Peak	47.80	H	< $\pm$ 3.70
7.32297	Peak	44.18	H	< $\pm$ 3.70


- High Channel (2480 MHz):

Spurious frequency (GHz)	Detector	Emission Level (dB μ V/m)	Polarization	Measurement Uncertainty (dB)
4.96023	Peak	46.53	H	< $\pm$ 3.70
7.4401	Peak	42.66	V	< $\pm$ 3.70

Verdict: PASS


FREQUENCY RANGE 30 MHz - 1 GHz

The spurious signals detected do not depend on the operating channel, so this plot is valid for Low, Middle and High Channels.




FREQUENCY RANGE 1 - 3 GHz

- Low Channel:




The peak shown in the plot above the limit is the carrier frequency.

- Middle Channel:



The peak shown in the plot above the limit is the carrier frequency.


- High Channel:




The peak shown in the plot above the limit is the carrier frequency.

FREQUENCY RANGE 3 - 17 GHz


- Low Channel:



- Middle Channel:




- High Channel:




FREQUENCY RANGE 17 - 26 GHz

The spurious signals detected do not depend on the operating channel, so this plot is valid for Low, Middle and High Channels.




FREQUENCY RANGE 2.31 - 2.39 GHz


- Low Channel:



- Middle Channel:




- High Channel:




FREQUENCY RANGE 2.4835 - 2.5 GHz


- Low Channel:



- Middle Channel:



- High Channel:



Appendix C: Test results. Proprietary protocol DM

TEST CONDITIONS	54
Occupied Bandwidth	56
Section 15.249 Subclause (a) / RSS-210 B.10. (a) Field strength of fundamental and harmonics emissions	58
Section 15.249 Subclause (d) / RSS-210 B.10. (b) Emissions radiated outside of the specific frequency bands	61

TEST CONDITIONS

POWER SUPPLY (V):

V nominal: 1.4 Vdc
Type of power supply: DC voltage from battery.
Type of antenna: Internal antenna.
Declared antenna gain: - 7 dBi

TEST FREQUENCIES:

Low Channel: 2402 MHz
Middle Channel: 2440 MHz
High Channel: 2480 MHz

CONDUCTED MEASUREMENTS

The equipment under test was set up in a shielded room and it is connected to the spectrum analyser using a low loss RF cable. The reading of the spectrum analyser is corrected taking into account the cable loss.



RADIATED MEASUREMENTS


All radiated tests were performed in a semi-anechoic chamber. The measurement antenna is situated at a distance of 3 m for the frequency range 30 MHz-1000 MHz (30 MHz-1000 MHz Bilog antenna) and at a distance of 1m for the frequency range 1 GHz-26 GHz (1 GHz-18 GHz Double ridge horn antenna and 18 GHz-40 GHz horn antenna).

For radiated emissions in the range 1 GHz-26 GHz that is performed at a distance closer than the specified distance, an inverse proportionality factor of 20 dB per decade is used to normalize the measured data for determining compliance.


The equipment under test was set up on a non-conductive platform above the ground plane and the situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

Radiated measurements setup $f < 1$ GHz:



Radiated measurements setup $f > 1$ GHz:



Occupied Bandwidth

RESULTS:

	Low Channel 2402 MHz	Middle Channel 2440 MHz	High Channel 2480 MHz
99% Bandwidth (MHz)	1.900	1.905	1.905
Measurement Uncertainty (kHz)	<±5.00		


- Low Channel:



- Middle Channel:



- High Channel:



Section 15.249 Subclause (a) / RSS-210 B.10. (a) Field strength of fundamental and harmonics emissions

SPECIFICATION:

The field strength of emissions from intentional radiators shall comply with the following

Fundamental frequency (MHz)	Field strength of fundamental (mV/m)	Field strength (dBμV/m)	Measurement distance (m)
902 - 928	50	93.98	3
2400 – 2483.5	50	93.98	3
5725 - 5875	50	93.98	3
24000-24250	250	107.96	3


For frequencies above 1000 MHz, the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

RESULTS:


	Low Channel 2402 MHz	Middle Channel 2440 MHz	High Channel 2480 MHz
Average Field Strength (dBμV/m)	84.53	85.99	83.62
Peak Field Strength (dBμV/m)	84.87	86.30	84.00
Measurement Uncertainty (dB)	<±3.05		

Verdict: PASS


- Low Channel:



- Middle Channel:



- High Channel:



Section 15.249 Subclause (d) / RSS-210 B.10. (b) Emissions radiated outside of the specific frequency bands

SPECIFICATION:

The field strength of harmonics from intentional radiators shall comply with the following

Fundamental frequency (MHz)	Field strength of harmonics ($\mu\text{V/m}$)	Field strength of harmonics ($\text{dB}\mu\text{V/m}$)	Measurement distance (m)
902 - 928	500	54	3
2400 – 2483.5	500	54	3
5725 - 5875	500	54	3
24000-24250	2500	67.96	3

Emissions radiated outside of the specific frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of fundamental or to the general radiated emission limits specified in section 15.209:

Frequency Range (MHz)	Field strength ($\mu\text{V/m}$)	Field strength ($\text{dB}\mu\text{V/m}$)	Measurement distance (m)
0.009-0.490	$2400/F(\text{kHz})$	-	300
0.490-1.705	$24000/F(\text{kHz})$	-	30
1.705 - 30.0	30	-	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
960 - 25000	500	54	3

Whichever is the lesser attenuation.

RESULTS:

The situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

All tests were performed in a semi-anechoic chamber at a distance of 3 m for the frequency range 30 MHz-1000 MHz and at distance of 1m for the frequency range 1 GHz-26 GHz.

The field strength is calculated by adding correction factor to the measured level from the spectrum analyzer. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

Frequency range 30 MHz - 1 GHz.

The spurious signals detected do not depend on the operating channel.

No spurious emissions were found at less than 20 dB from the limit.

Frequency range 1 - 26 GHz.

The results in the next tables show the maximum measured levels in the 1-26 GHz range including the restricted bands 2.31-2.39 GHz and 2.4835-2.5 GHz (see next plots).

Spurious signals with peak levels above the average limit (54 dB μ V/m at 3 m) are measured with average detector for checking compliance with the average limit.

- Low Channel (2402 MHz):

Spurious frequency (GHz)	Detector	Emission Level (dB μ V/m)	Polarization	Measurement Uncertainty (dB)
4.80343	Peak	49.46	V	< $\pm$ 3.70

- Middle Channel (2440 MHz):

Spurious frequency (GHz)	Detector	Emission Level (dB μ V/m)	Polarization	Measurement Uncertainty (dB)
4.88043	Peak	47.33	H	< $\pm$ 3.70


- High Channel (2480 MHz):

Spurious frequency (GHz)	Detector	Emission Level (dB μ V/m)	Polarization	Measurement Uncertainty (dB)
2.84402	Peak	52.01	V	< $\pm$ 3.70
4.95930	Peak	46.34	V	< $\pm$ 3.70

Verdict: PASS


FREQUENCY RANGE 30 MHz - 1 GHz

The spurious signals detected do not depend on the operating channel, so this plot is valid for Low, Middle and High Channels.




FREQUENCY RANGE 1 - 3 GHz

- Low Channel:




The peak shown in the plot above the limit is the carrier frequency.

- Middle Channel:



The peak shown in the plot above the limit is the carrier frequency.


- High Channel:




The peak shown in the plot above the limit is the carrier frequency.

FREQUENCY RANGE 3 - 17 GHz


- Low Channel:



- Middle Channel:




- High Channel:




FREQUENCY RANGE 17 - 26 GHz

The spurious signals detected do not depend on the operating channel, so this plot is valid for Low, Middle and High Channels.




FREQUENCY RANGE 2.31 - 2.39 GHz (Restricted Band 1)


- Low Channel:



- Middle Channel:




- High Channel:




FREQUENCY RANGE 2.4835 - 2.5 GHz (Restricted Band 2)


- Low Channel:



- Middle Channel:



- High Channel:



Appendix D: Test results. Proprietary protocol Flora

TEST CONDITIONS	75
Occupied Bandwidth	77
Section 15.249 Subclause (a) / RSS-210 B.10. (a) Field strength of fundamental and harmonics emissions	79
Section 15.249 Subclause (d) / RSS-210 B.10. (b) Emissions radiated outside of the specific frequency bands	82

TEST CONDITIONS

POWER SUPPLY (V):

V nominal: 1.4 Vdc
Type of power supply: DC voltage from battery.
Type of antenna: Internal antenna.
Declared antenna gain: - 7 dBi

TEST FREQUENCIES:

Low Channel: 2402 MHz
Middle Channel: 2440 MHz
High Channel: 2480 MHz

CONDUCTED MEASUREMENTS

The equipment under test was set up in a shielded room and it is connected to the spectrum analyser using a low loss RF cable. The reading of the spectrum analyser is corrected taking into account the cable loss.



RADIATED MEASUREMENTS


All radiated tests were performed in a semi-anechoic chamber. The measurement antenna is situated at a distance of 3 m for the frequency range 30 MHz-1000 MHz (30 MHz-1000 MHz Bilog antenna) and at a distance of 1m for the frequency range 1 GHz-26 GHz (1 GHz-18 GHz Double ridge horn antenna and 18 GHz-40 GHz horn antenna).

For radiated emissions in the range 1 GHz-26 GHz that is performed at a distance closer than the specified distance, an inverse proportionality factor of 20 dB per decade is used to normalize the measured data for determining compliance.


The equipment under test was set up on a non-conductive platform above the ground plane and the situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

Radiated measurements setup $f < 1$ GHz:



Radiated measurements setup $f > 1$ GHz:




Occupied Bandwidth


RESULTS:

	Low Channel 2402 MHz	Middle Channel 2440 MHz	High Channel 2480 MHz
99% Bandwidth (MHz)	2.860	2.860	2.860
Measurement Uncertainty (kHz)	<±5.00		


- Low Channel:



- Middle Channel:



- High Channel:



Section 15.249 Subclause (a) / RSS-210 B.10. (a) Field strength of fundamental and harmonics emissions

SPECIFICATION:

The field strength of emissions from intentional radiators shall comply with the following

Fundamental frequency (MHz)	Field strength of fundamental (mV/m)	Field strength (dB μ V/m)	Measurement distance (m)
902 - 928	50	93.98	3
2400 – 2483.5	50	93.98	3
5725 - 5875	50	93.98	3
24000-24250	250	107.96	3


For frequencies above 1000 MHz, the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

RESULTS:


	Low Channel 2402 MHz	Middle Channel 2440 MHz	High Channel 2480 MHz
Average Field Strength (dB μ V/m)	87.12	86.41	81.89
Peak Field Strength (dB μ V/m)	87.71	87.05	82.64
Measurement Uncertainty (dB)	< $\pm$ 3.05		

Verdict: PASS


- Low Channel:



- Middle Channel:



- High Channel:



Section 15.249 Subclause (d) / RSS-210 B.10. (b) Emissions radiated outside of the specific frequency bands

SPECIFICATION:

The field strength of harmonics from intentional radiators shall comply with the following

Fundamental frequency (MHz)	Field strength of harmonics ($\mu\text{V/m}$)	Field strength of harmonics ($\text{dB}\mu\text{V/m}$)	Measurement distance (m)
902 - 928	500	54	3
2400 – 2483.5	500	54	3
5725 - 5875	500	54	3
24000-24250	2500	67.96	3

Emissions radiated outside of the specific frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of fundamental or to the general radiated emission limits specified in section 15.209:

Frequency Range (MHz)	Field strength ($\mu\text{V/m}$)	Field strength ($\text{dB}\mu\text{V/m}$)	Measurement distance (m)
0.009-0.490	2400/F(kHz)	-	300
0.490-1.705	24000/F(kHz)	-	30
1.705 - 30.0	30	-	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
960 - 25000	500	54	3

Whichever is the lesser attenuation.

RESULTS:

The situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

All tests were performed in a semi-anechoic chamber at a distance of 3 m for the frequency range 30 MHz-1000 MHz and at distance of 1m for the frequency range 1 GHz-26 GHz.

The field strength is calculated by adding correction factor to the measured level from the spectrum analyzer. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

Frequency range 30 MHz - 1 GHz.

The spurious signals detected do not depend on the operating channel.

No spurious emissions were found at less than 20 dB of the limit.

Frequency range 1 - 26 GHz.

The results in the next tables show the maximum measured levels in the 1-26 GHz range including the restricted bands 2.31-2.39 GHz and 2.4835-2.5 GHz (see next plots).

Spurious signals with peak levels above the average limit (54 dB μ V/m at 3 m) are measured with average detector for checking compliance with the average limit.

- Low Channel (2402 MHz):

Spurious frequency (GHz)	Detector	Emission Level (dB μ V/m)	Polarization	Measurement Uncertainty (dB)
4.80530	Peak	45.48	V	< $\pm$ 3.70

- Middle Channel (2440 MHz):

Spurious frequency (GHz)	Detector	Emission Level (dB μ V/m)	Polarization	Measurement Uncertainty (dB)
4.87903	Peak	46.66	V	< $\pm$ 3.70


- High Channel (2480 MHz):

Spurious frequency (GHz)	Detector	Emission Level (dB μ V/m)	Polarization	Measurement Uncertainty (dB)
2.48358	Peak	54.68	V	< $\pm$ 3.70
	Average	45.27		< $\pm$ 3.70
4.96154	Peak	48.03	V	< $\pm$ 3.70

Verdict: PASS


FREQUENCY RANGE 30 MHz - 1 GHz

The spurious signals detected do not depend on the operating channel, so this plot is valid for Low, Middle and High Channels.




FREQUENCY RANGE 1 - 3 GHz

- Low Channel:




The peak shown in the plot above the limit is the carrier frequency.

- Middle Channel:



The peak shown in the plot above the limit is the carrier frequency.


- High Channel:




The peak shown in the plot above the limit is the carrier frequency.

FREQUENCY RANGE 3 - 17 GHz


- Low Channel:



- Middle Channel:




- High Channel:




FREQUENCY RANGE 17 - 26 GHz

The spurious signals detected do not depend on the operating channel, so this plot is valid for Low, Middle and High Channels.




FREQUENCY RANGE 2.31 - 2.39 GHz (Restricted Band 1)


- Low Channel:



- Middle Channel:




- High Channel:




FREQUENCY RANGE 2.4835 - 2.5 GHz (Restricted Band 2)

- Low Channel:



- Middle Channel:



- High Channel:

