


Test report No:
NIE: 76950RAN.002

Assessment report

RF EXPOSURE REPORT ACCORDING TO

FCC 47 CFR Part 2.1093
FCC 47 CFR Part 1.1307

(*) Identification of item under evaluation	Receiver-In-The-Canal Hearing Aid (air-conduction, wireless)	
(*) Trademark	Phonak	
(*) Model and /or type reference	Phonak Audéo I90-R Phonak Audéo I70-R Phonak Audéo I50-R Phonak Audéo I30-R Phonak Audéo I-R Trial ampli-energy R 5 5P R PH ampli-energy R 4 5P R PH ampli-energy R 3 5P R PH ampli-energy R 2 5P R PH ampli-energy R Trial 5P Phonak CROS I-R Phonak CROS I-R Trial See section "Data provided by the client".	
(*) Other identification of the product	FCC ID : KWC-IRF HW version : 50-1050-P6 SW Version : 067-1604	
(*) Features	DM (Proprietary), Flora (Proprietary), Bluetooth Classic, Bluetooth EDR (2Mbps & 3Mbps), Bluetooth Low Energy	
(*) Manufacturer	Sonova AG Laubisrütistrasse 28 8712 Stäfa, Switzerland	
Test method requested, standard	FCC 47 CFR Part 2.1093. Radiofrequency radiation exposure evaluation: portable devices. FCC 47 CFR Part 1.1307: Actions that may have a significant environmental effect, for which Environmental Assessments (EAs) must be prepared.	
Summary	IN COMPLIANCE	
Approved by (name / position & signature)	Miguel Lacave Antennas Lab Manager	 2024.06.12 15:55:15 +02'00'
Date of issue	2024-06-12	
Report template No	FAN24_02 (*) "Data provided by the client"	

Index

Competences and guarantees 3

General conditions 3

Data provided by the client.....3

Identification of the client.....7

Document history 7

Appendix A: FCC RF Exposure assessment result 8

 General description of the device under evaluation 9

 Evaluation Results.....11

Appendix B: FCC RF Exposure information 12

 RF Exposure determination of exemption.....13

Competences and guarantees

In order to assure the traceability to other national and international laboratories, DEKRA Testing and Certification, S.A.U. has a calibration and maintenance program for its measurement equipment.

DEKRA Testing and Certification, S.A.U. guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Testing and Certification, S.A.U. at the time of performance of the test.

DEKRA Testing and Certification, S.A.U. is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Assessment Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Testing and Certification, S.A.U.

General conditions

1. This report is only referred to the item that has undergone the assessment.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Testing and Certification, S.A.U.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Testing and Certification, S.A.U. and the Accreditation Bodies

Data provided by the client

The following data has been provided by the client:

1. Information relating to the description of the sample ("Identification of the item under evaluation", "Trademark", "Model and/or type reference", "General description of the device", "Other identification of the product").
2. Maximum output power, maximum antenna gain, duty cycle and use distance information.
3. The device under evaluation consists of a hearing aid is intended to amplify and transmit sound to the ear and thereby compensate for impaired hearing.
4. The data used for the evaluation are from the device Phonak Audéo I90-R. On the following page, the models have been declared by the supplier as equivalent.



ID: <Do not edit>
Version: <Do not edit>

<Title: Do not edit>

To whom it may concern

Stäfa (Switzerland), June 2024 / David Sooprayen, Senior Regulatory Affairs Manager

Product Equality Declaration

We, Sonova AG, hereby declare under our own responsibility that the products listed below as “Hardware Equivalent Products” are in all relevant parts and hardware construction identical to the corresponding product identified as “Products with basis Hardware”. The following standards and/or technical regulations and corresponding test reports fully apply accordingly:

Standards
Hearing aid standards: ACUSTIC: IEC (International Electroacoustic Commission) 60118-0 and NSH 7.0 (including Annex A); EMC (Electromagnetic Compatibility): IEC 60118-13; EMC immunity: ANSI (American National Standards Institute) C63.19; Degrees of protection provided by enclosures (IP Code): IEC 60529 SW: IEC/EN 62304:2006 + A1:2015; UNE EN 62304:2007 + Corr:2009 + A1:2016; Europe: HEALTH & SAFETY: IEC/EN 60601-1; IEC/EN 60601-1-6; IEC/EN 60601-1-11; IEC/EN 60601-2-66; UN 38.3 Test 7; IEC/EN 62479; EMC: IEC/EN 60601-1-2; EN ETSI 301 489-1,-17 ; SPECTRUM: EN 300 328; USA: 47 CFR Part 15 (B); Part 15 (C):15.249, 15.209; Part 2: 2.1093; 2.1091 ; Canada: RSS-Gen, ICES-003, RSS-210, RSS-102; Japan: ARIB T66, Ordinance regulating Radio Equipment (2005-08) Art.12 item 19;

Place and date

Staefa, June 10, 2024

David Sooprayen
Senior Regulatory Affairs Manager

Staefa, June 10, 2024

Lora Braun
Regulatory Affairs Manager

Products with basis Hardware (tested representative model)	Hardware Equivalent Products
Phonak Audéo I90-R (with S/M/P/UP/MAV receivers) HW version: 050-1050-xx FW version: 067-1604 SW version: Target 10	Phonak Audéo I70-R (with S/M/P/UP/MAV receivers) HW version: 050-1049-xx SW version: Target 10 FW version: 067-1605 Phonak Audéo I50-R (with S/M/P/UP/MAV receivers) HW version: 050-1048-xx SW version: Target 10 FW version: 067-1606 Phonak Audéo I30-R (with S/M/P/UP/MAV receivers) HW version: 050-1047-xx SW version: Target 10 FW version: 067-1607 Phonak Audéo I-R Trial (with S/M/P/UP/MAV receivers) HW version: 050-1044-xx SW version: Target 10 FW version: 067-1604 ampli-energy R 5 5P R PH (with S/M/P/UP/MAV receivers) HW version: 050-1050-xx67 SW version: Target 10 FW Version: 067-1604 ampli-energy R 4 5P R PH (with S/M/P/UP/MAV receivers) HW version: 050-1049-xx67 SW version: Target 10 FW Version: 067-1605 ampli-energy R 3 5P R PH (with S/M/P/UP/MAV receivers) HW version: 050-1048-xx67 SW version: Target 10 FW Version: 067-1606 ampli-energy R 2 5P R PH (with S/M/P/UP/MAV receivers) HW version: 050-1047-xx67 SW version: Target 10 FW Version: 067-1607 ampli-energy R Trial 5P (with S/M/P/UP/MAV receivers) HW version: 050-1044-xx67 SW version: Target 10 FW Version: 067-1604

where xx – means colour identification



ID: PDL-21302
Version: 1

Declaration of equivalence DOE Audeo I-R - CROS I-R

To whom it may concern

Stäfa (Switzerland), April 2024 / David Sooprayen, Interim Head of Regulatory Affairs

Product Equality Declaration

We, Sonova AG, hereby declare under our own responsibility that the products listed below as "Hardware Equivalent Products" are in all relevant parts and hardware construction identical to the corresponding product identified as "Products with basis Hardware". The following standards and/or technical regulations and corresponding test reports fully apply accordingly:

Standards
Degrees of protection provided by enclosures (IP Code): IEC 60529
SW: IEC/EN 62304:2006 + A1:2015; UNE EN 62304:2007 + Corr:2009 + A1:2016;
Europe: HEALTH & SAFETY: IEC/EN 60601-1; IEC/EN 60601-1-6; IEC/EN 60601-1-11; IEC/EN 60601-2-66; UN 38.3 Test 7; IEC/EN 62479; EMC: IEC/EN 60601-1-2; EN ETSI 301 489-1,-17 ; SPECTRUM: EN 300 328;
USA: 47 CFR Part 15 (B); Part 15 (C):15.249, 15.209; Part 2: 2.1093; 2.1091 ;
Canada: RSS-Gen, ICES-003, RSS-210, RSS-102;
Japan: ARIB T66, Ordinance regulating Radio Equipment (2005-08) Art.12 item 19;

The only difference between the listed equivalent and corresponding basis models is the model's name, a separate set of audiological features per performance level.

Products with basis Hardware (tested representative model)	Hardware Equivalent Products
Phonak Audeo I90-R (with S/M/P/UP/MAV receivers) HW version: 050-1050-xx FW version: 067-1604 SW version: Target 10	Phonak CROS I-R HW version: 050-1043-xx SW version: Target 10 FW Version: 067-1608 Phonak CROS I-R Trial HW version: 050-1046-xx SW version: Target 10 FW Version: 067-1608

where xx – means colour identification

Place and date

Staefa, April 08, 2024

David Sooprayen
Interim Head of Regulatory Affairs

Staefa, April 08, 2024

Lora Braun
Regulatory Affairs Manager

Confidential and proprietary.
This document and its contents are confidential and proprietary to Sonova and shall not be reproduced or otherwise disclosed to anyone other than Sonova employees without written authorization from Sonova.
This printout is an uncontrolled copy. The original is stored in the Document Management System.
Template: TPL-748 [1] Page 1 of 1

DEKRA Testing and Certification S.A.U. declines any responsibility with respect to the information provided by the client and that may affect the validity of results.

Identification of the client

Sonova USA Inc.
44 commerce st. Aurora Illinois, 60504, United States

Document history

Report number	Date	Description
76950RAN.002	2024-06-12	First release

Appendix A: FCC RF Exposure assessment result

General description of the device under evaluation

Table 1 shows information used for the RF Evaluation, taking into account the following declared specifications for the device:

Description and technologies: the device under evaluation consists of a hearing aid is intended to amplify and transmit sound to the ear and thereby compensate for impaired hearing with the following features: DM, Flora, Bluetooth Classic, Bluetooth EDR and Bluetooth Low Energy. For RF Exposure evaluation, only transmission technologies: DM, Flora, Bluetooth Classic, Bluetooth EDR and Bluetooth Low Energy are taken into account.

Evaluation Distance: according to the manufacturer, during its normal use, the separation distance between the radiating structures of the device and nearby users will be greater than 0 cm. In order to perform the assessment a conservative evaluation distance of 0 cm (5mm applied for the evaluation) has been used.

Maximum output power:

Values corresponding to maximum output power have been declared by the device manufacturer (maximum output power values stated in manufacturer's technical description document.

The duty cycle of each transmission technology has been declared by the client in the Operational Description document.

Antennas: the device supports one antenna for the DM, Flora, Bluetooth Classic, Bluetooth EDR and Bluetooth Low Energy transmitting technology:

- "FPCB 03 ANT RIC 006-0439-03" antenna for Bluetooth Classic, Bluetooth EDR and Bluetooth Low Energy transmissions.
- "FPCB 03 ANT RIC 006-0439-03" antenna for DM and Flora transmissions.

Maximum peak antenna gain values have been declared by the device manufacturer (maximum peak gain stated in antenna manufacturer's datasheet)

The following table shows the information provided above:

Technology / Mode	Operating Band	Frequency under evaluation (MHz)	Maximum Conducted Output Power (Incl. Tune-Up) (dBm)	Duty Cycle (%)	Time Averaged Conducted Power (dBm)	FPCB 03 ANT RIC 006-0439-03 peak gain (dBi)	Maximum Averaged E.R.P (dBm)	Maximum Averaged E.R.P (mW)	Maximum Averaged E.I.R.P (dBm)	Maximum Averaged E.I.R.P (mW)
Proprietary DM	2.4 GHz	2402 - 2480	0.00	4.00	-13.98	-11.00	-27.13	0.00	-24.98	0.00
Proprietary Flora	2.4 GHz	2402 - 2480	6.00	60.00	3.78	-11.00	-9.37	0.12	-7.22	0.19
Bluetooth Classic	2.4 GHz	2400 - 2483.5	6.00	31.00	0.91	-11.00	-12.24	0.06	-10.09	0.10
Bluetooth EDR 2 Mb	2.4 GHz	2400 - 2483.5	2.00	31.00	-3.09	-11.00	-16.24	0.02	-14.09	0.04
Bluetooth EDR 3 Mb	2.4 GHz	2400 - 2483.5	2.00	31.00	-3.09	-11.00	-16.24	0.02	-14.09	0.04
Bluetooth Low Energy 1Mb	2.4 GHz	2400 - 2483.5	6.00	38.00	1.80	-11.00	-11.35	0.07	-9.20	0.12
Bluetooth Low Energy 2Mb	2.4 GHz	2400 - 2483.5	6.00	38.00	1.80	-11.00	-11.35	0.07	-9.20	0.12

Table 1: Equipment specifications

Evaluation Results

Determination of Exemption according to FCC 47 CFR Part 1.1307:

The evaluation according to the minimum intended use distance of 0 mm (5mm applied for the evaluation) will be as follow:

Technology / Mode	Operating Band	Frequency under evaluation (MHz)	Distance (cm)	Time Averaged Conducted Power (mW)	§ 1.1307(b)(3).i.(B) Exposure Limit (mW)	Verdict
Proprietary DM	2.4 GHz	2402 - 2480	0.50	0.04	2.72	Pass
Proprietary Flora	2.4 GHz	2402 - 2480	0.50	2.39	2.72	Pass
Bluetooth Classic	2.4 GHz	2400 - 2483.5	0.50	1.23	2.71	Pass
Bluetooth EDR 2 Mb	2.4 GHz	2400 - 2483.5	0.50	0.49	2.71	Pass
Bluetooth EDR 3 Mb	2.4 GHz	2400 - 2483.5	0.50	0.49	2.71	Pass
Bluetooth Low Energy 1Mb	2.4 GHz	2400 - 2483.5	0.50	1.51	2.71	Pass
Bluetooth Low Energy 2Mb	2.4 GHz	2400 - 2483.5	0.50	1.51	2.71	Pass

Table 2: FCC Exemption Evaluation Result

The computed value(s) are below the exemption limit(s), so these modes meet the requirements stated in FCC 47 CFR Part 1.1307.

Appendix B: FCC RF Exposure information

RF Exposure determination of exemption

According to FCC 47 CFR §1.1307 (b)(3) Determination of exemption:

(i) For single RF sources (i.e., any single fixed RF source, mobile device, or portable device, as defined in paragraph (b)(2), a single RF source is exempt if:

(A) The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(ii)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A);

(B) Or the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

(C) Or using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

TABLE 1 TO §1.1307(b)(3)(i)(C)—SINGLE RF SOURCES SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2 f$.
1,500-100,000	$19.2 R^2$.

(ii) For multiple RF sources: Multiple RF sources are exempt if:

(A) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(i)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(i)(A).

(B) in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure\ Limit_k} \leq 1$$

Where:

a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(B) of this section for P_{th}, including existing exempt transmitters and those being added.

b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added.

c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

P_i = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).

P_{th,i} = the exemption threshold power (P_{th}) according to paragraph (b)(3)(i)(B) of this section for fixed, mobile, or portable RF source i.

ERP_j = the ERP of fixed, mobile, or portable RF source j.

ERP_{th,j} = exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least λ/2π according to the applicable formula of paragraph (b)(3)(i)(C) of this section.

Evaluated_k = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

Exposure Limit_k = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k, as applicable from §1.1310 of this chapter.

The available maximum time-averaged power or effective radiated power (ERP), can be calculated using the following formula to assess compliance with the Exemption Limits:

$$P_{E.I.R.P.} = P_T + G_T - L_C$$

Where:

P_T = transmitter time-averaged output power (including Duty Cycle and tune-up tolerance, if applicable)

G_T = gain of the transmitting antenna

L_C = signal attenuation in the connecting cable between the transmitter and the antenna if applicable

$$P_{E.R.P.} = P_{E.I.R.P.} - 2.15 \text{ dB}$$