

RF EXPOSURE REPORT

CERTIFICATE OF CONFORMITY

FCC Rule Part: FCC Part 2 (Section 2.1091)

Report No.: MFBFKV-WTW-P25110335

FCC ID: L6AITN100-1

Product: Radar H2

Brand: BlackBerry

Model No.: ITN100-1

Received Date: 2025/11/16

Test Date: 2025/11/26

Issued Date: 2025/12/19

Applicant: BlackBerry Limited

Address: 2200 University Ave E, Waterloo, ON N2K 0A7

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, Taiwan

FCC Registration / 788550 / TW0003

Designation Number:

Approved by:

Jeremy Lin

Date:

2025/12/19

Jeremy Lin / Project Engineer

This test report consists of 9 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.



Prepared by : Polly Chien / Specialist

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	3
1 Certificate.....	4
2 Applicable RF Exposure Limit	5
3 Test Results	7
4 Conclusion.....	8
5 Information of the Testing Laboratories	9

Release Control Record

Issue No.	Description	Date Issued
MFBFKV-WTW-P25110335	Original release.	2025/12/19

1 Certificate

Product: Radar H2

Brand: BlackBerry

Test Model: ITN100-1

Sample Status: Engineering sample

Applicant: BlackBerry Limited

Test Date: 2025/11/26

FCC Rule Part: FCC Part 2 (Section 2.1091)

Standard: KDB 447498 D04 Interim General RF Exposure Guidance v01

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

2 Applicable RF Exposure Limit

§ 1.1310 Radiofrequency radiation exposure limits.

(a) Specific absorption rate (SAR) shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in § 1.1307(b) of this part within the frequency range of 100 kHz to 6 GHz (inclusive).

(b) The SAR limits for occupational/controlled exposure are 0.4 W/kg, as averaged over the whole body, and a peak spatial-average SAR of 8 W/kg, averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the parts of the human body treated as extremities, such as hands, wrists, feet, ankles, and pinnae, where the peak spatial-average SAR limit for occupational/controlled exposure is 20 W/kg, averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). Exposure may be averaged over a time period not to exceed 6 minutes to determine compliance with occupational/controlled SAR limits.

(c) The SAR limits for general population/uncontrolled exposure are 0.08 W/kg, as averaged over the whole body, and a peak spatial-average SAR of 1.6 W/kg, averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the parts of the human body treated as extremities, such as hands, wrists, feet, ankles, and pinnae, where the peak spatial-average SAR limit is 4 W/kg, averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). Exposure may be averaged over a time period not to exceed 30 minutes to determine compliance with general population/uncontrolled SAR limits.

(e) Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields

➤ Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	<30
1.34-30	824/f	2.19/f	(180/f ²)*	<30
30-300	27.5	0.073	0.2	<30
300-1,500	...	...	f/1500	<30
1,500-100,000	...	...	1.0	<30

f = frequency in MHz. * = Plane-wave equivalent power density.

➤ Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1,500	...	...	f/300	<6
1,500-100,000	...	...	5	<6

f = frequency in MHz. * = Plane-wave equivalent power density.

MPE-based Exemption – §1.1307(b)(3)(i)(C)

- The minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. The MPE-based test exemption condition is in terms of ERP, defined as the product of the maximum antenna gain and the delivered maximum time-averaged power.
- Table applies to any RF source (i.e. single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits.

Antenna for each of the five frequency ranges used for the MRE limits.			
RF Source frequency (MHz)	Minimum Distance		Threshold ERP (watts)
	$\lambda_L/2\pi$	$\lambda_H/2\pi$	
0.3-1.34	159 m–35.6 m		1,920 R ² .
1.34-30	35.6 m–1.6 m		3,450 R ² /f ² .
30-300	1.6 m–159 mm		3.83 R ² .
300-1,500	159 mm–31.8 mm		0.0128 R ² f.
1,500-100,000	31.8 mm–0.5 mm		19.2 R ² .
R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters.			

Fixed RF sources operating in the same time-averaging period – §1.1307(b)(3)(ii)(B)

- Either SAR-based or MPE-based exemption may be considered for test exemption for fixed, mobile, or portable device exposure conditions; therefore, the contributions from each exemption in conjunction with the measured SAR (Evaluated_k term) should be used to determine exemption for simultaneous transmission according to Formula below,

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

The sum of the ratios of the applicable terms for SAR-based, MPE-based and measured SAR or MPE should be less than 1, to determine simultaneous transmission exposure compliance.

Where:

a = number of fixed, mobile, or portable RF sources claiming exemption using [paragraph \(b\)\(3\)\(i\)\(B\)](#) of this section for P_{th} , including existing exempt transmitters and those being added.

c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

$P_{th,i}$ = the exemption threshold power (P_{th}) according to [paragraph \(b\)\(3\)\(i\)\(B\)](#) of this section for fixed, mobile, or portable RF source i .

$ERP_{th,j}$ = exemption threshold ERP for fixed, mobile, or portable RF source j , at a distance of at least $\lambda/2\pi$ according to the applicable formula of [paragraph \(b\)\(3\)\(i\)\(C\)](#) of this section.

$Exposure Limit_k$ = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k , as applicable from [§ 1.1310 of this chapter](#).

b = number of fixed, mobile, or portable RF sources claiming exemption using [paragraph \(b\)\(3\)\(i\)\(C\)](#) of this section for Threshold ERP, including existing exempt transmitters and those being added.

P_i = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).

ERP_j = the ERP of fixed, mobile, or portable RF source j .

$Evaluated_k$ = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

3 Test Results

Environmental Conditions:	25°C, 65% RH	Tested By:	Match Tsui
---------------------------	--------------	------------	------------

MPE-based Exemption §1.1307(b)(3)(i)(C)							
Operation Mode	Frequency Band (MHz)	Average Power (mW)	Antenna Gain (dBi)	Maximum ERP (mW)	Distance (cm)	Limit Threshold (mW)	Test Result
SRD_500kb/s	903-927	110.917	1.62	98.174	20	462.336	Pass
2.4GHz SRD	2405-2480	32.211	4.28	52.602	20	768	Pass
LTE Band 2	1850-1910	230.144	3.25	296.483	20	768	Pass
LTE Band 4	1710-1755	230.674	4.42	389.044	20	768	Pass
LTE Band 5	824-849	245.47	2.41	260.614	20	421.888	Pass
LTE Band 7	2500-2570	208.449	3.86	309.029	20	768	Pass
LTE Band 12	699-716	248.313	0.52	170.608	20	357.888	Pass
LTE Band 13	777-787	254.097	0.52	174.582	20	397.824	Pass
LTE Band 25	1850-1915	254.097	3.25	327.34	20	768	Pass
LTE Band 26	824-849	246.036	2.41	261.215	20	421.888	Pass
LTE Band 38	2570-2620	213.304	3.86	316.227	20	768	Pass
LTE Band 41	2496-2690	216.77	3.86	321.365	20	768	Pass
LTE Band 66	1710-1780	263.026	4.42	443.607	20	768	Pass

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

For Multiple RF Sources (Simultaneous Operations Condition 1)

Multiple RF Sources (Simultaneous Operations)							
Exemption Evaluation					Sum of Ratios	Limit of Ratios	Test Result
Operation Mode	Frequency Band (MHz)	Maximum ERP (mW)	Limit Threshold (mW)	Ratio			
SRD_500kb/s	903-927	98.174	462.336	0.212	0.830	1	Pass
LTE Band 5	824-849	260.614	421.888	0.618			

For Multiple RF Sources (Simultaneous Operations Condition 2)

Multiple RF Sources (Simultaneous Operations)							
Exemption Evaluation					Sum of Ratios	Limit of Ratios	Test Result
Operation Mode	Frequency Band (MHz)	Maximum ERP (mW)	Limit Threshold (mW)	Ratio			
2.4GHz SRD	2405-2480	52.602	768	0.068	0.686	1	Pass
LTE Band 5	824-849	260.614	421.888	0.618			

4 Conclusion

Source-base time average power is below Exemption Criteria and/or Routine Evaluation MPE thresholds, therefore the device is compliant FCC RF exposure requirement.

5 Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@bureauveritas.com

Web Site: <http://ee.bureauveritas.com.tw>

The address and road map of all our labs can be found in our web site also.

--- END ---