

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 1(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

SAR Compliance Test Report

Testing Lab: RIM Testing Services 440 Phillip Street Waterloo, Ontario Canada N2L 5R9 Phone: 519-888-7465 Fax: 519-746-0189	Applicant: Research In Motion Limited 295 Phillip Street Waterloo, Ontario Canada N2L 3W8 Phone: 519-888-7465 Fax: 519-888-6906 Web site: www.rim.com
--	---

Statement of Compliance: RIM Testing Services declares under its sole responsibility that the product to which this declaration relates, is in conformity with the appropriate RF exposure standards, recommendations and guidelines. It also declares that the product was tested in accordance with the appropriate measurement standards, guidelines and recommended practices.

Device Category: This BlackBerry® Smartphone is a portable device, designed to be used in direct contact with the user's head, hand and to be carried in approved accessories when carried on the user's body.

RF exposure environment: This device has been shown to be in compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in OET Bulletin 65 Supplement C (Edition 01-01), FCC 96-326, IEEE Std. C95.1-2005, Health Canada's Safety Code 6, as reproduced in RSS-102 issue 4-2010 and has been tested in accordance with the measurement procedures specified in FCC OET Procedures, OET Bulletin 65 Supplement C (Edition 01-01), ANSI/IEEE Std. C95.3-2002, IEEE 1528-2003, IEC 62209-1-2005, IEC 62209 - 2-2010 and Health Canada's Safety Code 6.


Tested by:
Hang Wang
Compliance Testing Associate

Signatures

Date
18-July-2011



Documented by:
Andrew Becker
SAR & HAC
Compliance Specialist



26-July-2011

Tested and reviewed by:
Daoud Attayi
Team Lead: Safety, SAR & HAC
Compliance



16-Sep-2011

Approved by:
Masud S. Attayi
Manager, Regulatory Compliance



16-Sep-2011

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 2(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

CONTENTS

SAR COMPLIANCE TEST REPORT.....	1
CONTENTS.....	2
REVISION INFORMATION.....	5
1.0 OPERATING CONFIGURATIONS AND TEST CONDITIONS.....	6
1.1 PICTURE OF DEVICE.....	6
1.2 ANTENNA DESCRIPTION.....	6
1.3 DEVICE DESCRIPTION.....	6
1.4 BODY WORN ACCESSORIES (HOLSTERS).....	9
1.5 HEADSET.....	9
1.6 BATTERY.....	9
1.7 PROCEDURE USED TO ESTABLISH TEST SIGNAL.....	10
1.8 HIGHLIGHTS OF THE FCC OET SAR MEASUREMENT REQUIREMENTS.....	10
1.8.1 SAR MEASUREMENT REQUIREMENTS FOR 3-6 GHZ AND MEASUREMENT PROCEDURES FOR 802.11 A/B/G/N TRANSMITTER.....	10
1.8.2 FCC SAR MEASUREMENT PROCEDURES FOR 3G DEVICES CDMA 2000.....	13
1.8.2.1 OUTPUT POWER VERIFICATION.....	13
1.8.2.2 3GPP2 C.S0011/ T1A-98-E, SECTION 4.4.5.2 METHOD OF MEASUREMENT.....	13
1.8.2.3 HEAD SAR MEASUREMENTS.....	14
1.8.2.4 BODY SAR MEASUREMENTS.....	14
1.8.2.5 1X EV-DO.....	14
TABLE 1.8.9. CONDUCTED RF OUTPUT POWER (DBM) MEASURED FOR VARIOUS SETTINGS.....	15
1.8.3 SAR MEASUREMENT REQUIREMENTS FOR BLUETOOTH.....	16
1.8.4 SAR MEASUREMENT PROCEDURES FOR 3G DEVICES.....	16
1.9 HIGHLIGHTS OF THE FCC OET SAR EVALUATION CONSIDERATIONS FOR HANDSETS WITH MULTIPLE TRANSMITTERS/ ANTENNAS & GSM/GPRS/EDGE PROCEDURE.....	18
2.1 SAR MEASUREMENT SYSTEM.....	23
2.1.1 EQUIPMENT LIST.....	24
2.2 DESCRIPTION OF THE TEST SETUP.....	25
2.2.1 DEVICE AND BASE STATION SIMULATOR SETUP.....	25
2.2.2 DASY SETUP.....	25
3.0 ELECTRIC FIELD PROBE CALIBRATION.....	25
3.1 PROBE SPECIFICATIONS.....	25
3.2 PROBE CALIBRATION AND MEASUREMENT UNCERTAINTY.....	26
4.0 SAR MEASUREMENT SYSTEM VERIFICATION.....	26
4.1 SYSTEM ACCURACY VERIFICATION FOR HEAD ADJACENT USE.....	27
5.0 PHANTOM DESCRIPTION.....	28
6.0 TISSUE DIELECTRIC PROPERTIES.....	29
6.1 COMPOSITION OF TISSUE SIMULANT.....	29
6.1.1 EQUIPMENT.....	29
6.1.2 PREPARATION PROCEDURE.....	30
6.2 ELECTRICAL PARAMETERS OF THE TISSUE SIMULATING LIQUID.....	30
6.2.2 TEST CONFIGURATION.....	32
6.2.3 PROCEDURE.....	32
7.0 SAR SAFETY LIMITS.....	33
8.0 DEVICE POSITIONING.....	34
8.1 DEVICE HOLDER FOR SAM TWIN PHANTOM.....	34
8.2 DESCRIPTION OF THE TEST POSITIONING.....	35
8.2.1 TEST POSITIONS OF DEVICE RELATIVE TO HEAD.....	35
8.2.1.1 DEFINITION OF THE "CHEEK" POSITION.....	36
8.2.1.2 DEFINITION OF THE "TILTED" POSITION.....	37
8.2.2 BODY HOLSTER CONFIGURATION.....	37
9.0 HIGH LEVEL EVALUATION.....	38
9.1 MAXIMUM SEARCH.....	38
9.2 EXTRAPOLATION.....	38
9.3 BOUNDARY CORRECTION.....	38
9.4 PEAK SEARCH FOR 1G AND 10G CUBE AVERAGED SAR.....	38
10.0 MEASUREMENT UNCERTAINTY.....	39
11.0 TEST RESULTS.....	42
11.1 SAR MEASUREMENT RESULTS AT HIGHEST POWER MEASURED AGAINST THE HEAD.....	42
11.2 SAR MEASUREMENT RESULTS AT HIGHEST POWER MEASURED AGAINST THE BODY USING ACCESSORIES.....	50

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 3(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

12.0	REFERENCES	57
------	------------------	----

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 4(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

APPENDIX A: SAR DISTRIBUTION COMPARISON FOR ACCURACY VERIFICATION

APPENDIX B: SAR DISTRIBUTION PLOTS - HEAD CONFIGURATION

APPENDIX C: SAR DISTRIBUTION PLOTS - BODY-WORN CONFIGURATION

APPENDIX D: PROBE & DIPOLE CALIBRATION DATA

APPENDIX E: PHOTOGRAPHS

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 5(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

Revision Information

RTS-2580-1106-03 Rev2 report includes 5-6 GHz SAR zoom scan graded grid measurement procedure on page 10.

In addition, zoom scan graded grid parameters have been added in Appendix B & C of the plots.

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 6(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

1.0 OPERATING CONFIGURATIONS AND TEST CONDITIONS

1.1 Picture of Device

Please refer to Appendix E.

Figure 1.1.1 BlackBerry Smartphone

1.2 Antenna description

Type	Internal fixed antenna
Location	Back bottom centre (main licensed transmitters)
Configuration	Internal fixed antenna

Table 1.2.1. Antenna description

1.3 Device description

Device Model	RDU71CW				
FCC ID	L6ARDU70CW				
PIN	32D4BD0D (Radiated Rev2), 32D4BD3C, 32E46EDD (Radiated Rev3), 32E895E6 (Radiated Rev4)				
Hardware Rev	Rev 2, Rev 3, Rev 4				
Software Version	6.1.0.260/420/677/825				
Prototype or Production Unit	Production				
Mode(s) of Operation in North America	1-slot GSM 850 GSM 1900	2-slots EDGE/GPRS 850/1900	3-slots EDGE/GPRS 850/1900	4-slots EDGE/GPRS 850/1900	CDMA2000 Cell 850
Nominal Maximum conducted RF Output Power (dBm)	32.5 30.0	30.0 29.0	29.0 26.0	27.0 25.5	24.0
Tolerance in Power Setting on centre channel (dB)	± 0.50	± 0.50	± 0.50	± 0.50	± 0.50
Duty Cycle	1:8	2:8	3:8	4:8	1:1
Transmitting Frequency Range (MHz)	824.2 – 848.8 1850.2 – 1909.8	824.2 – 848.8 1850.2 – 1909.8	824.2 – 848.8 1850.2 – 1909.8	824.2 – 848.8 1850.2 – 1909.8	824.70 – 848.52
Mode(s) of Operation	802.11b	802.11g	802.11n	Bluetooth	CDMA2000 PCS 1900
Nominal Maximum conducted RF Output Power (dBm)	18.5	17.0	17.0	10.5	23.5
Tolerance in Power Setting on centre channel (dB)	± 0.50	± 0.50	± 0.50	N/A	± 0.50
Duty Cycle	1:1	1:1	1:1	N/A	1:1

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 7(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

Transmitting Frequency Range (MHz)	2412-2462	2412-2462	2412-2462	2402-2483	1851.25-1908.50
Mode(s) of Operation	802.11a/n (low band)	802.11a/n (middle band)	802.11a/n (upper band I)	802.11a/n (upper band II)	
Nominal Maximum conducted RF Output Power (dBm)	11.0	12.0	14.0	13.5	
Tolerance in Power Setting on centre channel (dB)	± 0.50	± 0.50	± 0.50	± 0.50	
Duty Cycle	1:1	1:1	1:1	1:1	
Transmitting Frequency Range (MHz)	5180-5240	5260-5320	5500-5700	5749-5805	

Table 1.3.1. RDU71CW test device description

The RDU71CW device supports GSM/GPRS/EDGE 900/1800 MHz bands and UMTS band I & VIII that are not operational in North America, therefore no data is presented in this report for those bands.

Device Model	RDE71UW				
FCC ID	L6ARDE70UW				
PIN	2618EEE2 (Radiated Rev1), 272B6150 (Radiated Rev3), 2618F0FB(Conducted)				
Hardware Rev	Rev 1, Rev 3				
Software Version	6.1.0.132/157/677				
Prototype or Production Unit	Production				
Mode(s) of Operation in North America	1-slot GSM 850 GSM 1900	2-slots EDGE/GPRS 850/1900	3-slots EDGE/GPRS 850/1900	4-slots EDGE/GPRS 850/1900	WCDMA / UMTS FDD V (850)
Nominal Maximum conducted RF Output Power (dBm)	32.5 31.0	30.0 30.0	29.0 26.0	27.0 25.5	24.5
Tolerance in Power Setting on centre channel (dB)	± 0.50	± 0.50	± 0.50	± 0.50	± 0.50
Duty Cycle	1:8	2:8	3:8	4:8	1:1
Transmitting Frequency Range (MHz)	824.2 – 848.8 1850.2 – 1909.8	824.2 – 848.8 1850.2 – 1909.8	824.2 – 848.8 1850.2 – 1909.8	824.2 – 848.8 1850.2 – 1909.8	824.6 – 846.6
Mode(s) of Operation	802.11b	802.11g	802.11n	Bluetooth	WCDMA / UMTS FDD II (1900)
Nominal Maximum conducted RF Output Power (dBm)	18.5	17.0	17.0	10.5	23.5

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 8(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

Tolerance in Power Setting on centre channel (dB)	± 0.50	± 0.50	± 0.50	N/A	± 0.50
Duty Cycle	1:1	1:1	1:1	N/A	1:1
Transmitting Frequency Range (MHz)	2412-2462	2412-2462	2412-2462	2402-2483	1852.4 – 1907.6
Mode(s) of Operation	802.11a/n (low band)	802.11a/n (middle band)	802.11a/n (upper band I)	802.11a/n (upper band II)	
Nominal Maximum conducted RF Output Power (dBm)	11.0	12.0	14.0	13.5	
Tolerance in Power Setting on centre channel (dB)	± 0.50	± 0.50	± 0.50	± 0.50	
Duty Cycle	1:1	1:1	1:1	1:1	
Transmitting Frequency Range (MHz)	5180-5240	5260-5320	5500-5700	5749-5805	

Table 1.3.2. RDE71UW test device description

Note 1: The RDE71UW device supports GSM/GPRS/EDGE 900/1800 MHz bands and UMTS band I that are not operational in North America, therefore no data is presented in this report for those bands.

Note 2: According to manufacturer's hardware similarity declaration document, the two models (RDU71CW and RDE71UW) have identical design. Please refer to the declaration for more detail. The difference is model: RDE71UW does not support CDMA 2000 bands, instead it supports UMTS band II and V.

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 9(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

1.4 Body worn accessories (holsters)

The device has been tested with the holster below. The holster is designed with the intended device orientation being with the LCD facing the belt clip. Proper positioning is vital for protection of the LCD display, and to help maximize the battery life of the device. The device can also be placed in the holster with the backside facing the belt clip. Body SAR measurements were carried out with the worst-case configuration front LCD side and backside towards the belt clip.

Number	Holster Type	Part Number	Separation distance (mm)
1	Vertical Holster	HDW-38843-001	20

Table 1.4.1. Body worn holster

Please refer to Appendix E.

Figure 1.4.1. Body-worn holster

1.5 Headset

The device was tested with and without the following headset model numbers.

- 1) HDW-14322-003
- 2) HDW-15766-005
- 3) HDW-24529-001

1.6 Battery

The device was tested with the following Lithium Ion Battery pack.

- 1) BAT-30615-006

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 10(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

1.7 Procedure used to establish test signal

The device was put into test mode for SAR measurements by placing a voice call from a Rohde & Schwarz CMU 200 Communications Test Instrument. The power control level was set to command the device to transmit at full power at the specified frequency. Other parameters include: Channel type = full rate, discontinuous transmission off, frequency hopping off.

1.8 Highlights of the FCC OET SAR Measurement Requirements

1.8.1 SAR Measurement Requirements for 3-6 GHz and Measurement Procedures for 802.11 a/b/g/n Transmitter

- Maintained dielectric parameter uncertainty as close to $\pm 5.0\%$ of the target value as possible.
- Liquid depth from SAM ERP or flat phantom was kept at 15 cm.
- Probe Requirement: Used SPEAG probe model EX3DV4 for 2.4 – 6 GHz SAR testing specs are outlined below:

Probe tip to sensor center	1.0 mm
Probe tip diameter is	2.5 mm
Probe calibration uncertainty	< 15 % for $f = 2.45$ to < 6.0 GHz
Probe calibration range	± 100 MHz

Table 1.8.1. Probe requirement

- Area scan resolution was maintained at 10mm
- System accuracy validation was conducted within ± 100 MHz of device mid-band frequency and results were within $\pm 10\%$ of the manufacturers target value for each band.
- Zoom Scan: The following settings were used for the validation and measurement.

Closet Measurement Point to Phantom	2.0 mm
Zoom Scan (x,y) Resolution	4.0 mm
Zoom Scan (z) Resolution	2.5 mm
Zoom Scan Volume	32 x 32 x 20 mm
Graded Ratio	1.5

Table 1.8.2. Zoom Scan requirement

- **As per FCC KDB 865664**, graded grids have been used (z), the first measurement point was kept within 2 mm at 5-6 GHz. The subsequent graded grid ratio of 1.5 was used. A zoom scan of 32x32x20 mm³ was used. Step size of 4.0 mm on (x,y) and 2.5 mm (z) axis were used.
- Frequency Channel Configuration: 802.11 b/g modes are tested on “default test channels” 1, 6 and 11.
- 802.11a is tested for UNII operations on channels 36 and 48 in the lower band 5.15 – 5.25 GHz band; channels 52 and 64 in the 5.25 – 5.35 GHz band; channels 149 and 161 in the 5.8 GHz band.
- For each frequency band, testing at higher rates and higher modulations is not required when the maximum average output power for each of these configurations is less than $\frac{1}{4}$ dB higher than those measured at the lowest data rate.

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 11(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

- SAR is not required for 802.11g channels when the maximum average output power is less than ¼ dB higher than that measured on the corresponding 802.11b channels. The average output power for 802.11a should be measured on all channels in each frequency band.
- SAR test are conducted on each “default test channel” and each band with the worst case modulation that resulted in maximum duty cycle of 99.5 %.
- Conducted power measurements:

802.11a (low band) 6Mbps		802.11a (mid band) 6Mbps		802.11a (upper band I) 6Mbps		802.11a (upper band II) 6Mbps	
Chan	Cond. Power (dBm)	Chan	Cond. Power (dBm)	Chan	Cond. Power (dBm)	Chan	Cond. Power (dBm)
36	11.05	52	12.00	104	14.12	149	13.35
40	11.03	56	11.97	116	14.03	153	13.28
44	10.98	60	11.95	124	13.98	157	13.30
48	10.95	64	11.98	140	13.85	161	13.30

Table 1.8.3. 802.11a channel vs. conducted power

		802.11a (lower band)	802.11a (middle band)	802.11a (upper band I)
Data Rate (Mbps)	Mod.	Channel 36	Channel 52	Channel 149
		Cond. Power (dBm)	Cond. Power (dBm)	Cond. Power (dBm)
6	BPSK	11.05	12.00	13.35
9	BPSK	10.61	11.53	12.93
12	QPSK	9.40	10.71	12.33
18	QPSK	9.45	10.16	11.53
24	16-QAM	8.13	9.26	10.48
36	16-QAM	8.00	8.47	9.68
48	64-QAM	6.70	7.68	7.61
54	64-QAM	6.61	7.62	7.51
		802.11 n		
		Channel 149		
Data Rate (Mbps)	Mod.	Cond. Power (dBm)		
6.5	MCS0	13.30		
13	MCS1	12.28		
19.5	MCS2	11.58		
26	MCS3	10.61		
39	MCS4	9.81		
52	MCS5	7.85		
58.5	MCS6	7.71		
65	MCS7	6.72		

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 12(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

Table 1.8.4. 802.11a modulation type/data rate vs. conducted power

802.11b @ 1Mbps		802.11g @ 6Mbps		802.11n @ 6.5 Mbps	
Chan	Cond. Power (dBm)	Chan	Cond. Power (dBm)	Chan	Cond. Power (dBm)
1	18.86	1	13.02	1	12.82
6	19.00	6	17.18	6	16.93
11	18.30	11	12.63	11	12.45

Table 1.8.5. 802.11 b/g/n channel vs. conducted power

		802.11g		802.11b	
Data Rate (Mbps)	Mod.	Channel 6	Data Rate (Mbps)	Mod.	Channel 6
		Cond. Power (dBm)			Cond. Power (dBm)
6	BPSK	17.18	1	BPSK	19.00
9	BPSK	16.53	2	DQPSK	18.89
12	QPSK	15.62	5.5	CCK	17.97
18	QPSK	14.83	11	CCK	17.56
24	16-QAM	12.33	22	CCK	18.90
36	16-QAM	11.50			
48	64-QAM	9.37			
54	64-QAM	9.24			
			802.11 n		
Data Rate (Mbps)	Mod.		Channel 6		
			Cond. Power (dBm)		
6.5	MCS0		16.93		
13	MCS1		15.52		
19.5	MCS2		14.81		
26	MCS3		12.43		
39	MCS4		11.68		
52	MCS5		9.68		
58.5	MCS6		9.52		
65	MCS7		8.51		

Table 1.8.6. 802.11 b/g/n modulation type/data rate vs. conducted power

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 13(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

1.8.2 FCC SAR Measurement Procedures for 3G Devices CDMA 2000

The followings are the **FCC SAR Measurement Procedures for 3G Devices issued in Oct. 2006**, applicable to handsets operating under CDMA 2000, Release 0, with MS Protocol Revision 6 (**P_REV 6**). The default test configuration is to measure SAR in RC3 with an established radio link between the DUT and a communication test set. SAR in RC1 is selectively confirmed according to output power and exposure conditions.

1.8.2.1 Output Power Verification

Maximum output power is verified on the High, Middle and Low channels according to procedures in section 4.4.5.2 of 3GPP2 C.S0011/TIA-98-E. Results for at least steps 3, 4 and 10 of the power measurement procedures should be tabulated in the SAR report as shown on Table 1.9.2. Steps 3 and 4 should be measured using SO55 with power control bits in “All Up” condition. TDSO / SO32 may be used instead of SO55 for step 4. Step 10 should be measured using TDSO / SO32 with power control bits in the “Bits Hold” condition (i.e. alternative Up/Down Bits).

1.8.2.2 3GPP2 C.S0011/ TIA-98-E, section 4.4.5.2 Method of Measurement

1. If the mobile station supports Reverse Traffic Channel Radio Configuration 1 and 7 Forward Traffic Channel Radio Configuration 1, set up a call using Fundamental 8 Channel Test Mode 1 with 9600 bps data rate only and perform steps 6 through 8.
2. If the mobile station supports the Radio Configuration 3 Reverse Fundamental 11 Channel and demodulation of Radio Configuration 3, 4, or 5, set up a call using 12 Fundamental Channel Test Mode 3 with 9600 bps data rate only and 13 perform steps 6 through 8.
3. Set the test parameters as specified in Table 1.8.7.
4. Send continuously ‘0’ power control bits to the mobile station.
5. Measure the mobile station output power at the mobile station antenna connector.
6. If the mobile station supports the Radio Configuration 3 Reverse Fundamental Channel, Radio Configuration 3 Reverse Supplemental Channel 0 and demodulation of Radio Configuration 3, 4, or 5, set up a call using Supplemental Channel Test Mode 3 with 9600 bps Fundamental Channel and 9600 bps Supplemental Channel 0 data rate, and perform the following:
 - a) Set the test parameters as specified in Table 1.8.8.
 - b) Send alternating ‘0’ and ‘1’ power control bits to the mobile station using the smallest supported closed loop power control step size supported by the mobile station.
 - c) Determine the active channel configuration. If the desired channel configuration is not active, increase by 1 dB and repeat the verification. Repeat this step until the desired channel configuration becomes active.
 - d) Measure the mobile station output power at the mobile station antenna connector and record reading.

Parameter	Units	Value
$\bar{I}_{or}$	dBm/1.23 MHz	-104
$\frac{Pilot E_c}{I_{or}}$	dB	-7
$\frac{Traffic E_c}{I_{or}}$	dB	-7.4

Table 1.8.7.

Test Parameters for Maximum RF Output Power for Spreading Rate 1

Parameter	Units	Value
$\bar{I}_{or}$	dBm/1.23 MHz	-86
$\frac{Pilot E_c}{I_{or}}$	dB	-7
$\frac{Traffic E_c}{I_{or}}$	dB	-7.4

Table 1.8.8.

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 14(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

1.8.2.3 Head SAR Measurements

SAR for head exposure configurations is measured in RC3 with the DUT configured to transmit at full rate using Loopback Service Option SO55. SAR for RC1 is not required when the maximum average output of each channel is less than ¼ dB higher than that measured in RC3. Otherwise, SAR is measured on the maximum output channel in RC1 using the exposure configuration that results in the highest SAR for that channel in RC3.

1.8.2.4 Body SAR Measurements

SAR for body exposure configurations is measured in RC3 with the DUT configured to transmit at full rate on FCH with all other code channels disabled using TDSO / SO32. SAR for multiple code channels (FCH + SCH_n) is not required when the maximum average output of each RF channel is less than ¼ dB higher than that measured with FCH only. Otherwise, SAR is measured on the maximum output channel (FCH + SCH_n) with FCH at full rate and SCH₀ enabled at 9600 bps using the exposure configuration that results in the highest SAR for that channel with FCH only. When multiple code channels are enabled, the DUT output may shift by more than 0.5 dB and lead to higher SAR drifts and SCH dropouts.

Body SAR in RC1 is not required when the maximum average output of each channel is less than ¼ dB higher than that measured in RC3. Otherwise, SAR is measured on the maximum output channel in RC1; with Loopback Service Option SO55, at full rate, using the body exposure configuration that results in the highest SAR for that channel in RC3.

1.8.2.5 1x Ev-DO

For handsets with Ev-Do capabilities, when the maximum average output of each channel in Rev. 0 is less than ¼ dB higher than that measured in RC3 (1x RTT), body SAR for Ev-Do is not required. Otherwise, SAR for Rev. 0 is measured on the maximum output channel at 153.6 kbps using the body exposure configuration that results in the highest SAR for that channel in RC3. SAR for Rev. A is not required when the maximum average output of each channel is less than that measured in Rev. 0 or less than ¼ dB higher than that measured in RC3. Otherwise, SAR is measured on the maximum output channel for Rev. A using a Reverse Data Channel payload size of 4096 bits and a Termination Target of 16 slots defined for Subtype 2 Physical Layer configurations. A Forward Traffic Channel data rate corresponding to the 2-slot version of 307.2 kbps with the ACK Channel transmitting in all slots should be configured in the downlink for both Rev. 0 and Rev. A.

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 15(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

Band	Channel	1x EvDO (153.6kbps)	CDMA2000 RC	SO2 Loopback	SO55 Loopback	TDSO SO32 Test Data Service
CDMA 800	1013	24.6	RC1	24.7	24.7	N/A
			RC3	24.6	24.7	24.6
	384	24.7	RC1	24.7	24.7	N/A
			RC3	24.7	24.7	24.7
	777	24.6	RC1	24.6	24.5	N/A
			RC3	24.5	24.6	24.6
Band	Channel	1x EvDO (153.6kbps)	CDMA2000 RC	SO2 Loopback	SO55 Loopback	TDSO SO32 Test Data Service
CDMA 1900	25	23.7	RC1	23.7	23.8	N/A
			RC3	23.6	23.8	23.7
	600	23.8	RC1	23.9	23.9	N/A
			RC3	23.9	23.9	23.8
	1175	23.8	RC1	23.8	23.9	N/A
			RC3	23.9	23.9	23.8

Table 1.8.9. Conducted RF output power (dBm) measured for various settings

		Document		Page
		SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		16(58)
Author Data	Dates of Test	Test Report No	FCC ID:	IC ID
Andrew Becker	Feb 7 – May 25, July 18, 2011	RTS-3933-1105-11A RTS-2580-1106-03 Rev2	L6ARDU70CW L6ARDE70UW	2503A-RDU70CW 2503A-RDE70UW

1.8.3 SAR Measurement Requirements for Bluetooth

Channel	Freq (MHz)	Mode	Conducted Transmit Power (dBm)
0	2402	DH5	9.00
39	2441	DH5	10.67
78	2480	DH5	10.33

Table 1.8.10. Bluetooth peak conducted power measurements

1.8.4 SAR Measurement Procedures for 3G Devices

WCDMA Handsets

Output Power Verification

- Maximum output power is verified on the High, Middle and Low channels using 12.2 kbps RMC, 12.2 kbps AMR with a 3.4 kbps SRB (signal radio bearer) with TPC (transmit power control) set to all “1’s” for WCDMA/HSPA or applying the required inner loop.
- For Release 5 HSPA, output power is measured according to requirements for HS-DPCCH Sub-test 1-4

Head SAR Measurements

SAR for head exposure configurations is measured using the 12.2 kbps RMC with TPC bits configured to all “1s”. SAR in AMR configurations is not required when the maximum average output of each RF channel for 12.2 kbps AMR is less than ¼ dB higher than that measured in 12.2 kbps RMC. Otherwise, SAR is measured on the maximum output channel in 12.2 AMR with a 3.4 kbps SRB (signalling radio bearer) using the exposure configuration that results in the highest SAR for that RF channel in 12.2 RMC.

Body SAR Measurements

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits configured to all “1s”. SAR for other spreading codes and multiple DPDCH_n, when supported by the DUT, are not required when the maximum average outputs of each RF channel, for each spreading code and DPDCH_n configuration, are less than ¼ dB higher than those measured in 12.2 RMC. Otherwise, SAR is measured on the maximum output channel with an applicable RMC configuration for the corresponding spreading code or DPDCH_n using the exposure configuration that results in the highest SAR with 12.2 RMC.

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 17(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

Handsets with HSPA

Body SAR is not required for handsets with HSPA capabilities, when the maximum average output of each RF channel with HSPA active is less than ¼ dB higher than that measured in 12.2 kbps RMC without HSPA. Otherwise, SAR for HSPA is measured using FRC (fixed reference channel) in the body exposure configuration that results in the highest SAR for that RF channel in 12.2kbps RMC.

	Band	FDD V (850)			FDD II (1900)		
	Channel	4132	4182	4233	9262	9400	9538
	Freq (MHz)	826.4	836.4	846.6	1852.4	1880.0	1907.6
Mode	Subtest	Max burst averaged conducted power (dBm)			Max burst averaged conducted power (dBm)		
Rel99	12.2 kbps RMC	24.66	24.56	24.46	23.30	23.33	23.35
Rel99	12.2 kbps, Voice, AMR, SRB 3.4 kbps	24.70	24.65	24.30	23.41	23.34	23.44
Rel5 HSDPA	1	24.69	24.68	24.37	23.47	23.40	23.38
Rel5 HSDPA	2	24.60	24.58	24.65	23.35	23.36	23.46
Rel5 HSDPA	3	24.70	24.66	24.39	23.38	23.32	23.40
Rel5 HSDPA	4	24.68	24.63	24.40	23.37	23.30	23.43
Rel6 HSUPA	1	24.48	24.32	24.18	23.40	23.37	23.48
Rel6 HSUPA	2	24.58	24.50	24.13	23.34	23.37	23.29
Rel6 HSUPA	3	24.73	24.62	24.15	23.29	23.34	23.40
Rel6 HSUPA	4	24.80	24.52	24.43	23.30	23.40	23.31
Rel6 HSUPA	5	24.80	24.60	24.55	23.37	23.40	23.52

Table 1.8.11. WCDMA (Rel99) / HSPA conducted power measurements

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 18(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

1.9 Highlights of the FCC OET SAR Evaluation Considerations for Handsets with Multiple Transmitters/ Antennas & GSM/GPRS/EDGE Procedure

Unlicensed Transmitters

When there is simultaneous transmission –
Stand-alone SAR not required when

- output $\leq 2 \cdot P_{Ref}$ and antenna is > 5.0 cm from other antennas
- output $\leq P_{Ref}$ and antenna is > 2.5 cm from other antennas
- the other antenna(s), which are < 2.5 cm away, has an output $\leq P_{Ref}$ OR max 1g SAR < 1.2 W/kg

Otherwise stand-alone SAR is required

- test SAR on highest output channel for each wireless mode and exposure condition
- if SAR for highest output channel is $> 50\%$ of SAR limit, evaluate all channels according to normal procedure

Simultaneous Transmission SAR not required:

Unlicensed only

- when stand-alone 1-g SAR is not required and antenna is > 5 cm from other antennas
- when the other antenna(s), which are < 2.5 cm away, has an output $\leq P_{Ref}$ OR max 1g SAR < 1.2 W/kg

Licensed & Unlicensed

- when the sum of the 1-g SAR is < 1.6 W/kg for each pair of simultaneous transmitting antennas.
- or
- when the ratio of SAR to peak SAR separation distance of simultaneous transmitting antenna pair is < 0.3

Simultaneous Transmission SAR required:

Licensed & Unlicensed

- antenna pairs with SAR to antenna separation ratio ≥ 0.3 ; test is only required for the configuration that results in the highest SAR in standalone configuration for each wireless mode and exposure condition.

	2.45	5.15 - 5.35	5.47 - 5.85	GHz
P_{Ref}	12	6	5	mW
Device output power should be rounded to the nearest mW to compare with values specified in this table.				

Table 1.9.1. Output Power Thresholds for Unlicensed Transmitters




Figure 1.9.2. Back view of device showing closet distance between antenna pairs

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 19(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

Mode	Configuration	Highest 1 g SAR (W/kg)
GSM/GPRS/EDGE/CDMA	Head-Left-Touch	1.38
	15mm Spacer, Back	0.78
802.11a/b/g/n	Head-Left-Touch	0.52
	15mm Spacer, Back	0.49
BT	Head-Left-Touch	0.01
	15mm Spacer, Back	0.00

Table 1.9.3. Highest SAR values for the same setup (RDU71CW)

Mode	Configuration	Highest 1 g SAR (W/kg)
GSM/GPRS/EDGE/WCDMA	Head-Left-Touch	1.19
	15mm Spacer, Back	1.03
802.11a/b/g/n	Head- Left -Touch	0.52
	15mm Spacer, Back	0.49
BT	Head-Left-Touch	0.01
	15mm Spacer, Back	0.00

Table 1.9.4. Highest SAR values for the same setup (RDE71UW)

Antenna	Position	SAR Zoom 1g	X [mm]	Y [mm]	Z [mm]	
Antenna 1 (802.11 b)	LHS, Touch	0.52	55.9	328.0	-170.0	
Antenna 2 CDMA1900	LHS, Touch	1.38	66.0	252.4	-169.5	
	SAR Sum	1.90				
	Delta [cm]		-1.0	7.6	-0.1	
	closest Distance [cm]					7.63
	Ratio	0.25				

Table 1.9.4. RDU71CW Highest SAR values & Peak Coordinates distance

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 20(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

Antenna	Position	SAR Zoom 1g	X [mm]	Y [mm]	Z [mm]	
Antenna 1 (802.11 b)	LHS, Touch	0.52	55.9	328.0	170.0	-
Antenna 3 UMTS band II	LHS, Touch	1.19	72.2	265.1	169.0	-
Rev 1	SAR Sum	1.71				
	Delta [cm]		-1.6	6.3	-0.1	
	closest Distance [cm]					6.50
	Ratio	0.26				
Antenna	Position	SAR Zoom 1g	X [mm]	Y [mm]	Z [mm]	
Antenna 1 (802.11 b)	Body SAR 15mm back	0.49	-18.5	-34.0	206.4	-
Antenna 3 UMTS band II	Body SAR 15mm back	1.03	-33.5	51.5	206.1	-
Rev 1	SAR Sum	1.52				
	Delta [cm]		1.5	-8.6	0.0	
	closest Distance [cm]					8.68
	Ratio	0.18				
Antenna	Position	SAR Zoom 1g	X [mm]	Y [mm]	Z [mm]	
Antenna 1 (802.11 b)	LHS, Touch	0.52	55.9	328.0	170.0	-
Antenna 3 UMTS band II	LHS, Touch	1.10	75.0	276.4	168.5	-
Rev 3	SAR Sum	1.62				
	Delta [cm]		-1.9	5.2	-0.2	
	closest Distance [cm]					5.49
	Ratio	0.29				

Table 1.9.5. RDE71UW Highest SAR values & Peak Coordinates distance

BT & WiFi: BT Stand-alone and Simultaneous Transmission SAR are not required, since WiFi antenna is > 2.5 cm away and has max 1g SAR < 1.2 W/kg.

BT & GSM/WCDMA: BT Stand-alone SAR is required, since the other antenna(s), which are < 2.5 cm away, has an output > PRef and max 1g SAR > 1.2 W/kg

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 21(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

Simultaneous Transmission SAR is not required based on the sum of 1-g SAR values for this pair of simultaneous transmitting antennas being < 1.6W/kg.

GSM & WiFi: Simultaneous Transmission SAR is not required for head/body configuration based on the sum of 1-g SAR values for each pair of simultaneous transmitting antennas being < 1.6W/kg.

WCDMA & WiFi: Simultaneous Transmission SAR is not required for head configuration based on ratio of SAR to peak SAR separation distance is < 0.3

- The device supports DTM, GPRS Category Class A, Multi-Slot Class 12 with maximum 5 s-slots (4-slots uplink and 1-slot downlink).
- For head SAR configuration, GSM 1-slot (CS) uplink and 2/3/4-slots DTM {GSM (SC) + EDGE (PD)} were evaluated.
- For body SAR configuration, 2/3/4-slots GPRS (PD) mode were tested.
- In EDGE/GPRS mode, GMSK Modulation was used using CS1-CS4 or MCS1-MCS4.
- 8-PSK modulation or MCS5-MCS9 code scheme were avoided since maximum burst avg power was measured lower on those modulation schemes.
- Each slot is set to maximum power, but there is software power reduction of ~ 2/4/6 dB in DTM/EDGE/GPRS 2/3/4-slots uplink modes.

- Please refer to the conducted power measurements table below:

Mode	Freq. (MHz)	Max burst averaged conducted power (dBm) CS1	Max burst averaged conducted power (dBm) CS4	Max burst averaged conducted power (dBm) MCS1	Max burst averaged conducted power (dBm) MCS4	Max burst averaged conducted power (dBm) MCS5	Max burst averaged conducted power (dBm) MCS9
2-slots GPRS 850 MHz	824.2	29.8	29.7	N/A	N/A	N/A	N/A
	836.8	30.1	30.1	N/A	N/A	N/A	N/A
	848.8	29.9	29.8	N/A	N/A	N/A	N/A
3-slots GPRS 850 MHz	824.2	29.2	29.2	N/A	N/A	N/A	N/A
	836.8	29.1	29.1	N/A	N/A	N/A	N/A
	848.8	29.2	29.2	N/A	N/A	N/A	N/A
4-slots GPRS 850 MHz	824.2	26.8	26.8	N/A	N/A	N/A	N/A
	836.8	26.8	26.8	N/A	N/A	N/A	N/A
	848.8	26.9	26.9	N/A	N/A	N/A	N/A
2-slots EDGE/DTM 850 MHz	824.2	30.2	29.9	29.8	29.9	29.8	29.9
	836.8	30.4	30.2	30.1	30.1	30.3	30.0
	848.8	30.0	29.8	29.9	29.7	29.8	29.8
3-slots EDGE/DTM 850 MHz	824.2	29.2	29.3	29.3	29.2	29.2	29.2
	836.8	29.1	29.2	29.2	29.2	29.2	29.2
	848.8	29.2	29.2	29.2	29.2	29.2	29.2
4-slots EDGE/DTM 850 MHz	824.2	26.8	27.0	27.1	27.1	27.0	27.0
	836.8	26.8	27.0	27.0	27.1	27.1	26.9
	848.8	26.9	26.8	26.9	26.8	26.8	26.8

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW			Page 22(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW	

2-slots GPRS 1900 MHz	1850.2	28.9	29.3	N/A	N/A	N/A	N/A
	1880.0	29.0	29.1	N/A	N/A	N/A	N/A
	1909.8	28.8	29.2	N/A	N/A	N/A	N/A
3-slots GPRS 1900 MHz	1850.2	26.0	26.0	N/A	N/A	N/A	N/A
	1880.0	26.2	26.2	N/A	N/A	N/A	N/A
	1909.8	26.1	26.1	N/A	N/A	N/A	N/A
4-slots GPRS 1900 MHz	1850.2	25.5	25.4	N/A	N/A	N/A	N/A
	1880.0	25.6	25.5	N/A	N/A	N/A	N/A
	1909.8	25.6	25.6	N/A	N/A	N/A	N/A
2-slots EDGE/DTM 1900 MHz	1850.2	28.9	29.3	28.9	28.9	28.9	28.9
	1880.0	29.0	29.1	28.8	28.9	28.9	28.9
	1909.8	28.8	29.2	28.9	28.9	28.9	28.9
3-slots EDGE/DTM 1900 MHz	1850.2	26.0	26.0	26.1	26.2	26.3	26.3
	1880.0	26.2	26.2	26.1	26.1	26.3	26.3
	1909.8	26.1	26.1	26.0	26.0	26.2	26.2
4-slots EDGE/DTM 1900 MHz	1850.2	25.5	25.4	25.6	25.5	25.6	25.6
	1880.0	25.6	25.5	25.5	25.4	25.5	25.5
	1909.8	25.6	25.6	25.5	25.4	25.4	25.4
Mode		Freq. (MHz)			Max burst averaged conducted power (dBm)		
1-slot GSM (CS) 850 MHz		824.2			32.6		
		836.8			32.8		
		848.8			32.7		
1-slot GSM (CS) 1900 MHz		1850.2			29.8		
		1880.0			29.7		
		1909.8			29.7		

1.9.6. RDU71CW GSM/EDGE/GPRS channel vs. conducted power

Mode	Freq. (MHz)	Max burst averaged conducted power (dBm) CS1	Max burst averaged conducted power (dBm) CS4	Max burst averaged conducted power (dBm) MCS1	Max burst averaged conducted power (dBm) MCS4	Max burst averaged conducted power (dBm) MCS5	Max burst averaged conducted power (dBm) MCS9
2-slots EDGE/DTM 1900 MHz	1850.2	29.8	29.8	29.7	29.7	29.7	
	1880.0	29.7	29.7	29.7	29.7	29.7	
	1909.8	29.7	29.6	29.7	29.6	29.6	
Mode		Freq. (MHz)			Max burst averaged conducted power (dBm)		
1-slot GSM (CS) 1900 MHz		1850.2			31.3		
		1880.0			31.3		
		1909.8			31.2		

1.9.7. RDE71UW GSM/EDGE/GPRS channel vs. conducted power

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 24(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

2.1.1 Equipment List

Manufacturer	Test Equipment	Model Number	Serial Number	Cal. Due Date (MM/DD/YY)
SCHMID & Partner Engineering AG	E-field probe	ET3DV6	1643	03/09/2011
SCHMID & Partner Engineering AG	E-field probe	ES3DV3	3225	01/13/2012
SCHMID & Partner Engineering AG	E-field probe	EX3DV4	3548	01/20/2012
SCHMID & Partner Engineering AG	Data Acquisition Electronics (DAE3)	DAE3 V1	472	05/17/2011
SCHMID & Partner Engineering AG	Data Acquisition Electronics (DAE3)	DAE3 V1	472	03/07/2012
SCHMID & Partner Engineering AG	Data Acquisition Electronics (DAE3)	DAE3 V2	473	01/21/2011
SCHMID & Partner Engineering AG	Data Acquisition Electronics (DAE3)	DAE4	881	04/19/2011
SCHMID & Partner Engineering AG	Dipole Validation Kit	D835V2	446	01/21/2013
SCHMID & Partner Engineering AG	Dipole Validation Kit	D1900V2	545	01/13/2013
SCHMID & Partner Engineering AG	Dipole Validation Kit	D2450V2	747	11/11/2011
SCHMID & Partner Engineering AG	Dipole Validation Kit	D5GHzV2	1033	11/13/2011
Agilent Technologies	Signal generator	8648C	4037U03155	09/24/2011
Rohde & Schwarz	Signal generator	SMA 100A	11-9428537-0045	11/29/2011
Agilent Technologies	Power meter	E4419B	GB40202821	09/15/2011
Agilent Technologies	Power sensor	8481A	MY41095417	09/23/2011
Agilent Technologies	Power sensor	N1921A	SG45240281	05/22/2011
Agilent Technologies	Power sensor	N1921A	MY45241383	09/01/2011
Agilent Technologies	Power meter	N1911A	MY45100905	05/01/2011
Agilent Technologies	Power meter	N1911A	MY45100951	08/12/2011
Amplifier Research	Amplifier	5S1G4M3	300986	CNR
CPI Wireless Solutions	Amplifier	VZC-6961K4	SK4310E5	CNR
Agilent Technologies	Network analyzer	8753ES	US39174857	09/17/2011
Rohde & Schwarz	Base Station Simulator	CMU 200	109747	11/25/2011
Rohde & Schwarz	Bluetooth Tester	CBT	100678	11/28/2011

Table 2.1.1. Equipment list

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 25(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

2.2 Description of the test setup

Before SAR measurements are conducted, the device and the DASY equipment are setup as follows:

2.2.1 Device and base station simulator setup

- Power up the device.
- Turn on the base station simulator and set the radio channel and power to the appropriate values.
- Connect an antenna to the RF IN/OUT of the communication test set and place it close to the device.

2.2.2 DASY setup

- Turn the computer on and log on to Windows.
- Start the DASY software by clicking on the icon located on the Windows desktop.
- Mount the DAE unit and the probe. Turn on the DAE unit.
- Turn the Robot Controller on by turning the main power switch to the horizontal position
- Align the probe by clicking the ‘Align probe in light beam’ button.
- Open a file and configure the proper parameters - probe, medium, communications system etc.
- Establish a connection between the Device and the communications test instrument. Place the Device on the stand and adjust it under the phantom.
- Start SAR measurements.

3.0 ELECTRIC FIELD PROBE CALIBRATION

3.1 Probe Specifications

SAR measurements were conducted using the dosimetric probe ES3DV3/ET3DV6, designed by Schmid & Partner Engineering AG for the measurement of SAR. The probe is constructed using the thin film technique, with printed resistive lines on ceramic substrates. It has a symmetrical design with triangular core, built-in optical fibre for the surface detection system and built-in shielding against static discharge. The probe is sensitive to E-fields and thus incorporates three small dipoles arranged so that the overall response is close to isotropic. The table below summarizes the technical data for the probe.

Property	Data
Frequency range	30 MHz – 3 GHz
Linearity	±0.1 dB
Directivity (rotation around probe axis)	≤ ±0.2 dB
Directivity (rotation normal to probe axis)	±0.4 dB
Dynamic Range	5 mW/kg – 100 W/kg
Probe positioning repeatability	±0.2 mm
Spatial resolution	< 0.125 mm ³
Probe model EX3DV4 for 2.4 – 6 GHz	
Probe tip to sensor center	1.0 mm
Probe tip diameter is	2.5 mm
Probe calibration uncertainty	< 15 % for f = 2.45 to < 6.0 GHz
Probe calibration range	± 100 MHz

Table 3.1.1. Probe specifications

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 26(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

3.2 Probe calibration and measurement uncertainty

The probe had been calibrated with an accuracy better than $\pm 12\%$. The sensitivity parameters (NormX, NormY, NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe were tested. The probe calibration parameters are shown on Appendix D and below:

Calibration Parameter Determined in Head Tissue Simulating Media

f [MHz]	Validity [MHz] ^c	Permittivity	Conductivity	ConvF X	ConvF Y	ConvF Z	Alpha	Depth Unc (k=2)
900	$\pm 50 / \pm 100$	$41.5 \pm 5\%$	$0.97 \pm 5\%$	6.12	6.12	6.12	0.99	$1.07 \pm 11.0\%$
1810	$\pm 50 / \pm 100$	$40.0 \pm 5\%$	$1.40 \pm 5\%$	5.14	5.14	5.14	0.46	$1.60 \pm 11.0\%$
1950	$\pm 50 / \pm 100$	$40.0 \pm 5\%$	$1.40 \pm 5\%$	4.96	4.96	4.96	0.47	$1.57 \pm 11.0\%$
2450	$\pm 50 / \pm 100$	$39.2 \pm 5\%$	$1.80 \pm 5\%$	4.53	4.53	4.53	0.41	$1.89 \pm 11.0\%$

Calibration Parameter Determined in Body Tissue Simulating Media

f [MHz]	Validity [MHz] ^c	Permittivity	Conductivity	ConvF X	ConvF Y	ConvF Z	Alpha	Depth Unc (k=2)
900	$\pm 50 / \pm 100$	$55.0 \pm 5\%$	$1.05 \pm 5\%$	5.97	5.97	5.97	0.98	$1.12 \pm 11.0\%$
1810	$\pm 50 / \pm 100$	$53.3 \pm 5\%$	$1.52 \pm 5\%$	4.90	4.90	4.90	0.35	$2.07 \pm 11.0\%$
1950	$\pm 50 / \pm 100$	$53.3 \pm 5\%$	$1.52 \pm 5\%$	4.83	4.83	4.83	0.32	$2.45 \pm 11.0\%$
2450	$\pm 50 / \pm 100$	$52.7 \pm 5\%$	$1.95 \pm 5\%$	4.32	4.32	4.32	0.74	$1.27 \pm 11.0\%$

^c The validity of ± 100 MHz only applies for DASY v4.4 and higher.

DASY v4.7/DASY 52 has been used for measurements, therefore ± 100 MHz tolerance is valid.

Measured dielectric parameters are within $\pm 5\%$ of the probe calibration values and target values.

Expanded probe calibration uncertainty (k=2) is $< 15\%$

4.0 SAR MEASUREMENT SYSTEM VERIFICATION

Prior to conducting SAR measurements, the system was validated using the dipole validation kit and the flat section of the SAM phantom. A power level of 1.0W was applied to the dipole antenna. The verification results are in the table below with a comparison to reference values. Printouts are shown in Appendix A. All the measured parameters are within the allowed tolerances.

At above 1.5 – 2 GHz, dipoles maintain good return loss of -15 dB to -20 dB, therefore SAR measurements are limited to approximately ± 100 MHz of the probe/dipole calibration frequency.

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 27(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

4.1 System accuracy verification for head adjacent use

f (MHz)	Limits / Measured (MM/DD/YY)	SAR (W/kg) 1 g/ 10 g	Dielectric Parameters		Liquid Temp (°C)
			ϵ_r	σ [S/m]	
835	Measured (02/07/2011)	9.38/6.15	42.1	0.90	22.3
	Measured (03/07/2011)	9.47/6.18	40.5	0.90	22.5
	Measured (04/20/2011)	9.10/5.97	40.1	0.87	22.1
	Recommended Limits	9.50/6.27	41.5	0.90	N/A
1900	Measured (02/23/2011)	37.6/20.0	38.2	1.38	22.2
	Measured (02/24/2011)	39.1/20.7	38.4	1.33	22.2
	Measured (02/28/2011)	39.8/20.9	39.8	1.38	22.2
	Measured (04/18/2011)	37.5/19.7	38.2	1.38	22.4
	Recommended Limits	39.5/20.8	40.0	1.40	N/A
2450	Measured (03/03/2011)	53.4/24.5	37.5	1.86	21.8
	Recommended Limits	53.2/24.8	39.2	1.80	N/A
5200	Measured (05/24/2011)	84.4/24.4	35.3	4.80	23.0
	Recommended Limits	77.2/23.2	36.0	4.66	N/A
5500	Measured (05/24/2011)	87.4/25.1	35.0	4.87	22.8
	Recommended Limits	82.9/23.2	35.6	4.96	N/A
5800	Measured (05/24/2011)	81.9/23.4	45.8	5.00	22.9
	Recommended Limits	75.6/21.3	35.3	5.27	N/A

Table 4.1.1. RDU71CW System accuracy (validation for head adjacent use)

f (MHz)	Limits / Measured (MM/DD/YY)	SAR (W/kg) 1 g/ 10 g	Dielectric Parameters		Liquid Temp (°C)
			ϵ_r	σ [S/m]	
1900	Measured (04/27/2011)	37.8/19.7	38.2	1.38	22.3
	Measured (07/18/2011)	39.1/20.4	40.8	1.42	22.4
	Recommended Limits	39.5/20.8	40.0	1.40	N/A

Table 4.1.2. RDE71UW System accuracy (validation for head adjacent use)

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 28(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

5.0 PHANTOM DESCRIPTION

The SAM Twin Phantom, manufactured by SPEAG, was used during the SAR measurements. The phantom is made of a fibreglass shell integrated with a wooden table.

The SAM Twin Phantom is a fibreglass shell phantom with 2 mm shell thickness. It has three measurement areas:

- Left side head
- Right side head
- Flat phantom

The phantom table dimensions are: 100x50x85 cm (LxWxH). The table is intended for use with freestanding robots.

The bottom shelf contains three pair of bolts for locking the device holder in place. The device holder positions are adjusted to the standard measurement positions in the three sections. Only one device holder is necessary if two phantoms are used (e.g., for different solutions).

A white cover is provided to top the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. Free space scans of devices on the cover are possible; however the optical surface detector does not work properly at the cover surface. Place a sheet of white paper on the cover when using optical surface detection.

Liquid depth of ≥ 15 cm is maintained in the phantom for all the measurements.



Figure 5.0.1. SAM Twin Phantom

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 29(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

6.0 TISSUE DIELECTRIC PROPERTIES

6.1 Composition of tissue simulant

The composition of the brain and muscle simulating liquids are shown in the table below.

INGREDIENT	MIXTURE 800–900MHz		MIXTURE 1800–1900MHz		MIXTURE 2450 MHz		MIXTURE 5 – 6 GHz	
	Brain %	Muscle %	Brain %	Muscle %	Brain %	Muscle %	Brain %	Muscle %
Water	40.29	65.45	55.24	69.91	55.0	68.75	64	64-78
Sugar	57.90	34.31	0	0	0	0	0	0
Salt	1.38	0.62	0.31	0.13	0	0	0	0
HEC	0.24	0	0	0	0	0	0	0
Bactericide	0.18	0.10	0	0	0	0	0	0
DGBE	0	0	44.45	29.96	40.0	31.25	0	0
Triton X-100	0	0	0	0	5.0	0	0	0
Additives and Salt	0	0	0	0	0	0	3	2-3
Emulsifiers	0	0	0	0	0	0	15	9-15
Mineral Oil	0	0	0	0	0	0	18	11-18

Table 6.1.1. Tissue simulant recipe

6.1.1 Equipment

Manufacturer	Test Equipment	Model Number	Serial Number	Cal. Due Date (MM/DD/YY)
Pyrex, England	Graduated Cylinder	N/A	N/A	N/A
Pyrex, USA	Beaker	N/A	N/A	N/A
Acculab	Weight Scale	V1-1200	018WB2003	N/A
Control Company	Digital Thermometer	15-077-21	51129471	04/29/2011
Control Company	Digital Thermometer	23609-234	21352860	09/14/2011
IKA Works Inc.	Hot Plate	RC Basic	3.107433	N/A
Agilent Technologies	Network Analyzer	8753ES	US39174857	09/17/2011
Agilent Technologies	Dielectric probe kit	HP 85070C	US9936135	CNR

Table 6.1.2. Tissue simulant preparation equipment

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 30(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

6.1.2 Preparation procedure

800-900 MHz liquids

- Fill the container with **water**. Begin heating and stirring.
- Add the **Cellulose**, the **preservative substance** and the **salt**. After several hours, the liquid will become more transparent again. The container must be covered to prevent evaporation.
- Add **Sugar**. Stir it well until the sugar is sufficiently dissolved.
- Keep the liquid hot but below the boiling point for at least an hour. The container must be covered to prevent evaporation.
- Remove the container from, and turn the hotplate off and allow the liquid to cool off to room temperature prior to performing dielectric measurements.

1800-2450 MHz liquid

- Fill the container with water and place it on hotplate. Begin heating and stirring.
- Add the salt, Glycol/Triton X-100. The container must be covered to prevent evaporation.
- Keep the liquid hot enough to dissolve sugar for at least an hour. The container must be covered to prevent evaporation.
- Remove the container from, and turn the hotplate off and allow the liquid to cool off to room temperature prior to performing dielectric measurements.

6.2 Electrical parameters of the tissue simulating liquid

The tissue dielectric parameters shall be measured before a batch can be used for SAR measurements to ensure that the simulated tissue was properly made and will simulate the desired human characteristic. Limits and measured electrical parameters are shown in the table below.

Recommended limits are adopted from IEEE P1528-2003:

“ Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques”, DASY manual and from FCC Tissue Dielectric Properties web page at <http://www.fcc.gov/fcc-bin/dielec.sh>

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 31(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

f (MHz)	Tissue Type	Limits / Measured	Dielectric Parameters		Liquid Temp (°C)
			ϵ_r	σ [S/m]	
835	Head	Measured (02/07/2011)	42.1	0.90	21.8
		Measured (03/07/2011)	40.5	0.90	22.5
		Measured (04/20/2011)	40.1	0.88	22.1
		Recommended Limits	41.5	0.90	N/A
	Muscle	Measured (02/07/2011)	52.5	0.96	22.0
		Measured (03/07/2011)	52.4	1.01	22.5
		Measured (04/20/2011)	53.6	0.98	22.1
		Recommended Limits	55.2	0.97	N/A
1900	Head	Measured (02/23/2011)	38.2	1.38	22.2
		Measured (02/24/2011)	38.4	1.33	22.2
		Measured (02/28/2011)	39.8	1.38	22.2
		Measured (04/18/2011)	38.2	1.38	22.4
		Recommended Limits	40.0	1.40	N/A
	Muscle	Measured (02/23/2011)	51.4	1.54	22.0
		Measured (02/24/2011)	50.7	1.49	22.0
		Measured (02/28/2011)	51.5	1.55	22.1
		Measured (04/18/2011)	51.1	1.54	22.4
		Recommended Limits	53.3	1.52	N/A
2450	Head	Measured (03/03/2011)	37.5	1.86	21.8
		Recommended Limits	39.2	1.80	N/A
	Muscle	Measured (03/03/2011)	50.1	2.03	21.9
		Recommended Limits	52.7	1.95	N/A
5200	Head	Measured (05/24/2011)	35.3	4.83	23.0
		Recommended Limits	36.0	4.66	N/A
	Muscle	Measured (05/24/2011)	46.6	5.46	22.8
		Recommended Limits	49.0	5.30	N/A
5500	Head	Measured (05/24/2011)	35.0	4.87	22.8
		Recommended Limits	35.6	4.96	N/A
	Muscle	Measured (05/24/2011)	46.5	5.93	22.8
		Recommended Limits	48.6	5.65	N/A
5800	Head	Measured (05/24/2011)	34.7	5.00	22.9
		Recommended Limits	35.3	5.27	N/A
	Muscle	Measured (05/24/2011)	45.8	6.10	22.7
		Recommended Limits	48.2	6.00	N/A

Table 6.2.1. RDU71CW Electrical parameters of tissue simulating liquid

f (MHz)	Tissue Type	Limits / Measured	Dielectric Parameters		Liquid Temp (°C)
			ϵ_r	σ [S/m]	
1900	Head	Measured (04/27/2011)	38.2	1.38	22.3
		Measured (07/18/2011)	40.8	1.42	22.4
		Recommended Limits	40.0	1.40	N/A

Table 6.2.2. RDE71UW Electrical parameters of tissue simulating liquid

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 32(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

6.2.2 Test Configuration




Figure 6.2.1. Test configuration

6.2.3 Procedure

1. Turn NWA on and allow at least 30 minutes for warm up.
2. Mount dielectric probe kit so that interconnecting cable to NWA will not be moved during measurements or calibration.
3. Pour de-ionized water and measure water temperature ($\pm 1^\circ$).
4. Set water temperature in HP-Software (Calibration Setup).
5. Perform calibration.
6. Relative permittivity $\epsilon_r = \epsilon'$ and conductivity can be calculated from ϵ''
 $\sigma = \omega \epsilon_0 \epsilon''$
7. Measure liquid shortly after calibration.
8. Stir the liquid to be measured. Take a sample (~50ml) with a syringe from the center of the liquid container.
9. Pour the liquid into a small glass flask. Hold the syringe at the bottom of the flask to avoid air bubbles.
10. Put the dielectric probe in the glass flask. Check that there are no air bubbles in front of the opening in the dielectric probe kit.
11. Perform measurements.
12. Adjust medium parameters in DASY software for the frequencies necessary for the measurements ('Setup Config', select medium (e.g. Head 835 MHz) and press 'Option'-button.
13. Select the current medium for the frequency of the validation (e.g. Setup Medium Brain 835 MHz).

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 33(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

7.0 SAR SAFETY LIMITS

Standards/Guideline	Localized SAR Limit (W/kg) General public (uncontrolled)	Localized SAR Limits (W/kg) Workers (controlled)
ICNIRP (1998) Standard	2.0 (10g)	10.0 (10g)
IEEE C95.1 (1999) Standard	1.6 (1g)	8.0 (1g)

Table 7.0.1. SAR safety limits for Controlled / Uncontrolled environment

Human Exposure	Localized SAR Limits (W/kg) 10g, ICNIRP Standard	Localized SAR Limits (W/kg) 1g, IEEE C95.1 Standard
Spatial Average (averaged over the whole body)	0.08	0.08
Spatial Peak (averaged over any X g of tissue)	2.00	1.60
Spatial Peak (hands/wrists/feet/ankles averaged over 10 g)	4.00	4.00 (10g)

Table 7.0.2. SAR safety limits

Uncontrolled Environments are defined as locations where there is exposure of individuals who have no knowledge or control of their exposure.

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 34(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

8.0 DEVICE POSITIONING

8.1 Device holder for SAM Twin Phantom

The Device was positioned for all test configurations using the DASY4 holder. The device holder facilitates the rotation of the mounted transmitter in spherical coordinates whereby the rotation point is the ear opening. The devices can be easily, accurately and with repeatability positioned according to FCC and CENELEC specifications. The device holder can be locked at different phantom locations (left head, right head, flat phantom).




Figure 8.1.1. Device Holder

1. Put the phone in the clamp mechanism (1) and hold it straight while tightening. (Curved phones or phones with asymmetrical ear pieces should be positioned so that the earpiece is in the symmetry plane of the clamp).
2. Adjust the sliding carriage (2) to 90°. Then adjust the phone holder angle (3) until the reference line of the phone is horizontal (parallel to the flat phantom bottom). The phone reference line is defined as the front tangential line between the earpiece and the center of the device bottom (or the center of the flip hinge). For devices with parallel front and backsides, the phone holder angle (3) is 0°.
3. Place the device holder at the desired phantom section and move it securely against the positioning pins (4). The screw in front of the turning plate can be applied for correct positioning (5). (Do not tighten it too strongly).
4. Shift the phone clamp (6) so that the earpiece is exactly below the ear marking of the phantom. The phone is now correctly positioned in the holder for all standard phantom measurements, even after changing the phantom or phantom section.
5. Adjust the device position angles to the desired measurement position.

	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 35(58)	
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

6. After fixing the device angles, move the phone fixture up until the phone touches the ear marking. (The point of contact depends on the design of the device and the positioning angle).

8.2 Description of the test positioning

8.2.1 Test Positions of Device Relative to Head

The handset was tested in two test positions against the head phantom, the “cheek” position and the “tilted” position, on both left and right sides of the phantom.

The handset was tested in the above positions according to IEEE 1528- 2003 “Recommended Practice for Determining the Spatial-Peak Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques”.




Figure 8.2.1a. Handset vertical and horizontal reference lines – fixed case




Figure 8.2.1b. Handset vertical and horizontal reference lines – “clam-shell”

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 36(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

8.2.1.1 Definition of the “cheek” position

- 1) Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece, open the cover.
- 2) Define two imaginary lines on the handset: the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset: the midpoint of the width w_t of the handset at the level of the acoustic output (point A on Figures 8.2.1a and 8.2.1b), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 8.2.1a). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output. However, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 8.2.1b), especially for clamshell handsets, handsets with flip pieces, and other irregularly shaped handsets.
- 3) Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 8.2.1), such that the plane defined by the vertical center line and the horizontal center line is in a plane approximately parallel to the sagittal plane of the phantom.
- 4) Translate the handset towards the phantom along the line passing through RE and LE until the handset touches the ear.
- 5) While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is the plane normal to MB (“mouth-back”) - NF (“neck-front”) including the line MB (reference plane).
- 6) Rotate the phone around the vertical centerline until the phone (horizontal line) is symmetrical with respect to the line NF.
- 7) While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the phone contact with the ear, rotate the handset about the line NF until any point on the handset is in contact with a phantom point below the ear (cheek).




Figure 8.2.2. Phone position 1, “cheek” or “touch” position. The reference points for the right ear (RE), left ear (LE) and mouth (M), which define the reference plane for phone positioning, are indicated. The shoulders are shown for illustration purposes only.

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 37(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

8.2.1.2 Definition of the “Tilted” Position

- 1) Repeat steps 1 to 7 of 5.4.1 (in this report 8.2.1.1) to replace the device in the “cheek position.”
- 2) While maintaining the device in the reference plane (described above) and pivoting against the ear, move the device outward away from the mouth by an angle of 15 degrees, or until the antenna touches the phantom.




Figure 8.2.3. Phone position 2, “tilted position.” The reference points for the right ear (RE), left ear (LE) and mouth (M), which define the reference plane for phone positioning, are indicated. The shoulders are shown for illustration purposes only.

8.2.2 Body Holster Configuration

Body worn holsters, as shown on Figure 1.4.1, have been test with the device for FCC RF exposure compliance. The EUT was positioned in each holster case and the belt clip was placed against the flat section of the phantom. A headset was then connected to the device to simulate hands-free operation in a body worn holster configuration.

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 38(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

9.0 HIGH LEVEL EVALUATION

9.1 Maximum search

The maximum search is automatically performed after each coarse scan measurement. It is based on splines in two or three dimensions. The procedure can find the maximum for most SAR distributions even with relatively large grid spacing. After the coarse scan measurement, the probe is automatically moved to a position at the interpolated maximum. The following scan can directly use this position for reference, e.g., for a finer resolution grid or the cube evaluations.

9.2 Extrapolation

The extrapolation can be used in z-axis scans with automatic surface detection. The SAR values can be extrapolated to the inner phantom surface. The extrapolation distance is the sum of the probe sensor offset, the surface detection distance and the grid offset. The extrapolation is based on fourth order polynomial functions. The extrapolation is only available for SAR values.

9.3 Boundary correction

The correction of the probe boundary effect in the vicinity of the phantom surface is done in the standard (worst case) evaluation; the boundary effect is reduced by different weights for the lowest measured points in the extrapolation routine. The result is a slight overestimation of the extrapolated SAR values (2% to 8%) depending on the SAR distribution and gradient. The advanced evaluation makes a full compensation of the boundary effect before doing the extrapolation. This is only possible for probes with specifications on the boundary effect.

9.4 Peak search for 1g and 10g cube averaged SAR

The 1g and 10g peak evaluations are only available for the predefined cube 5x5x7 / 7x7x9 scan. The routines are verified and optimized for the grid dimensions used in these cube measurements. The measured volume of 30x30x30mm / 24x24x20 with 7.5mm / 4.0 resolution in (x,y) and 5mm / 2.5mm resolution in z axis amounts to 175 / 693 measurement points. The first procedure is an extrapolation (incl. Boundary correction) to get the points between the lowest measured plane and the surface. The next step uses 3D interpolation to get all points within the measured volume in a 1mm grid. In the last step, a 1g cube is placed numerically into the volume and its averaged SAR is calculated. This cube is then moved around until the highest averaged SAR is found. This last procedure is repeated for a 10 g cube. If the highest SAR is found at the edge of the measured volume, the system will issue a warning: higher SAR values might be found outside of the measured volume. In that case the cube measurement can be repeated, using the new interpolated maximum as the center.

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 39(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

10.0 MEASUREMENT UNCERTAINTY

DASY4 Uncertainty Budget According to IEEE P1528 [1]								
Error Description	Uncertainty value	Prob. Dist.	Div.	(c_1) 1g	(c_2) 10g	Std. Unc. (1g)	Std. Unc. (10g)	(v_i) v_{eff}
Measurement System								
Probe Calibration	±4.8 %	N	1	1	1	±4.8 %	±4.8 %	∞
Axial Isotropy	±4.7 %	R	√3	0.7	0.7	±1.9 %	±1.9 %	∞
Hemispherical Isotropy	±9.6 %	R	√3	0.7	0.7	±3.9 %	±3.9 %	∞
Boundary Effects	±1.0 %	R	√3	1	1	±0.6 %	±0.6 %	∞
Linearity	±4.7 %	R	√3	1	1	±2.7 %	±2.7 %	∞
System Detection Limits	±1.0 %	R	√3	1	1	±0.6 %	±0.6 %	∞
Readout Electronics	±1.0 %	N	1	1	1	±1.0 %	±1.0 %	∞
Response Time	±0.8 %	R	√3	1	1	±0.5 %	±0.5 %	∞
Integration Time	±2.6 %	R	√3	1	1	±1.5 %	±1.5 %	∞
RF Ambient Conditions	±3.0 %	R	√3	1	1	±1.7 %	±1.7 %	∞
Probe Positioner	±0.4 %	R	√3	1	1	±0.2 %	±0.2 %	∞
Probe Positioning	±2.9 %	R	√3	1	1	±1.7 %	±1.7 %	∞
Max. SAR Eval.	±1.0 %	R	√3	1	1	±0.6 %	±0.6 %	∞
Test Sample Related								
Device Positioning	±2.9 %	N	1	1	1	±2.9 %	±2.9 %	145
Device Holder	±3.6 %	N	1	1	1	±3.6 %	±3.6 %	5
Power Drift	±5.0 %	R	√3	1	1	±2.9 %	±2.9 %	∞
Phantom and Setup								
Phantom Uncertainty	±4.0 %	R	√3	1	1	±2.3 %	±2.3 %	∞
Liquid Conductivity (target)	±5.0 %	R	√3	0.64	0.43	±1.8 %	±1.2 %	∞
Liquid Conductivity (meas.)	±2.5 %	N	1	0.64	0.43	±1.6 %	±1.1 %	∞
Liquid Permittivity (target)	±5.0 %	R	√3	0.6	0.49	±1.7 %	±1.4 %	∞
Liquid Permittivity (meas.)	±2.5 %	N	1	0.6	0.49	±1.5 %	±1.2 %	∞
Combined Std. Uncertainty						±10.3 %	±10.0 %	330
Expanded STD Uncertainty						±20.6 %	±20.1 %	

Table 10.0.1. Worst-Case uncertainty budget for DASY4 assessed according to IEEE P1528.
Source: Schmid & Partner Engineering AG.

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 40(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

DASY5 Uncertainty Budget According to IEEE 1528/2003 [1]								
Error Description	Uncert. value	Prob. Dist.	Div.	(c_i) 1g	(c_i) 10g	Std. Unc. (1g)	Std. Unc. (10g)	(v_i) v_{eff}
Measurement System								
Probe Calibration	±5.5 %	N	1	1	1	±5.5 %	±5.5 %	∞
Axial Isotropy	±4.7 %	R	$\sqrt{3}$	0.7	0.7	±1.9 %	±1.9 %	∞
Hemispherical Isotropy	±9.6 %	R	$\sqrt{3}$	0.7	0.7	±3.9 %	±3.9 %	∞
Boundary Effects	±1.0 %	R	$\sqrt{3}$	1	1	±0.6 %	±0.6 %	∞
Linearity	±4.7 %	R	$\sqrt{3}$	1	1	±2.7 %	±2.7 %	∞
System Detection Limits	±1.0 %	R	$\sqrt{3}$	1	1	±0.6 %	±0.6 %	∞
Readout Electronics	±0.3 %	N	1	1	1	±0.3 %	±0.3 %	∞
Response Time	±0.8 %	R	$\sqrt{3}$	1	1	±0.5 %	±0.5 %	∞
Integration Time	±2.6 %	R	$\sqrt{3}$	1	1	±1.5 %	±1.5 %	∞
RF Ambient Noise	±3.0 %	R	$\sqrt{3}$	1	1	±1.7 %	±1.7 %	∞
RF Ambient Reflections	±3.0 %	R	$\sqrt{3}$	1	1	±1.7 %	±1.7 %	∞
Probe Positioner	±0.4 %	R	$\sqrt{3}$	1	1	±0.2 %	±0.2 %	∞
Probe Positioning	±2.9 %	R	$\sqrt{3}$	1	1	±1.7 %	±1.7 %	∞
Max. SAR Eval.	±1.0 %	R	$\sqrt{3}$	1	1	±0.6 %	±0.6 %	∞
Test Sample Related								
Device Positioning	±2.9 %	N	1	1	1	±2.9 %	±2.9 %	145
Device Holder	±3.6 %	N	1	1	1	±3.6 %	±3.6 %	5
Power Drift	±5.0 %	R	$\sqrt{3}$	1	1	±2.9 %	±2.9 %	∞
Phantom and Setup								
Phantom Uncertainty	±4.0 %	R	$\sqrt{3}$	1	1	±2.3 %	±2.3 %	∞
Liquid Conductivity (target)	±5.0 %	R	$\sqrt{3}$	0.64	0.43	±1.8 %	±1.2 %	∞
Liquid Conductivity (meas.)	±2.5 %	N	1	0.64	0.43	±1.6 %	±1.1 %	∞
Liquid Permittivity (target)	±5.0 %	R	$\sqrt{3}$	0.6	0.49	±1.7 %	±1.4 %	∞
Liquid Permittivity (meas.)	±2.5 %	N	1	0.6	0.49	±1.5 %	±1.2 %	∞
Combined Std. Uncertainty						±10.7 %	±10.5 %	387
Expanded STD Uncertainty						±21.4 %	±21.0 %	

**Table 10.0.2. Worst-Case uncertainty budget for DASY52 assessed according to IEEE P1528.
Source: Schmid & Partner Engineering AG.**

[1] The budget is valid for the frequency range 300MHz - 3 GHz and represents a worst-case analysis. For specific tests and configurations, the uncertainty could be considerably smaller.

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 41(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

DASY5 Uncertainty Budget for the 3 - 6 GHz range								
Error Description	Uncert. value	Prob. Dist.	Div.	(c ₁) 1g	(c ₁) 10g	Std. Unc. (1g)	Std. Unc. (10g)	(v ₁) v _{eff}
Measurement System								
Probe Calibration	±6.55 %	N	1	1	1	±6.55 %	±6.55 %	∞
Axial Isotropy	±4.7 %	R	√3	0.7	0.7	±1.9 %	±1.9 %	∞
Hemispherical Isotropy	±9.6 %	R	√3	0.7	0.7	±3.9 %	±3.9 %	∞
Boundary Effects	±2.0 %	R	√3	1	1	±1.2 %	±1.2 %	∞
Linearity	±4.7 %	R	√3	1	1	±2.7 %	±2.7 %	∞
System Detection Limits	±1.0 %	R	√3	1	1	±0.6 %	±0.6 %	∞
Readout Electronics	±0.3 %	N	1	1	1	±0.3 %	±0.3 %	∞
Response Time	±0.8 %	R	√3	1	1	±0.5 %	±0.5 %	∞
Integration Time	±2.6 %	R	√3	1	1	±1.5 %	±1.5 %	∞
RF Ambient Noise	±3.0 %	R	√3	1	1	±1.7 %	±1.7 %	∞
RF Ambient Reflections	±3.0 %	R	√3	1	1	±1.7 %	±1.7 %	∞
Probe Positioner	±0.8 %	R	√3	1	1	±0.5 %	±0.5 %	∞
Probe Positioning	±9.9 %	R	√3	1	1	±5.7 %	±5.7 %	∞
Max. SAR Eval.	±4.0 %	R	√3	1	1	±2.3 %	±2.3 %	∞
Test Sample Related								
Device Positioning	±2.9 %	N	1	1	1	±2.9 %	±2.9 %	145
Device Holder	±3.6 %	N	1	1	1	±3.6 %	±3.6 %	5
Power Drift	±5.0 %	R	√3	1	1	±2.9 %	±2.9 %	∞
Phantom and Setup								
Phantom Uncertainty	±4.0 %	R	√3	1	1	±2.3 %	±2.3 %	∞
Liquid Conductivity (target)	±5.0 %	R	√3	0.64	0.43	±1.8 %	±1.2 %	∞
Liquid Conductivity (meas.)	±2.5 %	N	1	0.64	0.43	±1.6 %	±1.1 %	∞
Liquid Permittivity (target)	±5.0 %	R	√3	0.6	0.49	±1.7 %	±1.4 %	∞
Liquid Permittivity (meas.)	±2.5 %	N	1	0.6	0.49	±1.5 %	±1.2 %	∞
Combined Std. Uncertainty						±12.8 %	±12.6 %	330
Expanded STD Uncertainty						±25.6 %	±25.2 %	

**Table 10.0.3. Worst-Case uncertainty budget for DASY52 assessed according to IEEE P1528.
Source: Schmid & Partner Engineering AG.**

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 42(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

11.0 TEST RESULTS

11.1 SAR Measurement results at highest power measured against the head

Test Position	Mode	f (MHz)	Cond. Output Power (dBm)	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
Right Head Cheek	4-slots GSM/EDGE 850 MHz	824.2					
		836.8	26.8	22.1	0.30	0.17	0.30
		848.8					
Right Head Cheek	3-slots GSM/EDGE 850 MHz	824.2					
		836.8	29.1	22.2	0.39	0.17	0.39
		848.8					
Right Head Cheek	2-slots GSM/EDGE 850 MHz	824.2					
		836.8	30.4	22.3	0.30	0.14	0.30
		848.8					
Right Head 15° Tilt	3-slots GSM/EDGE 850 MHz	824.2					
		836.8	29.1	22.1	0.30	0.28	0.30
		848.8					
Right Head Cheek	1-slot GSM 850 MHz	824.2					
		836.8	32.8	22.2	0.34	0.32	0.34
		848.8					
Left Head Cheek	3-slots GSM/EDGE 850 MHz	824.2					
		836.8	29.1	22.1	0.41	-0.17	0.41
		848.8					
Left Head 15° Tilt	3-slots GSM/EDGE 850 MHz	824.2					
		836.8	29.1	22.0	0.28	-0.14	0.28
		848.8					

Table 11.1.1. RDU71CW SAR results for GSM/EDGE 850 head configuration

Note 1: If the power drift is ≤ -0.200 dB, the extrapolated SAR is calculated using the formula:

$$\text{Extrapolated SAR} = (\text{Measured SAR}) * 10^{(|\text{Power Drift (dB)}| / 10)}$$

Note 2: Only Middle channel was tested when 1g Average SAR <0.8 W/Kg or 3dB lower than the limit.

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 43(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

Test Position	Mode	f (MHz)	Cond. Output Power (dBm)	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
Right Head Cheek	3-slots GSM/EDGE 850 MHz	824.2					
		836.8	29.1	22.3	0.51	0.75	0.51
		848.8					
Left Head Cheek	3-slots GSM/EDGE 850 MHz	824.2					
		836.8	29.1	22.2	0.39	0.57	0.39
		848.8					

Table 11.1.2. RDU71CW Rev3 SAR results for GSM/EDGE 850 head configuration

Test Position	Mode	f (MHz)	Peaks	Cond. Output Power (dBm)	Liquid Temp. (°C)	SAR, averaged over 1 g		
						Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
Right Head Cheek	CDMA 800 MHz	824.70						
		836.52		24.7	22.2	0.54	-0.24	0.57
		848.52						
Right Head 15° Tilt	CDMA 800 MHz	824.70						
		836.52		24.7	22.2	0.35	0.05	0.35
		848.52						
Left Head Cheek	CDMA 800 MHz	824.70						
		836.52		24.7	22.1	0.49	-0.23	0.52
		848.52						
Left Head 15° Tilt	CDMA 800 MHz	824.70						
		836.52		24.7	22.1	0.33	0.05	0.33
		848.52						
Right Head Cheek	CDMA 1900 MHz	1851.25		23.7	21.9	1.10	-0.07	1.10
		1880.00		23.8	22.0	1.12	-0.17	1.12
		1908.50		23.8	21.9	1.05	0.13	1.05
Right Head 15° Tilt	CDMA 1900 MHz	1851.25						
		1880.00		23.8	21.9	0.44	-0.15	0.44
		1908.50						
Left Head Cheek	CDMA 1900 MHz	1851.25	Peak 1	23.7	21.8	1.15	-0.16	1.15
		1851.25	Peak 2	23.7	21.8	1.15	-0.04	1.15
		1880.00		23.8	21.9	1.29	-0.28	1.38
		1908.50		23.8	22.0	1.19	-0.06	1.19
Left Head 15° Tilt	CDMA 1900 MHz	1851.25						
		1880.00		23.8	22.1	0.56	-0.05	0.56
		1908.50						

Table 11.1.3. RDU71CW SAR results for CDMA 800/1900 for head configuration

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 44(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

Test Position	Mode	f (MHz)	Cond. Output Power (dBm)	Peaks	Liquid Temp. (°C)	SAR, averaged over 1 g		
						Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
Right Head Cheek	CDMA 800 MHz	824.70						
		836.52	24.7		22.3	0.50	-0.77	0.60
		848.52						
Left Head Cheek	CDMA 800 MHz	824.70						
		836.52	24.7	Peak 1	22.2	0.53	0.11	0.53
		836.52	24.7	Peak 2	22.2	0.51	0.07	0.51
		848.52						

Table 11.1.4. RDU71CW Rev3 Head SAR results for CDMA 800/1900 for head configuration

Test Position	Mode	f (MHz)	Cond. Output Power (dBm)	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
Right Head Cheek	4-slots GSM/EDGE 1900 MHz	1850.2					
		1880.0	25.6	21.7	0.90	0.26	0.90
		1909.8					
Right Head Cheek	3-slots GSM/EDGE 1900 MHz	1850.2					
		1880.0	26.2	21.8	0.85	-0.15	0.85
		1909.8					
Right Head Cheek	2-slots GSM/EDGE 1900 MHz	1850.2	28.9	21.7	1.04	-0.07	1.04
		1880.0	29.0	21.8	1.12	0.19	1.12
		1909.8	28.8	21.9	1.08	0.12	1.08
Right Head 15° Tilt	2-slots GSM/EDGE 1900 MHz	1850.2					
		1880.0	29.0	21.9	0.35	-0.06	0.35
		1909.8					
Right Head Cheek	1-slot GSM 1900 MHz	1850.2					
		1880.0	29.7	22.0	0.84	0.04	0.84
		1909.8					
Left Head Cheek	2-slots GSM/EDGE 1900 MHz	1850.2	28.9	21.9	0.85	0.12	0.85
		1880.0	29.0	21.7	0.91	0.09	0.91
		1909.8	28.8	21.9	0.82	-0.11	0.82
Left Head 15° Tilt	2-slots GSM/EDGE 1900 MHz	1850.2					
		1880.0	29.0	21.8	0.53	0.11	0.53
		1909.8					

Table 11.1.5. RDU71CW SAR results for GSM/EDGE 1900 head configuration

This report shall NOT be reproduced except in full without the written consent of RIM Testing Services
Copyright 2005-2011, RIM Testing Services, A division of Research In Motion Limited

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 45(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

Test Position	Mode	f (MHz)	Cond. Output Power (dBm)	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
Right Head Cheek	2-slots GSM/EDGE 1900 MHz	1850.2					
		1880.0	29.0	22.3	0.77	0.19	0.77
		1909.8					
Left Head Cheek	2-slots GSM/EDGE 1900 MHz	1850.2					
		1880.0	29.0	22.1	0.66	-0.14	0.66
		1909.8					

Table 11.1.6. RDU71CW Rev3 SAR results for GSM/EDGE 1900 head configuration

Test Position	Mode	f (MHz)	Cond. Output Power (dBm)	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
Right Head Cheek	802.11 b 2450 MHz	2412					
		2437	19.0	21.8	0.21	0.04	0.21
		2462					
Right Head 15° Tilt	802.11 b 2450 MHz	2412					
		2437	19.0	21.8	0.18	-0.07	0.18
		2462					
Left Head Cheek	802.11 b 2450 MHz	2412					
		2437	19.0	21.7	0.52	0.11	0.52
		2462					
Left Head 15° Tilt	802.11 b 2450 MHz	2412					
		2437	19.0	21.7	0.22	-0.04	0.22
		2462					

Table 11.1.7. RDU71CW SAR results for WiFi/WLAN/802.11b head configuration

***Note:** Tested only highest output power channel

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 46(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

Test Position	Mode	f (MHz)	Cond. Output Power (dBm)	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
Right Head Cheek	802.11 a 5180-5805 MHz	5180	11.05	22.5	0.01	0.60	0.01
		5240					
		5260	12.00	22.5	0.01	0.64	0.01
		5320					
		5520	14.12	22.2	0.03	0.42	0.03
		5580					
		5680					
		5745	13.35	22.1	0.18	-0.12	0.18
		5805					
Right Head 15° Tilt	802.11 a 5180-5805 MHz	5745	13.35	22.0	0.00	-0.45	0.00
Left Head Cheek	802.11 a 5180-5805 MHz	5180	11.05	22.5	0.04	0.43	0.04
		5240					
		5260	12.00	22.3	0.04	0.29	0.04
		5320					
		5520	14.12	22.3	0.05	1.56	0.05
		5580					
		5680					
		5745	13.35	22.2	0.04	0.85	0.04
		5805					
Left Head 15° Tilt	802.11 a 5180-5805 MHz	5520	14.12	22.2	0.04	3.54	0.04

Table 11.1.8. RDU71CW Rev4 SAR results for 802.11a head configuration

***Note:** Tested only highest output power channel per band

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 47(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

Test Position	Mode	f (MHz)	Cond. Output Power (dBm)	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
Right Head Cheek	Bluetooth 2450 MHz	2402					
		2441	10.67	21.8	0.00	1.36	0.00
		2480					
Right Head 15° Tilt	Bluetooth 2450 MHz	2402					
		2441	10.67	22.0	0.00	0.32	0.00
		2480					
Left Head Cheek	Bluetooth 2450 MHz	2402					
		2441	10.67	21.9	0.01	0.98	0.01
		2480					
Left Head 15° Tilt	Bluetooth 2450 MHz	2402					
		2441	10.67	22.0	0.00	0.97	0.00
		2480					

Table 11.1.9. RDU71CW SAR results for Bluetooth head configuration

Test Position	Mode	f (MHz)	Cond. Output Power (dBm)	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
Right Head Cheek	2-slots GSM/EDGE 1900 MHz	1850.2					
		1880.0	29.7	22.4	0.87	0.42	0.87
		1909.8					
Right Head Cheek	1-slot GSM 1900 MHz	1850.2	31.3	22.4	0.57	0.00	0.57
		1880.0					
		1909.8					

Table 11.1.10. RDE71UW Rev3 SAR results for GSM/EDGE 1900 head configuration

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 48(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

Test Position	Mode	f (MHz)	Cond. Output Power (dBm)	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
Right Head Cheek	WCDMA FDD V 850 MHz	826.4					
		836.4	24.56	21.7	0.59	0.15	0.59
		846.6					
Right Head 15° Tilt	WCDMA FDD V 850 MHz	826.4					
		836.4	24.56	21.8	0.35	0.28	0.35
		846.6					
Left Head Cheek	WCDMA FDD V 850 MHz	826.4					
		836.4	24.56	21.8	0.52	-0.26	0.55
		846.6					
Left Head 15° Tilt	WCDMA FDD V 850 MHz	826.4					
		836.4	24.56	21.9	0.36	0.13	0.36
		846.6					

Table 11.1.11. RDE71UW SAR results for WCDMA FDD V head configuration

Test Position	Mode	f (MHz)	Peaks	Cond. Output Power (dBm)	Liquid Temp. (°C)	SAR, averaged over 1 g		
						Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
Right Head Cheek	WCDMA FDD V 850 MHz	826.4						
		836.4		24.56	22.4	0.50	-0.13	0.50
		846.6						
Left Head Cheek	WCDMA FDD V 850 MHz	826.4						
		836.4	Peak 1	24.56	22.2	0.55	-0.44	0.61
		836.4	Peak 2	24.56	22.2	0.56	-0.54	0.63
		846.6						

Table 11.1.12. RDE71UW Rev3 SAR results for WCDMA FDD V head configuration

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 49(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

Test Position	Mode	f (MHz)	Cond. Output Power (dBm)	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
Right Head Cheek	WCDMA FDD II 1900 MHz	1852.4					
		1880	23.33	22.2	0.78	0.01	0.78
		1907.6					
Right Head 15° Tilt	WCDMA FDD II 1900 MHz	1852.4					
		1880	23.33	22.1	0.34	-0.1	0.34
		1907.6					
Left Head Cheek	WCDMA FDD II 1900 MHz	1852.4	23.30	22.0	1.12	-0.28	1.19
		1880	23.33	22.0	1.08	-0.09	1.08
		1907.6	23.35	22.1	0.96	0.14	0.96
Left Head 15° Tilt	WCDMA FDD II 1900 MHz	1852.4					
		1880	23.33	22.0	0.32	0.07	0.32
		1907.6					

Table 11.1.13. RDE71UW SAR results for WCDMA FDD II head configuration

Test Position	Mode	f (MHz)	Peaks	Cond. Output Power (dBm)	Liquid Temp. (°C)	SAR, averaged over 1 g		
						Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
Right Head Cheek	WCDMA FDD II 1900 MHz	1852.4		23.30	22.4	0.92	0.01	0.92
		1880		23.33	22.2	1.13	0.04	1.13
		1907.6		23.35	22.4	0.96	-0.03	0.96
Left Head Cheek	WCDMA FDD II 1900 MHz	1852.4	Peak 1	23.30	22.1	0.99	0.01	0.99
		1852.4	Peak 2	23.30	22.1	0.99	-0.07	0.99
		1880	Peak 1	23.33	22.3	1.08	0.23	1.08
		1880	Peak 2	23.33	22.3	1.10	0.27	1.10
		1907.6	Peak 1	23.35	22.3	1.03	0.06	1.03
		1907.6	Peak 2	23.35	22.3	0.67	0.02	0.67

Table 11.1.14. RDE71UW Rev3 SAR results for WCDMA FDD II head configuration

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 50(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

11.2 SAR measurement results at highest power measured against the body using accessories

Mode	Freq. (MHz)	Cond. Power (dBm)	Holster type / device configuration	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
2-slots GPRS 850 MHz	836.8	30.1	15mm Spacer, back side facing phantom	22.0	0.44	-0.13	0.44
	836.8	30.1	15mm Spacer, front side facing phantom	22.1	0.37	-0.02	0.37
	836.8	30.1	Vertical Holster, back side facing phantom	22.1	0.41	0.03	0.41
	836.8	30.1	15mm Spacer, headset, back side facing phantom	22.0	0.40	-0.12	0.40
3-slots GPRS 850 MHz	836.8	29.1	15mm Spacer, back side facing phantom	21.9	0.60	-0.04	0.60
4-slots GPRS 850 MHz	836.8	26.8	15mm Spacer, back side facing phantom	21.9	0.47	0.32	0.47

Table 11.2.1. RDU71CW SAR results for GPRS850 body-worn configurations

Note 1: If the power drift is ≤ -0.200 dB, the extrapolated SAR is calculated using the formula:

$$\text{Extrapolated SAR} = (\text{Measured SAR}) * 10^{(|\text{Power Drift (dB)}| / 10)}$$

Note 2: Only Middle channel was tested when 1g Average SAR < 0.8 W/Kg or 3dB lower than the limit.

Mode	Freq. (MHz)	Cond. Power (dBm)	Holster type / device configuration	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
3-slots GPRS 850 MHz	836.8	29.1	15mm Spacer, back side facing phantom	22.3	0.66	-0.50	0.74

Table 11.2.2. RDU71CW Rev3 SAR results for GPRS850 body-worn configurations

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 51(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

Mode	Freq. (MHz)	Cond. Power (dBm)	Holster type / device configuration	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
CDMA 800 MHz	836.5	24.7	15mm Spacer, back side facing phantom	22.0	0.78	-0.06	0.78
	836.5	24.7	15mm Spacer, back side facing phantom	21.9	0.45	0.24	0.45
	836.5	24.7	15mm Spacer, headset, back side facing phantom	21.9	0.78	-0.08	0.78
CDMA 1900 MHz	1880.0	23.8	15mm Spacer, back side facing phantom	22.4	0.74	-0.10	0.74
	1880.0	23.8	15mm Spacer, front side facing phantom	22.3	0.50	-0.01	0.50
	1880.0	23.8	Vertical Holster, back side facing phantom	22.3	0.51	-0.09	0.51
	1880.0	23.8	15mm Spacer, headset, back side facing phantom	22.2	0.72	0.02	0.72

Table 11.2.3. RDU71CW SAR results for CDMA 800/1900 body-worn configurations

Mode	Freq. (MHz)	Cond. Power (dBm)	Peak	Holster type / device configuration	Liquid Temp. (°C)	SAR, averaged over 1 g		
						Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
CDMA 800 MHz	836.5	24.7	Peak 1	15mm Spacer, back side facing phantom	22.1	0.78	-0.20	0.78
	836.5	24.7	Peak 2	15mm Spacer, back side facing phantom	22.1	0.78	-0.17	0.78
	836.5	24.7		Vertical Holster, back side facing phantom	22.3	0.64	-0.04	0.64

Table 11.2.4. RDU71CW Rev3 SAR results for CDMA 800/1900 body-worn configurations

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 52(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

Mode	Freq. (MHz)	Cond. Power (dBm)	Holster type / device configuration	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
2-Slots GPRS 1900 MHz	1880.0	29.0	15mm Spacer, back side facing phantom	22.0	0.58	-0.12	0.58
	1880.0	29.0	Vertical Holster, back side facing phantom	22.1	0.47	0.12	0.47
	1880.0	29.0	15mm Spacer, front side facing phantom	22.2	0.35	-0.15	0.35
	1880.0	29.0	15mm Spacer, headset #1, back side facing phantom	22.1	0.59	-0.10	0.59
	1880.0	29.0	15mm Spacer, headset #2, back side facing phantom	22.0	0.59	0.22	0.59
	1880.0	29.0	15mm Spacer, headset #3, back side facing phantom	21.9	0.62	0.04	0.62
3-Slots GPRS 1900 MHz	1880.0	26.2	15mm Spacer, headset #3, back side facing phantom	22.0	0.43	-0.33	0.46
4-Slots GPRS 1900 MHz	1880.0	25.6	15mm Spacer, headset #3, back side facing phantom	22.0	0.50	-0.10	0.50

Table 11.2.5. RDU71CW SAR results for GPRS 1900 body-worn configurations

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 53(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

Mode	Freq. (MHz)	Cond. Power (dBm)	Holster type / device configuration	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
802.11b/WLAN 2450 MHz	2437	19.0	15mm Spacer, back side facing phantom	21.9	0.49	2.88	0.49
	2437	19.0	Vertical Holster, back side facing phantom	21.9	0.48	-0.38	0.52
	2437	19.0	Vertical Holster, front side facing phantom	21.8	0.04	-0.23	0.04
	2437	19.0	Vertical Holster, headset, back side facing phantom	21.7	0.46	-0.19	0.46

Table 11.2.6. RDU71CW SAR results for Wi-Fi/WLAN/802.11b body-worn configurations

***Note:** Tested only highest output power channel

Mode	Freq. (MHz)	Cond. Power (dBm)	Holster type / device configuration	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
Bluetooth 2450 MHz	2441	10.5	15mm Spacer, back side facing phantom	21.9	0.00	-0.19	0.00
	2441	10.5	Vertical Holster, back side facing phantom	21.9	0.00	0.61	0.00
	2441	10.5	Vertical Holster, front side facing phantom	21.8	0.00	1.97	0.00
	2441	10.5	Vertical Holster, headset, back side facing phantom	21.8	0.00	0.88	0.00

Table 11.2.7. RDU71CW SAR results for Bluetooth body-worn configurations

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 54(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

Mode	Freq. (MHz)	Cond. Power (dBm)	Holster type / device configuration	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
802.11 a 5180-5805 MHz	5180	11.05	No holster, 15 mm, back side facing	22.4	0.08	-0.17	0.08
	5240		No holster, 15 mm, back side facing				
	5260	12.00	No holster, 15 mm, back side facing	22.1	0.10	0.23	0.10
	5320		No holster, 15 mm, back side facing				
	5520	14.12	No holster, 15 mm, back side facing, 1 st hotspot	21.9	0.12	-0.11	0.12
	5580		No holster, 15 mm, back side facing				
	5680		No holster, 15 mm, back side facing				
	5745	13.35	No holster, 15 mm, back side facing	22.0	0.08	0.03	0.08
	5805		No holster, 15 mm, back side facing				
	5520	14.12	Vertical Holster, back side facing	22.1	0.10	-0.20	0.10
	5520	14.12	No holster, 15 mm, front side facing	22.2	0.01	1.65	0.01
	5520	14.12	No holster, 15 mm, back side facing, headset	22.2	0.12	0.09	0.12

Table 11.2.8. RDU71CW SAR results for 802.11a body-worn configurations

***Note:** Tested only highest output power channel per band

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 55(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

Mode	Freq. (MHz)	Cond. Power (dBm)	Holster type / device configuration	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
WCDMA FDD V 850 MHz	836.4	24.56	No Holster, back side 15mm away	21.8	0.70	0.07	0.70
	836.4	24.56	Vertical Holster, back side facing	21.8	0.62	-0.06	0.62
	836.4	24.56	No Holster, front side 15mm away	21.7	0.42	0.33	0.42
	836.4	24.56	No Holster, HS#1, back side 15mm away	21.6	0.66	0.10	0.66
	836.4	24.56	No Holster, HS#2, back side 15mm away	21.8	0.59	0.17	0.59
	836.4	24.56	No Holster, HS#3, back side 15mm away	21.8	0.61	0.20	0.61

Table 11.2.9. RDE71UW SAR results for WCDMA FDD V body-worn configurations

Mode	Freq. (MHz)	Cond. Power (dBm)	Holster type / device configuration	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
WCDMA FDD V 850 MHz	836.4	24.56	No Holster, back side 15mm away	22.3	0.75	-0.13	0.75
	836.4	24.56	No Holster, back side 15mm away	22.3	0.76	-0.16	0.76

Table 11.2.10. RDE71UW Rev3 SAR results for WCDMA FDD V body-worn configurations

Mode	Freq. (MHz)	Cond. Power (dBm)	Holster type / device configuration	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
WCDMA FDD II 1900 MHz	1852.4	23.30	No Holster, back side 15mm away	21.9	0.81	0.06	0.81
	1880.0	23.33	No Holster, back side 15mm away	22.0	1.03	0.02	1.03
	1907.6	23.35	No Holster, back side 15mm away	22.1	1.00	0.09	1.00
	1880.0	23.33	Vertical Holster, back side facing	21.9	0.60	0.74	0.60
	1880.0	23.33	No Holster, front side 15mm away	22.1	0.49	0.06	0.49
	1880.0	23.33	No Holster, headset 1, back side 15mm away	22.1	1.01	0.04	1.01

Table 11.2.11. RDE71UW SAR results for WCDMA FDD II body-worn configurations

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 56(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

Mode	Freq. (MHz)	Cond. Power (dBm)	Holster type / device configuration	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
WCDMA FDD II 1900 MHz	1880.0	23.33	No Holster, back side 15mm away	22.2	0.61	-0.07	0.61

Table 11.2.12. RDE71UW Rev3 SAR results for WCDMA FDD II body-worn configurations

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 57(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

12.0 REFERENCES

- [1] IEEE 1528-2003: Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.
- [2] EN 50360: 2001, Product standard to demonstrate the compliance of mobile phones with the basic restrictions related to human exposure to electromagnetic fields (300 MHz – 3 GHz)
- [3] ICNIRP, International Commission on Non-Ionizing Radiation Protection (2009), Guidelines for limiting exposure in time-varying electric, magnetic, and electromagnetic fields (up to 300 GHz).
- [4] Council Recommendation 1999/519/EC of July 1999 on the limitation of exposure of the general public to electromagnetic fields (0 Hz to 300 GHz)
- [5] IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields – RF and Microwave.
- [6] IEEE C95.1-2005, IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.
- [7] FCC OET Bulletin 65 (Edition 97-01) Supplement C (Edition 01-01), Evaluating Compliance with FCC Guidelines for Human Exposure to Radio Frequency Electromagnetic Fields.
- [8] FCC 96-326, Guidelines for Evaluating the Environmental Effects of Radio-Frequency Radiation.
- [9] DASY 4/5 DOSIMETRIC ASSESSMENT SYSTEM SOFTWARE MANUAL, Schmid & Partner Engineering AG.
- [10] Health Canada, Safety Code 6, 2009: Limits of Human Exposure to Radiofrequency Electromagnetic Fields in the Frequency range from 3 kHz to 300 GHz.
- [11] RSS-102, issue 4-2010: Evaluation Procedure for Mobile and Portable Radio Transmitters with respect to Health Canada's Safety Code 6 for Exposure of Humans to Radio Frequency Fields.
- [12] IEC 62209-1, First Edition-2005: Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Human models, instrumentation, and procedures –Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)
- [13] FCC OET SAR Measurement Requirements for 3 – 6 GHz, October, 2006.
- [14] FCC OET SAR Measurement Procedures for 802.11 a/b/g Transmitters, May, 2007.
- [15] FCC OET SAR Evaluation Considerations for Handsets with Multiple Transmitters & Antennas, September, 2008.

		Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RDU71CW/RDE71UW		Page 58(58)
Author Data Andrew Becker	Dates of Test Feb 7 – May 25, July 18, 2011	Test Report No RTS-3933-1105-11A RTS-2580-1106-03 Rev2	FCC ID: L6ARDU70CW L6ARDE70UW	IC ID 2503A-RDU70CW 2503A-RDE70UW

[16] FCC OET SAR Test Reduction Procedure for GSM/GPRS/EDGE, December, 2008.

[17] FCC OET SAR Probe Calibration and System Verification Considerations for Measurements at 150 MHz – 3 GHz, January, 2007.

[18] FCC OET RF Exposure Procedures for Mobile and Portable Devices, and Equipment Authorization Policies, November, 2009.

[19] FCC OET SAR Measurements Procedures for 3G Devices, October, 2007.

[20] Dipole Requirements for SAR System Validation and Verification, November, 2009.

[21] IEC 62209-2, Edition 1.0-2010: Human exposure to radio frequency fields from hand-held and body-mount wireless communication devices – Human Models, instrumentation, and procedures - part 2 - procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz).