



# Test Report

**Report No.:** MTi210107014-06E1

**Date of issue:** Aug. 12, 2021

**Applicant:** Koss Corporation

**Product name:** Bluetooth Earbuds

**Model(s):** KOSS TWS150i

**FCC ID:** L76-KSTWS520I

Shenzhen Microtest Co., Ltd.  
<http://www.mtitest.com>

## Instructions

1. The report shall not be partially reproduced without the written consent of the laboratory;
2. The test results of this report are only responsible for the samples submitted;
3. This report is invalid without the seal and signature of the laboratory;
4. This report is invalid if transferred, altered or tampered with in any form without authorization;
5. Any objection to this report shall be submitted to the laboratory within 15 days from the date of receipt of the report.



## Table of Contents

|          |                                                 |           |
|----------|-------------------------------------------------|-----------|
| <b>1</b> | <b>GENERAL INFORMATION .....</b>                | <b>6</b>  |
| 1.1      | DESCRIPTION OF EUT .....                        | 6         |
| 1.2      | OPERATION CHANNEL LIST .....                    | 6         |
| 1.3      | TEST CHANNEL LIST .....                         | 7         |
| 1.4      | ANCILLARY EQUIPMENT LIST .....                  | 7         |
| 1.5      | DESCRIPTION OF SUPPORT UNITS .....              | 7         |
| <b>2</b> | <b>SUMMARY OF TEST RESULTS .....</b>            | <b>8</b>  |
| <b>3</b> | <b>TEST FACILITIES AND ACCREDITATIONS .....</b> | <b>9</b>  |
| 3.1      | TEST LABORATORY .....                           | 9         |
| 3.2      | ENVIRONMENTAL CONDITIONS .....                  | 9         |
| 3.3      | MEASUREMENT UNCERTAINTY .....                   | 9         |
| 3.4      | TEST SOFTWARE .....                             | 9         |
| <b>4</b> | <b>EQUIPMENT LIST .....</b>                     | <b>10</b> |
| <b>5</b> | <b>TEST RESULT .....</b>                        | <b>11</b> |
| 5.1      | ANTENNA REQUIREMENT .....                       | 11        |
| 5.1.1    | Standard requirement .....                      | 11        |
| 5.1.2    | EUT antenna .....                               | 11        |
| 5.2      | PEAK OUTPUT POWER .....                         | 12        |
| 5.2.1    | Limit .....                                     | 12        |
| 5.2.2    | Test setup .....                                | 12        |
| 5.2.3    | Test procedure .....                            | 12        |
| 5.2.4    | Test results .....                              | 12        |
| 5.3      | CONDUCTED EMISSION .....                        | 19        |
| 5.3.1    | Limits .....                                    | 19        |
| 5.3.2    | Test setup .....                                | 19        |
| 5.3.3    | Test procedure .....                            | 20        |
| 5.3.4    | Test results .....                              | 20        |
| 5.4      | RADIATED SPURIOUS EMISSION .....                | 21        |
| 5.4.1    | Limits .....                                    | 21        |
| 5.4.2    | Test setup .....                                | 22        |
| 5.4.3    | Test procedure .....                            | 23        |
| 5.4.4    | Test results .....                              | 24        |
| 5.4.5    | Band edge – radiated .....                      | 28        |
| 5.5      | 20dB OCCUPIED CHANNEL BANDWIDTH .....           | 29        |
| 5.5.1    | Limit .....                                     | 29        |
| 5.5.2    | Test setup .....                                | 29        |
| 5.5.3    | Test procedure .....                            | 29        |
| 5.5.4    | Test results .....                              | 29        |
| 5.6      | CARRIER FREQUENCY SEPARATION .....              | 36        |
| 5.6.1    | Limit .....                                     | 36        |
| 5.6.2    | Test setup .....                                | 36        |
| 5.6.3    | Test procedure .....                            | 36        |
| 5.6.4    | Test results .....                              | 36        |
| 5.7      | HOPPING CHANNEL .....                           | 42        |
| 5.7.1    | Limit .....                                     | 42        |
| 5.7.2    | Test setup .....                                | 42        |
| 5.7.3    | Test procedure .....                            | 42        |
| 5.7.4    | Test results .....                              | 42        |
| 5.8      | DWELL TIME .....                                | 45        |



|                                            |                                       |           |
|--------------------------------------------|---------------------------------------|-----------|
| 5.8.1                                      | Limit .....                           | 45        |
| 5.8.2                                      | Test setup .....                      | 45        |
| 5.8.3                                      | Test procedure .....                  | 45        |
| 5.8.4                                      | Test results .....                    | 45        |
| 5.9                                        | CONDUCTED BAND EDGE .....             | 52        |
| 5.9.1                                      | Limit .....                           | 52        |
| 5.9.2                                      | Test setup .....                      | 52        |
| 5.9.3                                      | Test procedure .....                  | 52        |
| 5.9.4                                      | Test results .....                    | 52        |
| 5.10                                       | SPURIOUS RF CONDUCTED EMISSIONS ..... | 59        |
| 5.10.1                                     | Limit .....                           | 59        |
| 5.10.2                                     | Measuring instruments .....           | 59        |
| 5.10.3                                     | Test setup .....                      | 59        |
| 5.10.4                                     | Test procedure .....                  | 59        |
| 5.10.5                                     | Test results .....                    | 59        |
| <b>PHOTOGRAPHS OF THE TEST SETUP .....</b> |                                       | <b>62</b> |
| <b>PHOTOGRAPHS OF THE EUT .....</b>        |                                       | <b>63</b> |



## TEST RESULT CERTIFICATION

Applicant's name .....: Koss Corporation

Address .....: 4129 N Port Washington Ave Milwaukee, WI 53212 USA

Manufacturer's Name .....: Dongguan Cannice Precision Manufacturing Co., Ltd.

Address .....: Buiding2, No.21, Nange West Road Daojiao Town Dongguan  
Guangdong 523750 China

### Product description

Product name .....: Bluetooth Earbuds

Trademark .....: N/A

Model Name .....: KOSS TWS150i

Serial Model .....: N/A

Standards .....: FCC Part 15.247

Test procedure .....: ANSI C63.10-2013

### Date of Test

Date (s) of performance of tests ..... : 28 Jan. 2021 ~ 27 Feb. 2021

Test Result ..... : Pass

This device described above has been tested by Shenzhen Microtest Co., Ltd. and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

Testing Engineer

:

(Danny Xu)

Technical Manager

:

(Leo Su)

Authorized Signatory

:

(Tom Xue)



## 1 General Information

### 1.1 Description of EUT

|                              |                                                                   |
|------------------------------|-------------------------------------------------------------------|
| Product name:                | Bluetooth Earbuds                                                 |
| Model name:                  | KOSS TWS150i                                                      |
| Serial model:                | N/A                                                               |
| Difference in series models: | N/A                                                               |
| Operation frequency:         | 2402-2480MHz                                                      |
| Modulation type:             | GFSK, $\pi/4$ -DQPSK, 8DPSK                                       |
| Bit Rate of transmitter:     | 1 Mbps, 2Mbps, 3Mbps                                              |
| Antenna type:                | FPC Antenna                                                       |
| Antenna gain:                | -1.46dBi                                                          |
| Max. output power:           | 8.826dBm                                                          |
| Hardware version:            | V0E                                                               |
| Software version:            | V0G                                                               |
| Power source:                | DC 3.7V from battery                                              |
| Adapter information:         | N/A                                                               |
| Battery:                     | Charging box: DC 3.7V 500mAh<br>Bluetooth earphone: DC 3.7V 60mAh |
| Serial number:               | MTi210107014-06-S0001                                             |

### 1.2 Operation channel list

| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|---------|-----------------|
| 00      | 2402            | 27      | 2429            | 54      | 2456            |
| 01      | 2403            | 28      | 2430            | 55      | 2457            |
| 02      | 2404            | 29      | 2431            | 56      | 2458            |
| 03      | 2405            | 30      | 2432            | 57      | 2459            |
| 04      | 2406            | 31      | 2433            | 58      | 2460            |
| 05      | 2407            | 32      | 2434            | 59      | 2461            |
| 06      | 2408            | 33      | 2435            | 60      | 2462            |
| 07      | 2409            | 34      | 2436            | 61      | 2463            |



|    |      |    |      |    |      |
|----|------|----|------|----|------|
| 08 | 2410 | 35 | 2437 | 62 | 2464 |
| 09 | 2411 | 36 | 2438 | 63 | 2465 |
| 10 | 2412 | 37 | 2439 | 64 | 2466 |
| 11 | 2413 | 38 | 2440 | 65 | 2467 |
| 12 | 2414 | 39 | 2441 | 66 | 2468 |
| 13 | 2415 | 40 | 2442 | 67 | 2469 |
| 14 | 2416 | 41 | 2443 | 68 | 2470 |
| 15 | 2417 | 42 | 2444 | 69 | 2471 |
| 16 | 2418 | 43 | 2445 | 70 | 2472 |
| 17 | 2419 | 44 | 2446 | 71 | 2473 |
| 18 | 2420 | 45 | 2447 | 72 | 2474 |
| 19 | 2421 | 46 | 2448 | 73 | 2475 |
| 20 | 2422 | 47 | 2449 | 74 | 2476 |
| 21 | 2423 | 48 | 2450 | 75 | 2477 |
| 22 | 2424 | 49 | 2451 | 76 | 2478 |
| 23 | 2425 | 50 | 2452 | 77 | 2479 |
| 24 | 2426 | 51 | 2453 | 78 | 2480 |
| 25 | 2427 | 52 | 2454 | -- | --   |
| 26 | 2428 | 53 | 2455 | -- | --   |

### 1.3 Test channel list

| Channel | Channel | Frequency (MHz) |
|---------|---------|-----------------|
| Low     | 00      | 2402            |
| Middle  | 39      | 2441            |
| High    | 78      | 2480            |

### 1.4 Ancillary equipment list

| Equipment | Model | S/N | Manufacturer | Certificate type |
|-----------|-------|-----|--------------|------------------|
| /         | /     | /   | /            | /                |

### 1.5 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| Item | Equipment | Brand | Model/Type No. | Series No. | Note |
|------|-----------|-------|----------------|------------|------|
| /    | /         | /     | /              | /          | /    |

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



## 2 Summary of Test Results

Test procedures according to the technical standards:

| No. | Standard Section | Test Item                       | Result | Remark |
|-----|------------------|---------------------------------|--------|--------|
| 1   | 15.203           | Antenna requirement             | Pass   |        |
| 2   | 15.247(b)(1)     | Peak output power               | Pass   |        |
| 3   | 15.207           | Conducted emission              | N/A    |        |
| 4   | 15.247(d)        | Band edge                       | Pass   |        |
| 5   | 15.205/15.209    | Spurious emission               | Pass   |        |
| 6   | 15.247(a)(1)     | 20dB occupied bandwidth         | Pass   |        |
| 7   | 15.247(a)(1)     | Carrier Frequencies Separation  | Pass   |        |
| 8   | 15.247(a)(1)     | Hopping channel number          | Pass   |        |
| 9   | 15.247(a)(1)     | Dwell time                      | Pass   |        |
| 10  | 15.247(d)        | Spurious RF Conducted Emissions | Pass   |        |



### 3 Test Facilities and Accreditations

#### 3.1 Test laboratory

|                       |                                                                                                                                         |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| Test Laboratory       | Shenzhen Microtest Co., Ltd.                                                                                                            |
| Location              | 101, No. 7, Zone 2, Xinxing Industrial Park, Fuhai Avenue, Xinhe Community, Fuhai Street, Bao' an District, Shenzhen, Guangdong, China. |
| FCC Registration No.: | 448573                                                                                                                                  |

#### 3.2 Environmental conditions

|                      |              |
|----------------------|--------------|
| Temperature:         | 15°C~35°C    |
| Humidity             | 20%~75%      |
| Atmospheric pressure | 98kPa~101kPa |

#### 3.3 Measurement uncertainty

The reported uncertainty of measurement  $y \pm U$  where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$  providing a level of confidence of approximately 95 %

| No. | Item                          | Uncertainty             |
|-----|-------------------------------|-------------------------|
| 1   | Conducted Emission Test       | $\pm 1.38\text{dB}$     |
| 2   | RF power, conducted           | $\pm 0.16\text{dB}$     |
| 3   | Spurious emissions, conducted | $\pm 0.21\text{dB}$     |
| 4   | All emissions, radiated(<1G)  | $\pm 4.68\text{dB}$     |
| 5   | All emissions, radiated(>1G)  | $\pm 4.89\text{dB}$     |
| 6   | Temperature                   | $\pm 0.5^\circ\text{C}$ |
| 7   | Humidity                      | $\pm 2\%$               |

#### 3.4 Test software

| Software Name                  | Manufacturer                  | Model    | Version     |
|--------------------------------|-------------------------------|----------|-------------|
| Bluetooth and WiFi Test System | Shenzhen JS tonskend co., ltd | JS1120-3 | 2.5.77.0418 |



## 4 Equipment List

| Equipment No. | Equipment Name                       | Manufacturer    | Model       | Serial No.     | Calibration date | Due date   |
|---------------|--------------------------------------|-----------------|-------------|----------------|------------------|------------|
| MTI-E043      | EMI Test Receiver                    | Rohde&schwarz   | ESCI7       | 101166         | 2020/06/04       | 2021/06/03 |
| MTI-E044      | TRILOG Broadband Antenna             | schwarabeck     | VULB 9163   | 9163-1338      | 2020/06/05       | 2021/06/04 |
| MTI-E047      | Amplifier                            | Hewlett-Packard | 8447F       | 3113A06150     | 2020/06/04       | 2021/06/03 |
| MTI-E089      | ESG Vector Signal Generator          | Agilent         | N5182A      | MY49060455     | 2020/06/03       | 2021/06/02 |
| MTI-E058      | ESG Series Analog Ssignal Generator  | Agilent         | E4421B      | GB40051240     | 2020/07/03       | 2021/07/04 |
| MTI-E062      | PXA Signal Analyzer                  | Agilent         | N9030A      | MY51350296     | 2020/06/04       | 2021/06/03 |
| MTI-E066      | MXA Signal Analyzer                  | Agilent         | N9020A      | MY50143483     | 2020/06/04       | 2021/06/03 |
| MTI-E078      | Synthesized Sweeper                  | Agilent         | 83752A      | 3610A01957     | 2020/06/04       | 2021/06/03 |
| MTI-E079      | DC Power Supply                      | Agilent         | E3632A      | MY40027695     | 2020/06/04       | 2021/06/03 |
| MTI-E045      | Double Ridged Broadband Horn Antenna | schwarabeck     | BBHA 9120 D | 9120D-2278     | 2020/06/05       | 2021/06/04 |
| MTI-E021      | EMI Test Receiver                    | Rohde&schwarz   | ESCS30      | 100210         | 2020/06/04       | 2021/06/03 |
| MTI-E022      | Pulse Limiter                        | Schwarzbeck     | VSTD 9561-F | 00679          | 2020/06/03       | 2021/06/02 |
| MTI-E023      | Artificial mains network             | Schwarzbeck     | NSLK 8127   | NSLK 8127 #841 | 2020/06/04       | 2021/06/03 |
| MTI-E046      | Active Loop Antenna                  | Schwarzbeck     | FMZB 1519 B | 00044          | 2020/06/05       | 2021/06/04 |
| MTI-E048      | Amplifier                            | Agilent         | 8449B       | 3008A02400     | 2020/07/03       | 2021/07/04 |
| MTI-E072      | Thermometer Clock Humidity Monitor   | -               | HTC-1       | /              | 2020/06/07       | 2021/06/06 |

Note: the calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

## 5 Test Result

### 5.1 Antenna requirement

#### 5.1.1 Standard requirement

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device

#### 5.1.2 EUT antenna

The EUT antenna is FPC antenna (-1.46dBi). It comply with the standard requirement. In case of replacement of broken antenna the same antenna type must be used.




## 5.2 Peak output power

### 5.2.1 Limit

| FCC Part15 Subpart C |                   |                 |                       |
|----------------------|-------------------|-----------------|-----------------------|
| Section              | Test Item         | Limit           | Frequency Range (MHz) |
| 15.247(b)(1)         | Peak output power | Power<1W(30dBm) | 2400-2483.5           |

### 5.2.2 Test setup



### 5.2.3 Test procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:  
RBW=1MHz, VBW=3MHz, Detector=Peak (If 20dB BW ≤1 MHz)  
RBW=3MHz, VBW=8MHz, Detector=Peak (If 20dB BW > 1 MHz)
- (3) The EUT was set to continuously transmitting in the max power during the test.

### 5.2.4 Test results



Test data

|           |                   |               |                      |
|-----------|-------------------|---------------|----------------------|
| EUT:      | Bluetooth Earbuds | Model Name:   | KOSS TWS150i         |
| Pressure: | 1012 hPa          | Test Voltage: | DC 3.7V from battery |

GFSK

| Test Channel | Frequency (MHz) | Maximum Peak Output Power(dBm) | Limit (dBm) |
|--------------|-----------------|--------------------------------|-------------|
| CH00         | 2402            | 7.196                          | 30          |
| CH39         | 2441            | 7.737                          | 30          |
| CH78         | 2480            | 7.663                          | 30          |

$\pi/4$ -DQPSK

| Test Channel | Frequency (MHz) | Maximum Peak Output Power(dBm) | Limit (dBm) |
|--------------|-----------------|--------------------------------|-------------|
| CH00         | 2402            | 8.280                          | 30          |
| CH39         | 2441            | 8.639                          | 30          |
| CH78         | 2480            | 8.578                          | 30          |


8DPSK

| Test Channel | Frequency (MHz) | Maximum Peak Output Power(dBm) | Limit (dBm) |
|--------------|-----------------|--------------------------------|-------------|
| CH00         | 2402            | 8.597                          | 30          |
| CH39         | 2441            | 8.639                          | 30          |
| CH78         | 2480            | 8.826                          | 30          |




## Test plots

### GFSK mode-CH00



### GFSK mode-CH39





Agilent Spectrum Analyzer - Swept SA

RL 50  $\Omega$  AC SENSE:INT SOURCE OFF ALIGN:AUTO 06:31:37 PM Feb 22, 2021

**Center Freq 2.48000000 GHz** #Avg Type: RMS #Trig: Free Run Avg|Hold: 100/100

PNO: Fast IFGain: Low #Atten: 40 dB

TRACE 1 2 3 4 5 6 TYPE MAAAAA DET P P P P P

Ref Offset 9.17 dB Ref 30.00 dBm

**Mkr1 2.479 820 GHz 7.663 dBm**

10 dB/div Log

The spectrum analyzer display shows a swept signal with a peak marker at 2.479820 GHz. The y-axis is labeled '10 dB/div Log' and ranges from -60.0 to 20.0. The x-axis represents frequency, with a center frequency of 2.480000 GHz and a span of 5.000 MHz. The signal is a broad peak with a sharp marker at 2.479820 GHz. The marker value is 7.663 dBm. The display also shows various settings: PNO: Fast, IFGain: Low, #Atten: 40 dB, #Res BW 1.0 MHz, #VBW 3.0 MHz, Sweep 1.000 ms (1001 pts), and Auto Tune.

Center 2.480000 GHz #Res BW 1.0 MHz #VBW 3.0 MHz Span 5.000 MHz Sweep 1.000 ms (1001 pts)

MSG STATUS

Frequency

Auto Tune

Center Freq 2.48000000 GHz

Start Freq 2.477500000 GHz

Stop Freq 2.482500000 GHz

CF Step 500.000 kHz

Auto Man

Freq Offset 0 Hz

Agilent Spectrum Analyzer - Swept SA

RL 50 Ω AC SENSE:INT SOURCE OFF ALIGN:AUTO 06/34:33 PM Feb 22, 2021

**Center Freq 2.40200000 GHz** PNO: Fast → Trig: Free Run #Avg Type: RMS  
IFGain: Low #Atten: 40 dB Avg|Hold: 100/100

TRACE 1 2 3 4 5 6 TYPE MAAAAA DET P P P P P

Ref Offset 9.16 dB  
Ref 30.00 dBm

**Mkr1 2.402 240 GHz  
8.280 dBm**

10 dB/div  
Log

Center 2.402000 GHz  
#Res BW 3.0 MHz #VBW 8.0 MHz Span 5.000 MHz  
Sweep 1.000 ms (1001 pts)

Frequency

Auto Tune

Center Freq  
2.40200000 GHz

Start Freq  
2.399500000 GHz

Stop Freq  
2.404500000 GHz

CF Step  
500.000 kHz  
Auto Man

Freq Offset  
0 Hz

MSG STATUS



### $\pi/4$ -DQPSK mode-CH39



### $\pi/4$ -DQPSK mode-CH78





### 8DPSK mode-CH00



### 8DPSK mode-CH39





### 8DPSK mode-CH78






### 5.3 Conducted emission

#### 5.3.1 Limits

| FREQUENCY (MHz) | Class B (dBuV) |           |
|-----------------|----------------|-----------|
|                 | Quasi-peak     | Average   |
| 0.15 -0.5       | 66 - 56 *      | 56 - 46 * |
| 0.50 -5.0       | 56.00          | 46.00     |
| 5.0 -30.0       | 60.00          | 50.00     |

Note: \*Decreases with the logarithm of the frequency.

#### 5.3.2 Test setup



**Note: 1.Support units were connected to second LISN.**  
**2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes**



### 5.3.3 Test procedure

a. EUT Operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

b. The following table is the setting of the receiver

| Receiver Parameters | Setting  |
|---------------------|----------|
| Attenuation         | 10 dB    |
| Start Frequency     | 0.15 MHz |
| Stop Frequency      | 30 MHz   |
| IF Bandwidth        | 9 kHz    |

- c. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- d. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- e. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- f. LISN at least 80 cm from nearest part of EUT chassis.

For the actual test configuration, please refer to the related Item –EUT Test Photos.

### 5.3.4 Test results

Note:

1. The three modulated high, medium and low channels have been tested. The report only shows the worst mode. The worst mode is GFSK CH00.
2. Emission Level = Reading Level + Factor, Margin = Emission Level - Limit, Factor = LISN modulus + Cable Loss
3. Not applicable, because the product does not TX when it is charged, so this item not applicable.



## 5.4 Radiated spurious emission

### 5.4.1 Limits

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

| Frequency<br>(MHz) | Field Strength<br>(micровolts/meter) | Measurement Distance<br>(meters) |
|--------------------|--------------------------------------|----------------------------------|
| 0.009~0.490        | 2400/F(kHz)                          | 300                              |
| 0.490~1.705        | 24000/F(kHz)                         | 30                               |
| 1.705~30.0         | 30                                   | 30                               |
| 30~88              | 100                                  | 3                                |
| 88~216             | 150                                  | 3                                |
| 216~960            | 200                                  | 3                                |
| Above 960          | 500                                  | 3                                |


| Spectrum Parameter                    | Setting                                          |
|---------------------------------------|--------------------------------------------------|
| Attenuation                           | Auto                                             |
| Start Frequency                       | 1000 MHz                                         |
| Stop Frequency                        | 10th carrier harmonic                            |
| RB / VB (emission in restricted band) | 1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average |

| Receiver Parameter     | Setting                          |
|------------------------|----------------------------------|
| Attenuation            | Auto                             |
| Start ~ Stop Frequency | 9kHz~150kHz / RB 200Hz for QP    |
| Start ~ Stop Frequency | 150kHz~30MHz / RB 9kHz for QP    |
| Start ~ Stop Frequency | 30MHz~1000MHz / RB 120kHz for QP |




## 5.4.2 Test setup


### Radiated emission test-up frequency below 30MHz



### Radiated emission test-up frequency 30MHz~1GHz



### Radiated emission test-up frequency above 1GHz



### 5.4.3 Test procedure

- a. EUT operating conditions. The EUT tested system was configured as the statements of 3.2 Unless otherwise a special operating condition is specified in the follows during the testing.
- b. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- c. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For emission measurements above 1 GHz, the EUT shall be placed at a height of 1.5 m above the floor on a support that is RF transparent for the frequencies of interest. Final measurements for the EUT require a measurement antenna height scan of 1 m to 4 m.
- f. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- g. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- h. For the actual test configuration, please refer to the related Item –EUT Test photos.

Note: Both horizontal and vertical antenna polarities were tested. The worst case emissions were reported.

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

| Frequency Band (MHz) | Function | Resolution bandwidth | Video Bandwidth |
|----------------------|----------|----------------------|-----------------|
| 30 to 1000           | QP       | 120 kHz              | 300 kHz         |
| Above 1000           | Peak     | 1 MHz                | 1 MHz           |
|                      | Average  | 1 MHz                | 10 Hz           |

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where  $RBWCF [dB] = 10 \cdot \lg(100 [kHz] / \text{narrower RBW} [kHz])$ . , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.



#### 5.4.4 Test results

##### Below 30MHz

|            |                   |               |                      |
|------------|-------------------|---------------|----------------------|
| EUT:       | Bluetooth Earbuds | Model Name:   | KOSS TWS150i         |
| Pressure:  | 1010 hPa          | Test Voltage: | DC 3.7V from battery |
| Test Mode: | TX                | Polarization: | --                   |

| Freq. | Reading  | Limit    | Margin | State |
|-------|----------|----------|--------|-------|
| (MHz) | (dBuV/m) | (dBuV/m) | (dB)   | P/F   |
| --    | --       | --       | --     | Pass  |
| --    | --       | --       | --     | Pass  |


##### Note:

1. For 9kHz-30MHz, the amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Distance extrapolation factor =  $40 \log (\text{specific distance}/\text{test distance})$ (dB);
3. Limit line = specific limits (dBuV) + distance extrapolation factor.




Between 30MHz – 1GHz

|            |                   |               |                      |
|------------|-------------------|---------------|----------------------|
| EUT:       | Bluetooth Earbuds | Model Name:   | KOSS TWS150i         |
| Pressure:  | 1010 hPa          | Phase:        | H                    |
| Test Mode: | TX                | Test Voltage: | DC 3.7V from battery |



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1 * | 30.3173         | 37.30          | -14.92        | 22.38          | 40.00          | -17.62      | QP       |
| 2   | 39.9942         | 30.70          | -12.47        | 18.23          | 40.00          | -21.77      | QP       |
| 3   | 46.8303         | 29.70          | -11.91        | 17.79          | 40.00          | -22.21      | QP       |
| 4   | 56.1974         | 29.60          | -12.29        | 17.31          | 40.00          | -22.69      | QP       |
| 5   | 110.9571        | 27.99          | -12.66        | 15.33          | 43.50          | -28.17      | QP       |
| 6   | 807.4291        | 26.80          | -0.06         | 26.74          | 46.00          | -19.26      | QP       |

|            |                   |               |                      |
|------------|-------------------|---------------|----------------------|
| EUT:       | Bluetooth Earbuds | Model Name:   | KOSS TWS150i         |
| Pressure:  | 1010 hPa          | Phase:        | V                    |
| Test Mode: | TX                | Test Voltage: | DC 3.7V from battery |



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1 * | 30.4238         | 46.04          | -14.89        | 31.15          | 40.00          | -8.85       | QP       |
| 2   | 41.1320         | 33.58          | -12.37        | 21.21          | 40.00          | -18.79      | QP       |
| 3   | 55.4147         | 36.22          | -12.21        | 24.01          | 40.00          | -15.99      | QP       |
| 4   | 875.2470        | 26.63          | 1.12          | 27.75          | 46.00          | -18.25      | QP       |
| 5   | 922.5157        | 26.07          | 1.70          | 27.77          | 46.00          | -18.23      | QP       |
| 6   | 986.0717        | 25.51          | 3.06          | 28.57          | 54.00          | -25.43      | QP       |

Note:

1. Emission Level = Meter Reading + Factor, Margin= Emission Level- Limit, Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. The three modulated high, medium and low channels have been tested. The report only shows the worst mode. The worst mode is 8DPSK CH39.



**1GHz-25GHz**

| Frequency                                 | Read Level | Cable loss | Antenna Factor | Preamp Factor | Emission Level | Limits   | Margin | Remark | Comment    |
|-------------------------------------------|------------|------------|----------------|---------------|----------------|----------|--------|--------|------------|
| (MHz)                                     | (dBμV)     | (dB)       | dB/m           | (dB)          | (dBμV/m)       | (dBμV/m) | (dB)   |        |            |
| Low Channel (2402 MHz)(8DPSK)--Above 1G   |            |            |                |               |                |          |        |        |            |
| 4804.629                                  | 62.64      | 4.36       | 32.92          | 45.53         | 54.39          | 74.00    | -19.61 | Pk     | Vertical   |
| 4804.629                                  | 43.54      | 4.36       | 32.92          | 45.53         | 35.29          | 54.00    | -18.71 | AV     | Vertical   |
| 7206.567                                  | 61.07      | 5.02       | 37.63          | 45.56         | 58.16          | 74.00    | -15.84 | Pk     | Vertical   |
| 7206.567                                  | 41.37      | 5.02       | 37.63          | 45.56         | 38.46          | 54.00    | -15.54 | AV     | Vertical   |
| 4804.396                                  | 61.27      | 4.36       | 32.92          | 45.53         | 53.02          | 74.00    | -20.98 | Pk     | Horizontal |
| 4804.396                                  | 42.95      | 4.36       | 32.92          | 45.53         | 34.70          | 54.00    | -19.30 | AV     | Horizontal |
| 7206.424                                  | 60.60      | 5.02       | 37.63          | 45.56         | 57.69          | 74.00    | -16.31 | Pk     | Horizontal |
| 7206.424                                  | 49.23      | 5.02       | 37.63          | 45.56         | 46.32          | 54.00    | -7.68  | AV     | Horizontal |
| Mid Channel (2441 MHz)(8DPSK)--Above 1G   |            |            |                |               |                |          |        |        |            |
| 4881.539                                  | 61.84      | 4.43       | 33.04          | 45.81         | 53.50          | 74.00    | -20.50 | Pk     | Vertical   |
| 4881.539                                  | 41.32      | 4.43       | 33.04          | 45.81         | 32.98          | 54.00    | -21.02 | AV     | Vertical   |
| 7322.142                                  | 58.72      | 5.02       | 37.71          | 45.62         | 55.83          | 74.00    | -18.17 | Pk     | Vertical   |
| 7322.142                                  | 43.56      | 5.02       | 37.71          | 45.62         | 40.67          | 54.00    | -13.33 | AV     | Vertical   |
| 4881.285                                  | 58.79      | 4.43       | 33.04          | 45.81         | 50.45          | 74.00    | -23.55 | Pk     | Horizontal |
| 4881.285                                  | 47.38      | 4.43       | 33.04          | 45.81         | 39.04          | 54.00    | -14.96 | AV     | Horizontal |
| 7322.199                                  | 58.18      | 5.02       | 37.71          | 45.62         | 55.29          | 74.00    | -18.71 | Pk     | Horizontal |
| 7322.199                                  | 48.29      | 5.02       | 37.71          | 45.62         | 45.40          | 54.00    | -8.60  | AV     | Horizontal |
| High Channel (2480 MHz)(8DPSK)-- Above 1G |            |            |                |               |                |          |        |        |            |
| 4959.223                                  | 60.65      | 4.50       | 33.26          | 46.07         | 52.34          | 74.00    | -21.66 | Pk     | Vertical   |
| 4959.223                                  | 40.91      | 4.50       | 33.26          | 46.07         | 32.60          | 54.00    | -21.40 | AV     | Vertical   |
| 7439.201                                  | 61.48      | 5.02       | 37.78          | 45.77         | 58.51          | 74.00    | -15.49 | Pk     | Vertical   |
| 7439.201                                  | 46.22      | 5.02       | 37.78          | 45.77         | 43.25          | 54.00    | -10.75 | AV     | Vertical   |
| 4959.165                                  | 61.28      | 4.50       | 33.26          | 46.07         | 52.97          | 74.00    | -21.03 | Pk     | Horizontal |
| 4959.165                                  | 48.64      | 4.50       | 33.26          | 46.07         | 40.33          | 54.00    | -13.67 | AV     | Horizontal |
| 7439.264                                  | 59.97      | 5.02       | 37.78          | 45.77         | 57.00          | 74.00    | -17.00 | Pk     | Horizontal |
| 7439.264                                  | 47.21      | 5.02       | 37.78          | 45.77         | 44.24          | 54.00    | -9.76  | AV     | Horizontal |

**Note:**

1. All Readings are Peak Value (VBW=3MHz) and AV Value (VBW=10Hz).
2. Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor.
3. All the modulation modes have been tested, and only the worst results are reflected in the report.



#### 5.4.5 Band edge – radiated

| Frequency                 | Meter Reading | Cable Loss | Antenna Factor | Preamp Factor | Emission Level | Limits   | Margin | Detector | Comment    |
|---------------------------|---------------|------------|----------------|---------------|----------------|----------|--------|----------|------------|
| (MHz)                     | (dBμV)        | (dB)       | dB/m           | (dB)          | (dBμV/m)       | (dBμV/m) | (dB)   | Type     |            |
| 1Mbps(8DPSK)- Non-hopping |               |            |                |               |                |          |        |          |            |
| 2310.00                   | 60.47         | 2.40       | 27.70          | 40.40         | 50.17          | 74       | -23.83 | Pk       | Horizontal |
| 2310.00                   | 42.66         | 2.40       | 27.70          | 40.40         | 32.36          | 54       | -21.64 | AV       | Horizontal |
| 2310.00                   | 63.33         | 2.40       | 27.70          | 40.40         | 53.03          | 74       | -20.97 | Pk       | Vertical   |
| 2310.00                   | 42.42         | 2.40       | 27.70          | 40.40         | 32.12          | 54       | -21.88 | AV       | Vertical   |
| 2390.00                   | 59.45         | 2.44       | 28.30          | 40.10         | 50.09          | 74       | -23.91 | Pk       | Vertical   |
| 2390.00                   | 41.50         | 2.44       | 28.30          | 40.10         | 32.14          | 54       | -21.86 | AV       | Vertical   |
| 2390.00                   | 60.36         | 2.44       | 28.30          | 40.10         | 51.00          | 74       | -23.00 | Pk       | Horizontal |
| 2390.00                   | 42.42         | 2.44       | 28.30          | 40.10         | 33.06          | 54       | -20.94 | AV       | Horizontal |
| 2400.00                   | 64.14         | 2.46       | 28.30          | 40.10         | 54.80          | 74       | -19.20 | Pk       | Vertical   |
| 2400.00                   | 43.94         | 2.46       | 28.30          | 40.10         | 34.60          | 54       | -19.40 | AV       | Vertical   |
| 2400.00                   | 64.40         | 2.46       | 28.30          | 40.10         | 55.06          | 74       | -18.94 | Pk       | Horizontal |
| 2400.00                   | 43.42         | 2.46       | 28.30          | 40.10         | 34.08          | 54       | -19.92 | AV       | Horizontal |
| 2483.50                   | 62.06         | 2.48       | 28.70          | 39.80         | 53.44          | 74       | -20.56 | Pk       | Vertical   |
| 2483.50                   | 40.60         | 2.48       | 28.70          | 39.80         | 31.98          | 54       | -22.02 | AV       | Vertical   |
| 2483.50                   | 60.79         | 2.48       | 28.70          | 39.80         | 52.17          | 74       | -21.83 | Pk       | Horizontal |
| 2483.50                   | 42.97         | 2.48       | 28.70          | 39.80         | 34.35          | 54       | -19.65 | AV       | Horizontal |
| 2500.00                   | 60.53         | 2.48       | 28.70          | 39.80         | 51.91          | 74       | -22.09 | Pk       | Vertical   |
| 2500.00                   | 42.32         | 2.48       | 28.70          | 39.80         | 33.70          | 54       | -20.30 | AV       | Vertical   |
| 2500.00                   | 60.14         | 2.48       | 28.70          | 39.80         | 51.52          | 74       | -22.48 | Pk       | Horizontal |
| 2500.00                   | 43.31         | 2.48       | 28.70          | 39.80         | 34.69          | 54       | -19.31 | AV       | Horizontal |
| 1Mbps (8DPSK)- hopping    |               |            |                |               |                |          |        |          |            |
| 2400.00                   | 59.36         | 2.46       | 28.30          | 40.10         | 50.02          | 74       | -23.98 | Pk       | Vertical   |
| 2400.00                   | 42.46         | 2.46       | 28.30          | 40.10         | 33.12          | 54       | -20.88 | AV       | Vertical   |
| 2400.00                   | 59.83         | 2.46       | 28.30          | 40.10         | 50.49          | 74       | -23.51 | Pk       | Horizontal |
| 2400.00                   | 43.50         | 2.46       | 28.30          | 40.10         | 34.16          | 54       | -19.84 | AV       | Horizontal |
| 2483.50                   | 62.98         | 2.48       | 28.70          | 39.80         | 54.36          | 74       | -19.64 | Pk       | Vertical   |
| 2483.50                   | 43.33         | 2.48       | 28.70          | 39.80         | 34.71          | 54       | -19.29 | AV       | Vertical   |
| 2483.50                   | 60.10         | 2.48       | 28.70          | 39.80         | 51.48          | 74       | -22.52 | Pk       | Horizontal |
| 2483.50                   | 42.71         | 2.48       | 28.70          | 39.80         | 34.09          | 54       | -19.91 | AV       | Horizontal |

Note:

1. All Readings are Peak Value (VBW=3MHz) and AV Value (VBW=10Hz).
2. Emission Level= Antenna Factor + Cable Loss + Read Level - Preamplifier Factor.
3. All the modulation modes have been tested, and only the worst results are reflected in the report.



## 5.5 20dB occupied channel bandwidth

### 5.5.1 Limit

| FCC Part15 (15.247) , Subpart C |                |       |                       |
|---------------------------------|----------------|-------|-----------------------|
| Section                         | Test Item      | Limit | Frequency Range (MHz) |
| 15.247a(1)                      | 20dB bandwidth | N/A   | 2400-2483.5           |

### 5.5.2 Test setup



### 5.5.3 Test procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:  
Bandwidth: RBW=30 kHz, VBW=100 kHz, detector= Peak

### 5.5.4 Test results



Test data

|           |                   |               |                      |
|-----------|-------------------|---------------|----------------------|
| EUT:      | Bluetooth Earbuds | Model Name:   | KOSS TWS150i         |
| Pressure: | 1012 hPa          | Test Voltage: | DC 3.7V from battery |


| Mode           | Frequency (MHz) | 20dB Bandwidth (MHz) | Limit (kHz) | Result |
|----------------|-----------------|----------------------|-------------|--------|
| GFSK           | 2402            | 0.9635               | N/A         | Pass   |
|                | 2441            | 0.9215               | N/A         | Pass   |
|                | 2480            | 0.9390               | N/A         | Pass   |
| $\pi/4$ -DQPSK | 2402            | 1.253                | N/A         | Pass   |
|                | 2441            | 1.234                | N/A         | Pass   |
|                | 2480            | 1.230                | N/A         | Pass   |
| 8DPSK          | 2402            | 1.268                | N/A         | Pass   |
|                | 2441            | 1.259                | N/A         | Pass   |
|                | 2480            | 1.260                | N/A         | Pass   |




Test plots

GFSK mode






$\pi/4$ -DQPSK






### TX CH39




### TX CH78







8DPSK mode

**TX CH00**



**TX CH39**








## 5.6 Carrier frequency separation

### 5.6.1 Limit

| FCC Part15 (15.247) , Subpart C |                    |                                                                 |                       |
|---------------------------------|--------------------|-----------------------------------------------------------------|-----------------------|
| Section                         | Test Item          | Limit                                                           | Frequency Range (MHz) |
| 15.247(a)(1)                    | Channel Separation | >25kHz or >two-thirds of the 20 dB bandwidth (Which is greater) | 2400-2483.5           |

### 5.6.2 Test setup



### 5.6.3 Test procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:  
RBW=30 kHz, VBW=100 kHz, detector= Peak, Sweep Time =auto.
- (3) The EUT was set to the Hopping Mode for Channel Separation Test and continuously transmitting for the Test.

### 5.6.4 Test results




### Test data

|            |                                               |               |                      |
|------------|-----------------------------------------------|---------------|----------------------|
| EUT:       | Bluetooth Earbuds                             | Model Name:   | KOSS TWS150i         |
| Pressure:  | 1012 hPa                                      | Test Voltage: | DC 3.7V from battery |
| Test Mode: | GFSK, $\pi/4$ -DQPSK, 8DPSK /CH00, CH39, CH78 |               |                      |

| Mode           | Channel | Frequency<br>(MHz) | Test Result<br>(kHz) | Limit<br>(kHz) |                | Result |
|----------------|---------|--------------------|----------------------|----------------|----------------|--------|
| GFSK           | Low     | 2402               | 1000                 | 642.333        | 2/3 of 20dB BW | Pass   |
|                | Middle  | 2441               | 1000                 | 614.333        | 2/3 of 20dB BW | Pass   |
|                | High    | 2480               | 1002                 | 626.000        | 2/3 of 20dB BW | Pass   |
| $\pi/4$ -DQPSK | Low     | 2402               | 1002                 | 835.333        | 2/3 of 20dB BW | Pass   |
|                | Middle  | 2441               | 1002                 | 822.667        | 2/3 of 20dB BW | Pass   |
|                | High    | 2480               | 1002                 | 820.000        | 2/3 of 20dB BW | Pass   |
| 8DPSK          | Low     | 2402               | 1002                 | 845.333        | 2/3 of 20dB BW | Pass   |
|                | Middle  | 2441               | 1000                 | 839.333        | 2/3 of 20dB BW | Pass   |
|                | High    | 2480               | 1000                 | 840.000        | 2/3 of 20dB BW | Pass   |

### Test plots





### GFSK mode-CH39




### GFSK mode-CH78






### $\pi/4$ -DQPSK mode-CH00




### $\pi/4$ -DQPSK mode-CH39





### $\pi/4$ -DQPSK mode-CH78



### 8DPSK mode-CH00





### 8DPSK mode-CH39



### 8DPSK mode-CH78




## 5.7 Hopping Channel

### 5.7.1 Limit

Frequency hopping systems in the 2400-2483.5MHz band shall use at least 15 channels.

### 5.7.2 Test setup



### 5.7.3 Test procedure

The testing follows ANSI C63.10-2013 clause 7.8.3

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT must have its hopping function enabled.

Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW : To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold


### 5.7.4 Test results




| Mode                        | Quantity of Hopping Channel | Limit | Results |
|-----------------------------|-----------------------------|-------|---------|
| GFSK, $\pi/4$ -DQPSK, 8DPSK | 79                          | >15   | Pass    |

### Test plots

#### GFSK mode




#### $\pi/4$ -DQPSK mode





### 8DPSK mode






## 5.8 Dwell time

### 5.8.1 Limit

| FCC Part15 (15.247) , Subpart C |            |         |                       |
|---------------------------------|------------|---------|-----------------------|
| Section                         | Test Item  | Limit   | Frequency Range (MHz) |
| 15.247(a)(1)                    | Dwell time | 0.4 sec | 2400-2483.5           |

### 5.8.2 Test setup



### 5.8.3 Test procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting: RBW=1MHz, VBW=3MHz, Span=0Hz, Detector=Peak
- (3) Use video trigger with the trigger level set to enable triggering only on full pulses.
- (4) Sweep Time is more than once pulse time.
- (5) Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- (6) Measure the maximum time duration of one single pulse.
- (7) Set the EUT for packet transmitting.
- (8) Measure the maximum time duration of one single pulse.
- (9) The EUT was set to the Hopping Mode for Dwell Time Test.

### 5.8.4 Test results



Test data

|            |                                   |               |                      |
|------------|-----------------------------------|---------------|----------------------|
| EUT:       | Bluetooth Earbuds                 | Model Name:   | KOSS TWS150i         |
| Pressure:  | 1012 hPa                          | Test Voltage: | DC 3.7V from battery |
| Test Mode: | GFSK, $\pi/4$ -DQPSK, 8DPSK /CH39 |               |                      |

| Mode          | Data Packet | Frequency (MHz) | Pulse Duration (ms) | Dwell Time (ms) | Limit(s) | Conclusion |
|---------------|-------------|-----------------|---------------------|-----------------|----------|------------|
| GFSK          | DH1         | 2441            | 0.399               | 127.68          | <0.4     | Pass       |
|               | DH3         | 2441            | 1.656               | 264.96          | <0.4     | Pass       |
|               | DH5         | 2441            | 2.904               | 309.76          | <0.4     | Pass       |
| $\pi/4$ DQPSK | 2DH1        | 2441            | 0.4104              | 131.33          | <0.4     | Pass       |
|               | 2DH3        | 2441            | 1.644               | 263.04          | <0.4     | Pass       |
|               | 2DH5        | 2441            | 2.910               | 310.40          | <0.4     | Pass       |
| 8DPSK         | 3DH1        | 2441            | 0.4028              | 128.90          | <0.4     | Pass       |
|               | 3DH3        | 2441            | 1.659               | 265.44          | <0.4     | Pass       |
|               | 3DH5        | 2441            | 2.910               | 310.40          | <0.4     | Pass       |

Note:

1.A period time =  $0.4 \text{ (s)} * 79 = 31.6\text{(s)}$

2.DH1 time slot = Pulse Duration \*  $(1600/(2*79)) * \text{A period time}$



DH3 time slot = Pulse Duration \*  $(1600/(4*79)) * \text{A period time}$



DH5 time slot = Pulse Duration \*  $(1600/(6*79)) * \text{A period time}$

3. For GFSK,  $\pi/4$ -DQPSK and 8DPSK: The test period:  $T = 0.4 \text{ Second/Channel} * 79 \text{ Channel} = 31.6 \text{ s}$




Test plots

| Modulation mode |  | GFSK mode                                                                            |  |
|-----------------|--|--------------------------------------------------------------------------------------|--|
| DH1             |  |   |  |
| DH3             |  |  |  |






2-DH3



2-DH5



3-DH3



Agilent Spectrum Analyzer - Swept SA

RL RF 50  $\Omega$  AC SENSE:INT SOURCE:OFF ALIGN:AUTO 06:24:27 PM Feb 22, 2021

Center Freq 2.441000000 GHz Trig Delay:200.0  $\mu$ s #Avg Type: RMS

PNO: Fast IF Gain:Low Trig: Video #Atten: 40 dB

TRACE 1 2 3 4 5 6 TYPE W W W W W W W W DET P P P P P P

10 dB/div Ref 30.00 dBm

Log

$\Delta$ Mkr2 2.910 ms  
-0.60 dB

1 2  $\Delta$ 1

Center 2.441000000 GHz Res BW 1.0 MHz #VBW 3.0 MHz Span 0 Hz Sweep 10.13 ms (8000 pts)

MSG STATUS

Frequency

Auto Tune

Center Freq  
2.441000000 GHz

Start Freq  
2.441000000 GHz

Stop Freq  
2.441000000 GHz

CF Step  
1.000000 MHz  
Man

Auto


Freq Offset  
0 Hz

## 5.9 Conducted band edge

### 5.9.1 Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### 5.9.2 Test setup



### 5.9.3 Test procedure

- Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- Repeat above procedures until all measured frequencies were complete.

### 5.9.4 Test results




## Test data


|           |                   |               |                      |
|-----------|-------------------|---------------|----------------------|
| EUT:      | Bluetooth Earbuds | Model Name:   | KOSS TWS150i         |
| Pressure: | 1012 hPa          | Test Voltage: | DC 3.7V from battery |

## Test plots

### GFSK: Band Edge, Left Side




### GFSK: Band Edge, Right Side






$\pi/4$ -DQPSK: Band Edge, Left Side




$\pi/4$ -DQPSK: Band Edge, Right Side






### 8DPSK: Band Edge, Left Side




### 8DPSK: Band Edge, Right Side






Hopping Mode  
Test plots

GFSK: Band Edge, Left Side




GFSK: Band Edge, Right Side






$\pi/4$ -DQPSK: Band Edge, Left Side




$\pi/4$ -DQPSK Band Edge, Right Side






### 8DPSK: Band Edge, Left Side



### 8DPSK Band Edge, Right Side





## 5.10 Spurious RF Conducted Emissions


### 5.10.1 Limit

Below -20dB of the highest emission level in operating band.

### 5.10.2 Measuring instruments

The Measuring equipment is listed in the section 4 of this test report.

### 5.10.3 Test setup



### 5.10.4 Test procedure

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=100kHz and VBW= 300kHz to measure the peak field strength, and measure frequency range from 9kHz to 26.5GHz.

### 5.10.5 Test results

Note:


- 1: The measurement frequency range is from 9kHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and band edge measurement data.
- 2: The worst mode is 8DPSK mode, and the report only show the worst mode data.




8DPSK on Channel 00




8DPSK on Channel 00




8DPSK on Channel 00




8DPSK on Channel 39



8DPSK on Channel 39



8DPSK on Channel 39







### 8DPSK on Channel 78



### 8DPSK on Channel 78



### GFSK on Channel 78





## Photographs of the Test Setup

Radiated emission





## Photographs of the EUT

See the APPENDIX 1- EUT PHOTO.

----END OF REPORT----