

RETLIF TESTING LABORATORIES								
EMISSION DATA SHEET								
TEST METHOD: Spurious Emissions 125KHz to 1GHz								
CUSTOMER: Global Data					JOB NO: R-3652N			
TEST SAMPLE: 125KHz Portable RF ID Read/Write Terminal								
MODEL NO: NOVAS-110					SERIAL NO: 450147			
TEST SPECIFICATION: FCC Part 15 Subpart C (Section 15.209)								
OPERATING MODE: Continuously Transmitting								
TECHNICIAN: M. Hippert, J. Monahan					DATE: 6-23-00			
NOTES: Detector Function: Average (Measured at 3 meters)								
TRANSMIT FREQUENCY	TEST FREQUENCY	3 METER READING	CORRECTION FACTOR	CORRECTED READING	300 METER DISTANCE CORRECTION FACTOR	300 METER DISTANCE CORRECTED READING	300 METER CONVERTED READING	300 METER LIMIT
MHz	MHz	dBuV	dB	dBuV/m	DB	dBuV/m	uV/m	uV/m
0.125	30.0	-	-	-	-	-	-	100.0
		-	-	-	-	-	-	
	88.0	-	-	-	-	-	-	100.0
	88.0	-	-	-	-	-	-	150.0
		-	-	-	-	-	-	
	216.0	-	-	-	-	-	-	150.0
	216.0	-	-	-	-	-	-	200.0
		-	-	-	-	-	-	
	960.0	-	-	-	-	-	-	200.0
	960.0	-	-	-	-	-	-	500.0
		-	-	-	-	-	-	
0.125	1000.0	-	-	-	-	-	-	500.0
No spurious signals were observed at the specified test distance throughout the noted frequency range.								

