

FCC PART 95 EMI MEASUREMENT AND TEST REPORT



For

Continental Conair Limited

35/F Standard Chartered Tower
Millennium City, 388 Kwun Tong Road
Kwun Tong, Kowloon, HK

FCC ID: LBBHUM1200

2004-02-02

This Report Concerns: ☒ Original Report	Equipment Type: GMRS Radio
Test Engineer: Ming Jing / 	
Report Number: R0401124	
Test Date: 2004-01-19	
Reviewed By: Ling Zhang / 	
Prepared By: Bay Area Compliance Laboratory Corporation 230 Commercial Street Sunnyvale, CA 94085 Tel: (408) 732-9162 Fax: (408) 732 9164	

Note: This test report is specially limited to the above client company and product model. It may not be duplicated without prior written consent of Bay Area Compliance Laboratory Corporation. This report **must not** be used by the client to claim product endorsement by NVLAP or any agency of the U.S. Government.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED GRANT/SUBMISSION.....	4
TEST METHODOLOGY	4
TEST FACILITY	5
EXTERNAL I/O CABLING LIST AND DETAILS	5
SYSTEM TEST CONFIGURATION.....	6
JUSTIFICATION	6
EUT TEST CONFIGURATION	6
SPECIAL ACCESSORIES.....	6
SCHEMATICS / BLOCK DIAGRAM	6
EQUIPMENT MODIFICATIONS	6
CONFIGURATION OF TEST SYSTEM	6
TEST SETUP BLOCK DIAGRAM.....	7
REQUIREMENTS OF PROVISIONS	8
§2.1046, §95.639(D), AND §95.639 (A)(1) - EFFECTIVE RADIATED POWER.....	9
STANDARD APPLICABLE	9
TEST PROCEDURE	9
TEST EQUIPMENT	10
ENVIRONMENTAL CONDITIONS.....	10
TEST RESULTS	10
§2.1047, §95.631(D), §95.637(A), AND § 95.637(B) - MODULATION CHARACTERISTICS	12
STANDARD APPLICABLE	12
TEST PROCEDURE	12
TEST EQUIPMENT	12
ENVIRONMENTAL CONDITIONS	13
TEST RESULTS	13
§2.1049, §95.633(A), AND § 95.633(C) - OCCUPIED BANDWIDTH OF EMISSION.....	15
STANDARD APPLICABLE	15
TEST PROCEDURE	15
TEST EQUIPMENT	15
ENVIRONMENTAL CONDITIONS.....	15
TEST RESULTS	15
§2.1053 AND §15.109(A) - RADIATED SPURIOUS EMISSION.....	17
STANDARD APPLICABLE	17
TEST PROCEDURE	17
TEST EQUIPMENT	17
ENVIRONMENTAL CONDITIONS	17
TEST RESULT	18
§95.635(B)(1), §95.635(B)(3), AND §95.635(B)(7) - SPURIOUS EMISSION.....	19
STANDARD APPLICABLE	19
MEASUREMENT PROCEDURE.....	19
TEST EQUIPMENT	19
ENVIRONMENTAL CONDITIONS.....	19
TEST RESULT	19
§2.1055, §95.621(B), AND §95.627(B) - FREQUENCY STABILITY MEASUREMENT	22
STANDARD APPLICABLE	22
TEST PROCEDURE	22
TEST EQUIPMENT	22
ENVIRONMENTAL CONDITIONS	23

TEST RESULTS23

GENERAL INFORMATION

Product Description for Equipment Under Test (EUT)

The *Continental Conair Limited's product, FCC ID: LBBHUM1200* or the "EUT" as referred to in this report is a 22 channel GMRS radio which is measured approximately 7.9"L x 2.6"W x 1.7"H.

The EUT has the following features:

- 22 Channel and 38 CTCSS
- Channel Scan & Dual Watch
- VOX
- 10 NOAA Weather Channels
- Weather Alert
- Vibration Alert
- Received Signal Strength Indicator
- Selectable Call Signal
- Key Tone On/Off
- Auto Battery Save
- Monitor
- LCD Back Lighting
- Low Battery Indicator
- Roger Beep Tone
- Keypad Lock
- TX LED indicator
- Power Hi/Low
- Compass
- Clock

** The test data gathered are from production sample, serial number: #0003, provided by the manufacturer.*

Objective

This report is prepared on behalf of *Continental Conair Limited* in accordance with Part 95 Subpart A, Subpart B and Subpart E of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC rules for effective radiated power, modulation characteristics, occupied bandwidth, radiated spurious emissions, AC line conducted emissions and frequency stability.

Related Grant/Submission

No Related Submittals.

Test Methodology

Measurements contained in this report were also conducted with TIA/EIA Standard 603, Telecommunications Industry Association Land Mobile FM or PM Communications Equipment Measurement and Performance Standards.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratory, Corp. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The Open Area Test site used by Bay Area Compliance Laboratory Corporation to collect radiated and conducted emission measurement data is located in the back parking lot of the building at 230 Commercial Street, Sunnyvale, California, USA.

Test site at Bay Area Compliance Laboratory Corporation has been fully described in reports submitted to the Federal Communication Commission (FCC) and Voluntary Control Council for Interference (VCCI). The details of these reports has been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 11 and December 10, 1997 and Article 8 of the VCCI regulations on December 25, 1997. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2001.

The Federal Communications Commission and Voluntary Control Council for Interference has the reports on file and is listed under FCC file 31040/SIT 1300F2 and VCCI Registration No.: C-1298 and R-1234. The test site has been approved by the FCC and VCCI for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratory Corporation is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (NVLAP). The scope of the accreditation covers the FCC Method - 47 CFR Part 15 - Digital Devices, IEC/CISPR 22: 1998, and AS/NZS 3548: Electromagnetic Interference - Limits and Methods of Measurement of Information Technology Equipment test methods under NVLAP Lab Code 200167-0.

External I/O Cabling List and Details

Cable Description	Length (M)	Port/From	To
Headset Cable	0.5	Headset	EUT

SYSTEM TEST CONFIGURATION

Justification

The EUT was tested according to ANSI C63.4-2001 to represent the worst-case results during the final qualification test.

EUT Test Configuration

The EUT was powered and fully operated by pushing PTT (Push To Talk) button and then change the channel to Low, Middle, and High by using up and down buttons.

Special Accessories

As shown in following test block diagram setup, interface cable used for compliance testing is shielded as normally supplied by customer and its respective support equipment manufacturers.


Schematics / Block Diagram

Please refer to Appendix D.

Equipment Modifications


No modifications were made to the EUT.

Configuration of Test System



Test Setup Block Diagram

For tabletop systems, the EUT shall be centered laterally on the tabletop and its rear shall be flushed with the rear of the table. If the EUT is a stand-alone unit, it shall be placed in the center of the tabletop.



REQUIREMENTS OF PROVISIONS

Results reported relate only to the product tested, serial number: #4.

FCC Rules	Rules Description	Requirement	Result
2.1046 95.639 (a) (1) 95.639 (d)	Effective Radiated Power	0.5W for FRS 50 W for GMRS	Complied
2.1047 95.631 (d) 95.637 (a) 95.637 (b)	Modulation Characteristics F3E analogy voice Peak Frequency Deviation Audio Frequency Response Over Modulation	Deviation < 2.5 kHz for FRS Deviation < 5 kHz for GMRS	Complied
2.1049 95.633 (a) 95.633 (c)	Occupied Bandwidth	12.5 kHz for FRS 20 kHz for GMRS	Complied
2.1053 15.109 (a)	Field Strength of Spurious Radiation	Worst Case < 48dB	Complied
95.635 (b)(1) 95.635 (b)(3) 95.635(b)(7)	Spurious Emission	Complied	Complied
2.1055 95.621 (b) 95.627 (b)	Frequency Stability Vs. Temperature Vs. Voltage	Deviation < 5 ppm for GMRS Deviation < 2.5 ppm for FRS	Complied

§2.1046, §95.639(d), and §95.639 (a)(1) - EFFECTIVE RADIATED POWER

Standard Applicable

Per FCC §2.1046 and FCC § 95.639 (a) (1), no GMRS unit, under any condition of modulation, shall exceed 50W Carrier Power (average TP during one unmodulated RF cycle) when transmission type A1D, F1D, .G1D, A3E, F3E or G3E.

Per FCC §2.1046 and FCC § 95.639 (d), no FRS unit, under any condition of modulation, shall exceed 0.500W effective radiated power (ERP).

Test Procedure

1. On a test site, the EUT shall be placed at 1.5m height on a turn table, and in the position closest to normal use as declared by the applicant.
2. The test antenna shall be oriented initially for vertical polarization located 3m from EUT to correspond to the frequency of the transmitter.
3. The output of the test antenna shall be connected to the measuring receiver and the quasi-peak detector is used for the measurement.
4. The transmitter shall be switched on, if possible, without modulation and the measuring receiver shall be tuned to the frequency of the transmitter under test.
5. The test antenna shall be raised and lowered through the specified range of height until a maximum signal level is detected by the measuring receiver.
6. The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
7. The test antenna shall be raised and lowered again through the specified range of height until a maximum signal level is detected by the measuring receiver.
8. The maximum signal level detected by the measuring receiver shall be noted.
9. The transmitter shall be replaced by a tuned dipole (substitution antenna).
10. The substitution antenna shall be orientated for vertical polarization and the length of the substitution antenna shall be adjusted to correspond to the frequency of the transmitter.
11. The substitution antenna shall be connected to a calibrated signal generator.
12. In necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
13. The test antenna shall be raised and lowered through the specified range of height to ensure that the maximum signal is received.
14. The input signal to the substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, which is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuator setting of the measuring receiver.
15. The input level to the substitution antenna shall be recorded as power level in dBm, corrected for any change of input attenuator setting of the measuring receiver.

16. The measurement shall be repeated with the test antenna and the substitution antenna orientated for horizontal polarization.
17. The measure of the effective radiated power is the large of the two levels recorded, at the input to the substitution antenna, corrected for gain of the substitution antenna if necessary.

Test Equipment

Manufacturer	Description	Model	Serial Number	Cal. Date
Rohde & Schwarz	Signal Generator	SMIQ03	1125.5555.03	2003-07-10
Rohde & Schwarz	I/O Modulation Generator	AMIQ	1110.2003.02	2003-07-10
HP	Spectrum Analyzer	8564E	08303	2003-08-20
Com-Power	Log Periodic Antenna	AL-100	16091	2003-05-01
Com-Power	Biconical Antenna	AB-100	14012	2003-11-02
A.H.System	Horn Antenna (700MHz-18GHz)	SAS-200/571	261	2003-05-30

* **Statement of Traceability:** **BACL Corp.** certifies that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Environmental Conditions

Temperature:	10 °C
Relative Humidity:	48%
ATM Pressure:	1100 mbar

Test Results

The measured output power showed as follows:

FREQUENCY (MHZ)	SUBSTITUTION READING (dBm)	SUBSTITUTION ANTENNA GAIN	SUBSTITUTION CALBE LOSS (dBm)	ERP (dBm)
462.5625	32.7	0	0.1	32.6
467.7125	26.5	0	0.1	26.3
462.7250	32.5	0	0.1	32.4

Sample calculation:

Absolute level = substitution reading + antenna gain - cable loss

For example:

$$32.7 + 0 - 0.1 = 32.6$$

Summary of the Test Result:

32.6 dBm at 462.5625 MHz, Channel 1
26.3 dBm at 467.7125 MHz , Channel 14
32.4 dBm at 462.7250 MHz, Channel 22

§2.1047, §95.631(d), §95.637(a), and § 95.637(b) - MODULATION CHARACTERISTICS

Standard Applicable

Per FCC § 2.1047 and FCC §95.637 (a), a GMRS transmitter that transmits emission types F3E must not exceed a peak frequency deviation of plus or minus 5 kHz. A FRS unit that transmits emission type F3E must not exceed a peak frequency deviation of plus or minus 2.5 kHz, and the audio frequency response must not exceed 3.125 kHz.

Test Procedure

Audio Frequency Response

The RF output of the transceiver was connected to the input of a FM deviation meter through sufficient attenuation so as not to overload the meter or distort the reading. An audio signal generator was coupled into the external microphone jack of the transceiver, or alternatively, the microphone element was removed the generator output was connected to the microphone connectors.

The audio signal input level was adjusted to obtain 20% of the maximum rated system deviation at 1 kHz, and recorded as DEV_{REF}. With the audio signal generator level unchanged, set the generator frequency between 100 Hz to 5000 Hz. The transmitter deviations (DEV_{FREQ}) were measured and the audio frequency response was calculated as

$$20\log_{10} [\text{DEV}_{\text{FREQ}} / \text{DEV}_{\text{REF}}]$$

Audio Low-Pass Filter Response

An audio signal generator and an audio spectrum analyzer were connected to the input and output of the post limiter low pass filter respectively. The audio signal generator frequency was set between 1000 Hz and the upper low pass filter limit. The audio frequency response at test frequency was calculated as

$$\text{LEV}_{\text{FREQ}} - \text{LEV}_{\text{REF}}$$

Modulation Limiting

With the same setup as above, at three different modulating frequencies, the output level of the audio generator was varied and the FM deviation level was recorded.

Test Equipment

Manufacturer	Description	Model	Serial Number	Cal. Date
HP	Spectrum Analyzer	8564E	08303	2003-08-20
HP	Modulation Analyzer	8901A	2026A00847	2003-08-19
Nanyan	Audio Generator	NY2201	000420	Not Required


* **Statement of Traceability:** BACL Corp. certifies that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.



Environmental Conditions

Temperature:	10 °C
Relative Humidity:	48%
ATM Pressure:	1100 mbar

Test Results

The plot(s) of modulation characteristic is presented hereinafter as reference.





am 10-4-19

§2.1049, §95.633(a), and § 95.633(c) - OCCUPIED BANDWIDTH OF EMISSION

Standard Applicable

Per FCC §2.1049 and FCC §95.633 (a), the authorized bandwidth for emission type F3E transmitted is 20 kHz.

Per FCC §2.1049 and FCC §95.633 (c), the authorized bandwidth for emission type F3E transmitted by a FRS unit is 12.5 kHz.

Test Procedure

The antenna was disconnected from the transmitter and the short cable was connected to the transmitter RF output.

The RF output was connected to the input of the spectrum analyzer through sufficient attenuation.

The resolution bandwidth of the spectrum analyzer was set up at least 10 times higher than the authorized bandwidth of the transmitter. With the transmitter keyed, the level of the unmodulated carrier was set to the full scale reference line of the spectrum analyzer. This is used as a 0dB reference for emission mask measurements.

The transmitter was then modulated with a 2500 Hz tone at an input level 20 dB greater than the necessary to produce 50% of rated system deviation. The resolution bandwidth of the spectrum analyzer was set up to 300 Hz and the spectrum of the transmitting signal was recorded. This spectrum was compared to the required emission mask.

Test Equipment

Manufacturer	Description	Model	Serial Number	Cal. Due Date
HP	Spectrum Analyzer	8564E	08303	2003-08-20
Nanyan	Audio Generator	NY2201	000420	Not Required



* **Statement of Traceability:** BACL Corp. certifies that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Environmental Conditions

Temperature:	10 ° C
Relative Humidity:	48%
ATM Pressure:	1100 mbar

Test Results

Test Result: Pass
Please refer the following curve and plots.



§2.1053 and §15.109(a) - RADIATED SPURIOUS EMISSION

Standard Applicable

According to FCC §2.1053, measurements shall be made to detect spurious emission that may be radiated directly from the cabinet, control circuits, power leads, or intermediated circuit elements under normal condition of installation and operation. Information submitted shall include the relative radiated power of spurious emission with reference to the rated power output of the transmitter, assuming all emissions are radiated from a halfwave dipole antenna.

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB = $10 \lg (\text{TXpwr in Watts}/0.001)$ – the absolute level

Spurious attenuation limit in dB = $43 + 10 \log_{10} (\text{power out in Watts})$

Test Equipment

Manufacturer	Description	Model	Serial Number	Cal. Date
Com-Power	Biconical Antennas	CDI B100/200/300	14012	2004-05-01
Com-Power	Bi-logcon Antenna	3110B	9603-2315	2004-10-11
A.H. System	Horn Antenna	SAS-200	2455	2004-08-02
Hewlett Packard	Spectrum Analyzer	HP8565EC	06042	2004-05-03
Rohde & Schwarz	Generator	SMIQ03	1048004	2004-08-01

* **Statement of Traceability: BACL Corp.** certifies that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Environmental Conditions

Temperature:	10 °C
Relative Humidity:	48%
ATM Pressure:	1100 mbar

Test Result

-8.8 dBm at 925.1250 MHz, Channel 1
 -11.0 dBm at 935.4250 MHz, Channel 14
 -9.0 dBm at 925.4500 MHz, Channel 22

EUT					Generator						Standard	
Indicated		Table	Test Antenna		Substitution			Antenna	Cable	Absolute	FCC	FCC
Frequency MHz	Ampl. dBuV/m	Angle Degree	Height Meter	Polar H/V	Frequency MHz	Level dBm	Polar H/V	Gain Corrected	Loss DB	Level dBm	Limit dBm	Margin DBm
CHANNEL 1, LOW FREQUENCY AT 462.5625 MHZ												
462.5625	109.5	0	1.8	V	462.5625	32.7	V	0.00	0.1	32.6		
462.5625	98.2	180	1.5	H	462.5625	23.4	H	0.00	0.1	23.3		
925.1250	47.3	90	1.8	V	925.1250	-21.5	V	0.00	0.3	-21.8	-13	-8.8
925.1250	46.2	0	1.5	H	925.1250	-22.9	H	0.00	0.3	-23.2	-13	-10.2
1387.6875	42.6	60	1.5	V	1387.6875	-31.7	V	3.60	0.5	-28.6	-13	-15.6
1850.2500	37.8	30	1.5	V	1850.2500	-34.4	V	4.20	0.7	-30.9	-13	-17.9
1850.2500	36.2	210	1.8	H	1850.2500	-35.9	H	4.20	0.7	-32.4	-13	-19.4
1387.6875	35.5	0	1.8	H	1387.6875	-36.8	H	3.60	0.5	-33.7	-13	-20.7
CHANNEL 14, HIGH FREQUENCY AT 467.7125 MHZ												
467.7125	106.1	45	2.2	V	467.7125	26.5	V	0.00	0.1	26.4		
467.7125	97.7	0	1.5	H	467.7125	22.3	H	0.00	0.1	22.2		
935.4250	45.2	45	1.7	V	935.4250	-23.7	V	0.00	0.3	-24.0	-13	-11.0
935.4250	44.3	90	1.5	H	935.4250	-25.1	H	0.00	0.3	-25.4	-13	-12.4
1403.1375	40.9	90	2.2	V	1403.1375	-33.9	V	3.60	0.5	-30.8	-13	-17.8
1870.8500	36.1	45	1.5	V	1870.8500	-36.5	V	4.20	0.7	-33.0	-13	-20.0
1870.8500	35.5	180	2.1	H	1870.8500	-37.4	H	4.20	0.7	-33.9	-13	-20.9
1403.1375	34.2	100	2.5	H	1403.1375	-38.2	H	3.60	0.5	-35.1	-13	-22.1
CHANNEL 22, FREQUENCY AT 462.725 MHZ												
462.7250	109.3	45	2.2	V	462.7250	32.5	V	0.00	0.1	32.4		
462.7250	97.8	290	1.8	H	462.7250	22.9	H	0.00	0.1	22.8		
925.4500	47.2	0	1.8	V	925.4500	-21.7	V	0.00	0.3	-22.0	-13	-9.0
925.4500	46.1	180	1.5	H	925.4500	-23.2	H	0.00	0.3	-23.5	-13	-10.5
1388.1750	42.4	180	2.0	V	1388.1750	-31.9	V	3.60	0.5	-28.8	-13	-15.8
1850.9000	37.6	200	2.0	V	1850.9000	-34.8	V	4.20	0.7	-31.3	-13	-18.3
1850.9000	36.1	120	2.2	H	1850.9000	-36.5	H	4.20	0.7	-33.0	-13	-20.0
1388.1750	35.3	90	1.8	H	1388.1750	-37.3	H	3.60	0.5	-34.2	-13	-21.2

Note: No Preamplifier Used. The EUT was tested in three orthogonal planes.

§95.635(b)(1), §95.635(b)(3), and §95.635(b)(7) - SPURIOUS EMISSION**Standard Applicable**

Per FCC §95.635 (b)(1), at least 25 dB (decibels) on any frequency removed from the center of the authorized bandwidth by more than 50% up to and including 100% of the authorized bandwidth.

Per FCC §95.635 (b)(3), at least 35 dB on any frequency removed from the center of the authorized bandwidth by more than 100% up to and including 250% of the authorized bandwidth.

Per FCC §95.635 (b)(7), at least $43 \pm 10 \log_{10}(T)$ dB on any frequency removed from the center of the authorized bandwidth by more than 250%.

Measurement Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set the SA on Max-Hold Mode, and then keep the EUT in transmitting mode. Record all the signals from each channel until each one has been recorded.
4. Set the SA on View mode and then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.
6. Spurious attenuation limits in dB = $43 + 10\log_{10}(\text{power out in Watts})$

Test Equipment

Manufacturer	Description	Model No.	Serial No.	Calibration Date
HP	Spectrum Analyzer	8564E	08303	2003-08-20
Nanyan	Audio Generator	NY2201	000420	Not Required



* **Statement of Traceability:** **BACL Corp.** certifies that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.


Environmental Conditions

Temperature:	10 °C
Relative Humidity:	48%
ATM Pressure:	1100 mbar

Test Result

Please refer to the following plot(s).





§2.1055, §95.621(b), and §95.627(b) - FREQUENCY STABILITY MEASUREMENT

Standard Applicable

According to FCC §2.1055(a)(1), the frequency stability shall be measure with variation of ambient temperature from -30°C to $+50^{\circ}\text{C}$, and according to FCC 2.1055(d)(2), the frequency stability shall be measured with reducing primary supply voltage to the battery operating end point which is specified by the manufacturer.

According to FCC §95.621 (a), the GMRS transmitter channel frequencies (reference frequencies from which the carrier frequency, suppressed or otherwise, may not deviate by more than the specified frequency to tolerance) are 462.5500, 462.5625, 462.5750, 462.5875, 462.6000, 462.6125, 462.6250, 462.6375, 462.6500, 462.6625, 462.6750, 462.6875, 462.7000, 462.7125, 462.7250, 467.5500, 467.5750, 467.6000, 467.6250, 467.6500, 467.6750, 467.7000 and 467.7250.

According to FCC §95.621 (b), each GMRS transmitter for mobile station, small base station and control station operation must be maintained within a frequency tolerance of 0.0005%. Each GMRS transmitter for base station (except small base), mobile relay station or fixed station operation must be maintained within a frequency tolerance of 0.00025%.

According to FCC §95.627, each FRS unit must be maintained within a frequency tolerance of 0.00025%.

Test Procedure

Frequency stability versus environmental temperature

The equipment under test was connected to an external DC power supply and the RF output was connected to a frequency counter via feedthrough attenuators. The EUT was placed inside the temperature chamber.

After the temperature stabilized for approximately 20 minutes, the frequency of the output signal was recorded from the counter.

Frequency Stability versus Input Voltage

At room temperature ($25\pm 5^{\circ}\text{C}$), an external variable DC power supply was connected to the EUT. The frequency of the transmitter was measured for 115%, 100% and 85% of the nominal operating input voltage.

Test Equipment

Manufacturer	Description	Model No.	Serial No.	Calibration Date
HP	Spectrum Analyzer	8564E	08303	2003-08-20
Tenny	Temperature Chamber	Versa	4581	2003-04-23

* **Statement of Traceability:** **BACL Corp.** certifies that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Environmental Conditions

Temperature:	10 °C
Relative Humidity:	48%
ATM Pressure:	1100 mbar

Test Results

Reference Frequency: 462.5625 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (Vdc)	Frequency Measure with Time Elapsed	
		MCF (MHz)	PPM Error
50	6	462.5614	-2.4
40	6	462.5617	-1.7
30	6	462.5621	-0.9
20	6	462.5623	-0.4
10	6	462.5625	0.0
0	6	462.5626	0.2
-10	6	462.5628	0.6
-20	6	462.5631	1.2
-30	6	462.5632	1.5

Frequency Stability Versus Input Voltage

Reference Frequency: 462.5625 MHz, Limit: 2.5ppm						
Power Supplied (Vdc)	Frequency Measure with Time Elapsed					
	2 Minutes		5 Minutes		10 Minutes	
	MHz	ppm	MHz	ppm	MHz	ppm
4.8	462.5622	-0.6	462.5622	-0.6	462.5622	-0.6

End Point = 4.8 V

Conclusion: The EUT complied with the applicable Frequency Stability Limits.