



FCC §2.1091, LP0002-2018 §5.20.2,
ISED RSS-102
RF EXPOSURE REPORT


For

Cisco Systems, Inc.

125 W Tasman Drive
San Jose, CA 95134, USA

FCC ID: LDKEDAC92157
IC: 2461N-EDAC92157

C9120AXE-X
(X=A, B, and T)
2400-2483.5 MHz, 5150-5250 MHz
5250-5350 MHz, 5470-5725 MHz, 5725-5850 MHz

Product Type: Cisco Catalyst 9120AX Series	
Prepared By: Christian McCaig Test Technician	
Reviewed By: Frank Wang RF Lead	
Bay Area Compliance Laboratories Corp. 1274 Anvilwood Ave Sunnyvale, CA 94089, USA Tel: (408) 732-9162, Fax: (408) 732 9164	



Note: This test report was prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This test report **shall not** be used by the customer to claim product certification, approval, or endorsement by A2LA or any agency of the United States Government or any foreign government.

* This test report may contain data and test methods that are not covered by BACL's scope of accreditation as of the test report date shown above. These items are marked within the test report text with an asterisk "*"

1 FCC §2.1091, §15.247(i) & ISED RSS-102 & LP0002– RF Exposure

1.1 Applicable Standards

According to FCC §15.407(f), §1.1307(b)(1) and LP0002 5.20.2.2, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	* (100)	30
1.34-30	824/f	2.19/f	* (180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

According to ISED RSS-102 Issue 5:

2.5.2 Exemption Limits for Routine Evaluation – RF Exposure Evaluation

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz⁶ and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

1.2 MPE Prediction

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

1.3 MPE Results for FCC

2.4 GHz Wi-Fi Aux

<u>Maximum output power at antenna input terminal (dBm):</u>	<u>13.4</u>
<u>Maximum output power at antenna input terminal (mW):</u>	<u>21.88</u>
<u>Prediction distance (cm):</u>	<u>30</u>
<u>Prediction frequency (MHz):</u>	<u>2437</u>
<u>Maximum Antenna Gain, typical (dBi):</u>	<u>6</u>
<u>Maximum Antenna Gain (numeric):</u>	<u>3.98</u>
<u>Power density of prediction frequency at 30.0 cm (mW/cm²):</u>	<u>0.008</u>
<u>FCC MPE limit for uncontrolled exposure at prediction frequency (mW/cm²):</u>	<u>1.0</u>

The device is compliant with the requirement MPE limit for uncontrolled exposure. The maximum power density at the distance of 30 cm is 0.008 mW/cm². Limit is 1.0 mW/cm².

2.4 GHz Wi-Fi

<u>Maximum output power at antenna input terminal (dBm):</u>	<u>23.1</u>
<u>Maximum output power at antenna input terminal (mW):</u>	<u>204.17</u>
<u>Prediction distance (cm):</u>	<u>30</u>
<u>Prediction frequency (MHz):</u>	<u>2437</u>
<u>Maximum Antenna Gain, typical (dBi):</u>	<u>12</u>
<u>Maximum Antenna Gain (numeric):</u>	<u>15.85</u>
<u>Power density of prediction frequency at 30.0 cm (mW/cm²):</u>	<u>0.286</u>
<u>FCC MPE limit for uncontrolled exposure at prediction frequency (mW/cm²):</u>	<u>1.0</u>

The device is compliant with the requirement MPE limit for uncontrolled exposure. The maximum power density at the distance of 30 cm is 0.286 mW/cm². Limit is 1.0 mW/cm².

2.4 GHz BLE

<u>Maximum peak output power at antenna input terminal (dBm):</u>	<u>2.88</u>
<u>Maximum peak output power at antenna input terminal (mW):</u>	<u>1.94</u>
<u>Prediction distance (cm):</u>	<u>30</u>
<u>Prediction frequency (MHz):</u>	<u>2426</u>
<u>Maximum Antenna Gain, typical (dBi):</u>	<u>6</u>
<u>Maximum Antenna Gain (numeric):</u>	<u>3.98</u>
<u>Power density of prediction frequency at 30.0 cm (mW/cm²):</u>	<u>0.001</u>
<u>FCC MPE limit for uncontrolled exposure at prediction frequency (mW/cm²):</u>	<u>1.0</u>

The device is compliant with the requirement MPE limit for uncontrolled exposure. The maximum power density at the distance of 30 cm is 0.001 mW/cm². Limit is 1.0 mW/cm².

5 GHz Wi-Fi Aux

<u>Maximum peak output power at antenna input terminal (dBm):</u>	<u>13.9</u>
<u>Maximum peak output power at antenna input terminal (mW):</u>	<u>24.55</u>
<u>Prediction distance (cm):</u>	<u>30</u>
<u>Prediction frequency (MHz):</u>	<u>5825</u>
<u>Maximum Antenna Gain, typical (dBi):</u>	<u>6</u>
<u>Maximum Antenna Gain (numeric):</u>	<u>3.98</u>
<u>Power density of prediction frequency at 30.0 cm (mW/cm²):</u>	<u>0.0086</u>
<u>FCC MPE limit for uncontrolled exposure at prediction frequency (mW/cm²):</u>	<u>1</u>

The device is compliant with the requirement MPE limit for uncontrolled exposure. The maximum power density at the distance of 30 cm is 0.0089 mW/cm². Limit is 1.0 mW/cm².

5 GHz Wi-Fi XOR

<u>Maximum peak output power at antenna input terminal (dBm):</u>	<u>22.7</u>
<u>Maximum peak output power at antenna input terminal (mW):</u>	<u>186.21</u>
<u>Prediction distance (cm):</u>	<u>30</u>
<u>Prediction frequency (MHz):</u>	<u>5785</u>
<u>Maximum Antenna Gain, typical (dBi):</u>	<u>12</u>
<u>Maximum Antenna Gain (numeric):</u>	<u>15.85</u>
<u>Power density of prediction frequency at 30.0 cm (mW/cm²):</u>	<u>0.2609</u>
<u>FCC MPE limit for uncontrolled exposure at prediction frequency (mW/cm²):</u>	<u>1</u>

The device is compliant with the requirement MPE limit for uncontrolled exposure. The maximum power density at the distance of 30 cm is 0.2609 mW/cm². Limit is 1.0 mW/cm².

5 GHz Wi-Fi Regular

Maximum peak output power at antenna input terminal (dBm): 24
Maximum peak output power at antenna input terminal (mW): 251.19
Prediction distance (cm): 30
Prediction frequency (MHz): 5745
Maximum Antenna Gain, typical (dBi): 11
Maximum Antenna Gain (numeric): 12.59
Power density of prediction frequency at 30.0 cm (mW/cm²): 0.2796
FCC MPE limit for uncontrolled exposure at prediction frequency (mW/cm²): 1

The device is compliant with the requirement MPE limit for uncontrolled exposure. The maximum power density at the distance of 30 cm is 0.2796 mW/cm². Limit is 1.0 mW/cm².

RF Exposure evaluation has been evaluated for all radio co-location to represent the worst case.

Frequency Band	Max Conducted Power(dBm)	Evaluated Distance (cm)	Worst-Case MPE (mW/cm ²)	MPE Limit (mW/cm ²)	Worst-Case MPE Ratios	Sum of MPE Ratios	Limit
Worst Case							
5 GHz Wi-Fi Regular	24	30	0.2796	1.0	27.96 %	84.41 %	100%
5 GHz Wi-Fi Aux	13.9	30	0.0086	1.0	0.86 %		
5 GHz Wi-Fi XOR	22.7	30	0.2609	1.0	26.09 %		
2.4 GHz Wi-Fi	23.1	30	0.286	1.0	28.60 %		
2.4 GHz Aux	13.4	30	0.008	1.0	0.8 %		
2.4 GHz BLE	2.88	30	0.001	1.0	0.1 %		

1.4 RF exposure evaluation exemption for ISEDC

2.4 GHz Wi-Fi

$$23.1 + 12 \text{ dBi} = 35.1 \text{ dBm} < 1.31 \times 10^{-2} f^{0.6834} = 4.903 \text{ W} = 36.904 \text{ dBm}$$

2.4 GHz Wi-Fi Aux

$$13.4 + 6 \text{ dBi} = 19.4 \text{ dBm} < 1.31 \times 10^{-2} f^{0.6834} = 4.903 \text{ W} = 36.904 \text{ dBm}$$

BLE

$$2.88 + 6 \text{ dBi} = 8.88 \text{ dBm} < 1.31 \times 10^{-2} f^{0.6834} = 4.903 \text{ W} = 36.904 \text{ dBm}$$

5 GHz Wi-Fi Aux

$$13.9 + 6 \text{ dBi} = 19.9 \text{ dBm} < 1.31 \times 10^{-2} f^{0.6834} = 4.903 \text{ W} = 36.904 \text{ dBm}$$

5 GHz Wi-Fi XOR

$$22.7 + 12 \text{ dBi} = 34.7 \text{ dBm} < 1.31 \times 10^{-2} f^{0.6834} = 4.880 \text{ W} = 36.884 \text{ dBm}$$

5 GHz Wi-Fi Regular

$$24 + 11 \text{ dBi} = 35 \text{ dBm} < 1.31 \times 10^{-2} f^{0.6834} = 4.880 \text{ W} = 36.884 \text{ dBm}$$

Therefore the RF exposure is not required.