

FCC TEST REPORT

(PART 24)

Applicant:	Continental Automotive Systems, Inc.
Address:	21440 W Lake Cook Rd., Deer Park, IL 60010, USA

Manufacturer or Supplier:	Continental Automotive Systems, Inc.
Address:	21440 W Lake Cook Rd., Deer Park, IL 60010, USA
Product:	FE3NA0031
Brand Name:	Continental
Model Name:	FE3NA0031
FCC ID:	LHJ-FE3NA0031
Date of tests:	Dec. 20, 2021 ~ Jan. 17, 2022

The tests have been carried out according to the requirements of the following standard:

☒ **FCC PART 24, Subpart E** ☒ **FCC PART 2**
☒ **ANSI/TIA/EIA-603-D** ☒ **ANSI/TIA/EIA-603-E** ☒ **ANSI C63.26-2015**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Simon Wang Engineer / Mobile Department	Approved by Luke Lu Manager / Mobile Department
	
Date: Jan. 17, 2022	Date: Jan. 17, 2022

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



TABLE OF CONTENTS

RELEASE CONTROL RECORD	4
1 SUMMARY OF TEST RESULTS	5
1.1 MEASUREMENT UNCERTAINTY	5
1.2 TEST SITE AND INSTRUMENTS	6
2 GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 CONFIGURATION OF SYSTEM UNDER TEST	9
2.3 DESCRIPTION OF SUPPORT UNITS	10
2.4 TEST ITEM AND TEST CONFIGURATION.....	10
2.5 EUT OPERATING CONDITIONS	13
2.6 GENERAL DESCRIPTION OF APPLIED STANDARDS	13
3 TEST TYPES AND RESULTS	14
3.1 OUTPUT POWER MEASUREMENT	14
3.1.1 LIMITS OF OUTPUT POWER MEASUREMENT	14
3.1.2 TEST PROCEDURES	14
3.1.3 TEST SETUP	15
3.1.4 TEST RESULTS	15
3.2 FREQUENCY STABILITY MEASUREMENT	26
3.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT	26
3.2.2 TEST PROCEDURE	26
3.2.3 TEST SETUP	26
3.2.4 TEST RESULTS	27
3.3 OCCUPIED BANDWIDTH MEASUREMENT	28
3.3.1 TEST PROCEDURES	28
3.3.2 TEST SETUP	28
3.3.3 TEST RESULTS	29
3.4 BAND EDGE MEASUREMENTC	30
3.4.1 LIMITS OF BAND EDGE MEASUREMENT	30
3.4.2 TEST SETUP	30
3.4.3 TEST PROCEDURES	31
3.4.4. TEST RESULTS	31
3.5 CONDUCTED SPURIOUS EMISSIONS	32
3.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT	32
3.5.2 TEST PROCEDURE	32
3.5.3 TEST SETUP	32
3.5.4 TEST RESULTS	33
3.6 RADIATED EMISSION MEASUREMENT	34
3.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT	34
3.6.2 TEST PROCEDURES	34
3.6.3 DEVIATION FROM TEST STANDARD	34



Test Report No.: W7L-211220W001RF02

3.6.4 TEST SETUP	35
3.6.5 TEST RESULTS	37
3.7 PEAK TO AVERAGE RATIO	73
3.7.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT	73
3.7.2 TEST SETUP	73
3.7.3 TEST PROCEDURES	73
3.7.4 TEST RESULTS	74
4 INFORMATION ON THE TESTING LABORATORIES	75
5 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	76
APPENDIX B.....	77



Test Report No.: W7L-211220W001RF02

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
W7L-211220W001RF02	Original release	Jan. 17, 2022



1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 24 & Part 2		
STANDARD SECTION	TEST TYPE	RESULT
§2.1046	Coducted Output Power	Compliance
§24.232(c)	Equivalent Isotropic Radiated Power	Compliance
§2.1055 §24.235	Frequency Stability	Compliance
§2.1049	Occupied Bandwidth	Compliance
§24.232(d)	Peak to average ratio	Compliance
§24.238(a)(b)	Band Edge Measurements	Compliance
§2.1051 §24.238(a)(b)	Conducted Spurious Emissions	Compliance
§2.1053 §24.238(a)(b)	Radiated Spurious Emissions	Compliance

1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	UNCERTAINTY
Frequency Stability	$\pm 76.97\text{Hz}$
Radiated emissions & Radiated Power (30MHz~1GMHz)	$\pm 4.98\text{dB}$
Radiated emissions & Radiated Power (1GMHz ~6GMHz)	$\pm 4.70\text{dB}$
Radiated emissions (6GMHz ~18GMHz)	$\pm 4.60\text{dB}$
Radiated emissions (18GMHz ~40GMHz)	$\pm 4.12\text{dB}$
Conducted emissions	$\pm 4.01\text{dB}$
Occupied Channel Bandwidth	$\pm 43.58\text{KHz}$
Conducted Output power	$\pm 2.06\text{dB}$
Band Edge Measurements	$\pm 4.70\text{dB}$
Peak to average ratio	$\pm 0.76\text{dB}$

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.



1.2 TEST SITE AND INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Apr. 22,21	Apr. 21,22
EXA Signal Analyzer	KEYSIGHT	N9010A-544	MY54510355	Jun. 03,21	Jun. 02,22
Loop Antenna	Schwarzbeck	FMZB 1519B	1519B-051	Feb. 14,20	Feb. 13,23
Bilog Antenna	ETS-LINDGREN	3143B	00161965	Mar. 05,21	Mar. 04,22
Horn Antenna	ETS-LINDGREN	3117	00168692	Apr. 02,21	Apr. 01,22
Horn Antenna (18GHz-40GHz)	N/A	QWH-SL-18-40-K-SG/QMS-00361	15433	Aug. 25, 21	Aug. 24, 22
Radio Communication Analyzer	ANRITSU	MT8820C	6201465426	Feb. 25,21	Feb. 24,22
Signal Pre-Amplifier	EMSI	EMC 9135	980249	Jun. 02,21	Jun. 01,22
Signal Pre-Amplifier	EMSI	EMC 012645B	980257	Jun. 03,21	Jun. 02,22
Signal Pre-Amplifier	EMSI	EMC 184045B	980259	Apr. 22,21	Apr. 21,22
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldpn-CT0001143-1216	May. 19,20	May. 18,23
Test Software	E3	V 9.160323	N/A	N/A	N/A
Test Software	ADT	ADT_Radiated_V 7.6.15.9.2	N/A	N/A	N/A
10dB Attenuator	JFW/USA	50HF-010-SMA	1505	Jun. 03,21	Jun. 02,22
Power Meter	Anritsu	ML2495A	1506002	Apr. 07,21	Apr. 06,22
Power Sensor	Anritsu	MA2411B	1339352	May. 07,21	May. 06,22
Temperature Chamber	ESPEC	SH-242	93000855	Jun. 02,21	Jun. 01,22
MXG Analog Microwave Signal Generator	KEYSIGHT	N5183A	MY50143024	Mar. 05,21	Mar. 04,22

NOTE: 1. The calibration interval of the above test instruments is 12 months or 36 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

2. The test was performed in 3m Semi-anechoic Chamber and RF Oven Room.

3. The horn antenna is used only for the measurement of emission frequency above 1GHz if tested.

4. The FCC Site Registration No. is 525120; The Designation No. is CN1171.

2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	FE3NA0031	
BRAND NAME	Continental	
MODEL NAME	FE3NA0031	
NOMINAL VOLTAGE	EUT 4.0V	
MODULATION TYPE	GSM/GPRS: GMSK EDGE: 8PSK WCDMA: QPSK LTE Band 2: QPSK, 16QAM	
FREQUENCY RANGE	GSM/GPRS, EDGE	1850.2MHz ~ 1909.8MHz
	WCDMA	1852.4MHz ~ 1907.6MHz
	LTE Band 2 Channel Bandwidth: 1.4MHz	1850.7MHz ~ 1909.3MHz
	LTE Band 2 Channel Bandwidth: 3MHz	1851.5MHz ~ 1908.5MHz
	LTE Band 2 Channel Bandwidth: 5MHz	1852.5MHz ~ 1907.5MHz
	LTE Band 2 Channel Bandwidth: 10MHz	1855.0MHz ~ 1905.0MHz
	LTE Band 2 Channel Bandwidth: 15MHz	1857.5MHz ~ 1902.5MHz
	LTE Band 2 Channel Bandwidth: 20MHz	1860.0MHz ~ 1900.0MHz
MAX. EIRP POWER	GSM/GPRS	1172.2mW
	EDGE	468.81mW
	WCDMA	318.42mW
	LTE Band 2 Channel Bandwidth: 1.4MHz	272.27mW
	LTE Band 2 Channel Bandwidth: 3MHz	262.42mW
	LTE Band 2 Channel Bandwidth: 5MHz	263.03mW
	LTE Band 2 Channel Bandwidth: 10MHz	264.24mW
	LTE Band 2 Channel Bandwidth: 15MHz	266.07mW



	LTE Band 2 Channel Bandwidth: 20MHz	266.69mW
EMISSION DESIGNATOR	GSM/GPRS	242KGXW
	EDGE	244KG7W
	WCDMA	4M17F9W
	LTE Band 2 Channel Bandwidth: 1.4MHz	QPSK: 1M09G7D
		16QAM: 1M09W7D
	LTE Band 2 Channel Bandwidth: 3MHz	QPSK: 2M70G7D
		16QAM: 2M69W7D
	LTE Band 2 Channel Bandwidth: 5MHz	QPSK: 4M50G7D
		16QAM: 4M50W7D
	LTE Band 2 Channel Bandwidth: 10MHz	QPSK: 8M98G7D
		16QAM: 8M99W7D
	LTE Band 2 Channel Bandwidth: 15MHz	QPSK: 13M5G7D
		16QAM: 13M5W7D
	LTE Band 2 Channel Bandwidth: 20MHz	QPSK: 18M0G7D
		16QAM: 18M0W7D
ANTENNA TYPE	Dipole Antenna with 1.52dBi gain for GSM1900 Dipole Antenna with 1.52dBi gain for WCDMA II/LTE B2	
HW VERSION	P1.5	
SW VERSION	MODEMSA415M_01.11.22	
I/O PORTS	Refer to user's manual	
CABLE SUPPLIED	N/A	
EXTREME TEMPERATURE	-30-75 °C	
EXTREME VOLTAGE	EUT 3.8V - EUT 4.2V	

NOTE:

- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- The EUT incorporates a SISO function. Physically, the EUT provides one completed transmitter and one receiver.


MODULATION MODE	TX FUNCTION
GSM/GPRS/EDGE	1TX/1RX
WCDMA	1TX/1RX
LTE	1TX/1RX

- For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.



2.2 CONFIGURATION OF SYSTEM UNDER TEST

FOR RADIATION EMISSION TEST





2.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	DC source	Kikusui/JP	PMX18-5A	0000001	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	DC Line: Unshielded, Detachable 1.0m

2.4 TEST ITEM AND TEST CONFIGURATION

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case in EIRP and radiated emission was found when positioned on X-plane for GSM/EDGE/ LTE. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	DESCRIPTION
A	EUT + DC Source with GSM or WCDMA or LTE link

GSM MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
A	EIRP	512 to 810	512, 661, 810	GSM, EDGE
A	FREQUENCY STABILITY	512 to 810	512, 661, 810	GSM, EDGE
A	OCCUPIED BANDWIDTH	512 to 810	512, 661, 810	GSM, EDGE
A	PEAK TO AVERAGE RATIO	512 to 810	512, 661, 810	GSM, EDGE
A	BAND EDGE	512 to 810	512, 810	GSM, EDGE
A	CONDUCTED EMISSION	512 to 810	512, 661, 810	GSM, EDGE
A	RADIATED EMISSION	512 to 810	512, 661, 810	GSM, EDGE

WCDMA

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
A	EIRP	9262 to 9538	9262, 9400, 9538	WCDMA
A	FREQUENCY STABILITY	9262 to 9538	9262, 9400, 9538	WCDMA
A	OCCUPIED BANDWIDTH	9262 to 9538	9262, 9400, 9538	WCDMA
A	PEAK TO AVERAGE RATIO	9262 to 9538	9262, 9400, 9538	WCDMA
A	BAND EDGE	9262 to 9538	9262, 9538	WCDMA
A	CONDCUDED EMISSION	9262 to 9538	9262, 9400, 9538	WCDMA
A	RADIATED EMISSION	9262 to 9538	9262, 9400, 9538	WCDMA

LTE BAND 2 MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	CHANNEL BANDWIDTH	MODULATION	MODE
A	EIRP	18607 to 19193	18607, 18900, 19193	1.4MHz	QPSK,16QAM	1 RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3MHz	QPSK,16QAM	1 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5MHz	QPSK,16QAM	1 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10MHz	QPSK,16QAM	1 RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15MHz	QPSK,16QAM	1 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20MHz	QPSK,16QAM	1 RB / 0 RB Offset
A	FREQUENCY STABILITY	18607 to 19193	18607, 18900, 19193	1.4MHz	QPSK,16QAM	6 RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3MHz	QPSK,16QAM	15 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5MHz	QPSK,16QAM	25 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10MHz	QPSK,16QAM	50 RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15MHz	QPSK,16QAM	75 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20MHz	QPSK,16QAM	100 RB / 0 RB Offset
A	OCCUPIED BANDWIDTH	18607 to 19193	18607, 18900, 19193	1.4MHz	QPSK,16QAM	6 RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3MHz	QPSK,16QAM	15 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5MHz	QPSK,16QAM	25 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10MHz	QPSK,16QAM	50 RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15MHz	QPSK,16QAM	75 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20MHz	QPSK,16QAM	100 RB / 0 RB Offset
A	PEAK TO AVERAGE RATIO	18607 to 19193	18607, 18900, 19193	1.4MHz	QPSK,16QAM	1 RB / 0 RB Offset 6 RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3MHz	QPSK,16QAM	1 RB / 0 RB Offset 15 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5MHz	QPSK,16QAM	1 RB / 0 RB Offset 25 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10MHz	QPSK,16QAM	1 RB / 0 RB Offset 50 RB / 0 RB Offset



**BUREAU
VERITAS**

Test Report No.: W7L-211220W001RF02

		18675 to 19125	18675, 18900, 19125	15MHz	QPSK,16QAM	1 RB / 0 RB Offset 75 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20MHz	QPSK,16QAM	1 RB / 0 RB Offset 100 RB / 0 RB Offset
A	BAND EDGE	18607 to 19193	18607	1.4MHz	QPSK,16QAM	1 RB / 0 RB Offset 6 RB / 0 RB Offset
			19193	1.4MHz	QPSK,16QAM	1 RB / 5 RB Offset 6 RB / 0 RB Offset
		18615 to 19185	18615	3MHz	QPSK,16QAM	1 RB / 0 RB Offset 15 RB / 0 RB Offset
			19185	3MHz	QPSK,16QAM	1 RB / 14 RB Offset 15 RB / 0 RB Offset
		18625 to 19175	18625	5MHz	QPSK,16QAM	1 RB / 0 RB Offset 25 RB / 0 RB Offset
			19175	5MHz	QPSK,16QAM	1 RB / 24 RB Offset 25 RB / 0 RB Offset
		18650 to 19150	18650	10MHz	QPSK,16QAM	1 RB / 0 RB Offset 50 RB / 0 RB Offset
			19150	10MHz	QPSK,16QAM	1 RB / 49 RB Offset 50 RB / 0 RB Offset
		18675 to 19125	18675	15MHz	QPSK,16QAM	1 RB / 0 RB Offset 75 RB / 0 RB Offset
			19125	15MHz	QPSK,16QAM	1 RB / 74 RB Offset 75 RB / 0 RB Offset
		18700 to 19100	18700	20MHz	QPSK,16QAM	1 RB / 0 RB Offset 100 RB / 0 RB Offset
			19100	20MHz	QPSK,16QAM	1 RB / 99 RB Offset 100 RB / 0 RB Offset
A	CONDCUDET D EMISSION	18607 to 19193	18607, 18900, 19193	1.4MHz	QPSK,16QAM	1 RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3MHz	QPSK,16QAM	1 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5MHz	QPSK,16QAM	1 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10MHz	QPSK,16QAM	1 RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15MHz	QPSK,16QAM	1 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20MHz	QPSK,16QAM	1 RB / 0 RB Offset
A	RADIATED EMISSION	18607 to 19193	18900	1.4MHz	QPSK	1 RB / 0 RB Offset
		18615 to 19185	18900	3MHz	QPSK	1 RB / 0 RB Offset
		18625 to 19175	18900	5MHz	QPSK	1 RB / 0 RB Offset
		18650 to 19150	18607, 18900, 19193	10MHz	QPSK	1 RB / 0 RB Offset
		18675 to 19125	18900	15MHz	QPSK	1 RB / 0 RB Offset
		18700 to 19100	18900	20MHz	QPSK	1 RB / 0 RB Offset

TEST CONDITION:

TEST ITEM	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
EIRP	25deg. C, 57%RH	EUT 4.0V	Jace Hu
FREQUENCY STABILITY	23deg. C, 61%RH	EUT 4.0V	James Fu
OCCUPIED BANDWIDTH	23deg. C, 61%RH	EUT 4.0V	James Fu
PEAK TO AVERAGE RATIO	23deg. C, 61%RH	EUT 4.0V	James Fu
BAND EDGE	23deg. C, 61%RH	EUT 4.0V	James Fu
CONDCUDED EMISSION	23deg. C, 61%RH	EUT 4.0V	James Fu
RADIATED EMISSION	23deg. C, 70%RH	EUT 4.0V	Jace Hu

2.5 EUT OPERATING CONDITIONS

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

2.6 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 24

KDB 971168 D01 Power Meas License Digital Systems v03r01

ANSI/TIA/EIA-603-D

ANSI/TIA/EIA-603-E

ANSI C63.26-2015

NOTE: All test items have been performed and recorded as per the above standards.

3 TEST TYPES AND RESULTS

3.1 OUTPUT POWER MEASUREMENT

3.1.1 LIMITS OF OUTPUT POWER MEASUREMENT

Mobile and portable stations are limited to 2 watts EIRP.

3.1.2 TEST PROCEDURES

EIRP MEASUREMENT:

Per KDB 971168 D01 Power Meas License Digital Systems v03r01 or subclause 5.2.5.5 of ANSI C63.26-2015, the relevant equation for determining the ERP or EIRP from the conducted RF output power measured using the guidance provided above is:

$$\text{ERP or EIRP} = P_{\text{Meas}} + G_T - L_C$$

Where:

ERP or EIRP = effective radiated power or equivalent isotropically radiated power, respectively

(expressed in the same units as P_{Meas} , typically dBW or dBm);

P_{Meas} = measured transmitter output power or PSD, in dBm or dBW;

G_T = gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP);

L_C = signal attenuation in the connecting cable between the transmitter and antenna, in dB.


CONDUCTED POWER MEASUREMENT:

The EUT was set up for the maximum power with WCDMA link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

3.1.3 TEST SETUP

EIRP / ERP Measurement:

CONDUCTED POWER MEASUREMENT:



3.1.4 TEST RESULTS

CONDUCTED OUTPUT POWER (dBm)

Band	GSM1900			Max. Tune-up Power
Channel	512	661	810	
Frequency	1850.2	1880	1909.8	
GPRS (GMSK, 1Tx-slot)	29.13	29.17	29.12	30.5
GPRS (GMSK, 2Tx-slot)	27.44	27.42	27.48	27.5
GPRS (GMSK, 3Tx-slot)	25.57	25.54	25.63	26.0
GPRS (GMSK, 4Tx-slot)	24.42	24.43	24.47	24.5
EDGE (8PSK, 1Tx-slot)	25.06	25.19	25.13	26.5
EDGE (8PSK, 2Tx-slot)	23.57	23.62	23.57	24.5
EDGE (8PSK, 3Tx-slot)	22.47	22.76	22.61	23.5
EDGE (8PSK, 4Tx-slot)	21.68	21.62	21.57	22.5

Band	WCDMA II			Max. Tune-up Power
Channel	9262	9400	9538	
Frequency	1852.4	1880	1907.6	
RMC 12.2K	23.43	23.44	23.51	24.5
HSDPA Subtest-1	22.39	22.43	22.46	23.5
HSDPA Subtest-2	22.43	22.49	22.54	23.5
HSDPA Subtest-3	22.18	22.21	22.22	23.0
HSDPA Subtest-4	22.14	22.16	22.29	23.0
DC-HSDPA Subtest-1	22.45	22.47	22.52	23.5
DC-HSDPA Subtest-2	22.38	22.42	22.45	23.5
DC-HSDPA Subtest-3	22.08	22.14	22.19	23.0
DC-HSDPA Subtest-4	22.15	22.18	22.19	23.0
HSUPA Subtest-1	22.35	22.42	22.42	23.5
HSUPA Subtest-2	20.49	20.46	20.54	21.5
HSUPA Subtest-3	21.31	21.38	21.38	22.5
HSUPA Subtest-4	20.47	20.44	20.52	21.5
HSUPA Subtest-5	22.31	22.35	22.38	23.5



**BUREAU
VERITAS**

Test Report No.: W7L-211220W001RF02

LTE BAND 2

Band/BW	Modulation	RB Size	RB Offset	Low CH 18607	Mid CH 18900	High CH 19193	MPR
				Frequency 1850.7 MHz	Frequency 1880 MHz	Frequency 1909.3 MHz	
2/ 1.4	QPSK	1	0	22.62	22.64	22.57	0
		1	2	22.63	22.62	22.61	0
		1	5	22.70	22.67	22.64	0
		3	0	22.68	22.68	22.76	0
		3	1	22.83	22.82	22.71	0
		3	3	22.78	22.81	22.82	0
		6	0	21.86	21.82	21.82	1
	16QAM	1	0	22.07	22.08	22.03	1
		1	2	22.02	21.96	22.03	1
		1	5	22.05	22.07	22.11	1
		3	0	21.79	21.77	21.81	1
		3	1	21.71	21.87	21.79	1
		3	3	21.82	21.83	21.88	1
		6	0	20.79	20.84	20.75	2

Band/BW	Modulation	RB Size	RB Offset	Low CH 18615	Mid CH 18900	High CH 19185	MPR
				Frequency 1851.5 MHz	Frequency 1880 MHz	Frequency 1908.5 MHz	
2/ 3	QPSK	1	0	22.64	22.66	22.56	0
		1	7	22.59	22.63	22.61	0
		1	14	22.66	22.67	22.64	0
		8	0	21.67	21.71	21.76	1
		8	3	21.76	21.82	21.73	1
		8	7	21.75	21.88	21.86	1
		15	0	21.83	21.83	21.76	1
	16QAM	1	0	22.04	22.14	22.06	1
		1	7	21.99	21.99	22.01	1
		1	14	22.08	22.07	22.11	1
		8	0	20.75	20.78	20.81	2
		8	3	20.76	20.82	20.82	2
		8	7	20.84	20.81	20.84	2
		15	0	20.79	20.78	20.78	2

Band/BW	Modulation	RB Size	RB Offset	Low CH 18625	Mid CH 18900	High CH 19175	MPR
				Frequency 1852.5 MHz	Frequency 1880 MHz	Frequency 1907.5 MHz	
2/ 5	QPSK	1	0	22.65	22.61	22.57	0
		1	12	22.64	22.60	22.61	0
		1	24	22.67	22.66	22.68	0
		12	0	21.70	21.71	21.73	1
		12	6	21.76	21.83	21.74	1
		12	13	21.79	21.84	21.87	1
		25	0	21.81	21.86	21.79	1
	16QAM	1	0	22.05	22.10	22.06	1
		1	12	21.96	22.02	22.00	1
		1	24	22.08	22.07	22.10	1
		12	0	20.75	20.76	20.78	2
		12	6	20.73	20.86	20.78	2
		12	13	20.79	20.83	20.87	2
		25	0	20.79	20.79	20.75	2



BUREAU
VERITAS

Test Report No.: W7L-211220W001RF02

Band/BW	Modulation	RB Size	RB Offset	Low CH 18650	Mid CH 18900	High CH 19150	MPR
				Frequency 1855 MHz	Frequency 1880 MHz	Frequency 1905 MHz	
2/ 10	QPSK	1	0	22.62	22.64	22.57	0
		1	24	22.64	22.60	22.62	0
		1	49	22.64	22.70	22.64	0
		25	0	21.71	21.70	21.76	1
		25	12	21.82	21.77	21.74	1
		25	25	21.77	21.81	21.86	1
		50	0	21.86	21.86	21.76	1
	16QAM	1	0	22.05	22.07	22.02	1
		1	24	22.01	21.98	22.03	1
		1	49	22.08	22.08	22.07	1
		25	0	20.77	20.74	20.84	2
		25	12	20.77	20.80	20.83	2
		25	25	20.78	20.84	20.84	2
		50	0	20.83	20.78	20.79	2



BUREAU
VERITAS

Test Report No.: W7L-211220W001RF02

Band/BW	Modulation	RB Size	RB Offset	Low CH 18675	Mid CH 18900	High CH 19125	MPR
				Frequency 1857.5 MHz	Frequency 1880 MHz	Frequency 1902.5 MHz	
2/ 15	QPSK	1	0	22.69	22.64	22.54	0
		1	37	22.62	22.65	22.57	0
		1	74	22.70	22.73	22.65	0
		36	0	21.68	21.71	21.77	1
		36	19	21.83	21.82	21.74	1
		36	39	21.75	21.82	21.86	1
		75	0	21.86	21.84	21.81	1
	16QAM	1	0	22.09	22.14	22.02	1
		1	37	22.00	21.99	22.03	1
		1	74	22.04	22.13	22.09	1
		36	0	20.81	20.74	20.85	2
		36	19	20.71	20.84	20.79	2
		36	39	20.83	20.82	20.87	2
		75	0	20.84	20.81	20.72	2

Band/BW	Modulation	RB Size	RB Offset	Low CH 18700	Mid CH 18900	High CH 19100	MPR
				Frequency 1860 MHz	Frequency 1880 MHz	Frequency 1900 MHz	
2/ 20	QPSK	1	0	22.70	22.68	22.62	0
		1	50	22.66	22.68	22.63	0
		1	99	22.72	22.74	22.69	0
		50	0	21.74	21.76	21.78	1
		50	25	21.84	21.84	21.79	1
		50	50	21.83	21.89	21.88	1
		100	0	21.87	21.88	21.84	1
	16QAM	1	0	22.12	22.15	22.08	1
		1	50	22.04	22.04	22.05	1
		1	99	22.10	22.15	22.12	1
		50	0	20.83	20.82	20.86	2
		50	25	20.79	20.88	20.84	2
		50	50	20.86	20.88	20.89	2
		100	0	20.85	20.86	20.80	2



**BUREAU
VERITAS**

Test Report No.: W7L-211220W001RF02

EIRP POWER (dBm)

GSM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
512	1850.2	29.13	1.52	30.65	1161.45	2
661	1880.0	29.17	1.52	30.69	1172.2	2
810	1909.8	29.12	1.52	30.64	1158.78	2

EDGE

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
512	1850.2	25.06	1.52	26.58	454.99	2
661	1880.0	25.19	1.52	26.71	468.81	2
810	1909.8	25.13	1.52	26.65	462.38	2

WCDMA

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
9662	1852.4	23.43	1.52	24.95	312.61	2
9800	1880	23.44	1.52	24.96	313.33	2
9938	1907.6	23.51	1.52	25.03	318.42	2



LTE BAND 2

CHANNEL BANDWIDTH: 1.4MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18607	1850.7	22.83	1.52	24.35	272.27	2
18900	1880.0	22.82	1.52	24.34	271.64	2
19193	1908.3	22.82	1.52	24.34	271.64	2

CHANNEL BANDWIDTH: 1.4MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18607	1850.7	22.07	1.52	23.59	228.56	2
18900	1880.0	22.08	1.52	23.6	229.09	2
19193	1908.3	22.11	1.52	23.63	230.67	2

CHANNEL BANDWIDTH: 3MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18615	1851.5	22.66	1.52	24.18	261.82	2
18900	1880.0	22.67	1.52	24.19	262.42	2
19185	1908.5	22.64	1.52	24.16	260.62	2

CHANNEL BANDWIDTH: 3MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18615	1851.5	22.08	1.52	23.6	229.09	2
18900	1880.0	22.14	1.52	23.66	232.27	2
19185	1908.5	22.11	1.52	23.63	230.67	2



CHANNEL BANDWIDTH: 5MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _{T-Lc} (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18625	1852.5	22.67	1.52	24.19	262.42	2
18900	1880.0	22.66	1.52	24.18	261.82	2
19175	1907.5	22.68	1.52	24.2	263.03	2

CHANNEL BANDWIDTH: 5MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _{T-Lc} (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18625	1852.5	22.08	1.52	23.6	229.09	2
18900	1880.0	22.1	1.52	23.62	230.14	2
19175	1907.5	22.1	1.52	23.62	230.14	2

CHANNEL BANDWIDTH: 10MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _{T-Lc} (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18650	1855.0	22.64	1.52	24.16	260.62	2
18900	1880.0	22.7	1.52	24.22	264.24	2
19150	1905.0	22.64	1.52	24.16	260.62	2

CHANNEL BANDWIDTH: 10MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _{T-Lc} (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18650	1855.0	22.08	1.52	23.6	229.09	2
18900	1880.0	22.08	1.52	23.6	229.09	2
19150	1905.0	22.07	1.52	23.59	228.56	2



BUREAU
VERITAS

Test Report No.: W7L-211220W001RF02

CHANNEL BANDWIDTH: 15MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _{T-LC} (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18675	1857.5	22.7	1.52	24.22	264.24	2
18900	1880.0	22.73	1.52	24.25	266.07	2
19125	1902.5	22.65	1.52	24.17	261.22	2

CHANNEL BANDWIDTH: 15MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _{T-LC} (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18675	1857.5	22.09	1.52	23.61	229.61	2
18900	1880.0	22.14	1.52	23.66	232.27	2
19125	1902.5	22.09	1.52	23.61	229.61	2

CHANNEL BANDWIDTH: 20MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _{T-LC} (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18700	1860	22.72	1.52	24.24	265.46	2
18900	1880	22.74	1.52	24.26	266.69	2
19100	1900	22.69	1.52	24.21	263.63	2

CHANNEL BANDWIDTH: 20MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _{T-LC} (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18700	1860	22.12	1.52	23.64	231.21	2
18900	1880	22.15	1.52	23.67	232.81	2
19100	1900	22.12	1.52	23.64	231.21	2

3.2 FREQUENCY STABILITY MEASUREMENT

3.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT


The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

3.2.2 TEST PROCEDURE

- Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the $\pm 0.5^{\circ}\text{C}$ during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the communication simulator.

3.2.3 TEST SETUP





Test Report No.: W7L-211220W001RF02

3.2.4 TEST RESULTS

Please Refer to Appendix B Of this test report.




3.3 OCCUPIED BANDWIDTH MEASUREMENT

3.3.1 TEST PROCEDURES

The EUT makes a call to the communication simulator. All measurements were done at low, middle and high operational frequency range. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

3.3.2 TEST SETUP





Test Report No.: W7L-211220W001RF02

3.3.3 TEST RESULTS

Please Refer to Appendix B Of this test report.




3.4 BAND EDGE MEASUREMENTC

3.4.1 LIMITS OF BAND EDGE MEASUREMENT

Power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

3.4.2 TEST SETUP



3.4.3 TEST PROCEDURES

- a. All measurements were done at low and high operational frequency range.
- b. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz.
RBW of the spectrum is 10kHz and VBW of the spectrum is 30kHz (LTE bandwidth for (1.4M/3M/5M/10M/15M/20M)1RB/0RB&1RB/MAXRB).
- c. The center frequency of spectrum is the band edge frequency and span is 10MHz.
RBW of the spectrum is 100kHz and VBW of the spectrum is 300kHz (WCDMA).
- d. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz.
RBW of the spectrum is $\geq 1\% \cdot \text{EBW}$ kHz and VBW of the spectrum is $3 \cdot \text{RBW}$ kHz. (LTE bandwidth 1.4M/3M/5M/10M/15M/20MHz).
- e. Record the max trace plot into the test report.

3.4.4. TEST RESULTS

Please Refer to Appendix B Of this test report.



3.5 CONDUCTED SPURIOUS EMISSIONS


3.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13dBm .

3.5.2 TEST PROCEDURE

- a. The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- b. Measuring frequency range is from 9kHz up to a frequency including its 10th harmonic. 10dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz is used for conducted emission measurement.

3.5.3 TEST SETUP





Test Report No.: W7L-211220W001RF02

3.5.4 TEST RESULTS

NOTE : The 9K~30MHz amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

Please Refer to Appendix B Of this test report.

3.6 RADIATED EMISSION MEASUREMENT

3.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13dBm .

3.6.2 TEST PROCEDURES

- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value " of step a. Record the power level of S.G
- c. $\text{EIRP} = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}.$


NOTE: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.

3.6.3 DEVIATION FROM TEST STANDARD


No deviation

3.6.4 TEST SETUP


< Frequency Range below 30MHz >



< Frequency Range 30MHz~1GHz >



<Frequency Range above 1GHz>



Note: Above 1G is a directional antenna depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).



**BUREAU
VERITAS**

Test Report No.: W7L-211220W001RF02

3.6.5 TEST RESULTS

NOTE : The 9K~30MHz amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

BELOW 1GHz WORST-CASE DATA


30 MHz – 1GHz data:

LTE Band 2

CHANNEL BANDWIDTH: 20MHz / QPSK


MODE	TX channel 18900	FREQUENCY RANGE	Below 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	30.000	-32.52	-52.82	-13.00	-19.52	20.30	Peak	Horizontal
2		55.220	-34.63	-42.71	-13.00	-21.63	8.08	Peak	Horizontal
3		87.230	-38.23	-46.06	-13.00	-25.23	7.83	Peak	Horizontal
4		234.670	-45.74	-58.27	-13.00	-32.74	12.53	Peak	Horizontal
5		440.310	-41.92	-59.55	-13.00	-28.92	17.63	Peak	Horizontal
6		689.600	-42.61	-65.10	-13.00	-29.61	22.49	Peak	Horizontal



MODE	TX channel 18900	FREQUENCY RANGE	Below 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	30.970	-34.06	-53.83	-13.00	-21.06	19.77	Peak	Vertical
2		55.220	-34.39	-42.82	-13.00	-21.39	8.43	Peak	Vertical
3		88.200	-38.98	-47.44	-13.00	-25.98	8.46	Peak	Vertical
4		233.700	-46.76	-59.81	-13.00	-33.76	13.05	Peak	Vertical
5		310.330	-43.10	-58.33	-13.00	-30.10	15.23	Peak	Vertical
6		444.190	-40.88	-58.92	-13.00	-27.88	18.04	Peak	Vertical



ABOVE 1GHz


Note: For higher frequency, the emission is too low to be detected.

EDGE 1900:

CH 512


MODE	TX channel 512	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	3698.000	-47.85	-56.63	-13.00	-34.85	8.78	Peak	Horizontal
2		5550.600	-49.24	-59.43	-13.00	-36.24	10.19	Peak	Horizontal



MODE	TX channel 512	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			


	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	3698.000	-47.59	-56.84	-13.00	-34.59	9.25	Peak	Vertical
2	5550.600	-49.52	-59.42	-13.00	-36.52	9.90	Peak	Vertical



CH 661


MODE	TX channel 661	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3755.000	-48.76	-57.61	-13.00	-35.76	8.85	Peak	Horizontal
2 PP	5640.000	-48.10	-58.58	-13.00	-35.10	10.48	Peak	Horizontal



MODE	TX channel 661	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	3755.000	-47.93	-57.20	-13.00	-34.93	9.27	Peak	Vertical
2		5640.000	-48.97	-59.22	-13.00	-35.97	10.25	Peak	Vertical






BUREAU
VERITAS

Test Report No.: W7L-211220W001RF02

CH 810


MODE	TX channel 810	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3819.600	-47.54	-56.45	-13.00	-34.54	8.91	Peak	Horizontal
2 PP	5729.400	-46.55	-57.33	-13.00	-33.55	10.78	Peak	Horizontal



MODE	TX channel 810	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3819.600	-48.31	-57.60	-13.00	-35.31	9.29	Peak	Vertical
2 PP	5729.400	-46.01	-56.60	-13.00	-33.01	10.59	Peak	Vertical




EDGE 1900:

CH 512


MODE	TX channel 512	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	3698.000	-49.38	-58.16	-13.00	-36.38	8.78	Peak	Horizontal
2	5550.600	-50.85	-61.04	-13.00	-37.85	10.19	Peak	Horizontal



MODE	TX channel 512	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			


	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3698.000	-48.11	-57.36	-13.00	-35.11	9.25	Peak	Vertical
2 PP	5550.600	-47.90	-57.80	-13.00	-34.90	9.90	Peak	Vertical



CH 661


MODE	TX channel 661	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3755.000	-49.25	-58.10	-13.00	-36.25	8.85	Peak	Horizontal
2 PP	5640.000	-48.22	-58.70	-13.00	-35.22	10.48	Peak	Horizontal



MODE	TX channel 661	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			


		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	3755.000	-48.08	-57.35	-13.00	-35.08	9.27	Peak	Vertical
2		5640.000	-48.61	-58.86	-13.00	-35.61	10.25	Peak	Vertical



CH 810


MODE	TX channel 810	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3819.600	-48.21	-57.12	-13.00	-35.21	8.91	Peak	Horizontal
2 PP	5729.400	-46.31	-57.09	-13.00	-33.31	10.78	Peak	Horizontal



MODE	TX channel 810	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3819.600	-48.01	-57.30	-13.00	-35.01	9.29	Peak	Vertical
2 PP	5729.400	-46.64	-57.23	-13.00	-33.64	10.59	Peak	Vertical





BUREAU
VERITAS


Test Report No.: W7L-211220W001RF02

WCDMA Band II

CH 9262


MODE	TX channel 9262	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	3698.000	-45.26	-54.04	-13.00	-32.26	8.78	Peak	Horizontal
2	5557.200	-47.95	-58.16	-13.00	-34.95	10.21	Peak	Horizontal



MODE	TX channel 9262	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			


	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	3698.000	-47.17	-56.42	-13.00	-34.17	9.25	Peak	Vertical
2	5557.200	-49.38	-59.31	-13.00	-36.38	9.93	Peak	Vertical



CH 9400


MODE	TX channel 9400	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 3755.000	-45.96	-54.81	-13.00	-32.96	8.85	Peak	Horizontal
2	5640.000	-48.65	-59.13	-13.00	-35.65	10.48	Peak	Horizontal



MODE	TX channel 9400	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			


	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	3755.000	-47.86	-57.13	-13.00	-34.86	9.27	Peak	Vertical
2	5640.000	-48.87	-59.12	-13.00	-35.87	10.25	Peak	Vertical



CH 9538


MODE	TX channel 9538	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	3815.200	-44.82	-53.73	-13.00	-31.82	8.91	Peak	Horizontal
2	5722.800	-46.80	-57.56	-13.00	-33.80	10.76	Peak	Horizontal



MODE	TX channel 9538	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3815.200	-47.82	-57.11	-13.00	-34.82	9.29	Peak	Vertical
2 PP	5722.800	-45.77	-56.34	-13.00	-32.77	10.57	Peak	Vertical




LTE Band 2

CHANNEL BANDWIDTH: 1.4MHz / QPSK

CH18900


MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3760.000	-48.49	-57.34	-13.00	-35.49	8.85	Peak	Horizontal
2 PP	5636.000	-48.38	-58.85	-13.00	-35.38	10.47	Peak	Horizontal



MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			


	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	3755.000	-48.47	-57.74	-13.00	-35.47	9.27	Peak	Vertical
2	5640.000	-48.99	-59.24	-13.00	-35.99	10.25	Peak	Vertical



CHANNEL BANDWIDTH: 3MHz / QPSK


MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3755.000	-48.49	-57.34	-13.00	-35.49	8.85	Peak	Horizontal
2 PP	5640.000	-48.34	-58.82	-13.00	-35.34	10.48	Peak	Horizontal



MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	3760.000	-48.96	-58.23	-13.00	-35.96	9.27	Peak	Vertical
2		5636.000	-49.17	-59.40	-13.00	-36.17	10.23	Peak	Vertical





BUREAU
VERITAS


Test Report No.: W7L-211220W001RF02

CHANNEL BANDWIDTH: 5MHz / QPSK

CH18900:


MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3760.000	-49.02	-57.87	-13.00	-36.02	8.85	Peak	Horizontal
2 PP	5636.000	-47.76	-58.23	-13.00	-34.76	10.47	Peak	Horizontal



MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3755.000	-49.41	-58.68	-13.00	-36.41	9.27	Peak	Vertical
2 PP	5640.000	-48.57	-58.82	-13.00	-35.57	10.25	Peak	Vertical




CHANNEL BANDWIDTH: 10MHz / QPSK

CH18900


MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	3760.000	-48.14	-56.99	-13.00	-35.14	8.85	Peak	Horizontal
2	5636.000	-48.41	-58.88	-13.00	-35.41	10.47	Peak	Horizontal



MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			


		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	3755.000	-48.18	-57.45	-13.00	-35.18	9.27	Peak	Vertical
2		5640.000	-49.18	-59.43	-13.00	-36.18	10.25	Peak	Vertical



CHANNEL BANDWIDTH: 15MHz / QPSK


MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3755.000	-49.25	-58.10	-13.00	-36.25	8.85	Peak	Horizontal
2 PP	5640.000	-48.94	-59.42	-13.00	-35.94	10.48	Peak	Horizontal



MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3755.000	-48.35	-57.62	-13.00	-35.35	9.27	Peak	Vertical
2 PP	5640.000	-47.31	-57.56	-13.00	-34.31	10.25	Peak	Vertical




CHANNEL BANDWIDTH: 20MHz / QPSK

CH18700


MODE	TX channel 18700	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	3720.000	-48.15	-56.96	-13.00	-35.15	8.81	Peak	Horizontal
2	5579.000	-48.43	-58.71	-13.00	-35.43	10.28	Peak	Horizontal



MODE	TX channel 18700	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			


		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	3717.000	-48.58	-57.84	-13.00	-35.58	9.26	Peak	Vertical
2		5580.000	-49.67	-59.68	-13.00	-36.67	10.01	Peak	Vertical



CH18900


MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3755.000	-49.40	-58.25	-13.00	-36.40	8.85	Peak	Horizontal
2 PP	5640.000	-48.27	-58.75	-13.00	-35.27	10.48	Peak	Horizontal



MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	3760.000	-46.85	-56.12	-13.00	-33.85	9.27	Peak	Vertical
2	5636.000	-47.82	-58.05	-13.00	-34.82	10.23	Peak	Vertical






BUREAU
VERITAS

Test Report No.: W7L-211220W001RF02

CH19100


MODE	TX channel 19100	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3793.000	-47.85	-56.74	-13.00	-34.85	8.89	Peak	Horizontal
2 PP	5700.000	-44.98	-55.66	-13.00	-31.98	10.68	Peak	Horizontal



MODE	TX channel 19100	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	3800.000	-46.20	-55.48	-13.00	-33.20	9.28	Peak	Vertical
2		5693.000	-47.96	-58.41	-13.00	-34.96	10.45	Peak	Vertical




3.7 PEAK TO AVERAGE RATIO

3.7.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB

3.7.2 TEST SETUP



3.7.3 TEST PROCEDURES

1. Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1%.



Test Report No.: W7L-211220W001RF02

3.7.4 TEST RESULTS

Please Refer to Appendix B Of this test report.



BUREAU
VERITAS

Test Report No.: W7L-211220W001RF02

4 INFORMATION ON THE TESTING LABORATORIES

We, BV 7LAYERS COMMUNICATIONS TECHNOLOGY (SHENZHEN) CO., LTD., were founded in 2015 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Shenzhen EMC/RF Lab:

Tel: +86-755-88696566

Fax: +86-755-88696577

Email: customerservice.sw@bureauveritas.com

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.

5 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

Appendix B

GSM1900

PEAK-TO-AVERAGE RATIO(CCDF)

Test Result

Band	Channel	Result(dB)	Limit(dB)	Verdict
GSM1900	512	2.75	13	PASS
GSM1900	661	2.78	13	PASS
GSM1900	810	2.76	13	PASS
EGPRS1900	512	5.67	13	PASS
EGPRS1900	661	5.68	13	PASS
EGPRS1900	810	5.65	13	PASS

Test Graphs






BUREAU
VERITAS


Test Report No.: W7L-211220W001RF02



EGPRS1900-512-2



EGPRS1900-661-2




EGPRS1900-810-2



BUREAU
VERITAS

Test Report No.: W7L-211220W001RF02




26DB BANDWIDTH AND OCCUPIED BANDWIDTH

Test Result

Band	Channel	Occupied Bandwidth (MHz)	26dB Bandwidth (MHz)	Limit (MHz)	Verdict
GSM1900	512	0.24237	0.3118	---	PASS
GSM1900	661	0.24121	0.3092	---	PASS
GSM1900	810	0.24194	0.3136	---	PASS
EGPRS1900	512	0.24449	0.3063	---	PASS
EGPRS1900	661	0.24439	0.3030	---	PASS
EGPRS1900	810	0.24033	0.2964	---	PASS

Test Graphs






BUREAU
VERITAS


Test Report No.: W7L-211220W001RF02



EGPRS1900-512-2-0.3063



EGPRS1900-661-2-0.3030




EGPRS1900-810-2-0.2964



BUREAU
VERITAS

Test Report No.: W7L-211220W001RF02






Test Report No.: W7L-211220W001RF02

BAND EDGE

Test Result

Band	Channel	Freq (MHz)	Result (dBm)	Limit(dBm)	Verdict
GSM1900	512	1849.98	-18.54	-13	PASS
GSM1900	810	1910.02	-17.21	-13	PASS
EGPRS1900	512	1849.98	-24.92	-13	PASS
EGPRS1900	810	1910.02	-22.91	-13	PASS


Test Graphs






BUREAU
VERITAS

Test Report No.: W7L-211220W001RF02



EGPRS1900-810-2




CONDUCTED SPURIOUS EMISSION

Test Result

Band	Channel	Frequency Range(MHz)	Max.Freq. (MHz)	Result (dBm)	Limit (dBm)	Verdict
GSM1900	512	30~1000MHz	950.98	-47.67	-13	PASS
GSM1900	512	1000~3000MHz	2641.2	-46.93	-13	PASS
GSM1900	512	3000~20000MHz	3838.67	-43.88	-13	PASS
GSM1900	661	30~1000MHz	922.3	-48.4	-13	PASS
GSM1900	661	1000~3000MHz	2684.73	-46.99	-13	PASS
GSM1900	661	3000~20000MHz	3736.67	-43.85	-13	PASS
GSM1900	810	30~1000MHz	845.45	-46.74	-13	PASS
GSM1900	810	1000~3000MHz	2629.33	-46.95	-13	PASS
GSM1900	810	3000~20000MHz	3752.53	-43.9	-13	PASS
EGPRS1900	512	30~1000MHz	899.67	-47.35	-13	PASS
EGPRS1900	512	1000~3000MHz	2618.67	-46.98	-13	PASS
EGPRS1900	512	3000~20000MHz	3769.53	-43.88	-13	PASS
EGPRS1900	661	30~1000MHz	933.68	-47.59	-13	PASS
EGPRS1900	661	1000~3000MHz	2635.27	-46.89	-13	PASS
EGPRS1900	661	3000~20000MHz	3782.57	-43.7	-13	PASS
EGPRS1900	810	30~1000MHz	836.04	-47.95	-13	PASS
EGPRS1900	810	1000~3000MHz	2657.93	-46.86	-13	PASS
EGPRS1900	810	3000~20000MHz	3732.7	-43.81	-13	PASS

Test Graphs






BUREAU
VERITAS

Test Report No.: W7L-211220W001RF02



GSM1900-661-0-30~1000MHz



GSM1900-661-0-1000~3000MHz



GSM1900-661-0-3000~20000MHz




BUREAU
VERITAS

Test Report No.: W7L-211220W001RF02



GSM1900-810-0-30~1000MHz



GSM1900-810-0-1000~3000MHz



GSM1900-810-0-3000~20000MHz




BUREAU
VERITAS

Test Report No.: W7L-211220W001RF02



EGPRS1900-512-2-30~1000MHz



EGPRS1900-512-2-1000~3000MHz



EGPRS1900-512-2-3000~20000MHz




BUREAU
VERITAS

Test Report No.: W7L-211220W001RF02



EGPRS1900-661-2-30~1000MHz



EGPRS1900-661-2-1000~3000MHz



EGPRS1900-661-2-3000~20000MHz




BUREAU
VERITAS

Test Report No.: W7L-211220W001RF02



EGPRS1900-810-2-30~1000MHz



EGPRS1900-810-2-1000~3000MHz



EGPRS1900-810-2-3000~20000MHz



BUREAU
VERITAS

Test Report No.: W7L-211220W001RF02



FREQUENCY STABILITY

Test Result

Voltage							
Band	Channel	Voltage [Vdc]	Temperature (°C)	Deviation (Hz)	Deviation (ppm)	Limit (ppm)	Verdict
GSM1900	512	VL	NT	29.15	0.015755	±2.5	PASS
GSM1900	512	VN	NT	39.20	0.021187	±2.5	PASS
GSM1900	512	VH	NT	28.06	0.015166	±2.5	PASS
GSM1900	661	VL	NT	44.23	0.023527	±2.5	PASS
GSM1900	661	VN	NT	37.16	0.019766	±2.5	PASS
GSM1900	661	VH	NT	36.03	0.019165	±2.5	PASS
GSM1900	810	VL	NT	31.67	0.016583	±2.5	PASS
GSM1900	810	VN	NT	41.29	0.021620	±2.5	PASS
GSM1900	810	VH	NT	29.48	0.015436	±2.5	PASS
EGPRS1900	512	VL	NT	22.37	0.012091	±2.5	PASS
EGPRS1900	512	VN	NT	27.54	0.014885	±2.5	PASS
EGPRS1900	512	VH	NT	21.70	0.011728	±2.5	PASS
EGPRS1900	661	VL	NT	30.28	0.016106	±2.5	PASS
EGPRS1900	661	VN	NT	27.99	0.014888	±2.5	PASS
EGPRS1900	661	VH	NT	38.19	0.020314	±2.5	PASS
EGPRS1900	810	VL	NT	27.06	0.014169	±2.5	PASS
EGPRS1900	810	VN	NT	31.45	0.016468	±2.5	PASS
EGPRS1900	810	VH	NT	23.92	0.012525	±2.5	PASS

Temperature							
Band	Channel	Voltage [Vdc]	Temperature (°C)	Deviation (Hz)	Deviation (ppm)	Limit (ppm)	Verdict
GSM1900	512	NV	-30	36.74	0.019857	±2.5	PASS
GSM1900	512	NV	-20	29.67	0.016036	±2.5	PASS
GSM1900	512	NV	-10	35.81	0.019355	±2.5	PASS
GSM1900	512	NV	0	36.74	0.019857	±2.5	PASS
GSM1900	512	NV	10	29.61	0.016004	±2.5	PASS
GSM1900	512	NV	20	32.58	0.017609	±2.5	PASS
GSM1900	512	NV	30	27.83	0.015042	±2.5	PASS
GSM1900	512	NV	40	32.83	0.017744	±2.5	PASS
GSM1900	512	NV	50	38.71	0.020922	±2.5	PASS



BUREAU
VERITAS

Test Report No.: W7L-211220W001RF02

GSM1900	661	NV	-30	27.70	0.014734	±2.5	PASS
GSM1900	661	NV	-20	33.74	0.017947	±2.5	PASS
GSM1900	661	NV	-10	26.60	0.014149	±2.5	PASS
GSM1900	661	NV	0	42.07	0.022378	±2.5	PASS
GSM1900	661	NV	10	39.68	0.021106	±2.5	PASS
GSM1900	661	NV	20	36.94	0.019649	±2.5	PASS
GSM1900	661	NV	30	44.23	0.023527	±2.5	PASS
GSM1900	661	NV	40	38.90	0.020691	±2.5	PASS
GSM1900	661	NV	50	36.00	0.019149	±2.5	PASS
GSM1900	810	NV	-30	26.05	0.013640	±2.5	PASS
GSM1900	810	NV	-20	33.93	0.017766	±2.5	PASS
GSM1900	810	NV	-10	26.57	0.013912	±2.5	PASS
GSM1900	810	NV	0	35.39	0.018531	±2.5	PASS
GSM1900	810	NV	10	17.79	0.009315	±2.5	PASS
GSM1900	810	NV	20	29.15	0.015263	±2.5	PASS
GSM1900	810	NV	30	29.57	0.015483	±2.5	PASS
GSM1900	810	NV	40	26.51	0.013881	±2.5	PASS
GSM1900	810	NV	50	36.74	0.019238	±2.5	PASS
EGPRS1900	512	NV	-30	24.54	0.013263	±2.5	PASS
EGPRS1900	512	NV	-20	30.41	0.016436	±2.5	PASS
EGPRS1900	512	NV	-10	28.28	0.015285	±2.5	PASS
EGPRS1900	512	NV	0	32.51	0.017571	±2.5	PASS
EGPRS1900	512	NV	10	39.81	0.021517	±2.5	PASS
EGPRS1900	512	NV	20	35.74	0.019317	±2.5	PASS
EGPRS1900	512	NV	30	30.35	0.016404	±2.5	PASS
EGPRS1900	512	NV	40	31.64	0.017101	±2.5	PASS
EGPRS1900	512	NV	50	23.37	0.012631	±2.5	PASS
EGPRS1900	661	NV	-30	33.55	0.017846	±2.5	PASS
EGPRS1900	661	NV	-20	36.87	0.019612	±2.5	PASS
EGPRS1900	661	NV	-10	32.74	0.017415	±2.5	PASS
EGPRS1900	661	NV	0	29.02	0.015436	±2.5	PASS
EGPRS1900	661	NV	10	38.90	0.020691	±2.5	PASS
EGPRS1900	661	NV	20	32.58	0.017330	±2.5	PASS
EGPRS1900	661	NV	30	36.81	0.019580	±2.5	PASS
EGPRS1900	661	NV	40	39.71	0.021122	±2.5	PASS



BUREAU
VERITAS

Test Report No.: W7L-211220W001RF02

EGPRS19 00	661	NV	50	25.96	0.013809	±2.5	PASS
EGPRS19 00	810	NV	-30	26.02	0.013624	±2.5	PASS
EGPRS19 00	810	NV	-20	25.41	0.013305	±2.5	PASS
EGPRS19 00	810	NV	-10	15.66	0.008200	±2.5	PASS
EGPRS19 00	810	NV	0	20.50	0.010734	±2.5	PASS
EGPRS19 00	810	NV	10	22.15	0.011598	±2.5	PASS
EGPRS19 00	810	NV	20	28.51	0.014928	±2.5	PASS
EGPRS19 00	810	NV	30	28.64	0.014996	±2.5	PASS
EGPRS19 00	810	NV	40	16.79	0.008791	±2.5	PASS
EGPRS19 00	810	NV	50	16.79	0.008791	±2.5	PASS



Test Report No.: W7L-211220W001RF02

WCDMA

APPENDIX B: PEAK-TO-AVERAGE RATIO

Test Result

Band	Channel	Peak-to-Average Ratio(dB)	Limit(dBm)	Verdict
Band2	9262	3.12	13	PASS
Band2	9400	2.98	13	PASS
Band2	9538	2.93	13	PASS


Test Graphs





BUREAU
VERITAS

Test Report No.: W7L-211220W001RF02



26DB BANDWIDTH AND OCCUPIED BANDWIDTH

Test Result

Band	Channel	Occupied Bandwidth (MHz)	26dB Bandwidth (MHz)	Limit(MHz)	Verdict
Band2	9262	4.1568	4.723	---	PASS
Band2	9400	4.1682	4.740	---	PASS
Band2	9538	4.1642	4.753	---	PASS

Test Graphs





BUREAU
VERITAS

Test Report No.: W7L-211220W001RF02






Test Report No.: W7L-211220W001RF02

BAND EDGE

Test Result

Band	Channel	Frequency (MHz)	Result (dBm)	Limit(dBm)	Verdict
Band2	9262	1849.86	-27.26	-13	PASS
Band2	9538	1910.00	-26.21	-13	PASS

Test Graphs



CONDUCTED SPURIOUS EMISSION

Test Result

Band	Channel	Frequency Range (Mhz)	Frequency (dBm)	Result (dBm)	Limit (dBm)	Verdict
Band2	9262	30~1000MHz	927.83	-48.42	-13	PASS
Band2	9262	1000~3000MHz	2632.27	-46.97	-13	PASS
Band2	9262	3000~20000MHz	3706.63	-43.11	-13	PASS
Band2	9400	30~1000MHz	887.35	-48.59	-13	PASS
Band2	9400	1000~3000MHz	2662.93	-47.03	-13	PASS
Band2	9400	3000~20000MHz	3758.2	-42.87	-13	PASS
Band2	9538	30~1000MHz	810.69	-48.7	-13	PASS
Band2	9538	1000~3000MHz	2646.13	-47.03	-13	PASS
Band2	9538	3000~20000MHz	3813.17	-42.78	-13	PASS

Test Graphs






BUREAU
VERITAS


Test Report No.: W7L-211220W001RF02



Band2-9400-30~1000MHz



Band2-9400-1000~3000MHz



Band2-9400-3000~20000MHz

BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

No.B102, Dazu Chuangxin Mansion, North of Beihuan
Avenue, North Area, Hi-Tech Industrial Park, Nanshan
District, Shenzhen, Guangdong, China

Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email: customerservice.sw@bureauveritas.com




BUREAU
VERITAS


Test Report No.: W7L-211220W001RF02



Band2-9538-30~1000MHz



Band2-9538-1000~3000MHz



Band2-9538-3000~20000MHz

BV 7Layers Communications Technology
(Shenzhen) Co., Ltd

No.B102, Dazu Chuangxin Mansion, North of Beihuan
Avenue, North Area, Hi-Tech Industrial Park, Nanshan
District, Shenzhen, Guangdong, China

Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email: customerservice.sw@bureauveritas.com



BUREAU
VERITAS

Test Report No.: W7L-211220W001RF02



FREQUENCY STABILITY

Test Result

Voltage							
Band	Channel	Voltage (Vdc)	Temperature (°C)	Deviation (Hz)	Deviation (ppm)	Limit (ppm)	Verdict
Band2	9262	VL	NT	11.49	0.006203	±2.5	PASS
Band2	9262	VN	NT	11.76	0.006349	±2.5	PASS
Band2	9262	VH	NT	11.54	0.006230	±2.5	PASS
Band2	9400	VL	NT	11.93	0.006346	±2.5	PASS
Band2	9400	VN	NT	11.64	0.006191	±2.5	PASS
Band2	9400	VH	NT	12.08	0.006426	±2.5	PASS
Band2	9538	VL	NT	12.06	0.006322	±2.5	PASS
Band2	9538	VN	NT	11.79	0.006181	±2.5	PASS
Band2	9538	VH	NT	11.75	0.006160	±2.5	PASS
Temperature							
Band	Channel	Voltage (Vdc)	Temperature (°C)	Deviation (Hz)	Deviation (ppm)	Limit (ppm)	Verdict
Band2	9262	NV	-30	11.47	0.006192	±2.5	PASS
Band2	9262	NV	-20	11.82	0.006381	±2.5	PASS
Band2	9262	NV	0	11.67	0.006300	±2.5	PASS
Band2	9262	NV	10	11.85	0.006397	±2.5	PASS
Band2	9262	NV	20	11.54	0.006230	±2.5	PASS
Band2	9400	NV	-30	11.94	0.006351	±2.5	PASS
Band2	9400	NV	-20	12.04	0.006404	±2.5	PASS
Band2	9400	NV	0	11.78	0.006266	±2.5	PASS
Band2	9400	NV	10	12.09	0.006431	±2.5	PASS
Band2	9400	NV	20	12.22	0.006500	±2.5	PASS
Band2	9538	NV	-30	11.54	0.006049	±2.5	PASS
Band2	9538	NV	-20	11.37	0.005960	±2.5	PASS
Band2	9538	NV	0	11.14	0.005840	±2.5	PASS
Band2	9538	NV	10	11.26	0.005903	±2.5	PASS
Band2	9538	NV	20	11.19	0.005866	±2.5	PASS