

FCC SAR TEST REPORT

FCC ID : LHJ-FE5NAR110
Equipment : FE5NAR110, FE5NAR111
Brand Name : Continental
Model Name : FE5NAR110, FE5NAR111
Applicant : Continental Automotive Systems, Inc.
21440 W Lake Cook Rd., Deer Park, IL 60010, USA
Manufacturer : Continental Automotive Systems, Inc.
21440 W Lake Cook Rd., Deer Park, IL 60010, USA
Standard : FCC 47 CFR Part 2 (2.1093)

The product was installed into G12N51RG1, G12N50RG1 (Brand Name: Continental, Model Name: G12N51RG1, G12N50RG1) during test.

The product was received on Aug. 06, 2024 and testing was started from Aug. 09, 2024 and completed on Aug. 13, 2024. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample provide by manufacturer and the test data has been evaluated in accordance with the test procedures given in 47 CFR Part 2.1093 and FCC KDB and has been pass the FCC requirement.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Laboratory, the test report shall not be reproduced except in full.



Approved by: Cona Huang / Deputy Manager



Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan

Table of Contents

1. Statement of Compliance	4
2. Guidance Applied.....	4
3. Equipment Under Test (EUT) Information.....	5
3.1 General Information	5
3.2 General LTE SAR Test and Reporting Considerations	6
3.3 General 5G NR SAR Test and Reporting Considerations	8
4. RF Exposure Limits.....	10
4.1 Uncontrolled Environment.....	10
4.2 Controlled Environment.....	10
5. Specific Absorption Rate (SAR).....	11
5.1 Introduction	11
5.2 SAR Definition.....	11
6. System Description and Setup	12
6.1 Test Site Location.....	12
6.2 E-Field Probe	13
6.3 Data Acquisition Electronics (DAE)	13
6.4 Phantom.....	14
6.5 Device Holder.....	15
7. Measurement Procedures	16
7.1 Spatial Peak SAR Evaluation.....	16
7.2 Power Reference Measurement.....	17
7.3 Area Scan	17
7.4 Zoom Scan.....	18
7.5 Volume Scan Procedures.....	18
7.6 Power Drift Monitoring.....	18
8. Test Equipment List.....	19
9. System Verification.....	20
9.1 Tissue Verification	20
9.2 System Performance Check Results.....	21
10. UMTS/LTE Output Power (Unit: dBm)	22
11. 5G NR Output Power (Unit: dBm)	44
12. SAR Test Results	56
12.1 Body SAR	57
12.2 Power Class 2 and Power Class 3 Linearity	59
13. Simultaneous Transmission Analysis.....	60
13.1 Body Exposure Conditions	60
14. Uncertainty Assessment	61
15. References.....	61
Appendix A. Plots of System Performance Check	
Appendix B. Plots of High SAR Measurement	
Appendix C. DASY Calibration Certificate	
Appendix D. Test Setup Photos	

History of this test report

Report No.	Version	Description	Issued Date
FA480602-01	01	Initial issue of report	May 21, 2025



1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) for Continental Automotive Systems, Inc., FE5NAR110, FE5NAR111, FE5NAR110, FE5NAR111, are as follows.

Equipment Class	Frequency Band	Highest SAR Summary	Highest Simultaneous Transmission 1g SAR (W/kg)
		Body (Separation 20mm)	
		1g SAR (W/kg)	
Licensed	WCDMA II	0.12	0.34
	WCDMA IV	0.21	
	WCDMA V	0.04	
	LTE Band 2	0.12	
	LTE Band 5	0.09	
	LTE Band 7	0.12	
	LTE Band 12	0.05	
	LTE Band 13	0.08	
	LTE Band 14	0.08	
	LTE Band 4/66	0.17	
	LTE Band 71	0.04	
	FR1 n5	0.08	
	FR1 n2/n25	0.12	
	FR1 n41	0.14	
	FR1 n66	0.20	
	FR1 n71	0.04	
	FR1 n77	0.06	
Date of Testing:		2025/05/09 ~ 2025/05/10	

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation and the FCC designation No. TW1190 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC test. This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg for Partial-Body 1g SAR) specified in FCC 47 CFR part 2 (2.1093), and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013 and FCC KDB publications.

Reviewed by: Jason Wang
Report Producer: Paula Chen

2. Guidance Applied

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards, the below KDB standard may not including in the TAF code without accreditation.

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2013
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- FCC KDB 865664 D02 SAR Reporting v01r02
- FCC KDB 447498 D01 General RF Exposure Guidance v06
- FCC KDB 941225 D01 3G SAR Procedures v03r01
- FCC KDB 941225 D05 SAR for LTE Devices v02r05
- FCC KDB 941225 D05A Rel.10 LTE SAR Test Guidance v01r02

3. Equipment Under Test (EUT) Information

3.1 General Information

Product Feature & Specification	
Equipment Name	FE5NAR110, FE5NAR111
Brand Name	Continental
Model Name	FE5NAR110, FE5NAR111
FCC ID	LHJ-FE5NAR110
Wireless Technology and Frequency Range	WCDMA Band II: 1850 MHz ~ 1910 MHz WCDMA Band IV: 1710 MHz ~ 1755 MHz WCDMA Band V: 824 MHz ~ 849 MHz LTE Band 2: 1850 MHz ~ 1910 MHz LTE Band 4: 1710 MHz ~ 1755 MHz LTE Band 5: 824 MHz ~ 849 MHz LTE Band 7: 2500 MHz ~ 2570 MHz LTE Band 12: 699 MHz ~ 716 MHz LTE Band 13: 777 MHz ~ 787 MHz LTE Band 14: 788 MHz ~ 798 MHz LTE Band 66: 1710 MHz ~ 1780 MHz LTE Band 71: 663 MHz ~ 698 MHz 5G NR n2 : 1850 MHz ~ 1910 MHz 5G NR n5 : 824 MHz ~ 849 MHz 5G NR n25 : 1850 MHz ~ 1915 MHz 5G NR n41 : 2496 MHz ~ 2690 MHz 5G NR n66 : 1710 MHz ~ 1780 MHz 5G NR n71 : 663 MHz ~ 698 MHz 5G NR n77: 3700 MHz ~ 3980 MHz
Mode	RMC/AMR 12.2Kbps HSDPA HSUPA DC-HSDPA LTE: QPSK, 16QAM, 64QAM 5G NR: DFT-s-OFDM/CP-OFDM, Pi/2 BPSK/QPSK/16QAM/64QAM/256QAM
HW Version	P2.0
Host Information	
Equipment Name	G12N51RG1, G12N50RG1
Brand Name	Continental
Model Name	G12N51RG1, G12N50RG1
HW Version	P7
EUT Stage	Identical Prototype
External Antenna Information	
Brand Name	Continental
Antenna type	External Front Fender Antenna of type Continental Y2XX (Composed by component PN: 86784729, 86784728)
Ant 1	Cell primary antenna (right side, passenger side). PN: 86784729.
Ant 2	Cell secondary antenna (left side, driver side). PN: 86784728.

3.2 General LTE SAR Test and Reporting Considerations

Summarized necessary items addressed in KDB 941225 D05 v02r05												
FCC ID			LHJ-FE5NAR110									
Equipment Name			FE5NAR110, FE5NAR111									
Operating Frequency Range of each LTE transmission band			LTE Band 2: 1850 MHz ~ 1910 MHz									
			LTE Band 4: 1710 MHz ~ 1755 MHz									
			LTE Band 5: 824 MHz ~ 849 MHz									
			LTE Band 7: 2500 MHz ~ 2570 MHz									
			LTE Band 12: 699 MHz ~ 716 MHz									
			LTE Band 13: 777 MHz ~ 787 MHz									
			LTE Band 14: 788 MHz ~ 798 MHz									
			LTE Band 66: 1710 MHz ~ 1780 MHz									
			LTE Band 71: 663 MHz ~ 698 MHz									
Channel Bandwidth			LTE Band 2:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz									
			LTE Band 4:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz									
			LTE Band 5:1.4MHz, 3MHz, 5MHz, 10MHz									
			LTE Band 7: 5MHz, 10MHz, 15MHz, 20MHz									
			LTE Band 12:1.4MHz, 3MHz, 5MHz, 10MHz									
			LTE Band 13: 5MHz, 10MHz									
			LTE Band 14: 5MHz, 10MHz									
			LTE Band 66:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz									
			LTE Band 71: 5MHz, 10MHz, 15MHz, 20MHz									
uplink modulations used			QPSK / 16QAM / 64QAM									
LTE Voice / Data requirements			Voice and Data									
LTE MPR permanently built-in by design			Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1, 2 and 3									
			Modulation	Channel bandwidth / Transmission bandwidth (N _{RB})						MPR (dB)		
				1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz			
			QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1		
			16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1		
			16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2		
			64 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 2		
			64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 3		
			256 QAM	≥ 1						≤ 5		
LTE A-MPR			In the base station simulator configuration, Network Setting value is set to NS_01 to disable A-MPR during SAR testing and the LTE SAR tests was transmitting on all TTI frames (Maximum TTI)									
Spectrum plots for RB configuration			A properly configured base station simulator was used for the SAR and power measurement; therefore, spectrum plots for each RB allocation and offset configuration are not included in the SAR report.									
LTE Carrier Aggregation Combinations			Intra-Band possible combinations and the detail power measurement please referred to section 10.									
LTE Carrier Aggregation Additional Information			Additional following LTE Release features are not supported: Relay, HetNet, Enhanced MIMO, eICI, WiFi Offloading, MDH, eMBMA, Cross-Carrier Scheduling, Enhanced SC-FDMA.									
Transmission (H, M, L) channel numbers and frequencies in each LTE band												
LTE Band 2												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	18607	1850.7	18615	1851.5	18625	1852.5	18650	1855	18675	1857.5	18700	1860
M	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880
H	19193	1909.3	19185	1908.5	19175	1907.5	19150	1905	19125	1902.5	19100	1900
LTE Band 4												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	19957	1710.7	19965	1711.5	19975	1712.5	20000	1715	20025	1717.5	20050	1720
M	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5
H	20393	1754.3	20385	1753.5	20375	1752.5	20350	1750	20325	1747.5	20300	1745

LTE Band 5												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)				
L	20407	824.7	20415	825.5	20425	826.5	20450	829				
M	20525	836.5	20525	836.5	20525	836.5	20525	836.5				
H	20643	848.3	20635	847.5	20625	846.5	20600	844				
LTE Band 7												
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)				
L	20775	2502.5	20800	2505	20825	2507.5	20850	2510				
M	21100	2535	21100	2535	21100	2535	21100	2535				
H	21425	2567.5	21400	2565	21375	2562.5	21350	2560				
LTE Band 12												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)				
L	23017	699.7	23025	700.5	23035	701.5	23060	704				
M	23095	707.5	23095	707.5	23095	707.5	23095	707.5				
H	23173	715.3	23165	714.5	23155	713.5	23130	711				
LTE Band 13												
	Bandwidth 5 MHz				Bandwidth 10 MHz							
	Channel #		Freq.(MHz)		Channel #		Freq.(MHz)					
L	23205		779.5		23230		782					
M	23230		782									
H	23255		784.5									
LTE Band 14												
	Bandwidth 5 MHz				Bandwidth 10 MHz							
	Channel #		Channel #		Channel #		Freq.(MHz)					
L	23305		790.5		23330		793					
M	23330		793									
H	23355		795.5									
LTE Band 66												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	131979	1710.7	131987	1711.5	131997	1712.5	132022	1715	132047	1717.5	132072	1720
M	132322	1745	132322	1745	132322	1745	132322	1745	132322	1745	132322	1745
H	132665	1779.3	132657	1778.5	132647	1777.5	132622	1775	132597	1772.5	132572	1770
LTE Band 71												
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)		
L	133147	665.5	133172	668	133197	670.5	133222	673				
M	133297	680.5	133297	680.5	133297	680.5	133297	680.5				
H	133447	695.5	133422	693	133397	690.5	133372	688				



3.3 General 5G NR SAR Test and Reporting Considerations

5G NR Information																
FCC ID		LHJ-FE5NAR110														
Equipment Name		FE5NAR110, FE5NAR111														
Operating Frequency Range of each 5G NR transmission band		5G NR n2 : 1850 MHz ~ 1910 MHz														
		5G NR n5 : 824 MHz ~ 849 MHz														
		5G NR n25 : 1850 MHz ~ 1915 MHz														
		5G NR n41 : 2496 MHz ~ 2690 MHz														
		5G NR n66 : 1710 MHz ~ 1780 MHz														
		5G NR n71 : 663 MHz ~ 698 MHz														
		5G NR n77: 3700 MHz ~ 3980 MHz														
Channel Bandwidth		5G NR n2: 5MHz, 10MHz, 15MHz, 20MHz														
		5G NR n5: 5MHz, 10MHz, 15MHz, 20MHz														
		5G NR n25: 5MHz, 10MHz, 15MHz, 20MHz														
		5G NR n41: 20MHz, 30MHz, 40MHz, 50MHz, 60MHz, 80MHz, 90MHz, 100MHz														
		5G NR n66: 5MHz, 10MHz, 15MHz, 20MHz, 30MHz, 40MHz														
		5G NR n71: 5MHz, 10MHz, 15MHz, 20MHz														
		5G NR n77: 20MHz, 30MHz, 40MHz, 50MHz, 60MHz, 70MHz, 80MHz, 90MHz, 100MHz														
SCS		FDD: SCS15KHz, TDD: SCS30KHz														
uplink modulations used		DFT-s-OFDM: PI/2 BPSK / QPSK / 16QAM / 64QAM / 256QAM CP-OFDM QPSK / 16QAM / 64QAM / 256QAM														
A-MPR (Additional MPR) disabled for SAR Testing?		Yes														
LTE Anchor Bands for n2		LTE B2/5/12/14														
LTE Anchor Bands for n5		LTE B5/66														
LTE Anchor Bands for n66		LTE B2/5/12/14														
LTE Anchor Bands for n77		LTE B2/5/7/12/14/66														
NR Band 2																
	Bandwidth 5MHz		Bandwidth 10MHz				Bandwidth 15MHz				Bandwidth 20MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)			Ch. #	Freq. (MHz)			Ch. #	Freq. (MHz)				
L	370500	1852.5	371000	1855			371500	1857.5			372000	1860				
M	376000	1880	376000	1880			376000	1880			376000	1880				
H	381500	1907.5	381000	1905			380500	1902.5			380000	1900				
NR Band 5																
	Bandwidth 5MHz		Bandwidth 10MHz				Bandwidth 15MHz				Bandwidth 20MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)			Ch. #	Freq. (MHz)			Ch. #	Freq. (MHz)				
L	165300	826.5	165800	829			166300	831.5			166800	834				
M	167300	836.5	167300	836.5			167300	836.5			167300	836.5				
H	169300	846.5	168800	844			168300	841.5			167800	839				
NR Band 25																
	Bandwidth 5MHz		Bandwidth 10MHz				Bandwidth 15MHz				Bandwidth 20MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)			Ch. #	Freq. (MHz)			Ch. #	Freq. (MHz)				
L	370500	1852.5	371000	1855			371500	1857.5			372000	1860				
M	376500	1882.5	376500	1882.5			376500	1882.5			376500	1882.5				
H	382500	1912.5	382000	1910			381500	1907.5			381000	1905				
NR Band 41																
	Bandwidth20MHz		Bandwidth30MHz		Bandwidth 40MHz		Bandwidth 50MHz		Bandwidth 60MHz		Bandwidth 80MHz		Bandwidth 90MHz		Bandwidth100MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	501204	2506.02	502200	2511	503202	2516.01	504204	2521.02	505200	2526	507204	2536.02	508200	2541	509202	2546.01
M	518598	2592.99	518598	2592.99	518598	2592.99	518598	2592.99	518598	2592.99	518598	2592.99	518598	2592.99	518598	2592.99
H	535998	2679.99	534996	2674.98	534000	2670	532998	2664.99	531996	2659.98	529998	2649.99	528996	2644.98	528000	2640
NR Band 66																
	Bandwidth 5MHz		Bandwidth 10MHz		Bandwidth 15MHz		Bandwidth 20MHz		Bandwidth 30MHz		Bandwidth 40MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)				
L	342500	1712.5	343000	1715	343500	1717.5	344000	1720	345000	1725	346000	1730				
M	349000	1745	349000	1745	349000	1745	349000	1745	349000	1745	349000	1745				
H	355500	1777.5	355000	1775	354500	1772.5	354000	1770	353000	1765	352000	1760				



NR Band 71																		
	Bandwidth 5MHz				Bandwidth 10MHz				Bandwidth 15MHz				Bandwidth 20MHz					
	Ch. #		Freq. (MHz)		Ch. #		Freq. (MHz)		Ch. #		Freq. (MHz)		Ch. #		Freq. (MHz)			
L	133100		665.5		133600		668		13410		670.5		134600		673			
M	136100		680.5		136100		680.5		136100		680.5		136100		680.5			
H	139100		695.5		138600		693		13810		690.5		137600		688			
NR Band 77																		
	Bandwidth 20MHz		Bandwidth 30MHz		Bandwidth 40MHz		Bandwidth 50MHz		Bandwidth 60MHz		Bandwidth 70MHz		Bandwidth 80MHz		Bandwidth 90MHz		Bandwidth 100MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	647334	3710.01	647668	3715.02	648000	3720	648334	3725.01	648668	3730.02	649000	3735	649334	3740.01	649668	3745.02	650000	3750
M	656000	3840	656000	3840	656000	3840	656000	3840	656000	3840	656000	3840	656000	3840	656000	3840	656000	3840
H	664666	3969.99	664332	3964.98	664000	3960	663666	3954.99	663332	3949.98	663000	3945	662666	3939.99	662332	3934.98	662000	3930

4. RF Exposure Limits

4.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

4.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

1. Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

5. Specific Absorption Rate (SAR)

5.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

5.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg)

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

6. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:



- The DASY system in SAR Configuration is shown above
- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running windows software and the DASY software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

6.1 Test Site Location

The SAR measurement facilities used to collect data are within both Sporton Lab list below test site location are accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190 and 3786) and the FCC designation No. TW1190 and TW3786 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC test.

Laboratory	EMC & Wireless Communications Laboratory		Wensan Laboratory				
Test Site Location	TW1190 No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan		TW3786 No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan				
Test Site No.	SAR01-HY	SAR03-HY	SAR08-HY	SAR09-HY	SAR15-HY	SAR18-HY	SAR21-HY
	SAR04-HY	SAR05-HY	SAR11-HY	SAR12-HY	SAR16-HY	SAR19-HY	SAR22-HY
	SAR06-HY	SAR10-HY	SAR13-HY	SAR14-HY	SAR17-HY	SAR20-HY	

6.2 E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG). The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

<ES3DV3 Probe>

Construction	Symmetric design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	4 MHz – 4 GHz; Linearity: ± 0.2 dB (30 MHz – 4 GHz)	
Directivity	± 0.2 dB in TSL (rotation around probe axis) ± 0.3 dB in TSL (rotation normal to probe axis)	
Dynamic Range	5 μ W/g – >100 mW/g; Linearity: ± 0.2 dB	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 3.9 mm (body: 12 mm) Distance from probe tip to dipole centers: 3.0 mm	

<EX3DV4 Probe>

Construction	Symmetric design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	4 MHz – >6 GHz Linearity: ± 0.2 dB (30 MHz – 6 GHz)	
Directivity	± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)	
Dynamic Range	10 μ W/g – >100 mW/g Linearity: ± 0.2 dB (noise: typically <1 μ W/g)	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 2.5 mm (body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

6.3 Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.

The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



Fig 5.1 Photo of DAE

6.4 Phantom

<SAM Twin Phantom>

Shell Thickness	2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm	
Filling Volume	Approx. 25 liters	
Dimensions	Length: 1000 mm; Width: 500 mm; Height: adjustable feet	
Measurement Areas	Left Hand, Right Hand, Flat Phantom	

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

<ELI Phantom>

Shell Thickness	2 ± 0.2 mm (sagging: <1%)	
Filling Volume	Approx. 30 liters	
Dimensions	Major ellipse axis: 600 mm Minor axis: 400 mm	

The ELI phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with standard and all known tissue simulating liquids.

6.5 Device Holder

<Mounting Device for Hand-Held Transmitter>

In combination with the Twin SAM V5.0/V5.0c or ELI phantoms, the Mounting Device for Hand-Held Transmitters enables rotation of the mounted transmitter device to specified spherical coordinates. At the heads, the rotation axis is at the ear opening. Transmitter devices can be easily and accurately positioned according to IEC 62209-1, IEEE 1528, FCC, or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat). And upgrade kit to Mounting Device to enable easy mounting of wider devices like big smart-phones, e-books, small tablets, etc. It holds devices with width up to 140 mm.



Mounting Device for Hand-Held Transmitters



Mounting Device Adaptor for Wide-Phones

<Mounting Device for Laptops and other Body-Worn Transmitters>

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the mounting device in place of the phone positioned. The extension is fully compatible with the SAM Twin and ELI phantoms.



Mounting Device for Laptops

7. Measurement Procedures

The measurement procedures are as follows:

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

7.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

7.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

7.3 Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB0) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}	≤ 2 GHz: ≤ 15 mm $2 - 3$ GHz: ≤ 12 mm	$3 - 4$ GHz: ≤ 12 mm $4 - 6$ GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

7.4 Zoom Scan

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

7.5 Volume Scan Procedures

The volume scan is used to assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

7.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASy measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.

8. Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	750MHz System Validation Kit ⁽²⁾	D750V3	1107	Jun. 22, 2022	Jun. 19, 2025
SPEAG	835MHz System Validation Kit ⁽²⁾	D835V2	4d167	Nov. 24, 2022	Nov. 21, 2025
SPEAG	1750MHz System Validation Kit	D1750V2	1112	Feb. 20, 2025	Feb. 19, 2026
SPEAG	1900MHz System Validation Kit	D1900V2	5d093	Mar. 20, 2025	Mar. 19, 2026
SPEAG	2600MHz System Validation Kit	D2600V2	1008	Aug. 15, 2024	Aug. 14, 2025
SPEAG	3500MHz System Validation Kit	D3500V2	1014	Jan. 15, 2025	Jan. 14, 2026
SPEAG	3700MHz System Validation Kit	D3700V2	1022	Jul. 10, 2024	Jul. 09, 2025
SPEAG	3900MHz System Validation Kit ⁽²⁾	D3900V2	1092	May. 15, 2023	May. 13, 2025
SPEAG	Data Acquisition Electronics	DAE4	1647	Oct. 15, 2024	Oct. 14, 2025
SPEAG	Dosimetric E-Field Probe	EX3DV4	7814	Jun. 20, 2024	Jun. 19, 2025
Testo	Hygro meter	608-H1	45196600	Oct. 28, 2024	Oct. 27, 2025
Anritsu	Radio Communication Analyzer	MT8821C	6201341950	Nov. 12, 2024	Nov. 11, 2025
R&S	Wideband Radio Communication Tester	CMX500	101931	Sep. 23, 2024	Sep. 22, 2025
SPEAG	Device Holder	N/A	N/A	N/A	N/A
Anritsu	Signal Generator	MG3710A	6201502524	Sep. 24, 2024	Sep. 23, 2025
Keysight	ENA Network Analyzer	E5071C	MY46104758	Oct. 20, 2024	Oct. 19, 2025
SPEAG	Dielectric Probe Kit	DAK-3.5	1126	Sep. 17, 2024	Sep. 16, 2025
LINE SEIKI	Digital Thermometer	DTM3000-spezial	3690	Aug. 07, 2024	Aug. 06, 2025
Anritsu	Power Meter	ML2495A	1419002	Aug. 13, 2024	Aug. 12, 2025
Anritsu	Power Sensor	MA2411B	1911176	Aug. 13, 2024	Aug. 12, 2025
Anritsu	Spectrum Analyzer	MS2830A	6201396378	Jul. 09, 2024	Jul. 08, 2025
Mini-Circuits	Power Amplifier	ZVE-8G+	6418	Oct. 23, 2024	Oct. 22, 2025
ATM	Dual Directional Coupler	C122H-10	P610410z-02	Note 1	
Warison	Directional Coupler	WCOU-10-50S-10	WR889BMC4B1	Note 1	
Woken	Attenuator 1	WK0602-XX	N/A	Note 1	
PE	Attenuator 2	PE7005-10	N/A	Note 1	
PE	Attenuator 3	PE7005- 3	N/A	Note 1	

General Note:

1. Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check source.
2. The dipole calibration interval can be extended to 3 years with justification according to KDB 865664 D01. The dipoles are also not physically damaged, or repaired during the interval. The justification data in appendix C can be found which the return loss is < -20dB, within 20% of prior calibration, the impedance is within 5 ohm of prior calibration for each dipole.

9. System Verification

9.1 Tissue Verification

The tissue dielectric parameters of tissue-equivalent media used for SAR measurements must be characterized within a temperature range of 18°C to 25°C, measured with calibrated instruments and apparatuses, such as network analyzers and temperature probes. The temperature of the tissue-equivalent medium during SAR measurement must also be within 18°C to 25°C and within $\pm 2^\circ\text{C}$ of the temperature when the tissue parameters are characterized. The tissue dielectric measurement system must be calibrated before use. The dielectric parameters must be measured before the tissue-equivalent medium is used in a series of SAR measurements.

The liquid tissue depth was at least 15cm in the phantom for all SAR testing

<Tissue Dielectric Parameter Check Results>

Frequency (MHz)	Liquid Temp. (°C)	Conductivity (σ)	Permittivity (ϵ_r)	Conductivity Target (σ)	Permittivity Target (ϵ_r)	Delta (σ) (%)	Delta (ϵ_r) (%)	Limit (%)	Date
750	22.5	0.887	41.760	0.89	41.90	-0.34	-0.33	± 5	2025/5/9
750	22.6	0.889	43.215	0.89	41.90	-0.11	3.14	± 5	2025/5/10
835	22.5	0.921	41.464	0.90	41.50	2.33	-0.09	± 5	2025/5/9
835	22.6	0.922	42.819	0.90	41.50	2.44	3.18	± 5	2025/5/10
1750	22.5	1.355	40.505	1.37	40.10	-1.09	1.01	± 5	2025/5/9
1750	22.6	1.371	40.504	1.37	40.10	0.07	1.01	± 5	2025/5/10
1900	22.5	1.431	38.957	1.40	40.00	2.21	-2.61	± 5	2025/5/9
1900	22.6	1.386	40.252	1.40	40.00	-1.00	0.63	± 5	2025/5/10
2600	22.5	1.981	38.026	1.96	39.00	1.07	-2.50	± 5	2025/5/9
2600	22.6	1.991	38.033	1.96	39.00	1.58	-2.48	± 5	2025/5/10
3500	22.5	2.893	37.803	2.91	37.90	-0.58	-0.26	± 5	2025/5/9
3700	22.5	3.075	37.504	3.12	37.70	-1.44	-0.52	± 5	2025/5/9
3900	22.5	3.274	37.226	3.33	37.51	-1.68	-0.76	± 5	2025/5/9

9.2 System Performance Check Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Test Site	Date	Frequency (MHz)	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 1g SAR (W/kg)	Targeted 1g SAR (W/kg)	Normalized 1g SAR (W/kg)	Deviation (%)
SAR-12	2025/5/9	750	250	D750V3-1107	EX3DV4 - SN7814	DAE4 Sn1647	2.230	8.540	8.92	4.45
SAR-12	2025/5/10	750	250	D750V3-1107	EX3DV4 - SN7814	DAE4 Sn1647	2.230	8.540	8.92	4.45
SAR-12	2025/5/9	835	250	D835V2-4d167	EX3DV4 - SN7814	DAE4 Sn1647	2.280	9.800	9.12	-6.94
SAR-12	2025/5/10	835	250	D835V2-4d167	EX3DV4 - SN7814	DAE4 Sn1647	2.230	9.800	8.92	-8.98
SAR-12	2025/5/9	1750	50	D1750V2-1112	EX3DV4 - SN7814	DAE4 Sn1647	1.820	36.800	36.4	-1.09
SAR-12	2025/5/10	1750	50	D1750V2-1112	EX3DV4 - SN7814	DAE4 Sn1647	1.860	36.800	37.2	1.09
SAR-12	2025/5/9	1900	50	D1900V2-5d093	EX3DV4 - SN7814	DAE4 Sn1647	1.890	39.300	37.8	-3.82
SAR-12	2025/5/10	1900	50	D1900V2-5d093	EX3DV4 - SN7814	DAE4 Sn1647	1.950	39.300	39	-0.76
SAR-12	2025/5/9	2600	50	D2600V2-1008	EX3DV4 - SN7814	DAE4 Sn1647	2.700	55.700	54	-3.05
SAR-12	2025/5/10	2600	50	D2600V2-1008	EX3DV4 - SN7814	DAE4 Sn1647	2.570	55.700	51.4	-7.72
SAR-12	2025/5/9	3500	50	D3500V2-1014	EX3DV4 - SN7814	DAE4 Sn1647	3.400	65.700	68	3.50
SAR-12	2025/5/9	3700	50	D3700V2-1022	EX3DV4 - SN7814	DAE4 Sn1647	3.620	68.100	72.4	6.31
SAR-12	2025/5/9	3900	50	D3900V2-1092-3900	EX3DV4 - SN7814	DAE4 Sn1647	3.130	67.000	62.6	-6.57




Fig 8.3.1 System Performance Check Setup



Fig 8.3.2 Setup Photo

10. UMTS/LTE Output Power (Unit: dBm)

<WCDMA Conducted Power>

1. The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification.
2. The procedures in KDB 941225 D01v03r01 are applied for 3GPP Rel. 6 HSPA to configure the device in the required sub-test mode(s) to determine SAR test exclusion.
3. For DC-HSDPA, the device was configured according to the H-Set 12, Fixed Reference Channel (FRC) configuration in Table C.8.1.12 of 3GPP TS 34.121-1, with the primary and the secondary serving HS-DSCH Cell enabled during the power measurement.

A summary of these settings are illustrated below:

HSDPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
 - i. Set Gain Factors (β_c and β_d) and parameters were set according to each
 - ii. Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - iii. Set RMC 12.2Kbps + HSDPA mode.
 - iv. Set Cell Power = -86 dBm
 - v. Set HS-DSCH Configuration Type to FRC (H-set 1, QPSK)
 - vi. Select HSDPA Uplink Parameters
 - vii. Set Delta ACK, Delta NACK and Delta CQI = 8
 - viii. Set Ack-Nack Repetition Factor to 3
 - ix. Set CQI Feedback Cycle (k) to 4 ms
 - x. Set CQI Repetition Factor to 2
 - xi. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

Table C.10.1.4: β values for transmitter characteristics tests with HS-DPCCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note 1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (Note 4)	15/15 (Note 4)	64	12/15 (Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{HS} = 30/15 * \beta_c$.

Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, Δ_{ACK} and $\Delta_{NACK} = 30/15$ with $\beta_{HS} = 30/15 * \beta_c$, and $\Delta_{CQI} = 24/15$ with $\beta_{HS} = 24/15 * \beta_c$.

Note 3: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{HS}/\beta_c = 24/15$. For all other combinations of DPCCH, DPDCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Note 4: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11/15$ and $\beta_d = 15/15$.

Setup Configuration

HSUPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting * :
 - i. Call Configs = 5.2B, 5.9B, 5.10B, and 5.13.2B with QPSK
 - ii. Set the Gain Factors (β_c and β_d) and parameters (AG Index) were set according to each specific sub-test in the following table, C11.1.3, quoted from the TS 34.121
 - iii. Set Cell Power = -86 dBm
 - iv. Set Channel Type = 12.2k + HSPA
 - v. Set UE Target Power
 - vi. Power Ctrl Mode= Alternating bits
 - vii. Set and observe the E-TFCI
 - viii. Confirm that E-TFCI is equal to the target E-TFCI of 75 for sub-test 1, and other subtest's E-TFCI
- d. The transmitted maximum output power was recorded.

Table C.11.1.3: β values for transmitter characteristics tests with HS-DPCCH and E-DCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note 1)	β_{ec}	β_{ed} (Note 4) (Note 5)	β_{ed} (SF)	β_{ed} (Codes)	CM (dB) (Note 2)	MPR (dB) (Note 2) (Note 6)	AG Index (Note 5)	E-TFCI
1	11/15 (Note 3)	15/15 (Note 3)	64	11/15 (Note 3)	22/15	209/25	1309/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	β_{ed1} : 47/15 β_{ed2} : 47/15	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15	0	-	-	5/15	5/15	47/15	4	1	1.0	0.0	12	67

Note 1: For sub-test 1 to 4, Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$. For sub-test 5, Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 5/15$ with $\beta_{hs} = 5/15 * \beta_c$.

Note 2: CM = 1 for $\beta_d/\beta_c = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_d/β_c ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g.

Note 5: β_{ed} can not be set directly; it is set by Absolute Grant Value.

Note 6: For subtests 2, 3 and 4, UE may perform E-DPDCH power scaling at max power which could results in slightly smaller MPR values.

Setup Configuration


DC-HSDPA 3GPP release 8 Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration below
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
 - i. Set RMC 12.2Kbps + HSDPA mode.
 - ii. Set Cell Power = -25 dBm
 - iii. Set HS-DSCH Configuration Type to FRC (H-set 12, QPSK)
 - iv. Select HSDPA Uplink Parameters
 - v. Set Gain Factors (β_c and β_d) and parameters were set according to each Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - a). Subtest 1: $\beta_c/\beta_d=2/15$
 - b). Subtest 2: $\beta_c/\beta_d=12/15$
 - c). Subtest 3: $\beta_c/\beta_d=15/8$
 - d). Subtest 4: $\beta_c/\beta_d=15/4$
 - vi. Set Delta ACK, Delta NACK and Delta CQI = 8
 - vii. Set Ack-Nack Repetition Factor to 3
 - viii. Set CQI Feedback Cycle (k) to 4 ms
 - ix. Set CQI Repetition Factor to 2
 - x. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification. A summary of these settings are illustrated below:

C.8.1.12 Fixed Reference Channel Definition H-Set 12
Table C.8.1.12: Fixed Reference Channel H-Set 12

Parameter	Unit	Value
Nominal Avg. Inf. Bit Rate	kbps	60
Inter-TTI Distance	TTI's	1
Number of HARQ Processes	Processes	6
Information Bit Payload (N_{INF})	Bits	120
Number Code Blocks	Blocks	1
Binary Channel Bits Per TTI	Bits	960
Total Available SML's in UE	SML's	19200
Number of SML's per HARQ Proc.	SML's	3200
Coding Rate		0.15
Number of Physical Channel Codes	Codes	1
Modulation		QPSK
Note 1: The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table.		
Note 2: Maximum number of transmission is limited to 1, i.e., retransmission is not allowed. The redundancy and constellation version 0 shall be used.		


Figure C.8.19: Coding rate for Fixed reference Channel H-Set 12 (QPSK)
Setup Configuration

<WCDMA Conducted Power>
General Note:

1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. The maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA / DC-HSDPA is $\leq \frac{1}{4}$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA / DC-HSDPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA, and according to the following RF output power, the output power results of the secondary modes (HSUPA, HSDPA, DC-HSDPA) are less than $\frac{1}{4}$ dB higher than the primary modes; therefore, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA.

<WCDMA>

Band		WCDMA II_Ant 1_Index 1			Tune-up Limit (dBm)	WCDMA IV_Ant 1_Index 1			Tune-up Limit (dBm)	WCDMA V_Ant 1_Index 1			Tune-up Limit (dBm)
TX Channel		9262	9400	9538		1312	1413	1513		4132	4182	4233	
Rx Channel		9662	9800	9938		1537	1638	1738		4357	4407	4458	
Frequency (MHz)		1852.4	1880	1907.6		1712.4	1732.6	1752.6		826.4	836.4	846.6	
3GPP Rel 99	AMR 12.2Kbps	23.12	23.16	23.24	24.00	22.86	22.88	22.82	24.00	22.91	23.06	23.04	24.00
3GPP Rel 99	RMC 12.2Kbps	23.13	23.26	23.25	24.00	22.96	23.03	22.92	24.00	22.95	23.13	23.06	24.00
3GPP Rel 6	HSDPA Subtest-1	23.16	23.03	23.15	24.00	22.96	23.02	22.98	24.00	22.97	23.03	23.11	24.00
3GPP Rel 6	HSDPA Subtest-2	23.12	23.15	23.22	24.00	22.95	22.98	23.02	24.00	22.93	23.10	23.11	24.00
3GPP Rel 6	HSDPA Subtest-3	23.07	23.21	23.14	23.50	22.96	22.98	23.01	23.50	22.92	23.06	23.10	23.50
3GPP Rel 6	HSDPA Subtest-4	23.11	23.24	23.14	23.50	22.95	22.98	22.99	23.50	22.92	23.03	22.91	23.50
3GPP Rel 8	DC-HSDPA Subtest-1	23.06	23.00	23.10	24.00	22.87	22.97	22.94	24.00	22.89	23.03	23.07	24.00
3GPP Rel 8	DC-HSDPA Subtest-2	23.10	23.07	23.20	24.00	22.85	22.95	22.96	24.00	22.87	23.04	23.04	24.00
3GPP Rel 8	DC-HSDPA Subtest-3	23.00	23.13	23.08	23.50	22.94	22.93	22.98	23.50	22.87	22.97	23.00	23.50
3GPP Rel 8	DC-HSDPA Subtest-4	23.11	23.22	23.05	23.50	22.92	22.93	22.94	23.50	22.91	22.95	22.84	23.50
3GPP Rel 6	HSUPA Subtest-1	22.70	22.57	22.62	24.00	22.87	22.87	22.40	24.00	23.05	22.99	22.90	24.00
3GPP Rel 6	HSUPA Subtest-2	20.65	20.54	20.54	22.00	20.92	20.85	20.48	22.00	21.07	20.95	20.95	22.00
3GPP Rel 6	HSUPA Subtest-3	21.59	21.49	21.56	23.00	21.94	21.89	21.51	23.00	22.07	21.94	21.91	23.00
3GPP Rel 6	HSUPA Subtest-4	20.60	20.56	20.52	22.00	20.83	20.78	20.50	22.00	21.01	20.95	20.94	22.00
3GPP Rel 6	HSUPA Subtest-5	22.63	22.53	22.55	24.00	22.42	22.41	22.43	24.00	23.04	23.00	22.94	24.00

<LTE Conducted Power>**General Note:**

1. A Base station simulator was used to setup the connection with EUT; the frequency band, channel bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUT transmitting at maximum power and at different configurations which are requested to be reported to FCC, for conducted power measurement and SAR testing.
2. Per KDB 941225 D05v02r05, when a properly configured base station simulator is used for the SAR and power measurements, spectrum plots for each RB allocation and offset configuration is not required.
3. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
4. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
5. Per KDB 941225 D05v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
6. Per KDB 941225 D05v02r05, 16QAM output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, 16QAM SAR testing is not required.
7. Per KDB 941225 D05v02r05, Smaller bandwidth output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
8. For LTE B4/B5/B12/B71 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.
9. LTE band 4 SAR test was covered by Band 66; according to April 2015 TCB workshop, SAR test for overlapping LTE bands can be reduced if
 - a. the maximum output power, including tolerance, for the smaller band is $\leq$ the larger band to qualify for the SAR test exclusion
 - b. the channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band



<LTE Band 2_Ant 1_Index 1>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				18700	18900	19100	
Frequency (MHz)				1860	1880	1900	
20	QPSK	1	0	22.75	23.02	22.90	24
20	QPSK	1	49	22.63	22.76	22.84	
20	QPSK	1	99	22.73	22.86	22.75	
20	QPSK	50	0	21.70	21.78	21.81	23
20	QPSK	50	24	21.83	21.95	21.89	
20	QPSK	50	50	21.83	21.92	21.87	
20	QPSK	100	0	21.76	21.75	21.90	
20	16QAM	1	0	22.11	22.14	22.19	23
20	16QAM	1	49	22.09	22.09	22.10	
20	16QAM	1	99	22.01	22.16	22.00	
20	16QAM	50	0	20.73	20.78	20.79	22
20	16QAM	50	24	20.89	20.93	20.97	
20	16QAM	50	50	20.84	20.97	20.95	
20	16QAM	100	0	20.83	20.82	20.88	
20	64QAM	1	0	20.97	20.97	21.08	22
20	64QAM	1	49	20.94	20.97	21.06	
20	64QAM	1	99	20.97	21.09	21.14	
20	64QAM	50	0	19.75	19.84	19.81	21
20	64QAM	50	24	19.96	19.91	20.02	
20	64QAM	50	50	19.85	19.95	19.95	
20	64QAM	100	0	19.81	19.80	19.87	
Channel				18675	18900	19125	Tune-up limit (dBm)
Frequency (MHz)				1857.5	1880	1902.5	
15	QPSK	1	0	22.73	22.92	22.82	24
15	QPSK	1	37	22.59	22.85	22.82	
15	QPSK	1	74	22.68	22.84	22.76	
15	QPSK	36	0	21.83	21.79	21.84	23
15	QPSK	36	20	21.91	21.87	21.85	
15	QPSK	36	39	21.82	21.96	21.95	
15	QPSK	75	0	21.83	21.77	21.89	
15	16QAM	1	0	21.99	22.08	22.14	23
15	16QAM	1	37	21.99	22.10	22.11	
15	16QAM	1	74	22.00	22.23	22.13	
15	16QAM	36	0	20.82	20.82	20.79	22
15	16QAM	36	20	20.85	20.90	20.85	
15	16QAM	36	39	20.84	21.01	20.97	
15	16QAM	75	0	20.85	20.89	20.83	
15	64QAM	1	0	20.85	20.94	21.08	22
15	64QAM	1	37	20.97	21.21	21.14	
15	64QAM	1	74	20.95	21.05	21.13	
15	64QAM	36	0	19.80	19.82	19.87	21
15	64QAM	36	20	19.89	19.85	19.91	
15	64QAM	36	39	19.95	20.01	19.93	
15	64QAM	75	0	19.86	19.87	19.91	
Channel				18650	18900	19150	Tune-up limit (dBm)
Frequency (MHz)				1855	1880	1905	
10	QPSK	1	0	22.86	22.91	22.90	24
10	QPSK	1	25	22.42	22.57	22.88	
10	QPSK	1	49	22.56	22.62	22.88	
10	QPSK	25	0	21.80	21.85	21.85	23
10	QPSK	25	12	21.88	21.91	22.00	
10	QPSK	25	25	21.81	21.86	21.83	
10	QPSK	50	0	21.85	21.83	22.00	
10	16QAM	1	0	21.80	21.88	22.29	23
10	16QAM	1	25	22.23	22.27	22.30	
10	16QAM	1	49	21.88	21.95	22.17	



FCC SAR TEST REPORT

Report No. : FA480602-01

10	16QAM	25	0	20.84	20.83	20.85	22
10	16QAM	25	12	20.91	20.92	21.02	
10	16QAM	25	25	20.76	20.85	20.89	
10	16QAM	50	0	20.81	20.83	20.87	
10	64QAM	1	0	20.61	20.65	21.06	22
10	64QAM	1	25	21.13	21.20	21.14	
10	64QAM	1	49	20.70	20.84	21.04	
10	64QAM	25	0	19.87	19.86	19.88	21
10	64QAM	25	12	19.96	20.01	20.03	
10	64QAM	25	25	19.88	19.95	19.94	
10	64QAM	50	0	19.83	19.89	19.95	
Channel				18625	18900	19175	Tune-up limit (dBm)
Frequency (MHz)				1852.5	1880	1907.5	
5	QPSK	1	0	22.83	22.97	22.83	24
5	QPSK	1	12	22.81	22.79	22.82	
5	QPSK	1	24	22.70	22.78	22.82	
5	QPSK	12	0	21.95	21.98	21.95	23
5	QPSK	12	7	21.94	21.94	22.01	
5	QPSK	12	13	21.90	21.95	21.93	
5	QPSK	25	0	21.90	21.90	21.93	
5	16QAM	1	0	22.13	22.05	22.16	23
5	16QAM	1	12	22.20	22.21	22.23	
5	16QAM	1	24	22.02	22.16	22.08	
5	16QAM	12	0	20.98	20.97	21.00	22
5	16QAM	12	7	20.96	21.00	21.00	
5	16QAM	12	13	20.92	21.01	20.95	
5	16QAM	25	0	20.93	20.99	20.94	
5	64QAM	1	0	21.13	21.06	20.99	22
5	64QAM	1	12	21.03	21.18	21.19	
5	64QAM	1	24	20.99	21.06	21.10	
5	64QAM	12	0	20.00	20.00	19.99	21
5	64QAM	12	7	19.99	20.03	20.03	
5	64QAM	12	13	19.95	20.02	20.00	
5	64QAM	25	0	19.92	19.90	19.95	
Channel				18615	18900	19185	Tune-up limit (dBm)
Frequency (MHz)				1851.5	1880	1908.5	
3	QPSK	1	0	22.86	23.01	22.92	24
3	QPSK	1	8	22.85	22.87	22.90	
3	QPSK	1	14	22.77	22.88	22.84	
3	QPSK	8	0	21.96	22.00	21.97	23
3	QPSK	8	4	21.99	21.94	22.05	
3	QPSK	8	7	21.86	21.98	21.92	
3	QPSK	15	0	21.93	21.92	22.00	
3	16QAM	1	0	22.11	22.20	22.28	23
3	16QAM	1	8	22.18	22.31	22.28	
3	16QAM	1	14	22.12	22.19	22.17	
3	16QAM	8	0	20.99	21.01	21.08	22
3	16QAM	8	4	21.00	21.01	21.06	
3	16QAM	8	7	20.93	21.03	21.05	
3	16QAM	15	0	20.94	20.99	21.04	
3	64QAM	1	0	21.16	21.16	21.12	22
3	64QAM	1	8	21.12	21.21	21.18	
3	64QAM	1	14	21.07	21.05	21.05	
3	64QAM	8	0	19.98	20.00	20.05	21
3	64QAM	8	4	20.00	20.06	20.07	
3	64QAM	8	7	19.93	20.01	20.02	
3	64QAM	15	0	19.92	20.01	20.03	
Channel				18607	18900	19193	Tune-up limit (dBm)
Frequency (MHz)				1850.7	1880	1909.3	
1.4	QPSK	1	0	22.80	22.93	22.89	24
1.4	QPSK	1	3	22.78	22.91	22.88	
1.4	QPSK	1	5	22.74	22.78	22.82	
1.4	QPSK	3	0	22.78	22.87	22.86	



FCC SAR TEST REPORT

Report No. : FA480602-01

1.4	QPSK	3	1	22.85	22.89	22.90	
1.4	QPSK	3	3	22.76	22.88	22.81	
1.4	QPSK	6	0	21.84	21.93	21.91	23
1.4	16QAM	1	0	22.09	22.12	22.13	
1.4	16QAM	1	3	22.19	22.22	22.26	
1.4	16QAM	1	5	22.02	22.17	22.11	
1.4	16QAM	3	0	21.88	21.92	21.96	23
1.4	16QAM	3	1	21.94	22.02	22.00	
1.4	16QAM	3	3	21.75	21.93	21.87	
1.4	16QAM	6	0	20.96	20.96	21.02	22
1.4	64QAM	1	0	21.01	21.11	21.05	
1.4	64QAM	1	3	21.04	21.16	21.05	
1.4	64QAM	1	5	20.96	21.08	21.03	
1.4	64QAM	3	0	20.97	21.07	21.06	
1.4	64QAM	3	1	21.02	21.13	21.09	
1.4	64QAM	3	3	20.95	21.04	21.07	
1.4	64QAM	6	0	19.86	19.93	19.93	21

<LTE Band 4_Ant 1_Index 1>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				20050	20175	20300	
Frequency (MHz)				1720	1732.5	1745	
20	QPSK	1	0	22.59	22.63	22.53	
20	QPSK	1	49	22.30	22.34	22.34	24
20	QPSK	1	99	22.31	22.34	22.36	
20	QPSK	50	0	21.58	21.58	21.56	
20	QPSK	50	24	21.67	21.74	21.66	23
20	QPSK	50	50	21.65	21.63	21.58	
20	QPSK	100	0	21.66	21.69	21.62	
20	16QAM	1	0	21.63	21.62	21.62	
20	16QAM	1	49	21.90	21.94	21.90	23
20	16QAM	1	99	21.66	21.67	21.64	
20	16QAM	50	0	20.56	20.63	20.54	
20	16QAM	50	24	20.73	20.68	20.71	22
20	16QAM	50	50	20.66	20.66	20.66	
20	16QAM	100	0	20.61	20.64	20.64	
20	64QAM	1	0	20.53	20.54	20.60	
20	64QAM	1	49	20.79	20.79	20.76	22
20	64QAM	1	99	20.57	20.57	20.55	
20	64QAM	50	0	19.63	19.62	19.57	
20	64QAM	50	24	19.75	19.69	19.74	21
20	64QAM	50	50	19.71	19.67	19.65	
20	64QAM	100	0	19.69	19.66	19.66	
Channel				20025	20175	20325	
Frequency (MHz)				1717.5	1732.5	1747.5	
15	QPSK	1	0	22.45	22.44	22.45	
15	QPSK	1	37	22.58	22.60	22.57	24
15	QPSK	1	74	22.50	22.47	22.42	
15	QPSK	36	0	21.60	21.58	21.57	
15	QPSK	36	20	21.75	21.77	21.68	23
15	QPSK	36	39	21.73	21.67	21.69	
15	QPSK	75	0	21.70	21.70	21.66	
15	16QAM	1	0	21.76	21.83	21.76	
15	16QAM	1	37	21.96	21.96	21.95	23
15	16QAM	1	74	21.87	21.82	21.68	
15	16QAM	36	0	20.63	20.60	20.62	
15	16QAM	36	20	20.73	20.74	20.70	22
15	16QAM	36	39	20.28	20.67	20.66	
15	16QAM	75	0	20.68	20.67	20.68	
15	64QAM	1	0	20.59	20.55	20.58	22



FCC SAR TEST REPORT

Report No. : FA480602-01

15	64QAM	1	37	20.80	20.82	20.75	21
15	64QAM	1	74	20.70	20.72	20.77	
15	64QAM	36	0	19.63	19.61	19.57	
15	64QAM	36	20	19.78	19.77	19.75	
15	64QAM	36	39	19.76	19.70	19.71	
15	64QAM	75	0	19.68	19.70	19.62	Tune-up limit (dBm)
Channel				20000	20175	20350	
Frequency (MHz)				1715	1732.5	1750	24
10	QPSK	1	0	22.55	22.58	22.40	
10	QPSK	1	25	22.28	22.39	22.52	
10	QPSK	1	49	22.35	22.31	22.36	
10	QPSK	25	0	21.51	21.38	21.58	23
10	QPSK	25	12	21.75	21.69	21.64	
10	QPSK	25	25	21.61	21.57	21.60	
10	QPSK	50	0	21.63	21.66	21.59	
10	16QAM	1	0	21.67	21.69	21.66	23
10	16QAM	1	25	21.93	21.99	21.99	
10	16QAM	1	49	21.63	21.70	21.73	
10	16QAM	25	0	20.60	20.56	20.59	
10	16QAM	25	12	20.73	20.70	20.68	22
10	16QAM	25	25	20.63	20.61	20.62	
10	16QAM	50	0	20.62	20.69	20.55	
10	64QAM	1	0	20.44	20.57	20.56	
10	64QAM	1	25	20.90	20.85	20.92	22
10	64QAM	1	49	20.58	20.64	20.61	
10	64QAM	25	0	19.62	19.64	19.60	
10	64QAM	25	12	19.76	19.73	19.74	
10	64QAM	25	25	19.62	19.68	19.64	21
10	64QAM	50	0	19.69	19.65	19.58	
Channel				19975	20175	20375	Tune-up limit (dBm)
Frequency (MHz)				1712.5	1732.5	1752.5	
5	QPSK	1	0	22.56	22.58	22.53	24
5	QPSK	1	12	22.56	22.47	22.48	
5	QPSK	1	24	22.52	22.49	22.51	
5	QPSK	12	0	21.67	21.64	21.64	23
5	QPSK	12	7	21.78	21.73	21.75	
5	QPSK	12	13	21.72	21.69	21.66	
5	QPSK	25	0	21.71	21.72	21.69	
5	16QAM	1	0	21.82	21.81	21.81	23
5	16QAM	1	12	21.93	22.03	21.99	
5	16QAM	1	24	21.86	21.93	21.89	
5	16QAM	12	0	20.70	20.70	20.65	
5	16QAM	12	7	20.74	20.81	20.73	22
5	16QAM	12	13	20.70	20.72	20.70	
5	16QAM	25	0	20.74	20.74	20.69	
5	64QAM	1	0	20.84	20.88	20.84	
5	64QAM	1	12	20.91	20.93	20.86	22
5	64QAM	1	24	20.80	20.78	20.86	
5	64QAM	12	0	19.75	19.72	19.75	
5	64QAM	12	7	19.86	19.84	19.80	
5	64QAM	12	13	19.73	19.72	19.77	21
5	64QAM	25	0	19.72	19.73	19.70	
Channel				19965	20175	20385	Tune-up limit (dBm)
Frequency (MHz)				1711.5	1732.5	1753.5	
3	QPSK	1	0	22.52	22.55	22.45	24
3	QPSK	1	8	22.51	22.40	22.41	
3	QPSK	1	14	22.52	22.48	22.41	
3	QPSK	8	0	21.57	21.60	21.63	
3	QPSK	8	4	21.73	21.69	21.72	23
3	QPSK	8	7	21.63	21.65	21.64	
3	QPSK	15	0	21.65	21.64	21.65	
3	16QAM	1	0	21.74	21.71	21.73	
3	16QAM	1	8	21.86	21.95	21.90	23



FCC SAR TEST REPORT

Report No. : FA480602-01

3	16QAM	1	14	21.84	21.92	21.82	22
3	16QAM	8	0	20.68	20.70	20.58	
3	16QAM	8	4	20.66	20.79	20.65	
3	16QAM	8	7	20.63	20.64	20.70	
3	16QAM	15	0	20.64	20.73	20.59	
3	64QAM	1	0	20.83	20.83	20.79	22
3	64QAM	1	8	20.87	20.92	20.84	
3	64QAM	1	14	20.78	20.77	20.83	
3	64QAM	8	0	19.73	19.68	19.72	21
3	64QAM	8	4	19.82	19.84	19.74	
3	64QAM	8	7	19.65	19.68	19.68	
3	64QAM	15	0	19.64	19.73	19.69	
Channel				19957	20175	20393	Tune-up limit (dBm)
Frequency (MHz)				1710.7	1732.5	1754.3	
1.4	QPSK	1	0	22.56	22.57	22.45	24
1.4	QPSK	1	3	22.50	22.47	22.40	
1.4	QPSK	1	5	22.47	22.49	22.44	
1.4	QPSK	3	0	22.51	22.54	22.39	
1.4	QPSK	3	1	22.53	22.57	22.42	
1.4	QPSK	3	3	22.46	22.52	22.42	
1.4	QPSK	6	0	21.70	21.66	21.60	23
1.4	16QAM	1	0	21.77	21.76	21.78	23
1.4	16QAM	1	3	21.88	22.01	21.95	
1.4	16QAM	1	5	21.84	21.88	21.89	
1.4	16QAM	3	0	21.67	21.67	21.55	
1.4	16QAM	3	1	21.70	21.60	21.56	
1.4	16QAM	3	3	21.65	21.62	21.56	
1.4	16QAM	6	0	20.72	20.73	20.65	22
1.4	64QAM	1	0	20.74	20.81	20.80	22
1.4	64QAM	1	3	20.82	20.85	20.77	
1.4	64QAM	1	5	20.78	20.75	20.83	
1.4	64QAM	3	0	20.75	20.65	20.72	
1.4	64QAM	3	1	20.80	20.76	20.78	
1.4	64QAM	3	3	20.69	20.62	20.77	
1.4	64QAM	6	0	19.64	19.65	19.60	21

<LTE Band 5_Ant 1_Index 1>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				20450	20525	20600	
Frequency (MHz)				829	836.5	844	
10	QPSK	1	0	22.76	22.93	22.84	24
10	QPSK	1	25	22.62	22.75	22.80	
10	QPSK	1	49	22.72	22.76	22.80	
10	QPSK	25	0	21.75	21.80	21.81	23
10	QPSK	25	12	21.83	21.83	21.77	
10	QPSK	25	25	21.78	21.87	21.82	
10	QPSK	50	0	21.78	21.75	21.75	
10	16QAM	1	0	22.19	22.11	22.13	23
10	16QAM	1	25	22.06	22.16	22.07	
10	16QAM	1	49	22.07	22.16	22.03	
10	16QAM	25	0	20.76	20.81	20.76	22
10	16QAM	25	12	20.86	20.78	20.79	
10	16QAM	25	25	20.75	20.82	20.76	
10	16QAM	50	0	20.72	20.75	20.66	
10	64QAM	1	0	20.88	21.05	20.87	22
10	64QAM	1	25	21.04	21.05	21.00	
10	64QAM	1	49	20.98	21.03	20.97	
10	64QAM	25	0	19.84	19.87	19.83	21
10	64QAM	25	12	19.83	19.88	19.89	
10	64QAM	25	25	19.84	19.84	19.91	



FCC SAR TEST REPORT

Report No. : FA480602-01

10	64QAM	50	0	19.78	19.74	19.76	Tune-up limit (dBm)
Channel				20425	20525	20625	
Frequency (MHz)				826.5	836.5	846.5	
5	QPSK	1	0	22.67	22.86	22.85	24
5	QPSK	1	12	22.60	22.68	22.70	
5	QPSK	1	24	22.59	22.75	22.73	
5	QPSK	12	0	21.72	21.81	21.81	23
5	QPSK	12	7	21.78	21.88	21.88	
5	QPSK	12	13	21.79	21.89	21.81	
5	QPSK	25	0	21.73	21.79	21.88	23
5	16QAM	1	0	21.90	22.02	21.98	
5	16QAM	1	12	22.13	22.17	22.11	
5	16QAM	1	24	21.99	22.09	22.05	22
5	16QAM	12	0	20.75	20.83	20.78	
5	16QAM	12	7	20.91	20.96	20.88	
5	16QAM	12	13	20.75	20.86	20.80	22
5	16QAM	25	0	20.82	20.84	20.93	
5	64QAM	1	0	20.82	20.93	21.00	
5	64QAM	1	12	20.91	21.11	21.01	22
5	64QAM	1	24	20.99	20.98	20.97	
5	64QAM	12	0	19.74	19.89	19.83	
5	64QAM	12	7	19.88	19.94	19.89	21
5	64QAM	12	13	19.85	19.91	19.88	
5	64QAM	25	0	19.77	19.81	19.95	
Channel				20415	20525	20635	Tune-up limit (dBm)
Frequency (MHz)				825.5	836.5	847.5	
3	QPSK	1	0	22.56	22.81	22.65	24
3	QPSK	1	8	22.51	22.57	22.51	
3	QPSK	1	14	22.58	22.67	22.58	
3	QPSK	8	0	21.66	21.80	21.75	23
3	QPSK	8	4	21.66	21.75	21.83	
3	QPSK	8	7	21.67	21.76	21.69	
3	QPSK	15	0	21.71	21.69	21.75	23
3	16QAM	1	0	21.86	21.94	21.92	
3	16QAM	1	8	22.06	22.11	21.92	
3	16QAM	1	14	21.87	22.07	21.88	22
3	16QAM	8	0	20.75	20.68	20.71	
3	16QAM	8	4	20.79	20.93	20.77	
3	16QAM	8	7	20.64	20.83	20.77	22
3	16QAM	15	0	20.72	20.82	20.79	
3	64QAM	1	0	20.77	20.76	20.88	
3	64QAM	1	8	20.82	20.92	20.92	22
3	64QAM	1	14	20.85	20.98	20.84	
3	64QAM	8	0	19.73	19.70	19.79	
3	64QAM	8	4	19.78	19.81	19.87	21
3	64QAM	8	7	19.82	19.89	19.78	
3	64QAM	15	0	19.60	19.78	19.86	
Channel				20407	20525	20643	Tune-up limit (dBm)
Frequency (MHz)				824.7	836.5	848.3	
1.4	QPSK	1	0	22.61	22.75	22.83	24
1.4	QPSK	1	3	22.57	22.55	22.78	
1.4	QPSK	1	5	22.60	22.65	22.67	
1.4	QPSK	3	0	22.41	22.55	22.65	23
1.4	QPSK	3	1	22.45	22.39	22.73	
1.4	QPSK	3	3	22.54	22.52	22.59	
1.4	QPSK	6	0	21.76	21.67	21.66	23
1.4	16QAM	1	0	22.09	21.96	22.12	
1.4	16QAM	1	3	21.97	21.99	21.98	
1.4	16QAM	1	5	22.01	22.06	21.89	23
1.4	16QAM	3	0	22.08	21.80	21.93	
1.4	16QAM	3	1	21.81	21.86	21.88	
1.4	16QAM	3	3	22.00	22.03	21.78	22
1.4	16QAM	6	0	20.61	20.63	20.53	



FCC SAR TEST REPORT

Report No. : FA480602-01

1.4	64QAM	1	0	20.80	21.01	20.78	22
1.4	64QAM	1	3	20.91	20.94	20.97	
1.4	64QAM	1	5	20.88	21.03	20.84	
1.4	64QAM	3	0	20.68	20.68	20.69	
1.4	64QAM	3	1	20.70	20.64	20.63	
1.4	64QAM	3	3	20.85	21.03	20.68	
1.4	64QAM	6	0	19.76	19.69	19.59	21

<LTE Band 7_Ant 1_Index 1>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				20850	21100	21350	
Frequency (MHz)				2510	2535	2560	
20	QPSK	1	0	22.91	22.41	22.30	24
20	QPSK	1	49	22.65	22.17	22.01	
20	QPSK	1	99	22.47	22.33	22.28	
20	QPSK	50	0	21.60	21.24	21.12	23
20	QPSK	50	24	21.75	21.28	21.06	
20	QPSK	50	50	21.60	21.10	21.00	
20	QPSK	100	0	21.68	21.25	21.02	
20	16QAM	1	0	22.08	21.71	21.40	23
20	16QAM	1	49	22.05	21.40	21.25	
20	16QAM	1	99	21.76	21.30	21.36	
20	16QAM	50	0	20.63	20.19	20.06	22
20	16QAM	50	24	20.76	20.28	20.10	
20	16QAM	50	50	20.64	20.10	20.04	
20	16QAM	100	0	20.67	20.25	20.04	
20	64QAM	1	0	20.91	20.52	20.34	22
20	64QAM	1	49	20.85	20.33	20.19	
20	64QAM	1	99	20.71	20.25	20.23	
20	64QAM	50	0	19.66	19.28	19.11	21
20	64QAM	50	24	19.81	19.37	19.12	
20	64QAM	50	50	19.63	19.15	19.03	
20	64QAM	100	0	19.68	19.26	19.07	
Channel				20825	21100	21375	Tune-up limit (dBm)
Frequency (MHz)				2507.5	2535	2562.5	
15	QPSK	1	0	22.80	22.29	22.28	24
15	QPSK	1	37	22.69	22.15	22.10	
15	QPSK	1	74	22.59	22.11	22.24	
15	QPSK	36	0	21.69	21.30	21.06	23
15	QPSK	36	20	21.82	21.30	21.16	
15	QPSK	36	39	21.73	21.16	21.10	
15	QPSK	75	0	21.79	21.22	21.06	
15	16QAM	1	0	22.11	21.60	21.35	23
15	16QAM	1	37	22.01	21.46	21.41	
15	16QAM	1	74	21.98	21.27	21.36	
15	16QAM	36	0	20.69	20.22	20.11	22
15	16QAM	36	20	20.80	20.26	20.21	
15	16QAM	36	39	20.73	20.09	20.06	
15	16QAM	75	0	20.77	20.23	20.03	
15	64QAM	1	0	20.97	20.37	20.31	22
15	64QAM	1	37	20.94	20.40	20.32	
15	64QAM	1	74	20.79	20.27	20.27	
15	64QAM	36	0	19.74	19.24	19.09	
15	64QAM	36	20	19.90	19.36	19.17	21
15	64QAM	36	39	19.79	19.15	19.08	
15	64QAM	75	0	19.79	19.29	19.04	
Channel				20800	21100	21400	Tune-up limit (dBm)
Frequency (MHz)				2505	2535	2565	
10	QPSK	1	0	22.73	22.29	22.11	24
10	QPSK	1	25	22.63	22.17	22.05	



FCC SAR TEST REPORT

Report No. : FA480602-01

10	QPSK	1	49	22.65	22.11	22.02	23
10	QPSK	25	0	21.78	21.26	21.05	
10	QPSK	25	12	21.78	21.30	21.09	
10	QPSK	25	25	21.77	21.24	21.11	
10	QPSK	50	0	21.74	21.19	21.01	23
10	16QAM	1	0	22.14	21.64	21.35	
10	16QAM	1	25	22.07	21.52	21.32	
10	16QAM	1	49	21.99	21.43	21.34	
10	16QAM	25	0	20.76	20.27	20.07	22
10	16QAM	25	12	20.86	20.30	20.06	
10	16QAM	25	25	20.82	20.19	20.05	
10	16QAM	50	0	20.75	20.23	20.01	
10	64QAM	1	0	20.89	20.44	20.29	22
10	64QAM	1	25	20.95	20.51	20.29	
10	64QAM	1	49	20.90	20.37	20.22	
10	64QAM	25	0	19.79	19.19	19.12	
10	64QAM	25	12	19.91	19.35	19.14	21
10	64QAM	25	25	19.89	19.30	19.13	
10	64QAM	50	0	19.78	19.25	19.01	
Channel				20775	21100	21425	Tune-up limit (dBm)
Frequency (MHz)				2502.5	2535	2567.5	
5	QPSK	1	0	22.89	22.31	22.15	24
5	QPSK	1	12	22.86	22.26	22.14	
5	QPSK	1	24	22.78	22.16	22.07	
5	QPSK	12	0	21.87	21.24	21.06	
5	QPSK	12	7	21.90	21.29	21.19	23
5	QPSK	12	13	21.79	21.21	21.11	
5	QPSK	25	0	21.80	21.26	21.08	
5	16QAM	1	0	22.09	21.57	21.42	
5	16QAM	1	12	22.20	21.64	21.41	23
5	16QAM	1	24	22.11	21.53	21.34	
5	16QAM	12	0	20.84	20.24	20.08	
5	16QAM	12	7	20.88	20.32	20.22	
5	16QAM	12	13	20.84	20.22	20.12	22
5	16QAM	25	0	20.85	20.24	20.12	
5	64QAM	1	0	21.03	20.54	20.33	
5	64QAM	1	12	20.99	20.53	20.29	
5	64QAM	1	24	21.09	20.42	20.33	22
5	64QAM	12	0	19.87	19.30	19.14	
5	64QAM	12	7	19.89	19.36	19.22	
5	64QAM	12	13	19.85	19.32	19.12	
5	64QAM	25	0	19.86	19.27	19.13	21

<LTE Band 12_Ant 1_Index 1>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				23060	23095	23130	
Frequency (MHz)				704	707.5	711	
10	QPSK	1	0	22.71	22.77	22.75	24
10	QPSK	1	25	22.68	22.58	22.57	
10	QPSK	1	49	22.66	22.61	22.70	
10	QPSK	25	0	21.69	21.61	21.62	
10	QPSK	25	12	21.79	21.84	21.74	23
10	QPSK	25	25	21.67	21.74	21.71	
10	QPSK	50	0	21.73	21.68	21.57	
10	16QAM	1	0	22.00	22.02	22.07	
10	16QAM	1	25	22.04	21.95	22.04	23
10	16QAM	1	49	21.97	22.05	22.01	
10	16QAM	25	0	20.67	20.58	20.66	
10	16QAM	25	12	20.80	20.81	20.75	
10	16QAM	25	25	20.68	20.66	20.71	22



FCC SAR TEST REPORT

Report No. : FA480602-01

10	16QAM	50	0	20.75	20.68	20.62	22
10	64QAM	1	0	20.92	20.95	20.82	
10	64QAM	1	25	20.88	20.99	20.84	
10	64QAM	1	49	21.00	20.78	20.92	
10	64QAM	25	0	19.72	19.64	19.68	21
10	64QAM	25	12	19.87	19.86	19.80	
10	64QAM	25	25	19.68	19.70	19.76	
10	64QAM	50	0	19.81	19.78	19.66	
Channel				23035	23095	23155	Tune-up limit (dBm)
Frequency (MHz)				701.5	707.5	713.5	
5	QPSK	1	0	22.60	22.64	22.71	24
5	QPSK	1	12	22.63	22.53	22.45	
5	QPSK	1	24	22.65	22.58	22.51	
5	QPSK	12	0	21.61	21.44	21.56	23
5	QPSK	12	7	21.77	21.72	21.61	
5	QPSK	12	13	21.67	21.58	21.55	
5	QPSK	25	0	21.73	21.62	21.56	
5	16QAM	1	0	21.90	21.98	21.94	23
5	16QAM	1	12	22.00	21.91	21.90	
5	16QAM	1	24	21.79	21.96	21.92	
5	16QAM	12	0	20.55	20.55	20.60	22
5	16QAM	12	7	20.78	20.68	20.70	
5	16QAM	12	13	20.55	20.48	20.52	
5	16QAM	25	0	20.63	20.64	20.42	
5	64QAM	1	0	20.92	20.83	20.73	22
5	64QAM	1	12	20.70	20.84	20.80	
5	64QAM	1	24	20.93	20.71	20.79	
5	64QAM	12	0	19.65	19.45	19.55	21
5	64QAM	12	7	19.85	19.82	19.77	
5	64QAM	12	13	19.62	19.61	19.57	
5	64QAM	25	0	19.80	19.65	19.53	
Channel				23025	23095	23165	Tune-up limit (dBm)
Frequency (MHz)				700.5	707.5	714.5	
3	QPSK	1	0	22.67	22.57	22.60	24
3	QPSK	1	8	22.59	22.41	22.38	
3	QPSK	1	14	22.55	22.58	22.60	
3	QPSK	8	0	21.62	21.41	21.46	23
3	QPSK	8	4	21.74	21.72	21.57	
3	QPSK	8	7	21.58	21.54	21.64	
3	QPSK	15	0	21.61	21.55	21.49	
3	16QAM	1	0	21.92	21.91	22.07	23
3	16QAM	1	8	21.89	21.83	21.93	
3	16QAM	1	14	21.83	21.90	21.86	
3	16QAM	8	0	20.59	20.58	20.49	22
3	16QAM	8	4	20.77	20.73	20.64	
3	16QAM	8	7	20.64	20.63	20.52	
3	16QAM	15	0	20.59	20.61	20.62	
3	64QAM	1	0	20.88	20.90	20.69	22
3	64QAM	1	8	20.80	20.95	20.69	
3	64QAM	1	14	20.97	20.76	20.74	
3	64QAM	8	0	19.59	19.53	19.68	21
3	64QAM	8	4	19.71	19.72	19.66	
3	64QAM	8	7	19.68	19.58	19.64	
3	64QAM	15	0	19.72	19.67	19.61	
Channel				23017	23095	23173	Tune-up limit (dBm)
Frequency (MHz)				699.7	707.5	715.3	
1.4	QPSK	1	0	22.60	22.63	22.69	24
1.4	QPSK	1	3	22.59	22.42	22.41	
1.4	QPSK	1	5	22.57	22.48	22.51	
1.4	QPSK	3	0	22.55	22.68	22.61	
1.4	QPSK	3	1	22.65	22.56	22.46	
1.4	QPSK	3	3	22.57	22.43	22.56	23
1.4	QPSK	6	0	21.54	21.54	21.41	



FCC SAR TEST REPORT

Report No. : FA480602-01

1.4	16QAM	1	0	21.90	21.91	21.97	23
1.4	16QAM	1	3	21.95	21.86	21.97	
1.4	16QAM	1	5	21.84	21.85	21.83	
1.4	16QAM	3	0	21.55	21.64	21.45	
1.4	16QAM	3	1	21.97	21.99	22.06	
1.4	16QAM	3	3	22.01	21.85	22.04	22
1.4	16QAM	6	0	20.68	20.61	20.46	
1.4	64QAM	1	0	20.91	20.81	20.62	22
1.4	64QAM	1	3	20.77	20.84	20.73	
1.4	64QAM	1	5	20.97	20.77	20.90	
1.4	64QAM	3	0	20.57	20.61	20.47	
1.4	64QAM	3	1	20.91	20.78	20.70	
1.4	64QAM	3	3	20.85	20.80	20.68	21
1.4	64QAM	6	0	19.78	19.61	19.56	

<LTE Band 13_Ant 1_Index 1>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				23230			
Frequency (MHz)				782			
10	QPSK	1	0		22.63		24
10	QPSK	1	25		22.36		
10	QPSK	1	49		22.41		
10	QPSK	25	0		21.51		23
10	QPSK	25	12		21.55		
10	QPSK	25	25		21.43		
10	QPSK	50	0		21.26		23
10	16QAM	1	0		21.22		
10	16QAM	1	25		21.89		
10	16QAM	1	49		21.68		22
10	16QAM	25	0		20.52		
10	16QAM	25	12		20.57		
10	16QAM	25	25		20.35		22
10	16QAM	50	0		20.21		
10	64QAM	1	0		20.02		
10	64QAM	1	25		20.81		22
10	64QAM	1	49		20.48		
10	64QAM	25	0		19.32		
10	64QAM	25	12		19.39		21
10	64QAM	25	25		19.14		
10	64QAM	50	0		19.00		
Channel				23205	23230	23255	Tune-up limit (dBm)
Frequency (MHz)				779.5	782	784.5	
5	QPSK	1	0	22.47	22.49	22.39	24
5	QPSK	1	12	22.19	22.28	22.10	
5	QPSK	1	24	22.38	22.39	22.06	
5	QPSK	12	0	21.33	21.44	21.31	23
5	QPSK	12	7	21.49	21.42	21.25	
5	QPSK	12	13	21.41	21.24	21.30	
5	QPSK	25	0	21.26	21.13	21.06	23
5	16QAM	1	0	21.11	21.09	21.04	
5	16QAM	1	12	21.70	21.86	21.61	
5	16QAM	1	24	21.54	21.51	21.63	22
5	16QAM	12	0	20.39	20.41	20.17	
5	16QAM	12	7	20.55	20.56	20.39	
5	16QAM	12	13	20.30	20.22	20.13	22
5	16QAM	25	0	20.08	20.14	20.05	
5	64QAM	1	0	20.06	20.01	20.11	
5	64QAM	1	12	20.77	20.76	20.61	22
5	64QAM	1	24	20.43	20.42	20.36	
5	64QAM	12	0	19.18	19.27	19.11	



FCC SAR TEST REPORT

Report No. : FA480602-01

5	64QAM	12	7	19.25	19.26	19.11	
5	64QAM	12	13	19.01	19.04	19.09	
5	64QAM	25	0	19.00	19.10	19.08	

<LTE Band 14_Ant 1_Index 1>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				23330			
Frequency (MHz)				793			
10	QPSK	1	0		22.58		24
10	QPSK	1	25		22.31		
10	QPSK	1	49		22.29		
10	QPSK	25	0		21.51		23
10	QPSK	25	12		21.60		
10	QPSK	25	25		21.44		
10	QPSK	50	0		21.52		
10	16QAM	1	0		21.95		23
10	16QAM	1	25		21.79		
10	16QAM	1	49		21.85		
10	16QAM	25	0		20.44		22
10	16QAM	25	12		20.61		
10	16QAM	25	25		20.44		
10	16QAM	50	0		20.58		
10	64QAM	1	0		20.90		22
10	64QAM	1	25		20.78		
10	64QAM	1	49		20.57		
10	64QAM	25	0		19.51		21
10	64QAM	25	12		19.61		
10	64QAM	25	25		19.48		
10	64QAM	50	0		19.58		
Channel				23305	23330	23355	Tune-up limit (dBm)
Frequency (MHz)				790.5	793	795.5	
5	QPSK	1	0	22.43	22.47	22.44	24
5	QPSK	1	12	22.13	22.11	22.13	
5	QPSK	1	24	22.09	22.14	22.20	
5	QPSK	12	0	21.39	21.41	21.50	23
5	QPSK	12	7	21.41	21.52	21.52	
5	QPSK	12	13	21.39	21.35	21.26	
5	QPSK	25	0	21.47	21.39	21.47	23
5	16QAM	1	0	21.87	21.88	21.80	
5	16QAM	1	12	21.75	21.72	21.62	
5	16QAM	1	24	21.66	21.68	21.70	
5	16QAM	12	0	20.34	20.24	20.40	22
5	16QAM	12	7	20.47	20.45	20.50	
5	16QAM	12	13	20.28	20.33	20.38	
5	16QAM	25	0	20.52	20.40	20.57	
5	64QAM	1	0	20.73	20.73	20.86	22
5	64QAM	1	12	20.75	20.72	20.75	
5	64QAM	1	24	20.54	20.39	20.51	
5	64QAM	12	0	19.46	19.33	19.46	21
5	64QAM	12	7	19.53	19.47	19.44	
5	64QAM	12	13	19.31	19.28	19.46	
5	64QAM	25	0	19.54	19.45	19.50	

**<LTE Band 66_Ant 1_Index 1>**

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				132072	132322	132572	
Frequency (MHz)				1720	1745	1770	
20	QPSK	1	0	22.62	22.60	22.73	24
20	QPSK	1	49	22.38	22.34	22.54	
20	QPSK	1	99	22.40	22.40	22.51	
20	QPSK	50	0	21.64	21.68	21.64	23
20	QPSK	50	24	21.74	21.68	21.78	
20	QPSK	50	50	21.69	21.65	21.64	
20	QPSK	100	0	21.63	21.60	21.65	23
20	16QAM	1	0	21.73	21.68	22.04	
20	16QAM	1	49	22.00	21.93	21.91	
20	16QAM	1	99	21.79	21.81	21.78	22
20	16QAM	50	0	20.65	20.62	20.65	
20	16QAM	50	24	20.83	20.66	20.68	
20	16QAM	50	50	20.73	20.69	20.64	22
20	16QAM	100	0	20.66	20.64	20.59	
20	64QAM	1	0	20.58	20.54	20.87	
20	64QAM	1	49	20.81	20.83	20.85	22
20	64QAM	1	99	20.71	20.53	20.81	
20	64QAM	50	0	19.73	19.68	19.68	
20	64QAM	50	24	19.80	19.72	19.72	21
20	64QAM	50	50	19.71	19.69	19.63	
20	64QAM	100	0	19.69	19.59	19.59	
Channel				132047	132322	132597	Tune-up limit (dBm)
Frequency (MHz)				1717.5	1745	1772.5	
15	QPSK	1	0	22.42	22.45	22.55	24
15	QPSK	1	37	22.26	22.14	22.44	
15	QPSK	1	74	22.37	22.40	22.32	
15	QPSK	36	0	21.56	21.65	21.45	23
15	QPSK	36	20	21.67	21.51	21.73	
15	QPSK	36	39	21.56	21.45	21.62	
15	QPSK	75	0	21.47	21.40	21.51	23
15	16QAM	1	0	21.58	21.67	22.02	
15	16QAM	1	37	21.83	21.91	21.77	
15	16QAM	1	74	21.75	21.64	21.61	22
15	16QAM	36	0	20.54	20.46	20.61	
15	16QAM	36	20	20.69	20.48	20.52	
15	16QAM	36	39	20.59	20.61	20.50	22
15	16QAM	75	0	20.46	20.54	20.45	
15	64QAM	1	0	20.47	20.43	20.68	
15	64QAM	1	37	20.66	20.77	20.85	22
15	64QAM	1	74	20.71	20.52	20.64	
15	64QAM	36	0	19.54	19.62	19.52	
15	64QAM	36	20	19.62	19.59	19.52	21
15	64QAM	36	39	19.64	19.69	19.53	
15	64QAM	75	0	19.56	19.58	19.59	
Channel				132022	132322	132622	Tune-up limit (dBm)
Frequency (MHz)				1715	1745	1775	
10	QPSK	1	0	22.53	22.48	22.72	24
10	QPSK	1	25	22.27	22.21	22.40	
10	QPSK	1	49	22.40	22.37	22.35	
10	QPSK	25	0	21.64	21.53	21.54	23
10	QPSK	25	12	21.63	21.50	21.69	
10	QPSK	25	25	21.50	21.46	21.44	
10	QPSK	50	0	21.60	21.54	21.45	23
10	16QAM	1	0	21.62	21.56	21.93	
10	16QAM	1	25	21.81	21.89	21.90	
10	16QAM	1	49	21.70	21.77	21.66	



FCC SAR TEST REPORT

Report No. : FA480602-01

10	16QAM	25	0	20.64	20.61	20.58	22
10	16QAM	25	12	20.69	20.52	20.63	
10	16QAM	25	25	20.60	20.53	20.58	
10	16QAM	50	0	20.63	20.49	20.42	
10	64QAM	1	0	20.56	20.44	20.73	22
10	64QAM	1	25	20.76	20.73	20.65	
10	64QAM	1	49	20.65	20.46	20.77	
10	64QAM	25	0	19.53	19.67	19.55	21
10	64QAM	25	12	19.79	19.65	19.64	
10	64QAM	25	25	19.59	19.69	19.59	
10	64QAM	50	0	19.54	19.42	19.39	
Channel				131997	132322	132647	Tune-up limit (dBm)
Frequency (MHz)				1712.5	1745	1777.5	
5	QPSK	1	0	22.52	22.51	22.59	24
5	QPSK	1	12	22.21	22.17	22.50	
5	QPSK	1	24	22.24	22.30	22.34	
5	QPSK	12	0	21.48	21.64	21.48	23
5	QPSK	12	7	21.78	21.60	21.64	
5	QPSK	12	13	21.67	21.63	21.51	
5	QPSK	25	0	21.46	21.48	21.51	
5	16QAM	1	0	21.54	21.56	21.96	23
5	16QAM	1	12	21.96	21.73	21.85	
5	16QAM	1	24	21.69	21.61	21.74	
5	16QAM	12	0	20.54	20.51	20.51	22
5	16QAM	12	7	20.81	20.60	20.57	
5	16QAM	12	13	20.55	20.66	20.50	
5	16QAM	25	0	20.63	20.58	20.58	
5	64QAM	1	0	20.42	20.47	20.87	22
5	64QAM	1	12	20.79	20.68	20.82	
5	64QAM	1	24	20.68	20.37	20.61	
5	64QAM	12	0	19.68	19.54	19.53	21
5	64QAM	12	7	19.60	19.61	19.67	
5	64QAM	12	13	19.56	19.66	19.50	
5	64QAM	25	0	19.67	19.47	19.46	
Channel				131987	132322	132657	Tune-up limit (dBm)
Frequency (MHz)				1711.5	1745	1778.5	
3	QPSK	1	0	22.61	22.60	22.69	24
3	QPSK	1	8	22.30	22.15	22.54	
3	QPSK	1	14	22.24	22.26	22.35	
3	QPSK	8	0	21.44	21.62	21.46	23
3	QPSK	8	4	21.62	21.63	21.57	
3	QPSK	8	7	21.56	21.47	21.47	
3	QPSK	15	0	21.65	21.53	21.43	
3	16QAM	1	0	21.68	21.49	21.98	23
3	16QAM	1	8	21.87	21.73	21.91	
3	16QAM	1	14	21.78	21.81	21.73	
3	16QAM	8	0	20.51	20.43	20.60	22
3	16QAM	8	4	20.82	20.59	20.52	
3	16QAM	8	7	20.62	20.50	20.64	
3	16QAM	15	0	20.53	20.46	20.55	
3	64QAM	1	0	20.53	20.48	20.71	22
3	64QAM	1	8	20.70	20.68	20.80	
3	64QAM	1	14	20.69	20.40	20.81	
3	64QAM	8	0	19.66	19.66	19.55	21
3	64QAM	8	4	19.64	19.70	19.52	
3	64QAM	8	7	19.53	19.59	19.45	
3	64QAM	15	0	19.58	19.49	19.48	
Channel				131979	132322	132665	Tune-up limit (dBm)
Frequency (MHz)				1710.7	1745	1779.3	
1.4	QPSK	1	0	22.45	22.49	22.56	24
1.4	QPSK	1	3	22.36	22.14	22.47	
1.4	QPSK	1	5	22.29	22.22	22.36	
1.4	QPSK	3	0	22.42	22.39	22.39	



FCC SAR TEST REPORT

Report No. : FA480602-01

1.4	QPSK	3	1	22.43	22.36	22.44	23
1.4	QPSK	3	3	22.45	22.46	22.44	
1.4	QPSK	6	0	21.65	21.54	21.45	
1.4	16QAM	1	0	21.63	21.61	21.92	23
1.4	16QAM	1	3	21.94	21.88	21.74	
1.4	16QAM	1	5	21.62	21.77	21.76	
1.4	16QAM	3	0	21.47	21.54	21.61	
1.4	16QAM	3	1	21.54	21.55	21.51	
1.4	16QAM	3	3	21.56	21.50	21.51	22
1.4	16QAM	6	0	20.60	20.63	20.54	
1.4	64QAM	1	0	20.55	20.34	20.67	22
1.4	64QAM	1	3	20.72	20.71	20.85	
1.4	64QAM	1	5	20.68	20.51	20.72	
1.4	64QAM	3	0	20.61	20.52	20.62	
1.4	64QAM	3	1	20.65	20.51	20.65	
1.4	64QAM	3	3	20.64	20.66	20.57	21
1.4	64QAM	6	0	19.62	19.51	19.42	

<LTE Band 71_Ant 1_Index 1>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				133222	133297	133372	
Frequency (MHz)				673	680.5	688	
20	QPSK	1	0	22.48	22.58	22.54	24
20	QPSK	1	49	22.44	22.51	22.53	
20	QPSK	1	99	22.44	22.48	22.37	
20	QPSK	50	0	21.36	21.51	21.51	23
20	QPSK	50	24	21.58	21.62	21.61	
20	QPSK	50	50	21.51	21.60	21.57	
20	QPSK	100	0	21.47	21.57	21.55	23
20	16QAM	1	0	21.85	21.76	21.90	
20	16QAM	1	49	21.82	21.94	21.88	
20	16QAM	1	99	21.73	21.81	21.76	22
20	16QAM	50	0	20.44	20.52	20.59	
20	16QAM	50	24	20.45	20.67	20.65	
20	16QAM	50	50	20.60	20.64	20.67	22
20	16QAM	100	0	20.46	20.52	20.54	
20	64QAM	1	0	20.64	20.54	20.80	
20	64QAM	1	49	20.58	20.66	20.57	21
20	64QAM	1	99	20.62	20.69	20.60	
20	64QAM	50	0	19.40	19.52	19.54	
20	64QAM	50	24	19.50	19.62	19.60	21
20	64QAM	50	50	19.66	19.66	19.64	
20	64QAM	100	0	19.56	19.57	19.55	
Channel				133197	133297	133397	
Frequency (MHz)				670.5	680.5	690.5	
15	QPSK	1	0	22.31	22.39	22.56	24
15	QPSK	1	37	22.44	22.51	22.47	
15	QPSK	1	74	22.28	22.32	22.26	
15	QPSK	36	0	21.23	21.47	21.37	23
15	QPSK	36	20	21.44	21.51	21.57	
15	QPSK	36	39	21.40	21.57	21.43	
15	QPSK	75	0	21.38	21.52	21.55	23
15	16QAM	1	0	21.68	21.64	21.79	
15	16QAM	1	37	21.79	21.89	21.83	
15	16QAM	1	74	21.64	21.69	21.61	22
15	16QAM	36	0	20.34	20.43	20.44	
15	16QAM	36	20	20.39	20.66	20.47	
15	16QAM	36	39	20.54	20.55	20.65	22
15	16QAM	75	0	20.45	20.46	20.38	
15	64QAM	1	0	20.51	20.34	20.68	22



FCC SAR TEST REPORT

Report No. : FA480602-01

15	64QAM	1	37	20.54	20.52	20.43	21
15	64QAM	1	74	20.58	20.59	20.58	
15	64QAM	36	0	19.38	19.47	19.48	
15	64QAM	36	20	19.32	19.48	19.40	
15	64QAM	36	39	19.51	19.59	19.46	
15	64QAM	75	0	19.49	19.47	19.38	
Channel				133172	133297	133422	Tune-up limit (dBm)
Frequency (MHz)				668	680.5	693	
10	QPSK	1	0	22.48	22.39	22.43	24
10	QPSK	1	25	22.38	22.45	22.36	
10	QPSK	1	49	22.34	22.45	22.27	
10	QPSK	25	0	21.24	21.37	21.39	23
10	QPSK	25	12	21.46	21.42	21.45	
10	QPSK	25	25	21.39	21.49	21.48	
10	QPSK	50	0	21.27	21.52	21.45	
10	16QAM	1	0	21.83	21.73	21.71	
10	16QAM	1	25	21.69	21.86	21.68	23
10	16QAM	1	49	21.69	21.77	21.74	
10	16QAM	25	0	20.24	20.48	20.51	
10	16QAM	25	12	20.31	20.51	20.59	22
10	16QAM	25	25	20.48	20.54	20.66	
10	16QAM	50	0	20.33	20.34	20.35	
10	64QAM	1	0	20.59	20.54	20.62	22
10	64QAM	1	25	20.53	20.64	20.50	
10	64QAM	1	49	20.53	20.50	20.55	
10	64QAM	25	0	19.29	19.50	19.39	21
10	64QAM	25	12	19.39	19.44	19.56	
10	64QAM	25	25	19.54	19.66	19.56	
10	64QAM	50	0	19.45	19.49	19.47	
Channel				133147	133297	133447	Tune-up limit (dBm)
Frequency (MHz)				665.5	680.5	695.5	
5	QPSK	1	0	22.37	22.52	22.40	24
5	QPSK	1	12	22.31	22.46	22.51	
5	QPSK	1	24	22.39	22.48	22.32	
5	QPSK	12	0	21.25	21.46	21.45	23
5	QPSK	12	7	21.53	21.47	21.52	
5	QPSK	12	13	21.44	21.58	21.56	
5	QPSK	25	0	21.28	21.56	21.44	
5	16QAM	1	0	21.85	21.56	21.70	23
5	16QAM	1	12	21.74	21.84	21.83	
5	16QAM	1	24	21.56	21.69	21.61	
5	16QAM	12	0	20.36	20.40	20.44	22
5	16QAM	12	7	20.30	20.55	20.52	
5	16QAM	12	13	20.41	20.59	20.63	
5	16QAM	25	0	20.43	20.44	20.35	
5	64QAM	1	0	20.46	20.40	20.80	22
5	64QAM	1	12	20.50	20.63	20.54	
5	64QAM	1	24	20.62	20.64	20.44	
5	64QAM	12	0	19.25	19.46	19.34	21
5	64QAM	12	7	19.39	19.60	19.47	
5	64QAM	12	13	19.56	19.54	19.60	
5	64QAM	25	0	19.55	19.41	19.42	

<LTE DL Carrier Aggregation>

General Note:

1. According to 202410 TCB workshop, the downlink (DL) pertains to receiver functionality, thus it is not related to RF exposure compliance limits related to cumulative effects of different transmitters.
2. According to 202410 TCB workshop, equipment authorization applications shall refer to the worst-case UL powers resulting from all the possible modes of operations. Accordingly, CA-DL cases do not need to be analyzed separately, unless pertinent to establishing UL power setting.
3. This device supports LTE carrier aggregation in the downlink. All uplink maximum output power with downlink carrier aggregation active does not show more than ¼ dB higher than the maximum output power without downlink carrier aggregation active, therefore SAR evaluation with downlink carrier aggregation active can be excluded

<LTE UL carrier aggregation>

General Note:

1. The device supports intra-band uplink carrier aggregation with a maximum of two 20MHz component carriers. For intra band contiguous carrier aggregation scenarios, 3GPP 36.101 table 6.2.2A-1 specifies that the aggregate maximum allowed output power is equivalent to the single carrier scenario. 3GPP 36.101 6.2.3A allows for several dB of MPR to be applied when not-contiguous RB allocation is implemented. The conducted power and MPR setting in this device are permanently implemented pre 3GPP requirement.
2. The device supports uplink carrier aggregation with a maximum of two 20MHz component carriers. For intra band contiguous carrier aggregation scenarios, 3GPP 36.101 table 6.2.2A-1 specifies that the aggregate maximum allowed output power is equivalent to the single carrier scenario. 3GPP 36.101 6.2.3A allows for several dB of MPR to be applied when not-contiguous RB allocation is implemented. The conducted power and MPR setting in this device are permanently implemented pre the 3GPP requirement.
3. According TCB workshop, the output power with uplink CA active was measured for the configuration with the highest reported SAR with single carrier for each exposure condition. The power was measured with wideband signal integration over both component carriers.
4. According TCB workshop, the output power with uplink CA active was measured for the configuration with the highest reported SAR with single carrier for each exposure condition. The power was measured with wideband signal integration over both component carriers.
5. Additional SAR measurement for LTE UL CA whit other DL CA combinations active were not required since the maximum output power for this configuration was not > 0.25dB higher than the maximum output power for UL CA active.

2CC Uplink Carrier Aggregation	
Number	Combination
1	5B
2	7C
3	66B
4	66C

CA_5B_Ant 1										
Combination 10MHz+10MHz (50RB+50RB)										
PCC Channel	SCC Channel	Modulation	PCC		SCC		Total RB Size	Target MPR Level (dB)	Measured Power (dBm)	Tune up Power (dBm)
			RB Size	RB offset	RB Size	RB offset				
20450	20549	QPSK	1	0	0	0	1	0	22.76	24
20475	20574	QPSK	1	49	1	0	2	0	22.86	24
20600	20501	QPSK	1	0	1	49	2	0	22.79	24

CA_7C_Ant 1										
Combination 20MHz+20MHz (100RB+100RB)										
PCC Channel	SCC Channel	Modulation	PCC		SCC		Total RB Size	Target MPR Level (dB)	Measured Power (dBm)	Tune up Power (dBm)
			RB Size	RB offset	RB Size	RB offset				
20850	21048	QPSK	1	0	0	0	1	0	22.89	24
21100	20902	QPSK	1	0	1	99	2	0	22.84	24
21350	21152	QPSK	1	0	1	99	2	0	22.83	24

CA_66B_Ant 1										
Combination 15MHz+5MHz (75RB+25RB)										
PCC Channel	SCC Channel	Modulation	PCC		SCC		Total RB Size	Target MPR Level (dB)	Measured Power (dBm)	Tune up Power (dBm)
			RB Size	RB offset	RB Size	RB offset				
132047	132140	QPSK	1	0	0	0	1	0	22.48	24
132322	132229	QPSK	1	0	1	24	2	0	22.52	24
132597	132504	QPSK	1	0	1	24	2	0	22.66	24

CA_66C_Ant 1										
Combination 20MHz+20MHz (100RB+100RB)										
PCC Channel	SCC Channel	Modulation	PCC		SCC		Total RB Size	Target MPR Level (dB)	Measured Power (dBm)	Tune up Power (dBm)
			RB Size	RB offset	RB Size	RB offset				
132072	132270	QPSK	1	0	0	0	1	0	22.47	24
132322	132124	QPSK	1	0	1	99	2	0	22.68	24
132572	132374	QPSK	1	0	1	99	2	0	22.71	24

11. 5G NR Output Power (Unit: dBm)

General Note:

1. Referencing the procedure in KDB 941225, the test procedures are outlined as below
 - a. For DFT-OFDM output power measurement, full measurement was done for Pi/2 BPSK and QPSK and for the largest supported bandwidth, repeat test for 16QAM/64QAM/256QAM under 1RB 1Offset configuration. For smaller bandwidth, measure conducted power for Pi/2 BPSK and 1RB 1Offset configuration.
 - b. According to the tune-up, CP-OFDM output power is not ½ dB higher than DFT-OFDM mode, and the reported SAR of DFT-OFDM mode reported SAR is ≤ 1.45 W/kg, SAR test and thus conducted power for CP-OFDM mode is not required.
 - c. To start SAR test for the largest channel bandwidth for Pi/2 BPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel. Also do SAR test for 50% RB allocation for Pi/2 BPSK SAR testing using 1RB Pi/2 BPSK allocation procedure
 - d. For Pi/2 BPSK with 100% RB allocation, SAR test is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
 - e. For higher modulation QPSK/16QAM/64QAM/256QAM, according to tune-up document the power level is not ½ dB higher than the same configuration in Pi/2 BPSK, also reported SAR for the Pi/2 BPSK configuration is less than 1.45 W/kg, QPSK/16QAM/64QAM/256QAM SAR testing are not required.
 - f. Smaller bandwidth output power for each RB allocation configuration for this device is not ½ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg, smaller bandwidth SAR testing is not required for this device
2. Due to test setup limitations, SAR testing for NR was performed using Factory Test Mode software to establish the connection and perform SAR with 100% transmission. And only for TDD power class2 was performed using Factory Test Mode software to establish the connection and perform SAR with 50% transmission.

<3GPP 38.101 MPR for EN-DC>

Table 6.2.2-1 Maximum power reduction (MPR) for power class 3

Modulation		MPR (dB)		
		Edge RB allocations	Outer RB allocations	Inner RB allocations
DFT-s-OFDM	Pi/2 BPSK	$\leq 3.5^1$	$\leq 1.2^1$	$\leq 0.2^1$
		$\leq 0.5^2$	$\leq 0.5^2$	0 ²
	QPSK	≤ 1		0
	16 QAM	≤ 2		≤ 1
	64 QAM	≤ 2.5		
CP-OFDM	256 QAM	≤ 4.5		
	QPSK	≤ 3		≤ 1.5
	16 QAM	≤ 3		≤ 2
	64 QAM	≤ 3.5		
	256 QAM	≤ 6.5		

NOTE 1: Applicable for UE operating in TDD mode with Pi/2 BPSK modulation and UE indicates support for UE capability powerBoosting-pi2BPSK and if the IE powerBoostPi2BPSK is set to 1 and 40 % or less slots in radio frame are used for UL transmission for bands n40, n41, n77, n78 and n79. The reference power of 0 dB MPR is 26 dBm.

NOTE 2: Applicable for UE operating in FDD mode, or in TDD mode in bands other than n40, n41, n77, n78 and n79 with Pi/2 BPSK modulation and if the IE powerBoostPi2BPSK is set to 0 and if more than 40 % of slots in radio frame are used for UL transmission for bands n40, n41, n77, n78 and n79.

Table 6.2.2-2 Maximum power reduction (MPR) for power class 2

Modulation		MPR (dB)		
		Edge RB allocations	Outer RB allocations	Inner RB allocations
DFT-s-OFDM	Pi/2 BPSK	≤ 3.5	≤ 0.5	0
	QPSK	≤ 3.5	≤ 1	0
	16 QAM	≤ 3.5	≤ 2	≤ 1
	64 QAM	≤ 3.5	≤ 2.5	
	256 QAM	≤ 4.5		
CP-OFDM	QPSK	≤ 3.5	≤ 3	≤ 1.5
	16 QAM	≤ 3.5	≤ 3	≤ 2
	64 QAM	≤ 3.5		
	256 QAM	≤ 6.5		

<FR1 n2_Ant 1_Index 1>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				372000	376000	380000	
Frequency (MHz)				1860	1880	1900	
20	PI/2 BPSK	1	1	23.04	23.11	23.06	24.0
20	PI/2 BPSK	1	53	22.91	23.10	22.97	
20	PI/2 BPSK	1	104	23.05	23.06	22.87	
20	PI/2 BPSK	50	0	22.40	22.55	22.44	23.5
20	PI/2 BPSK	50	28	22.90	23.00	22.93	24.0
20	PI/2 BPSK	50	56	22.47	22.60	22.60	23.5
20	PI/2 BPSK	100	0	22.47	22.55	22.35	
20	QPSK	1	1	22.97	23.07	22.89	24.0
20	QPSK	1	53	23.06	23.06	22.97	
20	QPSK	1	104	22.99	23.01	22.95	
20	QPSK	50	0	22.08	22.08	21.95	23.0
20	QPSK	50	28	22.89	23.02	22.83	24.0
20	QPSK	50	56	22.00	22.12	21.92	23.0
20	QPSK	100	0	22.08	22.10	22.09	
20	16QAM	1	1	22.02	22.09	21.90	23.0
20	64QAM	1	1	20.36	20.48	20.38	21.5
20	256QAM	1	1	18.43	18.45	18.31	19.5
Channel				371500	376000	380500	Tune-up limit (dBm)
Frequency (MHz)				1857.5	1880	1902.5	
15	PI/2 BPSK	1	1	22.92	23.08	22.88	24.0
Channel				371000	376000	381000	Tune-up limit (dBm)
Frequency (MHz)				1855	1880	1905	
10	PI/2 BPSK	1	1	22.85	23.07	22.92	24.0
Channel				370500	376000	381500	Tune-up limit (dBm)
Frequency (MHz)				1852.5	1880	1907.5	
5	PI/2 BPSK	1	1	22.92	22.98	23.01	24.0

<FR1 n5_Ant 1_Index 1>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				166800	167300	167800	
Frequency (MHz)				834	836.5	839	
20	PI/2 BPSK	1	1	22.83	22.97	22.87	24.0
20	PI/2 BPSK	1	53	22.69	22.85	22.74	
20	PI/2 BPSK	1	104	22.61	22.79	22.67	
20	PI/2 BPSK	50	0	22.25	22.30	22.17	23.5
20	PI/2 BPSK	50	28	22.79	22.91	22.78	24.0
20	PI/2 BPSK	50	56	22.27	22.31	22.16	23.5
20	PI/2 BPSK	100	0	22.23	22.28	22.20	
20	QPSK	1	1	22.64	22.82	22.65	24.0
20	QPSK	1	53	22.78	22.92	22.72	
20	QPSK	1	104	22.66	22.86	22.79	
20	QPSK	50	0	21.57	21.77	21.66	23.0
20	QPSK	50	28	22.77	22.83	22.75	24.0
20	QPSK	50	56	21.78	21.85	21.68	23.0
20	QPSK	100	0	21.76	21.85	21.77	
20	16QAM	1	1	21.73	21.79	21.65	23.0
20	64QAM	1	1	20.16	20.16	20.01	21.5
20	256QAM	1	1	18.03	18.19	18.03	19.5
Channel				166300	167300	168300	Tune-up limit (dBm)
Frequency (MHz)				831.5	836.5	841.5	
15	PI/2 BPSK	1	1	22.65	22.92	22.86	24.0
Channel				165800	167300	168800	Tune-up limit (dBm)
Frequency (MHz)				829	836.5	844	
10	PI/2 BPSK	1	1	22.63	22.95	22.67	24.0
Channel				165300	167300	169300	Tune-up limit (dBm)
Frequency (MHz)				826.5	836.5	846.5	
5	PI/2 BPSK	1	1	22.79	22.87	22.76	24.0

<FR1 n25_Ant 1_Index 1>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				372000	376500	381000	
Frequency (MHz)				1860	1882.5	1905	
20	PI/2 BPSK	1	1	23.10	23.15	23.08	24.0
20	PI/2 BPSK	1	53	22.91	23.04	22.84	
20	PI/2 BPSK	1	104	22.92	23.00	22.85	
20	PI/2 BPSK	50	0	22.37	22.56	22.54	23.5
20	PI/2 BPSK	50	28	22.88	23.07	22.96	24.0
20	PI/2 BPSK	50	56	22.29	22.48	22.43	23.5
20	PI/2 BPSK	100	0	22.31	22.49	22.30	
20	QPSK	1	1	23.00	23.10	22.95	24.0
20	QPSK	1	53	22.99	23.09	23.07	
20	QPSK	1	104	22.89	23.03	22.86	
20	QPSK	50	0	21.90	22.02	21.89	23.0
20	QPSK	50	28	23.01	23.04	22.95	24.0
20	QPSK	50	56	21.88	21.98	21.85	23.0
20	QPSK	100	0	22.02	22.04	21.85	
20	16QAM	1	1	21.98	22.05	21.96	23.0
20	64QAM	1	1	20.47	20.53	20.33	21.5
20	256QAM	1	1	18.44	18.55	18.39	19.5
Channel				371500	376500	381500	Tune-up limit (dBm)
Frequency (MHz)				1857.5	1882.5	1907.5	
15	PI/2 BPSK	1	1	23.01	22.98	22.99	24.0
Channel				371000	376500	382000	Tune-up limit (dBm)
Frequency (MHz)				1855	1882.5	1910	
10	PI/2 BPSK	1	1	22.94	23.12	22.96	24.0
Channel				370500	376500	382500	Tune-up limit (dBm)
Frequency (MHz)				1852.5	1882.5	1912.5	
5	PI/2 BPSK	1	1	22.99	23.05	22.94	24.0

<FR1 n66_Ant 1_Index 1>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				346000	349000	352000	
Frequency (MHz)				1730	1745	1760	
40	PI/2 BPSK	1	1	23.15	23.18	23.12	24.0
40	PI/2 BPSK	1	108	22.86	23.06	23.06	
40	PI/2 BPSK	1	214	22.92	23.00	22.80	
40	PI/2 BPSK	108	0	22.47	22.57	22.44	23.5
40	PI/2 BPSK	108	54	22.99	23.10	22.99	24.0
40	PI/2 BPSK	108	108	22.37	22.53	22.35	23.5
40	PI/2 BPSK	216	0	22.49	22.63	22.61	
40	QPSK	1	1	23.01	23.14	23.11	24.0
40	QPSK	1	108	22.97	23.10	22.95	
40	QPSK	1	214	22.94	23.03	22.92	
40	QPSK	108	0	22.01	22.07	21.91	23.0
40	QPSK	108	54	22.97	23.06	22.92	24.0
40	QPSK	108	108	22.00	22.09	21.90	23.0
40	QPSK	216	0	22.00	22.13	21.94	
40	16QAM	1	1	21.98	22.18	22.01	23.0
40	64QAM	1	1	20.43	20.60	20.60	21.5
40	256QAM	1	1	18.67	18.73	18.60	19.5
Channel				345000	349000	353000	Tune-up limit (dBm)
Frequency (MHz)				1725	1745	1765	
30	PI/2 BPSK	1	1	23.06	23.04	22.92	24.0
Channel				344000	349000	354000	Tune-up limit (dBm)
Frequency (MHz)				1720	1745	1770	
20	PI/2 BPSK	1	1	23.08	22.98	23.05	24.0
Channel				343500	349000	354500	Tune-up limit (dBm)
Frequency (MHz)				1717.5	1745	1772.5	
15	PI/2 BPSK	1	1	22.98	23.14	22.98	24.0
Channel				343000	349000	355000	Tune-up limit (dBm)
Frequency (MHz)				1715	1745	1775	
10	PI/2 BPSK	1	1	22.98	22.98	23.00	24.0
Channel				342500	349000	355500	Tune-up limit (dBm)
Frequency (MHz)				1712.5	1745	1777.5	
5	PI/2 BPSK	1	1	23.15	23.12	23.04	24.0

<FR1 n71_Ant 1_Index 1>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				134600	136100	137600	
Frequency (MHz)				673	680.5	688	
20	PI/2 BPSK	1	1	22.86	22.96	22.94	24.0
20	PI/2 BPSK	1	53	22.71	22.89	22.73	
20	PI/2 BPSK	1	104	22.65	22.81	22.77	
20	PI/2 BPSK	50	0	22.22	22.39	22.24	23.5
20	PI/2 BPSK	50	28	22.79	22.84	22.64	24.0
20	PI/2 BPSK	50	56	22.31	22.35	22.15	23.5
20	PI/2 BPSK	100	0	22.29	22.40	22.25	
20	QPSK	1	1	22.84	22.85	22.65	24.0
20	QPSK	1	53	22.71	22.83	22.68	
20	QPSK	1	104	22.69	22.82	22.82	
20	QPSK	50	0	22.38	22.39	22.35	23.0
20	QPSK	50	28	22.79	22.81	22.75	24.0
20	QPSK	50	56	22.11	22.29	22.14	23.0
20	QPSK	100	0	22.21	22.40	22.20	
20	16QAM	1	1	21.72	21.89	21.87	23.0
20	64QAM	1	1	20.25	20.32	20.21	21.5
20	256QAM	1	1	18.08	18.25	18.07	19.5
Channel				134100	136100	138100	Tune-up limit (dBm)
Frequency (MHz)				670.5	680.5	690.5	
15	PI/2 BPSK	1	1	22.72	22.91	22.80	24.0
Channel				133600	136100	138600	Tune-up limit (dBm)
Frequency (MHz)				668	680.5	693	
10	PI/2 BPSK	1	1	22.61	22.91	22.78	24.0
Channel				133100	136100	139100	Tune-up limit (dBm)
Frequency (MHz)				665.5	680.5	695.5	
5	PI/2 BPSK	1	1	22.75	22.93	22.88	24.0

<FR1 n41_Ant 1_Index 1>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				509202	518598	528000	24.0
Frequency (MHz)				2546.01	2592.99	2640	
100	PI/2 BPSK	1	1	23.12	22.67	22.55	
100	PI/2 BPSK	1	137	22.91	22.59	22.53	23.5
100	PI/2 BPSK	1	271	22.99	22.58	22.52	
100	PI/2 BPSK	135	0	22.40	22.22	22.39	
100	PI/2 BPSK	135	69	22.91	22.46	22.41	23.5
100	PI/2 BPSK	135	138	22.42	22.30	22.29	
100	PI/2 BPSK	270	0	22.41	22.38	22.40	
100	QPSK	1	1	23.08	22.59	22.47	24.0
100	QPSK	1	137	22.88	22.54	22.46	
100	QPSK	1	271	22.98	22.53	22.43	
100	QPSK	135	0	21.92	21.85	21.80	23.0
100	QPSK	135	69	22.85	22.45	22.41	
100	QPSK	135	138	21.95	21.95	21.79	
100	QPSK	270	0	21.92	21.89	21.76	23.0
100	16QAM	1	1	21.95	21.84	21.94	
100	64QAM	1	1	20.81	20.80	20.76	
100	256QAM	1	1	18.69	18.68	18.51	19.5
Channel				508200	518598	528996	24.0
Frequency (MHz)				2541	2592.99	2644.98	
90	PI/2 BPSK	1	1	23.06	22.64	22.42	
Channel				507204	518598	529998	24.0
Frequency (MHz)				2536.02	2592.99	2649.99	
80	PI/2 BPSK	1	1	23.11	22.55	22.55	
Channel				505200	518598	531996	24.0
Frequency (MHz)				2526	2592.99	2659.98	
60	PI/2 BPSK	1	1	23.07	22.47	22.37	
Channel				504204	518598	532998	24.0
Frequency (MHz)				2521.02	2592.99	2664.99	
50	PI/2 BPSK	1	1	23.00	22.60	22.39	
Channel				503202	518598	534000	24.0
Frequency (MHz)				2516.01	2592.99	2670	
40	PI/2 BPSK	1	1	23.00	22.56	22.38	
Channel				502200	518598	534996	24.0
Frequency (MHz)				2511	2592.99	2674.98	
30	PI/2 BPSK	1	1	23.08	22.57	22.45	
Channel				501204	518598	535998	24.0
Frequency (MHz)				2506.02	2592.99	2679.99	
20	PI/2 BPSK	1	1	23.04	22.53	22.47	

<FR1 n41_Ant 2_Index 1>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				509202	518598	528000	24.0
Frequency (MHz)				2546.01	2592.99	2640	
100	PI/2 BPSK	1	1	23.70	23.58	23.43	
100	PI/2 BPSK	1	137	23.07	22.98	22.87	23.5
100	PI/2 BPSK	1	271	22.57	22.39	22.38	
100	PI/2 BPSK	135	0	22.98	22.82	22.96	
100	PI/2 BPSK	135	69	23.28	23.21	23.26	23.5
100	PI/2 BPSK	135	138	22.73	22.68	22.69	
100	PI/2 BPSK	270	0	23.03	22.91	22.89	
100	QPSK	1	1	23.35	23.30	23.17	24.0
100	QPSK	1	137	22.98	22.87	22.81	
100	QPSK	1	271	22.48	22.33	22.41	
100	QPSK	135	0	23.00	22.97	22.83	23.0
100	QPSK	135	69	23.27	23.26	23.08	
100	QPSK	135	138	22.74	22.62	22.62	
100	QPSK	270	0	22.99	22.97	22.90	23.0
100	16QAM	1	1	22.93	22.79	22.76	
100	64QAM	1	1	21.48	21.46	21.31	
100	256QAM	1	1	19.46	19.28	19.28	19.5
Channel				508200	518598	528996	24.0
Frequency (MHz)				2541	2592.99	2644.98	
90	PI/2 BPSK	1	1	23.66	23.52	23.27	
Channel				507204	518598	529998	24.0
Frequency (MHz)				2536.02	2592.99	2649.99	
80	PI/2 BPSK	1	1	23.65	23.44	23.41	
Channel				505200	518598	531996	24.0
Frequency (MHz)				2526	2592.99	2659.98	
60	PI/2 BPSK	1	1	23.56	23.39	23.42	
Channel				504204	518598	532998	24.0
Frequency (MHz)				2521.02	2592.99	2664.99	
50	PI/2 BPSK	1	1	23.63	23.44	23.33	
Channel				503202	518598	534000	24.0
Frequency (MHz)				2516.01	2592.99	2670	
40	PI/2 BPSK	1	1	23.50	23.47	23.24	
Channel				502200	518598	534996	24.0
Frequency (MHz)				2511	2592.99	2674.98	
30	PI/2 BPSK	1	1	23.52	23.48	23.42	
Channel				501204	518598	535998	24.0
Frequency (MHz)				2506.02	2592.99	2679.99	
20	PI/2 BPSK	1	1	23.57	23.57	23.30	



<FR1 n41_HPUE_Ant 2_Index 1>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				509202	518598	528000	27.0
Frequency (MHz)				2546.01	2592.99	2640	
100	PI/2 BPSK	1	1	26.04	26.33	26.31	
100	PI/2 BPSK	1	137	25.94	26.21	26.17	26.5
100	PI/2 BPSK	1	271	25.98	26.25	26.21	
100	PI/2 BPSK	135	0	25.50	25.69	25.64	
100	PI/2 BPSK	135	69	25.94	26.21	26.12	26.5
100	PI/2 BPSK	135	138	25.49	25.67	25.49	
100	PI/2 BPSK	270	0	25.64	25.70	25.69	
100	QPSK	1	1	26.01	26.28	26.25	27.0
100	QPSK	1	137	25.96	26.26	26.17	
100	QPSK	1	271	25.99	26.25	26.09	
100	QPSK	135	0	25.13	25.19	25.05	26.0
100	QPSK	135	69	25.98	26.19	26.13	
100	QPSK	135	138	25.11	25.17	24.98	
100	QPSK	270	0	25.00	25.20	25.20	24.5
100	16QAM	1	1	25.66	25.69	25.66	
100	64QAM	1	1	23.72	23.88	23.76	
100	256QAM	1	1	21.89	21.89	21.71	22.5
Channel				508200	518598	528996	27.0
Frequency (MHz)				2541	2592.99	2644.98	
90	PI/2 BPSK	1	1	25.92	26.31	26.26	
Channel				507204	518598	529998	27.0
Frequency (MHz)				2536.02	2592.99	2649.99	
80	PI/2 BPSK	1	1	25.98	26.14	26.28	
Channel				505200	518598	531996	27.0
Frequency (MHz)				2526	2592.99	2659.98	
60	PI/2 BPSK	1	1	25.95	26.31	26.27	
Channel				504204	518598	532998	27.0
Frequency (MHz)				2521.02	2592.99	2664.99	
50	PI/2 BPSK	1	1	25.98	26.26	26.19	
Channel				503202	518598	534000	27.0
Frequency (MHz)				2516.01	2592.99	2670	
40	PI/2 BPSK	1	1	26.02	26.21	26.18	
Channel				502200	518598	534996	27.0
Frequency (MHz)				2511	2592.99	2674.98	
30	PI/2 BPSK	1	1	25.96	26.14	26.12	
Channel				501204	518598	535998	27.0
Frequency (MHz)				2506.02	2592.99	2679.99	
20	PI/2 BPSK	1	1	25.84	26.22	26.13	



<FR1 n77_Ant 1_Index 1>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				650000	656000	662000	
Frequency (MHz)				3750	3840	3930	
100	PI/2 BPSK	1	1	23.36	23.50	23.00	24.0
100	PI/2 BPSK	1	137	23.32	23.32	22.99	
100	PI/2 BPSK	1	271	23.02	23.04	22.88	
100	PI/2 BPSK	135	0	22.75	22.87	22.70	23.5
100	PI/2 BPSK	135	69	23.09	23.26	22.96	24.0
100	PI/2 BPSK	135	138	22.55	22.62	22.52	23.5
100	PI/2 BPSK	270	0	22.53	22.69	22.66	
100	QPSK	1	1	23.28	23.46	22.93	24.0
100	QPSK	1	137	23.13	23.32	22.88	
100	QPSK	1	271	22.94	23.03	22.88	
100	QPSK	135	0	22.32	22.36	22.31	23.0
100	QPSK	135	69	23.09	23.19	22.83	24.0
100	QPSK	135	138	21.96	22.11	21.99	23.0
100	QPSK	270	0	21.95	22.15	22.06	
100	16QAM	1	1	22.32	22.42	22.34	23.0
100	64QAM	1	1	21.11	21.24	21.17	21.5
100	256QAM	1	1	19.03	19.05	18.96	19.5
Channel				649668	656000	662332	Tune-up limit (dBm)
Frequency (MHz)				3745.02	3840	3934.98	
90	PI/2 BPSK	1	1	23.31	23.39	22.93	24.0
Channel				649334	656000	662666	Tune-up limit (dBm)
Frequency (MHz)				3740.01	3840	3939.99	
80	PI/2 BPSK	1	1	23.16	23.45	22.94	24.0
Channel				649000	656000	663000	Tune-up limit (dBm)
Frequency (MHz)				3735	3840	3945	
70	PI/2 BPSK	1	1	23.22	23.31	22.89	24.0
Channel				648668	656000	663332	Tune-up limit (dBm)
Frequency (MHz)				3730.02	3840	3949.98	
60	PI/2 BPSK	1	1	23.32	23.43	22.82	24.0
Channel				648334	656000	663666	Tune-up limit (dBm)
Frequency (MHz)				3725.01	3840	3954.99	
50	PI/2 BPSK	1	1	23.28	23.35	23.00	24.0
Channel				648000	656000	664000	Tune-up limit (dBm)
Frequency (MHz)				3720	3840	3960	
40	PI/2 BPSK	1	1	23.22	23.32	22.97	24.0
Channel				647668	656000	664332	Tune-up limit (dBm)
Frequency (MHz)				3715.02	3840.00	3964.98	
30	PI/2 BPSK	1	1	23.24	23.42	22.82	24.0
Channel				647334	656000	664666	Tune-up limit (dBm)
Frequency (MHz)				3710.01	3840	3969.99	
20	PI/2 BPSK	1	1	23.36	23.48	22.99	24.0



<FR1 n77_Ant 2_Index 1>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				650000	656000	662000	24.0
Frequency (MHz)				3750	3840	3930	
100	PI/2 BPSK	1	1	22.66	22.52	23.13	
100	PI/2 BPSK	1	137	22.46	22.39	22.76	23.5
100	PI/2 BPSK	1	271	22.47	22.38	22.89	
100	PI/2 BPSK	135	0	22.47	22.26	22.72	
100	PI/2 BPSK	135	69	22.49	22.45	23.03	24.0
100	PI/2 BPSK	135	138	22.12	22.15	22.82	
100	PI/2 BPSK	270	0	22.21	22.48	22.83	
100	QPSK	1	1	22.53	22.42	22.85	23.0
100	QPSK	1	137	22.48	22.46	22.81	
100	QPSK	1	271	22.41	22.36	22.81	
100	QPSK	135	0	22.43	22.33	22.71	24.0
100	QPSK	135	69	22.39	22.39	22.82	
100	QPSK	135	138	22.48	22.34	22.97	
100	QPSK	270	0	22.69	22.32	22.80	23.0
100	16QAM	1	1	21.37	21.43	21.52	
100	64QAM	1	1	20.32	20.34	20.49	
100	256QAM	1	1	18.06	17.96	18.07	19.5
Channel				649668	656000	662332	24.0
Frequency (MHz)				3745.02	3840	3934.98	
90	PI/2 BPSK	1	1	22.59	22.41	22.94	
Channel				649334	656000	662666	24.0
Frequency (MHz)				3740.01	3840	3939.99	
80	PI/2 BPSK	1	1	22.61	22.36	22.96	
Channel				649000	656000	663000	24.0
Frequency (MHz)				3735	3840	3945	
70	PI/2 BPSK	1	1	22.63	22.32	23.04	
Channel				648668	656000	663332	24.0
Frequency (MHz)				3730.02	3840	3949.98	
60	PI/2 BPSK	1	1	22.52	22.47	23.03	
Channel				648334	656000	663666	24.0
Frequency (MHz)				3725.01	3840	3954.99	
50	PI/2 BPSK	1	1	22.57	22.35	23.11	
Channel				648000	656000	664000	24.0
Frequency (MHz)				3720	3840	3960	
40	PI/2 BPSK	1	1	22.65	22.34	22.95	
Channel				647668	656000	664332	24.0
Frequency (MHz)				3715.02	3840.00	3964.98	
30	PI/2 BPSK	1	1	22.62	22.45	23.06	
Channel				647334	656000	664666	24.0
Frequency (MHz)				3710.01	3840	3969.99	
20	PI/2 BPSK	1	1	22.58	22.47	23.01	



<FR1 n77_HPUE_Ant 2_Index 1>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				650000	656000	662000	27.0
Frequency (MHz)				3750	3840	3930	
100	PI/2 BPSK	1	1	25.45	25.33	26.17	
100	PI/2 BPSK	1	137	25.22	25.29	25.92	26.5
100	PI/2 BPSK	1	271	25.29	25.24	26.12	
100	PI/2 BPSK	135	0	25.11	25.15	25.22	
100	PI/2 BPSK	135	69	25.39	25.26	25.87	26.5
100	PI/2 BPSK	135	138	25.25	25.17	25.52	
100	PI/2 BPSK	270	0	25.19	25.26	25.37	
100	QPSK	1	1	25.37	25.28	26.13	27.0
100	QPSK	1	137	25.26	25.21	25.98	
100	QPSK	1	271	25.34	25.17	26.08	
100	QPSK	135	0	24.64	24.56	24.74	26.0
100	QPSK	135	69	25.36	25.29	25.86	
100	QPSK	135	138	24.84	24.84	25.02	
100	QPSK	270	0	24.83	24.83	24.86	24.5
100	16QAM	1	1	24.84	25.01	25.03	
100	64QAM	1	1	23.25	23.12	23.32	
100	256QAM	1	1	21.04	21.12	21.20	22.5
Channel				649668	656000	662332	27.0
Frequency (MHz)				3745.02	3840	3934.98	
90	PI/2 BPSK	1	1	25.36	25.30	26.16	
Channel				649334	656000	662666	27.0
Frequency (MHz)				3740.01	3840	3939.99	
80	PI/2 BPSK	1	1	25.33	25.33	26.06	
Channel				649000	656000	663000	27.0
Frequency (MHz)				3735	3840	3945	
70	PI/2 BPSK	1	1	25.28	25.27	26.10	
Channel				648668	656000	663332	27.0
Frequency (MHz)				3730.02	3840	3949.98	
60	PI/2 BPSK	1	1	25.31	25.28	26.16	
Channel				648334	656000	663666	27.0
Frequency (MHz)				3725.01	3840	3954.99	
50	PI/2 BPSK	1	1	25.31	25.25	26.08	
Channel				648000	656000	664000	27.0
Frequency (MHz)				3720	3840	3960	
40	PI/2 BPSK	1	1	25.31	25.17	26.11	
Channel				647668	656000	664332	27.0
Frequency (MHz)				3715.02	3840.00	3964.98	
30	PI/2 BPSK	1	1	25.44	25.33	26.15	
Channel				647334	656000	664666	27.0
Frequency (MHz)				3710.01	3840	3969.99	
20	PI/2 BPSK	1	1	25.31	25.22	26.14	

12. SAR Test Results

General Note:

1. Per KDB 447498 D01v06, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - b. For WWAN: Reported SAR(W/kg)= Measured SAR(W/kg)*Tune-up Scaling Factor
2. Per KDB 447498 D01v06, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the *reported* 1-g or 10-g SAR for the mid-band or highest output power channel is:
 - ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
 - ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
 - ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz
3. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥ 0.8 W/kg.

UMTS Note:

1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. The maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA / DC-HSDPA is $\leq \frac{1}{4}$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA / DC-HSDPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA, and according to the following RF output power, the output power results of the secondary modes (HSUPA, HSDPA, DC-HSDPA) are less than $\frac{1}{4}$ dB higher than the primary modes; therefore, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA.

LTE Note:

1. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
2. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
3. Per KDB 941225 D05v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
4. Per KDB 941225 D05v02r05, 16QAM output power for each RB allocation configuration is $> \text{not } \frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, 16QAM SAR testing is not required.
5. Per KDB 941225 D05v02r05, Smaller bandwidth output power for each RB allocation configuration is $> \text{not } \frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
6. For LTE B4/B5/B12/B71 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.
7. LTE band 4 SAR test was covered by Band 66; according to TCB workshop, SAR test for overlapping LTE bands can be reduced if
 - a. The maximum output power, including tolerance, for the smaller band is $\leq$ the larger band to qualify for the SAR test exclusion.
 - b. The channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band.

5G NR Note:

1. Referencing the procedure in KDB 941225, the test procedures are outlined as below:
 - a. To start SAR test for the largest channel bandwidth for PI/2 BPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel. Also do SAR test for 50% RB allocation for PI/2 BPSK SAR testing using 1RB PI/2 BPSK allocation procedure.
 - b. For PI/2 BPSK with 100% RB allocation, SAR test is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
 - c. For higher modulation QPSK/16QAM/64QAM/256QAM, according to tune-up document the power level is not $\frac{1}{2}$ dB higher than the same configuration in PI/2 BPSK, also reported SAR for the PI/2 BPSK configuration is less than 1.45 W/kg, QPSK/16QAM/64QAM/256QAM SAR testing are not required.
 - d. Smaller bandwidth output power for each RB allocation configuration for this device is not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg, smaller bandwidth SAR testing is not required for this device
 - e. For 5G FR1 n5/n41/n71/n77, the maximum channel bandwidth does not support three non-overlapping channels in the frequency band, the middle channel of the group of overlapping channels were selected for testing.
 - f. Due to test setup limitations, SAR testing for NR was performed using Factory Test Mode software to establish the connection and perform SAR with 100% transmission. And only for TDD power class2 was performed using Factory Test Mode software to establish the connection and perform SAR with 50% transmission.

12.1 Body SAR

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
01	WCDMA II_Ant 1	RMC 12.2Kbps	Front	20mm	9400	1880	23.26	24.00	1.186	-0.1	0.099	0.117
02	WCDMA IV_Ant 1	RMC 12.2Kbps	Front	20mm	1413	1732.6	23.03	24.00	1.250	-0.02	0.164	0.205
	WCDMA IV_Ant 1	RMC 12.2Kbps	Front	20mm	1312	1712.4	22.96	24.00	1.271	0.08	0.153	0.194
	WCDMA IV_Ant 1	RMC 12.2Kbps	Front	20mm	1513	1752.6	22.92	24.00	1.282	0.01	0.149	0.191
03	WCDMA V_Ant 1	RMC 12.2Kbps	Front	20mm	4182	836.4	23.13	24.00	1.222	0.14	0.031	0.038

<LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
04	LTE Band 2_Ant 1	20M	QPSK	1	0	Front	20mm	18900	1880	23.02	24.00	1.253	-0.03	0.098	0.123
	LTE Band 2_Ant 1	20M	QPSK	50	24	Front	20mm	18900	1880	21.95	23.00	1.274	0.05	0.075	0.096
05	LTE Band 5_Ant 1	10M	QPSK	1	0	Front	20mm	20525	836.5	22.93	24.00	1.279	0.04	0.067	0.086
	LTE Band 5_Ant 1	10M	QPSK	25	25	Front	20mm	20525	836.5	21.87	23.00	1.297	0.07	0.051	0.066
	LTE Band 5B_Ant 1	10M	QPSK	1	49	Front	20mm	20475+20574	831.5	22.86	24.00	1.300	-0.03	0.061	0.079
06	LTE Band 7_Ant 1	20M	QPSK	1	0	Front	20mm	20850	2510	22.91	24.00	1.285	0.14	0.092	0.118
	LTE Band 7_Ant 1	20M	QPSK	50	24	Front	20mm	20850	2510	21.75	23.00	1.334	-0.03	0.074	0.099
	LTE Band 7C_Ant 1	20M	QPSK	1	0	Front	20mm	20850+21048	2510	22.89	24.00	1.291	-0.05	0.088	0.114
07	LTE Band 12_Ant 1	10M	QPSK	1	0	Front	20mm	23095	707.5	22.77	24.00	1.327	0.14	0.035	0.046
	LTE Band 12_Ant 1	10M	QPSK	25	12	Front	20mm	23095	707.5	21.84	23.00	1.306	0.03	0.028	0.037
08	LTE Band 13_Ant 1	10M	QPSK	1	0	Front	20mm	23230	782	22.63	24.00	1.371	0.14	0.060	0.082
	LTE Band 13_Ant 1	10M	QPSK	25	12	Front	20mm	23230	782	21.55	23.00	1.396	-0.02	0.049	0.068
09	LTE Band 14_Ant 1	10M	QPSK	1	0	Front	20mm	23330	793	22.58	24.00	1.387	0.1	0.058	0.080
	LTE Band 14_Ant 1	10M	QPSK	25	12	Front	20mm	23330	793	21.60	23.00	1.380	0.07	0.046	0.063
10	LTE Band 66_Ant 1	20M	QPSK	1	0	Front	20mm	132572	1770	22.73	24.00	1.340	0	0.127	0.170
	LTE Band 66_Ant 1	20M	QPSK	50	24	Front	20mm	132572	1770	21.78	23.00	1.324	0.07	0.101	0.134
	LTE Band 66B_Ant 1	15M	QPSK	1	0	Front	20mm	132597+132504	1772.5	22.66	24.00	1.361	0.08	0.113	0.154
	LTE Band 66C_Ant 1	20M	QPSK	1	0	Front	20mm	132572+132374	1770	22.71	24.00	1.346	-0.05	0.121	0.163
11	LTE Band 71_Ant 1	20M	QPSK	1	0	Front	20mm	133297	680.5	22.58	24.00	1.387	0.04	0.028	0.039
	LTE Band 71_Ant 1	20M	QPSK	50	24	Front	20mm	133297	680.5	21.62	23.00	1.374	0.01	0.022	0.030

<5G NR SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
12	FR1 n5_Ant 1	20M	BPSK	1	1	Front	20mm	167300	836.5	22.97	24.00	1.268	-0.07	0.060	0.076
	FR1 n5_Ant 1	20M	BPSK	50	28	Front	20mm	167300	836.5	22.91	24.00	1.285	0.05	0.054	0.069
13	FR1 n25_Ant 1	20M	BPSK	1	1	Front	20mm	376500	1882.5	23.15	24.00	1.216	-0.12	0.101	0.123
	FR1 n25_Ant 1	20M	BPSK	50	28	Front	20mm	376500	1882.5	23.07	24.00	1.239	0.07	0.098	0.121
14	FR1 n66_Ant 1	40M	BPSK	1	1	Front	20mm	349000	1745	23.18	24.00	1.208	-0.04	0.163	0.197
	FR1 n66_Ant 1	40M	BPSK	108	54	Front	20mm	349000	1745	23.10	24.00	1.230	0.07	0.159	0.196
15	FR1 n71_Ant 1	20M	BPSK	1	1	Front	20mm	136100	680.5	22.96	24.00	1.271	-0.02	0.029	0.037
	FR1 n71_Ant 1	20M	BPSK	50	28	Front	20mm	136100	680.5	22.84	24.00	1.306	0.02	0.020	0.026
	FR1 n41_Ant 1	100M	BPSK	1	1	Front	20mm	518598	2592.99	22.67	24.00	1.358	-0.06	0.089	0.121
	FR1 n41_Ant 1	100M	BPSK	135	69	Front	20mm	518598	2592.99	22.46	24.00	1.426	0.05	0.082	0.117
16	FR1 n41_Ant 2	100M	BPSK	1	1	Front	20mm	518598	2592.99	23.58	24.00	1.102	0.12	0.123	0.136
	FR1 n41_Ant 2	100M	BPSK	135	69	Front	20mm	518598	2592.99	23.21	24.00	1.199	0.02	0.112	0.134
	FR1 n41_HPUE_Ant 2	100M	BPSK	1	1	Front	20mm	518598	2592.99	26.33	27.00	1.167	0.19	0.116	0.135
17	FR1 n77_Ant 1	100M	BPSK	1	1	Front	20mm	656000	3840	23.50	24.00	1.122	0.14	0.052	0.058
	FR1 n77_Ant 1	100M	BPSK	135	69	Front	20mm	656000	3840	23.26	24.00	1.186	0.07	0.048	0.057
	FR1 n77_Ant 2	100M	BPSK	1	1	Front	20mm	662000	3930	23.13	24.00	1.222	0.05	0.028	0.034
	FR1 n77_Ant 2	100M	BPSK	135	69	Front	20mm	662000	3930	23.03	24.00	1.250	-0.05	0.024	0.030
	FR1 n77_HPUE_Ant 2	100M	BPSK	1	1	Front	20mm	662000	3930	26.17	27.00	1.211	0.08	0.026	0.031

**12.2 Power Class 2 and Power Class 3 Linearity****General Note:**

This device support Power Class 2 and Power Class 3 operations. Per FCC Guidance based on the device behavior, all SAR tests were performed using Power Class 3. Power Class 2 is tested using the highest SAR test configuration in Power Class 3 for each LTE and FR1 configuration and exposure condition combination, according to the highest time averaged power for Power Class 2. When the reported SAR vs. output power is linearly scaled with < 10% discrepancy between power classes and all reported SAR are < 1.4 W/kg, Separate SAR testing for Power Class 2 is not required. Use PC3 power level and SAR to estimated PC2 SAR linearly, and check if the deviation from the measured PC2 SAR is <10%.

	FR1 n41_Ant 2	FR1 n41_Ant 2
	(Power Class 3)	(Power Class 2)
Maximum Tune up Power (dBm)	24	27
Reported 1g SAR (W/kg)	0.136	0.135
Duty Cycle	100.00%	50.00%
Frame Averaged (mW)	251.19	250.59
Linearity SAR(W/kg)	0.14	
% deviation from expected linearity		-0.50%

	FR1 n77_Ant 2	FR1 n77_Ant 2
	(Power Class 3)	(Power Class 2)
Maximum Tune up Power (dBm)	24	27
Reported 1g SAR (W/kg)	0.034	0.031
Duty Cycle	100.00%	50.00%
Frame Averaged (mW)	251.19	250.59
Linearity SAR(W/kg)	0.03	
% deviation from expected linearity		-8.61%

13. Simultaneous Transmission Analysis

NO.	Simultaneous Transmission Configurations	Body
1.	WWAN Ant 1 + WWAN Ant 2	Yes

General Note:

1. The Scaled SAR summation is calculated based on the same configuration and test position.
2. Per KDB 447498 D01v06, simultaneous transmission SAR is compliant if,
 - i) Scalar SAR summation $< 1.6\text{W/kg}$.
 - ii) $\text{SPLSR} = (\text{SAR1} + \text{SAR2})^{1.5} / (\text{min. separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$, where $(x1, y1, z1)$ and $(x2, y2, z2)$ are the coordinates of the extrapolated peak SAR locations in the zoom scan.
 - iii) If $\text{SPLSR} \leq 0.04$, simultaneously transmission SAR measurement is not necessary.
 - iv) Simultaneously transmission SAR measurement, and the reported multi-band SAR $< 1.6\text{W/kg}$.

13.1 Body Exposure Conditions

Exposure Position	1	2	1+2 Summed 1g SAR (W/kg)
	Maximum WWAN Ant 1	Maximum WWAN Ant 2	
	1g SAR (W/kg)	1g SAR (W/kg)	
Front at 20mm	0.205	0.136	0.341

Test Engineer : Albert Chen and Daniel Teng

14. Uncertainty Assessment

Per KDB 865664 D01 SAR measurement 100MHz to 6GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg and the measured 10-g SAR within a frequency band is < 3.75 W/kg. The expanded SAR measurement uncertainty must be $\leq 30\%$, for a confidence interval of $k = 2$. If these conditions are met, extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. For this device, the highest measured 1-g SAR is less 1.5W/kg. Therefore, the measurement uncertainty table is not required in this report.

Declaration of Conformity:

The test results with all measurement uncertainty excluded is presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

15. References

- [1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [2] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- [3] IEEE Std. 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", Sep 2013
- [4] SPEAG DASY System Handbook
- [5] FCC KDB 447498 D01 v06, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", Oct 2015
- [6] FCC KDB 941225 D01 v03r01, "3G SAR MEAUREMENT PROCEDURES", Oct 2015
- [7] FCC KDB 941225 D05 v02r05, "SAR Evaluation Considerations for LTE Devices", Dec 2015
- [8] FCC KDB 941225 D05A v01r02, "Rel. 10 LTE SAR Test Guidance and KDB Inquiries", Oct 2015
- [9] FCC KDB 865664 D01 v01r04, "SAR Measurement Requirements for 100 MHz to 6 GHz", Aug 2015.
- [10] FCC KDB 865664 D02 v01r02, "RF Exposure Compliance Reporting and Documentation Considerations" Oct 2015.