

TEST REPORT

Application No.: SUCR2606000576AU
Applicant: AUMOVIO Systems, Inc.
Address of Applicant: 21440 West Lake Cook, Deer Park, Illinois 60010, USA
Manufacturer: AUMOVIO Systems, Inc.
Address of Manufacturer: 21440 West Lake Cook, Deer Park, Illinois 60010, USA
EUT Description: FE5RW0D31
Model No.: FE5RW0D31
Trade Mark: AUMOVIO
FCC ID: LHJ-FE5RW0D31
Standards: 47 CFR Part 2.1091
FCC KDB 447498 D01 v06
Date of Receipt: 2026-06-26
Date of Issue: 2026-09-16

Test Result:
PASS*

* In the configuration tested, the EUT complied with the standards specified above.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Revision Record			
Version	Description	Date	Remark
00	Original	2026-09-16	/

Authorized for issue by:				
Prepared By		Nature Shen		
		Nature_Shen/Project Engineer		
Approved By		Cedar Cheng		
		Cedar Cheng /Reviewer		

Contents

1	General Information.....	4
1.1	Client Information	4
1.2	Test Facility	4
1.3	General Description of EUT	5
2	RF Exposure Evaluation.....	6
2.1	RF Exposure Compliance Requirement	6

1 General Information

1.1 Client Information

Applicant:	AUMOVIO Systems, Inc.
Address of Applicant:	21440 West Lake Cook, Deer Park, Illinois 60010, USA
Manufacturer:	AUMOVIO Systems, Inc.
Address of Manufacturer:	21440 West Lake Cook, Deer Park, Illinois 60010, USA

1.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 6336.01)**

SGS Tongfang Technical Services (Suzhou) Co., Ltd. is accredited by the American Association for Laboratory Accreditation (A2LA).

- **FCC (Designation Number: CN1312)**

This site has been recognized as an accredited testing laboratory. Test Firm Registration Number: 717327

- **ISED (CAB Identifier: CN0120)**

This site has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory.

Company Number: 27594

1.3 General Description of EUT

Hardware Version:	P2		
Software Version:	MODEMSA515M_SOP5_01.01.02		
Power Supply:	12V		
Antenna Type:	☒ External, ☐ Integrated		
HPUE Power Class:	LTE Band 41; NR Band n77		
Antenna Gain:	GSM850:	2.56dBi (Ant1)	GSM1900: 1.93dBi (Ant1)
	WCDMA Band V:	2.56dBi (Ant1)	
	LTE Band 2:	1.93dBi (Ant1)	LTE Band 4: 1.93dBi (Ant1)
	LTE Band 5:	2.56dBi (Ant1)	LTE Band 7: 1.24dBi (Ant1)
	LTE Band 25:	1.93dBi (Ant1)	LTE Band 26: 2.56dBi (Ant1)
	LTE Band 38:	1.24dBi (Ant1)	LTE Band 41: 1.24dBi (Ant1)
	NR Band n77:	-0.84dBi (Ant2)	
	ENDC: DC_2A_n77A; DC_5A_n77A; DC_7A_n77A; DC_41A_n77A		
	Note: The antenna gain are derived from the gain information report provided by the manufacturer.		
Remark: As above information is provided and confirmed by the applicant. SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.			

2 RF Exposure Evaluation

2.1 RF Exposure Compliance Requirement

2.1.1 Limits

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

F=frequency in MHz
 *=Plane-wave equivalent power density
 RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2.1.2 Test Procedure

Software provided by client enabled the EUT to transmit data at lowest, middle and highest channel individually

2.1.3 EUT RF Exposure Evaluation

Output Power Into Antenna & RF Exposure Evaluation Distance:

This confirmed that the device comply with MPE limit.

Operating Band	Frequency (MHz)	Antenna Gain (dBi)	Max Conducted Power (dBm)	EIRP(ERP) (dBm)	EIRP(ERP) Limit (dBm)	Power Density at R = 20 cm (mW/cm ²)	Limit (mW/cm ²)	Gain according to EIRP(ERP) (dBi)	Gain according to Pd (dBi)	Max Gain Allowed (dBi)	conclusion
GSM850	824.2	2.56	33.50	33.91	38.45	0.0968	0.5495	7.10	10.10	7.10	Pass
GSM1900	1850.2	1.93	30.50	32.43	33.00	0.0419	1.0000	2.50	15.70	2.50	Pass
WCDMA Band V	826.4	2.56	24.00	24.41	38.45	0.0901	0.5509	16.60	10.42	10.42	Pass
LTE Band 2	1850.7	1.93	24.00	25.93	33.00	0.0779	1.0000	9.00	13.01	9.00	Pass
LTE Band 4	1710.7	1.93	24.00	25.93	30.00	0.0779	1.0000	6.00	13.01	6.00	Pass
LTE Band 5	824.7	2.56	24.00	24.41	38.45	0.0901	0.5498	16.60	10.41	10.41	Pass
LTE Band 7	2502.5	1.24	24.00	25.24	33.00	0.0665	1.0000	9.00	13.01	9.00	Pass
LTE Band 25	1850.7	1.93	24.00	25.93	33.00	0.0779	1.0000	9.00	13.01	9.00	Pass
LTE Band 26 (814-824)	814.7	2.56	24.00	24.41	NA	0.0901	0.5431	NA	10.36	10.36	Pass
LTE Band 26 (824-849)	824.7	2.56	24.00	24.41	38.45	0.0901	0.5498	16.60	10.41	10.41	Pass
LTE Band 38	2572.5	1.24	24.00	25.24	33.00	0.0665	1.0000	9.00	13.01	9.00	Pass
LTE Band 41	2498.5	1.24	24.00	25.24	33.00	0.0665	1.0000	9.00	13.01	9.00	Pass
LTE Band 41(HPUE)	2498.5	1.24	27.00	28.24	33.00	0.1327	1.0000	6.00	10.01	6.00	Pass
NR Band n77 (3700-3980)	3710.0	-0.84	24.00	23.16	30.00	0.0412	1.0000	6.00	13.01	6.00	Pass
NR Band n77 (3700-3980)(HPUE)	3710.0	-0.84	27.00	26.16	30.00	0.0822	1.0000	3.00	10.01	3.00	Pass

Remark: Frame-average power=Burst power+ Division Factors(-9.19)

Due to the EUT support NR ENDC and CA

$$\sum_{i=1}^n \frac{S_{E_i} (duty factor)}{MPE_{E_i}} < 1$$

Both LTE and NR/LTE band can transmit simultaneously, the formula of the calculated the MPE is:
 NOTE The corresponding MEs must be expressed in terms of power density in the above summation
 Therefore, the worst-case(DC_5A_n77A) situation is 0.164+0.082=0.246, which is less than “1”,
 this confirmed that the device comply with MPE limit.

---End of Report---