



FCC RADIO TEST REPORT

FCC ID : LHJ-LNAD
Equipment : LHJ-LNAD
Brand Name : Continental
Model Name : LNAD, LNADV
Applicant : Continental Automotive Systems, Inc.
21440 W Lake Cook Rd., Deer Park, IL 60010, USA
Manufacturer : Continental Automotive Systems, Inc.
21440 W Lake Cook Rd., Deer Park, IL 60010, USA
Standard : FCC 47 CFR Part 2, 22(H), 24(E)

The product was received on Feb. 01, 2024 and testing was performed from Feb. 19, 2024 to Feb. 21, 2024. We, Sporton International Inc. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA-603-E and has been in compliance with the applicable technical standards.

The test results in this partial report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Sporton International Inc. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Product Feature of Equipment Under Test	5
1.2 Product Specification of Equipment Under Test	5
1.3 Modification of EUT	6
1.4 Testing Location	6
1.5 Applicable Standards	7
2 Test Configuration of Equipment Under Test	8
2.1 Test Mode.....	8
2.2 Connection Diagram of Test System	9
2.3 Support Unit used in test configuration	9
2.4 Frequency List of Low/Middle/High Channels	9
3 Conducted Test Result	10
3.1 Measuring Instruments.....	10
3.2 Conducted Output Power and ERP/EIRP	11
4 Radiated Test Items	12
4.1 Measuring Instruments.....	12
4.2 Test Setup	12
4.3 Test Result of Radiated Test.....	13
4.4 Field Strength of Spurious Radiation Measurement	14
5 List of Measuring Equipment.....	15
6 Measurement Uncertainty	16
Appendix A. Test Results of Conducted Test	
Appendix B. Test Results of Radiated Test	
Appendix C. Test Setup Photographs	



History of this test report

Report No.	Version	Description	Issue Date
FG420209A	01	Initial issue of report	Mar. 01, 2024

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.2	§2.1046	Conducted Output Power	Pass	-
	§22.913 (a)(5)	Effective Radiated Power (WCDMA Band V)		
	§24.232 (c)	Equivalent Isotropic Radiated Power (WCDMA Band II)		
4.4	§2.1053 §22.917 (a) §24.238 (a)	Field Strength of Spurious Radiation (WCDMA Band V) (WCDMA Band II)	Pass	32.35 dB under the limit at 5565.00 MHz

Note:

1. This partial report differs from FCC ID: LHJ-LNAD report as it tests for the replacement of the end-of-life (EOL) RF front-end switch with a pin-to-pin compatible replacement part, which is declared by the customer.
2. The test configurations are specified by the manufacturer.

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

1. The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.
2. The purpose of different model name is that LNAD does not support voice function and LNADV support.

Reviewed by: Yun Huang

Report Producer: Michelle Chen



1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	LHJ-LNAD
Brand Name	Continental
Model Name	LNAD, LNADV
FCC ID	LHJ-LNAD
Installed into the Host	Equipment name: LNAD Brand name: Continental Model name: LNAD
EUT supports Radios application	WCDMA/HSPA/LTE/GNSS
EUT Stage	Identical Prototype

Support Band and Evaluated Information	
Supported Band	WCDMA Band V, II
Evaluated and Tested Band	WCDMA Band V, II

TDD Band Power Class		
	PC3	PC2
WCDMA Band II	V	-
WCDMA Band V	V	-

1.2 Product Specification of Equipment Under Test

Product Specification is subject to this standard	
Tx Frequency	WCDMA: Band V: 826.4 MHz ~ 846.6 MHz Band II: 1852.4 MHz ~ 1907.6 MHz
Rx Frequency	WCDMA: Band V: 871.4 MHz ~ 891.6 MHz Band II: 1932.4 MHz ~ 1987.6 MHz
Maximum Output Power to Antenna	WCDMA: Band V: 22.52 dBm Band II: 23.95 dBm
Antenna Type	Dipole Antenna
Antenna Gain	Cellular Band: 0.82 dBi PCS Band: 1.52 dBi
Type of Modulation	WCDMA: QPSK (Uplink) HSDPA: 64QAM (Downlink) HSUPA: QPSK (Uplink)

Remark: The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.



1.3 Modification of EUT

No modifications made to the EUT during the testing.

1.4 Testing Location

Test Site	Sporton International Inc. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	Sporton Site No. TH03-HY
Test Engineer	Cotty Hsu
Temperature (°C)	22.1~22.8
Relative Humidity (%)	53.2~55.3

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No. 03CH15-HY (TAF Code: 3786)
Test Engineer	Danel Lee, Quentin Liu and Bigshow Wang
Temperature (°C)	21.4~22.8
Relative Humidity (%)	48~59
Remark	The Radiated Spurious Emission test item subcontracted to Sporton International Inc. Wensan Laboratory.

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC Designation No.: TW1190 and TW3786



1.5 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ ANSI C63.26-2015
- ♦ ANSI / TIA-603-E
- ♦ FCC 47 CFR Part 2, 22(H), 24(E)
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.
3. The TAF code is not including all the FCC KDB listed without accreditation.



2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in two config (Degree 0 and Degree 90), and adjusting the measurement antenna orientation, following C63.26 exploratory test procedures and only the worst case emissions were reported in this report..

Radiated emissions were investigated as following frequency range:

1. 30 MHz to 9000 MHz for WCDMA Band V
2. 30 MHz to 19100 MHz for WCDMA Band II


All modes, data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	Radiated TCs	Conducted TCs
WCDMA Band V	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band II	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link

Remark: All the tests were performed with LNADV.

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration

Item	Equipment	Brand Name	Model No.	FCC ID	Data Cable	Power Cord
1.	WWAN Antenna	LARSEN	SPDA24700/2700	N/A	N/A	N/A
2.	System Simulator	Anritsu	MT8820C	N/A	N/A	N/A

2.4 Frequency List of Low/Middle/High Channels

Frequency List				
Band	Channel/Frequency(MHz)	Lowest	Middle	Highest
WCDMA Band V	Channel	4132	4182	4233
	Frequency	826.4	836.4	846.6
WCDMA Band II	Channel	9262	9400	9538
	Frequency	1852.4	1880.0	1907.6


3 Conducted Test Result

3.1 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.1 Test Setup

3.1.2 Conducted Output Power



3.1.3 Test Result of Conducted Test

Please refer to Appendix A.

3.2 Conducted Output Power and ERP/EIRP

3.2.1 Description of the Conducted Output Power and ERP/EIRP

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for WCDMA Band V

The EIRP of mobile transmitters must not exceed 2 Watts for WCDMA Band II

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.2.2 Test Procedures

1. The transmitter output port is connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select the lowest, middle, and the highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.


4 Radiated Test Items

4.1 Measuring Instruments


Please refer to the measuring equipment list in this test report.

4.2 Test Setup


For radiated test below 30MHz




For radiated test from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.

Note:

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

4.4 Field Strength of Spurious Radiation Measurement

4.4.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 7 and ANSI C63.26-2015 section 5.5.4 Radiated measurement using the field strength method.

1. The EUT is placed on a rotatable wooden table 0.8 meters for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz above the ground.
2. The EUT is set 3 meters away from the receiving antenna, which is mounted on the antenna tower.
3. The table is rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1 MHz, VBW = 3 MHz, taking record of maximum spurious emission.
6. To convert spectrum reading E(dBuV/m) to EIRP(dBm)
$$\text{EIRP(dBm)} = \text{Level (dBuV/m)} + 20\log(d) - 104.77$$
, where d is the distance at which field strength limit is specified in the rules
7. Field Strength Level (dBm) = Spectrum Reading (dBm) + Antenna Factor + Cable Loss + Read Level - Preamp Factor.
8. ERP (dBm) = EIRP (dBm) - 2.15
9. The RF fundamental frequency shall be excluded against the limit line in the operating frequency band.
10. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)



5 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Sep. 12, 2023	Feb. 19, 2024~ Feb. 20, 2024	Sep. 11, 2024	Radiation (03CH15-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00802N1D01N-06	47020 & 06	30MHz~1GHz	Oct. 07, 2023	Feb. 19, 2024~ Feb. 20, 2024	Oct. 06, 2024	Radiation (03CH15-HY)
Horn Antenna	SCHWARZB ECK	BBHA 9120 D	9120D-02294	1GHz~18GHz	Jun. 30, 2023	Feb. 19, 2024~ Feb. 20, 2024	Jun. 29, 2024	Radiation (03CH15-HY)
SHF-EHF Horn Antenna	SCHWARZB ECK	BBHA 9170	00993	18GHz~40GHz	Nov. 24, 2023	Feb. 19, 2024~ Feb. 20, 2024	Nov. 23, 2024	Radiation (03CH15-HY)
Amplifier	SONOMA	310N	363440	9kHz~1GHz	Dec. 25, 2023	Feb. 19, 2024~ Feb. 20, 2024	Dec. 24, 2024	Radiation (03CH15-HY)
Preamplifier	EMEC	EM1G18G	060812	1GHz~18GHz	Dec. 25, 2023	Feb. 19, 2024~ Feb. 20, 2024	Dec. 24, 2024	Radiation (03CH15-HY)
Preamplifier	EM Electronics	EM01G18G	060802	1GHz~18GHz	Mar. 03, 2023	Feb. 19, 2024~ Feb. 20, 2024	Mar. 02, 2024	Radiation (03CH15-HY)
Preamplifier	EMEC	EM18G40G	060801	18GHz~40GHz	Jun. 27, 2023	Feb. 19, 2024~ Feb. 20, 2024	Jun. 26, 2024	Radiation (03CH15-HY)
Spectrum Analyzer	Keysight	N9010B	MY60241058	10Hz~44GHz	Jul. 06, 2023	Feb. 19, 2024~ Feb. 20, 2024	Jul. 05, 2024	Radiation (03CH15-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Feb. 19, 2024~ Feb. 20, 2024	N/A	Radiation (03CH15-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Feb. 19, 2024~ Feb. 20, 2024	N/A	Radiation (03CH15-HY)
Software	Audix	E3 6.2009-8-24(k5)	RK-000451	N/A	N/A	Feb. 19, 2024~ Feb. 20, 2024	N/A	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104, 102E	MY582185/4, 519228/2,803 950/2	30MHz~18G	Jun. 13, 2023	Feb. 19, 2024~ Feb. 20, 2024	Jun. 12, 2024	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	804011/2,804 012/2	18-40G	Jan. 02, 2024	Feb. 19, 2024~ Feb. 20, 2024	Jan. 01, 2025	Radiation (03CH15-HY)
Filter	Wainwright	WHKX12-1080-12 00-15000-60ST	SN5	1.2GHz High Pass Filter	Jun. 14, 2023	Feb. 19, 2024~ Feb. 20, 2024	Jun. 13, 2024	Radiation (03CH15-HY)
Filter	Wainwright	WHKX12-2700-30 00-18000-60ST	SN4	3GHz High Pass Filter	Jun. 14, 2023	Feb. 19, 2024~ Feb. 20, 2024	Jun. 13, 2024	Radiation (03CH15-HY)
Radio Communication Analyzer	Anritsu	MT8821C	6262025353	LTE FDD/TDD LTE-2CC DLCA/ULCA	Oct. 03, 2023	Feb. 21, 2024	Oct. 02, 2024	Conducted (TH03-HY)
Thermal Chamber	ESPEC	SH-641	92013720	-40℃ ~90℃	Sep. 04, 2023	Feb. 21, 2024	Sep. 03, 2024	Conducted (TH03-HY)
DC Power Supply	GW Instek	GPP-2323	GES906037	0V~64V ; 0A~6A	Nov. 28, 2023	Feb. 21, 2024	Nov. 27, 2024	Conducted (TH03-HY)
Coupler	Warison	20dB 25W SMA Directional Coupler	#B	1-18GHz	Jan. 08, 2024	Feb. 21, 2024	Jan. 07, 2025	Conducted (TH03-HY)
Spectrum Analyzer	Rohde & Schwarz	FSV40	101905	10Hz~40GHz	Jul. 14, 2023	Feb. 21, 2024	Jul. 13, 2024	Conducted (TH03-HY)



6 Measurement Uncertainty

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.02 dB
--	---------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.57 dB
--	---------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.97 dB
--	---------



Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power) & ERP / EIRP

WCDMA Band V Maximum Average Power [dBm] (GT - LC = 0.82 dB)					
Channel	4132	4182	4233	ERP (dBm)	ERP (W)
Frequency	826.4	836.4	846.6		
RMC 12.2K	22.52	22.15	21.95	21.19	0.1315
HSDPA Subtest-1	19.40	19.26	19.16		
HSDPA Subtest-2	19.40	19.24	19.23		
HSDPA Subtest-3	19.38	19.22	18.84		
HSDPA Subtest-4	19.38	19.22	19.17		
HSUPA Subtest-1	20.64	20.82	20.61		
HSUPA Subtest-2	20.39	20.14	20.20		
HSUPA Subtest-3	20.01	19.73	19.81		
HSUPA Subtest-4	20.19	20.41	20.08		
HSUPA Subtest-5	21.40	21.20	21.20		
Limit	ERP < 7W			Result	Pass


WCDMA Band II Maximum Average Power [dBm] (GT - LC = 1.52 dB)					
Channel	9262	9400	9538	EIRP (dBm)	EIRP (W)
Frequency	1852.4	1880	1907.6		
RMC 12.2K	23.55	23.60	23.95	25.47	0.3524
HSDPA Subtest-1	20.38	20.35	20.82		
HSDPA Subtest-2	20.48	20.35	20.83		
HSDPA Subtest-3	20.45	20.34	20.83		
HSDPA Subtest-4	20.44	20.33	20.83		
HSUPA Subtest-1	22.47	22.48	22.90		
HSUPA Subtest-2	21.37	21.33	21.75		
HSUPA Subtest-3	21.17	21.16	21.46		
HSUPA Subtest-4	21.70	21.40	21.99		
HSUPA Subtest-5	22.70	22.50	23.00		
Limit	EIRP < 2W			Result	Pass



Appendix B. Test Results of Radiated Test


B1. Summary of each worse mode

Mode	Part	Band	Ch	Freq (MHz)	Level (dBm)	Det	Ant Factor (dB)	Amp\Cbl (dB)	Filter (dB)	EIRPCF (dB)	Reading (dBuV)	Limit (dBm)	Margin (dB)	Pol	Ant
1	Part 22H	WCDMA B5	L	2487	-51.14	RMS	27.72	-31.05	0.45	-95.23	46.97	-13.00	-38.14	H	Main
2	Part 24E	WCDMA B2	L	5565	-45.35	RMS	32.93	-27.94	0.39	-95.23	44.50	-13.00	-32.35	V	Main

**Main****Part 22H Mode 1****WCDMA B5 Ch4132****L**

Site : 03CH15-HY
Condition: -13 3m BBHA 9120 D_9120D-02294 Horizontal
Mode : WCADMA Band V Ch4132

	Freq	Level	Detector	Ant Factor	Amp\Cb 1	Filter	EIRPCF	Readin g	Limit	Margin	Pol
	MHz	dBm		dB/m	dB	dB	dB	dBuV	dBm	dB	
1	1653.00	-65.06	RMS	25.39	-32.23	0.63	-95.23	36.38	-13.00	-52.06	Horizontal
2	2487.00	-51.14	RMS	27.72	-31.05	0.45	-95.23	46.97	-13.00	-38.14	Horizontal
3	3306.00	-60.58	RMS	29.61	-30.11	0.36	-95.23	34.79	-13.00	-47.58	Horizontal
4	4132.80	-58.61	RMS	30.83	-29.57	0.35	-95.23	35.01	-13.00	-45.61	Horizontal



Site : 03CH15-HY
Condition: -13 3m BBHA 9120 D_9120D-02294 Vertical
Mode : WCADMA Band V Ch4132

	Freq	Level	Detector	Ant Factor	Amp\Cb 1	Filter	EIRPCF	Readin g	Limit	Margin	Pol
	MHz	dBm		dB/m	dB	dB	dB	dBuV	dBm	dB	
1	1653.00	-65.11	RMS	25.39	-32.23	0.63	-95.23	36.33	-13.00	-52.11	Vertical
2	2487.00	-62.89	RMS	27.72	-31.05	0.45	-95.23	35.22	-13.00	-49.89	Vertical
3	3306.00	-60.46	RMS	29.61	-30.11	0.36	-95.23	34.91	-13.00	-47.46	Vertical
4	4132.80	-55.79	RMS	30.83	-29.57	0.35	-95.23	37.83	-13.00	-42.79	Vertical




Main

Part 24E Mode 2

WCDMA B2 Ch9262

L




Site : 03CH15-HY

Condition: -13 3m BBHA 9120 D_9120D-02294 Horizontal

Mode : WCDMA Band II Ch9262

	Freq	Level	Detector	Ant Factor	Amp\Cb	Filter	EIRPCF	Readin g	Limit	Margin	Pol
	MHz	dBm			dB	dB	dB	dBuV	dBm	dB	
1	3705.00	-49.34	RMS	29.84	-29.87	0.84	-95.23	0.00	-13.00	-36.34	Horizontal
2	5565.00	-50.13	RMS	32.93	-27.94	0.39	-95.23	39.72	-13.00	-37.13	Horizontal
3	7410.00	-51.99	RMS	36.18	-26.29	0.37	-95.23	32.98	-13.00	-38.99	Horizontal



Site : 03CH15-HY

Condition: -13 3m BBHA 9120 D_9120D-02294 Vertical

Mode : WCDMA Band II Ch9262

	Freq	Level	Detector	Ant Factor	Amp\Cb	Filter	EIRPCF	Readin g	Limit	Margin	Pol
	MHz	dBm			dB	dB	dB	dBuV	dBm	dB	
1	3705.00	-45.40	RMS	29.84	-29.87	0.84	-95.23	49.02	-13.00	-32.40	Vertical
2	5565.00	-45.35	RMS	32.93	-27.94	0.39	-95.23	44.50	-13.00	-32.35	Vertical
3	7410.00	-51.77	RMS	36.18	-26.29	0.37	-95.23	33.20	-13.00	-38.77	Vertical




Main

Part 24E Mode 2

WCDMA B2 Ch9262

L




Site : 03CH15-HY

Condition: -13 3m BBHA 9120 D_9120D-02294 Horizontal

Mode : WCDMA Band II Ch9262

	Freq	Level	Detector	Ant Factor	Amp\Cb	Filter 1	EIRPCF	Readin g	Limit	Margin	Pol
1	1854.00	11.70	RMS	25.54	4.94	0.00	-95.23	76.45	-----	-----	Horizontal



Site : 03CH15-HY

Condition: -13 3m BBHA 9120 D_9120D-02294 Vertical

Mode : WCDMA Band II Ch9262

	Freq	Level	Detector	Ant Factor	Amp\Cb	Filter 1	EIRPCF	Readin g	Limit	Margin	Pol
1	1852.00	17.66	RMS	25.52	4.94	0.00	-95.23	82.43	-----	-----	Vertical

Remark: #1 is fundamental signal which can be ignored.