




PCTEST Engineering Laboratory, Inc.

6660-B Dobbin Road • Columbia, MD 21045 • U.S.A.

TEL (410) 290-6652 • FAX (410) 290-6654

<http://www.pctestlab.com>



CERTIFICATE OF COMPLIANCE

HITRON SYSTEMS INC.
109-19, Majeon-Ri, Samjuk-Myeon,
Ansung-City, Kyungki-Do, 456-880, KOREA
Attention: Se Bong, Lee – R & D Display 1 Team

Dates of Tests: January 07-08, 1999
Test Report S/N: TX.981222850.LLI
Test Site: PCTEST Lab, MD U.S.A.

FCC ID

LLICTX44

APPLICANT

HITRON SYSTEMS INC.

FCC Rule Part(s):	§ 15.249 Subpart C – Intentional Radiator
Classification:	Low Power Communications Transmitter (DXX)
EUT Type:	4-Channel Wireless Transmitter
Freq. Range:	2.410 GHz ~ 2.4835 GHz
Channel Freq.:	Ch.1/2.43GHz, Ch.2/2.45GHz, Ch.3/2.47GHz, Ch.4/2.41GHz
Trade Name:	HITRON SYSTEMS INC.
Model:	CTX4412N

This device has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-1992 with the following remarks (Note Codes):

- (#37) This device has shown to be in compliance with the new rules under Docket 87-389 and is not affected by Section 15.37 transition rule.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 853(a)




Randy Ortanez
President & Chief Engineer



TABLE OF CONTENTS

ATTACHMENT A:	COVER LETTER(S)	
ATTACHMENT B:	ATTESTATION STATEMENT(S)	
ATTACHMENT C:	TEST REPORT	
	SCOPE	1
	INTRODUCTION (SITE DESCRIPTION)	2
	PRODUCTION INFORMATION	3
	DESCRIPTION OF TESTS (CONDUCTED)	4
	DESCRIPTION OF TESTS (RADIATED)	5
	ANTENNA REQUIREMENT	6
	FREQUENCY MEASUREMENTS (Fundamental & Harmonics)	7-10
	FREQUENCY MEASUREMENTS (Fundamental & Spurious)	11
	LIST OF SUPPORT EQUIPMENT	12
	CONDUCTED EMISSIONS	13
	PLOTS OF EMISSION	14
	SAMPLE CALCULATIONS	15
	ACCURACY OF MEASUREMENT	16
	LIST OF TEST EQUIPMENT	17
	RECOMMENDATION / CONCLUSION	18
ATTACHMENT D:	TEST PLOTS	
ATTACHMENT E:	FCC ID LABEL & LOCATION	
ATTACHMENT F:	BLOCK DIAGRAM(S)	
ATTACHMENT G:	SCHEMATIC DIAGRAM(S)	
ATTACHMENT H:	CIRCUIT DESCRIPTION	
ATTACHMENT I:	TEST SETUP PHOTOGRAPHS	
ATTACHMENT J:	EXTERNAL PHOTOGRAPHS	
ATTACHMENT K:	INTERNAL PHOTOGRAPHS	
ATTACHMENT L:	USER S MANUAL	

MEASUREMENT REPORT



Scope - Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.

Company Name:	HITRON SYSTEMS INC.
Address:	109-19, Majeon-Ri, Samjuk-Myeon Ansung-City, Kyungki-Do, 456-880, KOREA
Attention:	Se Bong, Lee – R&D Display Team 1

- FCC ID: **LLICTX44**
- Model: **CTX4412N**
- Trade Name: **HITRON SYSTEMS INC.**
- EUT Type: Wireless Transmitter
- Equipment Class: DXX (Low Power Communications Transmitter)
- Application Type: Transmitter Certification
- Frequency Range: 2.410 – 2.4835 GHz
- No. of Channels: 4
- Channel Frequencies: Ch.1/2.43GHz, Ch.2/2.45GHz, Ch.3/2.47GHz, Ch.4/2.41GHz
- FCC Rule Part(s): § 15.249 Subpart C (Intentional Radiator)
- Dates of Tests: January 07-08, 1999
- Place of Tests: PCTEST Lab, Columbia, MD U.S.A.
- Test Report S/N: TX.981222850.LLI



1.1 INTRODUCTION

The measurement procedure described in Section 15.249 of FCC Rules, and American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40GHz (ANSI C63.4-1992) was used in determining radiated and conducted emissions emanating from **HITRON SYSTEMS INC. Low Power Wireless Transmitter FCC ID: LLICTX44**.

These measurement tests were conducted at **PCTEST Engineering Laboratory, Inc.** facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49'38" W longitude. The facility is 1.5 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4 on October 19, 1992.

1.2 PCTEST Location

The map at right shows the location of the PCTEST Lab, its proximity to the FCC Lab, the Columbia vicinity area, the Baltimore-Washington International (BWI) airport, and the city of Baltimore, and the Washington, D.C. area. (see Figure1).




Figure 1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area.

2.1 Product Information

2.2 Equipment Description


The Equipment Under Test (EUT) is the **HITRON SYSTEMS INC. (Model: CTX4412N) Low Power Wireless Transmitter FCC ID: LLICTX44**. The EUT is a four-channel wireless transmitter, which transmits modulated video and audio between 2.410GHz and 2.4835GHz frequency range. The EUT operates with a portable superheterodyne wireless receiver FCC DoC Model: CRX4412N.

* Tx Freq. Range:	2.410 ~ 2.4835 GHz
* No. of Channels:	4
* Channel Frequencies:	Ch.1/2.43GHz, Ch.2/2.45GHz, Ch.3/2.47GHz, Ch.4/2.41GHz
* Modulation:	FM
* RF Output Power:	10mW
* Antenna:	High Gain Directional Dipole
* Ports/Connectors:	Video Input, Audio Input (Left & Right), DC In
* Cable(s):	Unshielded
* AC Power Adapter:	Youkyoung Electronics Co., Ltd. Model: YK-12050U Input: 120VAC 60Hz 9.5W Output: 12V DC 500mA
* Power Cord:	Unshielded
* Dimensions (LxWxH):	116 x 111 x 32 mm
* Weight:	310g
* Rx FCC ID:	n/a (FCC DoC Model: CRX4412N)


2.4 EMI Suppression Device(s)

EMI suppression device(s) added and/or modified during testing:


- none




**Figure 2. Shielded Enclosure
Line-Conducted Test Facility**



**Figure 3. Line Conducted
Emission Test Set-Up**



**Figure 4. Wooden Table &
Bonded LISNs**



**Figure 5. LISN Schematic
Diagram**

3.1 Description of Tests

3.2 Conducted Emissions

The line-conducted facility is located inside a 16'x20'x10' shielded enclosure. It is manufactured by Ray Proof Series 81 (see Figure 2). The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-6. A 1m. x 1.5m. wooden table 80cm. high is placed 40cm. away from the vertical wall and 1.5m away from the side wall of the shielded room (see Figure 3). Solar Electronics and EMCO Model 3725/2 (10kHz-30MHz) 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room (see Figure 4). The EUT is powered from the Solar LISN and the support equipment is powered from the EMCO LISN. Power to the LISNs are filtered by a high-current high-insertion loss Ray Proof power line filters (100dB 14kHz-10GHz). The purpose of the filter is to attenuate ambient signal interference and this filter is also bonded to the shielded enclosure. All electrical cables are shielded by braided tinned copper zipper tubing, with an inner diameter of 1/2". If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply lines will be connected to the Solar LISN. LISN schematic diagram is shown in Figure 5. All interconnecting cables more than 1 meter were shortened by non-inductive bundling (serpentine fashion) to a 1-meter length. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer to determine the frequency producing the maximum EME from the EUT. The spectrum was scanned from 450kHz to 30MHz with 20 msec. sweep time. The frequency producing the maximum level was reexamined using EMI/ Field Intensity Meter and Quasi-Peak adapter. The detector function was set to CISPR quasi-peak mode. The bandwidth of the receiver was set to 10 kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each EME emission. Each emission was maximized by: switching power lines; varying the mode of operation or resolution; clock or data exchange speed; scrolling H pattern to the EUT and/or support equipment, and powering the monitor from the floor mounted outlet box and the computer aux AC outlet, if applicable; whichever determined the worst-case emission. Photographs of the worst-case emission can be seen in Attachment I. Each EME reported was calibrated using the HP8640B signal generator.

3.1 Description of Tests (continued)

3.3 Radiated Emissions




Figure 6. 3-Meter Test Site




Figure 7. Dimensions of Outdoor Test Site




Figure 8. Turntable and System Setup




Figure 9. Normalized Site Attenuation Curves (H&V)

Preliminary measurements were made indoors at 1 meter using broadband antennas, broadband amplifier, and spectrum analyzer to determine the frequency producing the maximum EME. Appropriate precaution was taken to ensure that all EME from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, turntable azimuth with respect to the antenna were noted for each frequency found. The spectrum was scanned from 30 to 200 MHz using biconical antenna and from 200 to 1000 MHz using log-spiral antenna. Above 1 GHz, linearly polarized double ridge horn antennas were used.

Final measurements were made outdoors at 3-meter test range using Roberts™ Dipole antennas or horn antenna (see Figure 6). The test equipment was placed on a wooden and plastic bench situated on a 1.5 x 2 meter area adjacent to the measurement area (see Figure 7). Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. Each frequency found during pre-scan measurements was re-examined and investigated using EMI/Field Intensity Meter and Quasi-Peak Adapter. The detector function was set to CISPR quasi-peak mode and the bandwidth of the receiver was set to 100kHz or 1 MHz depending on the frequency or type of signal.

The half-wave dipole antenna was tuned to the frequency found during preliminary radiated measurements. The EUT, support equipment and interconnecting cables were re-configured to the set-up producing the maximum emission for the frequency and were placed on top of a 0.8-meter high non-metallic 1 x 1.5 meter table (see Figure 8). The EUT, support equipment, and interconnecting cables were re-arranged and manipulated to maximize each EME emission. The turntable containing the system was rotated; the antenna height was varied 1 to 4 meters and stopped at the azimuth or height producing the maximum emission. Each emission was maximized by: varying the mode of operation or resolution; clock or data exchange speed; scrolling H pattern to the EUT and/or support equipment; powering the monitor from the floor mounted outlet box and the computer aux AC outlet if applicable, and changing the polarity of the antenna; whichever determined the worst-case emission. Photographs of the worst-case emission can be seen in Attachment I. Each EME reported was calibrated using the HP8640B signal generator. The Theoretical Normalized Site Attenuation Curves for both horizontal and vertical polarization are shown in Figure 9 according to ANSI C63.4.

4.1 §15.203 Antenna Requirement

An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the applicant can be used with the device. The use of permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with this requirement.

CONCLUSION

The HITRON SYSTEMS INC. wireless transmitter complies with the requirement of §15.203 with a high-gain directional dipole antenna uniquely coupled to the transmitter.

5.1 Applied Modulation

The modulation used was the test procedure specified in ANSI C63.4-1992. For audio modulation we used a 1kHz tone at 100Db SPL (Extech Model: 407740 Digital Sound Level Meter), an audio signal generator (Tenma), and a speaker at 10cm away from the microphone (condensor). Various audio tones were also used to simulate the sounds generated by typical use. For video modulation, various intensity of light and focus of objects were used to determine the worst-case modulation. The worst-case modulation that produces the widest bandwidth was used during final testing.

6.1 Frequency Measurements (Fundamental & Harmonics)

Operating Frequency: 2.43 GHz
 Distance of Measurements: 3 meters
 Channel: 1

FREQ. (MHz)	Level* (dBm)	AFCL (dB)	POL (H/V)	FS (μ V/m)	F/S (dB μ V/m)	DET. (QP/AVG)	MARGIN (dB)
2.43	- 54.3	37.4	V	31989.0	90.1	AVG.	- 3.9
4.86*	- 102.1	46.6	V	375.8	51.5	AVG.	- 2.5
4.86*	- 100.5	46.6	V	451.9	53.1	PEAK	- 0.9
7.29*	- 119.0	52.0	V	167.9	40.0	PEAK	- 14.0
9.72	- 124.0	56.8	V	138.0	39.8	PEAK	- 14.2

NOTES:

1. The limit at fundamental frequency is 50,000 μ V/m @ 3m. using QP detector. The harmonic limit is 500 μ V/m @ 3m.
2. The emissions radiated outside of the specified frequency band, except harmonics, are attenuated by at least 50dBc or to the limits in §15.209, whichever is lesser.
3. All harmonic emissions in the restricted bands specified in §15.205 are below the limit shown in Fig. 10 (Note: *).
4. The antenna is manipulated through typical positions and length during the tests.
5. The emissions are maximized by changing polarity of the antenna.
6. The EUT is supplied with the nominal AC voltage and/or a new/fully recharged battery.
7. All channels were investigated and the worst-case is reported.

* Restricted Band




Figure 10. Spurious Radiated Limits at 3 meters

6.2 Frequency Measurements (Fundamental & Harmonics)

Operating Frequency: 2.45 GHz
 Distance of Measurements: 3 meters
 Channel: 2

FREQ. (MHz)	Level* (dBm)	AFCL (dB)	POL (H/V)	FS ($\mu\text{V/m}$)	F/S (dB $\mu\text{V/m}$)	DET. (QP/AVG)	MARGIN (dB)
2.45	- 55.2	37.5	V	29174.3	89.3	AVG.	- 4.7
4.90*	- 103.0	46.8	V	346.7	50.8	AVG.	- 3.2
4.90*	- 101.2	46.8	V	426.6	52.6	PEAK	- 1.4
7.35*	- 120.0	52.2	V	91.2	39.2	PEAK	- 14.8
9.80	- 125.0	57.0	V	89.1	39.0	PEAK	- 15.0

NOTES:

1. The limit at fundamental frequency is 50,000 $\mu\text{V/m}$ @ 3m. using QP detector. The harmonic limit is 500 $\mu\text{V/m}$ @ 3m.
2. The emissions radiated outside of the specified frequency band, except harmonics, are attenuated by at least 50dBc or to the limits in §15.209, whichever is lesser.
3. All harmonic emissions in the restricted bands specified in §15.205 are below the limit shown in Fig. 10 (Note: *).
4. The antenna is manipulated through typical positions and length during the tests.
5. The emissions are maximized by changing polarity of the antenna.
6. The EUT is supplied with the nominal AC voltage and/or a new/fully recharged battery.
7. All channels were investigated and the worst-case is reported.

* Restricted Band




Figure 11. Spurious Radiated Limits at 3 meters

6.3 Frequency Measurements (Fundamental & Harmonics)

Operating Frequency: 2.47 GHz
 Distance of Measurements: 3 meters
 Channel: 3

FREQ. (MHz)	Level* (dBm)	AFCL (dB)	POL (H/V)	FS ($\mu\text{V/m}$)	F/S (dB $\mu\text{V/m}$)	DET. (QP/AVG)	MARGIN (dB)
2.47	- 56.4	37.5	V	25409.7	88.1	AVG.	- 5.9
4.94*	- 104.0	46.9	V	312.6	49.9	AVG.	- 4.1
4.94*	- 102.0	46.9	V	393.6	51.9	PEAK	- 2.1
7.41*	- 121.0	52.3	V	82.2	38.3	PEAK	- 15.7
9.88	- 125.0	57.2	V	91.2	39.2	PEAK	- 14.8

NOTES:

1. The limit at fundamental frequency is 50,000 $\mu\text{V/m}$ @ 3m. using QP detector. The harmonic limit is 500 $\mu\text{V/m}$ @ 3m.
2. The emissions radiated outside of the specified frequency band, except harmonics, are attenuated by at least 50dBc or to the limits in §15.209, whichever is lesser.
3. All harmonic emissions in the restricted bands specified in §15.205 are below the limit shown in Fig. 10 (Note: *).
4. The antenna is manipulated through typical positions and length during the tests.
5. The emissions are maximized by changing polarity of the antenna.
6. The EUT is supplied with the nominal AC voltage and/or a new/fully recharged battery.
7. All channels were investigated and the worst-case is reported.

* Restricted Band




Figure 12. Spurious Radiated Limits at 3 meters

6.4 Frequency Measurements (Fundamental & Harmonics)

Operating Frequency: 2.41 GHz
 Distance of Measurements: 3 meters
 Channel: 4

FREQ. (MHz)	Level* (dBm)	AFCL (dB)	POL (H/V)	FS ($\mu\text{V/m}$)	F/S (dB $\mu\text{V/m}$)	DET. (QP/AVG)	MARGIN (dB)
2.41	- 54.9	37.2	V	29174.3	89.3	AVG.	- 4.7
4.82*	- 103.0	46.5	V	335.0	50.5	AVG.	- 3.5
4.82*	- 101.0	46.5	V	421.7	52.5	PEAK	- 1.5
7.23*	- 120.0	52.0	V	177.8	45.0	PEAK	- 9.0
9.64	- 125.0	56.6	V	85.1	38.6	PEAK	- 15.4

NOTES:

1. The limit at fundamental frequency is 50,000 $\mu\text{V/m}$ @ 3m. using QP detector. The harmonic limit is 500 $\mu\text{V/m}$ @ 3m.
2. The emissions radiated outside of the specified frequency band, except harmonics, are attenuated by at least 50dBc or to the limits in §15.209, whichever is lesser.
3. All harmonic emissions in the restricted bands specified in §15.205 are below the limit shown in Fig. 10 (Note: *).
4. The antenna is manipulated through typical positions and length during the tests.
5. The emissions are maximized by changing polarity of the antenna.
6. The EUT is supplied with the nominal AC voltage and/or a new/fully recharged battery.
7. All channels were investigated and the worst-case is reported.

* Restricted Band





Figure 13. Spurious Radiated Limits at 3 meters

7.1 Frequency Measurements (Fundamental & Spurious)

Operating Frequencies: 2.410 – 2.4835 GHz
 Distance of Measurements: 3 meters
 Channel(s): 1,2,3,4

Freq. (MHz)	Level* (dBm)	AFCL** (dB)	POL (H/V)	Height (m)	Azimuth (° angle)	F/S (μV/m)	MARGIN*** (dB)
61.6	- 78.0	5.1	V	2.6	30	50.8	- 5.9
126.2	- 83.5	11.9	H	2.2	160	59.1	- 8.1
184.1	- 85.0	15.7	V	1.9	310	76.8	- 5.8
212.0	- 88.0	17.1	V	1.7	180	63.5	- 7.4
219.5	- 89.5	17.4	V	1.6	180	55.6	- 11.1
300.0	- 96.0	20.6	H	1.1	210	38.0	- 14.4

Table 1. Radiated Measurements at 3-meters.



NOTES:

1. All channels were investigated and the worst-case are reported.
2. The antenna is fully extended during the tests and the emissions are maximized by changing polarity of the antenna.
3. The EUT is supplied with the nominal AC voltage and/or a new/fully-charged battery.
4. The radiated limits are shown in Fig. 14.
5. Peak readings were taken with the resolution bandwidth and video bandwidth set at 1MHz.

Figure 14. Spurious Radiated Limits at 3 meters

- * All readings are calibrated by HP8640B signal generator with accuracy traceable to the National Institute of Standards and Technology (formerly NBS).
- ** AFCL = Antenna Factor (Roberts dipole) and Cable Loss (30 ft. RG58C/U).
- *** Measurements using CISPR quasi-peak mode.

8.1 Support Equipment Used

1. **HITRON Wireless Transmitter** **FCC ID: LLICTX44** **(EUT)**
2.0 m. unshielded RCA A/V cables (x3)
Youkyoung AC Power Adapter Model: YK-12050U
1.8 m. unshielded DC power cord
2. **DAEWOO VCR** **FCC ID: C5F7NF0001** **S/N: 309DB00062**
1.8 m. unshielded AC power cord
3. **HITRON Wireless Receiver** **FCC ID: n/a (FCC DoC Model: CRX4412N)** **S/N: 8120001**
2.0 m. unshielded RCA A/V cables (x3)
1.2 m. shielded RF cable
Youkyoung AC Power Adapter Model: YK-12050U
1.8 m. unshielded DC power cord
4. **SONY Television** **Model: KV-10FMR20** **S/N: 2006150**
1.8 m. unshielded AC power cord

(See "Attachment I – Test Photographs" for actual system test setup.)

9.1 LINE-CONDUCTED TEST DATA

9.2 Conducted Emissions

(See Data under PLOTS – Attachment D)

NOTES:

1. All channels & modes of operation were investigated and the worst-case emissions are reported.
2. The limit for Class B device is 250 μ V from 450kHz to 30MHz.
3. Line A = Phase; Line B = Neutral
4. Deviations to the Specifications: None

10.1 Plot(s) of Emissions

See Attachment D

11.1 Sample Calculations

$$\begin{aligned}\text{dB}\mu\text{V} &= 20 \log_{10} (\mu\text{V}/\text{m}) \\ \text{dB}\mu\text{V} &= \text{dBm} + 107\end{aligned}$$

11.2 Example 1:

@ 20.3 MHz

Class B limit	= 250 μV = 47.96 dB μV
Reading	= - 67.8 dBm (calibrated level)
Convert to dB μV	= - 67.8 + 107 = 39.2 dB μV
$10^{(39.2/20)}$	= 91.2 μV
Margin	= 39.2 - 47.96 = - 8.76
	= 8.8 dB below limit

11.3 Example 2:

@ 66.7 MHz

Class B limit	= 100 $\mu\text{V}/\text{m}$ = 47.96 dB $\mu\text{V}/\text{m}$
Reading	= - 76.0 dBm (calibrated level)
Convert to dB $\mu\text{V}/\text{m}$	= - 76.0 + 107 = 31.0 dB $\mu\text{V}/\text{m}$
Antenna Factor + Cable Loss	= 5.8 dB
Total	= 36.8 dB $\mu\text{V}/\text{m}$
Margin	= 36.8 - 40.0 = - 3.2
	= 3.2 dB below limit

12.1 Accuracy of Measurement

12.2 Measurement Uncertainty Calculations:

The measurement uncertainties stated were calculated in accordance with the requirements of NIST Technical Note 1297 and NIS 81 (1994).

Contribution (Line Conducted)	Probability Distribution	Uncertainty (± dB)	
		9kHz-150MHz	150-30MHz
Receiver specification	Rectangular	1.5	1.5
LISN coupling specification	Rectangular	1.5	1.5
Cable and input attenuator calibration	Normal (k=2)	0.3	0.5
Mismatch: Receiver VRC $\Gamma_1 = 0.03$ LISN VRC $\Gamma_R = 0.8$ (9kHz) 0.2 (30MHz) Uncertainty limits $20\text{Log}(1 \pm \Gamma_1 \Gamma_R)$	U-Shaped	0.2	0.35
System repeatability	Std. deviation	0.2	0.05
Repeatability of EUT		-	-
Combined standard uncertainty	Normal	1.26	1.30
Expanded uncertainty	Normal (k=2)	2.5	2.6

Calculations for 150kHz to 30MHz:

$$u_c(y) = \sqrt{\sum_{i=1}^m u_i^2(y)} = \pm \sqrt{\frac{1.5^2 + 1.5^2}{3} + \left(\frac{0.5}{2}\right)^2 + 0.35} = \pm 1.298\text{dB}$$

$$U = 2U_c(y) = \pm 2.6\text{dB}$$

Contribution (Radiated Emissions)	Probability Distribution	Uncertainties (± dB)	
		3 m	10 m
Ambient Signals		-	-
Antenna factor calibration	Normal (k=2)	± 1.0	± 1.0
Cable loss calibration	Normal (k=2)	± 0.5	± 0.5
Receiver specification	Rectangular	± 1.5	± 1.5
Antenna directivity	Rectangular	+ 0.5 / - 0	+ 0.5
Antenna factor variation with height	Rectangular	± 2.0	± 0.5
Antenna phase centre variation	Rectangular	0.0	± 0.2
Antenna factor frequency interpolation	Rectangular	± 0.25	± 0.25
Measurement distance variation	Rectangular	± 0.6	± 0.4
Site imperfections	Rectangular	± 2.0	± 2.0
Mismatch: Receiver VRC $\Gamma_1 = 0.2$ Antenna VRC $\Gamma_R = 0.67$ (Bi) 0.3 (Lp) Uncertainty limits $20\text{Log}(1 \pm \Gamma_1 \Gamma_R)$	U-Shaped	+ 1.1 - 1.25	± 0.5
System repeatability	Std. Deviation	± 0.5	± 0.5
Repeatability of EUT		-	-
Combined standard uncertainty	Normal	+ 2.19 / - 2.21	+ 1.74 / - 1.72
Expanded uncertainty U	Normal (k=2)	+ 4.38 / - 4.42	+ 3.48 / - 3.44

Calculations for 3m biconical antenna. Coverage factor of k=2 will ensure that the level of confidence will be approximately 95%, therefore:

$$U = 2U_c(y) = 2 \times \pm 2.19 = \pm 4.38\text{dB}$$

13.1 Test Equipment

Type	Model	Cal. Due Date	S/N
Microwave Spectrum Analyzer	HP 8566B (100Hz-22GHz)	08/15/99	3638A08713
Microwave Spectrum Analyzer	HP 8566B (100Hz-22GHz)	04/17/99	2542A11898
Spectrum Analyzer/Tracking Gen.	HP 8591A (100Hz-1.8GHz)	08/10/99	3144A02458
Signal Generator*	HP 8640B (500Hz-1GHz)	08/09/99	2232A19558
Signal Generator*	HP 8640B (500Hz-1GHz)	08/09/99	1851A09816
Signal Generator*	Rohde & Schwarz (0.1-1000MHz)	09/11/99	894215/012
Ailtech/Eaton Receiver	NM 37/57A-SL (30-1000MHz)	04/12/99	0792-03271
Ailtech/Eaton Receiver	NM 37/57A (30-1000MHz)	03/11/99	0805-03334
Ailtech/Eaton Receiver	NM 17/27A (0.1-32MHz)	09/17/99	0608-03241
Quasi-Peak Adapter	HP 85650A	08/15/99	2043A00301
Ailtech/Eaton Adapter	CCA-7 CISPR/ANSI QP Adapter	03/11/99	0194-04082
RG58 Coax Test Cable	No. 167		n/a
Harmonic/Flicker Test System	HP 6841A (IEC 555-2/3)		3531A00115
Broadband Amplifier (2)	HP 8447D		1145A00470, 1937A03348
Broadband Amplifier	HP 8447F		2443A03784
Transient Limiter	HP 11947A (9kHz-200MHz)	2820A00300	
Horn Antenna	EMCO Model 3115 (1-18GHz)		9704-5182
Horn Antenna	EMCO Model 3115 (1-18GHz)		9205-3874
Horn Antenna	EMCO Model 3116 (18-40GHz)		9203-2178
Biconical Antenna (4)	Eaton 94455/Eaton 94455-1/Singer 94455-1/Compliance Design 1295, 1332, 0355		
Log-Spiral Antenna (3)	Ailtech/Eaton 93490-1		0608, 1103, 1104
Roberts Dipoles	Compliance Design (1 set)		
Ailtech Dipoles	DM-105A (1 set)		33448-111
EMCO LISN	3816/2		1079
EMCO LISN	3816/2		1077
EMCO LISN	3725/2		2009
Microwave Preamplifier 40dB Gain	HP 83017A (0.5-26.5GHz)		3123A00181
Microwave Cables	MicroCoax (1.0-26.5GHz)		
Ailtech/Eaton Receiver	NM37/57A-SL		0792-03271
Spectrum Analyzer	HP 8594A		3051A00187
Spectrum Analyzer (2)	HP 8591A		3034A01395, 3108A02053
Modulation Analyzer	HP 8901A		2432A03467
NTSC Pattern Generator	Leader 408		0377433
Noise Figure Meter	HP 8970B		3106A02189
Noise Figure Meter	Ailtech 7510		TE31700
Noise Generator	Ailtech 7010		1473
Microwave Survey Meter	Holaday Model 1501 (2.450GHz)		80931
Digital Thermometer	Extech Instruments 421305		426966
Attenuator	HP 8495A (0-70dB) DC-4GHz		
Bi-Directional Coax Coupler	Narda 3020A (50-1000MHz)		
Shielded Screen Room	RF Lindgren Model 26-2/2-0		6710 (PCT270)
Shielded Semi-Anechoic Chamber	Ray Proof Model S81		R2437 (PCT278)
Environmental Chamber	Associated Systems Model 1025 (Temperature/Humidity)		PCT285

* Calibration traceable to the National Institute of Standards and Technology (NIST).

14.1 Recommendation/Conclusion

The data collected shows that the **HITRON SYSTEMS INC. (Model: CTX4412N) Low Power Wireless Transmitter FCC ID: LLICTX44** complies with Part 15 Subpart C of the FCC Rules.