

RF MEASUREMENT REPORT

FCC ID: LNQ-WF810G-2

Applicant: Actiontec Electronics Inc.

Product: Wi-Fi 6E Mesh Extender

Model No.: GE6E220C, WF-810G

FCC Classification: 15E 6GHz Low Power Indoor Access Point (6ID)

FCC Rule Part(s): Part 15 Subpart E (Section 15.407)

Result: Complies

Received Date: 2024-01-15


Test Date: 2024-01-17 ~ 2024-02-28

Reviewed By:



Kevin Guo

Approved By:



Robin Wu



The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in KDB789033. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
2401RSU026-U5	V01	Initial Report	2024-03-11	Valid

CONTENTS

Description	Page
1. General Information	6
1.1. Applicant	6
1.2. Manufacturer	6
1.3. Testing Facility	6
1.4. Product Information	7
1.5. Radio Specification under Test	7
1.6. Working Frequencies	8
1.7. Antenna Details	10
2. Test Configuration	11
2.1. Test Mode	11
2.2. Test System Connection Diagram	11
2.3. Test Software	12
2.4. Applied Standards	13
2.5. Test Environment Condition	13
3. Antenna Requirements	14
4. Measuring Instrument	15
5. Decision Rules and Measurement Uncertainty	16
5.1. Decision Rules	16
5.2. Measurement Uncertainty	16
6. Test Result	17
6.1. Summary	17
6.2. 26dB Bandwidth Measurement	18
6.2.1. Test Limit	18
6.2.2. Test Procedure	18
6.2.3. Test Setting	18
6.2.4. Test Setup	19
6.2.5. Test Result	19
6.3. Output Power Measurement	20
6.3.1. Test Limit	20
6.3.2. Test Procedure	20
6.3.3. Test Setting	20
6.3.4. Test Setup	21
6.3.5. Test Result	21
6.4. Power Spectral Density Measurement	22
6.4.1. Test Limit	22

6.4.2.	Test Procedure	22
6.4.3.	Test Setting	22
6.4.4.	Test Setup.....	23
6.4.5.	Test Result.....	23
6.5.	In-Band Emission Measurement	24
6.5.1.	Test Limit	24
6.5.2.	Test Procedure	24
6.5.3.	Test Setting	24
6.5.4.	Test Setup.....	25
6.5.5.	Test Result.....	25
6.6.	Frequency Stability Measurement.....	26
6.6.1.	Test Limit	26
6.6.2.	Test Procedure	26
6.6.3.	Test Setup.....	26
6.6.4.	Test Result.....	27
6.7.	Contention Based Protocol Measurement	28
6.7.1.	Test Limit	28
6.7.2.	Test Procedure	28
6.7.3.	Test Setting	28
6.7.4.	Test Setup.....	29
6.7.5.	Test Result.....	29
6.8.	Radiated Spurious Emission Measurement	30
6.8.1.	Test Limit	30
6.8.2.	Test Procedure	30
6.8.3.	Test Setting	31
6.8.4.	Test Setup.....	33
6.8.5.	Test Result.....	34
6.9.	Radiated Restricted Band Edge Measurement.....	35
6.9.1.	Test Limit	35
6.9.2.	Test Procedure	37
6.9.3.	Test Setting	37
6.9.4.	Test Setup.....	38
6.9.5.	Test Result.....	38
6.10.	AC Conducted Emissions Measurement.....	39
6.10.1.	Test Limit	39
6.10.2.	Test Setup.....	39
6.10.3.	Test Result.....	39
Appendix A – Test Result.....		40

A.1	Duty Cycle Test Result	40
A.2	26dB Bandwidth Test Result	42
A.3	Output Power Test Result	57
A.4	Power Spectral Density Test Result	59
A.5	In-Band Emission Measurement	74
A.6	Frequency Stability Test Result	96
A.7	Contention Based Protocol Test Result	97
A.8	Radiated Spurious Emission Test Result	109
A.9	Radiated Restricted Band Edge Test Result	168
A.10	AC Conducted Emissions Test Result	208
Appendix B – Test Setup Photograph		210
Appendix C – EUT Photograph		211

1. General Information

1.1. Applicant

Actiontec Electronics Inc.

2445 Augustine Drive Suite 501, Santa Clara, California 95054, United States

1.2. Manufacturer

Actiontec Electronics Inc.

2445 Augustine Drive Suite 501, Santa Clara, California 95054, United States

1.3. Testing Facility

☒	Test Site – MRT Suzhou Laboratory Laboratory Location (Suzhou - Wuzhong) D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China Laboratory Location (Suzhou - SIP) 4b Building, Liando U Valley, No.200 Xingpu Rd., Shengpu Town, Suzhou Industrial Park, China Laboratory Accreditations A2LA: 3628.01 CNAS: L10551 FCC: CN1166 ISED: CN0001 VCCI: ☐ R-20025 ☐ G-20034 ☐ C-20020 ☐ T-20020 ☐ R-20141 ☐ G-20134 ☐ C-20103 ☐ T-20104
☐	Test Site – MRT Shenzhen Laboratory Laboratory Location (Shenzhen) 1G, Building A, Junxiangda Building, Zhongshanyuan Road West, Nanshan District, Shenzhen, China Laboratory Accreditations A2LA: 3628.02 CNAS: L10551 FCC: CN1284 ISED: CN0105
☐	Test Site – MRT Taiwan Laboratory Laboratory Location (Taiwan) No. 38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.) Laboratory Accreditations TAF: 3261 FCC: 291082, TW3261 ISED: TW3261

1.4. Product Information

Product Name	Wi-Fi 6E Mesh Extender
Model No.	GE6E220C, WF-810G
EUT Identification No.	20240115Sample#04(Conducted Testing) 20240115Sample#02(Radiated Testing)
Wi-Fi Specification	802.11a/b/g/n/ac/ax
Bluetooth Specification	V5.0 (Single mode, LE only)
Antenna Information	Refer to Section 1.5
Accessory	
Adapter #1	Model No.: ADT-38FKJ-PCU00F Input: 100-240V, 50/60Hz, Max. 1.0A Output: 5.0V=3.0A or 12.0V=3.0A
Adapter #2	Model No.: MS-V3000R150-038B0-US Input: 100-240V ~ 50-60Hz, 1.3A Output: 5.0V=3.0A or 9.0V=3.0A or 12.0V=3.0A or 15.0V=3.0A
Notes:	
1. There is not any hardware or software differences between GE6E220C and WF-810G, only for different brand.	
2. The information of EUT was provided by the manufacturer, and the accuracy of the information shall be the responsibility of the manufacturer.	
3. Adapter #1 was selected in this report.	

1.5. Radio Specification under Test

Frequency Range	For 802.11a/ax-HE20: 5955 ~ 7095MHz For 802.11ax-HE40: 5965 ~ 7085MHz For 802.11ax-HE80: 59855 ~ 7025MHz For 802.11ax-HE160: 6025 ~ 6985MHz	
Type of Modulation	802.11a: OFDM 802.11ax: OFDMA	
Data Rate	802.11a: 6/9/12/18/24/36/48/54Mbps 802.11ax: up to 4804Mbps	
Channel Puncturing Function	☐ Supported	☒ Unsupported
Support RU	☒ Full RU	☐ Partial RU

1.6. Working Frequencies

802.11a/ax-HE20

Channel	Frequency	Channel	Frequency	Channel	Frequency
1	5955 MHz	5	5975 MHz	9	5995 MHz
13	6015 MHz	17	6035 MHz	21	6055 MHz
25	6075 MHz	29	6095 MHz	33	6115 MHz
37	6135 MHz	41	6155 MHz	45	6175 MHz
49	6195 MHz	53	6215 MHz	57	6235 MHz
61	6255 MHz	65	6275 MHz	69	6295 MHz
73	6315 MHz	77	6335 MHz	81	6355 MHz
85	6375 MHz	89	6395 MHz	93	6415 MHz
97	6435 MHz	101	6455 MHz	105	6475 MHz
109	5495 MHz	113	6515 MHz	117	6535 MHz
121	6555 MHz	125	6575 MHz	129	6595 MHz
133	6615 MHz	137	6635 MHz	141	6655 MHz
145	6675 MHz	149	6695 MHz	153	6715 MHz
157	6735 MHz	161	6755 MHz	165	6775 MHz
169	6795 MHz	173	6815 MHz	177	6835 MHz
181	6855 MHz	185	6875 MHz	189	6895 MHz
193	6915 MHz	197	6935 MHz	201	6955 MHz
205	6975 MHz	209	6995 MHz	213	7015 MHz
217	7035 MHz	221	7055 MHz	225	7075 MHz
229	7095 MHz	--	--	--	--

802.11ax-HE40

Channel	Frequency	Channel	Frequency	Channel	Frequency
3	5965 MHz	11	6005 MHz	19	6045 MHz
27	6085 MHz	35	6125 MHz	43	6165 MHz
51	6205 MHz	59	6245 MHz	67	6285 MHz
75	6325 MHz	83	6365 MHz	91	6405 MHz
99	6445 MHz	107	6485 MHz	115	6525 MHz
123	6565 MHz	131	6605 MHz	139	6645 MHz
147	6685 MHz	155	6725 MHz	163	6765 MHz
171	6805 MHz	179	6845 MHz	187	6885 MHz
195	6925 MHz	203	6965 MHz	211	7005 MHz
219	7045 MHz	227	7085 MHz	--	--

802.11ax-HE80

Channel	Frequency	Channel	Frequency	Channel	Frequency
7	5985 MHz	23	6065 MHz	39	6145 MHz
55	6225 MHz	71	6305 MHz	87	6385 MHz
103	6465 MHz	119	6545 MHz	135	6625 MHz
151	6705 MHz	167	6785 MHz	183	6865 MHz
199	6945 MHz	215	7025 MHz	--	--

802.11ax-HE160

Channel	Frequency	Channel	Frequency	Channel	Frequency
15	6025 MHz	47	6185 MHz	79	6345 MHz
111	6505 MHz	143	6665 MHz	175	6825 MHz
207	6985 MHz	--	--	--	--

1.7. Antenna Details

Antenna Type	Frequency (MHz)	TX Paths	Antenna Gain (dBi)				Directional Gain (dBi)	
			Ant 0	Ant 1	Ant 2	Ant 3	Correlated	Uncorrelated
Wi-Fi Antenna								
PIFA	2412 ~ 2462	2	3.90	4.25	--	--	4.0	1.6
	5180 ~ 5825	2	5.42	4.47	--	--	6.3	3.6
	5925 ~ 7125	4	4.60	4.89	4.62	5.47	9.0	3.1
Remark:								
1. The antenna gain and directional gain refer to manufacturer's antenna specification. 2. The device supports CDD Mode and STBC mode, details refer to the table as below. 3. CDD signals are correlated, the directional gain as follows, For power measurements: Array Gain = 0 dB for $N_{ANT} \leq 4$, the directional gain = max antenna gain + array gain For power spectral density (PSD) measurements: the max directional gain (each angle) = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2 / N_{ANT}]$ 4. STBC signals are uncorrelated, the directional gain as follows, the max directional gain (each angle) = $10 \log[(10^{G1/10} + 10^{G2/10} + \dots + 10^{GN/10})/N_{ANT}]$								

Test Mode	T _x Paths	CDD Mode	STBC Mode
Wi-Fi 2.4G			
802.11b/g	2	√	X
802.11n/ax	2	X	√
Wi-Fi 5G			
802.11a	2	√	X
802.11n/ac/ax	2	X	√
Wi-Fi 6G			
802.11a	4	√	X
802.11ax	4	X	√
Remark: "√" means "Support", "X" means "Not support".			


2. Test Configuration

2.1. Test Mode

Mode 1: Transmit by 802.11a (6Mbps) _ Nss=1 (CDD Mode)
Mode 2: Transmit by 802.11ax-HE20 (MCS0) _ Nss=4 (STBC Mode)
Mode 3: Transmit by 802.11ax-HE40 (MCS0) _ Nss=4 (STBC Mode)
Mode 4: Transmit by 802.11ax-HE80 (MCS0) _ Nss=4 (STBC Mode)
Mode 5: Transmit by 802.11 ax-HE160 (MCS0) _ Nss=4 (STBC Mode)
Notes:
1. For Radiated emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power.
2. For CDD mode, this device supports 2 Nss and power level is the same of spatial multiplexing. The worst case is Nss=1.
3. EUT supports one configuration only in 802.11ax full RU mode.
4. All modes of operation and data rates were investigated, so all RF test requirements shall be executed at the worse data rate which power is the greatest.

2.2. Test System Connection Diagram

The device was tested per the guidance ANSI C63.10: 2013 was used to reference the appropriate EUT setup for radiated emissions testing and AC line conducted testing.

Connection Diagram			
 <pre> graph LR EUT[EUT] --- A[A] --- Adapter[Adapter] Adapter --- B[B] --- 1[1] </pre>			
No.	Cable Type	Cable Spec.	Length
A	Power Cable	Non-Shielding	2.4m
B	Ethernet Cable	Non-Shielding	>5m

No.	Product	Manufacturer	Model No.
1	Notebook	Lenovo	E495

2.3. Test Software

The test utility software used during testing was “QRCT”, and the version was 3.0.268.0.

Note: Final power setting please refer to operational description

2.4. Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ANSI C63.10-2013
- FCC KDB 789033 D02v02r01
- FCC KDB 987594 D02v02r01
- FCC KDB 987594 D04v02
- FCC KDB 662911 D01v02r01
- FCC KDB 414788 D01v01r01
- FCC KDB 412172 D01v01r01

2.5. Test Environment Condition

Ambient Temperature	15 ~ 35°C
Relative Humidity	20 ~ 75%RH

3. Antenna Requirements

Excerpt from §15.407(a)(9) of the FCC Rules/Regulations:

Access points operating under the provisions of paragraphs (a)(5) and (a)(6) of this section must employ a permanently attached integrated antenna.

- The antenna of the device is built in and locked inside the enclosure.

Conclusion:

The device complies with the requirement of §15.407(a)(9).

4. Measuring Instrument

Instrument	Manufacturer	Model No.	Asset No.	Cali. Interval	Cali. Due Date	Test Site
EMI Test Receiver	R&S	ESR3	MRTSUE06185	1 year	2024-12-17	SIP-AC2
Preamplifier	EMCI	EMC184045SE	MRTSUE06602	1 year	2024-10-09	SIP-AC3
EMI Test Receiver	R&S	ESR3	MRTSUE06613	1 year	2024-10-23	SIP-AC3
Loop Antenna	Schwarzbeck	FMZB 1519 B	MRTSUE06937	1 year	2024-01-28	SIP-AC3
Loop Antenna	Schwarzbeck	FMZB 1519 B	MRTSUE06937	1 year	2025-01-27	SIP-AC3
Signal Analyzer	Keysight	N9010B	MRTSUE07028	1 year	2024-10-23	SIP-AC3
Thermohygrometer	testo	608-H1	MRTSUE06622	1 year	2024-11-03	SIP-AC2
TRILOG Antenna	Schwarzbeck	VULB 9168	MRTSUE06647	1 year	2024-06-17	SIP-AC2
Anechoic Chamber	RIKEN	SIP-AC2	MRTSUE06781	1 year	2024-12-21	SIP-AC2
Horn Antenna	Schwarzbeck	BBHA 9170	MRTSUE06599	1 year	2024-09-24	SIP-AC3
Horn Antenna	R&S	HF907	MRTSUE06611	1 year	2024-07-14	SIP-AC3
Thermohygrometer	testo	608-H1	MRTSUE06619	1 year	2024-10-28	SIP-AC3
Preamplifier	EMCI	EMC012645SE	MRTSUE06642	1 year	2024-01-12	SIP-AC3
Preamplifier	EMCI	EMC012645SE	MRTSUE06642	1 year	2025-01-11	SIP-AC3
TRILOG Antenna	Schwarzbeck	VULB 9168	MRTSUE06646	1 year	2024-08-04	SIP-AC3
Anechoic Chamber	RIKEN	SIP-AC3	MRTSUE06782	1 year	2024-12-21	SIP-AC3
Thermohygrometer	testo	608-H1	MRTSUE11022	1 year	2024-10-28	SIP-TR1
USB Power Sensor	Keysight	U2021XA	MRTSUE06596	1 year	2024-07-31	SIP-TR1
Signal Analyzer	Keysight	N9010B	MRTSUE07036	1 year	2024-02-04	SIP-TR1
Signal Analyzer	Keysight	N9010B	MRTSUE07036	1 year	2025-02-03	SIP-TR1
Pxle Microwave Vector Signal Source test set	Keysight	M9384B	MRTSUE06994	1 year	2024-09-05	SIP-TR1
Temperature Chamber	BAOYT	BYG-408CS	MRTSUE06847	1 year	2024-02-04	SIP-TR1
Temperature Chamber	BAOYT	BYG-408CS	MRTSUE06847	1 year	2025-02-03	SIP-TR1
Two-Line V-Network	R&S	ENV216	MRTSUE06003	1 year	2024-05-23	SIP-SR2
EMI Test Receiver	R&S	ESR3	MRTSUE06612	1 year	2024-05-23	SIP-SR2
Four-Line V-Network	R&S	ENV432	MRTSUE06614	1 year	2024-10-23	SIP-SR2
Thermohygrometer	testo	608-H1	MRTSUE06621	1 year	2024-11-03	SIP-SR2
Shielding Room	MIX-BEP	SIP-SR2	MRTSUE06949	5 years	2024-10-23	SIP-SR2

Software	Version	Function
EMI V3	V 3.0.0	EMI Test Software
Controller_MF 7802BS	1.02	RE Antenna & Turntable
BenchVue Power Meter	2019	Power

5. Decision Rules and Measurement Uncertainty

5.1. Decision Rules

The Decision Rule is based on Simple Acceptance in accordance with ISO Guide 98-4: 2012 Clause 8.2.
(Measurement uncertainty is not taken into account when stating conformity with a specified requirement.)

5.2. Measurement Uncertainty

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

AC Conducted Emission Measurement
The maximum measurement uncertainty is evaluated as: 9kHz~150kHz: 3.58dB 150kHz~30MHz: 3.20dB
Radiated Emission Measurement
The maximum measurement uncertainty is evaluated as: Coaxial: 9kHz~30MHz: 2.61dB Coplanar: 9kHz~30MHz: 2.62dB Horizontal: 30MHz~200MHz: 3.79dB 200MHz~1GHz: 3.91dB 1GHz~40GHz: 4.99dB Vertical: 30MHz~200MHz: 4.06dB 200MHz~1GHz: 5.21dB 1GHz~40GHz: 4.90dB
Spurious Emissions, Conducted
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 2.2dB
Output Power
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 1.4dB
Power Spectrum Density
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 2.2dB
Occupied Bandwidth
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 2.7%

6. Test Result

6.1. Summary

FCC Section(s)	Test Description	Test Condition	Verdict
15.407(a)(10)	26dB Bandwidth	Conducted	Pass
15.407(a)(5)	Maximum Equivalent Isotropically Radiated Power (EIRP)		Pass
15.407(a)(5)	Maximum Power Spectral Density (EIRP)		Pass
15.407(b)(7)	In-Band Emission		Pass
15.407(d)(6)	Contention-Based Protocol		Pass
15.407(b)(6)	Unwanted Emissions	Radiated	Pass
15.407(b)(9), (10)	General Field Strength (Restricted Bands and Radiated Emission)		Pass
15.207	AC Conducted Emissions 150kHz - 30MHz	Line Conducted	Pass

Notes:

- The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- For radiated emission test, every axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst-case emissions.

6.2. 26dB Bandwidth Measurement

6.2.1. Test Limit

The maximum transmitter channel bandwidth for U–NII devices in the 5.925–7.125 GHz band is 320 megahertz.

6.2.2. Test Procedure

KDB 789033 D02v02r01- Section II)C)1) (26dB Bandwidth)

KDB 789033 D02v02r01- Section II)D) (99% Bandwidth)

6.2.3. Test Setting

26dB Bandwidth


1. The analyzers' automatic bandwidth measurement capability was used to perform the 26dB bandwidth
2. RBW = approximately 1% of the emission bandwidth.
3. VBW > RBW
4. Detector = Peak.
5. Trace mode = max hold.
6. Measure the maximum width of the emission that is 26 dB down from the maximum of the emission.
Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

99% Bandwidth

1. Set center frequency to the nominal EUT channel center frequency.
2. RBW = 1% to 5% of the OBW
3. $VBW \geq 3 \times RBW$
4. Span = 1.5 times to 5 times the OBW
5. Detector = peak
6. Trace mode = max hold
7. Allow the trace to stabilize
8. Use the 99% power bandwidth function of the instrument.

6.2.4. Test Setup

Spectrum Analyzer



DC Block
&
Attenuator



EUT



6.2.5. Test Result

Refer to Appendix A.2.

6.3. Output Power Measurement

6.3.1. Test Limit

For an indoor access point operating in the 5.925-7.125 GHz band, the maximum EIRP over the frequency band of operation must not exceed 30 dBm.

6.3.2. Test Procedure


KDB 789033D02v02r01- Section II)A)1

KDB 789033D02v02r01- Section II)E)2)b) Method SA-2

6.3.3. Test Setting

1. Analyzer was set to the center frequency of the UNII channel under investigation
2. Span was set to encompass the entire 26dB EBW of the signal.
3. RBW = 1MHz
4. VBW = 3MHz
5. Number of sweep points $\geq 2 \times (\text{span} / \text{RBW})$
6. Detector = power averaging (Average)
7. Sweep time = auto
8. Trigger = free run
9. Trace average at least 100 traces in power averaging (rms) mode; however, the number of traces to be averaged shall be increased above 100 as needed to ensure that the average accurately represents the true average over the on and off periods of the transmitter.
10. Use the channel power function on the instrument to measure the power of the spectrum and record its value.
11. Add $10 \cdot \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times (because the measurement represents an average over both the on and off times of the transmission). For example, add $10 \cdot \log(1/0.25) = 6$ dB if the duty cycle is 25 percent.

6.3.4. Test Setup



6.3.5. Test Result

Refer to Appendix A.3.

6.4. Power Spectral Density Measurement

6.4.1. Test Limit

For an indoor access point operating in the 5.925-7.125 GHz band, the maximum power spectral density must not exceed 5 dBm EIRP in any 1-megahertz band.

6.4.2. Test Procedure


KDB 789033D02v02r01- Section II)A)1

KDB 789033 D02v02r01-Section II)F)

6.4.3. Test Setting

1. Analyzer was set to the center frequency of the UNII channel under investigation
2. Span was set to encompass the entire 26dB EBW of the signal.
3. RBW = 1MHz
4. VBW = 3MHz
5. Number of sweep points $\geq 2 \times (\text{span} / \text{RBW})$
6. Detector = power averaging (Average)
7. Sweep time = auto
8. Trigger = free run
9. Trace average at least 100 traces in power averaging (rms) mode; however, the number of traces to be averaged shall be increased above 100 as needed to ensure that the average accurately represents the true average over the on and off periods of the transmitter.
10. Use the peak search function on the instrument to find the peak of the spectrum and record its value.
11. Add $10 \cdot \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times (because the measurement represents an average over both the on and off times of the transmission). For example, add $10 \cdot \log(1/0.25) = 6$ dB if the duty cycle is 25 percent.

6.4.4. Test Setup



6.4.5. Test Result

Refer to Appendix A.4.

6.5. In-Band Emission Measurement

6.5.1. Test Limit

Suppressed by 20 dB at 1 MHz outside of the channel edge.

(The channel edge is defined as the 26-dB point on either side of the carrier center frequency.)

Suppressed by 28 dB at one channel bandwidth from the channel center.

Suppressed by 40 dB at one- and one-half times the channel bandwidth from the channel center.

6.5.2. Test Procedure

KDB 789033D02v02r01- Section II)A)1

KDB 987594 D02v01r01- Section J

6.5.3. Test Setting


Emissions Mask Reference Level Measurement

1. Set the span to encompass the entire 26 dB EBW of the signal.
2. Set RBW = same RBW used for 26 dB EBW measurement.
3. Set VBW $\geq 3 \times$ RBW.
4. Number of points in sweep $\geq [2 \times \text{span} / \text{RBW}]$.
5. Sweep time = auto.
6. Detector = RMS.
7. Trace average at least 100 traces in power averaging (rms) mode.
8. Use the peak search function on the instrument to find the peak of the spectrum.

In-Band Emission

1. Using the measuring equipment limit line function, develop the emissions mask based on rule.
2. Adjust the span to encompass the entire mask as necessary.
3. Clear trace.
4. Trace average at least 100 traces in power averaging (rms) mode.
5. Adjust the reference level as necessary so that the crest of the channel touches the top of the emission mask.

6.5.4. Test Setup



6.5.5. Test Result

Refer to Appendix A.5.

6.6. Frequency Stability Measurement

6.6.1. Test Limit

Manufactures of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

6.6.2. Test Procedure

Frequency Stability Under Temperature Variations:


The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20°C operating frequency as reference frequency. Turn EUT off and set the chamber temperature to highest. After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure with 10°C decreased per stage until the lowest temperature reached.

Frequency Stability Under Voltage Variations:

Set chamber temperature to 20°C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.

Reduce the input voltage to specify extreme voltage variation ($\pm 15\%$) and endpoint, record the maximum frequency change.

6.6.3. Test Setup



6.6.4. Test Result

Refer to Appendix A.6.

6.7. Contention Based Protocol Measurement

6.7.1. Test Limit

Unlicensed indoor low power device must detect co-channel radio frequency power that is at least -62dBm (The threshold is referenced to a 0dBi antenna gain.) or low.

Indoor low power device must detect an AWGN signal with 90% (or better) level of certainty.

6.7.2. Test Procedure


KDB 987594 D02v02r01- Section I

6.7.3. Test Setting

1. Configure the EUT to transmit with a constant duty cycle.
2. Set the operating parameters of the EUT including power level, operating frequency, modulation and bandwidth.
3. Set the signal analyzer center frequency to the nominal EUT channel center frequency. The span range of the signal analyzer shall be between two times and five times the OBW of the EUT.
Connect the output port of the EUT to the signal analyzer 2. Ensure that the attenuator 2 provides enough attenuation to not overload the signal analyzer 2 receiver.
4. Monitoring the signal analyzer 2, verify the EUT is operating and transmitting with the parameters set at step two.
5. Using an AWGN signal source, generate a 10 MHz-wide AWGN signal. Use Table 1 of KDB 987594 to determine the center frequency of the 10 MHz AWGN signal relative to the EUT's channel bandwidth and center frequency.
6. Set the AWGN signal power to an extremely low level. Connect the AWGN signal source, via a 3-dB splitter, to the signal analyzer 1 and the EUT as shown in below figure.
7. Transmit the AWGN signal (RF ON) and verify its characteristics on the signal analyzer 1.
8. Monitor the signal analyzer 2 to verify if the AWGN signal has been detected and the EUT has ceased transmission. If the EUT continues to transmit, then incrementally increase the AWGN signal power level until the EUT stops transmitting.
9. Determine and record the AWGN signal power level (at the EUT's antenna port) at which the EUT ceased transmission. Repeat the procedure at least 10 times to verify the EUT can detect an AWGN signal with 90% (or better) level of certainty.
10. Refer to Table 1 to determine number of times the detection threshold testing needs to be repeated. If

testing is required more than once, then go back to step 5, choose a different center frequency for the AWGN signal and repeat the process.

6.7.4. Test Setup



6.7.5. Test Result

Refer to Appendix A.7.

6.8. Radiated Spurious Emission Measurement

6.8.1. Test Limit

For 15.407(b)(5) requirement

For transmitters operating within the 5.925-7.125 GHz band: Any emissions outside of the 5.925-7.125 GHz band must not exceed an EIRP. of -27 dBm/MHz.

Refer to 987594 D02 U-NII 6GHz EMC Measurement v02r01 clause G

Use guidance in KDB 789033 for measurements below 1000 MHz and above 1000 MHz. Unwanted emissions outside of restricted bands are measured with a RMS detector. In addition, 15.35(b) applies where the peak emissions must be limited to no more than 20 dB above the average limit.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [uV/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

6.8.2. Test Procedure

KDB 789033 D02v02r01-Section II)G)

6.8.3. Test Setting

Table 1 - RBW as a function of frequency

Frequency	RBW
9 ~ 150 kHz	200 ~ 300 Hz
0.15 ~ 30 MHz	9 ~ 10 kHz
30 ~ 1000 MHz	100 ~ 120 kHz
> 1000MHz	1MHz

Quasi-Peak Measurements below 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. Span was set greater than 1MHz
3. RBW = as specified in Table 1
4. Detector = CISPR quasi-peak
5. Sweep time = auto couple
6. Trace was allowed to stabilize

Peak Measurements above 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Average Measurements above 1GHz (Method VB)


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW; If the EUT is configured to transmit with duty cycle $\geq 98\%$, set VBW = 10 Hz.

If the EUT duty cycle is $< 98\%$, set $\text{VBW} \geq 1/T$. T is the minimum transmission duration.


4. As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode
5. Detector = Peak
6. Sweep time = auto
7. Trace mode = max hold
8. Allow max hold to run for at least 50 times (1/duty cycle) traces

6.8.4. Test Setup


Below 30MHz Test Setup:



Below 1GHz Test Setup:



Above 1GHz Test Setup:



6.8.5. Test Result

Refer to Appendix A.8.

6.9. Radiated Restricted Band Edge Measurement

6.9.1. Test Limit

For 15.205 requirement:

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) of FCC part 15, must also comply with the radiated emission limits specified in Section 15.209(a).

Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)
13.36 - 13.41	--	--	--

For 15.407(b)(5) requirement:

For transmitters operating within the 5.925-7.125 GHz band: Any emissions outside of the 5.925-7.125 GHz band must not exceed an EIRP. of -27 dBm/MHz.

Refer to 987594 D02 U-NII 6GHz EMC Measurement v02r01 clause G - Unwanted Emission Measurement
Use guidance in KDB 789033 for measurements below 1000 MHz and above 1000 MHz. Unwanted emissions outside of restricted bands are measured with a RMS detector. In addition, 15.35(b) applies where the peak emissions must be limited to no more than 20 dB above the average limit.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [uV/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

6.9.2. Test Procedure

KDB 789033 D02v02r01-Section II)G)

6.9.3. Test Setting


Peak Measurements above 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = Peak
5. Sweep time = Auto couple
6. Trace mode = Max hold
7. Trace was allowed to stabilize

Average Measurements above 1GHz (Method VB)

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW; If the EUT is configured to transmit with duty cycle $\geq 98\%$, set VBW = 10 Hz.
If the EUT duty cycle is $< 98\%$, set $\text{VBW} \geq 1/T$. T is the minimum transmission duration.
4. As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode
5. Detector = Peak
6. Sweep time = Auto
7. Trace mode = Max hold
8. Trace was allowed to stabilize

6.9.4. Test Setup



6.9.5. Test Result

Refer to Appendix A.9.

6.10. AC Conducted Emissions Measurement


6.10.1. Test Limit

FCC Part 15.207 Limits		
Frequency (MHz)	QP (dBuV)	AV (dBuV)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.

Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.

6.10.2. Test Setup



6.10.3. Test Result


Refer to Appendix A.10.

Appendix A – Test Result

A.1 Duty Cycle Test Result

Test Site	SIP-AC3	Test Engineer	Barry Wu
Test Date	2024-01-17~2024-02-28		

Test Mode	Duty Cycle
802.11a	94.50%
802.11ax-HE20	79.24%
802.11ax-HE40	79.53%
802.11ax-HE80	80.29%
802.11ax-HE160	79.82%
Duty Cycle (T = Transmission Duration)	
802.11a (T = 1.970ms)	802.11ax-HE20 (T = 5.420ms)
802.11ax-HE40 (T = 5.440ms)	802.11ax-HE80 (T = 5.460ms)



A.2 26dB Bandwidth Test Result


Test Site	SIP-TR1	Test Engineer	Alisa Deng
Test Date	2024-01-30		

Test Mode	Data Rate/ MCS	Channel No.	Frequency (MHz)	26dB Bandwidth (MHz)	99% Bandwidth (MHz)	Test Limit (MHz)
802.11a	6Mbps	1	5955	18.99	16.359	≤ 320
802.11a	6Mbps	49	6195	19.03	16.330	≤ 320
802.11a	6Mbps	93	6415	19.01	16.338	≤ 320
802.11a	6Mbps	97	6435	18.69	16.346	≤ 320
802.11a	6Mbps	105	6475	18.69	16.343	≤ 320
802.11a	6Mbps	113	6515	18.94	16.329	≤ 320
802.11a	6Mbps	117	6535	19.09	16.350	≤ 320
802.11a	6Mbps	149	6695	19.02	16.350	≤ 320
802.11a	6Mbps	181	6855	18.89	16.347	≤ 320
802.11a	6Mbps	185	6875	19.14	16.337	≤ 320
802.11a	6Mbps	189	6895	19.05	16.349	≤ 320
802.11a	6Mbps	209	6995	19.13	16.344	≤ 320
802.11a	6Mbps	229	7095	19.01	16.329	≤ 320
802.11ax-HE20	MCS0	1	5955	20.81	18.875	≤ 320
802.11ax-HE20	MCS0	49	6195	20.52	18.854	≤ 320
802.11ax-HE20	MCS0	93	6415	20.89	18.876	≤ 320
802.11ax-HE20	MCS0	97	6435	20.79	18.887	≤ 320
802.11ax-HE20	MCS0	105	6475	20.59	18.892	≤ 320
802.11ax-HE20	MCS0	113	6515	20.83	18.892	≤ 320
802.11ax-HE20	MCS0	117	6535	20.70	18.874	≤ 320
802.11ax-HE20	MCS0	149	6695	20.39	18.865	≤ 320
802.11ax-HE20	MCS0	181	6855	20.74	18.871	≤ 320
802.11ax-HE20	MCS0	185	6875	20.64	18.873	≤ 320
802.11ax-HE20	MCS0	189	6895	21.05	18.902	≤ 320
802.11ax-HE20	MCS0	209	6995	20.72	18.858	≤ 320
802.11ax-HE20	MCS0	229	7095	20.44	18.874	≤ 320

Test Mode	Data Rate/ MCS	Channel No.	Frequency (MHz)	26dB Bandwidth (MHz)	99% Bandwidth (MHz)	Test Limit (MHz)
802.11ax-HE40	MCS0	3	5965	40.01	37.554	≤ 320
802.11ax-HE40	MCS0	51	6205	40.42	37.707	≤ 320
802.11ax-HE40	MCS0	91	6405	40.38	37.684	≤ 320
802.11ax-HE40	MCS0	99	6445	39.97	37.639	≤ 320
802.11ax-HE40	MCS0	107	6485	40.26	37.642	≤ 320
802.11ax-HE40	MCS0	115	6525	40.10	37.614	≤ 320
802.11ax-HE40	MCS0	123	6565	40.01	37.652	≤ 320
802.11ax-HE40	MCS0	147	6685	39.44	37.573	≤ 320
802.11ax-HE40	MCS0	179	6845	39.59	37.611	≤ 320
802.11ax-HE40	MCS0	187	6885	39.77	37.704	≤ 320
802.11ax-HE40	MCS0	195	6925	39.64	37.645	≤ 320
802.11ax-HE40	MCS0	211	7005	39.59	37.636	≤ 320
802.11ax-HE40	MCS0	227	7085	39.46	37.640	≤ 320
802.11ax-HE80	MCS0	7	5985	80.93	77.116	≤ 320
802.11ax-HE80	MCS0	55	6225	81.49	76.943	≤ 320
802.11ax-HE80	MCS0	87	6385	81.78	77.003	≤ 320
802.11ax-HE80	MCS0	103	6465	80.35	77.035	≤ 320
802.11ax-HE80	MCS0	119	6545	80.67	77.096	≤ 320
802.11ax-HE80	MCS0	135	6625	82.37	77.002	≤ 320
802.11ax-HE80	MCS0	151	6705	81.50	77.075	≤ 320
802.11ax-HE80	MCS0	167	6785	80.95	76.928	≤ 320
802.11ax-HE80	MCS0	183	6865	81.01	76.796	≤ 320
802.11ax-HE80	MCS0	199	6945	80.97	77.102	≤ 320
802.11ax-HE80	MCS0	215	7025	80.80	76.916	≤ 320
802.11ax-HE160	MCS0	15	6025	162.1	154.65	≤ 320
802.11ax-HE160	MCS0	47	6185	163.9	155.01	≤ 320
802.11ax-HE160	MCS0	79	6345	164.0	154.58	≤ 320
802.11ax-HE160	MCS0	111	6505	162.9	154.90	≤ 320
802.11ax-HE160	MCS0	143	6665	164.4	155.00	≤ 320
802.11ax-HE160	MCS0	175	6825	163.2	154.80	≤ 320
802.11ax-HE160	MCS0	207	6985	162.6	154.66	≤ 320


Note: For channels with a nominal bandwidth less than 320 MHz compliance is demonstrated by way of the 26 dB EBW.

For channels with a nominal bandwidth of 320 MHz compliance is demonstrated by way of the 99% BW.




802.11a 26dB Bandwidth


Channel 117 (6535MHz)




Channel 149 (6695MHz)




Channel 181 (6855MHz)




Channel 185 (6875MHz)




Channel 189 (6895MHz)




Channel 209 (6995MHz)






802.11ax-HE20 26dB Bandwidth


Channel 1 (5955MHz)



Channel 49 (6195MHz)




Channel 93 (6415MHz)



Channel 97 (6435MHz)



Channel 105 (6475MHz)




Channel 113 (6515MHz)




802.11ax-HE20 26dB Bandwidth


Channel 117 (6535MHz)




Channel 149 (6695MHz)




Channel 181 (6855MHz)



Channel 185 (6875MHz)




Channel 189 (6895MHz)




Channel 209 (6995MHz)






802.11ax-HE40 26dB Bandwidth


Channel 3 (5965MHz)




Channel 51 (6205MHz)




Channel 91 (6405MHz)




Channel 99 (6445MHz)



Channel 107 (6485MHz)




Channel 115 (6525MHz)




802.11ax-HE40 26dB Bandwidth


Channel 123 (6565MHz)




Channel 147 (6685MHz)




Channel 179 (6845MHz)




Channel 187 (6885MHz)




Channel 195 (6925MHz)




Channel 211 (7005MHz)






802.11ax-HE80 26dB Bandwidth


Channel 7 (5985MHz)




Channel 55 (6225MHz)




Channel 87 (6385MHz)




Channel 103 (6465MHz)



Channel 119 (6545MHz)




Channel 135 (6625MHz)



802.11ax-HE80 26dB Bandwidth


Channel 151 (6705MHz)




Channel 167 (6785MHz)




Channel 183 (6865MHz)



Channel 199 (6945MHz)




Channel 215 (7025MHz)




802.11ax-HE160 26dB Bandwidth


Channel 15 (6025MHz)



Channel 47 (6185MHz)




Channel 79 (6345MHz)



Channel 111 (6505MHz)




Channel 143 (6665MHz)



Channel 175 (6825MHz)





A.3 Output Power Test Result

Test Site	SIP-AC3	Test Engineer	Barry Wu
Test Date	2024-01-18~2024-01-30		

Test Mode	Data Rate/ MCS	Channel No.	Freq. (MHz)	EIRP (dBuV/m)	EIRP (dBm)	Duty Cycle (%)	Duty Cycle Factor	Total EIRP (dBm)	Limit (dBm)
802.11a	6Mbps	1	5955	108.1	12.90	94.50	0.25	13.15	≤ 30.00
802.11a	6Mbps	49	6195	108.3	13.10	94.50	0.25	13.35	≤ 30.00
802.11a	6Mbps	93	6415	108.7	13.50	94.50	0.25	13.75	≤ 30.00
802.11a	6Mbps	97	6435	108.7	13.50	94.50	0.25	13.75	≤ 30.00
802.11a	6Mbps	105	6475	108.5	13.30	94.50	0.25	13.55	≤ 30.00
802.11a	6Mbps	113	6515	108.7	13.50	94.50	0.25	13.75	≤ 30.00
802.11a	6Mbps	117	6535	108.3	13.10	94.50	0.25	13.35	≤ 30.00
802.11a	6Mbps	149	6695	108.0	12.80	94.50	0.25	13.05	≤ 30.00
802.11a	6Mbps	181	6855	108.5	13.30	94.50	0.25	13.55	≤ 30.00
802.11a	6Mbps	185	6875	108.0	12.80	94.50	0.25	13.05	≤ 30.00
802.11a	6Mbps	189	6895	108.1	12.90	94.50	0.25	13.15	≤ 30.00
802.11a	6Mbps	209	6995	108.9	13.70	94.50	0.25	13.95	≤ 30.00
802.11a	6Mbps	229	7095	109.3	14.10	94.50	0.25	14.35	≤ 30.00
802.11ax-HE20	MCS0	1	5955	112.0	16.80	79.24	1.01	17.81	≤ 30.00
802.11ax-HE20	MCS0	49	6195	112.0	16.80	79.24	1.01	17.81	≤ 30.00
802.11ax-HE20	MCS0	93	6415	112.2	17.00	79.24	1.01	18.01	≤ 30.00
802.11ax-HE20	MCS0	97	6435	112.2	17.00	79.24	1.01	18.01	≤ 30.00
802.11ax-HE20	MCS0	105	6475	112.0	16.80	79.24	1.01	17.81	≤ 30.00
802.11ax-HE20	MCS0	113	6515	111.8	16.60	79.24	1.01	17.61	≤ 30.00
802.11ax-HE20	MCS0	117	6535	112.1	16.90	79.24	1.01	17.91	≤ 30.00
802.11ax-HE20	MCS0	149	6695	111.4	16.20	79.24	1.01	17.21	≤ 30.00
802.11ax-HE20	MCS0	181	6855	111.3	16.10	79.24	1.01	17.11	≤ 30.00
802.11ax-HE20	MCS0	185	6875	111.8	16.60	79.24	1.01	17.61	≤ 30.00
802.11ax-HE20	MCS0	189	6895	111.8	16.60	79.24	1.01	17.61	≤ 30.00
802.11ax-HE20	MCS0	209	6995	111.4	16.20	79.24	1.01	17.21	≤ 30.00
802.11ax-HE20	MCS0	229	7095	111.3	16.10	79.24	1.01	17.11	≤ 30.00

Test Mode	Data Rate/ MCS	Channel No.	Freq. (MHz)	EIRP (dBuV/m)	EIRP (dBm)	Duty Cycle (%)	Duty Cycle Factor	Total EIRP (dBm)	Limit (dBm)
802.11ax-HE40	MCS0	3	5965	115.0	19.80	79.53	0.99	20.79	≤ 30.00
802.11ax-HE40	MCS0	51	6205	114.6	19.40	79.53	0.99	20.39	≤ 30.00
802.11ax-HE40	MCS0	91	6405	114.6	19.40	79.53	0.99	20.39	≤ 30.00
802.11ax-HE40	MCS0	99	6445	115.1	19.90	79.53	0.99	20.89	≤ 30.00
802.11ax-HE40	MCS0	107	6485	115.1	19.90	79.53	0.99	20.89	≤ 30.00
802.11ax-HE40	MCS0	115	6525	115.1	19.90	79.53	0.99	20.89	≤ 30.00
802.11ax-HE40	MCS0	123	6565	114.9	19.70	79.53	0.99	20.69	≤ 30.00
802.11ax-HE40	MCS0	147	6685	114.8	19.60	79.53	0.99	20.59	≤ 30.00
802.11ax-HE40	MCS0	179	6845	114.7	19.50	79.53	0.99	20.49	≤ 30.00
802.11ax-HE40	MCS0	187	6885	114.7	19.50	79.53	0.99	20.49	≤ 30.00
802.11ax-HE40	MCS0	195	6925	114.8	19.60	79.53	0.99	20.59	≤ 30.00
802.11ax-HE40	MCS0	211	7005	115.2	20.00	79.53	0.99	20.99	≤ 30.00
802.11ax-HE40	MCS0	227	7085	115.0	19.80	79.53	0.99	20.79	≤ 30.00
802.11ax-HE80	MCS0	7	5985	118.1	22.90	80.29	0.95	23.85	≤ 30.00
802.11ax-HE80	MCS0	55	6225	118.2	23.00	80.29	0.95	23.95	≤ 30.00
802.11ax-HE80	MCS0	87	6385	117.7	22.50	80.29	0.95	23.45	≤ 30.00
802.11ax-HE80	MCS0	103	6465	117.6	22.40	80.29	0.95	23.35	≤ 30.00
802.11ax-HE80	MCS0	119	6545	118.1	22.90	80.29	0.95	23.85	≤ 30.00
802.11ax-HE80	MCS0	135	6625	118.3	23.10	80.29	0.95	24.05	≤ 30.00
802.11ax-HE80	MCS0	151	6705	117.9	22.70	80.29	0.95	23.65	≤ 30.00
802.11ax-HE80	MCS0	167	6785	117.7	22.50	80.29	0.95	23.45	≤ 30.00
802.11ax-HE80	MCS0	183	6865	117.9	22.70	80.29	0.95	23.65	≤ 30.00
802.11ax-HE80	MCS0	199	6945	118.0	22.80	80.29	0.95	23.75	≤ 30.00
802.11ax-HE80	MCS0	215	7025	117.8	22.60	80.29	0.95	23.55	≤ 30.00
802.11ax-HE160	MCS0	15	6025	120.7	25.50	79.82	0.98	26.48	≤ 30.00
802.11ax-HE160	MCS0	47	6185	120.1	24.90	79.82	0.98	25.88	≤ 30.00
802.11ax-HE160	MCS0	79	6345	120.8	25.60	79.82	0.98	26.58	≤ 30.00
802.11ax-HE160	MCS0	111	6505	121.3	26.10	79.82	0.98	27.08	≤ 30.00
802.11ax-HE160	MCS0	143	6665	121.0	25.80	79.82	0.98	26.78	≤ 30.00
802.11ax-HE160	MCS0	175	6825	121.0	25.80	79.82	0.98	26.78	≤ 30.00
802.11ax-HE160	MCS0	207	6985	121.1	25.90	79.82	0.98	26.88	≤ 30.00

Note 1: EIRP (dBm) = EIRP (dBuV/m) - 95.2.

Note 2: Total EIRP (dBm) = EIRP (dBm) + Duty Cycle Factor.

Duty Cycle Factor = $10 * \log(100 / \text{Duty Cycle})$.

A.4 Power Spectral Density Test Result

Test Site	SIP-AC3	Test Engineer	Barry Wu
Test Date	2024-01-17~2024-01-30		

Test Mode	Data Rate/ MCS	Channel No.	Freq. (MHz)	EIRP PSD (dBuV/MHz)	EIRP PSD (dBm/MHz)	Duty Cycle (%)	Duty Cycle Factor	Final EIRP PSD (dBm/MHz)	Limit (dBm/MHz)
802.11a	6Mbps	1	5955	99.754	4.55	94.50	0.25	4.80	≤ 5.00
802.11a	6Mbps	49	6195	99.399	4.20	94.50	0.25	4.44	≤ 5.00
802.11a	6Mbps	93	6415	99.564	4.36	94.50	0.25	4.61	≤ 5.00
802.11a	6Mbps	97	6435	99.450	4.25	94.50	0.25	4.50	≤ 5.00
802.11a	6Mbps	105	6475	99.573	4.37	94.50	0.25	4.62	≤ 5.00
802.11a	6Mbps	113	6515	99.742	4.54	94.50	0.25	4.79	≤ 5.00
802.11a	6Mbps	117	6535	99.500	4.30	94.50	0.25	4.55	≤ 5.00
802.11a	6Mbps	149	6695	99.286	4.09	94.50	0.25	4.33	≤ 5.00
802.11a	6Mbps	181	6855	99.524	4.32	94.50	0.25	4.57	≤ 5.00
802.11a	6Mbps	185	6875	99.348	4.15	94.50	0.25	4.39	≤ 5.00
802.11a	6Mbps	189	6895	99.572	4.37	94.50	0.25	4.62	≤ 5.00
802.11a	6Mbps	209	6995	99.443	4.24	94.50	0.25	4.49	≤ 5.00
802.11a	6Mbps	229	7095	99.349	4.15	94.50	0.25	4.39	≤ 5.00
802.11ax-HE20	MCS0	1	5955	98.798	3.60	79.24	1.01	4.61	≤ 5.00
802.11ax-HE20	MCS0	49	6195	98.867	3.67	79.24	1.01	4.68	≤ 5.00
802.11ax-HE20	MCS0	93	6415	98.922	3.72	79.24	1.01	4.73	≤ 5.00
802.11ax-HE20	MCS0	97	6435	99.070	3.87	79.24	1.01	4.88	≤ 5.00
802.11ax-HE20	MCS0	105	6475	98.492	3.29	79.24	1.01	4.30	≤ 5.00
802.11ax-HE20	MCS0	113	6515	98.757	3.56	79.24	1.01	4.57	≤ 5.00
802.11ax-HE20	MCS0	117	6535	98.700	3.50	79.24	1.01	4.51	≤ 5.00
802.11ax-HE20	MCS0	149	6695	98.552	3.35	79.24	1.01	4.36	≤ 5.00
802.11ax-HE20	MCS0	181	6855	98.502	3.30	79.24	1.01	4.31	≤ 5.00
802.11ax-HE20	MCS0	185	6875	98.972	3.77	79.24	1.01	4.78	≤ 5.00
802.11ax-HE20	MCS0	189	6895	98.788	3.59	79.24	1.01	4.60	≤ 5.00
802.11ax-HE20	MCS0	209	6995	98.625	3.43	79.24	1.01	4.44	≤ 5.00
802.11ax-HE20	MCS0	229	7095	98.349	3.15	79.24	1.01	4.16	≤ 5.00

Test Mode	Data Rate/ MCS	Channel No.	Freq. (MHz)	EIRP PSD (dBuV/MHz)	EIRP PSD (dBm/MHz)	Duty Cycle (%)	Duty Cycle Factor	Final EIRP PSD (dBm/MHz)	Limit (dBm/MHz)
802.11ax-HE40	MCS0	3	5965	99.029	3.83	79.53	0.99	4.82	≤ 5.00
802.11ax-HE40	MCS0	51	6205	98.643	3.44	79.53	0.99	4.44	≤ 5.00
802.11ax-HE40	MCS0	91	6405	98.529	3.33	79.53	0.99	4.32	≤ 5.00
802.11ax-HE40	MCS0	99	6445	99.040	3.84	79.53	0.99	4.83	≤ 5.00
802.11ax-HE40	MCS0	107	6485	98.909	3.71	79.53	0.99	4.70	≤ 5.00
802.11ax-HE40	MCS0	115	6525	98.724	3.52	79.53	0.99	4.52	≤ 5.00
802.11ax-HE40	MCS0	123	6565	98.542	3.34	79.53	0.99	4.34	≤ 5.00
802.11ax-HE40	MCS0	147	6685	98.996	3.80	79.53	0.99	4.79	≤ 5.00
802.11ax-HE40	MCS0	179	6845	99.046	3.85	79.53	0.99	4.84	≤ 5.00
802.11ax-HE40	MCS0	187	6885	98.982	3.78	79.53	0.99	4.78	≤ 5.00
802.11ax-HE40	MCS0	195	6925	98.673	3.47	79.53	0.99	4.47	≤ 5.00
802.11ax-HE40	MCS0	211	7005	98.926	3.73	79.53	0.99	4.72	≤ 5.00
802.11ax-HE40	MCS0	227	7085	98.980	3.78	79.53	0.99	4.77	≤ 5.00
802.11ax-HE80	MCS0	7	5985	99.090	3.89	80.29	0.95	4.84	≤ 5.00
802.11ax-HE80	MCS0	55	6225	99.051	3.85	80.29	0.95	4.80	≤ 5.00
802.11ax-HE80	MCS0	87	6385	99.007	3.81	80.29	0.95	4.76	≤ 5.00
802.11ax-HE80	MCS0	103	6465	98.709	3.51	80.29	0.95	4.46	≤ 5.00
802.11ax-HE80	MCS0	119	6545	98.898	3.70	80.29	0.95	4.65	≤ 5.00
802.11ax-HE80	MCS0	135	6625	99.042	3.84	80.29	0.95	4.80	≤ 5.00
802.11ax-HE80	MCS0	151	6705	98.562	3.36	80.29	0.95	4.32	≤ 5.00
802.11ax-HE80	MCS0	167	6785	98.849	3.65	80.29	0.95	4.60	≤ 5.00
802.11ax-HE80	MCS0	183	6865	98.613	3.41	80.29	0.95	4.37	≤ 5.00
802.11ax-HE80	MCS0	199	6945	99.053	3.85	80.29	0.95	4.81	≤ 5.00
802.11ax-HE80	MCS0	215	7025	98.500	3.30	80.29	0.95	4.25	≤ 5.00
802.11ax-HE160	MCS0	15	6025	98.900	3.70	79.82	0.98	4.68	≤ 5.00
802.11ax-HE160	MCS0	47	6185	98.830	3.63	79.82	0.98	4.61	≤ 5.00
802.11ax-HE160	MCS0	79	6345	99.103	3.90	79.82	0.98	4.88	≤ 5.00
802.11ax-HE160	MCS0	111	6505	99.089	3.89	79.82	0.98	4.87	≤ 5.00
802.11ax-HE160	MCS0	143	6665	98.753	3.55	79.82	0.98	4.53	≤ 5.00
802.11ax-HE160	MCS0	175	6825	99.049	3.85	79.82	0.98	4.83	≤ 5.00
802.11ax-HE160	MCS0	207	6985	99.035	3.83	79.82	0.98	4.81	≤ 5.00


Note 1: EIRP PSD (dBm/MHz) = EIRP PSD (dBuV/MHz) - 95.2.

Note 2: Final EIRP PSD (dBm/MHz) = EIRP PSD (dBm/MHz) + Duty Cycle Factor.


Duty Cycle Factor = $10 * \log(100 / \text{Duty Cycle})$.

802.11a Power Spectral Density


Channel 1 (5955MHz)




Channel 49 (6195MHz)




Channel 93 (6415MHz)



Channel 97 (6435MHz)



Channel 105 (6475MHz)



Channel 113 (6515MHz)

