



Title: Actiontec R3000 Wireless Router
To: FCC CFR 47 Part 15C, 15.407
Serial #: ATEC01-U19 Rev A
Issue Date: 20th January 2015
Page: 86 of 261

APPENDIX

A. SUPPORTING INFORMATION

A.1. CONDUCTED TEST PLOTS


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

A.1.1. 26 dB & 99% Bandwidth



26 dB & 99% BANDWIDTH


Variant: 802.11a, Channel: 5745.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5733.928 MHz : -11.904 dBm M2 : 5749.158 MHz : 14.274 dBm Delta1 : 22.144 MHz : 0.789 dB T1 : 5736.633 MHz : 6.810 dBm T2 : 5753.367 MHz : 6.648 dBm OBW : 16.733 MHz	Measured 26 dB Bandwidth: 22.144 MHz Measured 99% Bandwidth: 16.733 MHz


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5733.427 MHz : -13.566 dBm M2 : 5738.938 MHz : 13.400 dBm Delta1 : 23.046 MHz : 0.972 dB T1 : 5736.533 MHz : 5.269 dBm T2 : 5753.367 MHz : 6.564 dBm OBW : 16.834 MHz	Measured 26 dB Bandwidth: 23.046 MHz Measured 99% Bandwidth: 16.834 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5733.727 MHz : -12.431 dBm M2 : 5746.052 MHz : 14.146 dBm Delta1 : 22.044 MHz : 1.151 dB T1 : 5736.633 MHz : 6.335 dBm T2 : 5753.367 MHz : 6.572 dBm OBW : 16.733 MHz	Measured 26 dB Bandwidth: 22.044 MHz Measured 99% Bandwidth: 16.733 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5733.828 MHz : -11.414 dBm M2 : 5752.565 MHz : 14.683 dBm Delta1 : 23.146 MHz : 1.259 dB T1 : 5736.633 MHz : 7.380 dBm T2 : 5753.467 MHz : 5.478 dBm OBW : 16.834 MHz	Measured 26 dB Bandwidth: 23.146 MHz Measured 99% Bandwidth: 16.834 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5773.928 MHz : -11.778 dBm M2 : 5789.158 MHz : 14.667 dBm Delta1 : 22.244 MHz : 0.952 dB T1 : 5776.633 MHz : 6.910 dBm T2 : 5793.367 MHz : 6.835 dBm OBW : 16.733 MHz	Measured 26 dB Bandwidth: 22.244 MHz Measured 99% Bandwidth: 16.733 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5773.427 MHz : -13.671 dBm M2 : 5792.465 MHz : 13.241 dBm Delta1 : 22.846 MHz : 2.070 dB T1 : 5776.533 MHz : 4.646 dBm T2 : 5793.467 MHz : 4.116 dBm OBW : 16.934 MHz	Measured 26 dB Bandwidth: 22.846 MHz Measured 99% Bandwidth: 16.934 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5773.727 MHz : -12.585 dBm M2 : 5786.052 MHz : 13.725 dBm Delta1 : 22.244 MHz : 0.630 dB T1 : 5776.633 MHz : 6.143 dBm T2 : 5793.367 MHz : 6.611 dBm OBW : 16.733 MHz	Measured 26 dB Bandwidth: 22.244 MHz Measured 99% Bandwidth: 16.733 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5773.527 MHz : -12.974 dBm M2 : 5792.265 MHz : 14.087 dBm Delta1 : 23.447 MHz : 1.845 dB T1 : 5776.633 MHz : 6.865 dBm T2 : 5793.467 MHz : 5.116 dBm OBW : 16.834 MHz	Measured 26 dB Bandwidth: 23.447 MHz Measured 99% Bandwidth: 16.834 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5813.727 MHz : -12.941 dBm M2 : 5829.158 MHz : 14.020 dBm Delta1 : 22.345 MHz : 1.397 dB T1 : 5816.633 MHz : 6.471 dBm T2 : 5833.367 MHz : 5.676 dBm OBW : 16.733 MHz	Measured 26 dB Bandwidth: 22.345 MHz Measured 99% Bandwidth: 16.733 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5813.527 MHz : -13.804 dBm M2 : 5818.737 MHz : 12.556 dBm Delta1 : 22.745 MHz : 0.765 dB T1 : 0 Hz : 500.000 dBm T2 : 0 Hz : 500.000 dBm OBW : 16.834 MHz	Measured 26 dB Bandwidth: 22.745 MHz Measured 99% Bandwidth: 16.834 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5813.727 MHz : -13.682 dBm M2 : 5830.060 MHz : 12.861 dBm Delta1 : 22.144 MHz : 1.542 dB T1 : 5816.633 MHz : 5.061 dBm T2 : 5833.367 MHz : 5.350 dBm OBW : 16.733 MHz	Measured 26 dB Bandwidth: 22.144 MHz Measured 99% Bandwidth: 16.733 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5813.727 MHz : -13.175 dBm M2 : 5829.960 MHz : 13.605 dBm Delta1 : 22.745 MHz : 1.470 dB T1 : 5816.633 MHz : 6.343 dBm T2 : 5833.367 MHz : 5.901 dBm OBW : 16.733 MHz	Measured 26 dB Bandwidth: 22.745 MHz Measured 99% Bandwidth: 16.733 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5733.928 MHz : -11.904 dBm M2 : 5749.158 MHz : 14.274 dBm Delta1 : 22.144 MHz : 0.789 dB T1 : 5736.633 MHz : 6.810 dBm T2 : 5753.367 MHz : 6.648 dBm OBW : 16.733 MHz	Channel Frequency: 5745.00 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5733.427 MHz : -13.566 dBm M2 : 5738.938 MHz : 13.400 dBm Delta1 : 23.046 MHz : 0.972 dB T1 : 5736.533 MHz : 5.269 dBm T2 : 5753.367 MHz : 6.564 dBm OBW : 16.834 MHz	Channel Frequency: 5745.00 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5733.727 MHz : -12.431 dBm M2 : 5746.052 MHz : 14.146 dBm Delta1 : 22.044 MHz : 1.151 dB T1 : 5736.633 MHz : 6.335 dBm T2 : 5753.367 MHz : 6.572 dBm OBW : 16.733 MHz	Channel Frequency: 5745.00 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5733.828 MHz : -11.414 dBm M2 : 5752.565 MHz : 14.683 dBm Delta1 : 23.146 MHz : 1.259 dB T1 : 5736.633 MHz : 7.380 dBm T2 : 5753.467 MHz : 5.478 dBm OBW : 16.834 MHz	Channel Frequency: 5745.00 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5773.928 MHz : -11.778 dBm M2 : 5789.158 MHz : 14.667 dBm Delta1 : 22.244 MHz : 0.952 dB T1 : 5776.633 MHz : 6.910 dBm T2 : 5793.367 MHz : 6.835 dBm OBW : 16.733 MHz	Channel Frequency: 5785.00 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5773.427 MHz : -13.671 dBm M2 : 5792.465 MHz : 13.241 dBm Delta1 : 22.846 MHz : 2.070 dB T1 : 5776.533 MHz : 4.646 dBm T2 : 5793.467 MHz : 4.116 dBm OBW : 16.934 MHz	Channel Frequency: 5785.00 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5773.727 MHz : -12.585 dBm M2 : 5786.052 MHz : 13.725 dBm Delta1 : 22.244 MHz : 0.630 dB T1 : 5776.633 MHz : 6.143 dBm T2 : 5793.367 MHz : 6.611 dBm OBW : 16.733 MHz	Channel Frequency: 5785.00 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5773.527 MHz : -12.974 dBm M2 : 5792.265 MHz : 14.087 dBm Delta1 : 23.447 MHz : 1.845 dB T1 : 5776.633 MHz : 6.865 dBm T2 : 5793.467 MHz : 5.116 dBm OBW : 16.834 MHz	Channel Frequency: 5785.00 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5813.527 MHz : -13.804 dBm M2 : 5818.737 MHz : 12.556 dBm Delta1 : 22.745 MHz : 0.765 dB T1 : 0 Hz : 500.000 dBm T2 : 0 Hz : 500.000 dBm OBW : 16.834 MHz	Channel Frequency: 5825.00 MHz

[Back to Matrix](#)



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5813.727 MHz : -13.682 dBm M2 : 5830.060 MHz : 12.861 dBm Delta1 : 22.144 MHz : 1.542 dB T1 : 5816.633 MHz : 5.061 dBm T2 : 5833.367 MHz : 5.350 dBm OBW : 16.733 MHz	Channel Frequency: 5825.00 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5813.727 MHz : -13.175 dBm M2 : 5829.960 MHz : 13.605 dBm Delta1 : 22.745 MHz : 1.470 dB T1 : 5816.633 MHz : 6.343 dBm T2 : 5833.367 MHz : 5.901 dBm OBW : 16.733 MHz	Channel Frequency: 5825.00 MHz

[Back to Matrix](#)



26 dB & 99% BANDWIDTH

Variant: 802.11a, Channel: 5180.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5167.625 MHz : -15.604 dBm M2 : 5173.737 MHz : 10.892 dBm Delta1 : 24.248 MHz : 1.216 dB T1 : 5171.633 MHz : 3.735 dBm T2 : 5188.367 MHz : 3.243 dBm OBW : 16.733 MHz	Measured 26 dB Bandwidth: 24.248 MHz Measured 99% Bandwidth: 16.733 MHz


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



26 dB & 99% BANDWIDTH


Variant: 802.11a, Channel: 5180.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5167.024 MHz : -17.507 dBm M2 : 5173.737 MHz : 10.601 dBm Delta1 : 25.752 MHz : 2.971 dB T1 : 5171.533 MHz : 0.610 dBm T2 : 5188.467 MHz : 0.921 dBm OBW : 16.934 MHz	Measured 26 dB Bandwidth: 25.752 MHz Measured 99% Bandwidth: 16.934 MHz


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5168.928 MHz : -15.780 dBm M2 : 5185.060 MHz : 10.461 dBm Delta1 : 21.944 MHz : 1.088 dB T1 : 5171.633 MHz : 1.962 dBm T2 : 5188.367 MHz : 2.847 dBm OBW : 16.733 MHz	Measured 26 dB Bandwidth: 21.944 MHz Measured 99% Bandwidth: 16.733 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5167.625 MHz : -15.372 dBm M2 : 5185.060 MHz : 10.634 dBm Delta1 : 24.449 MHz : 1.381 dB T1 : 5171.633 MHz : 2.125 dBm T2 : 5188.467 MHz : 0.858 dBm OBW : 16.834 MHz	Measured 26 dB Bandwidth: 24.449 MHz Measured 99% Bandwidth: 16.834 MHz

[Back to Matrix](#)



26 dB & 99% BANDWIDTH


Variant: 802.11a, Channel: 5200.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5187.926 MHz : -14.853 dBm M2 : 5204.158 MHz : 11.401 dBm Delta1 : 23.848 MHz : 0.368 dB T1 : 5191.633 MHz : 3.884 dBm T2 : 5208.367 MHz : 3.975 dBm OBW : 16.733 MHz	Measured 26 dB Bandwidth: 23.848 MHz Measured 99% Bandwidth: 16.733 MHz


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5187.725 MHz : -15.856 dBm M2 : 5193.737 MHz : 10.412 dBm Delta1 : 24.950 MHz : 1.338 dB T1 : 5191.533 MHz : 0.620 dBm T2 : 5208.467 MHz : 1.077 dBm OBW : 16.934 MHz	Measured 26 dB Bandwidth: 24.950 MHz Measured 99% Bandwidth: 16.934 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5189.228 MHz : -15.166 dBm M2 : 5205.060 MHz : 10.986 dBm Delta1 : 21.643 MHz : 0.820 dB T1 : 5191.633 MHz : 2.155 dBm T2 : 5208.367 MHz : 3.565 dBm OBW : 16.733 MHz	Measured 26 dB Bandwidth: 21.643 MHz Measured 99% Bandwidth: 16.733 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5188.026 MHz : -14.328 dBm M2 : 5205.060 MHz : 11.929 dBm Delta1 : 24.048 MHz : 2.170 dB T1 : 5191.633 MHz : 2.944 dBm T2 : 5208.467 MHz : 2.123 dBm OBW : 16.834 MHz	Measured 26 dB Bandwidth: 24.048 MHz Measured 99% Bandwidth: 16.834 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5227.826 MHz : -14.265 dBm M2 : 5246.263 MHz : 12.792 dBm Delta1 : 24.048 MHz : 1.954 dB T1 : 5231.633 MHz : 5.255 dBm T2 : 5248.367 MHz : 5.350 dBm OBW : 16.733 MHz	Measured 26 dB Bandwidth: 24.048 MHz Measured 99% Bandwidth: 16.733 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5227.725 MHz : -14.953 dBm M2 : 5233.737 MHz : 11.421 dBm Delta1 : 24.850 MHz : 1.102 dB T1 : 5231.533 MHz : 1.679 dBm T2 : 5248.467 MHz : 2.123 dBm OBW : 16.934 MHz	Measured 26 dB Bandwidth: 24.850 MHz Measured 99% Bandwidth: 16.934 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5229.228 MHz : -14.208 dBm M2 : 5245.060 MHz : 12.175 dBm Delta1 : 21.643 MHz : 1.090 dB T1 : 5231.633 MHz : 3.249 dBm T2 : 5248.367 MHz : 4.689 dBm OBW : 16.733 MHz	Measured 26 dB Bandwidth: 21.643 MHz Measured 99% Bandwidth: 16.733 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5227.525 MHz : -15.520 dBm M2 : 5245.060 MHz : 13.341 dBm Delta1 : 24.950 MHz : 2.070 dB T1 : 5231.633 MHz : 4.455 dBm T2 : 5248.467 MHz : 3.546 dBm OBW : 16.834 MHz	Measured 26 dB Bandwidth: 24.950 MHz Measured 99% Bandwidth: 16.834 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5146.072 MHz : -11.865 dBm M2 : 5175.331 MHz : 14.488 dBm Delta1 : 121.443 MHz : 0.588 dB T1 : 5171.723 MHz : 6.623 dBm T2 : 5248.277 MHz : 8.014 dBm OBW : 76.553 MHz	Measured 26 dB Bandwidth: 121.443 MHz Measured 99% Bandwidth: 76.553 MHz

[Back to Matrix](#)



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5145.671 MHz : -14.046 dBm M2 : 5243.868 MHz : 13.324 dBm Delta1 : 119.840 MHz : 0.942 dB T1 : 5171.723 MHz : 6.906 dBm T2 : 5248.277 MHz : 7.294 dBm OBW : 76.553 MHz	Measured 26 dB Bandwidth: 119.840 MHz Measured 99% Bandwidth: 76.553 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5155.291 MHz : -12.073 dBm M2 : 5244.669 MHz : 14.276 dBm Delta1 : 103.808 MHz : 0.472 dB T1 : 5172.124 MHz : 7.982 dBm T2 : 5248.277 MHz : 8.002 dBm OBW : 76.152 MHz	Measured 26 dB Bandwidth: 103.808 MHz Measured 99% Bandwidth: 76.152 MHz

[Back to Matrix](#)



26 dB & 99% BANDWIDTH


Variant: 802.11ac-80, Channel: 5210.00 MHz, Chain d, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5146.072 MHz : -11.489 dBm M2 : 5244.269 MHz : 15.167 dBm Delta1 : 119.840 MHz : 1.418 dB T1 : 5171.723 MHz : 7.618 dBm T2 : 5248.277 MHz : 9.186 dBm OBW : 76.553 MHz	Measured 26 dB Bandwidth: 119.840 MHz Measured 99% Bandwidth: 76.553 MHz


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5168.327 MHz : -15.571 dBm M2 : 5173.737 MHz : 10.573 dBm Delta1 : 23.547 MHz : 0.449 dB T1 : 5171.032 MHz : 3.042 dBm T2 : 5189.068 MHz : 1.567 dBm OBW : 18.036 MHz	Measured 26 dB Bandwidth: 23.547 MHz Measured 99% Bandwidth: 18.036 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5167.625 MHz : -16.533 dBm M2 : 5173.737 MHz : 10.506 dBm Delta1 : 25.050 MHz : 0.757 dB T1 : 5170.932 MHz : -0.096 dBm T2 : 5189.168 MHz : -0.011 dBm OBW : 18.236 MHz	Measured 26 dB Bandwidth: 25.050 MHz Measured 99% Bandwidth: 18.236 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5168.427 MHz : -15.573 dBm M2 : 5185.060 MHz : 10.553 dBm Delta1 : 23.347 MHz : -0.065 dB T1 : 5171.032 MHz : 2.283 dBm T2 : 5189.068 MHz : 1.167 dBm OBW : 18.036 MHz	Measured 26 dB Bandwidth: 23.347 MHz Measured 99% Bandwidth: 18.036 MHz

[Back to Matrix](#)



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5167.625 MHz : -15.752 dBm M2 : 5185.060 MHz : 10.912 dBm Delta1 : 24.850 MHz : 0.757 dB T1 : 5171.032 MHz : 2.822 dBm T2 : 5189.168 MHz : 0.516 dBm OBW : 18.136 MHz	Measured 26 dB Bandwidth: 24.850 MHz Measured 99% Bandwidth: 18.136 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5188.327 MHz : -14.792 dBm M2 : 5206.263 MHz : 11.712 dBm Delta1 : 24.148 MHz : 0.866 dB T1 : 5191.032 MHz : 3.741 dBm T2 : 5209.168 MHz : 1.885 dBm OBW : 18.136 MHz	Measured 26 dB Bandwidth: 24.148 MHz Measured 99% Bandwidth: 18.136 MHz

[Back to Matrix](#)



26 dB & 99% BANDWIDTH


Variant: 802.11n HT-20, Channel: 5200.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5187.725 MHz : -15.654 dBm M2 : 5207.565 MHz : 10.799 dBm Delta1 : 24.749 MHz : 0.551 dB T1 : 5191.032 MHz : 2.637 dBm T2 : 5209.168 MHz : 0.500 dBm OBW : 18.136 MHz	Measured 26 dB Bandwidth: 24.749 MHz Measured 99% Bandwidth: 18.136 MHz


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5188.527 MHz : -15.128 dBm M2 : 5205.060 MHz : 11.089 dBm Delta1 : 23.347 MHz : 0.401 dB T1 : 5191.032 MHz : 2.599 dBm T2 : 5209.068 MHz : 1.877 dBm OBW : 18.036 MHz	Measured 26 dB Bandwidth: 23.347 MHz Measured 99% Bandwidth: 18.036 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5187.725 MHz : -14.625 dBm M2 : 5205.060 MHz : 11.964 dBm Delta1 : 25.050 MHz : 0.911 dB T1 : 0 Hz : 0.000 dBm T2 : 0 Hz : 0.000 dBm OBW : 18.136 MHz	Measured 26 dB Bandwidth: 25.050 MHz Measured 99% Bandwidth: 18.136 MHz

[Back to Matrix](#)



26 dB & 99% BANDWIDTH


Variant: 802.11n HT-20, Channel: 5240.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5228.427 MHz : -14.015 dBm M2 : 5246.263 MHz : 12.055 dBm Delta1 : 23.447 MHz : 0.364 dB T1 : 5231.032 MHz : 4.049 dBm T2 : 5249.068 MHz : 3.078 dBm OBW : 18.036 MHz	Measured 26 dB Bandwidth: 23.447 MHz Measured 99% Bandwidth: 18.036 MHz


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5228.327 MHz : -15.416 dBm M2 : 5247.565 MHz : 10.845 dBm Delta1 : 23.347 MHz : 0.175 dB T1 : 5231.032 MHz : 2.942 dBm T2 : 5249.068 MHz : 2.918 dBm OBW : 18.036 MHz	Measured 26 dB Bandwidth: 23.347 MHz Measured 99% Bandwidth: 18.036 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5228.527 MHz : -14.579 dBm M2 : 5245.060 MHz : 11.661 dBm Delta1 : 23.246 MHz : -0.155 dB T1 : 5231.032 MHz : 3.221 dBm T2 : 5249.068 MHz : 2.415 dBm OBW : 18.036 MHz	Measured 26 dB Bandwidth: 23.246 MHz Measured 99% Bandwidth: 18.036 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5228.527 MHz : -14.044 dBm M2 : 5245.060 MHz : 11.960 dBm Delta1 : 23.146 MHz : 0.165 dB T1 : 5231.032 MHz : 3.438 dBm T2 : 5249.068 MHz : 3.902 dBm OBW : 18.036 MHz	Measured 26 dB Bandwidth: 23.146 MHz Measured 99% Bandwidth: 18.036 MHz

[Back to Matrix](#)



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5160.040 MHz : -12.974 dBm M2 : 5181.683 MHz : 13.463 dBm Delta1 : 60.922 MHz : -0.301 dB T1 : 5171.463 MHz : 5.065 dBm T2 : 5208.737 MHz : 4.598 dBm OBW : 37.275 MHz	Measured 26 dB Bandwidth: 60.922 MHz Measured 99% Bandwidth: 37.275 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5157.234 MHz : -14.361 dBm M2 : 5187.495 MHz : 12.609 dBm Delta1 : 67.134 MHz : 1.210 dB T1 : 5171.263 MHz : 2.989 dBm T2 : 5208.537 MHz : 4.128 dBm OBW : 37.275 MHz	Measured 26 dB Bandwidth: 67.134 MHz Measured 99% Bandwidth: 37.275 MHz

[Back to Matrix](#)

26 dB & 99% BANDWIDTH




Variant: 802.11n HT-40, Channel: 5190.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5168.257 MHz : -14.267 dBm M2 : 5181.683 MHz : 12.489 dBm Delta1 : 46.293 MHz : 1.769 dB T1 : 5171.663 MHz : 5.767 dBm T2 : 5208.537 MHz : 5.716 dBm OBW : 36.874 MHz	Measured 26 dB Bandwidth: 46.293 MHz Measured 99% Bandwidth: 36.874 MHz


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5162.445 MHz : -12.703 dBm M2 : 5205.331 MHz : 13.780 dBm Delta1 : 61.924 MHz : 0.321 dB T1 : 5171.463 MHz : 5.362 dBm T2 : 5208.737 MHz : 4.470 dBm OBW : 37.275 MHz	Measured 26 dB Bandwidth: 61.924 MHz Measured 99% Bandwidth: 37.275 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5206.052 MHz : -12.362 dBm M2 : 5221.683 MHz : 14.124 dBm Delta1 : 53.707 MHz : 0.614 dB T1 : 5211.663 MHz : 7.614 dBm T2 : 5248.737 MHz : 5.615 dBm OBW : 37.074 MHz	Measured 26 dB Bandwidth: 53.707 MHz Measured 99% Bandwidth: 37.074 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5202.445 MHz : -13.194 dBm M2 : 5227.495 MHz : 13.331 dBm Delta1 : 57.315 MHz : 1.436 dB T1 : 5211.463 MHz : 5.230 dBm T2 : 5248.537 MHz : 5.149 dBm OBW : 37.074 MHz	Measured 26 dB Bandwidth: 57.315 MHz Measured 99% Bandwidth: 37.074 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5208.457 MHz : -12.301 dBm M2 : 5246.333 MHz : 13.705 dBm Delta1 : 46.293 MHz : 0.984 dB T1 : 5211.663 MHz : 6.430 dBm T2 : 5248.537 MHz : 6.924 dBm OBW : 36.874 MHz	Measured 26 dB Bandwidth: 46.293 MHz Measured 99% Bandwidth: 36.874 MHz

[Back to Matrix](#)



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5202.645 MHz : -11.687 dBm M2 : 5245.331 MHz : 14.878 dBm Delta1 : 57.114 MHz : 0.950 dB T1 : 5211.663 MHz : 7.819 dBm T2 : 5248.537 MHz : 6.768 dBm OBW : 36.874 MHz	Measured 26 dB Bandwidth: 57.114 MHz Measured 99% Bandwidth: 36.874 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5813.727 MHz : -12.941 dBm M2 : 5829.158 MHz : 14.020 dBm Delta1 : 22.345 MHz : 1.397 dB T1 : 5816.633 MHz : 6.471 dBm T2 : 5833.367 MHz : 5.676 dBm OBW : 16.733 MHz	Measured 26 dB Bandwidth: 22.345 MHz Measured 99% Bandwidth: 16.733 MHz

[Back to Matrix](#)



26 dB & 99% BANDWIDTH

Variant: 802.11ac-80, Channel: 5775.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5733.517 MHz : -10.924 dBm M2 : 5809.669 MHz : 16.351 dBm Delta1 : 82.565 MHz : 3.899 dB T1 : 5737.525 MHz : 10.764 dBm T2 : 5813.277 MHz : 10.054 dBm OBW : 75.752 MHz	Measured 26 dB Bandwidth: 82.565 MHz Measured 99% Bandwidth: 75.752 MHz


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



26 dB & 99% BANDWIDTH


Variant: 802.11ac-80, Channel: 5775.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5733.517 MHz : -11.418 dBm M2 : 5808.868 MHz : 15.722 dBm Delta1 : 82.966 MHz : 2.093 dB T1 : 5737.525 MHz : 10.762 dBm T2 : 5813.277 MHz : 9.507 dBm OBW : 75.752 MHz	Measured 26 dB Bandwidth: 82.966 MHz Measured 99% Bandwidth: 75.752 MHz

[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5733.116 MHz : -11.085 dBm M2 : 5740.731 MHz : 15.814 dBm Delta1 : 82.966 MHz : 3.598 dB T1 : 5737.124 MHz : 10.644 dBm T2 : 5812.876 MHz : 11.299 dBm OBW : 75.752 MHz	Measured 26 dB Bandwidth: 82.966 MHz Measured 99% Bandwidth: 75.752 MHz

[Back to Matrix](#)



26 dB & 99% BANDWIDTH


Variant: 802.11ac-80, Channel: 5775.00 MHz, Chain d, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5733.517 MHz : -9.935 dBm M2 : 5792.836 MHz : 16.469 dBm Delta1 : 82.164 MHz : 3.811 dB T1 : 5737.124 MHz : 10.524 dBm T2 : 5812.876 MHz : 12.021 dBm OBW : 75.752 MHz	Measured 26 dB Bandwidth: 82.164 MHz Measured 99% Bandwidth: 75.752 MHz


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5733.226 MHz : -12.390 dBm M2 : 5752.465 MHz : 14.075 dBm Delta1 : 23.747 MHz : 0.921 dB T1 : 5736.032 MHz : 6.170 dBm T2 : 5754.068 MHz : 5.214 dBm OBW : 18.036 MHz	Measured 26 dB Bandwidth: 23.747 MHz Measured 99% Bandwidth: 18.036 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5733.327 MHz : -12.567 dBm M2 : 5738.737 MHz : 13.514 dBm Delta1 : 23.848 MHz : 0.610 dB T1 : 5736.032 MHz : 5.932 dBm T2 : 5754.168 MHz : 4.010 dBm OBW : 18.136 MHz	Measured 26 dB Bandwidth: 23.848 MHz Measured 99% Bandwidth: 18.136 MHz

[Back to Matrix](#)



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5733.226 MHz : -12.093 dBm M2 : 5749.960 MHz : 14.040 dBm Delta1 : 23.647 MHz : 1.035 dB T1 : 5735.932 MHz : 5.108 dBm T2 : 5754.068 MHz : 5.246 dBm OBW : 18.136 MHz	Measured 26 dB Bandwidth: 23.647 MHz Measured 99% Bandwidth: 18.136 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5733.226 MHz : -12.935 dBm M2 : 5737.435 MHz : 13.634 dBm Delta1 : 24.048 MHz : 1.094 dB T1 : 5736.032 MHz : 6.631 dBm T2 : 5754.168 MHz : 4.527 dBm OBW : 18.136 MHz	Measured 26 dB Bandwidth: 24.048 MHz Measured 99% Bandwidth: 18.136 MHz

[Back to Matrix](#)

26 dB & 99% BANDWIDTH




Variant: 802.11n HT-20, Channel: 5785.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5773.226 MHz : -12.144 dBm M2 : 5792.465 MHz : 14.087 dBm Delta1 : 23.747 MHz : 1.308 dB T1 : 5776.032 MHz : 6.261 dBm T2 : 5794.068 MHz : 5.694 dBm OBW : 18.036 MHz	Measured 26 dB Bandwidth: 23.747 MHz Measured 99% Bandwidth: 18.036 MHz


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5773.327 MHz : -13.466 dBm M2 : 5792.565 MHz : 12.952 dBm Delta1 : 23.848 MHz : 0.281 dB T1 : 5776.032 MHz : 5.275 dBm T2 : 5794.168 MHz : 3.314 dBm OBW : 18.136 MHz	Measured 26 dB Bandwidth: 23.848 MHz Measured 99% Bandwidth: 18.136 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5773.226 MHz : -12.636 dBm M2 : 5789.960 MHz : 13.546 dBm Delta1 : 23.647 MHz : 1.047 dB T1 : 5776.032 MHz : 6.178 dBm T2 : 5794.068 MHz : 4.775 dBm OBW : 18.036 MHz	Measured 26 dB Bandwidth: 23.647 MHz Measured 99% Bandwidth: 18.036 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5773.226 MHz : -13.228 dBm M2 : 5789.960 MHz : 14.099 dBm Delta1 : 23.848 MHz : 1.755 dB T1 : 5776.032 MHz : 6.064 dBm T2 : 5794.168 MHz : 3.979 dBm OBW : 18.136 MHz	Measured 26 dB Bandwidth: 23.848 MHz Measured 99% Bandwidth: 18.136 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5812.926 MHz : -13.165 dBm M2 : 5829.158 MHz : 13.259 dBm Delta1 : 24.048 MHz : 0.045 dB T1 : 5816.032 MHz : 6.367 dBm T2 : 5834.068 MHz : 4.891 dBm OBW : 18.036 MHz	Measured 26 dB Bandwidth: 24.048 MHz Measured 99% Bandwidth: 18.036 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5813.427 MHz : -14.121 dBm M2 : 5818.737 MHz : 11.915 dBm Delta1 : 23.447 MHz : 0.702 dB T1 : 5816.032 MHz : 4.352 dBm T2 : 5834.168 MHz : 2.336 dBm OBW : 18.136 MHz	Measured 26 dB Bandwidth: 23.447 MHz Measured 99% Bandwidth: 18.136 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5813.327 MHz : -12.648 dBm M2 : 5829.960 MHz : 13.540 dBm Delta1 : 23.246 MHz : 1.434 dB T1 : 5815.932 MHz : 4.632 dBm T2 : 5834.068 MHz : 4.083 dBm OBW : 18.136 MHz	Measured 26 dB Bandwidth: 23.246 MHz Measured 99% Bandwidth: 18.136 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5813.226 MHz : -12.470 dBm M2 : 5830.060 MHz : 13.835 dBm Delta1 : 23.547 MHz : 2.164 dB T1 : 5816.032 MHz : 5.716 dBm T2 : 5834.068 MHz : 5.735 dBm OBW : 18.036 MHz	Measured 26 dB Bandwidth: 23.547 MHz Measured 99% Bandwidth: 18.036 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5733.457 MHz : -10.877 dBm M2 : 5759.309 MHz : 15.135 dBm Delta1 : 43.086 MHz : 1.470 dB T1 : 5736.663 MHz : 7.833 dBm T2 : 5773.537 MHz : 8.669 dBm OBW : 36.874 MHz	Measured 26 dB Bandwidth: 43.086 MHz Measured 99% Bandwidth: 36.874 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5733.657 MHz : -11.524 dBm M2 : 5771.132 MHz : 14.567 dBm Delta1 : 42.685 MHz : 1.961 dB T1 : 5736.663 MHz : 7.093 dBm T2 : 5773.337 MHz : 9.344 dBm OBW : 36.673 MHz	Measured 26 dB Bandwidth: 42.685 MHz Measured 99% Bandwidth: 36.673 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5733.257 MHz : -11.274 dBm M2 : 5746.683 MHz : 15.069 dBm Delta1 : 43.086 MHz : 1.523 dB T1 : 5736.663 MHz : 7.675 dBm T2 : 5773.537 MHz : 8.100 dBm OBW : 36.874 MHz	Measured 26 dB Bandwidth: 43.086 MHz Measured 99% Bandwidth: 36.874 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5733.457 MHz : -10.700 dBm M2 : 5770.331 MHz : 15.456 dBm Delta1 : 42.886 MHz : 2.115 dB T1 : 5736.663 MHz : 8.342 dBm T2 : 5773.337 MHz : 9.851 dBm OBW : 36.673 MHz	Measured 26 dB Bandwidth: 42.886 MHz Measured 99% Bandwidth: 36.673 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5773.457 MHz : -11.882 dBm M2 : 5799.309 MHz : 14.714 dBm Delta1 : 43.086 MHz : 1.672 dB T1 : 5776.663 MHz : 7.136 dBm T2 : 5813.537 MHz : 7.894 dBm OBW : 36.874 MHz	Measured 26 dB Bandwidth: 43.086 MHz Measured 99% Bandwidth: 36.874 MHz

[Back to Matrix](#)




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5773.457 MHz : -12.821 dBm M2 : 5811.132 MHz : 14.221 dBm Delta1 : 42.886 MHz : 2.939 dB T1 : 5776.663 MHz : 6.865 dBm T2 : 5813.337 MHz : 8.848 dBm OBW : 36.673 MHz	Measured 26 dB Bandwidth: 42.886 MHz Measured 99% Bandwidth: 36.673 MHz

[Back to Matrix](#)



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5773.457 MHz : -11.434 dBm M2 : 5786.683 MHz : 14.657 dBm Delta1 : 42.886 MHz : 1.615 dB T1 : 5776.663 MHz : 7.724 dBm T2 : 5813.337 MHz : 10.028 dBm OBW : 36.673 MHz	Measured 26 dB Bandwidth: 42.886 MHz Measured 99% Bandwidth: 36.673 MHz

[Back to Matrix](#)



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5773.457 MHz : -11.634 dBm M2 : 5792.495 MHz : 15.063 dBm Delta1 : 42.886 MHz : 2.534 dB T1 : 5776.663 MHz : 7.917 dBm T2 : 5813.337 MHz : 9.554 dBm OBW : 36.673 MHz	Measured 26 dB Bandwidth: 42.886 MHz Measured 99% Bandwidth: 36.673 MHz


[Back to Matrix](#)

A.1.2. Peak Power Spectral Density



PEAK POWER SPECTRAL DENSITY

Variant: 802.11a, Channel: 5180.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5184.359 MHz : 9.901 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



PEAK POWER SPECTRAL DENSITY

Variant: 802.11a, Channel: 5180.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5173.637 MHz : 9.340 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11a, Channel: 5180.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5186.263 MHz : 9.229 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11a, Channel: 5180.00 MHz, Chain d, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5177.445 MHz : 9.324 dBm	Limit: ≤ 10.980 dBm

[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY

Variant: 802.11a, Channel: 5180.00 MHz, SUM, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5174 MHz : 14.432 dBm Duty Cycle Correction Factor : +0.04 dB	Limit: ≤ 14.7 dBm Margin: -0.268 dB

[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



PEAK POWER SPECTRAL DENSITY

Variant: 802.11a, Channel: 5200.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5205.862 MHz : 10.604 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11a, Channel: 5200.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5206.663 MHz : 9.445 dBm	Channel Frequency: 5200.00 MHz


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11a, Channel: 5200.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5206.864 MHz : 9.934 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11a, Channel: 5200.00 MHz, Chain d, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5206.864 MHz : 10.649 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



PEAK POWER SPECTRAL DENSITY

Variant: 802.11a, Channel: 5200.00 MHz, SUM, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5207 MHz : 14.623 dBm Duty Cycle Correction Factor : +0.04 dB	Limit: ≤ 14.7 dBm Margin: -0.077 dB


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



PEAK POWER SPECTRAL DENSITY

Variant: 802.11a, Channel: 5240.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5246.663 MHz : 11.205 dBm	Limit: ≤ 10.980 dBm

[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY

Variant: 802.11a, Channel: 5240.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5246.663 MHz : 10.205 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11a, Channel: 5240.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5246.563 MHz : 10.448 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



PEAK POWER SPECTRAL DENSITY

Variant: 802.11a, Channel: 5240.00 MHz, Chain d, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5247.265 MHz : 11.037 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



PEAK POWER SPECTRAL DENSITY

Variant: 802.11a, Channel: 5240.00 MHz, SUM, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5247 MHz : 14.468 dBm Duty Cycle Correction Factor : +0.04 dB	Limit: ≤ 14.7 dBm Margin: -0.232 dB


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



PEAK POWER SPECTRAL DENSITY

Variant: 802.11ac-80, Channel: 5210.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5177.335 MHz : 5.380 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



PEAK POWER SPECTRAL DENSITY

Variant: 802.11ac-80, Channel: 5210.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5174.930 MHz : 4.143 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



PEAK POWER SPECTRAL DENSITY

Variant: 802.11ac-80, Channel: 5210.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5243.066 MHz : 4.862 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



PEAK POWER SPECTRAL DENSITY

Variant: 802.11ac-80, Channel: 5210.00 MHz, Chain d, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5243.868 MHz : 5.608 dBm	Limit: ≤ 10.980 dBm

[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY

Variant: 802.11ac-80, Channel: 5210.00 MHz, SUM, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5175 MHz : 10.237 dBm Duty Cycle Correction Factor : +0.13 dB	Limit: ≤ 14.7 dBm Margin: -4.5 dB


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



PEAK POWER SPECTRAL DENSITY

Variant: 802.11n HT-20, Channel: 5180.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5173.337 MHz : 9.598 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



PEAK POWER SPECTRAL DENSITY

Variant: 802.11n HT-20, Channel: 5180.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5172.735 MHz : 8.960 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11n HT-20, Channel: 5180.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5173.437 MHz : 8.986 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



PEAK POWER SPECTRAL DENSITY

Variant: 802.11n HT-20, Channel: 5180.00 MHz, Chain d, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5173.236 MHz : 9.526 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



PEAK POWER SPECTRAL DENSITY

Variant: 802.11n HT-20, Channel: 5180.00 MHz, SUM, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5173 MHz : 14.551 dBm Duty Cycle Correction Factor : +0.04 dB	Limit: ≤ 14.7 dBm Margin: -0.1 dB


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11n HT-20, Channel: 5200.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5204.359 MHz : 10.299 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11n HT-20, Channel: 5200.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5204.760 MHz : 9.254 dBm	Channel Frequency: 5200.00 MHz


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11n HT-20, Channel: 5200.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5206.864 MHz : 9.509 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11n HT-20, Channel: 5200.00 MHz, Chain d, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5207.064 MHz : 10.426 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



PEAK POWER SPECTRAL DENSITY

Variant: 802.11n HT-20, Channel: 5200.00 MHz, SUM, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5204 MHz : 14.423 dBm Duty Cycle Correction Factor : +0.04 dB	Limit: ≤ 14.7 dBm Margin: -0.3 dB


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11n HT-20, Channel: 5240.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5246.663 MHz : 10.758 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



PEAK POWER SPECTRAL DENSITY

Variant: 802.11n HT-20, Channel: 5240.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5233.537 MHz : 9.614 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11n HT-20, Channel: 5240.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5244.559 MHz : 10.148 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



PEAK POWER SPECTRAL DENSITY

Variant: 802.11n HT-20, Channel: 5240.00 MHz, Chain d, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5247.465 MHz : 10.474 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



PEAK POWER SPECTRAL DENSITY

Variant: 802.11n HT-20, Channel: 5240.00 MHz, SUM, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5245 MHz : 14.601 dBm Duty Cycle Correction Factor : +0.04 dB	Limit: ≤ 17.0 dBm Margin: -0.1 dB


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11n HT-40, Channel: 5190.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5182.285 MHz : 7.612 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



PEAK POWER SPECTRAL DENSITY

Variant: 802.11n HT-40, Channel: 5190.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5182.685 MHz : 6.101 dBm	Limit: ≤ 10.980 dBm

[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY

Variant: 802.11n HT-40, Channel: 5190.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5192.906 MHz : 6.666 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



PEAK POWER SPECTRAL DENSITY

Variant: 802.11n HT-40, Channel: 5190.00 MHz, Chain d, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5206.333 MHz : 7.948 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



PEAK POWER SPECTRAL DENSITY

Variant: 802.11n HT-40, Channel: 5190.00 MHz, SUM, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5207 MHz : 12.694 dBm Duty Cycle Correction Factor : +0.09 dB	Limit: ≤ 14.7 dBm Margin: -2.0 dB


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11n HT-40, Channel: 5230.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5245.932 MHz : 8.638 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



PEAK POWER SPECTRAL DENSITY

Variant: 802.11n HT-40, Channel: 5230.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5227.094 MHz : 6.630 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11n HT-40, Channel: 5230.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5246.132 MHz : 8.105 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11n HT-40, Channel: 5230.00 MHz, Chain d, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5234.309 MHz : 9.060 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



PEAK POWER SPECTRAL DENSITY

Variant: 802.11n HT-40, Channel: 5230.00 MHz, SUM, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5243 MHz : 13.878 dBm Duty Cycle Correction Factor : +0.09 dB	Limit: ≤ 14.7 dBm Margin: -0.91 dB


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11a, Channel: 5745.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5752.265 MHz : 10.318 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



PEAK POWER SPECTRAL DENSITY

Variant: 802.11a, Channel: 5745.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5751.764 MHz : 9.680 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11a, Channel: 5745.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5744.248 MHz : 10.703 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11a, Channel: 5745.00 MHz, Chain d, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5752.064 MHz : 11.133 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



PEAK POWER SPECTRAL DENSITY

Variant: 802.11a, Channel: 5745.00 MHz, SUM, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5751 MHz : 15.322 dBm Duty Cycle Correction Factor : +0.04 dB	Limit: ≤ 15.5 dBm Margin: -0.2 dB


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



PEAK POWER SPECTRAL DENSITY

Variant: 802.11a, Channel: 5785.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5792.465 MHz : 10.586 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11a, Channel: 5785.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5791.263 MHz : 9.240 dBm	Channel Frequency: 5785.00 MHz


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11a, Channel: 5785.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5784.248 MHz : 10.352 dBm	Limit: ≤ 10.980 dBm

[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY

Variant: 802.11a, Channel: 5785.00 MHz, Chain d, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5792.365 MHz : 10.544 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



PEAK POWER SPECTRAL DENSITY

Variant: 802.11a, Channel: 5785.00 MHz, SUM, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5793 MHz : 15.235 dBm Duty Cycle Correction Factor : +0.04 dB	Limit: ≤ 15.5 dBm Margin: -0.3 dB


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11a, Channel: 5825.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5831.764 MHz : 9.757 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11a, Channel: 5825.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5818.136 MHz : 8.262 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variants: 802.11a, Channel: 5825.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5824.248 MHz : 9.511 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11a, Channel: 5825.00 MHz, Chain d, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5817.836 MHz : 9.688 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



PEAK POWER SPECTRAL DENSITY

Variant: 802.11a, Channel: 5825.00 MHz, SUM, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5827 MHz : 15.128 dBm Duty Cycle Correction Factor : +0.04 dB	Limit: ≤ 15.5 dBm Margin: -0.4 dB


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11ac-80, Channel: 5775.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5806.864 MHz : 4.443 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11ac-80, Channel: 5775.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5808.868 MHz : 3.870 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



PEAK POWER SPECTRAL DENSITY

Variant: 802.11ac-80, Channel: 5775.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5809.669 MHz : 3.071 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



PEAK POWER SPECTRAL DENSITY

Variant: 802.11ac-80, Channel: 5775.00 MHz, Chain d, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5790.431 MHz : 3.928 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



PEAK POWER SPECTRAL DENSITY

Variant: 802.11ac-80, Channel: 5775.00 MHz, SUM, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5809 MHz : 9.672 dBm Duty Cycle Correction Factor : +0.13 dB	Limit: ≤ 15.5 dBm Margin: -5.8 dB


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11n HT-20, Channel: 5745.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5751.764 MHz : 9.622 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11n HT-20, Channel: 5745.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5752.565 MHz : 9.337 dBm	Limit: ≤ 10.980 dBm

[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY

Variant: 802.11n HT-20, Channel: 5745.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5752.064 MHz : 9.980 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11n HT-20, Channel: 5745.00 MHz, Chain d, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5752.465 MHz : 10.384 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



PEAK POWER SPECTRAL DENSITY

Variant: 802.11n HT-20, Channel: 5745.00 MHz, SUM, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5753 MHz : 15.445 dBm Duty Cycle Correction Factor : +0.04 dB	Limit: ≤ 15.5 dBm Margin: -0.1 dB


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11n HT-20, Channel: 5785.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5792.966 MHz : 9.897 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11n HT-20, Channel: 5785.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5792.265 MHz : 9.298 dBm	Channel Frequency: 5785.00 MHz


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11n HT-20, Channel: 5785.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5792.164 MHz : 9.424 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11n HT-20, Channel: 5785.00 MHz, Chain d, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5792.064 MHz : 9.950 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



PEAK POWER SPECTRAL DENSITY

Variant: 802.11n HT-20, Channel: 5785.00 MHz, SUM, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5792 MHz : 15.490 dBm Duty Cycle Correction Factor : +0.04 dB	Limit: ≤ 15.5 dBm Margin: -0.0 dB


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11n HT-20, Channel: 5825.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5832.766 MHz : 9.545 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11n HT-20, Channel: 5825.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5828.457 MHz : 8.246 dBm	Limit: ≤ 10.980 dBm

[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY

Variant: 802.11n HT-20, Channel: 5825.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5818.236 MHz : 9.089 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



PEAK POWER SPECTRAL DENSITY

Variant: 802.11n HT-20, Channel: 5825.00 MHz, Chain d, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5818.236 MHz : 9.698 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



PEAK POWER SPECTRAL DENSITY

Variant: 802.11n HT-20, Channel: 5825.00 MHz, SUM, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5818 MHz : 14.945 dBm Duty Cycle Correction Factor : +0.04 dB	Limit: ≤ 15.5 dBm Margin: -0.6 dB


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11n HT-40, Channel: 5755.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5764.118 MHz : 6.618 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11n HT-40, Channel: 5755.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5766.122 MHz : 5.500 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11n HT-40, Channel: 5755.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5760.311 MHz : 6.057 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11n HT-40, Channel: 5755.00 MHz, Chain d, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5758.707 MHz : 6.775 dBm	Limit: ≤ 10.980 dBm

[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY

Variant: 802.11n HT-40, Channel: 5755.00 MHz, SUM, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5767 MHz : 11.890 dBm Duty Cycle Correction Factor : +0.09 dB	Limit: ≤ 17.0 dBm Margin: -3.6 dB


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11n HT-40, Channel: 5795.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5793.096 MHz : 5.870 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



PEAK POWER SPECTRAL DENSITY

Variant: 802.11n HT-40, Channel: 5795.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5796.904 MHz : 5.261 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



PEAK POWER SPECTRAL DENSITY

Variant: 802.11n HT-40, Channel: 5795.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5801.713 MHz : 5.796 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

PEAK POWER SPECTRAL DENSITY



Variant: 802.11n HT-40, Channel: 5795.00 MHz, Chain d, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5792.295 MHz : 6.162 dBm	Limit: ≤ 10.980 dBm


[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



PEAK POWER SPECTRAL DENSITY

Variant: 802.11n HT-40, Channel: 5795.00 MHz, SUM, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker:Frequency:Amplitude	Test Results
Detector = RMS Sweep Count = 100 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5811 MHz : 11.667 dBm Duty Cycle Correction Factor : +0.09 dB	Limit: ≤ 15.5 dBm Margin: -3.8 dB

[Back to Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



575 Boulder Court
Pleasanton, California 94566, USA
Tel: 1.925.462.0304
Fax: 1.925.462.0306
www.micomlabs.com