


Site: WZ-AC2	Time: 2021/04/15 - 00:02
Limit: FCC_Part15.209_RE(3m)	Engineer: Buter Shi
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: WiFi 6 Extender	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE20 at Channel 2412MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2390.000	61.548	29.197	-12.452	74.000	32.351	PK
2		*	2412.368	109.715	77.369	N/A	N/A	32.346	PK

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: WZ-AC2	Time: 2021/04/15 - 00:03
Limit: FCC_Part15.209_RE(3m)	Engineer: Buter Shi
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: WiFi 6 Extender	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE20 at Channel 2412MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2390.000	50.029	17.678	-3.971	54.000	32.351	AV
2		*	2412.256	96.572	64.226	N/A	N/A	32.346	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: WZ-AC2	Time: 2021/04/15 - 00:03
Limit: FCC_Part15.209_RE(3m)	Engineer: Buter Shi
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: WiFi 6 Extender	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE20 at Channel 2412MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2389.016	69.995	37.641	-4.005	74.000	32.354	PK
2			2390.000	69.076	36.725	-4.924	74.000	32.351	PK
3		*	2410.408	118.206	85.862	N/A	N/A	32.345	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: WZ-AC2	Time: 2021/04/15 - 00:06
Limit: FCC_Part15_Band Edge(3m)	Engineer: Buter Shi
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: WiFi 6 Extender	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE20 at Channel 2412MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2389.240	53.387	21.034	-0.613	54.000	32.353	AV
2			2390.000	53.499	21.148	-0.501	54.000	32.351	AV
3		*	2409.400	104.730	72.386	N/A	N/A	32.344	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: WZ-AC2	Time: 2021/04/15 - 00:11
Limit: FCC_Part15.209_RE(3m)	Engineer: Buter Shi
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: WiFi 6 Extender	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE20 at Channel 2462MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2463.616	109.627	77.307	N/A	N/A	32.320	PK
2			2483.500	61.762	29.455	-12.238	74.000	32.307	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: WZ-AC2	Time: 2021/04/15 - 00:13
Limit: FCC_Part15.209_RE(3m)	Engineer: Buter Shi
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: WiFi 6 Extender	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE20 at Channel 2462MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2461.192	96.637	64.318	N/A	N/A	32.318	AV
2			2483.500	50.213	17.906	-3.787	54.000	32.307	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: WZ-AC2	Time: 2021/04/15 - 00:13
Limit: FCC_Part15.209_RE(3m)	Engineer: Buter Shi
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: WiFi 6 Extender	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE20 at Channel 2462MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2460.520	119.170	86.851	N/A	N/A	32.319	PK
2			2483.500	73.438	41.131	-0.562	74.000	32.307	PK
3			2483.512	73.781	41.474	-0.219	74.000	32.306	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: WZ-AC2	Time: 2021/04/15 - 00:16
Limit: FCC_Part15.209_RE(3m)	Engineer: Buter Shi
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: WiFi 6 Extender	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE20 at Channel 2462MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2460.808	105.935	73.616	N/A	N/A	32.319	AV
2			2483.500	53.759	21.452	-0.241	54.000	32.307	AV
3			2483.536	53.789	21.482	-0.211	54.000	32.306	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: WZ-AC2	Time: 2021/04/17 - 11:24
Limit: FCC_Part15.209_RE(3m)	Engineer: Buter Shi
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: WiFi 6 Extender	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE40 at Channel 2422MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2371.380	63.768	31.354	-10.232	74.000	32.414	PK
2			2390.000	62.267	29.916	-11.733	74.000	32.351	PK
3		*	2420.880	102.400	70.057	N/A	N/A	32.343	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: WZ-AC2	Time: 2021/04/17 - 11:27
Limit: FCC_Part15.209_RE(3m)	Engineer: Buter Shi
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: WiFi 6 Extender	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE40 at Channel 2422MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2390.000	51.527	19.176	-2.473	54.000	32.351	AV
2		*	2420.880	93.265	60.922	N/A	N/A	32.343	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: WZ-AC2	Time: 2021/04/17 - 11:22
Limit: FCC_Part15.209_RE(3m)	Engineer: Buter Shi
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: WiFi 6 Extender	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE40 at Channel 2422MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2386.164	69.751	37.389	-4.249	74.000	32.361	PK
2			2390.000	67.846	35.495	-6.154	74.000	32.351	PK
3		*	2425.236	114.734	82.395	N/A	N/A	32.340	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: WZ-AC2	Time: 2021/04/17 - 11:14
Limit: FCC_Part15_Band Edge(3m)	Engineer: Buter Shi
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: WiFi 6 Extender	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE40 at Channel 2422MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2388.144	53.617	21.261	-0.383	54.000	32.356	AV
2			2389.662	53.907	21.555	-0.093	54.000	32.352	AV
3			2390.000	53.648	21.297	-0.352	54.000	32.351	AV
4		*	2420.484	103.268	70.924	N/A	N/A	32.344	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: WZ-AC2	Time: 2021/04/17 - 11:37
Limit: FCC_Part15.209_RE(3m)	Engineer: Buter Shi
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: WiFi 6 Extender	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE40 at Channel 2452MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2449.714	102.942	70.620	N/A	N/A	32.322	PK
2			2483.500	61.714	29.407	-12.286	74.000	32.307	PK
3			2489.290	63.175	30.872	-10.825	74.000	32.303	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: WZ-AC2	Time: 2021/04/17 - 11:39
Limit: FCC_Part15.209_RE(3m)	Engineer: Buter Shi
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: WiFi 6 Extender	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE40 at Channel 2452MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2449.816	91.974	59.652	N/A	N/A	32.322	AV
2			2483.500	51.358	19.051	-2.642	54.000	32.307	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: WZ-AC2	Time: 2021/04/17 - 11:36
Limit: FCC_Part15.209_RE(3m)	Engineer: Buter Shi
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: WiFi 6 Extender	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE40 at Channel 2452MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2449.714	113.777	81.455	N/A	N/A	32.322	PK
2			2483.500	63.060	30.753	-10.940	74.000	32.307	PK
3			2488.236	68.356	36.055	-5.644	74.000	32.301	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: WZ-AC2	Time: 2021/04/17 - 11:34
Limit: FCC_Part15.209_RE(3m)	Engineer: Buter Shi
Probe: WZ-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: WiFi 6 Extender	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11ax-HE40 at Channel 2452MHz	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2450.802	102.234	69.913	N/A	N/A	32.321	AV
2			2483.500	53.309	21.002	-0.691	54.000	32.307	AV
3			2483.748	53.949	21.643	-0.051	54.000	32.306	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

5.8. AC Conducted Emissions Measurement


5.8.1. Test Limit

FCC Part 15 Subpart C Paragraph 15.207 Limits		
Frequency (MHz)	QP (dBuV)	AV (dBuV)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.


Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.

5.8.2. Test Setup



5.8.3.Test Result

Site: WZ-SR2	Time: 2021/06/08 - 09:26
Limit: FCC_Part15.207_CE_AC Power	Engineer: Hyde Yu
Probe: ENV216_101683_Filter Off_With Adapter	Polarity: Line
EUT: WiFi 6 Extender	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11b at Channel 2412MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV)	Factor (dB)	Type
1			0.190	35.721	26.083	-28.315	64.037	9.638	QP
2			0.190	21.632	11.994	-32.404	54.037	9.638	AV
3			0.346	41.110	31.456	-17.948	59.058	9.654	QP
4		*	0.346	34.423	24.768	-14.635	49.058	9.654	AV
5			0.418	25.025	15.363	-32.463	57.488	9.662	QP
6			0.418	10.969	1.307	-36.519	47.488	9.662	AV
7			0.862	23.746	14.051	-32.254	56.000	9.694	QP
8			0.862	11.272	1.577	-34.728	46.000	9.694	AV
9			1.210	24.762	15.060	-31.238	56.000	9.702	QP
10			1.210	11.799	2.097	-34.201	46.000	9.702	AV
11			4.022	35.566	25.499	-20.434	56.000	10.067	QP
12			4.022	25.858	15.791	-20.142	46.000	10.067	AV

Note: Measure Level (dBμV) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + LISN Factor (dB)

Site: WZ-SR2	Time: 2021/06/08 - 09:38
Limit: FCC_Part15.207_CE_AC Power	Engineer: Hyde Yu
Probe: ENV216_101683_Filter Off_With Adapter	Polarity: Neutral
EUT: WiFi 6 Extender	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11b at Channel 2412MHz	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV)	Factor (dB)	Type
1			0.150	37.323	27.693	-28.677	66.000	9.630	QP
2			0.150	15.417	5.787	-40.583	56.000	9.630	AV
3			0.342	38.439	28.781	-20.715	59.155	9.658	QP
4		*	0.342	30.433	20.775	-18.721	49.155	9.658	AV
5			1.070	29.467	19.757	-26.533	56.000	9.710	QP
6			1.070	22.803	13.093	-23.197	46.000	9.710	AV
7			1.186	28.475	18.765	-27.525	56.000	9.710	QP
8			1.186	19.351	9.641	-26.649	46.000	9.710	AV
9			3.742	32.283	22.259	-23.717	56.000	10.023	QP
10			3.742	20.520	10.496	-25.480	46.000	10.023	AV
11			16.926	18.851	8.270	-41.149	60.000	10.581	QP
12			16.926	11.498	0.917	-38.502	50.000	10.581	AV

Note: Measure Level (dBμV) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + LISN Factor (dB)

6. CONCLUSION

The data collected relate only the item(s) tested and show that the device is compliance with Part 15C of the FCC rules.

The End

Appendix A - Test Setup Photograph

Refer to "2012RSU047-UT" file.

Appendix B - EUT Photograph

Refer to "2102RSU047-UE" file.