



RF MEASUREMENT REPORT

FCC ID: LNQWF672
Applicant: Actiontec Electronics Inc.
Product: Wi-Fi 7 Outdoor Mesh AP
Model No.: WF-672A
Brand Name: Actiontec
FCC Classification: Digital Transmission System (DTS)
FCC Rule Part(s): Part 15 Subpart C (Section 15.247)
Result: Complies
Received Date: 2025-06-23
Test Date: 2025-07-17 ~ 2025-09-24

Reviewed By:

Kevin Guo

Kevin Guo

Approved By:

Robin Wu

Robin Wu



The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report. Testing was performed in accordance with the applicable measurement procedures. The test results reported herein apply only to the specific item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.



Revision History

Report No.	Version	Description	Issue Date	Note
R25S1040063-U202	V01	Initial Report	2025-12-05	Valid

CONTENTS

Description	Page
1. General Information	5
1.1. Applicant	5
1.2. Manufacturer	5
1.3. Testing Facility	5
1.4. Product Information	6
1.5. Radio Specification under Test	7
1.6. Working Frequencies	8
1.7. Antenna Details	9
2. Test Configuration	10
2.1. Test Mode	10
2.2. Test System Connection Diagram	10
2.3. Test Software	11
2.4. Applied Standards	11
2.5. Test Environment Condition	11
3. Antenna Requirements	12
4. Measuring Instrument	13
5. Decision Rules and Measurement Uncertainty	14
5.1. Decision Rules	14
5.2. Measurement Uncertainty	14
6. Test Result	15
6.1. Summary	15
6.2. 6 dB Bandwidth Measurement	16
6.2.1. Test Limit	16
6.2.2. Test Procedure	16
6.2.3. Test Setting	16
6.2.4. Test Setup	16
6.2.5. Test Result	16
6.3. Output Power Measurement	17
6.3.1. Test Limit	17
6.3.2. Test Procedure	17
6.3.3. Test Setting	17
6.3.4. Test Setup	17
6.3.5. Test Result	17
6.4. Power Spectral Density Measurement	18
6.4.1. Test Limit	18

6.4.2.	Test Procedure	18
6.4.3.	Test Setting	18
6.4.4.	Test Setup	18
6.4.5.	Test Result	19
6.5.	Conducted Band Edge and Out-of-Band Emissions Measurement	20
6.5.1.	Test Limit	20
6.5.2.	Test Procedure	20
6.5.3.	Test Setting	20
6.5.4.	Test Setup	20
6.5.5.	Test Result	21
6.6.	Radiated Spurious Emission Measurement.....	22
6.6.1.	Test Limit	22
6.6.2.	Test Procedure	22
6.6.3.	Test Setting	22
6.6.4.	Test Setup	24
6.6.5.	Test Result	25
6.7.	Radiated Restricted Band Edge Measurement	26
6.7.1.	Test Limit	26
6.7.2.	Test Procedure	27
6.7.3.	Test Setting	27
6.7.4.	Test Setup	28
6.7.5.	Test Result	28
6.8.	AC Conducted Emissions Measurement.....	29
6.8.1.	Test Limit	29
6.8.2.	Test Setup	29
6.8.3.	Test Result	29
Appendix A - Test Result.....		30
A.1	Duty Cycle Test Result.....	30
A.2	6 dB Bandwidth Test Result	32
A.3	Output Power Test Result	37
A.4	Power Spectral Density Test Result.....	39
A.5	Conducted Band Edge and Out-of-Band Emissions Test Result.....	48
A.6	Radiated Spurious Emission Test Result.....	81
A.7	Radiated Restricted Band Edge Test Result.....	91
A.8	AC Conducted Emissions Test Result	227
Appendix B - Test Setup Photograph		231
Appendix C - EUT Photograph		232

1. General Information

1.1. Applicant

Actiontec Electronics Inc.

2445 Augustine Drive Suite 501, Santa Clara, California 95054, United States

1.2. Manufacturer

Actiontec Electronics Inc.

2445 Augustine Drive Suite 501, Santa Clara, California 95054, United States

1.3. Testing Facility

☒	Test Site - MRT Suzhou Laboratory
	Laboratory Location (Suzhou - Wuzhong) D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China
	Laboratory Location (Suzhou - SIP) 4b Building, Liando U Valley, No.200 Xingpu Rd., Shengpu Town, Suzhou Industrial Park, China
	Laboratory Location (Suzhou - Wujiang) Building 1, No.1 Xingdong Road, Wujiang, Suzhou, Jiangsu, People's Republic of China
	Laboratory Accreditations
	A2LA: 3628.01CNAS: L10551
	FCC: CN1166ISED: CN0001
☐	Test Site - MRT Shenzhen Laboratory
	Laboratory Location (Shenzhen) 1G, Building A, Junxiangda Building, Zhongshanyuan Road West, Nanshan District, Shenzhen, China
	Laboratory Accreditations
	A2LA: 3628.02CNAS: L10551
	FCC: CN1284ISED: CN0105
☐	Test Site - MRT Taiwan Laboratory
	Laboratory Location (Taiwan) No. 38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)
	Laboratory Accreditations
	TAF: 3261
	FCC: 291082, TW3261ISED: TW3261

1.4. Product Information

Product Name	Wi-Fi 7 Outdoor Mesh AP
Model No.	WF-672A
Brand Name	Actiontec
EUT Identification No.	20250623Sample#03 (Conducted) 20250623Sample#04 (Radiated)
Wi-Fi Specification	802.11a/b/g/n/ac/ax/be
Bluetooth Specification	Bluetooth_LE
Antenna Specification	Refer to clause 1.7
Operating Temperature	-40 ~ 65 °C
Power Type	PoE Adapter
Operating Environment	Outdoor Use
Accessory(ies)	
PoE Adapter #1	Model No.: PoE 35-54 A Input: 100-240 V ~ 50/60 Hz, Max.1.0 A Output: 54 V = 0.65 A
PoE Adapter #2	Model No.: EN30GT Input: 100-240 V ~ 50/60 Hz, Max.1.0 A Output: 52 V = 0.58 A
Notes:	
- The information of the EUT (Equipment Under Test) was provided by the manufacturer. The accuracy, completeness, and validity of the information are solely the responsibility of the manufacturer. - The product is available in two configurations. Configuration 1 can be powered by AC 120 V/60 Hz or by 802.3 at PoE, while Configuration 2 supports PoE power only. The difference between the two configurations lies in the AC power module, all other aspects are identical.	

1.5. Radio Specification under Test

Frequency Range	2400 ~ 2483.5 MHz	
Channel Number	802.11b/g/n-HT20/ax-HE20/be-EHT20: 11 802.11n-HT40/ax-HE40/be-EHT40: 7	
Type of Modulation	802.11b: DSSS 802.11g/n: OFDM 802.11ax/be: OFDMA	
Data Rate	802.11b: 1/2/5.5/11 Mbps 802.11g: 6/9/12/18/24/36/48/54 Mbps 802.11n: up to 300 Mbps 802.11ax: up to 574 Mbps 802.11be: up to 688 Mbps	
Channel Puncturing Function	☐ Supported	☒ Unsupported
Support RU	☒ Full RU	☐ Partial RU

1.6. Working Frequencies

802.11b/g/n-HT20/ax-HE20/be-EHT20

Channel	Frequency	Channel	Frequency	Channel	Frequency
01	2412 MHz	02	2417 MHz	03	2422 MHz
04	2427 MHz	05	2432 MHz	06	2437 MHz
07	2442 MHz	08	2447 MHz	09	2452 MHz
10	2457 MHz	11	2462 MHz	--	--

802.11n-HT40/ax-HE40/be-EHT40

Channel	Frequency	Channel	Frequency	Channel	Frequency
03	2422 MHz	04	2427 MHz	05	2432 MHz
06	2437 MHz	07	2442 MHz	08	2447 MHz
09	2452 MHz	--	--	--	--

1.7. Antenna Details

Antenna Type	Frequency Band (MHz)	N _{SS}		Antenna Gain (dBi)				STBC	CDD		Elevation angle	
								Directi onal Gain (dBi)	Directional Gain (dBi)		above 30° (dBi)	
	STBC	CDD	Ant 0	Ant 1	Ant 2	Ant 3	Gain (dBi)		For Power	For PSD	Correla ted	Uncorr elated
2.4G Wi-Fi Antenna												
Dipole	2400 ~ 2483.5	2	1	7.51	6.80	--	--	6.88	6.88	9.88	--	--
5G Wi-Fi Antenna for Tri-band mode												
Dipole	5150 ~ 5250	2	1	10.86	10.82	--	--	10.81	10.81	13.82	-1.55	-4.55
	5250 ~ 5350	2	1	10.86	10.82	--	--	10.81	10.81	13.82	--	--
	5470 ~ 5725	2	1	9.77	9.76	--	--	9.53	9.53	12.54	--	--
	5725 ~ 5850	2	1	9.47	10.82	--	--	9.23	9.23	12.23	--	--
5G Wi-Fi Antenna for Dual-band mode												
Dipole	5150 ~ 5250	4	1	10.86	10.82	11.83	10.61	11.01	11.01	17.02	1.26	-4.75
	5250 ~ 5350	4	1	10.86	10.82	11.83	10.61	11.01	11.01	17.02	--	--
	5470 ~ 5725	4	1	9.77	9.76	10.44	9.87	9.68	9.68	15.70	--	--
	5725 ~ 5850	4	1	9.47	10.82	10.58	10.55	9.90	9.90	15.90	--	--
6G Wi-Fi Antenna												
Dipole	5925 ~ 6425	2	1	10.56	9.85	--	--	10.55	10.55	13.54	-1.25	-4.24
	6525 ~ 6875	2	1	10.05	10.69	--	--	10.35	10.35	13.35	-1.46	-4.45
Notes:												
1. The EUT supports CDD mode for 802.11a/b/g.												
2. The EUT supports STBC mode for 802.11n/ac/ax/be.												
3. All antenna information is provided by the manufacturer.												


2. Test Configuration

2.1. Test Mode

Mode 1: Transmit by 802.11b_Nss=1 (1Mbps) - CDD Mode
Mode 2: Transmit by 802.11g_Nss=1 (6Mbps) - CDD Mode
Mode 3: Transmit by 802.11n-HT20_Nss=2 (MCS0) - STBC Mode
Mode 4: Transmit by 802.11n-HT40_Nss=2 (MCS0) - STBC Mode
Mode 5: Transmit by 802.11ax-HE20_Nss=2 (MCS0) - STBC Mode
Mode 6: Transmit by 802.11ax-HE40_Nss=2 (MCS0) - STBC Mode
Mode 7: Transmit by 802.11be-EHT20_Nss=2 (MCS0) - STBC Mode
Mode 8: Transmit by 802.11be-EHT40_Nss=2 (MCS0) - STBC Mode
Note: As Designated by manufacturer, the lowest data rate was the worst condition, so all the tests were done with lowest data rate.

2.2. Test System Connection Diagram

The device was tested per the guidance ANSI C63.10-2020 was used to reference the appropriate EUT setup for radiated emissions testing and AC line conducted testing.

Connection Diagram			
			
Cable Type		Cable Description	Length
A	LAN Cable	Non shielded	> 10 m
B	LAN Cable	Non shielded	> 10 m
Product		Manufacturer	Model No.
1	PoE Adapter	Dongguan Shilong Fuhua Electronic Co., Ltd	PoE 35-54A
2	Notebook	Lenovo	E430C

2.3. Test Software

The test utility software used during testing was “QSPR” and the version was 5.0-00202.

Final power setting please refer to operational description.

2.4. Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15.247
- KDB 558074 D01 v05r02
- KDB 662911 D01 v02r01
- ANSI C63.10-2020
- ANSI C63.10-2020/Cor1-2023
- ANSI C63.10a-2024

2.5. Test Environment Condition

Ambient Temperature	15 ~ 35 °C
Relative Humidity	20 ~ 75 %RH

3. Antenna Requirements

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna of the device is **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The unit complies with the requirement of §15.203.

4. Measuring Instrument

Instrument	Manufacturer	Model No.	Asset No.	Cali. Interval	Cali. Due Date	Test Site
Loop Antenna	Schwarzbeck	FMZB 1519 -60D	MRTSUE07076	1 year	2025-11-19	WJ-AC2
TRILOG Broad Band Antenna	Schwarzbeck	VULB 9163	MRTSUE07097	1 year	2026-04-20	WJ-AC2
Horn Antenna	RFSPIN	DRH18-E	MRTSUE07105	1 year	2026-05-12	WJ-AC2
Pre-Amplifier	EMCI	EMC118A45SEE	MRTSUE07102	1 year	2026-04-09	WJ-AC2
Signal Analyzer	Keysight	N9020B	MRTSUEWJ-AC2	1 year	2026-02-18	WJ-AC2
Thermohygrometer	testo	608-H1	MRTSUE11315	1 year	2026-06-16	WJ-AC2
Broadband Horn Antenna	Schwarzbeck	BBHA 9170	MRTSUE07100	1 year	2026-04-09	WJ-AC2
Pre-Amplifier	EMCI	EMC184045SEE	MRTSUE07103	1 year	2026-04-09	WJ-AC2
Anechoic Chamber	TDK	WJ-AC2	MRTSUE07117	1 year	2026-05-12	WJ-AC2
USB Power Sensor	Keysight	U2021XA	MRTSUE06446	1 year	2026-04-26	WZ-SR6
Thermohygrometer	testo	608-H1	MRTSUE06362	1 year	2026-01-23	WZ-SR6
Shielding Room	HUAMING	WZ-SR6	MRTSUE06443	N/A	N/A	WZ-SR6
Signal Analyzer	Keysight	N9010B	MRTSUE06457	1 year	2026-04-26	WZ-SR6
Attenuator	MVE	MVE2213	MRTSUE11091	1 year	2026-06-02	WZ-SR6
RF Cable	UCwave	UCE500	MRTSUE07382	N/A	N/A	WZ-SR6
Two-Line V-Network	R&S	ENV216	MRTSUE06002	1 year	2026-04-26	WZ-SR2
Shielding Room	MIX-BEP	WZ-SR2	MRTSUE06215	5 years	2026-12-20	WZ-SR2
Thermohygrometer	testo	608-H1	MRTSUE06404	1 year	2026-04-24	WZ-SR2
Two-Line V-Network	R&S	ENV216	MRTSUE06002	1 year	2026-04-26	WZ-SR2
EMI Test Receiver	R&S	ESR3	MRTSUE06909	1 year	2025-09-05	WZ-SR2
				1 year	2026-08-31	WZ-SR2

Software	Version	Function
e3	230711	RE & CE
CONTROLLER CO3000	v 1.03.02	RE Antenna & Turntable
Agilent Power Panel	V 3.9	Power

5. Decision Rules and Measurement Uncertainty

5.1. Decision Rules

The Decision Rule is based on Simple Acceptance in accordance with ISO Guide 98-4: 2012 Clause 8.2.

(Measurement uncertainty is not taken into account when stating conformity with a specified requirement.)

5.2. Measurement Uncertainty

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

AC Conducted Emission Measurement	
The maximum measurement uncertainty is evaluated as:	
9 kHz ~ 150 kHz:	3.58 dB
150 kHz ~ 30 MHz:	3.20 dB
Radiated Emission Measurement	
The maximum measurement uncertainty is evaluated as:	
Coaxial:	9 kHz ~ 30 MHz: 2.35 dB
Coplanar:	9 kHz ~ 30 MHz: 2.37 dB
Horizontal:	30 MHz ~ 200 MHz: 3.47 dB
	200 MHz ~ 1 GHz: 4.17 dB
	1 GHz ~ 40 GHz: 4.97 dB
Vertical:	30 MHz ~ 200 MHz: 4.07 dB
	200 MHz ~ 1 GHz: 5.28 dB
	1 GHz ~ 40 GHz: 4.84 dB
Spurious Emissions, Conducted	
Measuring Uncertainty for a Level of Confidence of 95% ($U=2 U_c(y)$): 2.5 dB	
Output Power	
Measuring Uncertainty for a Level of Confidence of 95% ($U=2 U_c(y)$): 1.5 dB	
Power Spectrum Density	
Measuring Uncertainty for a Level of Confidence of 95% ($U=2 U_c(y)$): 2.5 dB	
Occupied Bandwidth	
Measuring Uncertainty for a Level of Confidence of 95% ($U=2 U_c(y)$): 3.2%	

6. Test Result

6.1. Summary

FCC Section(s)	Test Description	Test Condition	Verdict
15.247(a)(2)	6 dB Bandwidth	Conducted	Pass
15.247(b)(3)	Output Power		Pass
15.247(e)	Power Spectral Density		Pass
15.247(d)	Band Edge / Out-of-Band Emissions		Pass
15.205 15.209	General Field Strength (Restricted Bands and Radiated Emission)	Radiated	Pass
15.207	AC Conducted Emissions 150 kHz - 30 MHz	Line Conducted	Pass

Notes:

1. The analyzer plots shown in this section were captured using a correction table to account for cable and attenuator losses in the system connecting the EUT to the analyzer across relevant frequencies.
2. For radiated emission tests, every axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst-case emissions.

6.2. 6 dB Bandwidth Measurement

6.2.1. Test Limit

The minimum 6 dB bandwidth shall be at least 500 kHz.


6.2.2. Test Procedure

ANSI C63.10 - 2020 - Section 11.8

6.2.3. Test Setting

1. The Spectrum's automatic bandwidth measurement capability was used to perform the 6 dB bandwidth measurement. The "X" dB bandwidth parameter was set to $X = 6$. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. Set RBW = 1% to 5% of the OBW, but not less than 100 kHz
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = Max hold
6. Sweep = Auto couple
7. Allow the trace to stabilize.

6.2.4. Test Setup



6.2.5. Test Result

Refer to Appendix A.2.

6.3. Output Power Measurement

6.3.1. Test Limit

The maximum output power shall be less 1 Watt (30 dBm).

The conducted output power limit specified in paragraph FCC Part 15.247(b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs FCC Part 15.247(b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

6.3.2. Test Procedure


ANSI C63.10 - 2020 - Section 11.9.2.3.2

6.3.3. Test Setting

Average Power Measurement

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter.

6.3.4. Test Setup



6.3.5. Test Result

Refer to Appendix A.3.

6.4. Power Spectral Density Measurement

6.4.1. Test Limit

The maximum permissible power spectral density is 8 dBm in any 3 kHz band.

The same method of determining the conducted output power shall be used to determine the power spectral density.


6.4.2. Test Procedure

ANSI C63.10 - 2020 - Section 11.10.5

6.4.3. Test Setting

1. Measure the duty cycle (x) of the transmitter output signal.
2. Set instrument center frequency to DTS channel center frequency.
3. Set span to at least 1.5 times the OBW.
4. RBW = 10 kHz.
5. VBW = 30 kHz.
6. Detector = RMS.
7. Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span/RBW}$.
8. Sweep time = auto couple.
9. Don't use sweep triggering. Allow sweep to "free run".
10. Employ trace averaging (RMS) mode over a minimum of 100 traces.
11. Use the peak marker function to determine the maximum amplitude level.
12. Add $10 \log (1/x)$, where x is the duty cycle measured in step (a, to the measured PSD to compute the average PSD during the actual transmission time. If measured value exceeds requirement specified by regulatory agency, then reduce RBW (but no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span to meet the minimum measurement point requirement as the RBW is reduced).

6.4.4. Test Setup



6.4.5. Test Result

Refer to Appendix A.4.

6.5. Conducted Band Edge and Out-of-Band Emissions Measurement

6.5.1. Test Limit

The limit for out-of-band spurious emissions at the band edge is 30 dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100 kHz bandwidth per the PSD procedure.

6.5.2. Test Procedure

ANSI C63.10-2020 - Section 11.11

6.5.3. Test Setting


Reference level measurement

1. Set instrument center frequency to DTS channel center frequency
2. Set the span to ≥ 1.5 times the DTS bandwidth
3. Set the RBW = 100 kHz
4. Set the VBW $\geq 3 \times$ RBW
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Allow trace to fully stabilize

Emission level measurement

1. Set the center frequency and span to encompass frequency range to be measured
2. RBW = 100 kHz
3. VBW = 300 kHz
4. Detector = Peak
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

6.5.4. Test Setup



6.5.5. Test Result

Refer to Appendix A.5.

6.6. Radiated Spurious Emission Measurement

6.6.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [$\mu\text{V/m}$]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

6.6.2. Test Procedure

ANSI C63.10 - 2020 - Section 11.11 & 11.12

ANSI C63.10 - 2020 - Section 6.3 (General Requirements)

ANSI C63.10 - 2020 - Section 6.4 (Standard test method below 30 MHz)

ANSI C63.10 - 2020 - Section 6.5 (Standard test method above 30 MHz to 1 GHz)

ANSI C63.10 - 2020 - Section 6.6 (Standard test method above 1 GHz)

6.6.3. Test Setting

Table 1 - RBW as a function of frequency

Frequency	RBW
9 ~ 150 kHz	200 ~ 300 Hz
0.15 ~ 30 MHz	9 ~ 10 kHz
30 ~ 1000 MHz	100 ~ 120 kHz
> 1000 MHz	1 MHz

Quasi-Peak Measurements below 1 GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. Span was set greater than 1 MHz
3. RBW = as specified in Table 1
4. Detector = CISPR quasi-peak
5. Sweep time = auto couple
6. Trace was allowed to stabilize

Peak Measurements above 1 GHz


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1 MHz
3. VBW = 3 MHz
4. Detector = Peak
5. Sweep time = Auto couple
6. Trace mode = Max hold
7. Trace was allowed to stabilize

Average Measurements above 1 GHz (Method VB)


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1 MHz
3. VBW; if the EUT is configured to transmit with duty cycle $\geq 98\%$, set VBW = 10 Hz
If the EUT duty cycle is $< 98\%$, set $\text{VBW} \geq 1/T$. T is the minimum transmission duration.
4. As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode
5. Detector = Peak
6. Sweep time = Auto
7. Trace mode = Max hold
8. Trace was allowed to stabilize

6.6.4. Test Setup


Below 30 MHz Test Setup:



Below 1 GHz Test Setup:



Above 1 GHz Test Setup:



6.6.5. Test Result

Refer to Appendix A.6.

6.7. Radiated Restricted Band Edge Measurement

6.7.1. Test Limit

For 15.205 requirement:

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) of FCC part 15, must also comply with the radiated emission limits specified in Section 15.209(a).

Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	- 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)
13.36 - 13.41	--	--	--

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [$\mu\text{V/m}$]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

6.7.2. Test Procedure

ANSI C63.10-2020 Section 6.3 & 6.6 & 11.13

6.7.3. Test Setting

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1 MHz
3. VBW = 3 MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize


Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1 MHz
3. VBW; If the EUT is configured to transmit with duty cycle $\geq 98\%$, set VBW = 10 Hz.

If the EUT duty cycle is $< 98\%$, set VBW $\geq 1/T$. T is the minimum transmission duration.

4. As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode
5. Detector = Peak
6. Sweep time = auto
7. Trace mode = max hold
8. Allow max hold to run for at least 50 times (1/duty cycle) traces

6.7.4. Test Setup



6.7.5. Test Result

Refer to Appendix A.7.

6.8. AC Conducted Emissions Measurement


6.8.1. Test Limit

FCC Part 15 Subpart C Paragraph 15.207 Limits		
Frequency (MHz)	QP (dB μ V)	AV (dB μ V)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.

Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

6.8.2. Test Setup



6.8.3. Test Result

Refer to Appendix A.8.


Appendix A - Test Result

A.1 Duty Cycle Test Result

Test Site	WZ-SR6	Test Engineer	Molly Wu
Test Date	2025-07-22		


Test Mode	Duty Cycle
802.11b	98.00%
802.11g	98.65%
802.11n-HT20	97.66%
802.11n-HT40	96.42%
802.11ax-HE20	97.13%
802.11ax-HE40	96.43%
802.11be-EHT20	97.32%
802.11be-EHT40	96.94%

Duty Cycle (T = Transmission Duration)




Duty Cycle (T = Transmission Duration)


802.11ax-HE20 (T = 5.410 ms)




802.11ax-HE40 (T = 5.400 ms)



802.11be-EHT20 (T = 5.450 ms)



802.11be-EHT40 (T = 5.380 ms)




A.2 6 dB Bandwidth Test Result

Test Site	WZ-SR6	Test Engineer	Molly Wu
Test Date	2025-09-24		


Test Mode	Data Rate / MCS	Channel No.	Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
11b	1 Mbps	01	2412	8.125	≥ 0.5
11b	1 Mbps	06	2437	7.631	≥ 0.5
11b	1 Mbps	11	2462	7.633	≥ 0.5
11g	6 Mbps	01	2412	15.500	≥ 0.5
11g	6 Mbps	06	2437	15.590	≥ 0.5
11g	6 Mbps	11	2462	15.750	≥ 0.5
11n-HT20	MCS0	01	2412	17.210	≥ 0.5
11n-HT20	MCS0	06	2437	17.010	≥ 0.5
11n-HT20	MCS0	11	2462	17.020	≥ 0.5
11n-HT40	MCS0	03	2422	35.070	≥ 0.5
11n-HT40	MCS0	06	2437	35.440	≥ 0.5
11n-HT40	MCS0	09	2452	35.480	≥ 0.5
11ax-HE20	MCS0	01	2412	18.580	≥ 0.5
11ax-HE20	MCS0	06	2437	18.780	≥ 0.5
11ax-HE20	MCS0	11	2462	18.730	≥ 0.5
11ax-HE40	MCS0	03	2422	37.050	≥ 0.5
11ax-HE40	MCS0	06	2437	36.500	≥ 0.5
11ax-HE40	MCS0	09	2452	37.210	≥ 0.5
11be-EHT20	MCS0	01	2412	18.840	≥ 0.5
11be-EHT20	MCS0	06	2437	18.810	≥ 0.5
11be-EHT20	MCS0	11	2462	16.900	≥ 0.5
11be-EHT40	MCS0	03	2422	36.950	≥ 0.5
11be-EHT40	MCS0	06	2437	37.230	≥ 0.5
11be-EHT40	MCS0	09	2452	37.090	≥ 0.5

802.11b 6 dB Bandwidth


Channel 01 (2412 MHz)



Channel 06 (2437 MHz)




Channel 11 (2462 MHz)




802.11g 6 dB Bandwidth


Channel 01 (2412 MHz)



Channel 06 (2437 MHz)



Channel 11 (2462 MHz)




802.11n-HT20 6 dB Bandwidth


Channel 01 (2412 MHz)



Channel 06 (2437 MHz)




Channel 11 (2462 MHz)




802.11n-HT40 6 dB Bandwidth


Channel 03 (2422 MHz)



Channel 06 (2437 MHz)




Channel 09 (2452 MHz)




802.11ax-HE20 6 dB Bandwidth


Channel 01 (2412 MHz)



Channel 06 (2437 MHz)




Channel 11 (2462 MHz)




802.11ax-HE40 6 dB Bandwidth


Channel 03 (2422 MHz)



Channel 06 (2437 MHz)




Channel 09 (2452 MHz)




802.1be-EHT20 6 dB Bandwidth


Channel 01 (2412 MHz)



Channel 06 (2437 MHz)




Channel 11 (2462 MHz)




802.11be-EHT40 6 dB Bandwidth


Channel 03 (2422 MHz)



Channel 06 (2437 MHz)



Channel 09 (2452 MHz)



A.3 Output Power Test Result

Test Site	WZ-SR6	Test Engineer	Molly Wu
Test Date	2025-07-22 ~ 2025-07-23		

Test Mode	Data Rate / MCS	Channel No.	Freq. (MHz)	Average Power (dBm)		Total Average Power (dBm)	Limit (dBm)
				Ant 0	Ant 1		
11b	1 Mbps	01	2412	22.60	23.01	25.82	≤ 30.00
11b	1 Mbps	06	2437	23.08	23.60	26.36	≤ 30.00
11b	1 Mbps	11	2462	22.04	22.46	25.27	≤ 30.00
11g	6 Mbps	01	2412	20.58	21.10	23.86	≤ 30.00
11g	6 Mbps	06	2437	23.13	23.49	26.32	≤ 30.00
11g	6 Mbps	10	2457	20.76	21.18	23.99	≤ 30.00
11g	6 Mbps	11	2462	19.53	20.09	22.83	≤ 30.00
11n-HT20	MCS0	01	2412	21.65	22.33	25.01	≤ 30.00
11n-HT20	MCS0	06	2437	22.90	23.56	26.25	≤ 30.00
11n-HT20	MCS0	10	2457	20.22	20.63	23.44	≤ 30.00
11n-HT20	MCS0	11	2462	19.55	20.27	22.94	≤ 30.00
11n-HT40	MCS0	03	2422	14.96	15.48	18.24	≤ 30.00
11n-HT40	MCS0	04	2427	16.86	17.29	20.09	≤ 30.00
11n-HT40	MCS0	06	2437	19.22	19.65	22.45	≤ 30.00
11n-HT40	MCS0	08	2447	18.38	18.74	21.57	≤ 30.00
11n-HT40	MCS0	09	2452	15.21	15.76	18.50	≤ 30.00
11ax-HE20	MCS0	01	2412	20.81	21.23	24.04	≤ 30.00
11ax-HE20	MCS0	06	2437	23.21	23.54	26.39	≤ 30.00
11ax-HE20	MCS0	10	2457	20.28	20.69	23.50	≤ 30.00
11ax-HE20	MCS0	11	2462	19.35	19.75	22.56	≤ 30.00
11ax-HE40	MCS0	03	2422	15.65	16.18	18.93	≤ 30.00
11ax-HE40	MCS0	04	2427	17.94	18.08	21.02	≤ 30.00
11ax-HE40	MCS0	06	2437	19.35	19.65	22.51	≤ 30.00
11ax-HE40	MCS0	08	2447	18.42	18.75	21.60	≤ 30.00
11ax-HE40	MCS0	09	2452	16.50	17.25	19.90	≤ 30.00
11be-EHT20	MCS0	01	2412	21.25	21.75	24.52	≤ 30.00
11be-EHT20	MCS0	06	2437	23.15	23.52	26.35	≤ 30.00
11be-EHT20	MCS0	09	2452	21.85	22.37	25.13	≤ 30.00
11be-EHT20	MCS0	10	2457	19.40	19.70	22.56	≤ 30.00
11be-EHT20	MCS0	11	2462	18.78	18.96	21.88	≤ 30.00

Test Mode	Data Rate / MCS	Channel No.	Freq. (MHz)	Average Power (dBm)		Total Average Power (dBm)	Limit (dBm)
				Ant 0	Ant 1		
11be-EHT40	MCS0	03	2422	15.87	16.08	18.99	≤ 30.00
11be-EHT40	MCS0	04	2427	17.83	17.98	20.92	≤ 30.00
11be-EHT40	MCS0	06	2437	19.75	20.03	22.90	≤ 30.00
11be-EHT40	MCS0	08	2447	18.15	18.75	21.47	≤ 30.00
11be-EHT40	MCS0	09	2452	15.65	15.89	18.78	≤ 30.00

Note: Total Average Power (dBm) = $10 \times \log \{10^{(\text{Ant 0 Average Power} / 10)} + 10^{(\text{Ant 1 Average Power} / 10)}\}$ (dBm).

A.4 Power Spectral Density Test Result

Test Site	WZ-SR6	Test Engineer	Molly Wu
Test Date	2025-07-22 ~ 2025-07-23		

Test Mode	Data Rate/ MCS	Channel No.	Freq. (MHz)	PSD (dBm/ 10 kHz)		Duty Cycle (%)	10×log (1/x)	Total PSD (dBm/10 kHz)	Limit (dBm/3 kHz)
				Ant 0	Ant 1				
11b	1 Mbps	01	2412	-1.824	-1.288	98.00	0.09	1.55	≤ 4.12
11b	1 Mbps	06	2437	-0.894	-0.605	98.00	0.09	2.35	≤ 4.12
11b	1 Mbps	11	2462	-2.338	-2.278	98.00	0.09	0.79	≤ 4.12
11g	6 Mbps	01	2412	-5.184	-5.896	98.65	0.06	-2.52	≤ 4.12
11g	6 Mbps	06	2437	-3.064	-2.119	98.65	0.06	0.44	≤ 4.12
11g	6 Mbps	11	2462	-6.861	-7.109	98.65	0.06	-3.97	≤ 4.12
11n-HT20	MCS0	01	2412	-5.198	-4.671	97.66	0.10	-1.81	≤ 7.12
11n-HT20	MCS0	06	2437	-4.094	-3.539	97.66	0.10	-0.69	≤ 7.12
11n-HT20	MCS0	11	2462	-7.187	-6.902	97.66	0.10	-3.93	≤ 7.12
11n-HT40	MCS0	03	2422	-14.458	-13.809	96.42	0.16	-10.95	≤ 7.12
11n-HT40	MCS0	06	2437	-10.800	-10.272	96.42	0.16	-7.36	≤ 7.12
11n-HT40	MCS0	09	2452	-14.185	-14.054	96.42	0.16	-10.95	≤ 7.12
11ax-HE20	MCS0	01	2412	-6.563	-6.071	97.13	0.13	-3.17	≤ 7.12
11ax-HE20	MCS0	06	2437	-4.379	-4.012	97.13	0.13	-1.05	≤ 7.12
11ax-HE20	MCS0	11	2462	-8.056	-7.760	97.13	0.13	-4.77	≤ 7.12
11ax-HE40	MCS0	03	2422	-14.238	-13.829	96.43	0.16	-10.86	≤ 7.12
11ax-HE40	MCS0	06	2437	-11.038	-10.493	96.43	0.16	-7.59	≤ 7.12
11ax-HE40	MCS0	09	2452	-13.543	-13.029	96.43	0.16	-10.11	≤ 7.12
11be-EHT20	MCS0	01	2412	-6.154	-5.342	97.32	0.12	-2.60	≤ 7.12
11be-EHT20	MCS0	06	2437	-4.571	-3.980	97.32	0.12	-1.14	≤ 7.12
11be-EHT20	MCS0	11	2462	-8.797	-8.104	97.32	0.12	-5.31	≤ 7.12
11be-EHT40	MCS0	03	2422	-14.456	-13.893	96.94	0.13	-11.02	≤ 7.12
11be-EHT40	MCS0	06	2437	-10.493	-10.389	96.94	0.13	-7.30	≤ 7.12
11be-EHT40	MCS0	09	2452	-14.585	-14.441	96.94	0.13	-11.37	≤ 7.12

Note 1:

When EUT duty cycle ≥ 98%, Total PSD (dBm/10 kHz) = $10 \times \log \{10^{(\text{Ant 0 PSD}/10)} + 10^{(\text{Ant 1 PSD}/10)}\}$ (dBm/10 kHz).


When EUT duty cycle < 98%, Total PSD (dBm/10 kHz) = $10 \times \log \{10^{(\text{Ant 0 PSD}/10)} + 10^{(\text{Ant 1 PSD}/10)}\}$ (dBm/10 kHz) + $10 \times \log (1/\text{Duty Cycle})$.

Note 2: For CDD Mode, Limit (dBm/3 kHz) = 8 - (9.88-6) = 4.12 dBm/3 kHz.

For STBC Mode, Limit (dBm/3 kHz) = 8 - (6.88-6) = 7.12 dBm/3 kHz.

802.11b - AVGPSD - Ant 0


Channel 01 (2412 MHz)



Channel 06 (2437 MHz)




Channel 11 (2462 MHz)




802.11g - AVGPSD - Ant 0


Channel 01 (2412 MHz)



Channel 06 (2437 MHz)




Channel 11 (2462 MHz)




802.11n-HT20 - AVGPSPD - Ant 0


Channel 01 (2412 MHz)



Channel 06 (2437 MHz)




Channel 11 (2462 MHz)



802.11n-HT40 - AVGPSPD - Ant 0


Channel 03 (2422 MHz)



Channel 06 (2437 MHz)




Channel 09 (2452 MHz)




802.11ax-HE20 - AVGPSD - Ant 0


Channel 01 (2412 MHz)



Channel 06 (2437 MHz)




Channel 11 (2462 MHz)




802.11ax-HE40 - AVGPSD - Ant 0


Channel 03 (2422 MHz)



Channel 06 (2437 MHz)




Channel 09 (2452 MHz)




802.11be-EHT20 - AVGPSPD - Ant 0

Channel 01 (2412 MHz)



Channel 06 (2437 MHz)




Channel 11 (2462 MHz)




802.11be-EHT40 - AVGPSPD - Ant


Channel 03 (2422 MHz)



Channel 06 (2437 MHz)




Channel 09 (2452 MHz)




802.11b - AVGPSD - Ant 1


Channel 01 (2412 MHz)



Channel 06 (2437 MHz)




Channel 11 (2462 MHz)




802.11g - AVGPSD - Ant 1

Channel 01 (2412 MHz)



Channel 06 (2437 MHz)



Channel 11 (2462 MHz)

