



2.4 GHz 15 dBi Yagi Antenna - 12in N-Female Connector


Item # HG2415Y-NF



User Manual



3D CAD
Model
(.step)



2D Drawing
(.pdf)

Price Table

Quantity	Price
1 - 9	\$83.67
10 - 24	\$76.98
25 - 99	\$70.28
100 +	Call Us

Add to Cart

Quantity:

 **ADD TO CART**

Description

Superior Performance

The HyperGain HG2415Y Radome Enclosed Yagi WiFi Antenna features high gain and a 30° beam-width. It is ideally suited for directional and multipoint IEEE 802.11b, 802.11g and 802.11n wireless LANs, Bluetooth®, public wireless hotspot applications and other systems operating in the 2.4GHz ISM band. The unique design of this antenna allows it to be installed for either vertical or horizontal polarization.

Rugged and Weatherproof

This WiFi antenna is enclosed within a UV-stable, UL flame rated radome for all-weather operation. The HG2415Y antenna is supplied with a 60 degree tilt and swivel mast mount kit.

Custom Connectors

If you need a custom connector for this antenna, please contact sales for connector options, prices and availability.

Features

- 30° beam-width & DC Short lightning protection
- Includes tilt and swivel mast mount
- 12in low-loss coax lead terminated with a N-Female connector
- Can be installed for either vertical or horizontal polarization
- Light weight, UV-stable & UL flame rated radome

Application

- Bluetooth® & public wireless hotspot
- 2.4 GHz ISM Band
- Directional and multipoint applications
- IEEE 802.11b, 802.11g & IEEE 802.11n Wireless LAN
- WiFi & wireless video systems