


Appendix B

RF Power Output




Marker 1 [T1] RBW 3 MHz RF Att 50 dB
Ref Lvl 32.54 dBm VBW 3 MHz
36 dBm 824.29018036 MHz SWT 5 ms Unit dBm



Title: Output power conducted / Channel: 128
Comment A: Wavecom MD 740-1
Date: 24.NOV.2005 14:08:21




Marker 1 [T1] RBW 3 MHz RF Att 50 dB
Ref Lvl 32.80 dBm VBW 3 MHz
36 dBm 836.04969940 MHz SWT 5 ms Unit dBm



Title: Output power conducted / Channel: 188
Comment A: Wavecom MD 740-1
Date: 24.NOV.2005 14:09:15




Marker 1 [T1] RBW 3 MHz RF Att 50 dB
Ref Lvl 33.04 dBm VBW 3 MHz
36 dBm 848.83006012 MHz SWT 5 ms Unit dBm



Title: Output power conducted / Channel: 251
Comment A: Wavecom MD 740-1
Date: 24.NOV.2005 14:10:00




Marker 1 [T1] RBW 3 MHz RF Att 50 dB
Ref Lvl 29.89 dBm VBW 3 MHz
36 dBm 1.85004970 GHz SWT 5 ms Unit dBm



Title: Output power conducted / Channel: 512
Comment A: Wavecom MD 740-1
Date: 23.NOV.2005 14:17:33




Marker 1 [T1] RBW 3 MHz RF Att 50 dB
Ref Lvl 30.12 dBm VBW 3 MHz
36 dBm 1.87984970 GHz SWT 5 ms Unit dBm



Title: Output power conducted / Channel: 661
Comment A: Wavecom MD 740-1
Date: 23.NOV.2005 14:18:26



Marker 1 [T1] RBW 3 MHz RF Att 50 dB
Ref Lvl 29.72 dBm VBW 3 MHz
36 dBm 1.90958958 GHz SWT 5 ms Unit dBm




Title: Output power conducted / Channel: 810
Comment A: Wavecom MD 740-1
Date: 23.NOV.2005 14:19:07

Appendix C

ERP, EIRP


Effective Radiated Power
FCC RULES PART 22 SUBPART H

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 128
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Schostek
Test Specification: according to §22.913
Comment 1: Dist.: 3m, Ant.: HL223
Comment 2: Freq: 824.306MHz, Pmax: 25.95dBm, RBW: 3MHz




Effective Radiated Power
FCC RULES PART 22 SUBPART H

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 128
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Schostek
Test Specification: according to §22.913
Comment 1: Dist.: 3m, Ant.: HL223
Comment 2: Freq: 824.583MHz, Pmax: 11.39dBm, RBW: 3MHz




Effective Radiated Power
FCC RULES PART 22 SUBPART H

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 188
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Schostek
Test Specification: according to §22.913
Comment 1: Dist.: 3m, Ant.: HL223
Comment 2: Freq: 836.400MHz, Pmax: 29.49dBm, RBW: 3MHz




Effective Radiated Power
FCC RULES PART 22 SUBPART H

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 188
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Schostek
Test Specification: according to §22.913
Comment 1: Dist.: 3m, Ant.: HL223
Comment 2: Freq: 836.507MHz, Pmax: 13.78dBm, RBW: 3MHz




Effective Radiated Power
FCC RULES PART 22 SUBPART H

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 251
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Schostek
Test Specification: according to §22.913
Comment 1: Dist.: 3m, Ant.: HL223
Comment 2: Freq: 849.000MHz, Pmax: 31.45dBm, RBW: 3MHz




**Effective Radiated Power
FCC RULES PART 22 SUBPART H**

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 251
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Schostek
Test Specification: according to §22.913
Comment 1: Dist.: 3m, Ant.: HL223
Comment 2: Freq: 848.973MHz, Pmax: 17.69dBm, RBW: 3MHz




Equivalent Isotropically Radiated Power
FCC RULES PART 24 SUBPART E

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 512
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §24.232
Comment 1: Dist.: 3m, Ant.: HL025,PCL 0
Comment 2: Freq: 1.850GHz, Pmax: 30.65dBm, RBW: 3MHz




Equivalent Isotropically Radiated Power
FCC RULES PART 24 SUBPART E

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 512
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §24.232
Comment 1: Dist.: 3m, Ant.: HL025,PCL 0
Comment 2: Freq: 1.850GHz, Pmax: 15.73dBm, RBW: 3MHz




**Equivalent Isotropically Radiated Power
FCC RULES PART 24 SUBPART E**

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 661
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §24.232
Comment 1: Dist.: 3m, Ant.: HL025,PCL 0
Comment 2: Freq: 1.880GHz, Pmax: 30.37dBm, RBW: 3MHz




Equivalent Isotropically Radiated Power
FCC RULES PART 24 SUBPART E

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 661
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §24.232
Comment 1: Dist.: 3m, Ant.: HL025,PCL 0
Comment 2: Freq: 1.880GHz, Pmax: 17.32dBm, RBW: 3MHz




**Equivalent Isotropically Radiated Power
FCC RULES PART 24 SUBPART E**

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 810
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §24.232
Comment 1: Dist.: 3m, Ant.: HL025,PCL 0
Comment 2: Freq: 1.910GHz, Pmax: 29.42dBm, RBW: 3MHz



Equivalent Isotropically Radiated Power
FCC RULES PART 24 SUBPART E

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 810
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §24.232
Comment 1: Dist.: 3m, Ant.: HLO25,PCL 0
Comment 2: Freq: 1.910GHz, Pmax: 13.95dBm, RBW: 3MHz



Appendix D

Modulation Requirements

Appendix E

Audio Filter Characteristics

Appendix F


Emission Limitation

Appendix G

Occupied Bandwidth




Marker 1 [T1] RBW 3 kHz RF Att 50 dB
Ref Lvl 25.84 dBm VBW 3 kHz
36 dBm 824.18496994 MHz SWT 280 ms Unit dBm



Title: Occupied Bandwidth / Channel: 128
Comment A: Wavecom MD 740-1
Date: 24.NOV.2005 14:35:33




Marker 1 [T1] RBW 3 kHz RF Att 50 dB
Ref Lvl 25.67 dBm VBW 3 kHz
36 dBm 836.17895792 MHz SWT 280 ms Unit dBm



Title: Occupied Bandwidth / Channel: 188
Comment A: Wavecom MD 740-1
Date: 24.NOV.2005 14:37:50




Marker 1 [T1] RBW 3 kHz RF Att 50 dB
Ref Lvl 24.70 dBm VBW 3 kHz
36 dBm 848.78296593 MHz SWT 280 ms Unit dBm



Title: Occupied Bandwidth / Channel: 251
Comment A: Wavecom MD 740-1
Date: 24.NOV.2005 14:39:38




Marker 1 [T1 ndB] RBW 3 kHz RF Att 50 dB
Ref Lvl ndB 26.00 dB VBW 3 kHz
36 dBm BW 322.64529058 kHz SWT 280 ms Unit dBm



Title: Emission Bandwidth (-26 dB) / Channel: 128
Comment A: Wavecom MD 740-1
Date: 24.NOV.2005 14:51:04




Marker 1 [T1 ndB] RBW 3 kHz RF Att 50 dB
Ref Lvl ndB 26.00 dB VBW 3 kHz
36 dBm BW 320.64128257 kHz SWT 280 ms Unit dBm



Title: Emission Bandwidth (-26 dB) / Channel: 188
Comment A: Wavecom MD 740-1
Date: 24.NOV.2005 14:52:42




Marker 1 [T1 ndB] RBW 3 kHz RF Att 50 dB
Ref Lvl ndB 26.00 dB VBW 3 kHz
36 dBm BW 318.63727455 kHz SWT 280 ms Unit dBm



Title: Emission Bandwidth (-26 dB) / Channel: 251
Comment A: Wavecom MD 740-1
Date: 24.NOV.2005 14:53:57




Marker 1 [T1] RBW 3 kHz RF Att 50 dB
Ref Lvl 21.56 dBm VBW 3 kHz
36 dBm 1.85021102 GHz SWT 280 ms Unit dBm



Title: Occupied Bandwidth \ Channel: 512
Comment A: Wavecom MD 740-1
Date: 23.NOV.2005 14:10:52




Marker 1 [T1] RBW 3 kHz RF Att 50 dB
Ref Lvl 21.60 dBm VBW 3 kHz
36 dBm 1.87998497 GHz SWT 280 ms Unit dBm



Title: Occupied Bandwidth / Channel: 661
Comment A: Wavecom MD 740-1
Date: 23.NOV.2005 14:12:42




Marker 1 [T1] RBW 3 kHz RF Att 50 dB
Ref Lvl 23.11 dBm VBW 3 kHz
36 dBm 1.90978297 GHz SWT 280 ms Unit dBm



Title: Occupied Bandwidth / Channel: 810
Comment A: Wavecom MD 740-1
Date: 23.NOV.2005 14:15:45




Marker 1 [T1 ndB] RBW 3 kHz RF Att 50 dB
Ref Lvl ndB 26.00 dB VBW 3 kHz
36 dBm BW 312.62525050 kHz SWT 280 ms Unit dBm



Title: Emission Bandwidth (-26 dB) / Channel: 512
Comment A: Wavecom MD 740-1
Date: 23.NOV.2005 13:58:21




Marker 1 [T1 ndB] RBW 3 kHz RF Att 50 dB
Ref Lvl ndB 26.00 dB VBW 3 kHz
36 dBm BW 314.62925852 kHz SWT 280 ms Unit dBm



Title: Emission Bandwidth (-26 dB) / Channel: 661
Comment A: Wavecom MD 740-1d
Date: 23.NOV.2005 14:02:31



Marker 1 [T1 ndB] RBW 3 kHz RF Att 50 dB
Ref Lvl ndB 26.00 dB VBW 3 kHz
36 dBm BW 314.62925852 kHz SWT 280 ms Unit dBm



Title: Emission Bandwidth (-26 dB) / Channel: 810
Comment A: Wavecom MD 740-1
Date: 23.NOV.2005 14:04:06

Appendix H


Out of Band Emission at Antenna Terminals Mobile Emissions In Base
Frequency Range

Appendix I

Spurious Radiation


Radiated Emissions Tx
FCC RULES PART 22 SUBPART H

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 128
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §22.917
Comment 1: Dist.: 3m, Ant.: HK 116
Comment 2: Freq: 33.778MHz, Pmax: -46.82dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 22 SUBPART H

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 128
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §22.917
Comment 1: Dist.: 3m, Ant.: HK 116
Comment 2: Freq: 186.589MHz, Pmax: -50.35dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 22 SUBPART H

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 128
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §22.917
Comment 1: Dist.: 3m, Ant.: HL 223+notch
Comment 2: Freq: 823.994MHz, Pmax: -27.61dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 22 SUBPART H

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 128
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §22.917
Comment 1: Dist.: 3m, Ant.: HL 223+notch
Comment 2: Freq: 858.218MHz, Pmax: -38.46dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 22 SUBPART H

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 128
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Schostek
Test Specification: according to §22.917
Comment 1: Dist.: 3m, Ant.: HL025
Comment 2: Freq: 3.597GHz, Pmax: -22.73dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 22 SUBPART H

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 128
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Schostek
Test Specification: according to §22.917
Comment 1: Dist.: 3m, Ant.: HL025
Comment 2: Freq: 3.980GHz, Pmax: -23.03dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 22 SUBPART H

Company: Siemens AG
 EUT : GSM Modem
 Model / Channel: MD740-1 / Channel 128
 Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
 Test Site / Operator: ETS / Mr. Schostek
 Test Specification: according to §22.917
 Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
 Comment 2: Freq: 7.982GHz, Pmax: -44.47dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 22 SUBPART H

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 128
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Schostek
Test Specification: according to §22.917
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Comment 2: Freq: 7.996GHz, Pmax: -44.29dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 22 SUBPART H

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 128
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Schostek
Test Specification: according to §22.917
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Comment 2: Freq: 10.853GHz, Pmax: -40.64dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 22 SUBPART H

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 128
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Schostek
Test Specification: according to §22.917
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Comment 2: Freq: 10.738GHz, Pmax: -39.59dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 22 SUBPART H

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 188
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §22.917
Comment 1: Dist.: 3m, Ant.: HK 116
Comment 2: Freq: 34.722MHz, Pmax: -46.66dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 22 SUBPART H

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 188
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §22.917
Comment 1: Dist.: 3m, Ant.: HK 116
Comment 2: Freq: 80.433MHz, Pmax: -49.36dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 22 SUBPART H

Company: Siemens AG
 EUT : GSM Modem
 Model / Channel: MD740-1 / Channel 188
 Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
 Test Site / Operator: ETS / Mr. Pfeufer
 Test Specification: according to §22.917
 Comment 1: Dist.: 3m, Ant.: HL 223+notch
 Comment 2: Freq: 902.829MHz, Pmax: -40.32dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 22 SUBPART H

Company: Siemens AG
 EUT : GSM Modem
 Model / Channel: MD740-1 / Channel 188
 Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
 Test Site / Operator: ETS / Mr. Pfeufer
 Test Specification: according to §22.917
 Comment 1: Dist.: 3m, Ant.: HL 223+notch
 Comment 2: Freq: 619.544MHz, Pmax: -39.30dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 22 SUBPART H

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 188
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Schostek
Test Specification: according to §22.917
Comment 1: Dist.: 3m, Ant.: HL025
Comment 2: Freq: 1.677GHz, Pmax: -19.02dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 22 SUBPART H

Company: Siemens AG
 EUT : GSM Modem
 Model / Channel: MD740-1 / Channel 188
 Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
 Test Site / Operator: ETS / Mr. Schostek
 Test Specification: according to §22.917
 Comment 1: Dist.: 3m, Ant.: HL025
 Comment 2: Freq: 3.990GHz, Fmax: -22.73dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 22 SUBPART H

Company: Siemens AG
 EUT : GSM Modem
 Model / Channel: MD740-1 / Channel 188
 Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
 Test Site / Operator: ETS / Mr. Schostek
 Test Specification: according to §22.917
 Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
 Comment 2: Freq: 7.551GHz, Pmax: -44.93dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 22 SUBPART H

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 188
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Schostek
Test Specification: according to §22.917
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Comment 2: Freq: 7.982GHz, Pmax: -44.15dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 22 SUBPART H

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 188
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Schostek
Test Specification: according to §22.917
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Comment 2: Freq: 10.773GHz, Pmax: -40.88dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 22 SUBPART H

Company: Siemens AG
 EUT : GSM Modem
 Model / Channel: MD740-1 / Channel 188
 Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
 Test Site / Operator: ETS / Mr. Schostek
 Test Specification: according to §22.917
 Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
 Comment 2: Freq: 10.764GHz, Pmax: -40.31dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 22 SUBPART H

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 251
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §22.917
Comment 1: Dist.: 3m, Ant.: HK 116
Comment 2: Freq: 34.533MHz, Pmax: -46.65dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 22 SUBPART H

Company: Siemens AG
 EUT : GSM Modem
 Model / Channel: MD740-1 / Channel 251
 Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
 Test Site / Operator: ETS / Mr. Pfeufer
 Test Specification: according to §22.917
 Comment 1: Dist.: 3m, Ant.: HK 116
 Comment 2: Freq: 80.244MHz, Pmax: -49.79dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 22 SUBPART H

Company: Siemens AG
 EUT : GSM Modem
 Model / Channel: MD740-1 / Channel 251
 Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
 Test Site / Operator: ETS / Mr. Pfeufer
 Test Specification: according to §22.917
 Comment 1: Dist.: 3m, Ant.: HL 223+notch
 Comment 2: Freq: 849.017MHz, Pmax: -19.97dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 22 SUBPART H

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 251
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §22.917
Comment 1: Dist.: 3m, Ant.: HL 223+notch
Comment 2: Freq: 855.947MHz, Pmax: -38.94dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 22 SUBPART H

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 251
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Schostek
Test Specification: according to §22.917
Comment 1: Dist.: 3m, Ant.: HL025
Comment 2: Freq: 1.703GHz, Pmax: -15.51dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 22 SUBPART H

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 251
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Schostek
Test Specification: according to §22.917
Comment 1: Dist.: 3m, Ant.: HL025
Comment 2: Freq: 3.983GHz, Pmax: -22.28dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 22 SUBPART H

Company: Siemens AG
 EUT : GSM Modem
 Model / Channel: MD740-1 / Channel 251
 Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
 Test Site / Operator: ETS / Mr. Schostek
 Test Specification: according to §22.917
 Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
 Comment 2: Freq: 4.244GHz, Pmax: -43.70dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 22 SUBPART H

Company: Siemens AG
 EUT : GSM Modem
 Model / Channel: MD740-1 / Channel 251
 Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
 Test Site / Operator: ETS / Mr. Schostek
 Test Specification: according to §22.917
 Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
 Comment 2: Freq: 7.982GHz, Pmax: -44.23dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 22 SUBPART H

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 251
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Schostek
Test Specification: according to §22.917
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Comment 2: Freq: 10.827GHz, Pmax: -41.06dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 22 SUBPART H

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 251
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Schostek
Test Specification: according to §22.917
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Comment 2: Freq: 10.684GHz, Pmax: -39.94dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
 EUT : GSM Modem
 Model / Channel: MD740-1 / Channel 512
 Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
 Test Site / Operator: ETS / Mr. Pfeufer
 Test Specification: according to §24.238
 Comment 1: Dist.: 3m, Ant.: HK 116
 Comment 2: Freq: 34.722MHz, Pmax: -47.60dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 512
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §24.238
Comment 1: Dist.: 3m, Ant.: HK 116
Comment 2: Freq: 191.500MHz, Pmax: -50.20dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
 EUT : GSM Modem
 Model / Channel: MD740-1 / Channel 512
 Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
 Test Site / Operator: ETS / Mr. Pfeufer
 Test Specification: according to §24.238
 Comment 1: Dist.: 3m, Ant.: HL 223
 Comment 2: Freq: 990.222MHz, Pmax: -39.59dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
 EUT : GSM Modem
 Model / Channel: MD740-1 / Channel 512
 Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
 Test Site / Operator: ETS / Mr. Pfeufer
 Test Specification: according to §24.238
 Comment 1: Dist.: 3m, Ant.: HL 223
 Comment 2: Freq: 868.444MHz, Pmax: -39.31dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 512
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §24.238
Comment 1: Dist.: 3m, Ant.: HL025
Comment 2: Freq: 1.850GHz, Pmax: -20.93dBm, RBW: 1MHz/3kHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
 EUT : GSM Modem
 Model / Channel: MD740-1 / Channel 512
 Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
 Test Site / Operator: ETS / Mr. Pfeufer
 Test Specification: according to §24.238
 Comment 1: Dist.: 3m, Ant.: HL025
 Comment 2: Freq: 3.993GHz, Pmax: -23.21dBm, RBW: 1MHz/3kHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 512
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §24.238
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Comment 2: Freq: 5.556GHz, Pmax: -40.33dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 512
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §24.238
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Comment 2: Freq: 7.404GHz, Pmax: -43.34dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 512
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §24.238
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Comment 2: Freq: 9.253GHz, Pmax: -32.20dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
 EUT : GSM Modem
 Model / Channel: MD740-1 / Channel 512
 Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
 Test Site / Operator: ETS / Mr. Pfeufer
 Test Specification: according to §24.238
 Comment 1: Dist.: 3m, Ant.: HLO25, ampl.+HP.
 Comment 2: Freq: 9.253GHz, Pmax: -30.63dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 512
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §24.238
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Comment 2: Freq: 17.407GHz, Pmax: -31.68dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 512
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §24.238
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Comment 2: Freq: 17.427GHz, Pmax: -31.82dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 512
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §24.238
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Comment 2: Freq: 18.425GHz, Pmax: -26.66dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 512
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §24.238
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Comment 2: Freq: 26.387GHz, Pmax: -26.19dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 661
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §24.238
Comment 1: Dist.: 3m, Ant.: HK 116
Comment 2: Freq: 34.533MHz, Pmax: -47.21dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 661
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §24.238
Comment 1: Dist.: 3m, Ant.: HK 116
Comment 2: Freq: 186.778MHz, Pmax: -50.23dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 661
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §24.238
Comment 1: Dist.: 3m, Ant.: HL 223
Comment 2: Freq: 1000.000MHz, Pmax: -40.08dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 661
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §24.238
Comment 1: Dist.: 3m, Ant.: HL 223
Comment 2: Freq: 884.444MHz, Pmax: -38.81dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 661
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §24.238
Comment 1: Dist.: 3m, Ant.: HL025
Comment 2: Freq: 3.671GHz, Pmax: -23.59dBm, RBW: 1MHz/3kHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
 EUT : GSM Modem
 Model / Channel: MD740-1 / Channel 661
 Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
 Test Site / Operator: ETS / Mr. Pfeufer
 Test Specification: according to §24.238
 Comment 1: Dist.: 3m, Ant.: HL025
 Comment 2: Freq: 3.354GHz, Pmax: -22.86dBm, RBW: 1MHz/3kHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 661
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §24.238
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Comment 2: Freq: 5.644GHz, Pmax: -40.16dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 661
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §24.238
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Comment 2: Freq: 7.520GHz, Pmax: -43.45dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 661
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §24.238
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Comment 2: Freq: 9.404GHz, Pmax: -36.61dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
 EUT : GSM Modem
 Model / Channel: MD740-1 / Channel 661
 Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
 Test Site / Operator: ETS / Mr. Pfeufer
 Test Specification: according to §24.238
 Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
 Comment 2: Freq: 9.404GHz, Pmax: -34.61dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 661
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §24.238
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Comment 2: Freq: 17.467GHz, Pmax: -31.56dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 661
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §24.238
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Comment 2: Freq: 17.427GHz, Pmax: -31.31dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 661
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §24.238
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Comment 2: Freq: 18.349GHz, Pmax: -26.38dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 661
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §24.238
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Comment 2: Freq: 26.358GHz, Pmax: -25.77dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 810
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §24.238
Comment 1: Dist.: 3m, Ant.: HK 116
Comment 2: Freq: 33.589MHz, Pmax: -47.27dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 810
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §24.238
Comment 1: Dist.: 3m, Ant.: HK 116
Comment 2: Freq: 184.322MHz, Pmax: -50.72dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 810
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §24.238
Comment 1: Dist.: 3m, Ant.: HL 223
Comment 2: Freq: 919.111MHz, Pmax: -39.20dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 810
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §24.238
Comment 1: Dist.: 3m, Ant.: HL 223
Comment 2: Freq: 858.667MHz, Pmax: -38.93dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 810
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §24.238
Comment 1: Dist.: 3m, Ant.: HL025
Comment 2: Freq: 1.910GHz, Pmax: -18.85dBm, RBW: 1MHz/3kHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
 EUT : GSM Modem
 Model / Channel: MD740-1 / Channel 810
 Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
 Test Site / Operator: ETS / Mr. Pfeufer
 Test Specification: according to §24.238
 Comment 1: Dist.: 3m, Ant.: HL025
 Comment 2: Freq: 4.000GHz, Pmax: -23.53dBm, RBW: 1MHz/3kHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 810
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §24.238
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Comment 2: Freq: 7.640GHz, Pmax: -35.84dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
 EUT : GSM Modem
 Model / Channel: MD740-1 / Channel 810
 Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
 Test Site / Operator: ETS / Mr. Pfeufer
 Test Specification: according to §24.238
 Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
 Comment 2: Freq: 7.640GHz, Pmax: -40.06dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 810
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §24.238
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Comment 2: Freq: 9.551GHz, Pmax: -32.65dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
 EUT : GSM Modem
 Model / Channel: MD740-1 / Channel 810
 Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
 Test Site / Operator: ETS / Mr. Pfeufer
 Test Specification: according to §24.238
 Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
 Comment 2: Freq: 9.551GHz, Pmax: -34.83dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 810
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §24.238
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Comment 2: Freq: 17.427GHz, Pmax: -31.50dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 810
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §24.238
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Comment 2: Freq: 17.467GHz, Pmax: -31.60dBm, RBW: 1MHz




Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 810
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §24.238
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Comment 2: Freq: 18.009GHz, Pmax: -27.28dBm, RBW: 1MHz



Radiated Emissions Tx
FCC RULES PART 24 SUBPART E

Company: Siemens AG
EUT : GSM Modem
Model / Channel: MD740-1 / Channel 810
Temperature/ Voltage: Temp.: 23°C / Unom.: 24.00 V DC
Test Site / Operator: ETS / Mr. Pfeufer
Test Specification: according to §24.238
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Comment 2: Freq: 19.889GHz, Pmax: -26.69dBm, RBW: 1MHz



Appendix J

Line Conducted Emissions

Appendix K

Frequency Stability vs. Temperature

No diagrams
Refer to point 13.2

Appendix L

Frequency Stability vs. Voltage

No diagrams
Refer to point 14.2