



Electromagnetic Compatibility Test Report

Tests Performed on a Current Works

Side Keys Transmitter, Model SK0418TX

Radiometrics Document RP-5355



Product Detail:

FCC ID: **LYN20TX**

Equipment type: Momentarily Operated Transmitter

Test Standards:

US CFR Title 47, Chapter I, FCC Part 15 Subpart C

FCC Part 15 CFR Title 47: 2004

Industry Canada RSS-210, Issue 5 as required for Category I Equipment

This report concerns: Class II permissive change

FCC Part 15.231

RSS210 Section 6.1; Equipment Modification

Tests Performed For:

Current Works

1000 N. Rand Road Bldg. #122

Wauconda, IL 60084-1199

Test Facility:

Radiometrics Midwest Corporation

12 East Devonwood

Romeoville, IL 60446

Phone: (815) 293-0772

e-mail: info@radiomet.com

Test Date(s): (Month-Day-Year)

September 2, 2004

Document RP-5355 Revisions:

Rev.	Issue Date	Affected Pages	Revised By	Authorized Signature for Revision
0	11/22/2004			
1	11/24/2004	All	Joseph Strzelecki	
2	12/3/2004	1, 3	Joseph Strzelecki	
3	12/3/2004	1, 8	Joseph Strzelecki	
4	1/6/2005	1, 8	Joseph Strzelecki	
5	1/6/2005	All	Joseph Strzelecki	Joseph Strzelecki



Table of Contents

1 ADMINISTRATIVE DATA	3
2 TEST SUMMARY AND RESULTS	3
3 EQUIPMENT UNDER TEST (EUT) DETAILS	3
3.1 EUT Description	3
3.1.1 FCC Section 15.203 & RSS-210 Section 5.5 Antenna Requirements	4
3.2 Related Submittals	4
4 TESTED SYSTEM DETAILS	4
4.1 Tested System Configuration	4
4.2 Special Accessories	4
4.3 Equipment Modifications	4
5 TEST SPECIFICATIONS AND RELATED DOCUMENTS.....	4
6 RADIOMETRICS' TEST FACILITIES	5
7 DEVIATIONS AND EXCLUSIONS FROM THE TEST SPECIFICATIONS.....	5
8 CERTIFICATION	6
9 TEST EQUIPMENT TABLE	6
10 TEST SECTIONS	6
10.1 Radiated RF Emissions	6
10.1.1 Field Strength Calculation.....	7
10.1.2 Radiated Emissions Test Results	8
Figure 1. Drawing of Radiated Emissions Setup	9
10.2 Occupied Bandwidth Data	9
Figure 2. Occupied Bandwidth Plot.....	10
10.3 Peak to Average Calculations	10

Notice: This report must not be reproduced (except in full) without the written approval of Radiometrics Midwest Corporation.

RADIOMETRICS MIDWEST CORPORATION - EMC Test Report
Testing of the Current Works, Model SK0418TX, Side Keys Transmitter

1 ADMINISTRATIVE DATA

<i>Equipment Under Test:</i> A Current Works, Side Keys Transmitter Model: SK0418TX Serial Number: None This will be referred to as the EUT in this Report	
<i>Date EUT Received at Radiometrics: (Month-Day-Year)</i> August 19, 2004	<i>Test Date(s): (Month-Day-Year)</i> September 2, 2004
<i>Test Report Written By:</i> Joseph Strzelecki Senior EMC Engineer	<i>Test Witnessed By:</i> The tests were not witnessed by Current Works
<i>Radiometrics' Personnel Responsible for Test:</i>  Joseph Strzelecki Senior EMC Engineer NARTE EMC-000877-NE	<i>Test Report Approved By</i>  Chris W. Carlson Director of Engineering NARTE EMC-000921-NE

2 TEST SUMMARY AND RESULTS

The EUT (Equipment Under Test) is a Side Keys Transmitter, Model SK0418TX, manufactured by Current Works. The detailed test results are presented in a separate section. The following is a summary of the test results.

Emissions Tests Results

Environmental Phenomena	Frequency Range	Basic Standard	Test Result
RF Radiated Emissions	30-4200 MHz	RSS-210 & FCC Part 15	Pass
Occupied Bandwidth Test	Fundamental Freq.	RSS-210 & FCC Part 15	Pass

3 EQUIPMENT UNDER TEST (EUT) DETAILS

3.1 EUT Description

The EUT is a Side Keys Transmitter, Model SK0418TX, manufactured by Current Works. The EUT was in good working condition during the tests, with no known defects.

RADIOMETRICS MIDWEST CORPORATION - EMC Test Report
Testing of the Current Works, Model SK0418TX, Side Keys Transmitter

3.1.1 FCC Section 15.203 & RSS-210 Section 5.5 Antenna Requirements

There are no power level adjustments and the antenna is permanent. The antenna is a trace on the circuit board.

3.2 Related Submittals

Current Works is not submitting any other products simultaneously for equipment authorization related to the EUT. The associated receiver has not been changed from the original submittal.

4 TESTED SYSTEM DETAILS

4.1 Tested System Configuration

The system was configured for testing in a typical fashion. The EUT was placed on an 80-cm high, nonconductive test stand. The EUT was tested as a stand-alone device. Power was supplied with a new battery. No cables were connected to the EUT.

Tested System Configuration List

Item	Description	Type*	Manufacturer	Model Number	Serial Number
1	Side Keys Transmitter	E	Current Works	SK0418TX	None

* Type: E = EUT

4.2 Special Accessories

No special accessories were used during the tests in order to achieve compliance.

4.3 Equipment Modifications

No modifications were made to the EUT at Radiometrics' test facility in order to comply with the standards listed in this report.

5 TEST SPECIFICATIONS AND RELATED DOCUMENTS

Document	Date	Title
FCC CFR Title 47	2004	Code of Federal Regulations Title 47, Chapter 1, Federal Communications Commission, Part 15 - Radio Frequency Devices
ANSI C63.4-2001	2001	Methods of Measurement of Radio Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
IC RSS-210 Issue 5	2001	Low Power Licence-Exempt Radiocommunication Devices (All Frequency Bands)
IC RSS-212 Issue 1	1998	Test Methods For Radio Equipment

RADIOMETRICS MIDWEST CORPORATION - EMC Test Report

Testing of the Current Works, Model SK0418TX, Side Keys Transmitter

The test procedures used are in accordance with the Industry Canada RSS-212 and ANSI document C63.4-2001, "Methods of Measurement of Radio Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz". The specific procedures are described herein. Radiated testing was performed at an antenna to EUT distance of 3 meters. The antenna was raised and lowered from 1 to 4 meters.

6 RADIOMETRICS' TEST FACILITIES

The results of these tests were obtained at Radiometrics Midwest Corp. in Romeoville, Illinois, USA. Radiometrics is accredited by A2LA (American Association for Laboratory Accreditation) to conform to ISO/IEC 17025: 1999 "General Requirements for the Competence of Calibration and Testing Laboratories". Radiometrics' Lab Code is 121191 and Certification Number is 1495.01. Radiometrics' scope of accreditation includes all of the test methods listed herein. A copy of the accreditation can be accessed on our web site (www.radiomet.com). Radiometrics accreditation status can be verified at A2LA's web site (www.a2la2.net).

The following is a list of shielded enclosures located in Romeoville, Illinois:

Chamber A: Is an anechoic chamber that measures 24' L X 12' W X 12' H. The walls and ceiling are fully lined with ferrite absorber tiles. The floor has a 10' x 10' section of ferrite absorber tiles in the located in the center. Panashield of Rowayton, Connecticut manufactured the chamber. The enclosure is NAMAS certified.

Chamber B: Is a shielded enclosure that measures 24' L X 12' W X 8' H. Erik A. Lindgren & Associates of Chicago, Illinois manufactured the enclosure.

Chamber C: Is a shielded enclosure that measures 20' L X 10' W X 8' H. Lindgren RF Enclosures Inc. of Addison, Illinois manufactured the enclosure.

Chamber D: Is a fully anechoic chamber that measures 22' L X 10' W X 10' H. The walls, ceiling and floor are fully lined with ferrite absorber tiles. Braden Shielding Systems of Tulsa, Oklahoma manufactured the chamber.

A separate ten-foot long, brass plated, steel ground rod attached via a 6 inch copper braid grounds each of the above chambers. Each enclosure is also equipped with low-pass power line filters.

Open Area Test Site (OATS): Is located on 8625 Helmar Road in Newark, Illinois, USA and measures 56' L X 24' W X 17' H. The entire open field test site has a metal ground screen. The FCC has accepted these sites as test site number 31040/SIT 1300F2. The FCC test site Registration Number is 90897. Details of the site characteristics are on file with the Industry Canada as file number IC3124.

A complete list of the test equipment is provided herein. The calibration due dates are indicated on the equipment list. The equipment is calibrated in accordance to ANSI/NCSL Z540-1 with traceability to the National Institute of Standards and Technology (NIST).

7 DEVIATIONS AND EXCLUSIONS FROM THE TEST SPECIFICATIONS

There were no deviations or exclusions from the test specifications.

RADIOMETRICS MIDWEST CORPORATION - EMC Test Report							
Testing of the Current Works, Model SK0418TX, Side Keys Transmitter							

8 CERTIFICATION

Radiometrics Midwest Corporation certifies that the data contained herein was taken under conditions that meet or exceed the requirements of the test specification. The results relate only to the EUT listed herein. Any modifications made to the EUT subsequent to the indicated test date will invalidate the data and void this certification.

9 TEST EQUIPMENT TABLE

RMC ID	Manufacturer	Description	Model No.	Serial No.	Frequency Range	Cal Period	Cal Date
AMP-05	RMC/Celeritek	Pre-amplifier	MW110G	1001	1.0-12GHz	12 Mo.	11/27/03
AMP-22	Anritsu	Pre-amplifier	MH648A	M23969	0.1-1200MHz	12 Mo.	11/25/03
ANT-06	EMCO	Log-Periodic Ant.	3146	1248	200-1000MHz	24 mo	11/17/03
ANT-13	EMCO	Horn Antenna	3115	2502	1.0-18GHz	24 Mo.	09/30/02
ANT-42	EMCO	Bicon Antenna	3104C	9512-4713	25-300MHz	12 Mo.	12/02/03
ANT-44	Impossible Machine	Super Log Antenna	SL-20M2G	1002	20-2000MHz	24 Mo.	06/15/04
REC-01	Hewlett Packard	Spectrum Analyzer	8566A	2106A02115, 2209A01349	30Hz-22GHz	12 Mo.	08/17/04
REC-07	Anritsu	Spectrum Analyzer	MS2601A	MT53067	0.01-2200MHz	12 Mo.	12/29/03
REC-08	Hewlett Packard	Spectrum Analyzer	8566B	2648A13481 2209A01436	30Hz-22GHz	12 Mo.	05/26/04
THM-01	Extech Inst.	Temp/Humid Meter	4465CF	001106557	N/A	24 Mo.	01/28/04

Note: All calibrated equipment is subject to periodic checks.

NCR – No Calibration Required. Device monitored by calibrated equipment. N/A: Not Applicable.

10 TEST SECTIONS

10.1 Radiated RF Emissions

Radiated emission measurements were performed with linearly polarized broadband antennas. The results obtained with these antennas can be correlated with results obtained with a tuned dipole antenna. Below 1 GHz, when a radiated emission is detected approaching the specification limit, the measurement of the emission is repeated using a tuned dipole antenna with a Roberts Balun.

The radiated emission measurements were performed with a spectrum analyzer. The bandwidth used from 450 kHz to 30 MHz is 9 or 10 kHz and the bandwidth from 30 MHz to 1000 MHz is 100 or 120 kHz. Above 1 GHz, a 1 MHz bandwidth is used. A 10 dB linearity check is performed prior to start of testing in order to determine if an overload condition exists.

From 30 to 1000 MHz an Anritsu Spectrum analyzer and a MITEQ AM-1431 amplifier with a 10 dB attenuator connected to the input. The out of band emissions and the ambient emissions were below the level of input overload (80 dBuV).

For tests from 1 to 4.2 GHz, an HP8566A spectrum analyzer was used with a Celeritek uWave amplifier. The fundamental emission, out of band emissions and the ambient emissions were below the level of input overload (72 dBuV).

Preliminary radiated emission tests were performed inside of an anechoic enclosure. The frequency range from 30 to 4200 MHz was scanned and plotted using the peak detector function. The test antennas were positioned 3 meters from the EUT. The results of the preliminary scans were only used to identify the frequencies being emitted from the EUT and were not used to determine compliance with the test specification. Radiated emission measurements are performed with linearly polarized broadband antennas.

Final radiated emissions measurements were performed in the open area test site at a test distance of 3 meters. Measurements were performed using the peak or quasi-peak detector function. The detected emission levels were maximized by rotating the EUT, adjusting the positions of all cables, and by scanning the measurement antenna from 1 to 4 meters above the ground. The open area test site used to collect the radiated data is located on 8625 Helmar Road in Newark, Illinois. The open field test site has a metal ground screen. All other tests are performed at 12 East Devonwood Ave. Romeoville, Illinois EMI test lab.

The was device was rotated through three orthogonal axis as per 13.1.4.1 of ANSI C63.4 during the prescans and during final radiated tests.

The entire frequency range from 30 to 4200 MHz was slowly scanned with particular attention paid to those frequency ranges which appeared high in the preliminary emission scan. Measurements were performed using two antenna polarizations, (vertical and horizontal). The worst case emissions were recorded.

10.1.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Loss, and by subtracting the Amplifier Gain from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG + PKA$$

Where: FS = Field Strength

RA = Receiver Amplitude

AF = Antenna Factor

CF = Cable Attenuation Factor

AG = Amplifier Gain

PKA = Peak to Average Factor (This is zero for non-average measurements)

The Peak to Average factor is used when average measurements are required. It is calculated by the highest duty cycle in percent over any 100mS transmission. The factor in dB is $20 * \text{Log}(\text{Duty cycle}/100)$.

RADIOMETRICS MIDWEST CORPORATION - EMC Test Report	
Testing of the Current Works, Model SK0418TX, Side Keys Transmitter	

10.1.2 Radiated Emissions Test Results


Test Date	9/2/2004
Test Distance	3 Meters
Specification	FCC Part 15 Subpart C & RSS-210
Abbreviations	Pol = Antenna Polarization; V = Vertical; H = Horizontal; BC = Biconical (ANT-3); LP = Log-Periodic (ANT-6); HN = Horn (ANT-13) P = peak; Q = QP
Notes	A 30 dB preamp was used above 1 GHz, and a 20 dB preamp was used below 1 GHz

Freq. MHz	Peak Meter Rdg dBuV	Antenna		Peak to Ave. factor dB	Cable & Preamp dB	Average Field Strength dBuV/m		Margin Under Limit dB
		Factor dB	Pol/ ID			EUT	Limit	
418.0	95.8	16.6	H/44	-20.4	-14.7	77.3	80.3	3.0
836.0	46.1	22.2	H/44	-20.4	-11.5	36.4	60.3	23.9
418.0	94.3	16.3	V/44	-20.4	-14.7	75.5	80.3	4.8
836.0	44.9	20.6	V/44	-20.4	-11.5	33.6	60.3	26.7
1254.0	59.7	25.9	H/13	-20.4	-27.3	37.9	60.3	22.4
1672.0	67.4	27.6	H/13	-20.4	-27.0	47.6	54.0	6.4
2090.0	52.6	29.6	H/13	-20.4	-26.2	35.6	54.0	18.4
2508.0	51.3	30.9	H/13	-20.4	-26.0	35.8	54.0	18.2
2926.0	42.9	31.6	H/13	-20.4	-25.5	28.6	54.0	25.4
4180.0	41.0	34.9	H/13	-20.4	-24.7	30.8	54.0	23.2
1254.0	64.2	25.9	V/13	-20.4	-27.3	42.4	60.3	17.9
1672.0	69.3	27.6	V/13	-20.4	-27.0	49.5	54.0	4.5
2090.0	57.6	29.6	V/13	-20.4	-26.3	40.5	54.0	13.5
2508.0	54.3	30.9	V/13	-20.4	-26.2	38.6	54.0	15.4
2926.0	41.8	31.6	V/13	-20.4	-25.8	27.2	54.0	26.8

Freq. MHz	Peak Meter Rdg dBuV	Antenna		Peak to Ave. factor dB	Cable & Preamp dB	Peak Field Strength dBuV/m		Margin Under Limit dB
		Factor dB	Pol/ ID			EUT	Limit	
418.0	95.8	16.6	H/44	0.0	-14.7	97.7	100.3	2.6
836.0	46.1	22.2	H/44	0.0	-11.5	56.8	80.3	23.5
418.0	94.3	16.3	V/44	0.0	-14.7	95.9	100.3	4.4
836.0	44.9	20.6	V/44	0.0	-11.5	54.0	80.3	26.3
1254.0	59.7	25.9	H/13	0.0	-27.3	58.3	80.3	22.0
1672.0	67.4	27.6	H/13	0.0	-27.0	68.0	74.0	6.0
2090.0	52.6	29.6	H/13	0.0	-26.2	56.0	74.0	18.0
2508.0	51.3	30.9	H/13	0.0	-26.0	56.2	74.0	17.8
2926.0	42.9	31.6	H/13	0.0	-25.5	49.0	74.0	25.0
4180.0	41.0	34.9	H/13	0.0	-24.7	51.2	74.0	22.8
1254.0	64.2	25.9	V/13	0.0	-27.3	62.8	80.3	17.5
1672.0	69.3	27.6	V/13	0.0	-27.0	69.9	74.0	4.1
2090.0	57.6	29.6	V/13	0.0	-26.3	60.9	74.0	13.1
2508.0	54.3	30.9	V/13	0.0	-26.2	59.0	74.0	15.0
2926.0	41.8	31.6	V/13	0.0	-25.8	47.6	74.0	26.4


Judgment: Passed by 2.6 dB

Figure 1. Drawing of Radiated Emissions Setup



Notes:

- AC outlet with low-pass filter at the base of the turntable
- Antenna height varied from 1 to 4 meters
- Distance from antenna to tested system is 3 meters
- Not to Scale




10.2 Occupied Bandwidth Data

The occupied bandwidth of the RF output was measured using a spectrum analyzer. The bandwidth was measured using the peak detector function and a narrow resolution bandwidth.

A broadband antenna was used to receive the modulated signal. The spectrum analyzer was set to the MAX HOLD mode to record the worst case of the modulation. The spectrum analyzer display was digitized and plotted. The plots of the occupied bandwidth for the EUT are supplied on the following page.

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. Bandwidth is determined at the points 20 dB down from the modulated carrier.

Figure 2. Occupied Bandwidth Plot



In accordance with 15.231, the 20 dB bandwidth is to be less than 1.045 MHz.

10.3 Peak to Average Calculations

As required by section 15.35, the Peak to Average correction factor was calculated with the data supplied by the EUT designer. Using a spectrum analyzer, it was verified that the duty cycle was the same for the fundamental and the harmonics. Therefore the peak to average factor is the same for the transmitter fundamental and harmonics.

RADIOMETRICS MIDWEST CORPORATION - EMC Test Report

Testing of the Current Works, Model SK0418TX, Side Keys Transmitter

