



FCC 47 CFR PART 15 SUBPART C AND ANSI C63.4 : 2003

TEST REPORT

For

802.11 a/b/g Mini PCI Card

Model : AG-621

Trade Name : ZCOM

Issued for

Z-Com, Inc.

7F-2, No. 9. Prosperity RD.I Science-Based Industrial,

Park Hsinchu, 300 Taiwan

Issued by

Compliance Certification Services Inc.

Hsinchu Lab.

Rm. 258, Bldg. 17, NO.195, Sec.4 Chung Hsing Rd.,
Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C

TEL: (03) 591-0068

FAX: (03) 582-5720



Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. Ltd. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document.



TABLE OF CONTENTS

TITLE	PAGE NO.
1. TEST REPORT CERTIFICATION.....	3
2. EUT DESCRIPTION.....	4
2.1 DESCRIPTION OF EUT & POWER.....	4
3. DESCRIPTION OF TEST MODES.....	5
4. TEST METHODOLOGY.....	6
5. FACILITIES AND ACCREDITATIONS.....	6
5.1 FACILITIES	6
5.2 EQUIPMENT	6
5.3 LABORATORY ACCREDITATIONS LISTINGS.....	6
5.4 TABLE OF ACCREDITATIONS AND LISTINGS	7
6. CALIBRATION AND UNCERTAINTY.....	8
6.1 MEASURING INSTRUMENT CALIBRATION	8
6.2 MEASUREMENT UNCERTAINTY.....	8
7. SETUP OF EQUIPMENT UNDER TEST.....	9
8. APPLICABLE LIMITS AND TEST RESULTS	11
8.1 6dB BANDWIDTH	11-19
8.2 99% BANDWIDTH	20-28
8.3 MAXIMUM PEAK OUTPUT POWER.....	29-37
8.4 MAXIMUM PERMISSIBLE EXPOSURE	38-39
8.5 POWER SPECTRAL DENSITY.....	40-49
8.6 CONDUCTED SPURIOUS EMISSION.....	50-57
8.7 RADIATED EMISSIONS.....	58
8.7.1 TRANSMITTER RADIATED SUPURIOUS EMSSIONS	58-61
8.7.2 WORST-CASE RADIATED EMISSION BELOW 1 GHz	62
8.7.3 TRANSMITTER RADIATED EMISSION ABOVE 1 GHz.....	63-72
8.7.4 RESTRICTED BAND EDGES	73-84
8.8 POWERLINE CONDUCTED EMISSIONS	85-88
9. ANTENNA REQUIREMENT.....	89
9.1 STANDARD APPLICABLE.....	89
9.2 ANTENNA CONNECTED CONSTRUCTION	89
APPENDIX SETUP PHOTOS.....	90-94



1. TEST REPORT CERTIFICATION

Applicant : Z-Com Inc.
Address : 7F-2, No. 9. Prosperity RD.I Science-Based Industrial
Park, Hsinchu, Taiwan R.O.C.
Equipment Under Test : 802.11 a/b/g Mini PCI Card
Model : AG-621
Trade Name : ZCOM
Tested Date : March 16 ~ April 11, 2006

APPLICABLE STANDARD	
STANDARD	TEST RESULT
FCC Part 15 Subpart C:2004 AND ANSI C63.4:2003	No non-compliance noted

Approved by:

Reviewed by:

C. F. Wu

C. F. Wu
Manager of Hsinchu Laboratory
Compliance Certification Services Inc.



Alan Pan

Alan Pan
Test Engineer of Hsinchu Laboratory
Compliance Certification Services Inc.

WE HEREBY CERTIFY THAT: The measurements shown in the attachment were made in accordance with the procedures indicated, and the energy emitted by the equipment was found to be within the limits applicable. We assume full responsibility for the accuracy and completeness of these measurements and vouch for the qualifications of all persons taking them.



2. EUT DESCRIPTION

2.1 DESCRIPTION OF EUT & POWER

Product Name	802.11 a/b/g Mini PCI Card
Model Number	AG-621
Frequency Range	IEEE 802.11a (DTS Band) Base mode : 5745MHz~5825MHz IEEE 802.11b/g (DTS Band) Base mode : 2412MHz~2462MHz IEEE 802.11g (DTS Band) Turbo mode : 2437MHz
Transmit Power (ERP)	IEEE 802.11a Base mode : 23.06dBm IEEE 802.11b : 24.54dBm IEEE 802.11g Base mode : 27.25dBm , Turbo mode : 20.87dBm
Channel Spacing	IEEE 802.11a Base mode : 20MHz IEEE 802.11b/g Base mode : 5MHz
Channel Number	IEEE 802.11a Base mode : 5 Channels IEEE 802.11b/g Base mode : 11 Channels IEEE 802.11g Turbo mode : 1 Channel
Transmit Data Rate	IEEE 802.11a: 54, 48 ,36, 24, 18, 12, 9, 6Mbps IEEE 802.11b:11, 5.5, 2, 1Mbps IEEE 802.11g : 54, 48 ,36, 24, 18, 12, 11, 9, 6, 5.5, 2, 1Mbps IEEE 802.11g Turbo : 108, 96, 72, 48 ,36, 24, 18, 12, 11, 5.5, 2, 1Mbps
Type of Modulation	IEEE 802.11a : OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11b : DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g : DSSS/OFDM (64QAM, 16QAM, QPSK, BPSK, CCK, DQPSK, DBPSK)
Frequency Selection	by software / firmware
Antenna Type	Dipole Antenna, Antenna Gain : 2dBi at 2.4GHz, 2dBi at 5GHz. (ARISTOTLE ENTERPRISES INC. Model No:RFA-25-C2M2) Connector type: Reverse SMA PLUG
Power Source	3.3VDC (From Notebook PC ,Powered From Host Device)

Remark:

1. The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.
2. This submittal(s) (test report) is intended for FCC ID: M4Y-0AG621 filing to comply with Section 15.207,15.209 and 15.247 of the FCC Part 15, Subpart C Rules.



3. DESCRIPTION OF TEST MODES

The EUT had been tested under operating condition.

IEEE 802.11a Base mode (DTS Band)

There are three channels have been tested as following :

Channel	Frequency (MHz)
Low	5745
Middle	5785
High	5825

IEEE 802.11a base mode : 6Mbps data rate (worst case) were chosen for full testing.

IEEE 802.11b/g mode (DTS Band)

There are three channels have been tested as following :

Channel	Frequency (MHz)
Low	2412
Middle	2437
High	2462

IEEE 802.11b base mode : 11Mbps data rate (worst case) were chosen for full testing.

IEEE 802.11g base mode : 6Mbps data rate (worst case) were chosen for full testing.

IEEE 802.11g turbo mode (DTS Band)

There is one channel have been tested as following :

Channel	Frequency (MHz)
Middle	2437

IEEE 802.11g turbo mode : 12Mbps data rate (worst case) were chosen for full testing.



4. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4 and FCC CRF 47 2.1046, 2046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055, 2.1057, 15.207, 15.209 and 15.247.

5. FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at Rm.258, Bldg.17, NO.195 , Sec. 4, Chung Hsing Rd., Chu-Tung Chen. Hsin-Chu, Taiwan 310 R.O.C.

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with preselectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5.3 LABORATORY ACCREDITATIONS LISTINGS

The test facilities used to perform radiated and conducted emissions tests are accredited by National Voluntary Laboratory Accreditation Program for the specific scope of accreditation under Lab Code: 200118-0 to perform Electromagnetic Interference tests according to FCC PART 15 AND CISPR 22 requirements. No part of this report may be used to claim or imply product endorsement by NVLAP or any agency of the US Government. In addition, the test facilities are listed with Federal Communications Commission (registration no: 90585 and 90584).



5.4 TABLE OF ACCREDITATIONS AND LISTINGS

Country	Agency	Scope of Accreditation	Logo
USA	NVLAP	EN 55014-1, AS/NZS 1044, CNS 13783-1, IEC/CISPR 14-1, IEC/CISPR 22, EN 55022, EN 61000-3-2, EN 61000-3-3, ANSI C63.4, AS/NZS CISPR 22, AS/NZS 3548, IEC 61000-4-2/3/4/5/6/8/11	 200118-0
USA	FCC	3/10 meter Open Area Test Sites to perform FCC Part 15/18 measurements	 90585, 90584
Japan	VCCI	3/10 meter Open Area Test Sites to perform conducted/radiated measurements	 R-1229/1189 C-1250/1294
Taiwan	CNLA	FCC Method-47 CFR Part 15 Subpart C,D,E CISPR 11, FCC METHOD-47 CFR Part 18, EN 55011, CNS 13803, CISPR 13, CNS 13439, FCC Method-47 CFR Part 15 Subpart B, CISPR 14-1, EN 55014-1, CNS 13783-1, EN 55015, CNS 14115, CISPR 22, EN 55022, VCCI CNS 13438, EN 61000-4-2/3/4/5/6/8/11	 Testing Laboratory 0240
Taiwan	BSMI	CNS 13803, CNS 13438, CNS 13439, CNS 13783-1, CNS 14115	 SL2-IS-E-0002 SL2-IN-E-0002 SL2-A1-E-0002 SL2-R1-E-0002 SL2-R2-E-0002 SL2-L1-E-0002
Canada	Industry Canada	RSS212, Issue 1	 IC 4417-1

* No part of this report may be used to claim or imply product endorsement by NVLAP or any agency of the US Government.



6. CALIBRATION AND UNCERTAINTY

6.1 MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

6.2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Radiated Emission, 30 to 1000 MHz	+/- 3.2 dB
Radiated Emission, 1 to 26.5 GHz	+/- 3.2 dB
Power Line Conducted Emission	+/- 2.1 dB

Uncertainty figures are valid to a confidence level of 95%




7. SETUP OF EQUIPMENT UNDER TEST

SUPPORT EQUIPMENT


No.	Product	Manufacturer	Model No.	Serial No.	FCC ID
1	Notebook PC	DELL	Latitude D610	CN-0C4708-48643-625-5565	DoC
2	Notebook PC	HP	nx6130	CNU543274R	DoC
3	Wireless Access Point	D-Link	DWL-7100AP	DQ6114B00002	KA22003040018-1
4	Modem	ZyXEL	Omni 56K	S1Z4107727	1880MN156K
5	Printer	HP	hp desk jet 948c	CN19S6S1XS	DoC

SETUP DIAGRAM FOR TESTS



On table

Under table



**EUT OPERATING CONDITION**

1. Set up all computers like the setup diagram.
2. The “**Atheros Radio Test <ART> Revision 4.6 BUILD #6**” software was used for testing.

(1) TX Mode:

- ⇒ **Tx Data Rate: 11Mbps long** (IEEE 802.11b base mode)
6Mbps (IEEE 802.11a/g base mode)
12Mbps (IEEE 802.11g turbo mode)
- ⇒ **Toggle output mode = TX99**
- ⇒ **Target Power:** IEEE 802.11a mode (DTS) Channel Low (5745MHz) = **14.5**
IEEE 802.11a mode (DTS) Channel Middle (5785MHz) = **14.5**
IEEE 802.11a mode (DTS) Channel High (5825MHz) = **14.5**
Target Power: IEEE 802.11b mode (DTS) Channel 1 (2412MHz) = **16**
IEEE 802.11b mode (DTS) Channel 6 (2437MHz) = **20**
IEEE 802.11b mode (DTS) Channel 11 (2462MHz) = **16**
Target Power: IEEE 802.11g mode (DTS) Channel 1 (2412MHz) = **10**
IEEE 802.11g mode (DTS) Channel 6 (2437MHz) = **18.5**
IEEE 802.11g mode (DTS) Channel 11 (2462MHz) = **10**
- ⇒ **“ b “ => Toggle turbo mode**
Target Power: IEEE 802.11g Turbo mode (DTS) Channel 6 (2437MHz) = **13**

(2) RX Mode :

- ⇒ **Continuous RF <R>eceive mode**

3. All of the function are under run.
4. Start test.

For Normal operating :

1. Set up all computers like the setup diagram.
2. Notebook PC (2) ping 192.168.0.10 -t -l 5000 to Notebook PC(1)
3. Notebook PC (1) ping 192.168.0.20 -t -l 5000 to Notebook PC(2)
4. All of the function are under run.
5. Start test.



8. APPLICABLE LIMITS AND TEST RESULTS

8.1 6dB BANDWIDTH


LIMIT

§ 15.207(a) (2) For direct sequence systems, the minimum 6dB bandwidth shall be at least 500kHz

TEST EQUIPMENTS

Description & Manufacturer	Model No.	Serial No.	Date of Calibration
ROHDE & SCHWARZ SPECTRUM ANALYZER	FSEK30	835253/002	September 24, 2005
AGILENT SPECTRUM ANALYZER	E4446A	MY433601.32	March 22, 2006

TEST SETUP



TEST PROCEDURE

The transmitter output was connected to a spectrum analyzer. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 KHz RBW and 300 KHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

**TEST RESULTS**

No non-compliance noted

IEEE 802.11b mode


Channel	Channel Frequency (MHz)	6dB Bandwidth (kHz)	Minimum Limit (kHz)	Pass / Fail
Low	2412	12150	500	PASS
Middle	2437	11650	500	PASS
High	2462	11650	500	PASS


IEEE 802.11g mode


Channel	Channel Frequency (MHz)		6dB Bandwidth (kHz)	Minimum Limit (kHz)	Pass / Fail
Low	Base mode	2412	16350	500	PASS
Middle		2437	15850	500	PASS
High		2462	16300	500	PASS
Middle	Turbo mode	2437	32550	500	PASS


IEEE 802.11a mode

Channel	Channel Frequency (MHz)	6dB Bandwidth (kHz)	Minimum Limit (kHz)	Pass / Fail
Low	5745	16400	500	PASS
Middle	5785	16350	500	PASS
High	5825	16500	500	PASS

**6dB BANDWIDTH (802.11b MODE)**






**6dB BANDWIDTH (802.11g MODE)**






6dB BANDWIDTH (802.11g Turbo MODE)



**6dB BANDWIDTH (802.11a MODE)**





8.2 99% BANDWIDTH

LIMIT

None; for reporting purposes only.

TEST EQUIPMENTS

Description & Manufacturer	Model No.	Serial No.	Date of Calibration
ROHDE & SCHWARZ SPECTRUM ANALYZER	FSEK30	835253/002	September 24, 2005
AGILENT SPECTRUM ANALYZER	E4446A	MY433601.32	March 22, 2006

TEST SETUP



TEST PROCEDURE

1. The spectrum shall be set as follows :

Span : The minimum span to fully display the emission and approximately 20dB below peak level.

RBW : The set to 1% to 3% of the approximate emission width.

2. Compute the combined power of all signal responses contained in the trace by covering all the data points.
3. For 99% occupied BW, place the markers at the frequency at which 0.5% of the power lies to the right of the right marker and 0.5% of the power lies to the left of the left marker.
4. The 99% BW is the bandwidth between the right and left markers.

**TEST RESULTS**

No non-compliance noted

IEEE 802.11b mode



Channel	Channel Frequency (MHz)	99% Occupied power bandwidth (MHz)
Low	2412	15.33
Middle	2437	15.41
High	2462	15.37


IEEE 802.11g mode



Channel	Channel Frequency (MHz)		99% Occupied power bandwidth (MHz)
Low	Base mode	2412	16.82
Middle		2437	20.02
High		2462	16.75
Middle	Turbo mode	2437	33.56


IEEE 802.11a mode


Channel	Channel Frequency (MHz)	99% Occupied power bandwidth (MHz)
Low	5745	17.23
Middle	5785	17.48
High	5825	18.37



**99% BANDWIDTH (802.11b MODE)**




**99% BANDWIDTH (802.11g MODE)**



**99% BANDWIDTH (802.11g Turbo MODE)**

**99% BANDWIDTH (802.11a MODE)**





8.3 MAXIMUM PEAK OUTPUT POWER

LIMIT

§ 15.247(b) The maximum peak output power of the intentional radiator shall not exceed the following :


§ 15.247(b) (3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands : 1 watt.

§ 15.247(b) (4) Except as shown in paragraphs (c) of this section , if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2), and (b)(3) of this section , as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

TEST EQUIPMENTS

Description & Manufacturer	Model No.	Serial No.	Date of Calibration
ROHDE & SCHWARZ SPECTRUM ANALYZER	FSEK30	835253/002	September 24, 2005
AGILENT SPECTRUM ANALYZER	E4446A	MY433601.32	March 22 ,2006

TEST SETUP



TEST PROCEDURE

1. The spectrum shall be set as follows :
Span : 1.5 times channel integration bandwidth.
RBW : 1MHz
VBW : 3MHz
Detector : Peak
Sweep : Single trace
2. Compute the combined power of all signal responses contained in the trace by covering all the data points.
3. For 99% occupied BW, place the markers at the frequency at which 0.5% of the power lies to the right of the right marker and 0.5% of the power lies to the left of the left marker.
4. The peak output power is the channel power integrated over 99% bandwidth.

**TEST RESULTS****IEEE 802.11b mode**

Channel	Channel Frequency (MHz)	Peak Power Output Reading (dBm)	Factor Cable loss (dB)	Peak Power Output (dBm)	Peak Power Limit (dBm)	Pass / Fail
Low	2412	8.29	11.5	19.79	30	PASS
Middle	2437	13.04	11.5	24.54	30	PASS
High	2462	9.66	11.5	21.16	30	PASS

Remark:

1. At final test to get the worst-case emission at 6Mbps. (for Base mode)
2. The result basic equation calculation as follow : Peak Power Output = Peak Power Reading + Cable loss

IEEE 802.11g mode

IEEE 802.11g mode							
Channel	Channel Frequency (MHz)		Peak Power Output Reading (dBm)	Factor Cable loss (dB)	Peak Power Output (dBm)	Peak Power Limit (dBm)	Pass / Fail
Low	Base mode	2412	6.41	11.5	17.91	30	PASS
Middle		2437	15.75	11.5	27.25	30	PASS
High		2462	6.66	11.5	18.16	30	PASS
Middle	Turbo mode	2437	9.37	11.5	20.87	30	PASS

Remark:



1. At final test to get the worst-case emission at 6Mbps. (for Base mode)
2. At final test to get the worst-case emission at 12Mbps. (for Turbo mode)
3. The result basic equation calculation as follow : Peak Power Output = Peak Power Reading + Cable loss


IEEE 802.11a mode


Channel	Channel Frequency (MHz)	Peak Power Output Reading (dBm)	Factor Cable loss (dB)	Peak Power Output (dBm)	Peak Power Limit (dBm)	Pass / Fail
Low	5745	11.05	11.5	22.55	30	PASS
Middle	5785	10.88	11.5	22.38	30	PASS
High	5825	11.56	11.5	23.06	30	PASS


Remark:

1. At final test to get the worst-case emission at 6Mbps. (for Base mode)
2. The result basic equation calculation as follow : Peak Power Output = Peak Power Reading + Cable loss

**MAXIMUM PEAK OUTPUT POWER (802.11b MODE)**






**MAXIMUM PEAK OUTPUT POWER (802.11g MODE)**






MAXIMUM PEAK OUTPUT POWER (802.11g Turbo MODE)



**MAXIMUM PEAK OUTPUT POWER (802.11a MODE)**





8.4 MAXIMUM PERMISSIBLE EXPOSURE

According to FCC 1.1310 : The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b) LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time
(A) Limits for Occupational / Control Exposures				
300-1,500	--	--	F/300	6
1,500-100,000	--	--	5	6
(B) Limits for General Population / Uncontrol Exposures				
300-1,500	--	--	F/1500	6
1,500-100,000	--	--	1	30

CALCULATIONS

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{3770}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770 d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

**LIMIT**

Power Density Limit, $S=1.0\text{mW/cm}^2$

TEST RESULTS

No non-compliance noted

Mode	Minimum separation distance (cm)	Output Power (dBm)	Antenna Gain (dBi)	Power Density Limit (mW/cm^2)	Power Density at 20cm (mW/cm^2)
IEEE 802.11a	20.0	23.06	2	1.00	0.063787
IEEE 802.11b	20.0	24.54	2	1.00	0.089687
IEEE 802.11g	20.0	27.25	2	1.00	0.167390

Remark: For mobile or fixed location transmitters, the maximum power density is 1.0 mW/cm^2 even if the calculation indicates that the power density would be larger.



8.5 POWER SPECTRAL DENSITY


LIMIT

§ 15.247(e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

TEST EQUIPMENTS

Description & Manufacturer	Model No.	Serial No.	Date of Calibration
ROHDE & SCHWARZ SPECTRUM ANALYZER	FSEK30	835253/002	September 24, 2005
AGILENT SPECTRUM ANALYZER	E4446A	MY433601.32	March 22, 2006

TEST SETUP



TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using $RBW = 3\text{KHz}$ and $VBW \geq RBW$, set sweep time = span / 3KHz.

The power spectral density was measured and recorded.

The sweep time is allowed to be longer than span / 3KHz for a full response of the mixer in the spectrum analyzer.

**TEST RESULTS**

No non-compliance noted

IEEE 802.11b mode

Channel	Channel Frequency (MHz)	Reading (dBm)	Factor Cable loss (dB)	Final RF Power Level in 3KHz BW (dBm)	Maximum Limit (dBm)	Pass / Fail
Low	2412	-16.54	11.5	-5.04	8	PASS
Middle	2437	-15.73	11.5	-4.23	8	PASS
High	2462	-18.65	11.5	-7.15	8	PASS

Remark:

1. At final test to get the worst-case emission at 11Mbps.
2. The result basic equation calculation as follow : Average Power Output = Average Power Reading + Cable loss

IEEE 802.11g mode

Channel	Channel Frequency (MHz)		Reading (dBm)	Factor Cable loss (dB)	Final RF Power Level in 3KHz BW (dBm)	Maximum Limit (dBm)	Pass / Fail
Low	Base mode	2412	-25.30	11.5	-13.80	8	PASS
Middle		2437	-16.47	11.5	-4.97	8	PASS
High		2462	-24.93	11.5	-13.43	8	PASS
Middle	Turbo mode	2437	-22.10	11.5	-10.60	8	PASS

Remark:



1. At final test to get the worst-case emission at 6Mbps.(for Base mode)
2. At final test to get the worst-case emission at 12Mbps. (for Turbo mode)
3. The result basic equation calculation as follow : Average Power Output = Average Power Reading + Cable loss


**IEEE 802.11a mode**


Channel	Channel Frequency (MHz)	Reading (dBm)	Factor Cable loss (dB)	Final RF Power Level in 3KHz BW (dBm)	Maximum Limit (dBm)	Pass / Fail
Low	5745	-21.90	11.5	-10.40	8	PASS
Middle	5785	-22.15	11.5	-10.65	8	PASS
High	5825	-21.02	11.5	-9.52	8	PASS


Remark:

1. At final test to get the worst-case emission at 6Mbps.(for Base mode)
2. The result basic equation calculation as follow : Average Power Output = Average Power Reading + Cable loss

**POWER SPECTRAL DENSITY (IEEE 802.11b MODE)**






**POWER SPECTRAL DENSITY (IEEE 802.11g MODE)**






POWER SPECTRAL DENSITY (IEEE 802.11g Turbo MODE)



**POWER SPECTRAL DENSITY (IEEE 802.11a MODE)**





8.6 CONDUCTED SPURIOUS EMISSION

LIMITS

§ 15.247(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.

The spectrum from 30 MHz to 26.5 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.


The spectrum from 30 MHz to 40 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 5 GHz band.


TEST RESULTS

No non-compliance noted




OUT-OF-BAND SPURIOUS EMISSIONS-CONDUCTED MEASUREMENT (IEEE 802.11b MODE)









OUT-OF-BAND SPURIOUS EMISSIONS-CONDUCTED MEASUREMENT (802.11g MODE)









OUT-OF-BAND SPURIOUS EMISSIONS-CONDUCTED MEASUREMENT (IEEE 802.11g Turbo MODE)





OUT-OF-BAND SPURIOUS EMISSIONS-CONDUCTED MEASUREMENT (IEEE 802.11a MODE)







8.7 RADIATED EMISSIONS

8.7.1 TRANSMITTER RADIATED SUPURIOUS EMSSIONS

LIMITS

§ 15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3338	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)
13.36 - 13.41			

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

§ 15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.



§ 15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table :

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 - 88	100 **	3
88 - 216	150 **	3
216 - 960	200 **	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz, However, operation within these frequency bands is permitted under other sections of this Part, e-g, Sections 15.231 and 15.241.

§ 15.209 (b) In the emission table above, the tighter limit applies at the band edges.


TEST EQUIPMENTS

The following test equipments are utilized in making the measurements contained in this report.


Manufacturer or Type	Model No.	Serial No.	Date of Calibration	Calibration Period	Remark
CHASE BI-LOG ANTENNA	CBL6112B	2817	March 22, 2006	1 Year	FINAL
R/S SPECTRUM ANALYZER	FSEK30	835253/002	September 24, 2005	1 Year	FINAL
AGILENT SPECTRUM ANALYZER	E4446A	MY433601.32	March 22, 2006	1 Year	FINAL
R/S EMI TEST RECEIVER	ESCS30	835418/008	August 24, 2005	1 Year	FINAL
OPEN SITE	-----	No.2	May 07, 2005	1 Year	FINAL
N TYPE COAXIAL CABLE	9913-30M	-----	July 28, 2005	1 Year	FINAL
Horn Antenna	AH-118	10089	August 10, 2005	1 Year	FINAL
Horn Antenna	AH-840	03077	February 25, 2006	1 Year	FINAL
Agilent Pre-amplifier	8449B	3008A01471	December 07, 2005	1 Year	FINAL
HP Amplifier	8447D	1937A02748	December 07, 2005	1 Year	FINAL
HP High pass filter	84300/80038	002	CAL. ON USE	1 Year	FINAL
HP High pass filter	84300/80039	003	CAL. ON USE	1 Year	FINAL

TEST SETUP

The diagram below shows the test setup that is utilized to make the measurements for emission from 30 to 1GHz.



The diagram below shows the test setup that is utilized to make the measurements for emission above 1GHz.





TEST PROCEDURE

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarization of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Note :

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 KHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection and frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.

TEST RESULTS

No non-compliance noted



8.7.2 WORST-CASE RADIATED EMISSION BELOW 1 GHz

Product Name	802.11 a/b/g Mini PCI Card	Test Date	2006/04/08
Model	AG-621	Test By	Alan Fan
Test Mode	Normal operating	TEMP & Humidity	24°C, 79%

Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading at 3m(dBμV)		Limits (dBμV/m)	Emission Level at 3m(dBμV/m)	
			Horizontal	Vertical		Horizontal	Vertical
181.24	10.36	1.71	19.50	19.10	43.50	31.56	31.16
313.25	14.57	2.24	10.00	6.70	46.00	26.81	23.51
350.00	15.60	2.38	16.20	7.30	46.00	34.18	25.28
399.99	17.00	2.57	23.70	19.30	46.00	43.27	38.87
499.99	18.80	2.88	5.60	5.00	46.00	27.28	26.68
864.24	22.18	3.98	14.00	10.00	46.00	40.16	36.16

Remark: Emission level (dBμV/m) =Antenna Factor (dB/m) + Cable loss (dB) + Meter Reading (dBμV).



8.7.3 TRANSMITTER RADIATED EMISSION ABOVE 1 GHz

Product Name	802.11 a/b/g Mini PCI Card	Test Date	2006/04/08
Model	AG-621	Test By	Alan Fan
Test Mode	IEEE 802.11b TX (CH Low)	TEMP & Humidity	24°C, 79%

Measurement Distance at 3m Horizontal polarity										
Freq. (MHz)	Reading (dBμV)	AF (dBμV)	Cable (dB)	Pre-amp (dB)	Filter (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Mark (P/Q/A)	Height (Meter)
1459.93	45.00	26.64	3.54	35.15	0.00	40.04	74.00	-33.96	P	1.00
1459.93	32.18	26.64	3.54	35.15	0.00	27.22	54.00	-26.78	A	1.00
4824.02	49.25	34.02	6.32	35.30	0.35	54.63	74.00	-19.37	P	1.00
4824.02	34.28	34.02	6.32	35.30	0.35	39.66	54.00	-14.34	A	1.00
7236.00	43.32	38.86	8.27	35.55	0.90	54.90	74.00	-19.10	P	1.00
7236.00	32.05	38.86	8.27	35.55	0.90	43.63	54.00	-10.37	A	1.00
9648.00	44.06	38.98	9.35	35.93	0.54	56.46	74.00	-17.54	P	1.00
9648.00	33.75	38.98	9.35	35.93	0.54	46.15	54.00	-7.85	A	1.00
12060.00	42.53	41.98	10.56	35.26	0.43	59.80	74.00	-14.20	P	1.00
12060.00	31.02	41.98	10.56	35.26	0.43	48.29	54.00	-5.71	A	1.00
Measurement Distance at 3m Vertical polarity										
Freq. (MHz)	Reading (dBμV)	AF (dBμV)	Cable (dB)	Pre-amp (dB)	Filter (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Mark (P/Q/A)	Height (Meter)
1459.93	57.93	26.64	3.54	35.15	0.00	52.97	74.00	-21.03	P	1.00
1459.93	44.00	26.64	3.54	35.15	0.00	39.04	54.00	-14.96	A	1.00
4824.02	60.68	34.02	6.32	35.30	0.35	66.06	74.00	-7.94	P	1.34
4824.02	46.00	34.02	6.32	35.30	0.35	51.38	54.00	-2.62	A	1.34
7236.00	48.78	38.86	8.27	35.55	0.90	61.27	74.00	-12.73	P	1.00
7236.00	36.10	38.86	8.27	35.55	0.90	48.59	54.00	-5.41	A	1.00
9648.00	45.12	38.98	9.35	35.93	0.54	58.06	74.00	-15.94	P	1.00
9648.00	33.20	38.98	9.35	35.93	0.54	46.14	54.00	-7.86	A	1.00
12060.00	45.65	41.98	10.56	35.26	0.43	63.35	74.00	-10.65	P	1.00
12060.00	31.42	41.98	10.56	35.26	0.43	49.12	54.00	-4.88	A	1.00

Remark:

1. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
2. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
3. The result basic equation calculation is as follow:
$$\text{Level} = \text{Reading} + \text{AF} + \text{Cable} - \text{Preamp} + \text{Filter}, \text{Margin} = \text{Level} - \text{Limit}$$
4. The other emission levels were 20dB below the limit



Product Name	802.11 a/b/g Mini PCI Card	Test Date	2006/04/08
Model	AG-621	Test By	Alan Fan
Test Mode	IEEE 802.11b TX (CH Middle)	TEMP & Humidity	24°C, 79%

Measurement Distance at 3m Horizontal polarity										
Freq. (MHz)	Reading (dBμV)	AF (dBμV)	Cable (dB)	Pre-amp (dB)	Filter (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Mark (P/Q/A)	Height (Meter)
1496.33	51.32	26.79	3.59	35.10	0.00	46.60	74.00	-27.40	P	1.00
1496.33	34.31	26.79	3.59	35.10	0.00	29.59	54.00	-24.41	A	1.00
4873.94	49.70	34.10	6.32	35.30	0.30	55.11	74.00	-18.89	P	1.00
4873.94	34.57	34.10	6.32	35.30	0.30	39.98	54.00	-14.02	A	1.00
7311.00	44.20	39.07	8.30	35.56	0.83	55.17	74.00	-18.83	P	1.00
7311.00	31.83	39.07	8.30	35.56	0.83	42.80	54.00	-11.20	A	1.00
9748.00	45.36	38.90	9.54	35.95	0.57	57.28	74.00	-16.72	P	1.00
9748.00	31.79	38.90	9.54	35.95	0.57	43.71	54.00	-10.29	A	1.00
12185.00	45.56	41.93	10.52	35.19	0.39	62.43	74.00	-11.57	P	1.00
12185.00	31.17	41.93	10.52	35.19	0.39	48.04	54.00	-5.96	A	1.00
Measurement Distance at 3m Vertical polarity										
Freq. (MHz)	Reading (dBμV)	AF (dBμV)	Cable (dB)	Pre-amp (dB)	Filter (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Mark (P/Q/A)	Height (Meter)
1496.33	60.93	26.79	3.59	35.10	0.00	56.21	74.00	-17.79	P	1.00
1496.33	40.74	26.79	3.59	35.10	0.00	36.02	54.00	-17.98	A	1.00
4873.98	60.55	34.10	6.32	35.30	0.30	65.96	74.00	-8.04	P	1.00
4873.98	45.78	34.10	6.32	35.30	0.30	51.19	54.00	-2.81	A	1.00
7311.00	47.62	39.07	8.30	35.56	0.83	59.43	74.00	-14.57	P	1.00
7311.00	37.02	39.07	8.30	35.56	0.83	48.83	54.00	-5.17	A	1.00
9748.00	45.86	38.90	9.54	35.95	0.57	58.35	74.00	-15.65	P	1.00
9748.00	31.77	38.90	9.54	35.95	0.57	44.26	54.00	-9.74	A	1.00
12185.00	45.78	41.93	10.52	35.19	0.39	63.04	74.00	-10.96	P	1.00
12185.00	31.17	41.93	10.52	35.19	0.39	48.43	54.00	-5.57	A	1.00

Remark:

1. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
2. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
3. The result basic equation calculation is as follow:
$$\text{Level} = \text{Reading} + \text{AF} + \text{Cable} - \text{Preamp} + \text{Filter}, \text{Margin} = \text{Level} - \text{Limit}$$
4. The other emission levels were 20dB below the limit



Product Name	802.11 a/b/g Mini PCI Card	Test Date	2006/04/08
Model	AG-621	Test By	Alan Fan
Test Mode	IEEE 802.11b TX (CH High)	TEMP & Humidity	24°C, 79%

Measurement Distance at 3m Horizontal polarity										
Freq. (MHz)	Reading (dBμV)	AF (dBμV)	Cable (dB)	Pre-amp (dB)	Filter (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Mark (P/Q/A)	Height (Meter)
1509.38	53.77	26.87	3.61	35.10	0.00	49.15	74.00	-24.85	P	1.00
1509.38	36.39	26.87	3.61	35.10	0.00	31.77	54.00	-22.23	A	1.00
4924.05	49.70	34.18	6.32	35.30	0.25	55.14	74.00	-18.86	P	1.00
4924.05	35.17	34.18	6.32	35.30	0.25	40.61	54.00	-13.39	A	1.00
7386.00	45.55	39.28	8.33	35.58	0.76	58.35	74.00	-15.65	P	1.00
7386.00	31.03	39.28	8.33	35.58	0.76	43.83	54.00	-10.17	A	1.00
9848.00	46.16	38.82	9.73	35.97	0.61	59.35	74.00	-14.65	P	1.00
9848.00	32.01	38.82	9.73	35.97	0.61	45.20	54.00	-8.80	A	1.00
12310.00	44.53	41.88	10.49	35.11	0.35	62.13	74.00	-11.87	P	1.00
12310.00	31.50	41.88	10.49	35.11	0.35	49.10	54.00	-4.90	A	1.00

Measurement Distance at 3m Vertical polarity										
Freq. (MHz)	Reading (dBμV)	AF (dBμV)	Cable (dB)	Pre-amp (dB)	Filter (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Mark (P/Q/A)	Height (Meter)
1509.38	58.45	26.87	3.61	35.10	0.00	53.83	74.00	-20.17	P	1.00
1509.38	45.58	26.87	3.61	35.10	0.00	40.96	54.00	-13.04	A	1.00
4924.05	60.19	34.18	6.32	35.30	0.25	65.63	74.00	-8.37	P	1.00
4924.05	45.73	34.18	6.32	35.30	0.25	51.17	54.00	-2.83	A	1.00
7386.00	46.66	39.28	8.33	35.58	0.76	59.46	74.00	-14.54	P	1.00
7386.00	34.80	39.28	8.33	35.58	0.76	47.60	54.00	-6.40	A	1.00
9848.00	46.12	38.82	9.73	35.97	0.61	59.31	74.00	-14.69	P	1.00
9848.00	32.13	38.82	9.73	35.97	0.61	45.32	54.00	-8.68	A	1.00
12310.00	45.06	41.88	10.49	35.11	0.35	62.66	74.00	-11.34	P	1.00
12310.00	31.38	41.88	10.49	35.11	0.35	48.98	54.00	-5.02	A	1.00

Remark:

1. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
2. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
3. The result basic equation calculation is as follow:
$$\text{Level} = \text{Reading} + \text{AF} + \text{Cable} - \text{Preamp} + \text{Filter}, \text{Margin} = \text{Level} - \text{Limit}$$
4. The other emission levels were 20dB below the limit



Product Name	802.11 a/b/g Mini PCI Card	Test Date	2006/04/08
Model	AG-621	Test By	Alan Fan
Test Mode	IEEE 802.11g TX (CH Low)	TEMP & Humidity	24°C, 79%

Measurement Distance at 3m Horizontal polarity										
Freq. (MHz)	Reading (dBμV)	AF (dBμV)	Cable (dB)	Pre-amp (dB)	Filter (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Mark (P/Q/A)	Height (Meter)
1469.83	47.31	26.68	3.56	35.14	0.00	42.41	74.00	-31.59	P	1.00
1469.83	33.63	26.68	3.56	35.14	0.00	28.73	54.00	-25.27	A	1.00
4824.50	46.02	34.02	6.32	35.30	0.35	51.40	74.00	-22.60	P	1.00
4824.50	31.44	34.02	6.32	35.30	0.35	36.82	54.00	-17.18	A	1.00
7236.00	44.93	38.86	8.27	35.55	0.90	57.42	74.00	-16.58	P	1.00
7236.00	31.14	38.86	8.27	35.55	0.90	43.63	54.00	-10.37	A	1.00
9648.00	45.68	38.98	9.35	35.93	0.54	58.62	74.00	-15.38	P	1.00
9648.00	31.91	38.98	9.35	35.93	0.54	44.85	54.00	-9.15	A	1.00
12060.00	45.15	41.98	10.56	35.26	0.43	62.85	74.00	-11.15	P	1.00
12060.00	31.41	41.98	10.56	35.26	0.43	49.11	54.00	-4.89	A	1.00

Measurement Distance at 3m Vertical polarity										
Freq. (MHz)	Reading (dBμV)	AF (dBμV)	Cable (dB)	Pre-amp (dB)	Filter (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Mark (P/Q/A)	Height (Meter)
1469.83	53.22	26.68	3.56	35.14	0.00	48.32	74.00	-25.68	P	1.00
1469.83	38.00	26.68	3.56	35.14	0.00	33.10	54.00	-20.90	A	1.00
4824.50	56.48	34.02	6.32	35.30	0.35	61.86	74.00	-12.14	P	1.00
4824.50	41.92	34.02	6.32	35.30	0.35	47.30	54.00	-6.70	A	1.00
7236.00	45.04	38.86	8.27	35.55	0.90	57.53	74.00	-16.47	P	1.00
7236.00	30.55	38.86	8.27	35.55	0.90	43.04	54.00	-10.96	A	1.00
9648.00	46.23	38.98	9.35	35.93	0.54	59.17	74.00	-14.83	P	1.00
9648.00	31.98	38.98	9.35	35.93	0.54	44.92	54.00	-9.08	A	1.00
12060.00	45.59	41.98	10.56	35.26	0.43	63.29	74.00	-10.71	P	1.00
12060.00	31.52	41.98	10.56	35.26	0.43	49.22	54.00	-4.78	A	1.00

Remark:

1. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
2. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
3. The result basic equation calculation is as follow:
$$\text{Level} = \text{Reading} + \text{AF} + \text{Cable} - \text{Preamp} + \text{Filter}, \text{Margin} = \text{Level} - \text{Limit}$$
4. The other emission levels were 20dB below the limit



Product Name	802.11 a/b/g Mini PCI Card	Test Date	2006/04/08
Model	AG-621	Test By	Alan Fan
Test Mode	IEEE 802.11g TX (CH Middle)	TEMP & Humidity	24°C, 79%

Measurement Distance at 3m Horizontal polarity										
Freq. (MHz)	Reading (dBμV)	AF (dBμV)	Cable (dB)	Pre-amp (dB)	Filter (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Mark (P/Q/A)	Height (Meter)
1496.45	52.12	26.79	3.60	35.10	0.00	47.40	74.00	-26.60	P	1.00
1496.45	33.66	26.79	3.60	35.10	0.00	28.94	54.00	-25.06	A	1.00
4872.59	44.38	34.10	6.32	35.30	0.30	49.79	74.00	-24.21	P	1.00
4872.59	31.99	34.10	6.32	35.30	0.30	37.40	54.00	-16.60	A	1.00
7305.66	44.00	39.06	8.30	35.56	0.84	56.63	74.00	-17.37	P	1.00
7305.66	30.99	39.06	8.30	35.56	0.84	43.62	54.00	-10.38	A	1.00
9747.61	44.90	38.90	9.54	35.95	0.57	57.97	74.00	-16.03	P	1.00
9747.61	31.46	38.90	9.54	35.95	0.57	44.53	54.00	-9.47	A	1.00
12185.00	44.58	41.93	10.52	35.19	0.39	62.23	74.00	-11.77	P	1.00
12185.00	31.32	41.93	10.52	35.19	0.39	48.97	54.00	-5.03	A	1.00

Measurement Distance at 3m Vertical polarity										
Freq. (MHz)	Reading (dBμV)	AF (dBμV)	Cable (dB)	Pre-amp (dB)	Filter (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Mark (P/Q/A)	Height (Meter)
1496.45	57.55	26.79	3.60	35.10	0.00	52.83	74.00	-21.17	P	1.00
1496.45	37.72	26.79	3.60	35.10	0.00	33.00	54.00	-21.00	A	1.00
4872.59	56.74	34.10	6.32	35.30	0.30	61.56	74.00	-12.44	P	1.00
4872.59	42.97	34.10	6.32	35.30	0.30	47.79	54.00	-6.21	A	1.00
7305.66	48.45	39.06	8.30	35.56	0.84	59.40	74.00	-14.60	P	1.00
7305.66	35.16	39.06	8.30	35.56	0.84	46.11	54.00	-7.89	A	1.00
9747.61	45.71	38.90	9.54	35.95	0.57	57.63	74.00	-16.37	P	1.00
9747.61	32.03	38.90	9.54	35.95	0.57	43.95	54.00	-10.05	A	1.00
12185.00	45.40	41.93	10.52	35.19	0.39	62.27	74.00	-11.73	P	1.00
12185.00	31.68	41.93	10.52	35.19	0.39	48.55	54.00	-5.45	A	1.00

Remark:

1. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
2. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
3. The result basic equation calculation is as follow:
$$\text{Level} = \text{Reading} + \text{AF} + \text{Cable} - \text{Preamp} + \text{Filter}, \text{Margin} = \text{Level} - \text{Limit}$$
4. The other emission levels were 20dB below the limit



Product Name	802.11 a/b/g Mini PCI Card	Test Date	2006/04/08
Model	AG-621	Test By	Alan Fan
Test Mode	IEEE 802.11g TX (CH High)	TEMP & Humidity	24°C, 79%

Measurement Distance at 3m Horizontal polarity										
Freq. (MHz)	Reading (dBμV)	AF (dBμV)	Cable (dB)	Pre-amp (dB)	Filter (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Mark (P/Q/A)	Height (Meter)
1515.94	48.45	26.91	3.63	35.09	0.00	43.89	74.00	-30.11	P	1.00
1515.94	32.62	26.91	3.63	35.09	0.00	28.06	54.00	-25.94	A	1.00
4924.83	55.57	34.18	6.32	35.30	0.25	61.01	74.00	-12.99	P	1.00
4924.83	41.24	34.18	6.32	35.30	0.25	46.68	54.00	-7.32	A	1.00
7396.69	44.75	39.31	8.33	35.58	0.76	57.57	74.00	-16.43	P	1.00
7396.69	30.71	39.31	8.33	35.58	0.76	43.53	54.00	-10.47	A	1.00
9848.00	45.93	38.82	9.73	35.97	0.61	59.12	74.00	-14.88	P	1.00
9848.00	31.84	38.82	9.73	35.97	0.61	45.03	54.00	-8.97	A	1.00
12310.00	44.23	41.88	10.49	35.11	0.35	61.83	74.00	-12.17	P	1.00
12310.00	31.50	41.88	10.49	35.11	0.35	49.10	54.00	-4.90	A	1.00
Measurement Distance at 3m Vertical polarity										
Freq. (MHz)	Reading (dBμV)	AF (dBμV)	Cable (dB)	Pre-amp (dB)	Filter (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Mark (P/Q/A)	Height (Meter)
1515.94	57.81	26.91	3.63	35.09	0.00	53.25	74.00	-20.75	P	1.00
1515.94	44.06	26.91	3.63	35.09	0.00	39.50	54.00	-14.50	A	1.00
4924.83	60.58	34.18	6.32	35.30	0.25	66.02	74.00	-7.98	P	1.00
4924.83	45.61	34.18	6.32	35.30	0.25	51.05	54.00	-2.95	A	1.00
7396.69	48.53	39.31	8.33	35.58	0.76	61.35	74.00	-12.65	P	1.00
7396.69	33.59	39.31	8.33	35.58	0.76	46.41	54.00	-7.59	A	1.00
9848.00	45.95	38.82	9.73	35.97	0.61	59.14	74.00	-14.86	P	1.00
9848.00	31.77	38.82	9.73	35.97	0.61	44.96	54.00	-9.04	A	1.00
12310.00	44.62	41.88	10.49	35.11	0.35	62.22	74.00	-11.78	P	1.00
12310.00	31.28	41.88	10.49	35.11	0.35	48.88	54.00	-5.12	A	1.00

Remark:

1. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
2. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
3. The result basic equation calculation is as follow:
$$\text{Level} = \text{Reading} + \text{AF} + \text{Cable} - \text{Preamp} + \text{Filter}, \text{Margin} = \text{Level} - \text{Limit}$$
4. The other emission levels were 20dB below the limit



Product Name	802.11 a/b/g Mini PCI Card	Test Date	2006/04/08
Model	AG-621	Test By	Alan Fan
Test Mode	IEEE 802.11g Turbo TX (CH Middle)	TEMP & Humidity	24°C, 79%

Measurement Distance at 3m Horizontal polarity										
Freq. (MHz)	Reading (dBμV)	AF (dBμV)	Cable (dB)	Pre-amp (dB)	Filter (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Mark (P/Q/A)	Height (Meter)
1496.45	48.90	26.79	3.60	35.10	0.00	44.18	74.00	-29.82	P	1.00
1496.45	32.52	26.79	3.60	35.10	0.00	27.80	54.00	-26.20	A	1.00
4872.59	45.84	34.10	6.32	35.30	0.30	51.25	74.00	-22.75	P	1.00
4872.59	30.72	34.10	6.32	35.30	0.30	36.13	54.00	-17.87	A	1.00
7305.66	44.79	39.06	8.30	35.56	0.84	57.42	74.00	-16.58	P	1.00
7305.66	31.21	39.06	8.30	35.56	0.84	43.84	54.00	-10.16	A	1.00
9747.61	44.86	38.90	9.54	35.95	0.57	57.93	74.00	-16.07	P	1.00
9747.61	31.39	38.90	9.54	35.95	0.57	44.46	54.00	-9.54	A	1.00
12185.00	44.35	41.93	10.52	35.19	0.39	62.00	74.00	-12.00	P	1.00
12185.00	31.31	41.93	10.52	35.19	0.39	48.96	54.00	-5.04	A	1.00

Measurement Distance at 3m Vertical polarity										
Freq. (MHz)	Reading (dBμV)	AF (dBμV)	Cable (dB)	Pre-amp (dB)	Filter (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Mark (P/Q/A)	Height (Meter)
1496.45	57.05	26.79	3.60	35.10	0.00	52.33	74.00	-21.67	P	1.00
1496.45	37.50	26.79	3.60	35.10	0.00	32.78	54.00	-21.22	A	1.00
4872.59	56.77	34.10	6.32	35.30	0.30	61.59	74.00	-12.41	P	1.00
4872.59	43.88	34.10	6.32	35.30	0.30	48.70	54.00	-5.30	A	1.00
7305.66	46.13	39.06	8.30	35.56	0.84	57.08	74.00	-16.92	P	1.00
7305.66	31.33	39.06	8.30	35.56	0.84	42.28	54.00	-11.72	A	1.00
9747.61	45.70	38.90	9.54	35.95	0.57	57.62	74.00	-16.38	P	1.00
9747.61	31.54	38.90	9.54	35.95	0.57	43.46	54.00	-10.54	A	1.00
12185.00	45.64	41.93	10.52	35.19	0.39	62.51	74.00	-11.49	P	1.00
12185.00	31.29	41.93	10.52	35.19	0.39	48.16	54.00	-5.84	A	1.00

Remark:

1. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
2. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
3. The result basic equation calculation is as follow:
$$\text{Level} = \text{Reading} + \text{AF} + \text{Cable} - \text{Preamp} + \text{Filter}, \text{Margin} = \text{Level} - \text{Limit}$$
4. The other emission levels were 20dB below the limit



Product Name	802.11 a/b/g Mini PCI Card	Test Date	2006/04/08
Model	AG-621	Test By	Alan Fan
Test Mode	IEEE 802.11a TX (CH Low)	TEMP & Humidity	24°C, 79%

Measurement Distance at 3m Horizontal polarity										
Freq. (MHz)	Reading (dBμV)	AF (dBμV)	Cable (dB)	Pre-amp (dB)	Filter (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Mark (P/Q/A)	Height (Meter)
3922.12	58.86	31.01	5.86	35.03	0.23	60.93	74.00	-13.07	P	1.00
3922.12	40.90	31.01	5.86	35.03	0.23	42.97	54.00	-11.03	A	1.00
7565.13	45.50	39.69	8.36	35.61	0.66	57.94	74.00	-16.06	P	1.00
7565.13	30.96	39.69	8.36	35.61	0.66	43.40	54.00	-10.60	A	1.00
11490.00	45.43	41.36	10.03	35.30	0.71	61.52	74.00	-12.48	P	1.00
11490.00	31.12	41.36	10.03	35.30	0.71	47.21	54.00	-6.79	A	1.00
Measurement Distance at 3m Vertical polarity										
Freq. (MHz)	Reading (dBμV)	AF (dBμV)	Cable (dB)	Pre-amp (dB)	Filter (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Mark (P/Q/A)	Height (Meter)
3922.12	53.56	31.01	5.86	35.03	0.23	55.63	74.00	-18.37	P	1.00
3922.12	39.00	31.01	5.86	35.03	0.23	41.07	54.00	-12.93	A	1.00
7565.13	53.01	39.69	8.36	35.61	0.66	66.11	74.00	-7.89	P	1.00
7565.13	37.66	39.69	8.36	35.61	0.66	50.76	54.00	-3.24	A	1.00
11490.00	45.18	41.36	10.03	35.30	0.71	61.98	74.00	-12.02	P	1.00
11490.00	31.14	41.36	10.03	35.30	0.71	47.94	54.00	-6.06	A	1.00

Remark:

1. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
2. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
3. The result basic equation calculation is as follow:
$$\text{Level} = \text{Reading} + \text{AF} + \text{Cable} - \text{Preamp} + \text{Filter}, \text{Margin} = \text{Level} - \text{Limit}$$
4. The other emission levels were 20dB below the limit



Product Name	802.11 a/b/g Mini PCI Card	Test Date	2006/04/08
Model	AG-621	Test By	Alan Fan
Test Mode	IEEE 802.11a TX (CH Middle)	TEMP & Humidity	24°C, 79%

Measurement Distance at 3m Horizontal polarity										
Freq. (MHz)	Reading (dBμV)	AF (dBμV)	Cable (dB)	Pre-amp (dB)	Filter (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Mark (P/Q/A)	Height (Meter)
3959.51	60.04	31.10	5.86	35.02	0.17	62.16	74.00	-11.84	P	1.00
3959.51	38.93	31.10	5.86	35.02	0.17	41.05	54.00	-12.95	A	1.00
7604.43	46.12	39.75	8.36	35.62	0.66	57.94	74.00	-16.06	P	1.00
7604.43	31.28	39.75	8.36	35.62	0.66	43.10	54.00	-10.90	A	1.00
11570.00	44.96	41.48	10.11	35.30	0.67	60.58	74.00	-13.42	P	1.00
11570.00	31.00	41.48	10.11	35.30	0.67	46.62	54.00	-7.38	A	1.00
Measurement Distance at 3m Vertical polarity										
Freq. (MHz)	Reading (dBμV)	AF (dBμV)	Cable (dB)	Pre-amp (dB)	Filter (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Mark (P/Q/A)	Height (Meter)
3959.51	51.78	31.10	5.86	35.02	0.17	53.90	74.00	-20.10	P	1.00
3959.51	37.91	31.10	5.86	35.02	0.17	40.03	54.00	-13.97	A	1.00
7604.43	55.76	39.75	8.36	35.62	0.66	68.24	74.00	-5.76	P	1.00
7604.43	40.23	39.75	8.36	35.62	0.66	52.71	54.00	-1.29	A	1.00
11570.00	45.42	41.48	10.11	35.30	0.67	61.71	74.00	-12.29	P	1.00
11570.00	30.99	41.48	10.11	35.30	0.67	47.28	54.00	-6.72	A	1.00

Remark:

1. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
2. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
3. The result basic equation calculation is as follow:
$$\text{Level} = \text{Reading} + \text{AF} + \text{Cable} - \text{Preamp} + \text{Filter}, \text{Margin} = \text{Level} - \text{Limit}$$
4. The other emission levels were 20dB below the limit



Product Name	802.11 a/b/g Mini PCI Card	Test Date	2006/04/08
Model	AG-621	Test By	Alan Fan
Test Mode	IEEE 802.11a TX (CH High)	TEMP & Humidity	24°C, 79%



Measurement Distance at 3m Horizontal polarity										
Freq. (MHz)	Reading (dBμV)	AF (dBμV)	Cable (dB)	Pre-amp (dB)	Filter (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Mark (P/Q/A)	Height (Meter)
3973.10	57.81	31.14	5.87	35.01	0.14	59.94	74.00	-14.06	P	1.00
3973.10	40.64	31.14	5.87	35.01	0.14	42.77	54.00	-11.23	A	1.00
7644.97	45.02	39.80	8.35	35.63	0.66	58.20	74.00	-15.80	P	1.00
7644.97	32.41	39.80	8.35	35.63	0.66	45.59	54.00	-8.41	A	1.00
11650.00	45.22	41.58	10.20	35.30	0.63	62.33	74.00	-11.67	P	1.00
11650.00	30.85	41.58	10.20	35.30	0.63	47.96	54.00	-6.04	A	1.00
Measurement Distance at 3m Vertical polarity										
Freq. (MHz)	Reading (dBμV)	AF (dBμV)	Cable (dB)	Pre-amp (dB)	Filter (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Mark (P/Q/A)	Height (Meter)
3975.00	54.81	31.14	5.87	35.01	0.14	56.94	74.00	-17.06	P	1.00
3975.00	34.63	31.14	5.87	35.01	0.14	36.76	54.00	-17.24	A	1.00
7644.97	54.21	39.80	8.35	35.63	0.66	67.39	74.00	-6.61	P	1.00
7644.97	38.50	39.80	8.35	35.63	0.66	51.68	54.00	-2.32	A	1.00
11650.00	45.14	41.58	10.20	35.30	0.63	62.25	74.00	-11.75	P	1.00
11650.00	31.25	41.58	10.20	35.30	0.63	48.36	54.00	-5.64	A	1.00

Remark:

1. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
2. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
3. The result basic equation calculation is as follow:
$$\text{Level} = \text{Reading} + \text{AF} + \text{Cable} - \text{Preamp} + \text{Filter}, \text{Margin} = \text{Level} - \text{Limit}$$
4. The other emission levels were 20dB below the limit




8.7.4 RESTRICTED BAND EDGES

Detector mode : Peak**Polarity : Horizontal****Detector mode : Average****Polarity : Horizontal**




Detector mode : Peak

Polarity : Vertical



Detector mode : Average


Polarity : Vertical






Detector mode : Peak

Polarity : Horizontal



Detector mode : Average


Polarity : Horizontal






Detector mode : Peak

Polarity : Vertical



Detector mode : Average


Polarity : Vertical






Detector mode : Peak

Polarity : Horizontal



Detector mode : Average


Polarity : Horizontal






Detector mode : Peak

Polarity : Vertical



Detector mode : Average


Polarity : Vertical






Detector mode : Peak



Polarity : Horizontal



Detector mode : Average

Polarity : Horizontal




**Detector mode : Peak****Polarity : Vertical****Detector mode : Average****Polarity : Vertical**




Detector mode : Peak

Polarity : Horizontal



Detector mode : Average


Polarity : Horizontal






Detector mode : Peak

Polarity : Vertical



Detector mode : Average


Polarity : Vertical






Detector mode : Peak

Polarity : Horizontal



Detector mode : Average


Polarity : Horizontal






Detector mode : Peak

Polarity : Vertical



Detector mode : Average

Polarity : Vertical





8.8 POWERLINE CONDUCTED EMISSIONS

LIMITS

§ 15.207 (a) Except as shown in paragraph (b) and (c) this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal.


The lower limit applies at the boundary between the frequency ranges.

Frequency of Emission (MHz)	Conducted limit (dB μ v)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56	56 to 46
0.5 - 5	56	46
5 - 30	60	50

TEST EQUIPMENTS

The following test equipments are used during the conducted powerline tests :

Manufacturer or Type	Model No.	Serial No.	Date of Calibration	Calibration Period	Remark
HP SPECTRUM ANALYZER	8594E	3801A05627	April 28, 2005	1 Year	PRETEST
SOLAR ISOLATION TRANSFORMER	7032-1	N/A	N/A	N/A	FINAL
EMCO L.I.S.N.	3850/2	9311-1025	January 16, 2006	1 Year	FINAL
CHASE L.I.S.N	NNLK 8129	8129118	January 16, 2006	1 Year	FINAL
R & S TEST RECEIVER	ESHS30	838550/003	February 27, 2006	1 Year	FINAL
KEENE SHIELDED ROOM	5983	No.1	N/A	N/A	FINAL
R & S PULSE LIMIT	EHS3Z2	357.8810.52	July 10, 2005	1 Year	FINAL
N TYPE COAXIAL CABLE	-----	-----	July 10, 2005	1 Year	FINAL
50 Ω TERMINATOR	-----	-----	July 10, 2005	1 Year	FINAL

**TEST SETUP****TEST PROCEDURE**

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80cm above the horizontal ground plane. The EUT IS CONFIGURED IN ACCORDANCE WITH ANSI C63.4.

The resolution bandwidth is set to 9 kHz for both quasi-peak detection and average detection measurements.

Line conducted data is recorded for both NEUTRAL and LINE.


TEST RESULTS

No non-compliance noted

**CONDUCTED RF VOLTAGE MEASUREMENT**

Product Name	802.11 a/b/g Mini PCI Card	Test Date	2006/04/08
Model Name	AG-621	Test By	Alan Fan
Test Mode	Normal operating (worst case)	TEMP & Humidity	24°C, 79%

LINE


**Remark:**

1. Correction Factor = Insertion loss + cable loss
2. Margin value = Emission level – Limit value



Product Name	802.11 a/b/g Mini PCI Card	Test Date	2006/04/08
Model Name	AG-621	Test By	Alan Fan
Test Mode	Normal operating (worst case)	TEMP & Humidity	24°C, 79%

NEUTRAL

**Remark:**

1. Correction Factor = Insertion loss + cable loss
2. Margin value = Emission level - Limit value



9. ANTENNA REQUIREMENT

9.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

9.2 ANTENNA CONNECTED CONSTRUCTION

The antenna used for this product is dipole antenna. The temporary antenna connector is Reverse SMA PLUG connector and the peak Gain of this antenna is only 2dBi at 2.4GHz, 2dBi at 5GHz.