SPORTON International Inc.
No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, TaoYuan Hsien, Taiwan, R.O.C.
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

FCC RADIO TEST REPORT

Applicant's company	**Z-Com, Inc.**
Applicant Address	7F-2, No. 9. Prosperity RD.I Science-Based Industrial, Park Hsinchu, 300 Taiwan
FCC ID	**M4Y-AG623C**
Manufacturer's company	**Z-Com, Inc.**
Manufacturer Address	7F-2, No. 9. Prosperity RD.I Science-Based Industrial, Park Hsinchu, 300 Taiwan

Product Name	IEEE 802.11 a/b/g Wireless Network Mini PCI
Brand Name	ZCOM
Model Name	AG-623C
Test Rule Part(s)	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Received Date	Sep. 26, 2006
Final Test Date	Sep. 28, 2006
Submission Type	Original Equipment



Statement

Test result included is only for the 802.11b/g part and 802.11a (5725 ~ 5850MHz) of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.4-2003** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.

Table of Contents

1. CERTIFICATE OF COMPLIANCE 1

2. SUMMARY OF THE TEST RESULT 2

3. GENERAL INFORMATION 3

3.1. Product Details 3
3.2. Accessories 3
3.3. Table for Filed Antenna 3
3.4. Table for Carrier Frequencies 4
3.5. Table for Test Modes 4
3.6. Table for Testing Locations 5
3.7. Table for Supporting Units 5
3.8. Table for Parameters of Test Software Setting 5
3.9. Test Configurations 6

4. TEST RESULT 8

4.1. AC Power Line Conducted Emissions Measurement 8
4.2. Maximum Peak Output Power Measurement 12
4.3. Power Spectral Density Measurement 14
4.4. 6dB Spectrum Bandwidth Measurement 21
4.5. Radiated Emissions Measurement 28
4.6. Band Edge Emissions Measurement 52
4.7. Antenna Requirements 60

5. LIST OF MEASURING EQUIPMENTS 61

6. TEST LOCATION 63

APPENDIX A. PHOTOGRAPHS OF EUT ..... A1 ~ A6

APPENDIX B. TEST PHOTOS ..... B1 ~ B8

APPENDIX C. MAXIMUM PERMISSIBLE EXPOSURE ..... C1 ~C3

History of This Test Report

Original Issue Date: Sep. 29, 2006

Report No.: FR692606-AB

■ No additional attachment.

☐ Additional attachment were issued as following record:

Attachment No.	Issue Date	Description

1. CERTIFICATE OF COMPLIANCE

Product Name	:	IEEE 802.11 a/b/g Wireless Network Mini PCI
Brand Name	:	ZCOM
Model Name	:	AG-623C
Applicant	:	Z-Com, Inc.
Test Rule Part(s)	:	47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Sep. 26, 2006 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

Prepared By:	Tested By:	Reviewed By:
Mandy Liang / Specialist	Steven Lu / Engineer	Wayne Hsu

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	9.18 dB
4.2	15.247(b)(3)	Maximum Peak Conducted Output Power	Complies	8.08 dB
4.3	15.247(e)	Power Spectral Density	Complies	14.18 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	1.69 dB
4.6	15.247(d)	Band Edge Emissions	Complies	1.16 dB
4.7	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.26dB	Confidence levels of 95%
Maximum Peak Conducted Output Power	±0.776dB	Confidence levels of 95%
Power Spectral Density	±0.506dB	Confidence levels of 95%
6dB Spectrum Bandwidth	$\pm 1.64 \times 10^{-6}$	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.754dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.89dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.89dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.86dB	Confidence levels of 95%
Temperature	±0.7℃	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±0.04%	Confidence levels of 95%

3. GENERAL INFORMATION

3.1. Product Details

Items	Description
Power Type	From Host systom (Notebook)
Modulation	DSSS for IEEE 802.11b ; OFDM for IEEE 802.11a/g
Data Modulation	DSSS (BPSK / QPSK / CCK) ; OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	DSSS (1/ 2/ 5.5/11) ; OFDM (6/9/12/18/24/36/48/54)
Frequency Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Channel Number	11b/g: 11 ; 11a(Band 3): 5
Channel Band Width (99%)	11b: 15.60 MHz ; 11g: 16.80 MHz ; 11a(Band 3): 16.56 MHz
Conducted Output Power	11b: 17.68 dBm ; 11g: 21.92 dBm ; 11a(Band 3): 17.56 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

3.2. Accessories

N/A

3.3. Table for Filed Antenna

For 2.4GHz Band

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	Wha Yu	C356-510139-A	Dipole Antenna	Reversed-SMA	2.3

For 5GHz Band

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	Wha Yu	C356-510139-A	Dipole Antenna	Reversed-SMA	2.6

3.4. Table for Carrier Frequencies

Frequency Allocation for 802.11b/g

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz		

Frequency Allocation for 802.11a

Frequency Band	Channel No.	Frequency
5725~5850 MHz (Band 3)	149	5745 MHz
	153	5765 MHz
	157	5785 MHz
	161	5805 MHz
	165	5825 MHz

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	Normal Link	54 Mbps	6	1
Max. Peak Conducted Output Power	11b/BPSK	1 Mbps	1/6/11	NA
Power Spectral Density	11g/BPSK	6 Mbps	1/6/11	NA
6dB Spectrum Bandwidth	11a/BPSK	6 Mbps	149/157/165	NA
Radiated Emissions Below 1GHz	11g/BPSK	6 Mbps	6	1
Radiated Emissions Above 1GHz	11b/BPSK	1 Mbps	1/6/11	1
Band Edge Emissions	11g/BPSK	6 Mbps	1/6/11	1
	11a/BPSK	6 Mbps	149/157/165	1
Band Edge Emissions	11b/BPSK	1 Mbps	1/11	1
	11g/BPSK	6 Mbps	1/11	1
	11a/BPSK	6 Mbps	149/165	1

3.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No
03CH03-HY	SAC	Hwa Ya	101377	IC 4088	-
CO04-HY	Conduction	Hwa Ya	101377	IC 4088	-
TH01-HY	OVEN Room	Hwa Ya	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC); Fully Anechoic Chamber (FAC).

Please refer section 6 for Test Site Address.

3.7. Table for Supporting Units

Support Unit	Brand	Model	FCC ID
Notebook	DELL	D505	E2K24GBRL
Printer	EPSON	LQ-300	DoC
Modem	ACEEX	DM1414	IFAXDM1414

3.8. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power Parameters of IEEE 802.11b/g

Test Software Version	ART		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11b	17.5	17.5	17
IEEE 802.11g	15	19.5	14

Power Parameters of IEEE 802.11a

Test Software Version	ART		
Frequency	5745 MHz	5785 MHz	5825 MHz
IEEE 802.11a	12	12	12

An executive program, EMITEST.EXE under WIN XP, which generates a complete line of continuously repeating " H " pattern was used as the test software.

The program was executed as follows :

a. Turn on the power of all equipment.

b. The NB sends " H" messages to the panel, and the panel displays " H " patterns on the screen.

c. The NB sends " H " messages to the printer, then the printer prints them on the paper.

d. The NB sends " H " messages to the modem.

e. Repeat the steps from b to d.

At the same time, "ART" was executed the test program to control the EUT continuously transmit RF signal.

3.9. Test Configurations

3.9.1. Radiation Emissions Test Configuration

Test Configurations: 9kHz~1GHz



Test Configurations: Above 1GHz



3.9.2. AC Power Line Conduction Emissions Test Configuration



4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

4.1.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.4. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

4.1.4. Test Setup Layout



AMN = Artificial mains network (LISN)
AE = Associated equipment
EUT = Equipment under test
ISN = Impedance stabilization network

1. If cables, which hang closer than 40 cm to the horizontal metal groundplane, cannot be shortened to appropriate length, the excess shall be folded back and forth forming a bundle 30 cm to 40 cm long.
2. Excess mains cord shall be bundled in the centre or shortened to appropriate length.
3. EUT is connected to one artificial mains network (AMN). All AMNs and ISNs may alternatively be connected to a vertical reference plane or metal wall.
4. All other units of a system are powered from a second AMN. A multiple outlet strip can be used for multiple mains cords.
5. AMN and ISN are 80 cm from the EUT and at least 80 cm from other units and other metal planes.
6. Mains cords and signal cables shall be positioned for their entire lengths, as far as possible, at 40 cm from the vertical reference plane.
7. Cables of hand operated devices, such as keyboards, mouses, etc. shall be placed as for normal usage.
8. Peripherals shall be placed at a distance of 10 cm from each other and from the controller, except for the monitor which, if this is an acceptable installation practice, shall be placed directly on the top of the controller.
9. I/O signal cable intended for external connection.
10. The end of the I/O signal cables which are not connected to an AE may be terminated, if required, using correct terminating impedance.
11. If used, the current probe shall be placed at 0,1 m from the ISN.

4.1.5. Test Deviation

There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.

4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	27.9℃	Humidity	54%
Test Engineer	Johnson Chang	Phase	Line
Configuration	Normal Link		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.15403	44.45	-21.33	65.78	42.21	2.04	0.20	QP
2	0.15403	19.41	-36.37	55.78	17.17	2.04	0.20	AVERAGE
3 @	0.18056	51.79	-12.67	64.46	49.94	1.65	0.20	QP
4	0.18056	40.20	-14.26	54.46	38.35	1.65	0.20	AVERAGE
5 @	3.160	44.84	-11.16	56.00	44.31	0.30	0.23	QP
6 @	3.160	35.30	-10.70	46.00	34.77	0.30	0.23	AVERAGE
7 @	3.278	44.88	-11.12	56.00	44.32	0.30	0.26	QP
8 @	3.278	36.82	-9.18	46.00	36.26	0.30	0.26	AVERAGE
9 @	3.637	43.92	-12.08	56.00	43.29	0.33	0.30	QP
10	3.637	31.61	-14.39	46.00	30.98	0.33	0.30	AVERAGE
11	10.483	34.09	-25.91	60.00	33.39	0.30	0.40	QP
12	10.483	29.79	-20.21	50.00	29.09	0.30	0.40	AVERAGE

Temperature	27.9℃	Humidity	54%
Test Engineer	Johnson Chang	Phase	Neutral
Configuration	Normal Link		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.15000	51.25	-14.75	66.00	49.15	1.90	0.20	QP
2	0.15000	31.84	-24.16	56.00	29.74	1.90	0.20	AVERAGE
3 @	0.15567	52.78	-12.91	65.69	50.68	1.90	0.20	QP
4	0.15567	30.30	-25.39	55.69	28.20	1.90	0.20	AVERAGE
5	0.16155	48.80	-16.59	65.38	46.73	1.87	0.20	QP
6	0.16155	33.13	-22.26	55.38	31.06	1.87	0.20	AVERAGE
7	0.16854	51.30	-13.73	65.03	49.37	1.73	0.20	QP
8	0.16854	37.12	-17.91	55.03	35.19	1.73	0.20	AVERAGE
9	0.17125	50.27	-14.63	64.90	48.39	1.68	0.20	QP
10	0.17125	35.63	-19.27	54.90	33.75	1.68	0.20	AVERAGE
11	3.173	37.58	-18.42	56.00	37.04	0.30	0.24	QP
12	3.173	26.36	-19.64	46.00	25.82	0.30	0.24	AVERAGE
13	3.346	40.53	-15.47	56.00	39.96	0.30	0.27	QP
14	3.346	26.69	-19.31	46.00	26.12	0.30	0.27	AVERAGE
15	3.509	40.12	-15.88	56.00	39.52	0.30	0.30	QP
16	3.509	26.59	-19.41	46.00	25.99	0.30	0.30	AVERAGE

Note:

Level = Read Level + LISN Factor + Cable Loss.

4.2. Maximum Peak Output Power Measurement

4.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi. Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted output power.

4.2.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Filter No.	Auto
Measurement time	0.135 s ~ 26 s
Used Peak Sensor	NRV-Z32 (model 04)

4.2.3. Test Procedures

1. The transmitter output (antenna port) was connected to the power meter.
2. Turn on the EUT and power meter and then record the peak power value.
3. Repeat above procedures on all channels needed to be tested.

4.2.4. Test Setup Layout



4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of Maximum Peak Output Power

Temperature	24℃	Humidity	56%
Test Engineer	Leo Hung	Configurations	802.11a/b/g

Configuration IEEE 802.11b

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	17.58	30.00	Complies
6	2437 MHz	17.66	30.00	Complies
11	2462 MHz	17.68	30.00	Complies

Configuration IEEE 802.11g

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	19.58	30.00	Complies
6	2437 MHz	21.92	30.00	Complies
11	2462 MHz	19.34	30.00	Complies

Configuration IEEE 802.11a

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
149	5745 MHz	17.34	30.00	Complies
157	5785 MHz	17.56	30.00	Complies
165	5825 MHz	17.38	30.00	Complies

4.3. Power Spectral Density Measurement

4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

4.3.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of Spectrum Analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	1.5MHz
RB	3 kHz
VB	30 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	500s

4.3.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser.
2. Set RBW of spectrum analyzer to 3kHz and VBW to 30kHz. Set Detector to Peak, Trace to Max Hold.
3. Mark the frequency with maximum peak power as the center of the display of the spectrum.
4. Set the span to 1.5MHz and the sweep time to 500s and record the maximum peak value.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Power Spectral Density

Temperature	24℃	Humidity	56%
Test Engineer	Leo Hung	Configurations	802.11a/b/g

Configuration IEEE 802.11b

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-6.55	8.00	Complies
6	2437 MHz	-6.18	8.00	Complies
11	2462 MHz	-6.45	8.00	Complies

Configuration IEEE 802.11g

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-11.92	8.00	Complies
6	2437 MHz	-6.41	8.00	Complies
11	2462 MHz	-11.56	8.00	Complies

Configuration IEEE 802.11a

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
149	5745 MHz	-11.57	8.00	Complies
157	5785 MHz	-11.11	8.00	Complies
165	5825 MHz	-12.32	8.00	Complies

Power Density Plot on Configuration IEEE 802.11b / 2412 MHz



Date: 27.SEP.2006 03:46:28

Power Density Plot on Configuration IEEE 802.11b / 2437 MHz



Date: 27.SEP.2006 03:47:16

Power Density Plot on Configuration IEEE 802.11b / 2462 MHz



Date: 27.SEP.2006 03:49:45

Power Density Plot on Configuration IEEE 802.11g / 2412 MHz



Date: 27.SEP.2006 03:44:26

Power Density Plot on Configuration IEEE 802.11g / 2437 MHz



Date: 27.SEP.2006 03:43:33

Power Density Plot on Configuration IEEE 802.11g / 2462 MHz



Date: 27.SEP.2006 03:42:32

Power Density Plot on Configuration IEEE 802.11a / 5745 MHz



Date: 27.SEP.2006 04:02:56

Power Density Plot on Configuration IEEE 802.11a / 5785 MHz



Date: 27.SEP.2006 04:03:59

Power Density Plot on Configuration IEEE 802.11a / 5825 MHz



Date: 27.SEP.2006 04:05:19

4.4. 6dB Spectrum Bandwidth Measurement

4.4.1. Limit

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

4.4.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the Spectrum Analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RB	100 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
2. The resolution bandwidth of 100 kHz and the video bandwidth of 100 kHz were used.
3. Measured the spectrum width with power higher than 6dB below carrier.

4.4.4. Test Setup Layout



4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of 6dB Spectrum Bandwidth

Temperature	24℃	Humidity	56%
Test Engineer	Leo Hung	Configurations	802.11a/b/g

Configuration IEEE 802.11b

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	12.04	15.60	500	Complies
6	2437 MHz	12.08	15.60	500	Complies
11	2462 MHz	11.12	15.60	500	Complies

Configuration IEEE 802.11g

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	16.36	16.56	500	Complies
6	2437 MHz	16.56	16.80	500	Complies
11	2462 MHz	16.48	16.52	500	Complies

Configuration IEEE 802.11a

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	16.36	16.56	500	Complies
157	5785 MHz	16.32	16.52	500	Complies
165	5825 MHz	16.40	16.48	500	Complies

6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2412 MHz



Date: 27.SEP.2006 03:46:03

6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2437 MHz



Date: 27.SEP.2006 03:47:00

6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2462 MHz



Date: 27.SEP.2006 03:49:29

6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2412 MHz



Date: 27.SEP.2006 03:44:00

6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2437 MHz



Date: 27.SEP.2006 03:43:17

6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2462 MHz



Date: 27.SEP.2006 03:42:16

6 dB Bandwidth Plot on Configuration IEEE 802.11a / 5745 MHz



Date: 27.SEP.2006 04:02:30

6 dB Bandwidth Plot on Configuration IEEE 802.11a / 5785 MHz



Date: 27.SEP.2006 04:03:34

6 dB Bandwidth Plot on Configuration IEEE 802.11a / 5825 MHz



Date: 27.SEP.2006 04:04:53

4.5. Radiated Emissions Measurement

4.5.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100KHz / 100KHz for peak

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

4.5.3. Test Procedures

1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.5.4. Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade form 3m to 1.5m.

Distance extrapolation factor = 20 log (specific distance [3m] / test distance [1.5m]) (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [6 dB].

4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	23℃	Humidity	54%
Test Engineer	Beck Wu	Configurations	802.11g CH 6

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

Distance extrapolation factor = 40 log (specific distance / test distance) (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.5.8. Results of Radiated Emissions (30MHz~1GHz)

Temperature	23℃	Humidity	54%
Test Engineer	Beck Wu	Configurations	802.11g CH 6

Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	31.940	32.47	-7.53	40.00	39.68	18.96	0.32	26.49	Peak	400	0
2	164.830	27.05	-16.45	43.50	41.63	10.35	0.72	25.66	Peak	400	0
3	230.790	33.86	-12.14	46.00	46.83	11.39	1.08	25.44	Peak	400	0
4	365.620	34.82	-11.18	46.00	43.00	15.68	1.30	25.16	Peak	400	0
5	431.580	29.45	-16.55	46.00	36.81	16.94	1.49	25.79	Peak	400	0
6	564.470	30.60	-15.40	46.00	36.40	18.72	1.75	26.26	Peak	400	0
7	664.380	38.99	-7.01	46.00	43.34	19.63	2.14	26.12	Peak	400	0
8	948.590	35.31	-10.69	46.00	35.75	21.99	3.05	25.49	Peak	400	0

Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	30.000	24.95	-15.05	40.00	30.99	20.20	0.44	26.68	Peak	100	0
2	98.870	26.55	-16.95	43.50	41.14	11.01	0.36	25.96	Peak	100	0
3	164.830	34.17	-9.33	43.50	48.75	10.35	0.72	25.66	Peak	100	0
4 !	230.790	42.48	-3.52	46.00	55.45	11.39	1.08	25.44	Peak	100	0
5 !	365.620	41.24	-4.76	46.00	49.43	15.68	1.30	25.16	Peak	100	0
6	665.350	36.45	-9.55	46.00	40.79	19.63	2.14	26.12	Peak	100	0
7	801.150	32.97	-13.03	46.00	34.94	20.71	2.50	25.18	Peak	100	0
8	948.590	34.95	-11.05	46.00	35.39	21.99	3.05	25.49	Peak	100	0
9	998.060	36.14	-17.86	54.00	35.97	22.29	3.11	25.23	Peak	100	0

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5.9. Results for Radiated Emissions (1GHz~10th Harmonic)

Temperature	23℃	Humidity	54%
Test Engineer	Beck Wu	Configurations	802.11b CH 1

Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	2382.700	44.40	-9.60	54.00	44.68	28.09	5.14	33.50	AVERAGE	100	330
2	2382.700	51.86	-22.14	74.00	52.13	28.09	5.14	33.50	PEAK	100	330
3	4824.080	56.38	-17.62	74.00	49.21	33.22	7.18	33.24	PEAK	100	105
4 !	4824.080	48.43	-5.57	54.00	41.26	33.22	7.18	33.24	AVERAGE	100	105

Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	2382.740	39.10	-14.90	54.00	39.38	28.09	5.14	33.50	AVERAGE	100	7
2	2382.740	47.88	-26.12	74.00	48.15	28.09	5.14	33.50	PEAK	100	7
3	4824.100	40.84	-13.16	54.00	33.67	33.22	7.18	33.24	AVERAGE	100	112
4	4824.100	49.83	-24.17	74.00	42.66	33.22	7.18	33.24	PEAK	100	27

Temperature	23℃	Humidity	54%
Test Engineer	Beck Wu	Configurations	802.11b CH 6

Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	2376.100	52.97	-21.03	74.00	53.24	28.09	5.14	33.50	PEAK	100	331
2	2376.100	41.42	-12.58	54.00	41.69	28.09	5.14	33.50	AVERAGE	100	331
3	4873.912	53.94	-20.06	74.00	46.63	33.33	7.20	33.23	PEAK	100	257
4 !	4873.912	49.40	-4.60	54.00	42.09	33.33	7.20	33.23	AVERAGE	100	257

Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	2376.100	36.92	-17.08	54.00	37.20	28.09	5.14	33.50	AVERAGE	100	7
2	2376.100	49.05	-24.95	74.00	49.33	28.09	5.14	33.50	PEAK	100	7
3	4873.912	39.10	-14.90	54.00	31.79	33.33	7.20	33.23	AVERAGE	100	239
4	4873.912	49.61	-24.39	74.00	42.30	33.33	7.20	33.23	PEAK	100	239

Temperature	23℃	Humidity	54%
Test Engineer	Beck Wu	Configurations	802.11b CH 11

Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	2376.040	41.03	-12.97	54.00	41.30	28.09	5.14	33.50	AVERAGE	100	336
2	2376.040	51.47	-22.53	74.00	51.75	28.09	5.14	33.50	PEAK	100	336
3 !	4924.016	51.17	-2.83	54.00	43.72	33.45	7.22	33.22	AVERAGE	100	265
4	4924.016	56.08	-17.92	74.00	48.63	33.45	7.22	33.22	PEAK	100	265

Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	2376.040	34.85	-19.15	54.00	35.13	28.09	5.14	33.50	AVERAGE	100	30
2	2376.040	43.36	-30.64	74.00	43.64	28.09	5.14	33.50	PEAK	100	30
3	4924.016	40.41	-13.59	54.00	32.96	33.45	7.22	33.22	AVERAGE	100	0
4	4924.016	48.95	-25.05	74.00	41.50	33.45	7.22	33.22	PEAK	100	0

Temperature	23℃	Humidity	54%
Test Engineer	Beck Wu	Configurations	802.11g CH 1

Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	2375.600	44.77	-9.23	54.00	45.05	28.09	5.14	33.50	AVERAGE	100	5
2	2375.600	55.91	-18.09	74.00	56.19	28.09	5.14	33.50	PEAK	100	5

Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	2376.000	40.13	-13.87	54.00	40.41	28.09	5.14	33.50	AVERAGE	100	6
2	2376.000	51.34	-22.66	74.00	51.62	28.09	5.14	33.50	PEAK	100	6

Temperature	23℃	Humidity	54%
Test Engineer	Beck Wu	Configurations	802.11g CH 6

Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	2376.642	45.99	-8.01	54.00	46.27	28.09	5.14	33.50	AVERAGE	100	4
2	2376.642	60.45	-13.55	74.00	60.73	28.09	5.14	33.50	PEAK	100	4

Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	2376.900	40.39	-13.61	54.00	40.67	28.09	5.14	33.50	AVERAGE	100	7
2	2376.900	52.78	-21.22	74.00	53.06	28.09	5.14	33.50	PEAK	100	7

Temperature	23℃	Humidity	54%
Test Engineer	Beck Wu	Configurations	802.11g CH 11

Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	2376.142	45.87	-8.13	54.00	46.14	28.09	5.14	33.50	AVERAGE	100	16
2	2376.142	55.68	-18.32	74.00	55.96	28.09	5.14	33.50	PEAK	100	16

Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	2376.000	39.68	-14.32	54.00	39.95	28.09	5.14	33.50	AVERAGE	100	7
2	2376.000	47.98	-26.02	74.00	48.26	28.09	5.14	33.50	PEAK	100	7

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Temperature	23℃	Humidity	54%
Test Engineer	Beck Wu	Configurations	802.11a CH 149

Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 !	11488.260	57.38	-2.62	60.00	40.38	39.20	10.90	33.10	AVERAGE	108	196
2	11488.260	70.22	-9.78	80.00	53.22	39.20	10.90	33.10	PEAK	108	196
4 !	17234.020	75.97			53.13	40.93	14.31	32.40	PEAK	114	243

Note: Item 4 is on un-restricted band, so the limit is -20dBc for the field strength of fundamental emission.

Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 !	11491.060	54.90	-5.10	60.00	37.90	39.20	10.90	33.10	AVERAGE	116	338
2	11491.060	69.45	-10.55	80.00	52.45	39.20	10.90	33.10	PEAK	116	338
4 !	17234.020	75.18			52.33	40.93	14.31	32.40	PEAK	125	171

Note: Item 4 is on un-restricted band, so the limit is -20dBc for the field strength of fundamental emission.

Temperature	23℃	Humidity	54%
Test Engineer	Beck Wu	Configurations	802.11a CH 157

Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 !	11570.650	58.31	-1.69	60.00	41.30	39.21	10.91	33.12	AVERAGE	107	320
2	11570.650	71.28	-8.72	80.00	54.27	39.21	10.91	33.12	PEAK	107	320
4	17355.350	73.72			50.33	41.44	14.35	32.40	PEAK	103	322

Note: Item 4 is on un-restricted band, so the limit is -20dBc for the field strength of fundamental emission.

Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 !	11569.630	57.01	-2.99	60.00	40.00	39.21	10.91	33.11	AVERAGE	113	257
2	11569.630	69.31	-10.69	80.00	52.30	39.21	10.91	33.11	PEAK	113	257
4 !	17355.350	76.29			52.91	41.44	14.35	32.40	PEAK	113	200

Note: Item 4 is on un-restricted band, so the limit is -20dBc for the field strength of fundamental emission.

Temperature	23℃	Humidity	54%
Test Engineer	Beck Wu	Configurations	802.11a CH 165

Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 !	11652.500	57.66	-2.34	60.00	40.65	39.23	10.92	33.13	AVERAGE	102	319
2	11652.500	70.09	-9.91	80.00	53.07	39.23	10.92	33.13	PEAK	102	319
4	17475.100	73.44			49.49	41.95	14.39	32.40	PEAK	103	331

Note: Item 4 is on un-restricted band, so the limit is -20dBc for the field strength of fundamental emission.

Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 !	11650.110	57.48	-2.52	60.00	40.47	39.23	10.92	33.13	AVERAGE	120	256
2	11650.110	69.74	-10.26	80.00	52.72	39.23	10.92	33.13	PEAK	120	256
4	17475.100	73.50			49.55	41.95	14.39	32.40	PEAK	106	200

Note: Item 4 is on un-restricted band, so the limit is -20dBc for the field strength of fundamental emission.

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.6. Band Edge Emissions Measurement

4.6.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100 KHz /100 KHz for Peak

4.6.3. Test Procedures

1. The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around bandedges.
2. In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

4.6.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.5.4.

4.6.5. Test Deviation

There is no deviation with the original standard.

4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.6.7. Test Result of Band Edge and Fundamental Emissions

Temperature	23℃	Humidity	56%
Test Engineer	Beck Wu	Configurations	802.11b CH 1, 11

Channel 1



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	2386.200	61.07	-12.93	74.00	27.80	28.13	5.14	0.00	PEAK	100	261
2 !	2386.400	52.09	-1.91	54.00	18.83	28.13	5.14	0.00	AVERAGE	100	261
3	2413.200	109.46			76.10	28.18	5.19	0.00	PEAK	100	261
4	2414.800	105.53			72.17	28.18	5.19	0.00	AVERAGE	100	261

Note: Items 1 & 2 are Band- Edge.

Channel 11



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	2461.200	112.01			78.46	28.31	5.24	0.00	PEAK	100	280
2 @	2461.200	108.33			74.78	28.31	5.24	0.00	AVERAGE	100	280
3 !	2487.700	52.84	-1.16	54.00	19.15	28.40	5.29	0.00	AVERAGE	100	280
4	2487.700	62.11	-11.89	74.00	28.42	28.40	5.29	0.00	PEAK	100	280

Note: Items 3 & 4 are Band- Edge.

Temperature	23℃	Humidity	56%
Test Engineer	Beck Wu	Configurations	802.11g CH 1, 11

Channel 1



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 !	2390.000	50.77	-3.23	54.00	17.45	28.13	5.19	0.00	AVERAGE	100	330
2	2390.000	65.22	-8.78	74.00	31.90	28.13	5.19	0.00	PEAK	100	330
3	2415.000	108.57			75.21	28.18	5.19	0.00	PEAK	100	330
4	2415.000	98.89			65.53	28.18	5.19	0.00	AVERAGE	100	330

Note: Items 1 & 2 are Band- Edge.

Channel 11



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	2459.200	113.27			79.72	28.31	5.24	0.00	PEAK	100	34
2 @	2459.800	102.62			69.08	28.31	5.24	0.00	AVERAGE	100	34
3 !	2483.700	51.50	-2.50	54.00	17.86	28.36	5.29	0.00	AVERAGE	100	34
4 !	2484.100	72.78	-1.22	74.00	39.13	28.36	5.29	0.00	PEAK	100	34
5 !	2500.000	52.58	-1.42	54.00	18.89	28.40	5.29	0.00	AVERAGE	100	34
6	2500.000	62.58	-11.42	74.00	28.89	28.40	5.29	0.00	PEAK	100	34

Note: Items 3 & 4 & 5 & 6 are Band- Edge.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

For Emission not in Restricted Band

Low Band Edge Plot on Configuration IEEE 802.11b / 2412 MHz



Date: 27.SEP.2006 03:46:36

High Band Edge Plot on Configuration IEEE 802.11b / 2462 MHz



Date: 27.SEP.2006 03:49:53

Low Band Edge Plot on Configuration IEEE 802.11g / 2412 MHz



Date: 27.SEP.2006 03:44:34

High Band Edge Plot on Configuration IEEE 802.11g / 2462 MHz



Date: 27.SEP.2006 03:42:40

Low Band Edge Plot on Configuration IEEE 802.11a / 5745 MHz



Date: 27.SEP.2006 04:03:04

High Band Edge Plot on Configuration IEEE 802.11a / 5825 MHz



Date: 27.SEP.2006 04:05:27

4.7. Antenna Requirements

4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMC Receiver	R&S	ESCS 30	100174	9kHz – 2.75GHz	Feb. 22, 2006	Conduction (CO04-HY)
LISN	MessTec	NNB-2/16Z	99079	9kHz – 30MHz	Dec. 19, 2005	Conduction (CO04-HY)
LISN (Support Unit)	EMCO	3810/2NM	9708-1839	9kHz – 30MHz	Mar. 18, 2006	Conduction (CO04-HY)
RF Cable-CON	UTIFLEX	3102-26886-4	CB049	9kHz – 30MHz	Apr. 20, 2006	Conduction (CO04-HY)
EMI Filter	LINDGREN	LRE-2030	2651	< 450 Hz	N/A	Conduction (CO04-HY)
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30 MHz - 1 GHz 3m	Jun. 15, 2006	Radiation (03CH03-HY)
Amplifier	SCHAFFNER	CPA9231A	18667	9 kHz - 2 GHz	Jan. 18, 2006	Radiation (03CH03-HY)
Amplifier	Agilent	8449B	3008A02120	1 GHz - 26.5 GHz	May 29, 2006	Radiation (03CH03-HY)
Amplifier	MITEQ	AMF-6F-260400	923364	26.5 GHz - 40 GHz	Jan. 24, 2006*	Radiation (03CH03-HY)
Spectrum Analyzer	R&S	FSP40	100004/040	9 kHZ - 40 GHz	Sep. 30, 2005	Radiation (03CH03-HY)
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz - 30 MHz	May 23, 2006*	Radiation (03CH03-HY)
Bilog Antenna	SCHAFFNER	CBL 6112D	22237	30 MHz – 1 GHz	Jul. 24, 2006	Radiation (03CH03-HY)
Horn Antenna	EMCO	3115	6903	1GHz ~ 18GHz	Mar. 15, 2006	Radiation (03CH03-HY)
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	15 GHz - 40 GHz	NCR	Radiation (03CH03-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	30 MHz - 1 GHz	Dec.02, 2005	Radiation (03CH03-HY)
RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	1 GHz - 40 GHz	Dec.02, 2005	Radiation (03CH03-HY)
Turn Table	HD	DS 420	420/650/00	0 – 360 degree	N/A	Radiation (03CH03-HY)
Antenna Mast	HD	MA 240	240/560/00	1 m - 4 m	N/A	Radiation (03CH03-HY)
Spectrum Analyzer	R&S	FSP30	100023	9kHz ~ 30GHz	Nov. 26, 2005	Conducted (TH01-HY)
Power Meter	R&S	NRVS	100764	DC ~ 40GHz	Jul, 20, 2006	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z51	100666	DC ~ 40GHz	Jul. 20, 2006	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z32	100057	30MHz ~ 6GHz	Jun, 10, 2006	Conducted (TH01-HY)
AC Power Source	HPC	HPA-500W	HPA-9100024	AC 0 ~ 300V	Apr. 21, 2005*	Conducted (TH01-HY)
DC Power Source	G.W.	GPC-6030D	C671845	DC 1V ~ 60V	Dec. 28, 2005	Conducted (TH01-HY)
Temp. and Humidity Chamber	KSON	THS-C3L	612	N/A	Oct. 01, 2005	Conducted (TH01-HY)
RF CABLE-1m	Jye Bao	RG142	CB034-1m	20MHz ~ 7GHz	Dec. 30, 2005	Conducted (TH01-HY)

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
RF CABLE-2m	Jye Bao	RG142	CB035-2m	20MHz ~ 1GHz	Dec. 30, 2005	Conducted (TH01-HY)
Oscilloscope	Tektronix	TDS1012	CO38515	100MHz / 1GS/s	Jun. 20, 2006	Conducted (TH01-HY)
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	Dec. 30, 2005	Conducted (TH01-HY)
Data Generator	Tektronix	DG2030	063-2920-50	0.1Hz~400MHz	Jun. 16, 2006	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is one year.

Note: * Calibration Interval of instruments listed above is two year.

Note: NCR means Non-Calibration required.

6. TEST LOCATION

SHIJR	ADD	:	6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C.
	TEL	:	886-2-2696-2468
	FAX	:	886-2-2696-2255
HWA YA	ADD	:	No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.
	TEL	:	886-3-327-3456
	FAX	:	886-3-318-0055
LINKOU	ADD	:	No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C
	TEL	:	886-2-2601-1640
	FAX	:	886-2-2601-1695
DUNGHU	ADD	:	No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C.
	TEL	:	886-2-2631-4739
	FAX	:	886-2-2631-9740
JUNGHE	ADD	:	7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C.
	TEL	:	886-2-8227-2020
	FAX	:	886-2-8227-2626
NEIHU	ADD	:	4Fl., No. 339, Hsin Hu 2nd Rd., Taipei 114, Taiwan, R.O.C.
	TEL	:	886-2-2794-8886
	FAX	:	886-2-2794-9777
JHUBEI	ADD	:	No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C.
	TEL	:	886-3-656-9065
	FAX	:	886-3-656-9085