



Engineering and Testing for EMC and Safety Compliance

**Certification Application Report
FCC Part 15.225 & Industry Canada RSS-210**

Test Lab: Rhein Tech Laboratories, Inc. Phone: 703-689-0368 360 Herndon Parkway Fax: 703-689-2056 Suite 1400 Web: www.rheintech.com Herndon, VA 20170 E-Mail: atcbinfo@rheintech.com		Applicant: Sirit Technologies Inc. Phone: 972-243-7208 1321 Valwood Parkway Fax: 972-243-8034 Suite 620 Contact: Michael Koch Carrollton, TX 75006 E-Mail: mkoch@sirit.com Web: www.sirit.com	
FCC ID/ IC ID:	M4ZPNPUSB/ 3637B-PNPUSB	Test Report Date:	August 18, 2006
Platform:	N/A	RTL Work Order #:	2006114
Model Name/Model #:	PnP USB RFID Reader/ PnP USB	RTL Quote #:	QRTL06-317
American National Standard Institute:	ANSI C63.4-2003: Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz		
FCC Classification:	DXX – Part 15 Low Power Communication Device Transmitter		
FCC Rule Part(s):	FCC Rules Part 15.225 (10-01-05): Operation within the band 13.110-14.010 MHz		
Industry Canada:	RSS-210: Low Power License-Exempt Communications Devices		
Digital Interface Information	Digital Interface was found to be compliant		
Frequency Range (MHz)	Output Power (W)	Frequency Stability (%)	Emission Designator
13.56	0.000012*	0.001	14K0F1D

* power reported is peak EIRP

I, the undersigned, hereby declare that the equipment tested and referenced in this report conforms to the identified standard(s) as described in this test report. No modifications were made to the equipment during testing in order to achieve compliance with these standards. Furthermore, there was no deviation from, additions to, or exclusions from, the applicable parts of FCC Part 2, FCC Part 15, ANSI C63.4, and Industry Canada RSS-210.

Signature: 

Date: August 18, 2006

Typed/Printed Name: Desmond A. Fraser

Position: President

*This report may not be reproduced, except in full, without the written approval of Rhein Tech Laboratories, Inc.
The test results relate only to the item(s) tested.*

Table of Contents

1	General Information	4
1.1	Scope	4
1.2	Description of EUT	4
1.3	Test Facility	4
1.4	Related Submittal(s)/Grant(s)	4
1.5	Modifications	4
2	Test Information	5
2.1	Description of Test Modes	5
2.2	Exercising the EUT	5
2.3	Test Result Summary	5
2.4	Test System Details	6
2.5	Configuration of Tested System	7
3	Peak Output Power - §15.225(a); RSS-210 §A2.6	8
3.1	Power Output Test Procedure	8
3.2	Power Output Test Data	8
4	Frequency Stability – FCC §15.225(e); IC RSS-210 §A2.6, §2.1	9
4.1	Frequency Stability Test Procedure	9
4.2	Frequency Stability Test Data	9
5	20 dB Bandwidth – IC RSS-210 §A2.6; RSS-Gen	12
5.1	20 dB Bandwidth Test Procedure	12
5.2	20 dB Modulated Bandwidth Test Data	12
6	Conducted Limits - §15.207; RSS-GEN	14
6.1	Test Methodology for Conducted Line Emissions Measurements	14
6.2	Conducted Line Emissions Test	14
6.3	Conducted Line Emission Test Data	15
7	Radiated Emissions - §15.209; RSS-210 §A2.6 and RSS-Gen	16
7.1	Limits of Radiated Emissions Measurement	16
7.2	Radiated Emissions Measurement Test Procedure	16
7.3	Radiated Emissions Test Results	17
7.3.1	Radiated Emissions - Digital	17
7.3.2	Radiated Emissions Harmonics/Spurious	18
8	Conclusion	18

Figure Index

Figure 2-1:	Configuration of System Under Test	7
-------------	--	---

Table Index

Table 2-1:	Channel Tested	5
Table 2-3:	Test Result Summary – FCC Part 15, Subpart C (Section 15.225).....	5
Table 2-4:	Equipment Under Test.....	6
Table 3-1:	Power Output Test Equipment	8
Table 3-2:	Power Output Test Data.....	8
Table 4-1:	Temperature Frequency Stability	9
Table 4-2:	Test Equipment for Testing Frequency Stability	10
Table 4-2:	Voltage Frequency Stability	11
Table 5-1:	20 dB Bandwidth Test Equipment	12
Table 5-2:	20 db Bandwidth Test Data	13
Table 6-1:	Conducted Line Emissions Test Equipment.....	15
Table 6-2:	Conducted Emissions (Neutral Side) Transmitting.....	15
Table 6-3:	Conducted Emissions (Phase Side) Transmitting	15
Table 7-1:	Radiated Emissions Test Equipment	17
Table 7-2:	Digital Radiated Emissions	17
Table 7-3:	Radiated Emissions Harmonics/Spurious	18

Plot Index

Plot 4-1:	Temperature Stability	10
Plot 4-2:	Voltage Stability	11
Plot 5-1:	Occupied Bandwidth	12

Appendix Index

Appendix A:	FCC Part 1.1307, 1.1310, 2.1091, 2.1093.....	19
Appendix B:	Agency Authorization Letter.....	20
Appendix C:	Confidentiality Request Letter.....	21
Appendix D:	IC Letters	22
Appendix E:	Label and Label Location	23
Appendix F:	Technical Operational Description	24
Appendix G:	Schematics	25
Appendix H:	Block Diagram	26
Appendix I:	Manual	27
Appendix J:	Test Photographs.....	28
Appendix K:	External Photographs	32
Appendix L:	Internal Photographs	34

Photograph Index

Photograph 1:	ID Label Location	23
Photograph 2:	Radiated Testing – Front View	28
Photograph 3:	Radiated Testing – Back View	29
Photograph 4:	Conducted AC Testing – Front View	30
Photograph 5:	Conducted AC Testing – Back View	31
Photograph 6:	Front View	32
Photograph 7:	Back View	33
Photograph 8:	Inside Case	34
Photograph 9:	Top of PCB.....	35
Photograph 10:	Bottom of PCB	36

1 General Information

1.1 Scope

Applicable Standards:

- FCC Rules Part 15.225; Operation within the band 13.110-14.010 MHz
- Industry Canada RSS-210: Low Power License-Exempt Communications Devices

1.2 Description of EUT

Equipment Under Test	
Model Name/#	PnP USB RFID Reader/PnP USB
Power Supply	Powered by 5 VDC from the USB connector
Modulation Type	FSK; FM
Frequency	13.56 MHz
Antenna Connector Type	Internally hardwired
Antenna Type	Magnetic Loop

1.3 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located at 360 Herndon Parkway, Suite 1400, Herndon, Virginia 20170. This site has been fully described in a report and approved by the Federal Communications Commission to perform AC line conducted and radiated emissions testing (ANSI C63.4 2003).

1.4 Related Submittal(s)/Grant(s)

This is an original application for certification for Sirit Technologies Inc. Model #: PnP USB, FCC ID: M4ZPNPUSB, IC: 3637B-PNPUSB.

1.5 Modifications

A 3.3 V power regulator replaced a 5 V for compliance with radiated spurious emissions, and the antenna was replaced by a dummy load to determine the AC conducted emissions compliance.

2 Test Information

2.1 Description of Test Modes

In accordance with FCC 15.31(m), the following frequency was tested:

Table 2-1: Channel Tested

Frequency (MHz)
13.56

2.2 Exercising the EUT

The EUT was tested in all three orthogonal planes in order to determine worst-case emissions. The EUT was provided with software to transmit continuously during testing. The carrier was also checked to verify that information was being transmitted. There were no deviations from the test standard(s) and/or methods. The test results reported relate only to the item tested.

2.3 Test Result Summary

Table 2-2: Test Result Summary – FCC Part 15, Subpart C (Section 15.225)

Standard	Test	Pass/Fail or N/A
FCC 15.207	AC Power Conducted Emissions	Pass
FCC 15.209	Radiated Emissions	Pass
FCC 15.225(a)	Maximum Peak Power Output	Pass
FCC 15.225(e)	Frequency Stability	Pass

2.4 Test System Details

The test sample was received on August 7, 2006 and August 18th, 2006. The FCC identifiers for all applicable equipment, plus descriptions of all cables used in the tested system, are identified in the following tables.

Table 2-3: Equipment Under Test

Part	Manufacturer	Model	Serial Number	FCC ID	Cable Description	RTL Bar Code
RFID USB	Sirit, Inc.	PnP USB	N/A	M4ZPNPUSB	N/A	17425
RFIDUSB	Sirit, Inc.	PnP USB	N/A	M4ZPNPUSB	N/A	17422
RFIDUSB	Sirit, Inc.	PnP USB	N/A	M4ZPNPUSB	N/A	17455
RFIDUSB	Sirit, Inc.	PnP USB	N/A	M4ZPNPUSB	N/A	17451
USB Cable	Sirit, Inc.	N/A	N/A	N/A	1.8 m shielded USB-A/Mini-B5	17454
Laptop Computer	Toshiba	Satellite 1905-S301	92043315C	N/A	3 m unshielded power	16621
19V 4.74A AC Adaptor	EDA Power Elec.	EA1060B	N/A	N/A	1.9 m unshielded AC power, 1.2 m unshielded DC power	16672

2.5 Configuration of Tested System




Figure 2-1: Configuration of System Under Test

3 Peak Output Power - §15.225(a); RSS-210 §A2.6

3.1 Power Output Test Procedure

A radiated power measurement of the EUT was taken using a loop antenna and Agilent spectrum analyzer at 3 m. The device was rotated 360° and the antenna polarized in three orthogonal positions. The power was converted from a 3 m distance to a 30 m distance using the inverse square method, or $40\log(30/3) = 40$ dB was added to the limit of 15,848 uV/m or 84 dBuV/m at 30 m, which is 124 dBuV/m at 3 m; a 20 dB offset was used as the site factor at this frequency (reference OBW plot).

Table 3-1: Power Output Test Equipment

RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Due Date
901413	Agilent	E4448A	Spectrum Analyzer	US44020346	11/2/06
900151	Rohde and Schwarz	HFH2-Z2	Loop Antenna, (9 kHz - 30 MHz)	827525/019	8/25/06

3.2 Power Output Test Data

Table 3-2: Power Output Test Data


Frequency (MHz)	Peak EIRP (dBuV/m)	Limit (dBuV/m)	Peak EIRP (uW)
13.56	76.3	124.0	12.8

§ 15.225 Operation within the band 13.110–14.010 MHz.

(a) The field strength of any emissions within the band 13.553–13.567 MHz shall not exceed 15,848 microvolts/ meter at 30 meters.

Test Personnel:

Daniel W. Baltzell
EMC Test Engineer



Signature

August 7, 2006
Date Of Test

4 Frequency Stability – FCC §15.225(e); IC RSS-210 §A2.6, §2.1

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency over a temperature variation of -20° to $+50^{\circ}\text{C}$ at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20°C . For battery operated equipment, the equipment tests shall be performed using a new battery.

4.1 Frequency Stability Test Procedure

ANSI/TIA-603-B-2002, section 2.3.1 and 2.3.2

The carrier frequency stability is the ability of the transmitter to maintain an assigned carrier frequency.

The EUT was evaluated over the temperature range -20°C to $+50^{\circ}\text{C}$.

The temperature was initially set to -20°C and a 1-hour period was observed for stabilization of the EUT. The frequency stability was measured within one minute after application of primary power to the transmitter. The temperature was raised at intervals of 10°C through the range. A $\frac{1}{2}$ hour period was observed to stabilize the EUT at each measurement step, and the frequency stability was measured within one minute after application of primary power to the transmitter. Additionally, the power supply voltage of the EUT was varied $\pm 15\%$ nominal input voltage.

4.2 Frequency Stability Test Data

The worst-case test data are shown below in Table 4-1 and Table 4-2.

Table 4-1: Temperature Frequency Stability

Temperature ($^{\circ}\text{C}$)	Relative to 20°C	% difference	Limit ($\pm 0.01\%$)	Margin (%)
-30	13.55998088	-0.0001	0.01	-0.0099
-20	13.56001083	0.0001	0.01	-0.0099
-10	13.56003225	0.0002	0.01	-0.0098
0	13.56002892	0.0002	0.01	-0.0098
10	13.56000833	0.0001	0.01	-0.0099
20	13.56000000	0.0000	0.01	0
30	13.55997542	-0.0002	0.01	-0.0098
40	13.55995350	-0.0003	0.01	-0.0097

Plot 4-1: Temperature Stability




Table 4-2: Test Equipment for Testing Frequency Stability

RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Due
900946	Tenney Engineering, Inc.	TH65	Temperature Chamber with Humidity	11380	1/20/07
901300	Agilent	53131A (225 MHz)	Universal Frequency Counter	MY40001345	11/23/06
N/A	Hewlett Packard	6024A	Power Supply	N/A	N/A
901350	Meterman	33XR	Multimeter	040402802	8/3/06

Test Personnel:

Daniel W. Baltzell
Test Engineer


Signature

August 10, 2006
Date Of Test

Table 4-3: Voltage Frequency Stability

Voltage (VDC)	Frequency Measured (MHz)	% error	Limit (%)	Margin (%)
4.25	13.56017756	0.0013	0.01	-0.0087
5.00	13.56017947	0.0013	0.01	-0.0087
5.75	13.56018796	0.0014	0.01	-0.0086

Plot 4-2: Voltage Stability



Test Personnel:

Daniel W. Baltzell
 Test Engineer

Signature

August 11, 2006
 Date Of Test

5 20 dB Bandwidth – IC RSS-210 §A2.6; RSS-Gen

5.1 20 dB Bandwidth Test Procedure

The minimum 20 dB bandwidths were measured using a 50-ohm spectrum analyzer. The carrier was adjusted on the analyzer so that it was displayed entirely on the spectrum analyzer. The sweep time was set to auto with the max hold function used in peak detector mode. The resolution bandwidth was set to 9 kHz, and the video bandwidth set at 30 kHz

Table 5-1: 20 dB Bandwidth Test Equipment

RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Due Date
901413	Agilent	E4448A	Spectrum Analyzer	US44020346	11/2/06
900151	Rohde and Schwarz	HFH2-Z2	Loop Antenna (9 kHz - 30 MHz)	827525/019	8/25/06

5.2 20 dB Modulated Bandwidth Test Data

Plot 5-1: Occupied Bandwidth





Table 5-2: 20 db Bandwidth Test Data

Frequency (MHz)	20 dB Bandwidth (kHz)
13.56	14

Test Personnel:

Daniel W. Baltzell EMC Test Engineer	 Signature	August 7, 2006 Date Of Test
---	---	--------------------------------

6 Conducted Limits - §15.207; RSS-GEN

6.1 Test Methodology for Conducted Line Emissions Measurements

The power line conducted emission measurements were performed in a Series 81 type shielded enclosure manufactured by Rayproof. The EUT was assembled on a wooden table 80 centimeters high. Power was fed to the EUT through a 50 ohm / 50 micro Henry Line Impedance Stabilization Network (EUT LISN). The EUT LISN was fed power through an A.C. filter box on the outside of the shielded enclosure. The filter box and EUT LISN housing are bonded to the ground plane of the shielded enclosure. A second LISN, the peripheral LISN, provides isolation for the EUT test peripherals. This peripheral LISN was also fed A.C. power. A metal power outlet box, which is bonded to the ground plane and electrically connected to the peripheral LISN, powers the EUT host peripherals.

The spectrum analyzer was connected to the A.C. line through an isolation transformer. The 50-ohm output of the EUT LISN was connected to the spectrum analyzer input through a Solar filter. The filter is used to prevent overload of the spectrum analyzer from DC noise. Conducted emission levels were measured on each current-carrying line with the spectrum analyzer operating in the CISPR quasi-peak mode (or peak mode if applicable). The analyzer's 6 dB bandwidth was set to 9 kHz. No video filter less than 10 times the resolution bandwidth was used. Average measurements are performed in linear mode using a 10 kHz resolution bandwidth, a 1 Hz video bandwidth, and by increasing the sweep time in order to obtain a calibrated measurement. The emission spectrum was scanned from 150 kHz to 30 MHz. The highest emission amplitudes relative to the appropriate limit were measured and have been recorded in this report.

Note: Rhein Tech Laboratories, Inc. has implemented procedures to minimize errors that occur from test instruments, calibration, procedures, and test setups. Test instrument and calibration errors are documented from the manufacturer or calibration lab. Other errors have been defined and calculated within the Rhein Tech Quality Manual, Section 6.1. Rhein Tech implements the following procedures to minimize errors that may occur: yearly as well as daily calibration methods, technician training, and emphasis to employees on avoiding error.

6.2 Conducted Line Emissions Test

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range in peak mode. If the conducted emissions exceed the average limits, the instrument set to the quasi-peak mode, then measurements are made in the average mode and these compared to the appropriate limits to determine a pass/fail criteria, the emissions were scanned between 150 kHz to 30 MHz on the NEUTRAL SIDE and PHASE SIDE.

Table 6-1: Conducted Line Emissions Test Equipment

RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Due Date
900931	Hewlett Packard	8566B	Spectrum Analyzer (100 Hz - 22 GHz)	3138A07771	8/3/07
901084	AFJ international	LS16	16A LISN	16010020082	1/23/07

6.3 Conducted Line Emission Test Data

Table 6-2: Conducted Emissions (Neutral Side) Transmitting

Emission Frequency (MHz)	Test Detector	Analyzer Reading (dBuV)	Site Correction Factor (dB)	Emission Level (dBuV)	QP Limit (dBuV)	QP Margin (dBuV)	AV Limit (dBuV)	AV Margin (dBuV)	Pass/Fail
0.150	Qp	61.4	0.2	61.6	65.8	-4.2			Pass
0.150	Av	37.4	0.2	37.6			56.0	-18.4	Pass
0.225	Qp	50.6	0.2	50.8	62.6	-11.8			Pass
0.225	Av	44.0	0.2	44.2			52.6	-8.4	Pass
0.382	Pk	45.1	0.3	45.4			48.2	-2.8	Pass
0.834	Pk	42.3	0.3	42.6			46.0	-3.4	Pass
2.088	Pk	41.5	0.7	42.2			46.0	-3.8	Pass
22.936	Qp	41.8	2.4	44.2	60.0	-15.8			Pass
22.936	Av	32.3	2.4	34.7			50.0	-15.3	Pass

Pk = Peak; Qp = quasi-peak; Av = Average

Table 6-3: Conducted Emissions (Phase Side) Transmitting

Emission Frequency (MHz)	Test Detector	Analyzer Reading (dBuV)	Site Correction Factor (dB)	Emission Level (dBuV)	QP Limit (dBuV)	QP Margin (dBuV)	AV Limit (dBuV)	AV Margin (dBuV)	Pass/Fail
0.150	Qp	64.0	0.2	64.2	66.0	-1.8			Pass
0.150	Av	37.5	0.2	37.7			56.0	-18.3	Pass
0.284	Pk	46.5	0.2	46.7			50.7	-4.0	Pass
0.396	Pk	41.7	0.3	42.0			47.9	-5.9	Pass
1.862	Pk	41.7	0.7	42.4			46.0	-3.6	Pass
3.540	Pk	40.2	1.0	41.2			46.0	-4.8	
24.180	Qp	47.9	2.5	50.4	60.0	-9.6			Pass
24.180	Av	44.6	2.5	47.1			50.0	-2.9	

Pk = Peak; Qp = quasi-peak; Av = Average

7 Radiated Emissions - §15.209; RSS-210 §A2.6 and RSS-Gen

7.1 Limits of Radiated Emissions Measurement

Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
0.009-0.490	2400/f (kHz)	300
0.490-1.705	2400/f (kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

As shown in 15.35(b), for frequencies above 1000 MHz, the field strength limits are based on average detector, however the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB, under any circumstances of modulation.

7.2 Radiated Emissions Measurement Test Procedure

Before final measurements of radiated emissions were made on the open-field three/ten meter range, the EUT was scanned indoors at one and three meter distances. This was done in order to determine its emissions spectrum signature. The physical arrangement of the test system and associated cabling was varied in order to determine the effect on the EUT's emissions in amplitude, direction and frequency. This process was repeated during final radiated emissions measurements on the open-field range, at each frequency, in order to ensure that maximum emission amplitudes were attained.

Final radiated emissions measurements were made on the three/ten-meter, open-field test site. The EUT was placed on a nonconductive turntable 0.8 meters above the ground plane. The spectrum was examined from 9 kHz to the 10th harmonic of the highest fundamental transmitter frequency.

At each frequency, the EUT was rotated 360°, and the antenna was raised and lowered from 1 to 4 meters in order to determine the emission's maximum level. Measurements were taken using both horizontal and vertical antenna polarizations. For frequencies between 30 and 1000 MHz, the spectrum analyzer's 6 dB bandwidth was set to 120 kHz, and the analyzer was operated in the CISPR quasi-peak detection mode. For emissions above 1000 MHz, emissions are measured using the average detector function with a minimum resolution bandwidth of 1 MHz. No video filter less than 10 times the resolution bandwidth was used. The highest emission amplitudes relative to the appropriate limit were measured and recorded in this report.

Table 7-1: Radiated Emissions Test Equipment

RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Due Date
900151	Rohde and Schwarz	HFH2-Z2	Antenna (Loop antenna, (9 kHz - 30 MHz)	827525/019	8/25/06
900905	Rhein Tech Labs	PR-1040	OATS 1 Preamplifier 40 dB (30 MHz – 2 GHz)	1006	3/15/07
900878	Rhein Tech Labs	AM3-1197-0005	3 meter antenna mast, polarizing	Outdoor Range 1	Not Required
901242	Rhein Tech Labs	WRT-000-0003	Wood rotating table	N/A	Not Required
900931	Hewlett Packard	8566B	Spectrum Analyzer (100 Hz - 22 GHz)	3138A07771	8/3/07
900930	Hewlett Packard	85662A	Spectrum Analyzer Display Section	3144A20839	8/3/07
900889	Hewlett Packard	85685A	RF Preselector (20 Hz - 2 GHz)	3146A01309	4/12/07
901413	Agilent	E4448A	Spectrum Analyzer	US44020346	11/2/06

7.3 Radiated Emissions Test Results


7.3.1 Radiated Emissions - Digital

Table 7-2: Digital Radiated Emissions

Temperature: 82°F Humidity: 62%										
Emission Frequency (MHz)	Test Detector	Antenna Polarity (H/V)	Turntable Azimuth (deg)	Antenna Height (m)	Analyzer Reading (dBuV)	Site Correction Factor (dB/m)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pass/Fail
189.842	Qp	V	280	1.0	38.7	-18.3	20.4	54.0	-33.6	Pass
203.403	Qp	V	0	1.0	38.0	-17.6	20.4	54.0	-33.6	Pass
318.664	Qp	V	0	1.0	33.7	-13.4	20.3	56.9	-36.6	Pass
468.956	Qp	V	0	1.0	36.4	-8.6	27.8	56.9	-29.1	Pass
555.967	Qp	V	0	1.0	35.7	-6.0	29.7	56.9	-27.2	Pass
739.030	Qp	V	0	1.0	34.8	-4.0	30.8	56.9	-26.1	Pass

Test Personnel:

Daniel W. Baltzell
EMC Test Engineer



Signature

August 8, 2006
Date Of Test


7.3.2 Radiated Emissions Harmonics/Spurious

Table 7-3: Radiated Emissions Harmonics/Spurious

Emission Frequency (MHz)	Test Detector	Antenna Polarity (H/V)	Turntable Azimuth (deg)	Antenna Height (m)	Analyzer Reading (dBuV)	Site Correction Factor (dB/m)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
13.560	Pk	V	0	1.0	53.3	20.0	76.3	144.0	-70.7
13.560	Qp	V	0	1.0	52.7	20.0	72.7	124.0	-51.3
27.120	Pk	V	0	1.0	16.5	21.7	38.2	89.5	-51.3
27.120	Qp	V	0	1.0	12.4	21.7	34.1	69.5	-35.4
40.682	Pk	V	225	1.0	45.8	-17.6	28.2	60.0	-31.8
40.682	Qp	V	230	1.0	44.2	-17.6	26.6	40.0	-13.4
54.237	Pk	V	160	1.0	55.4	-22.4	33.0	60.0	-27.0
54.237	Qp	V	160	1.0	54.9	-22.4	32.5	40.0	-7.5
81.360	Pk	H	180	2.2	49.2	-21.3	27.9	60.0	-32.1
81.360	Qp	H	180	2.2	47.6	-21.3	26.3	40.0	-13.7
94.921	Pk	V	270	1.0	44.1	-17.8	26.3	63.5	-37.2
94.921	Qp	V	275	1.0	43.8	-17.8	26.0	43.5	-17.5
108.477	Pk	H	350	2.0	60.7	-16.6	44.1	63.5	-19.4
108.477	Qp	H	350	2.2	58.9	-16.6	42.3	43.5	-1.2
122.038	Pk	V	350	1.0	44.1	-15.5	28.6	63.5	-34.9
122.038	Qp	V	350	1.0	42.2	-15.5	26.7	43.5	-16.8
135.599	Pk	H	20	2.2	56.2	-16.6	39.6	63.5	-23.9
135.599	Qp	H	20	2.2	54.8	-16.6	38.2	43.5	-5.3

Test Personnel:

Daniel W. Baltzell
EMC Test Engineer



Signature

August 8, 2006
Date Of Test

8 Conclusion

The data in this measurement report shows that the EUT as tested, Sirit Technologies Inc. Model PnP USB RFID Reader, Model # PnP USB, FCC ID: M4ZPNPUSB, IC: 3637B-PNPUSB, complies with all the applicable requirements of Parts 2 and 15 of the FCC Rules and Regulations, and Industry Canada RSS-210 & RSS-Gen.