



中认信通

CHINA CERTIFICATION ICT CO., LTD (DONGGUAN)



TEST REPORT

Applicant: CHENG UEI PRECISION INDUSTRY CO., LTD.

Address: No.18, Chung Shan Road, Tu Cheng District, New Taipei City, Taiwan, R.O.C.

FCC ID: M6E-APC630

IC: 6632B-APC630

HVIN: APC630

Product Name: Dual-Band Gigabit ceiling wireless AP

Standard(s): 47 CFR Part 15, Subpart E(15.407)

RSS-247 Issue 4, July 24, 2025

RSS-Gen, Issue 5, February 2021 Amendment 2

ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 +

Errata to C63.10a-2024

KDB 789033 D02 General U-NII Test Procedures New Rules v02r01

The above device has been tested and found compliant with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

Report Number: 2603T12344E-RF-00B

Date Of Issue: 2026/8/19

Reviewed By: Calvin Chen

Title: RF Test Supervisor

Approved By: Sun Zhong

Title: Manager

Test Laboratory: China Certification ICT Co., Ltd (Dongguan)

Room 101 & 201, Building 2, 256 Pingdong Road, Dalang Town, Dongguan City, Guangdong, China.

Tel: +86-769-83085888

www.ccttt.com.cn

Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the Room 101 & 201, Building 2, 256 Pingdong Road, Dalang Town, Dongguan City, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0123.

Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

Each test item follows the test standard(s) without deviation.

CONTENTS

DOCUMENT REVISION HISTORY.....	5
1. GENERAL INFORMATION.....	6
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	6
1.2 DESCRIPTION OF TEST CONFIGURATION.....	9
1.2.1 EUT Operation Condition:	9
1.2.2 Support Equipment List and Details	11
1.2.3 Support Cable List and Details	11
1.2.4 Block Diagram of Test Setup.....	11
1.3 MEASUREMENT UNCERTAINTY	13
2. SUMMARY OF TEST RESULTS	14
3. REQUIREMENTS AND TEST PROCEDURES	15
3.1 AC LINE CONDUCTED EMISSIONS.....	15
3.1.1 Applicable Standard.....	15
3.1.2 EUT Setup.....	17
3.1.3 EMI Test Receiver Setup	17
3.1.4 Test Procedure	18
3.1.5 Corrected Amplitude & Margin Calculation.....	18
3.2 RADIATION SPURIOUS EMISSIONS.....	19
3.2.1 Applicable Standard.....	19
3.2.2 EUT Setup.....	21
3.2.3 EMI Test Receiver & Spectrum Analyzer Setup	23
3.2.4 Test Procedure	23
3.2.5 Corrected Amplitude & Margin Calculation.....	24
3.3 26dBATTENUATED BELOW THE CHANNEL POWER:.....	25
3.3.1 Applicable Standard.....	25
3.3.2 EUT Setup.....	25
3.3.3 Test Procedure	25
3.4 EMISSION BANDWIDTH:	26
3.4.1 Applicable Standard.....	26
3.4.2 EUT Setup.....	26
3.4.3 Test Procedure	26
3.5 MAXIMUM CONDUCTED OUTPUT POWER:	28
3.5.1 Applicable Standard.....	28
3.5.2 EUT Setup.....	29
3.5.3 Test Procedure	29
3.6 MAXIMUM POWER SPECTRAL DENSITY:	30
3.6.1 Applicable Standard.....	30
3.6.2 EUT Setup.....	31
3.6.3 Test Procedure	32
3.7 DUTY CYCLE:.....	33
3.7.1 EUT Setup.....	33
3.7.2 Test Procedure	33

3.7.3 Judgment.....	33
3.8 ANTENNA REQUIREMENT.....	34
3.8.1 Applicable Standard.....	34
3.8.2 Judgment.....	34
3.9 ADDITIONAL REQUIREMENT	35
3.9.1 Applicable Standard.....	35
3.9.2 Judgment.....	36
4. Test DATA AND RESULTS.....	37
4.1 AC LINE CONDUCTED EMISSIONS.....	37
4.2 RADIATION SPURIOUS EMISSIONS.....	42
4.3 RF CONDUCTED DATA	219
5. EUT PHOTOGRAPHS	220
6. TEST SETUP PHOTOGRAPHS	221

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	2603T12344E-RF-00B	Original Report	2026/8/19

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Name:	Dual-Band Gigabit ceiling wireless AP
EUT Model:	APC630
Operation Frequency:	Band 1: 5180-5240 MHz (802.11a/n ht20/ac vht20/ax he20) 5190-5230 MHz (802.11n ht40/ac vht40/ax he40) 5210 MHz (802.11ac vht80/ax he80) Band 4: 5745-5825 MHz (802.11a/n ht20/ac vht20/ax he20) 5755-5795 MHz (802.11n ht40/ac vht40/ax he40) 5775 MHz (802.11ac vht80/ax he80)
Maximum Average Output Power (Conducted):	12.42dBm in 5150-5250 MHz Band 19.89dBm in 5725-5850 MHz Band
Maximum Average Output Power (EIRP):	20.24dBm in 5150-5250 MHz Band
Modulation Type:	802.11a/n/ac: OFDM-BPSK, QPSK, 16QAM, 64QAM, 256QAM 802.11ax: OFDMA-BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM
Rated Input Voltage:	DC 12V from DC Port or DC 48V from PoE
Serial Number:	3M8Q-2 (for RF Conducted Test) 3M8Q-1 (for Conducted emissions& Radiated Spurious Emissions Test)
EUT Received Date:	2026/5/21
EUT Received Status:	Good

1.1.2 Operation Frequency Detail:**For 802.11a/n ht20/ac vht20/ax he20:**

5150-5250MHz Band		5725-5850MHz Band	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	149	5745
40	5200	153	5765
44	5220	157	5785
48	5240	161	5805
/	/	165	5825

Per section 15.31(m), the below channels were performed the test as below:

Test Channel	Test Frequency (MHz)	
	5150-5250 MHz	5725-5850 MHz
Lowest	5180	5745
Middle	5200	5785
Highest	5240	5825

For 802.11n ht40/ac vht40/ax he40:

5150-5250MHz		5725-5850MHz	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
38	5190	151	5755
46	5230	159	5795

Per section 15.31(m), the below channels were performed the test as below:

Test Channel	Test Frequency (MHz)	
	5150-5250 MHz	5725-5850 MHz
Lowest	5190	5755
Middle	/	/
Highest	5230	5795

For 802.11ac vht80/ax he80:

5150-5250MHz		5725-5850MHz	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
42	5210	155	5775

Per section 15.31(m), the below channels were performed the test as below:

Test Channel	Test Frequency (MHz)	
	5150-5250 MHz	5725-5850 MHz
Lowest	/	/
Middle	5210	5775
Highest	/	/

1.1.3 Antenna Information Detail▲ :

Antenna	Antenna Type	input impedance (Ohm)	Frequency Range (MHz)	Antenna Gain (dBi)
Chain 0	FPC	50	5150-5250	7.82
			5725-5850	8.28
Chain 1	FPC	50	5150-5250	6.65
			5725-5850	6.05
Chain 2	FPC	50	5150-5250	7.15
			5725-5850	6.93

Note:

The system supports 3T3R MIMO CDD modes at 802.11n/ac/ax modes.

Per KDB 662911 D01 Multiple Transmitter Output v02r01:

For power measurements:

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$

directional gain = 7.82dBi + 0dB = 7.82dBi for 5150-5250MHz

directional gain = 8.28dBi + 0dB = 8.28dBi for 5725-5850MHz

For power spectral density (PSD) measurements:

Array Gain = $10 \log(N_{ANT}/N_{SS})$ dB.

directional gain = 7.82dBi + 4.77dB = 12.59dBi for 5150-5250MHz

directional gain = 8.28dBi + 4.77dB = 13.05dBi for 5725-5850MHz

The Method of §15.203 Compliance:

☒ Antenna was permanently attached to the unit.

☐ Antenna use a unique type of connector to attach to the EUT.

☐ Unit was professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

1.1.4 Accessory Information:

Accessory Description	Manufacturer	Model	Parameters
/	/	/	/

1.2 Description of Test Configuration

1.2.1 EUT Operation Condition:

EUT Operation Mode:	The system was configured for testing in Engineering Mode, which was provided by the manufacturer.
Equipment Modifications:	No
EUT Exercise Software:	QATool
The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer▲:	

5150-5250 MHz Band:

Test Modes	Test Channels	Test Frequency (MHz)	Data rate	Power Level Setting		
				Chain 0	Chain 1	Chain 2
802.11a	Lowest	5180	6Mbps	10	10	10
	Middle	5200	6Mbps	10	10	10
	Highest	5240	6Mbps	10	10	10
802.11ac vht20	Lowest	5180	MCS0	6	6	6
	Middle	5200	MCS0	6	6	6
	Highest	5240	MCS0	6	6	6
802.11ac vht40	Lowest	5190	MCS0	6	6	6
	Highest	5230	MCS0	6	6	6
802.11ac vht80	Middle	5210	MCS0	6	6	6
802.11ax he20	Lowest	5180	MCS0	6	6	6
	Middle	5200	MCS0	6	6	6
	Highest	5240	MCS0	6	6	6
802.11ax he40	Lowest	5190	MCS0	6	6	6
	Highest	5230	MCS0	6	6	6
802.11ax he80	Middle	5210	MCS0	6	6	6

5725-5850 MHz Band:						
Test Modes	Test Channels	Test Frequency (MHz)	Data rate	Power Level Setting		
				Chain 0	Chain 1	Chain 2
802.11a	Lowest	5745	6Mbps	12	12	12
	Middle	5785	6Mbps	12	12	12
	Highest	5825	6Mbps	12	12	12
802.11ac vht20	Lowest	5745	MCS0	12	12	12
	Middle	5785	MCS0	12	12	12
	Highest	5825	MCS0	12	12	12
802.11ac vht40	Lowest	5755	MCS0	12	12	12
	Highest	5795	MCS0	12	12	12
802.11ac vht80	Middle	5775	MCS0	12	12	12
802.11ax he20	Lowest	5745	MCS0	12	12	12
	Middle	5785	MCS0	12	12	12
	Highest	5825	MCS0	12	12	12
802.11ax he40	Lowest	5755	MCS0	12	12	12
	Highest	5795	MCS0	12	12	12
802.11ax he80	Middle	5775	MCS0	12	12	12

Note:

1. The system support 802.11a/n ht20/n ht40/ac vht20/ac vht40/ac vht80/ax he20/ax he40/ax he80, the 802.11n ht20/n ht40 were reduced since the identical parameters with 802.11ac vht20/ac vht40.
2. The above are the worst-case data rates, which are determined for each mode based upon investigations by measuring the average power and PSD across all data rates, bandwidths, and modulations.
3. The device supports SISO in all modes and MIMO in 802.11n/ac/ax modes, per pretest, MIMO mode was the worst mode and reported for 802.11n/ac/ax modes.
4. 802.11ax mode only support full RU configuration.
5. For AC line conducted emissions, the maximum output power mode and channel was tested.
6. For Radiated Spurious Emissions 9kHz~1GHz and 18~40GHz, the maximum output power mode and channel was tested.

1.2.2 Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
GOSPELL DIGITAL	PoE	G0720-480-050	102702660
Lenovo	Laptop	T4610S	00331-10000-00001-AA729
Tenda	Wireless Router	RX12 Pro	ED331010215000033

1.2.3 Support Cable List and Details


Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
RJ45 Cable	No	No	3	EUT	Router
RJ45 Cable	No	No	3	EUT	Laptop
RJ45 Cable	No	No	1	PoE	EUT
Power Cable	No	No	1.2	Adapter	EUT
RJ45 Cable	No	No	3	PoE	Router

1.2.4 Block Diagram of Test Setup


AC line conducted emissions:



Spurious Emissions:
Below 1G:



Above 1G:



1.3 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	$\pm 5\%$
RF output power, conducted	± 0.55 dB
Power Spectral Density, conducted	± 0.55 dB
Unwanted Emissions, radiated	9kHz~30MHz: 3.06dB, 30MHz~1GHz: 6.13 dB, 1GHz~6GHz: 4.79 dB, 6GHz~18GHz: 4.63 dB, 18GHz~26.5GHz: 4.79 dB, 26.5GHz~40GHz: 4.63 dB
Unwanted Emissions, conducted	± 2.47 dB
Temperature	$\pm 1^{\circ}\text{C}$
Humidity	$\pm 5\%$
DC and low frequency voltages	$\pm 0.4\%$
Duty Cycle	1%
AC Power Lines Conducted Emission	2.83 dB (150 kHz to 30 MHz)

2. SUMMARY OF TEST RESULTS

Standard(s) Section	Test Items	Result
§15.207(a) RSS-Gen Clause 8.8	AC line conducted emissions	Compliant
FCC §15.205 & §15.209 & §15.407(b); RSS-247 Clause 7.3	Undesirable Emission& Restricted Bands	Compliant
RSS-247 Clause 7.3.1.3	26dB attenuated below the channel power	Compliant
FCC §15.407(a) (e) RSS-247 Clause 7.3 RSS-Gen Clause 6.7	Emission Bandwidth	Compliant
FCC §15.407(a) RSS-247 Clause 7.3	Maximum Conducted Output Power	Compliant
FCC §15.407 (a) RSS-247 Clause 7.3	Power Spectral Density	Compliant
§15.203 RSS-Gen Clause 6.8	Antenna Requirement	Compliant
RSS-247 Clause 7.3.7	Additional requirements	Compliant

Note: Per 15B&ICES 003 Issue 7 report, Powered by PoE was the worst for AC Line Conducted Emissions and Radiated Spurious Emissions Below 1G, Powered by DC 12V was the worst for Radiated Spurious Emissions Above 1G so only performed it this report.

3. REQUIREMENTS AND TEST PROCEDURES

3.1 AC Line Conducted Emissions

3.1.1 Applicable Standard

FCC §15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:

(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000 μ V within the frequency band 535-1705 kHz, as measured using a 50 μ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

RSS-Gen Clause 8.8

Unless stated otherwise in the applicable RSS, for radio apparatus that are designed to be connected to the public utility AC power network, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the range 150 kHz to 30 MHz shall not exceed the limits in table 4, as measured using a 50 μ H / 50 Ω line impedance stabilization network. This requirement applies for the radio frequency voltage measured between each power line and the ground terminal of each AC power-line mains cable of the EUT.

For an EUT that connects to the AC power lines indirectly, through another device, the requirement for compliance with the limits in table 4 shall apply at the terminals of the AC power-line mains cable of a representative support device, while it provides power to the EUT. The lower limit applies at the boundary between the frequency ranges. The device used to power the EUT shall be representative of typical applications.

Table 4 – AC power-line conducted emissions limits

Frequency (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 ¹	56 to 46 ¹
0.5 – 5	56	46
5 – 30	60	50


Note 1: The level decreases linearly with the logarithm of the frequency.

For an EUT with a permanent or detachable antenna operating between 150 kHz and 30 MHz, the AC power-line conducted emissions must be measured using the following configurations:

(a) Perform the AC power-line conducted emissions test with the antenna connected to determine compliance with the limits of table 4 outside the transmitter's fundamental emission band.

(b) Retest with a dummy load instead of the antenna to determine compliance with the limits of table 4 within the transmitter's fundamental emission band. For a detachable antenna, remove the antenna and connect a suitable dummy load to the antenna connector. For a permanent antenna, remove the antenna and terminate the RF output with a dummy load or network that simulates the antenna in the fundamental frequency band.

3.1.2 EUT Setup



The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207, RSS-Gen limits.

The spacing between the peripherals was 10 cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

3.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

3.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

3.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

3.2 Radiation Spurious Emissions

3.2.1 Applicable Standard

FCC §15.407 (b);

Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(4) For transmitters operating solely in the 5.725-5.850 GHz band:

(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

(ii) Devices certified before March 2, 2017 with antenna gain greater than 10 dBi may demonstrate compliance with the emission limits in § 15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease by March 2, 2018. Devices certified before March 2, 2018 with antenna gain of 10 dBi or less may demonstrate compliance with the emission limits in § 15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease before March 2, 2020.

(8) The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.

(9) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in § 15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in § 15.207.

(10) The provisions of § 15.205 apply to intentional radiators operating under this section.

(11) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the upper and lower frequency band edges as the design of the equipment permits.

(c) The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signalling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization a description of how this requirement is met.

Frequency band 5150-5250 MHz:

RSS-247 Clause 7.3.1.3

For transmitters with operating frequencies in the band 5150-5250 MHz:

a. all emissions outside the 5150-5350 MHz band shall not exceed -27 dBm/MHz peak e.i.r.p. spectral density;

b. any unwanted emissions that falls between the upper edge of the 26 dB bandwidth and 5350 MHz shall be attenuated below the channel power by at least 26 dB, when measured using a resolution bandwidth between 1 and 5% of the occupied bandwidth.

c. if the occupied bandwidth also falls within the 5250-5350 MHz band, the transmission is considered as intentional and the devices shall comply with all requirements in the band 5250-5350

MHz including implementing DFS (see section 7.3.6) and TPC, on the portion of the emission that resides in the 5250-5350 MHz band.

Frequency band 5250-5350 MHz:

RSS-247 Clause 7.3.2.3

Devices shall comply with the following:

- a. all emissions outside the band 5150-5350 MHz shall not exceed -27dBm/MHz peak e.i.r.p spectral density.
- b. all emissions inside the band 5150-5250 MHz shall either:
 - i. not exceed -27 dBm/MHz peak e.i.r.p spectral density, or
 - ii. comply with the power spectral density for operation in section 7.3.1.2.

Frequency bands 5470-5725 MHz:

RSS-247 Clause 7.3.3.3

Equipment operating in the bands 5470-5725 MHz shall comply with the following unwanted emission limits:

- a. for devices with fundamental emissions fully contained within the 5470-5725 MHz band, all unwanted emissions outside the band 5470-5725MHz shall not exceed -27 dBm/MHz peak e.i.r.p. spectral density.
- b. for devices with bandwidth overlapping the band edge of 5725 MHz, all unwanted emissions shall not exceed -27 dBm/MHz peak e.i.r.p. spectral density at 5850 MHz instead of 5725 MHz.

Frequency band 5725-5850 MHz


RSS-247 Clause 7.3.4.3

Equipment operating in the band 5725-5850 MHz shall comply with the following peak e.i.r.p. spectral density limits:


- a. 27 dBm/MHz at frequencies from the band edges decreasing linearly to 15.6 dBm/MHz at 5 MHz above or below the band edges;
- b. 15.6 dBm/MHz at 5 MHz above or below the band edges decreasing linearly to 10 dBm/MHz at 25 MHz above or below the band edges;
- c. 10 dBm/MHz at 25 MHz above or below the band edges decreasing linearly to -27 dBm/MHz at 75 MHz above or below the band edges; and
- d. -27 dBm/MHz at frequencies more than 75 MHz above or below the band edges.



3.2.2 EUT Setup

9kHz~30MHz:



30MHz~1GHz:



1-26.5GHz:**26.5-40GHz:**

The radiated emission tests were performed in the semi-anechoic chamber, using the setup accordance with the ANSI C63.10-2020. The specification used was FCC 15.209, FCC 15.407, RSS-247, RSS-Gen limits.

For 9kHz-30MHz test, the lowest height of the magnetic antenna shall be 1 m above the ground and three antenna orientations (parallel, perpendicular, and ground-parallel) shall be measured.

3.2.3 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 9 kHz to 40 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9kHz-1000MHz:

Frequency Range	Measurement	RBW	Video B/W	IF B/W	Detector
9 kHz – 150 kHz	QP/AV	200 Hz	1 kHz	200 Hz	QP/AV
150 kHz – 30 MHz	QP/AV	9 kHz	30 kHz	9 kHz	QP/AV
30MHz – 1000 MHz	PK	120 kHz	500 kHz	/	PK
	QP	/	/	120kHz	QP

1GHz- 40GHz:

Pre-scan:

Frequency Range	Measurement	RBW	Video B/W	Detector
Above 1 GHz	Peak	1MHz	3 MHz	PK
	AV	1MHz	5kHz	PK

Final measurement for emission identified during the pre-scan:

Measurement	Detector	Duty cycle	RBW	Video B/W
PK	PK	Any	1MHz	3 MHz
Ave.	PK	>98%	1MHz	10 Hz
		<98%	1MHz	$\geq 1/T$

Note: T is minimum transmission duration

3.2.4 Test Procedure

Data was recorded in Quasi-peak detection mode for frequency range of 9 kHz -1 GHz, except 9-90 kHz, 110-490 kHz, employing an average detector, peak and Average detection modes for frequencies above 1 GHz.

If the maximized peak measured value is under the QP/Average limit by more than 6dB, then it is unnecessary to perform an QP/Average measurement.

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, emission shall be computed as: $E [dB\mu V/m] = EIRP[dBm] + 95.2$, for $d = 3$ meters.

For Radiated 26.5-40GHz test, which was performed at 1.5 m distance, according to C63.10, the test result shall be extrapolated to the specified distance using an extrapolation Factor of 20dB/decade from 3m to 1.5m

Distance extrapolation Factor = $20 \log (\text{specific distance } [3m] / \text{test distance } [1.0m])$ dB= 6.0 dB

3.2.5 Corrected Amplitude & Margin Calculation

$$E_{Log} = 20 \times \log_{10}(E_{Linear})$$

E_{Linear} is the field strength of the emission, in $\mu\text{V/m}$

E_{Log} is the field strength of the emission, in $\text{dB}\mu\text{V/m}$

For 9kHz-30MHz test, test distance is 3m, extrapolation limit shall be calculated using Equation:

$$E_{\text{limit-measure}} = E_{\text{limit-Standard}} + 40 \times \log_{10} (d_{\text{standard}}/d_{\text{measure}})$$

The basic equation except 26.5-40GHz test is as follows:

Factor = Antenna Factor + Cable Loss- Amplifier Gain

For Radiated 26.5-40GHz test:

Factor = Antenna Factor + Cable Loss- Amplifier Gain - Distance extrapolation Factor

Result = Reading + Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

For the spurious emission below 30MHz, the limit was converted from $\text{dB}\mu\text{A/m}$ to $\text{dB}\mu\text{V/m}$ by adding 51.5 dB.


3.3 26dBattenuated below the channel power:

3.3.1 Applicable Standard

RSS-247 Clause 7.3.1.3

b. any unwanted emissions that falls between the upper edge of the 26 dB bandwidth and 5350 MHz shall be attenuated below the channel power by at least 26 dB, when measured using a resolution bandwidth between 1 and 5% of the occupied bandwidth.

3.3.2 EUT Setup



3.3.3 Test Procedure

- Set RBW = 1%~5% of the emission bandwidth.
- Set the VBW > RBW.
- Detector = RMS.
- Trace mode = Average
- Measure the emission attenuated below the channel power

3.4 Emission Bandwidth:

3.4.1 Applicable Standard

FCC §15.407 (a), (h)

(h)(2) Radar Detection Function of Dynamic Frequency Selection (DFS). U-NII devices operating with any part of its 26 dB emission bandwidth in the 5.25-5.35 GHz and 5.47-5.725 GHz bands shall employ a DFS radar detection mechanism to detect the presence of radar systems and to avoid co-channel operation with radar systems.

FCC §15.407 (e)

Within the 5.725-5.850 GHz and 5.850-5.895 GHz bands, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

RSS-247 Clause 7.3.1.3


b. any unwanted emissions that falls between the upper edge of the 26 dB bandwidth and 5350 MHz shall be attenuated below the channel power by at least 26 dB, when measured using a resolution bandwidth between 1 and 5% of the occupied bandwidth.

c. if the occupied bandwidth also falls within the 5250-5350 MHz band, the transmission is considered as intentional and the devices shall comply with all requirements in the band 5250-5350 MHz including implementing DFS (see section 7.3.6) and TPC, on the portion of the emission that resides in the 5250-5350 MHz band.

RSS-247 Clause 7.3.4.2

For equipment operating in the band 5725-5850 MHz, the 6 dB bandwidth shall be at least 500 kHz.

3.4.2 EUT Setup



3.4.3 Test Procedure

26dB Emission Bandwidth:

According to ANSI C63.10-2020 Section 12.5.2

- Set RBW = shall be in the range of 1% to 5% of the emission bandwidth.
- Set the VBW > RBW.
- Detector = peak.
- Trace mode = max hold.
- Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the instrument. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is in the range of 1% to 5%.

99% Occupied Bandwidth:

According to ANSI C63.10-2020 Section 12.5.3&6.9.3

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

- a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.6.2.
- d) Step a) through step c) might require iteration to adjust within the specified range.
- e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- g) If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
- h) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

6 dB emission bandwidth:

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) ≥ 3 RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Note: The automatic bandwidth measurement capability of a spectrum analyzer or EMI receiver may be employed if it implements the functionality described in this section. For devices that use channel aggregation refer to III.A and III.C for determining emission bandwidth.

3.5 Maximum Conducted Output Power:

3.5.1 Applicable Standard

FCC §15.407(a) (1)(ii)

For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

FCC §15.407(a) (3)(i)

For the band 5.725-5.850 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

RSS-247 Clause 7.3.1.2

Frequency band 5150-5250 MHz:

For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed the lesser of:

a. 30 mW; or

b. $1.76 + 10 \log_{10} B$, dBm.

OEM devices installed in vehicles with a maximum e.i.r.p. greater than 15 mW shall implement TPC in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

For all other devices the maximum e.i.r.p. spectral density shall not exceed 10dBm/MHz. The maximum e.i.r.p. shall not exceed the lesser of:

a. 200 mW; or

b. $10 + 10 \log_{10} B$, dBm.

RSS-247 Clause 7.3.4.3

Frequency band 5725-5850 MHz:

Equipment operating in the band 5725-5850 shall comply with the following power limits:


- a. the maximum conducted output power shall not exceed 1 W; and
- b. the maximum output power spectral density shall not exceed 30dBm/500 kHz.

When using transmitting antennas with a directional gain exceeding 6 dBi, the maximum conducted output power and the output power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

However, FFTP devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter maximum conducted output power and the power spectral density. FFTP operations exclude the use of PTMP systems, omnidirectional applications and multiple collocated transmitters transmitting the same information. However, remote stations of PTMP systems shall be permitted to operate at e.i.r.p. greater than 4 W under the same conditions as for FFTP systems.

The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10} B$, dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

3.5.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port. The insert loss of this RF cable/attenuator was offset into the setting of test equipment:

Offset=Insert loss of RF cable+ Insert loss of attenuator

3.5.3 Test Procedure

According to ANSI C63.10-2020 Section 12.4.3.2

Method PM-G is measurement using a gated RF average power meter. Measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

3.6 Maximum power spectral density:

3.6.1 Applicable Standard

FCC §15.407(a) (1)(ii)

For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

FCC §15.407(a) (3)(i)

For the band 5.725-5.850 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

RSS-247 Clause 7.3.1.2

Frequency band 5150-5250 MHz:

For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed the lesser of:

a. 30 mW; or

b. $1.76 + 10 \log_{10} B$, dBm.

OEM devices installed in vehicles with a maximum e.i.r.p. greater than 15 mW shall implement TPC in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

For all other devices the maximum e.i.r.p. spectral density shall not exceed 10dBm/MHz. The maximum e.i.r.p. shall not exceed the lesser of:

a. 200 mW; or

b. $10 + 10 \log_{10} B$, dBm.

RSS-247 Clause 7.3.4.3

Frequency band 5725-5850 MHz:

Equipment operating in the band 5725-5850 shall comply with the following power limits:


- a. the maximum conducted output power shall not exceed 1 W; and
- b. the maximum output power spectral density shall not exceed 30dBm/500 kHz.

When using transmitting antennas with a directional gain exceeding 6 dBi, the maximum conducted output power and the output power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

However, FFTP devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter maximum conducted output power and the power spectral density. FFTP operations exclude the use of PTMP systems, omnidirectional applications and multiple collocated transmitters transmitting the same information. However, remote stations of PTMP systems shall be permitted to operate at e.i.r.p. greater than 4 W under the same conditions as for FFTP systems.

The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10} B$, dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

3.6.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port. The insert loss of this RF cable/attenuator was offset into the setting of test equipment:

Offset=Insert loss of RF cable+ Insert loss of attenuator

3.6.3 Test Procedure

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01

Duty cycle $\geq 98\%$

KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method SA-1 should be applied.

Duty cycle $< 98\%$, duty cycle variations are less than $\pm 2\%$


KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method SA-2 should be applied.

Duty cycle $< 98\%$, duty cycle variations exceed $\pm 2\%$

KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method SA-3 should be applied.

3.7 Duty Cycle:

3.7.1 EUT Setup



3.7.2 Test Procedure

According to ANSI C63.10-2020 Section 12.2

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- 1) Set the center frequency of the instrument to the center frequency of the transmission.
- 2) Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
- 3) Set $VBW \geq RBW$. Set detector = peak or average.
- 4) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)

3.7.3 Judgment

Report Only. Please refer to section 4.8.

3.8 Antenna Requirement

3.8.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

RSS-Gen Clause 6.8

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter [enter the device's ISSED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

3.8.2 Judgment

Result: Compliant. Please refer to the Antenna Information detail in Section 1.3

3.9 Additional requirement

3.9.1 Applicable Standard

According to RSS-247 Clause 7.3.7 Additional Requirements

The following requirements shall apply:

a the device shall automatically discontinue transmission in cases of absence of information to transmit, or operational failure. A description on how this is done shall accompany the application for equipment certification. Note that this is not intended to prohibit transmission of control or signalling information or the use of repetitive codes where required by the technology.

b all LE-LAN devices must contain security features to protect against modification of software by unauthorized parties.

Manufacturers must implement security features in any digitally modulated devices capable of operating in any of the frequency ranges within the 5 GHz band, so that third parties are not able to reprogram the device to operate outside the parameters for which the device was certified. The software must prevent the user from operating the transmitter with operating frequencies, output power, modulation types or other radio frequency parameters outside those that were approved for the device. Manufacturers may use various means, including the use of a private network that allows only authenticated users to download software, electronic signatures in software or coding in hardware that is decoded by software to verify that new software can be legally loaded into a device to meet these requirements and must describe the methods in their application for equipment certification.

Manufacturers must take steps to ensure that DFS functionality cannot be disabled by the operator of the LE-LAN device.

c the user manual for LE-LAN devices shall contain instructions related to the restrictions mentioned in the above sections, namely that:

- i.** any devices capable of operating in the band 5150–5250 MHz shall only be used indoors to reduce the potential for harmful interference to co-channel mobile satellite systems (this requirement does not apply to OEM devices installed in vehicles by vehicle manufacturers);
- ii.** for devices with detachable antenna(s), the maximum antenna gain permitted for devices in the bands 5250-5350 MHz and 5470-5725 MHz shall be such that the equipment still complies with the e.i.r.p. limit;
- iii.** for devices with detachable antenna(s), the maximum antenna gain permitted for devices in the band 5725-5850 MHz shall be such that the equipment still complies with the e.i.r.p. limits as appropriate; and
- iv.** where applicable, antenna type(s), antenna models(s), and worst-case tilt angle(s) necessary to remain compliant with the e.i.r.p. elevation mask requirement set forth in section 7.3.2.4 or 7.3.5.3 shall be clearly indicated.

3.9.2 Judgment

RSS-247 Clause 7.3.7 a:

The device shall automatically discontinue transmission in cases of absence of information to transmit, or operational failure. Please refer to the declaration

RSS-247 Clause 7.3.7 b:

The devices must contain security features to protect against modification of software by unauthorized parties. Please refer to the declaration

RSS-247 Clause 7.3.7 c:

- i. The device operates on 5150-5250MHz is only for indoor use.
- ii. This device does not support the 5250-5350MHz/5470-5725MHz frequency band.
- iii. This device is equipped with three built-in integrated antennas, and all the EIPR compliance with RSS-247 requirement. Please refer to the conducted output power test result.
- iv. This device does not support the 5250-5350MHz/5850-5895MHz frequency band.

4. Test DATA AND RESULTS

4.1 AC Line Conducted Emissions

Sample Number:	3M8Q-1	Test Date:	2026/5/22
Test Site:	CE	Test Mode:	Transmitting
Tester:	Ella Huang	Test Result:	Pass


Environmental Conditions:					
Temperature: (°C)	23.1	Relative Humidity: (%)	55	ATM Pressure: (kPa)	100.4

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV216	101132	2025/9/26	2026/9/25
R&S	EMI Test Receiver	ESR3	103104	2026/5/8	2027/5/7
MICRO-COAX	Coaxial Cable	UTIFLEX	C-0200-01	2025/11/10	2026/11/9
Audix	Test Software	E3	190306 (V9)	N/A	N/A


** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Project No.: 2603T12344E-RF
 Tester: Ella Huang
 Port: Line
 Condition: RBW:9kHz
 Test Mode: Transmitting
 Note: maximum output power mode, MIMO, ax40_Ru_Full, 5795MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.499	37.47	10.41	47.88	56.02	8.14	QP
2	0.499	27.03	10.41	37.44	46.02	8.58	Average
3	2.593	28.12	10.06	38.18	56.00	17.82	QP
4	2.593	16.03	10.06	26.09	46.00	19.91	Average
5	2.847	27.90	10.08	37.98	56.00	18.02	QP
6	2.847	17.77	10.08	27.85	46.00	18.15	Average
7	3.360	30.32	10.12	40.44	56.00	15.56	QP
8	3.360	21.26	10.12	31.38	46.00	14.62	Average
9	13.559	33.62	10.17	43.79	60.00	16.21	QP
10	13.559	27.97	10.17	38.14	50.00	11.86	Average
11	19.678	35.72	9.73	45.45	60.00	14.55	QP
12	19.678	28.54	9.73	38.27	50.00	11.73	Average

Project No.: 2603T12344E-RF
 Tester: Ella Huang
 Port: neutral
 Condition: RBW:9kHz
 Test Mode: Transmitting
 Note: maximum output power mode, MIMO, ax40_Ru_Full, 5795MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.497	37.96	10.11	48.07	56.06	7.99	QP
2	0.497	27.91	10.11	38.02	46.06	8.04	Average
3	1.967	28.54	10.52	39.06	56.00	16.94	QP
4	1.967	14.06	10.52	24.58	46.00	21.42	Average
5	2.534	29.21	10.48	39.69	56.00	16.31	QP
6	2.534	16.25	10.48	26.73	46.00	19.27	Average
7	2.890	29.22	10.46	39.68	56.00	16.32	QP
8	2.890	19.24	10.46	29.70	46.00	16.30	Average
9	19.344	36.06	10.18	46.24	60.00	13.76	QP
10	19.344	30.13	10.18	40.31	50.00	9.69	Average
11	20.525	34.94	10.21	45.15	60.00	14.85	QP
12	20.525	27.62	10.21	37.83	50.00	12.17	Average

2.4G Wifi is transmitted simultaneously with 5G Wifi:
802.11ax40 2452MHz+802.11ac20 5240MHz was tested:

Project No.: 2603T12344E-RF
Tester: Ella Huang
Port: Line
Condition: RBW:9kHz
Test Mode: Transmitting
Note:


Date: 2026-05-22



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.474	41.59	10.41	52.00	56.44	4.44	QP
2	0.474	31.24	10.41	41.65	46.44	4.79	Average
3	7.027	36.09	10.47	46.56	60.00	13.44	QP
4	7.027	29.66	10.47	40.13	50.00	9.87	Average
5	7.455	35.05	10.49	45.54	60.00	14.46	QP
6	7.455	28.93	10.49	39.42	50.00	10.58	Average
7	10.332	35.27	10.54	45.81	60.00	14.19	QP
8	10.332	29.31	10.54	39.85	50.00	10.15	Average
9	10.775	36.66	10.50	47.16	60.00	12.84	QP
10	10.775	30.89	10.50	41.39	50.00	8.61	Average
11	13.560	38.40	10.17	48.57	60.00	11.43	QP
12	13.560	31.42	10.17	41.59	50.00	8.41	Average

Project No.: 2603T12344E-RF
 Tester: Ella Huang
 Port: neutral
 Condition: RBW:9kHz
 Test Mode: Transmitting
 Note:

Date: 2026-05-22



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.487	40.73	10.13	50.86	56.21	5.35	QP
2	0.487	32.36	10.13	42.49	46.21	3.72	Average
3	5.924	33.22	10.42	43.64	60.00	16.36	QP
4	5.924	24.86	10.42	35.28	50.00	14.72	Average
5	6.898	35.70	10.47	46.17	60.00	13.83	QP
6	6.898	28.29	10.47	38.76	50.00	11.24	Average
7	7.063	36.42	10.46	46.88	60.00	13.12	QP
8	7.063	30.05	10.46	40.51	50.00	9.49	Average
9	10.708	36.36	10.08	46.44	60.00	13.56	QP
10	10.708	30.65	10.08	40.73	50.00	9.27	Average
11	10.884	36.84	10.07	46.91	60.00	13.09	QP
12	10.884	31.25	10.07	41.32	50.00	8.68	Average

4.2 Radiation Spurious Emissions

1) 9kHz - 1GHz

Sample Number:	3M8Q-1	Test Date:	2026/6/8~2026/8/8
Test Site:	966-1	Test Mode:	Transmitting
Tester:	Jin He	Test Result:	Pass
Environmental Conditions:			
Temperature: (°C)	24.7~25.9	Relative Humidity: (%)	49~67
		ATM Pressure: (kPa)	99.5~100.3

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Antenna	JB6	A082520-5	2023/12/1	2026/11/30
GLOBAL	Loop Antenna	1313-1A	3110611	2026/1/29	2029/1/28
Daruikang	Coaxial Cable	BNC-JJ-RG58	C-0300-01	2025/11/10	2026/11/9
Daruikang	Coaxial Cable	BNC-JJ-RG58	C-0500-01	2025/11/10	2026/11/9
R&S	EMI Test Receiver	ESR3	102724	2026/2/27	2027/2/26
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0100-03	2025/11/10	2026/11/9
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0370-01	2025/11/10	2026/11/9
XQY	Coaxial Cable	XQY-CMR400UF-NJ-NJ-7M	24056379	2026/5/21	2027/5/20
Sonoma	Amplifier	310N	186165	2025/11/10	2026/11/9
Audix	Test Software	E3	191218 (V9)	N/A	N/A


* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

9kHz~30MHz

Three antenna orientations (parallel, perpendicular, and ground-parallel) was measured, the worst orientations was below:
5150-5250MHz:

Project No.: 2603T12344E-RF
Tester: Jin He
Condition: RBW:0.2 kHz VBW:1 kHz
Polarization: Parallel
Note: Transmitting 5.2G Wifi 802.11ax80_RU_Full 5210MHz



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	0.010	16.25	34.37	50.62	127.64	77.02	Peak
2	0.011	16.07	33.68	49.75	126.49	76.74	Peak
3	0.021	17.82	29.14	46.96	121.14	74.18	Peak
4	0.043	16.83	22.12	38.95	114.91	75.96	Peak
5	0.061	18.76	19.06	37.82	111.93	74.11	Peak
6	0.106	18.43	14.04	32.47	107.06	74.59	Peak


Project No.: 2603T12344E-RF

Tester: Jin He

Condition: RBW:9 kHz VBW:30 kHz

Polarization: Parallel


Note: Transmitting 5.2G Wifi 802.11ax80_RU_Full 5210MHz



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	0.165	35.61	11.32	46.93	103.25	56.32	Peak
2	0.227	34.47	8.45	42.92	100.49	57.57	Peak
3	0.712	35.79	-1.46	34.33	70.48	36.15	Peak
4	1.352	33.53	-5.54	27.99	64.80	36.81	Peak
5	12.852	31.68	-7.88	23.80	69.54	45.74	Peak
6	17.199	31.49	-7.47	24.02	69.54	45.52	Peak


5725-5850MHz:

Project No.: 2603T12344E-RF
 Tester: Jin He
 Condition: RBW:0.2 kHz VBW:1 kHz
 Polarization: Parallel
 Note: Transmitting 5.8G Wifi 802.11ax40_RU_Full 5795MHz



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	0.011	20.66	34.00	54.66	127.03	72.37	Peak
2	0.012	21.28	33.22	54.50	125.78	71.28	Peak
3	0.017	21.11	31.19	52.30	123.17	70.87	Peak
4	0.023	24.14	28.11	52.25	120.28	68.03	Peak
5	0.029	23.61	25.32	48.93	118.31	69.38	Peak
6	0.063	21.40	18.80	40.20	111.68	71.48	Peak


Project No.: 2603T12344E-RF
 Tester: Jin He
 Condition: RBW:9 kHz VBW:30 kHz
 Polarization: Parallel
 Note: Transmitting 5.8G Wifi 802.11ax40_RU_Full 5795MHz



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	0.169	37.11	11.15	48.26	103.07	54.81	Peak
2	0.227	37.86	8.45	46.31	100.49	54.18	Peak
3	0.343	39.32	4.15	43.47	96.90	53.43	Peak
4	0.686	38.59	-1.18	37.41	70.81	33.40	Peak
5	1.203	37.53	-5.09	32.44	65.83	33.39	Peak
6	13.695	37.61	-7.99	29.62	69.54	39.92	Peak


2.4G Wifi is transmitted simultaneously with 5G Wifi:
802.11ax40 2452MHz+802.11ac20 5240MHz was tested:

Project No.: 2603T12344E-RF
Tester: Jin He
Condition: RBW:0.2 kHz VBW:1 kHz
Polarization: Parallel
Note: Transmitting 2.4G Wifi & 5.8G Wifi



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	0.010	17.14	34.15	51.29	127.30	76.01	Peak
2	0.018	16.74	30.67	47.41	122.61	75.20	Peak
3	0.024	17.21	27.80	45.01	120.04	75.03	Peak
4	0.027	16.32	26.21	42.53	118.89	76.36	Peak
5	0.037	16.02	23.48	39.50	116.30	76.80	Peak
6	0.060	17.20	19.21	36.41	112.07	75.66	Peak


Project No.: 2603T12344E-RF
 Tester: Jin He
 Condition: RBW:9 kHz VBW:30 kHz
 Polarization: Parallel
 Note: Transmitting 2.4G Wifi & 5.8G Wifi



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	0.191	33.66	10.09	43.75	101.97	58.22	Peak
2	0.235	31.03	8.05	39.08	100.17	61.09	Peak
3	0.564	32.32	0.17	32.49	72.55	40.06	Peak
4	0.938	32.10	-3.83	28.27	68.04	39.77	Peak
5	1.487	30.86	-5.95	24.91	63.95	39.04	Peak
6	15.388	28.59	-7.52	21.07	69.54	48.47	Peak


30MHz-1GHz
5150-5250MHz:

Project No.: 2603T12344E-RF
Tester: Jin He
Condition: RBW:120 kHz VBW:500 kHz
Polarization: horizontal
Note: Transmitting 5.2G Wifi 802.11ax80_RU_Full 5210MHz



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	53.318	34.98	-17.53	17.45	40.00	22.55	Peak
2	125.007	30.68	-10.87	19.81	43.50	23.69	Peak
3	147.921	36.27	-12.01	24.26	43.50	19.24	Peak
4	178.758	34.63	-13.20	21.43	43.50	22.07	Peak
5	223.733	36.10	-13.33	22.77	46.00	23.23	Peak
6	396.242	33.40	-7.87	25.53	46.00	20.47	Peak


Project No.: 2603T12344E-RF
Tester: Jin He
Condition: RBW:120 kHz VBW:500 kHz
Polarization: vertical
Note: Transmitting 5.2G Wifi 802.11ax80_RU_Full 5210MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	37.155	34.27	-9.11	25.16	40.00	14.84	Peak
2	53.505	46.76	-17.54	29.22	40.00	10.78	Peak
3	147.921	35.14	-12.01	23.13	43.50	20.37	Peak
4	227.691	36.68	-13.14	23.54	46.00	22.46	Peak
5	400.432	33.94	-7.71	26.23	46.00	19.77	Peak
6	925.756	31.97	1.04	33.01	46.00	12.99	Peak

5725-5850MHz:

Project No.: 2603T12344E-RF
 Tester: Jin He
 Condition: RBW:120 kHz VBW:500 kHz
 Polarization: horizontal
 Note: Transmitting 5.8G Wifi 802.11ax40_RU_Full 5795MHz




Project No.: 2603T12344E-RF
 Tester: Jin He
 Condition: RBW:120 kHz VBW:500 kHz
 Polarization: vertical
 Note: Transmitting 5.8G Wifi 802.11ax40_RU_Full 5795MHz




2.4G Wifi is transmitted simultaneously with 5G Wifi:
802.11ax40 2452MHz+802.11ac20 5240MHz was tested:

Project No.: 2603T12344E-RF
Tester: Jin He
Condition: RBW:120 kHz VBW:500 kHz
Polarization: horizontal
Note: Transmitting 2.4G Wifi & 5.8G Wifi



Project No.: 2603T12344E-RF
 Tester: Jin He
 Condition: RBW:120 kHz VBW:500 kHz
 Polarization: vertical
 Note: Transmitting 2.4G Wifi & 5.8G Wifi



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	32.520	30.96	-5.24	25.72	40.00	14.28	Peak
2	34.760	33.35	-6.88	26.47	40.00	13.53	Peak
3	47.994	46.58	-15.82	30.76	40.00	9.24	Peak
4	50.057	43.96	-16.44	27.52	40.00	12.48	Peak
5	69.845	42.92	-16.55	26.37	40.00	13.63	Peak
6	199.286	36.24	-11.36	24.88	43.50	18.62	Peak

2) 1-40GHz:

Serial Number:	3M8Q-1	Test Date:	2026/6/12-2026/8/8
Test Site:	966-2	Test Mode:	Transmitting
Tester:	HuaYuan Miao	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	21.9-23.8	Relative Humidity: (%)	57-68	ATM Pressure: (kPa)	99.5~100.7
----------------------	-----------	---------------------------	-------	---------------------------	------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
ETS-Lindgren	Horn Antenna	3115	9912-5985	2023/12/6	2026/12/5
R&S	Spectrum Analyzer	FSV40	101591	2026/2/27	2027/2/26
MICRO-COAX	Coaxial Cable	UFA210A-1-1200-70U300	217423-008	2025/11/10	2026/11/9
MICRO-COAX	Coaxial Cable	UFA210A-1-2362-300300	235780-001	2025/11/10	2026/11/9
A.H	Pre-amplifier	PAM-0118P	628	2025/11/10	2026/11/9
Audix	Test Software	E3	191218 (V9)	N/A	N/A
PASTERNAK	Horn Antenna	PE9852/2F-20	112002	2024/2/4	2027/2/3
PASTERNAK	Horn Antenna	PE9850/2F-20	072001	2024/2/4	2027/2/3
Quinstar	Preamplifier	QLW-18405536-JO	15964001005	2025/11/10	2026/11/9
Decentest	Multiplex Switch Test Control Set	DT7220SCU	DQ77925	2025/8/4	2026/8/3
Decentest	Filter Switch Unit	DT7220FSU	DQ77928	2025/8/4	2026/8/3
Decentest	Multiplex Switch Test Control Set	DT7220SCU	DQ77925	2026/8/3	2027/8/2
Decentest	Filter Switch Unit	DT7220FSU	DQ77928	2026/8/3	2027/8/2

** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:

Please refer to the below table and plots.

5150-5250MHz:**802.11a Mode Chain 0:**

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Remark					
Low Channel: 5180 MHz							
10360.000	40.35	PK	H	13.26	53.61	68.20	14.59
10360.000	37.73	PK	V	13.26	50.99	68.20	17.21
15540.000	38.99	PK	H	13.48	52.47	74.00	21.53
15540.000	25.82	AV	H	13.48	39.30	54.00	14.70
15540.000	38.53	PK	V	13.48	52.01	74.00	21.99
15540.000	25.87	AV	V	13.48	39.35	54.00	14.65
Middle Channel: 5200 MHz							
10400.000	40.90	PK	H	13.28	54.18	68.20	14.02
10400.000	38.52	PK	V	13.28	51.80	68.20	16.40
15600.000	41.05	PK	H	13.38	54.43	74.00	19.57
15600.000	28.20	AV	H	13.38	41.58	54.00	12.42
15600.000	40.75	PK	V	13.38	54.13	74.00	19.87
15600.000	28.31	AV	V	13.38	41.69	54.00	12.31
High Channel: 5240 MHz							
10480.000	43.20	PK	H	13.38	56.58	68.20	11.62
10480.000	38.10	PK	V	13.38	51.48	68.20	16.72
15720.000	41.36	PK	H	13.30	54.66	74.00	19.34
15720.000	28.34	AV	H	13.30	41.64	54.00	12.36
15720.000	41.38	PK	V	13.30	54.68	74.00	19.32
15720.000	28.35	AV	V	13.30	41.65	54.00	12.35

802.11a Mode Chain 1:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Remark					
Low Channel: 5180 MHz							
10360.000	40.08	PK	H	13.26	53.34	68.20	14.86
10360.000	38.40	PK	V	13.26	51.66	68.20	16.54
15540.000	38.78	PK	H	13.48	52.26	74.00	21.74
15540.000	25.83	AV	H	13.48	39.31	54.00	14.69
15540.000	38.77	PK	V	13.48	52.25	74.00	21.75
15540.000	25.81	AV	V	13.48	39.29	54.00	14.71
Middle Channel: 5200 MHz							
10400.000	43.27	PK	H	13.28	56.55	68.20	11.65
10400.000	41.26	PK	V	13.28	54.54	68.20	13.66
15600.000	41.45	PK	H	13.38	54.83	74.00	19.17
15600.000	28.36	AV	H	13.38	41.74	54.00	12.26
15600.000	41.68	PK	V	13.38	55.06	74.00	18.94
15600.000	28.26	AV	V	13.38	41.64	54.00	12.36
High Channel: 5240 MHz							
10480.000	45.81	PK	H	13.38	59.19	68.20	9.01
10480.000	42.68	PK	V	13.38	56.06	68.20	12.14
15720.000	41.08	PK	H	13.30	54.38	74.00	19.62
15720.000	28.26	AV	H	13.30	41.56	54.00	12.44
15720.000	41.13	PK	V	13.30	54.43	74.00	19.57
15720.000	28.25	AV	V	13.30	41.55	54.00	12.45

802.11a Mode Chain 2:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Remark					
Low Channel: 5180 MHz							
10360.000	45.55	PK	H	13.26	58.81	68.20	9.39
10360.000	38.13	PK	V	13.26	51.39	68.20	16.81
15540.000	38.91	PK	H	13.48	52.39	74.00	21.61
15540.000	25.80	AV	H	13.48	39.28	54.00	14.72
15540.000	39.17	PK	V	13.48	52.65	74.00	21.35
15540.000	25.82	AV	V	13.48	39.30	54.00	14.70
Middle Channel: 5200 MHz							
10400.000	45.12	PK	H	13.28	58.40	68.20	9.80
10400.000	38.80	PK	V	13.28	52.08	68.20	16.12
15600.000	41.36	PK	H	13.38	54.74	74.00	19.26
15600.000	28.25	AV	H	13.38	41.63	54.00	12.37
15600.000	40.88	PK	V	13.38	54.26	74.00	19.74
15600.000	28.36	AV	V	13.38	41.74	54.00	12.26
High Channel: 5240 MHz							
10480.000	48.16	PK	H	13.38	61.54	68.20	6.66
10480.000	37.87	PK	V	13.38	51.25	68.20	16.95
15720.000	41.07	PK	H	13.30	54.37	74.00	19.63
15720.000	28.25	AV	H	13.30	41.55	54.00	12.45
15720.000	40.92	PK	V	13.30	54.22	74.00	19.78
15720.000	28.26	AV	V	13.30	41.56	54.00	12.44

802.11ac20 Mode:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Remark					
Low Channel: 5180 MHz							
10360.000	47.03	PK	H	13.26	60.29	68.20	7.91
10360.000	40.56	PK	V	13.26	53.82	68.20	14.38
15540.000	38.38	PK	H	13.48	51.86	74.00	22.14
15540.000	25.80	AV	H	13.48	39.28	54.00	14.72
15540.000	38.63	PK	V	13.48	52.11	74.00	21.89
15540.000	25.79	AV	V	13.48	39.27	54.00	14.73
Middle Channel: 5200 MHz							
10400.000	46.47	PK	H	13.28	59.75	68.20	8.45
10400.000	40.54	PK	V	13.28	53.82	68.20	14.38
15600.000	40.86	PK	H	13.38	54.24	74.00	19.76
15600.000	28.35	AV	H	13.38	41.73	54.00	12.27
15600.000	41.05	PK	V	13.38	54.43	74.00	19.57
15600.000	28.25	AV	V	13.38	41.63	54.00	12.37
High Channel: 5240 MHz							
10480.000	51.54	PK	H	13.38	64.92	68.20	3.28
10480.000	42.23	PK	V	13.38	55.61	68.20	12.59
15720.000	41.24	PK	H	13.30	54.54	74.00	19.46
15720.000	28.26	AV	H	13.30	41.56	54.00	12.44
15720.000	41.08	PK	V	13.30	54.38	74.00	19.62
15720.000	28.24	AV	V	13.30	41.54	54.00	12.46

802.11ac40 Mode:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Remark					
Low Channel:				5190	MHz		
10380.000	45.36	PK	H	13.27	58.63	68.20	9.57
10380.000	40.05	PK	V	13.27	53.32	68.20	14.88
15570.000	38.39	PK	H	13.43	51.82	74.00	22.18
15570.000	25.88	AV	H	13.43	39.31	54.00	14.69
15570.000	39.10	PK	V	13.43	52.53	74.00	21.47
15570.000	25.83	AV	V	13.43	39.26	54.00	14.74
High Channel:				5230	MHz		
10460.000	46.30	PK	H	13.35	59.65	68.20	8.55
10460.000	40.56	PK	V	13.35	53.91	68.20	14.29
15690.000	41.34	PK	H	13.33	54.67	74.00	19.33
15690.000	28.25	AV	H	13.33	41.58	54.00	12.42
15690.000	41.44	PK	V	13.33	54.77	74.00	19.23
15690.000	28.22	AV	V	13.33	41.55	54.00	12.45

802.11ac80 Mode:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Remark					
Middle Channel:				5210	MHz		
10420.000	41.18	PK	H	13.30	54.48	68.20	13.72
10420.000	38.49	PK	V	13.30	51.79	68.20	16.41
15630.000	40.54	PK	H	13.36	53.90	74.00	20.10
15630.000	27.60	AV	H	13.36	40.96	54.00	13.04
15630.000	41.04	PK	V	13.36	54.40	74.00	19.60
15630.000	27.51	AV	V	13.36	40.87	54.00	13.13

802.11ax20 Mode:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Remark					
Low Channel: 5180 MHz							
10360.000	46.24	PK	H	13.26	59.50	68.20	8.70
10360.000	40.05	PK	V	13.26	53.31	68.20	14.89
15540.000	38.87	PK	H	13.48	52.35	74.00	21.65
15540.000	25.77	AV	H	13.48	39.25	54.00	14.75
15540.000	38.40	PK	V	13.48	51.88	74.00	22.12
15540.000	25.76	AV	V	13.48	39.24	54.00	14.76
Middle Channel: 5200 MHz							
10400.000	46.28	PK	H	13.28	59.56	68.20	8.64
10400.000	40.20	PK	V	13.28	53.48	68.20	14.72
15600.000	41.64	PK	H	13.38	55.02	74.00	18.98
15600.000	28.26	AV	H	13.38	41.64	54.00	12.36
15600.000	41.03	PK	V	13.38	54.41	74.00	19.59
15600.000	28.36	AV	V	13.38	41.74	54.00	12.26
High Channel: 5240 MHz							
10480.000	49.01	PK	H	13.38	62.39	68.20	5.81
10480.000	42.13	PK	V	13.38	55.51	68.20	12.69
15720.000	41.46	PK	H	13.30	54.76	74.00	19.24
15720.000	28.24	AV	H	13.30	41.54	54.00	12.46
15720.000	41.57	PK	V	13.30	54.87	74.00	19.13
15720.000	28.42	AV	V	13.30	41.72	54.00	12.28

802.11ax40 Mode:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Remark					
Low Channel:				5190	MHz		
10380.000	44.79	PK	H	13.27	58.06	68.20	10.14
10380.000	39.22	PK	V	13.27	52.49	68.20	15.71
15570.000	38.46	PK	H	13.43	51.89	74.00	22.11
15570.000	25.83	AV	H	13.43	39.26	54.00	14.74
15570.000	38.69	PK	V	13.43	52.12	74.00	21.88
15570.000	25.80	AV	V	13.43	39.23	54.00	14.77
High Channel:				5230	MHz		
10460.000	45.96	PK	H	13.35	59.31	68.20	8.89
10460.000	40.22	PK	V	13.35	53.57	68.20	14.63
15690.000	40.71	PK	H	13.33	54.04	74.00	19.96
15690.000	28.22	AV	H	13.33	41.55	54.00	12.45
15690.000	41.06	PK	V	13.33	54.39	74.00	19.61
15690.000	28.19	AV	V	13.33	41.52	54.00	12.48

802.11ax80 Mode:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Remark					
Middle Channel:				5210	MHz		
10420.000	41.00	PK	H	13.30	54.30	68.20	13.90
10420.000	38.58	PK	V	13.30	51.88	68.20	16.32
15630.000	40.50	PK	H	13.36	53.86	74.00	20.14
15630.000	27.53	AV	H	13.36	40.89	54.00	13.11
15630.000	40.07	PK	V	13.36	53.43	74.00	20.57
15630.000	27.59	AV	V	13.36	40.95	54.00	13.05

5725-5850MHz**802.11a Mode Chain 0:**

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Remark					
Low Channel: 5745 MHz							
11490.000	38.45	PK	H	13.97	52.42	74.00	21.58
11490.000	25.33	AV	H	13.97	39.30	54.00	14.70
11490.000	38.29	PK	V	13.97	52.26	74.00	21.74
11490.000	25.35	AV	V	13.97	39.32	54.00	14.68
17235.000	38.93	PK	H	16.99	55.92	68.20	12.28
17235.000	39.45	PK	V	16.99	56.44	68.20	11.76
Middle Channel: 5785 MHz							
11570.000	39.07	PK	H	14.33	53.40	74.00	20.60
11570.000	26.00	AV	H	14.33	40.33	54.00	13.67
11570.000	38.46	PK	V	14.33	52.79	74.00	21.21
11570.000	25.51	AV	V	14.33	39.84	54.00	14.16
17355.000	40.10	PK	H	17.98	58.08	68.20	10.12
17355.000	39.16	PK	V	17.98	57.14	68.20	11.06
High Channel: 5825 MHz							
11650.000	39.60	PK	H	14.49	54.09	74.00	19.91
11650.000	26.36	AV	H	14.49	40.85	54.00	13.15
11650.000	39.47	PK	V	14.49	53.96	74.00	20.04
11650.000	25.92	AV	V	14.49	40.41	54.00	13.59
17475.000	39.25	PK	H	18.94	58.19	68.20	10.01
17475.000	39.21	PK	V	18.94	58.15	68.20	10.05

802.11a Mode Chain 1:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Remark					
Low Channel:				5745	MHz		
11490.000	46.36	PK	H	13.97	60.33	74.00	13.67
11490.000	30.96	AV	H	13.97	44.93	54.00	9.07
11490.000	38.40	PK	V	13.97	52.37	74.00	21.63
11490.000	25.37	AV	V	13.97	39.34	54.00	14.66
17235.000	38.77	PK	H	16.99	55.76	68.20	12.44
17235.000	39.01	PK	V	16.99	56.00	68.20	12.20
Middle Channel:				5785	MHz		
11570.000	46.03	PK	H	14.33	60.36	74.00	13.64
11570.000	31.75	AV	H	14.33	46.08	54.00	7.92
11570.000	39.10	PK	V	14.33	53.43	74.00	20.57
11570.000	26.02	AV	V	14.33	40.35	54.00	13.65
17355.000	39.04	PK	H	17.98	57.02	68.20	11.18
17355.000	38.78	PK	V	17.98	56.76	68.20	11.44
High Channel:				5825	MHz		
11650.000	46.84	PK	H	14.49	61.33	74.00	12.67
11650.000	33.43	AV	H	14.49	47.92	54.00	6.08
11650.000	39.70	PK	V	14.49	54.19	74.00	19.81
11650.000	28.02	AV	V	14.49	42.51	54.00	11.49
17475.000	39.31	PK	H	18.94	58.25	68.20	9.95
17475.000	39.70	PK	V	18.94	58.64	68.20	9.56

802.11a Mode Chain 2:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Remark					
Low Channel: 5745 MHz							
11490.000	39.45	PK	H	13.97	53.42	74.00	20.58
11490.000	25.63	AV	H	13.97	39.60	54.00	14.40
11490.000	38.67	PK	V	13.97	52.64	74.00	21.36
11490.000	25.37	AV	V	13.97	39.34	54.00	14.66
17235.000	38.92	PK	H	16.99	55.91	68.20	12.29
17235.000	38.79	PK	V	16.99	55.78	68.20	12.42
Middle Channel: 5785 MHz							
11570.000	42.47	PK	H	14.33	56.80	74.00	17.20
11570.000	27.70	AV	H	14.33	42.03	54.00	11.97
11570.000	38.98	PK	V	14.33	53.31	74.00	20.69
11570.000	26.22	AV	V	14.33	40.55	54.00	13.45
17355.000	38.91	PK	H	17.98	56.89	68.20	11.31
17355.000	39.93	PK	V	17.98	57.91	68.20	10.29
High Channel: 5825 MHz							
11650.000	41.69	PK	H	14.49	56.18	74.00	17.82
11650.000	28.18	AV	H	14.49	42.67	54.00	11.33
11650.000	40.09	PK	V	14.49	54.58	74.00	19.42
11650.000	28.84	AV	V	14.49	43.33	54.00	10.67
17475.000	38.98	PK	H	18.94	57.92	68.20	10.28
17475.000	38.90	PK	V	18.94	57.84	68.20	10.36

802.11ac20 Mode:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Remark					
Low Channel: 5745 MHz							
11490.000	46.72	PK	H	13.97	60.69	74.00	13.31
11490.000	30.75	AV	H	13.97	44.72	54.00	9.28
11490.000	38.49	PK	V	13.97	52.46	74.00	21.54
11490.000	25.38	AV	V	13.97	39.35	54.00	14.65
17235.000	38.99	PK	H	16.99	55.98	68.20	12.22
17235.000	38.89	PK	V	16.99	55.88	68.20	12.32
Middle Channel: 5785 MHz							
11570.000	48.30	PK	H	14.33	62.63	74.00	11.37
11570.000	31.45	AV	H	14.33	45.78	54.00	8.22
11570.000	39.72	PK	V	14.33	54.05	74.00	19.95
11570.000	26.61	AV	V	14.33	40.94	54.00	13.06
17355.000	39.09	PK	H	17.98	57.07	68.20	11.13
17355.000	38.69	PK	V	17.98	56.67	68.20	11.53
High Channel: 5825 MHz							
11650.000	47.55	PK	H	14.49	62.04	74.00	11.96
11650.000	33.24	AV	H	14.49	47.73	54.00	6.27
11650.000	40.86	PK	V	14.49	55.35	74.00	18.65
11650.000	27.62	AV	V	14.49	42.11	54.00	11.89
17475.000	39.13	PK	H	18.94	58.07	68.20	10.13
17475.000	39.14	PK	V	18.94	58.08	68.20	10.12

802.11ac40 Mode:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Remark					
Low Channel:				5755	MHz		
11510.000	40.22	PK	H	14.05	54.27	74.00	19.73
11510.000	26.14	AV	H	14.05	40.19	54.00	13.81
11510.000	38.97	PK	V	14.05	53.02	74.00	20.98
11510.000	25.84	AV	V	14.05	39.89	54.00	14.11
17265.000	39.31	PK	H	17.22	56.53	68.20	11.67
17265.000	38.75	PK	V	17.22	55.97	68.20	12.23
High Channel:				5795	MHz		
11590.000	45.77	PK	H	14.43	60.20	74.00	13.80
11590.000	30.34	AV	H	14.43	44.77	54.00	9.23
11590.000	40.09	PK	V	14.43	54.52	74.00	19.48
11590.000	26.34	AV	V	14.43	40.77	54.00	13.23
17385.000	38.54	PK	H	18.26	56.80	68.20	11.40
17385.000	39.24	PK	V	18.26	57.50	68.20	10.70

802.11ac80 Mode:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Remark					
Middle Channel:				5775	MHz		
11550.000	41.86	PK	H	14.24	56.10	74.00	17.90
11550.000	27.60	AV	H	14.24	41.84	54.00	12.16
11550.000	38.82	PK	V	14.24	53.06	74.00	20.94
11550.000	26.37	AV	V	14.24	40.61	54.00	13.39
17325.000	38.66	PK	H	17.70	56.36	68.20	11.84
17325.000	38.35	PK	V	17.70	56.05	68.20	12.15

802.11ax20 Mode:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)
	Reading (dBµV)	Remark					
Low Channel: 5745 MHz							
11490.000	39.13	PK	H	13.97	53.10	74.00	20.90
11490.000	26.01	AV	H	13.97	39.98	54.00	14.02
11490.000	38.02	PK	V	13.97	51.99	74.00	22.01
11490.000	25.33	AV	V	13.97	39.30	54.00	14.70
17235.000	39.03	PK	H	16.99	56.02	68.20	12.18
17235.000	38.80	PK	V	16.99	55.79	68.20	12.41
Middle Channel: 5785 MHz							
11570.000	45.73	PK	H	14.33	60.06	74.00	13.94
11570.000	31.02	AV	H	14.33	45.35	54.00	8.65
11570.000	39.50	PK	V	14.33	53.83	74.00	20.17
11570.000	26.42	AV	V	14.33	40.75	54.00	13.25
17355.000	38.84	PK	H	17.98	56.82	68.20	11.38
17355.000	38.87	PK	V	17.98	56.85	68.20	11.35
High Channel: 5825 MHz							
11650.000	48.10	PK	H	14.49	62.59	74.00	11.41
11650.000	32.82	AV	H	14.49	47.31	54.00	6.69
11650.000	40.75	PK	V	14.49	55.24	74.00	18.76
11650.000	27.79	AV	V	14.49	42.28	54.00	11.72
17475.000	38.97	PK	H	18.94	57.91	68.20	10.29
17475.000	39.13	PK	V	18.94	58.07	68.20	10.13

802.11ax40 Mode:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Remark					
Low Channel:				5755	MHz		
11510.000	39.71	PK	H	14.05	53.76	74.00	20.24
11510.000	26.34	AV	H	14.05	40.39	54.00	13.61
11510.000	38.56	PK	V	14.05	52.61	74.00	21.39
11510.000	25.15	AV	V	14.05	39.20	54.00	14.80
17265.000	38.35	PK	H	17.22	55.57	68.20	12.63
17265.000	38.22	PK	V	17.22	55.44	68.20	12.76
High Channel:				5795	MHz		
11590.000	44.45	PK	H	14.43	58.88	74.00	15.12
11590.000	31.89	AV	H	14.43	46.32	54.00	7.68
11590.000	40.57	PK	V	14.43	55.00	74.00	19.00
11590.000	28.03	AV	V	14.43	42.46	54.00	11.54
17385.000	39.26	PK	H	18.26	57.52	68.20	10.68
17385.000	39.00	PK	V	18.26	57.26	68.20	10.94

802.11ax80 Mode:


Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Remark					
Middle Channel:				5775	MHz		
11550.000	41.19	PK	H	14.24	55.43	74.00	18.57
11550.000	29.17	AV	H	14.24	43.41	54.00	10.59
11550.000	38.86	PK	V	14.24	53.10	74.00	20.91
11550.000	26.77	AV	V	14.24	41.01	54.00	12.99
17325.000	38.43	PK	H	17.70	56.13	68.20	12.07
17325.000	38.31	PK	V	17.70	56.01	68.20	12.19

2.4G Wifi is transmitted simultaneously with 5G Wifi:
802.11ax40 2452MHz+802.11ac20 5240MHz was tested:


Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Remark					
4904.000	37.57	PK	H	4.95	42.52	74.00	31.48
4904.000	37.37	PK	V	4.95	42.32	74.00	31.68
7356.000	43.68	PK	H	10.65	54.33	74.00	19.67
7356.000	26.09	AV	H	10.65	36.74	54.00	17.26
7356.000	39.57	PK	V	10.65	50.22	74.00	23.78
7356.000	25.39	AV	V	10.65	36.04	54.00	17.96
10480.000	36.15	PK	H	13.38	49.53	68.20	18.67
10480.000	36.06	PK	V	13.38	49.44	68.20	18.76
15720.000	40.20	PK	H	13.30	53.50	74.00	20.50
15720.000	26.94	AV	H	13.30	40.24	54.00	13.76
15720.000	40.75	PK	V	13.30	54.05	74.00	19.95
15720.000	26.95	AV	V	13.30	40.25	54.00	13.75

Worst radiation spurious emissions margin test plots for each mode
1-18GHz:

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: horizontal
Note: 5G WiFi B1 a Mode High Channel 5240MHz Chain 0




Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: vertical
Note: 5G WiFi B1 a Mode High Channel 5240MHz Chain 0




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5580.000	38.51	6.91	45.42	68.20	22.78	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
Polarization: horizontal
Note: 5G WiFi B1 a Mode High Channel 5240MHz Chain 0




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10480.000	43.20	13.38	56.58	68.20	11.62	Peak
2	15720.000	41.36	13.30	54.66	74.00	19.34	Peak
3	15720.000	28.34	13.30	41.64	54.00	12.36	Average
4	17731.200	39.83	21.11	60.94	74.00	13.06	Peak
5	17731.200	26.12	21.11	47.23	54.00	6.77	Average

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
 Polarization: vertical
 Note: 5G WiFi B1 a Mode High Channel 5240MHz Chain 0




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	10480.000	38.10	13.38	51.48	68.20	16.72	Peak
2	15720.000	41.38	13.30	54.68	74.00	19.32	Peak
3	15720.000	28.35	13.30	41.65	54.00	12.35	Average
4	17750.400	40.88	21.18	62.06	74.00	11.94	Peak
5	17750.400	26.66	21.18	47.84	54.00	6.16	Average

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: horizontal
Note: 5G WiFi B1 a Mode High Channel 5240MHz Chain 1




No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Result (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Remark
1	5803.000	37.52	6.85	44.37	68.20	23.83	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: vertical
Note: 5G WiFi B1 a Mode High Channel 5240MHz Chain 1




No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Result (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Remark
1	5891.000	37.86	7.07	44.93	68.20	23.27	Peak

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
 Polarization: horizontal
 Note: 5G WiFi B1 a Mode High Channel 5240MHz Chain 1




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	10480.000	45.81	13.38	59.19	68.20	9.01	Peak
2	15720.000	41.08	13.30	54.38	74.00	19.62	Peak
3	15720.000	28.26	13.30	41.56	54.00	12.44	Average
4	17750.400	40.06	21.18	61.24	74.00	12.76	Peak
5	17750.400	26.39	21.18	47.57	54.00	6.43	Average

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
 Polarization: vertical
 Note: 5G WiFi B1 a Mode High Channel 5240MHz Chain 1




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	10480.000	42.68	13.38	56.06	68.20	12.14	Peak
2	15720.000	41.13	13.30	54.43	74.00	19.57	Peak
3	15720.000	28.25	13.30	41.55	54.00	12.45	Average
4	17740.800	40.43	21.15	61.58	74.00	12.42	Peak
5	17740.800	26.56	21.15	47.71	54.00	6.29	Average

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: horizontal
Note: 5G WiFi B1 a Mode High Channel 5240MHz Chain 2




No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Result (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Remark
1	5525.000	37.33	6.88	44.21	68.20	23.99	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: vertical
Note: 5G WiFi B1 a Mode High Channel 5240MHz Chain 2




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5764.000	37.48	6.85	44.33	68.20	23.87	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
Polarization: horizontal
Note: 5G WiFi B1 a Mode High Channel 5240MHz Chain 2




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	10480.000	48.16	13.38	61.54	68.20	6.66	Peak
2	15720.000	41.07	13.30	54.37	74.00	19.63	Peak
3	15720.000	28.25	13.30	41.55	54.00	12.45	Average
4	17750.400	40.32	21.18	61.50	74.00	12.50	Peak
5	17750.400	26.34	21.18	47.52	54.00	6.48	Average

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
 Polarization: vertical
 Note: 5G WiFi B1 a Mode High Channel 5240MHz Chain 2




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10480.000	37.87	13.38	51.25	68.20	16.95	Peak
2	15720.000	40.92	13.30	54.22	74.00	19.78	Peak
3	15720.000	28.26	13.30	41.56	54.00	12.44	Average
4	17781.600	40.11	21.28	61.39	74.00	12.61	Peak
5	17781.600	26.37	21.28	47.65	54.00	6.35	Average

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: horizontal
Note: 5G WiFi B1 ac20 Mode High Channel 5240MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5934.000	37.13	7.21	44.34	68.20	23.86	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: vertical
Note: 5G WiFi B1 ac20 Mode High Channel 5240MHz




No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Result (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Remark
1	5861.000	37.25	6.96	44.21	68.20	23.99	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
Polarization: horizontal
Note: 5G WiFi B1 ac20 Mode High Channel 5240MHz




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10480.000	51.54	13.38	64.92	68.20	3.28	Peak
2	15720.000	41.24	13.30	54.54	74.00	19.46	Peak
3	15720.000	28.26	13.30	41.56	54.00	12.44	Average
4	17774.400	39.95	21.26	61.21	74.00	12.79	Peak
5	17774.400	26.37	21.26	47.63	54.00	6.37	Average

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
Polarization: vertical
Note: 5G WiFi B1 ac20 Mode High Channel 5240MHz




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10480.000	42.23	13.38	55.61	68.20	12.59	Peak
2	15720.000	41.08	13.30	54.38	74.00	19.62	Peak
3	15720.000	28.24	13.30	41.54	54.00	12.46	Average
4	17743.200	40.08	21.16	61.24	74.00	12.76	Peak
5	17743.200	26.52	21.16	47.68	54.00	6.32	Average

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: horizontal
Note: 5G WiFi B1 ac40 Mode High Channel 5230MHz




No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Result (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Remark
1	5676.000	37.51	6.82	44.33	68.20	23.87	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: vertical
Note: 5G WiFi B1 ac40 Mode High Channel 5230MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5797.000	37.03	6.85	43.88	68.20	24.32	Peak

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
 Polarization: horizontal
 Note: 5G WiFi B1 ac40 Mode High Channel 5230MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	10460.000	46.30	13.35	59.65	68.20	8.55	Peak
2	15690.000	41.34	13.33	54.67	74.00	19.33	Peak
3	15690.000	28.25	13.33	41.58	54.00	12.42	Average
4	17767.200	40.23	21.24	61.47	74.00	12.53	Peak
5	17767.200	26.31	21.24	47.55	54.00	6.45	Average

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
 Polarization: vertical
 Note: 5G WiFi B1 ac40 Mode High Channel 5230MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	10460.000	40.56	13.35	53.91	68.20	14.29	Peak
2	15690.000	41.44	13.33	54.77	74.00	19.23	Peak
3	15690.000	28.22	13.33	41.55	54.00	12.45	Average
4	17712.000	40.47	21.05	61.52	74.00	12.48	Peak
5	17712.000	26.61	21.05	47.66	54.00	6.34	Average

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: horizontal
Note: 5G WiFi B1 ac80 Mode Middle Channel 5210MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5797.000	37.38	6.85	44.23	68.20	23.97	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: vertical
Note: 5G WiFi B1 ac80 Mode Middle Channel 5210MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5892.000	37.69	7.07	44.76	68.20	23.44	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:10kHz
Polarization: horizontal
Note: 5G WiFi B1 ac80 Mode Middle Channel 5210MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	10420.000	41.18	13.30	54.48	68.20	13.72	Peak
2	15630.000	40.54	13.36	53.90	74.00	20.10	Peak
3	15630.000	27.60	13.36	40.96	54.00	13.04	Average
4	17772.000	40.00	21.26	61.26	74.00	12.74	Peak
5	17772.000	26.31	21.26	47.57	54.00	6.43	Average

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:10kHz
 Polarization: vertical
 Note: 5G WiFi B1 ac80 Mode Middle Channel 5210MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	10420.000	38.49	13.30	51.79	68.20	16.41	Peak
2	15630.000	41.04	13.36	54.40	74.00	19.60	Peak
3	15630.000	27.51	13.36	40.87	54.00	13.13	Average
4	17757.600	40.49	21.20	61.69	74.00	12.31	Peak
5	17757.600	26.64	21.20	47.84	54.00	6.16	Average

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: horizontal
Note: 5G WiFi B1 ax20 Mode High Channel 5240MHz




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5892.000	37.76	7.07	44.83	68.20	23.37	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: vertical
Note: 5G WiFi B1 ax20 Mode High Channel 5240MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5758.000	38.22	6.86	45.08	68.20	23.12	Peak

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
 Polarization: horizontal
 Note: 5G WiFi B1 ax20 Mode High Channel 5240MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	10480.000	49.01	13.38	62.39	68.20	5.81	Peak
2	15720.000	41.46	13.30	54.76	74.00	19.24	Peak
3	15720.000	28.24	13.30	41.54	54.00	12.46	Average
4	17788.800	40.14	21.32	61.46	74.00	12.54	Peak
5	17788.800	26.37	21.32	47.69	54.00	6.31	Average

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
 Polarization: vertical
 Note: 5G WiFi B1 ax20 Mode High Channel 5240MHz




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10480.000	42.13	13.38	55.51	68.20	12.69	Peak
2	15720.000	41.57	13.30	54.87	74.00	19.13	Peak
3	15720.000	28.42	13.30	41.72	54.00	12.28	Average
4	17788.800	39.92	21.32	61.24	74.00	12.76	Peak
5	17788.800	26.22	21.32	47.54	54.00	6.46	Average

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: horizontal
Note: 5G WiFi B1 ax40 Mode High Channel 5230MHz




No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Result (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Remark
1	5952.000	37.07	7.26	44.33	68.20	23.87	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: vertical
Note: 5G WiFi B1 ax40 Mode High Channel 5230MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5753.000	37.67	6.86	44.53	68.20	23.67	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
Polarization: horizontal
Note: 5G WiFi B1 ax40 Mode High Channel 5230MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	10460.000	45.96	13.35	59.31	68.20	8.89	Peak
2	15690.000	40.71	13.33	54.04	74.00	19.96	Peak
3	15690.000	28.22	13.33	41.55	54.00	12.45	Average
4	17776.800	39.82	21.27	61.09	74.00	12.91	Peak
5	17776.800	26.48	21.27	47.75	54.00	6.25	Average

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
Polarization: vertical
Note: 5G WiFi B1 ax40 Mode High Channel 5230MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	10460.000	40.22	13.35	53.57	68.20	14.63	Peak
2	15690.000	41.06	13.33	54.39	74.00	19.61	Peak
3	15690.000	28.19	13.33	41.52	54.00	12.48	Average
4	17750.400	40.41	21.18	61.59	74.00	12.41	Peak
5	17750.400	26.58	21.18	47.76	54.00	6.24	Average

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: horizontal
Note: 5G WiFi B1 ax80 Mode Middle Channel 5210MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5738.000	37.81	6.84	44.65	68.20	23.55	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: vertical
Note: 5G WiFi B1 ax80 Mode Middle Channel 5210MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5931.000	37.50	7.18	44.68	68.20	23.52	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
Polarization: horizontal
Note: 5G WiFi B1 ax80 Mode Middle Channel 5210MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	10420.000	41.00	13.30	54.30	68.20	13.90	Peak
2	15630.000	40.50	13.36	53.86	74.00	20.14	Peak
3	15630.000	27.53	13.36	40.89	54.00	13.11	Average
4	17776.800	40.58	21.27	61.85	74.00	12.15	Peak
5	17776.800	26.41	21.27	47.68	54.00	6.32	Average

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
 Polarization: vertical
 Note: 5G WiFi B1 ax80 Mode Middle Channel 5210MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	10420.000	38.58	13.30	51.88	68.20	16.32	Peak
2	15630.000	40.07	13.36	53.43	74.00	20.57	Peak
3	15630.000	27.59	13.36	40.95	54.00	13.05	Average
4	17776.800	40.49	21.27	61.76	74.00	12.24	Peak
5	17776.800	26.39	21.27	47.66	54.00	6.34	Average

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: horizontal
Note: 5G WiFi B4 a Mode High Channel 5825MHz Chain 0




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5527.000	37.83	6.89	44.72	68.20	23.48	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: vertical
Note: 5G WiFi B4 a Mode High Channel 5825MHz Chain 0




No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Result (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Remark
1	5926.000	37.24	7.17	44.41	68.20	23.79	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
Polarization: horizontal
Note: 5G WiFi B4 a Mode High Channel 5825MHz Chain 0




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	11650.000	39.60	14.49	54.09	74.00	19.91	Peak
2	11650.000	26.36	14.49	40.85	54.00	13.15	Average
3	17475.000	39.25	18.94	58.19	68.20	10.01	Peak
4	17781.600	40.37	21.28	61.65	74.00	12.35	Peak
5	17781.600	26.49	21.28	47.77	54.00	6.23	Average

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
 Polarization: vertical
 Note: 5G WiFi B4 a Mode High Channel 5825MHz Chain 0




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	11650.000	39.47	14.49	53.96	74.00	20.04	Peak
2	11650.000	25.92	14.49	40.41	54.00	13.59	Average
3	17475.000	39.21	18.94	58.15	68.20	10.05	Peak
4	17767.200	39.85	21.24	61.09	74.00	12.91	Peak
5	17767.200	26.43	21.24	47.67	54.00	6.33	Average

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: horizontal
Note: 5G WiFi B4 a Mode High Channel 5825MHz Chain 1




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5863.000	38.27	6.97	45.24	68.20	22.96	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: vertical
Note: 5G WiFi B4 a Mode High Channel 5825MHz Chain 1




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5963.000	37.75	7.37	45.12	68.20	23.08	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
Polarization: horizontal
Note: 5G WiFi B4 a Mode High Channel 5825MHz Chain 1




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	11650.000	46.84	14.49	61.33	74.00	12.67	Peak
2	11650.000	33.43	14.49	47.92	54.00	6.08	Average
3	17475.000	39.31	18.94	58.25	68.20	9.95	Peak
4	17793.600	40.23	21.33	61.56	74.00	12.44	Peak
5	17793.600	26.48	21.33	47.81	54.00	6.19	Average

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
 Polarization: vertical
 Note: 5G WiFi B4 a Mode High Channel 5825MHz Chain 1




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	11650.000	39.70	14.49	54.19	74.00	19.81	Peak
2	11650.000	28.02	14.49	42.51	54.00	11.49	Average
3	17475.000	39.70	18.94	58.64	68.20	9.56	Peak
4	17743.200	41.20	21.16	62.36	74.00	11.64	Peak
5	17743.200	26.67	21.16	47.83	54.00	6.17	Average

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: horizontal
Note: 5G WiFi B4 a Mode High Channel 5825MHz Chain 2




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5865.000	37.57	6.97	44.54	68.20	23.66	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: vertical
Note: 5G WiFi B4 a Mode High Channel 5825MHz Chain 2




Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
Polarization: horizontal
Note: 5G WiFi B4 a Mode High Channel 5825MHz Chain 2




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	11650.000	41.69	14.49	56.18	74.00	17.82	Peak
2	11650.000	28.18	14.49	42.67	54.00	11.33	Average
3	17475.000	38.98	18.94	57.92	68.20	10.28	Peak
4	17736.000	40.87	21.13	62.00	74.00	12.00	Peak
5	17736.000	26.66	21.13	47.79	54.00	6.21	Average

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
 Polarization: vertical
 Note: 5G WiFi B4 a Mode High Channel 5825MHz Chain 2




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	11650.000	40.09	14.49	54.58	74.00	19.42	Peak
2	11650.000	28.84	14.49	43.33	54.00	10.67	Average
3	17475.000	38.90	18.94	57.84	68.20	10.36	Peak
4	17817.600	40.70	21.39	62.09	74.00	11.91	Peak
5	17817.600	26.20	21.39	47.59	54.00	6.41	Average

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: horizontal
Note: 5G WiFi B4 ac20 Mode High Channel 5825MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5831.000	37.27	6.89	44.16	68.20	24.04	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: vertical
Note: 5G WiFi B4 ac20 Mode High Channel 5825MHz




No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Result (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Remark
1	5892.000	37.45	7.07	44.52	68.20	23.68	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
Polarization: horizontal
Note: 5G WiFi B4 ac20 Mode High Channel 5825MHz




No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Result (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Remark
1	11650.000	47.55	14.49	62.04	74.00	11.96	Peak
2	11650.000	33.24	14.49	47.73	54.00	6.27	Average
3	17475.000	39.13	18.94	58.07	68.20	10.13	Peak
4	17786.400	40.12	21.30	61.42	74.00	12.58	Peak
5	17786.400	26.34	21.30	47.64	54.00	6.36	Average

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
 Polarization: vertical
 Note: 5G WiFi B4 ac20 Mode High Channel 5825MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	11650.000	40.86	14.49	55.35	74.00	18.65	Peak
2	11650.000	27.62	14.49	42.11	54.00	11.89	Average
3	17475.000	39.14	18.94	58.08	68.20	10.12	Peak
4	17760.000	40.57	21.21	61.78	74.00	12.22	Peak
5	17760.000	26.65	21.21	47.86	54.00	6.14	Average

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: horizontal
Note: 5G WiFi B4 ac40 Mode High Channel 5795MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5531.000	37.76	6.92	44.68	68.20	23.52	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: vertical
Note: 5G WiFi B4 ac40 Mode High Channel 5795MHz




No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Result (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Remark
1	5924.000	37.29	7.18	44.47	68.20	23.73	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
Polarization: horizontal
Note: 5G WiFi B4 ac40 Mode High Channel 5795MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	11590.000	45.77	14.43	60.20	74.00	13.80	Peak
2	11590.000	30.34	14.43	44.77	54.00	9.23	Average
3	17385.000	38.54	18.26	56.80	68.20	11.40	Peak
4	17750.400	41.44	21.18	62.62	74.00	11.38	Peak
5	17750.400	26.69	21.18	47.87	54.00	6.13	Average

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
 Polarization: vertical
 Note: 5G WiFi B4 ac40 Mode High Channel 5795MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	11590.000	40.09	14.43	54.52	74.00	19.48	Peak
2	11590.000	26.34	14.43	40.77	54.00	13.23	Average
3	17385.000	39.24	18.26	57.50	68.20	10.70	Peak
4	17798.400	39.97	21.35	61.32	74.00	12.68	Peak
5	17798.400	26.31	21.35	47.66	54.00	6.34	Average

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: horizontal
Note: 5G WiFi B4 ac80 Mode Middle Channel 5775MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5998.000	36.69	7.71	44.40	68.20	23.80	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: vertical
Note: 5G WiFi B4 ac80 Mode Middle Channel 5775MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5672.000	37.64	6.82	44.46	68.20	23.74	Peak

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:10kHz
 Polarization: horizontal
 Note: 5G WiFi B4 ac80 Mode Middle Channel 5775MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	11550.000	41.86	14.24	56.10	74.00	17.90	Peak
2	11550.000	27.60	14.24	41.84	54.00	12.16	Average
3	17325.000	38.66	17.70	56.36	68.20	11.84	Peak
4	17748.000	40.71	21.17	61.88	74.00	12.12	Peak
5	17748.000	26.63	21.17	47.80	54.00	6.20	Average

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:10kHz
Polarization: vertical
Note: 5G WiFi B4 ac80 Mode Middle Channel 5775MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	11550.000	38.82	14.24	53.06	74.00	20.94	Peak
2	11550.000	26.37	14.24	40.61	54.00	13.39	Average
3	17325.000	38.35	17.70	56.05	68.20	12.15	Peak
4	17779.200	39.75	21.28	61.03	74.00	12.97	Peak
5	17779.200	26.49	21.28	47.77	54.00	6.23	Average

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: horizontal
Note: 5G WiFi B4 ax20 Mode High Channel 5825MHz




No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Result (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Remark
1	5995.000	37.25	7.68	44.93	68.20	23.27	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: vertical
Note: 5G WiFi B4 ax20 Mode High Channel 5825MHz




No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Result (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Remark
1	5900.000	37.63	7.11	44.74	68.20	23.46	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
Polarization: horizontal
Note: 5G WiFi B4 ax20 Mode High Channel 5825MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	11650.000	48.10	14.49	62.59	74.00	11.41	Peak
2	11650.000	32.82	14.49	47.31	54.00	6.69	Average
3	17475.000	38.97	18.94	57.91	68.20	10.29	Peak
4	17760.000	40.42	21.21	61.63	74.00	12.37	Peak
5	17760.000	26.41	21.21	47.62	54.00	6.38	Average

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
 Polarization: vertical
 Note: 5G WiFi B4 ax20 Mode High Channel 5825MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	11650.000	40.75	14.49	55.24	74.00	18.76	Peak
2	11650.000	27.79	14.49	42.28	54.00	11.72	Average
3	17475.000	39.13	18.94	58.07	68.20	10.13	Peak
4	17810.400	40.10	21.36	61.46	74.00	12.54	Peak
5	17810.400	26.36	21.36	47.72	54.00	6.28	Average

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: horizontal
Note: 5G WiFi B4 ax40 Mode High Channel 5795MHz




Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: vertical
Note: 5G WiFi B4 ax40 Mode High Channel 5795MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5988.000	37.19	7.62	44.81	68.20	23.39	Peak

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
 Polarization: horizontal
 Note: 5G WiFi B4 ax40 Mode High Channel 5795MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	11590.000	44.45	14.43	58.88	74.00	15.12	Peak
2	11590.000	31.89	14.43	46.32	54.00	7.68	Average
3	17385.000	39.26	18.26	57.52	68.20	10.68	Peak
4	17764.800	40.99	21.23	62.22	74.00	11.78	Peak
5	17764.800	26.65	21.23	47.88	54.00	6.12	Average

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
 Polarization: vertical
 Note: 5G WiFi B4 ax40 Mode High Channel 5795MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	11590.000	40.57	14.43	55.00	74.00	19.00	Peak
2	11590.000	28.03	14.43	42.46	54.00	11.54	Average
3	17385.000	39.00	18.26	57.26	68.20	10.94	Peak
4	17776.800	40.28	21.27	61.55	74.00	12.45	Peak
5	17776.800	26.52	21.27	47.79	54.00	6.21	Average

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: horizontal
Note: 5G WiFi B4 ax80 Mode Middle Channel 5775MHz




No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Result (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Remark
1	5934.000	37.38	7.21	44.59	68.20	23.61	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: vertical
Note: 5G WiFi B4 ax80 Mode Middle Channel 5775MHz




No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Result (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Remark
1	5742.000	37.69	6.86	44.55	68.20	23.65	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
Polarization: horizontal
Note: 5G WiFi B4 ax80 Mode Middle Channel 5775MHz



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	11550.000	41.19	14.24	55.43	74.00	18.57	Peak
2	11550.000	29.17	14.24	43.41	54.00	10.59	Average
3	17325.000	38.43	17.70	56.13	68.20	12.07	Peak
4	17752.800	39.78	21.19	60.97	74.00	13.03	Peak
5	17752.800	26.46	21.19	47.65	54.00	6.35	Average


Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
 Polarization: vertical
 Note: 5G WiFi B4 ax80 Mode Middle Channel 5775MHz



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	11550.000	38.86	14.24	53.10	74.00	20.90	Peak
2	11550.000	26.77	14.24	41.01	54.00	12.99	Average
3	17325.000	38.31	17.70	56.01	68.20	12.19	Peak
4	17755.200	39.42	21.20	60.62	74.00	13.38	Peak
5	17755.200	26.47	21.20	47.67	54.00	6.33	Average


2.4G Wifi is transmitted simultaneously with 5G Wifi:
802.11ax40 2452MHz+802.11ac20 5240MHz was tested:

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: horizontal
Note: 2.4G ax40 High Channel & 5G ac20 High Channel




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	4904.000	37.57	4.95	42.52	74.00	31.48	Peak
2	5863.000	37.26	6.97	44.23	68.20	23.97	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: vertical
Note: 2.4G ax40 High Channel & 5G ac20 High Channel




Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
 Polarization: horizontal
 Note: 2.4G ax40 High Channel & 5G ac20 High Channel



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark

1	7356.000	43.68	10.65	54.33	74.00	19.67	Peak
2	7356.000	26.09	10.65	36.74	54.00	17.26	Average
3	10480.000	36.15	13.38	49.53	68.20	18.67	Peak
4	15720.000	40.20	13.30	53.50	74.00	20.50	Peak
5	15720.000	26.94	13.30	40.24	54.00	13.76	Average
6	17733.600	40.28	21.12	61.40	74.00	12.60	Peak
7	17733.600	25.00	21.12	46.12	54.00	7.88	Average

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
 Polarization: vertical
 Note: 2.4G ax40 High Channel & 5G ac20 High Channel




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	7356.000	39.57	10.65	50.22	74.00	23.78	Peak
2	7356.000	25.39	10.65	36.04	54.00	17.96	Average
3	10480.000	36.06	13.38	49.44	68.20	18.76	Peak
4	15720.000	40.75	13.30	54.05	74.00	19.95	Peak
5	15720.000	26.95	13.30	40.25	54.00	13.75	Average
6	17743.200	39.98	21.16	61.14	74.00	12.86	Peak
7	17743.200	25.03	21.16	46.19	54.00	7.81	Average


18-40GHz:

No Emission was detected in the range 18-40GHz, test was performed on the mode and channel which with the maximum power.

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
 Polarization: Horizontal
 Note: 5G WiFi B4 ax40 Mode High Channel 5795MHz




Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
Polarization: Vertical
Note: 5G WiFi B4 ax40 Mode High Channel 5795MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	23077.900	49.08	7.46	56.54	74.00	17.46	Peak
2	23077.900	34.65	7.46	42.11	54.00	11.89	Average

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
Polarization: Horizontal
Note: 5G WiFi B4 ax40 Mode High Channel 5795MHz



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	39341.200	53.35	8.60	61.95	74.00	12.05	Peak
2	39341.200	38.98	8.60	47.58	54.00	6.42	Average


Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
Polarization: Vertical
Note: 5G WiFi B4 ax40 Mode High Channel 5795MHz



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	39395.200	54.00	8.02	62.02	74.00	11.98	Peak
2	39395.200	39.65	8.02	47.67	54.00	6.33	Average


2.4G Wifi is transmitted simultaneously with 5G Wifi:
802.11ax40 2452MHz+802.11ac20 5240MHz was tested:

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
Polarization: Horizontal
Note: 2.4G ax40 High Channel & 5G ac20 High Channel




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	19808.800	49.81	4.53	54.34	74.00	19.66	Peak
2	19808.800	42.28	4.53	46.81	54.00	7.19	Average

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
Polarization: Vertical
Note: 2.4G ax40 High Channel & 5G ac20 High Channel




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	19813.900	48.98	6.65	55.63	74.00	18.37	Peak
2	19813.900	40.09	6.65	46.74	54.00	7.26	Average

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
Polarization: Horizontal
Note: 2.4G ax40 High Channel & 5G ac20 High Channel



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	38928.100	51.60	9.59	61.19	74.00	12.81	Peak
2	38928.100	37.98	9.59	47.57	54.00	6.43	Average


Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
Polarization: Vertical
Note: 2.4G ax40 High Channel & 5G ac20 High Channel



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	38893.000	52.76	8.64	61.40	74.00	12.60	Peak
2	38893.000	38.97	8.64	47.61	54.00	6.39	Average


Band edge test plots

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: Horizontal
Note: 5G WiFi B1 a Mode Low Channel 5180 MHz Chain 0




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5136.920	48.17	5.78	53.95	74.00	20.05	Peak
2	5150.000	46.25	5.83	52.08	74.00	21.92	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: Vertical
Note: 5G WiFi B1 a Mode Low Channel 5180 MHz Chain 0




Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: Horizontal
Note: 5G WiFi B1 a Mode High Channel 5240 MHz Chain 0




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5350.000	45.30	6.43	51.73	74.00	22.27	Peak
2	5350.640	46.99	6.43	53.42	74.00	20.58	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: Vertical
Note: 5G WiFi B1 a Mode High Channel 5240 MHz Chain 0




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5350.000	45.43	6.43	51.86	74.00	22.14	Peak
2	5381.040	47.08	6.44	53.52	74.00	20.48	Peak


Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: Horizontal
Note: 5G WiFi B1 a Mode Low Channel 5180 MHz Chain 1



Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: Vertical
Note: 5G WiFi B1 a Mode Low Channel 5180 MHz Chain 1




Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: Horizontal
Note: 5G WiFi B1 a Mode High Channel 5240 MHz Chain 1




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5350.000	45.18	6.43	51.61	74.00	22.39	Peak
2	5394.280	47.36	6.45	53.81	74.00	20.19	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: Vertical
Note: 5G WiFi B1 a Mode High Channel 5240 MHz Chain 1




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5350.000	45.20	6.43	51.63	74.00	22.37	Peak
2	5382.240	46.97	6.44	53.41	74.00	20.59	Peak


Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
Polarization: Horizontal
Note: 5G WiFi B1 a Mode Low Channel 5180 MHz Chain 2



Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: Vertical
Note: 5G WiFi B1 a Mode Low Channel 5180 MHz Chain 2




Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: Horizontal
Note: 5G WiFi B1 a Mode High Channel 5240 MHz Chain 2




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5350.000	44.84	6.43	51.27	74.00	22.73	Peak
2	5372.520	46.96	6.44	53.40	74.00	20.60	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: Vertical
Note: 5G WiFi B1 a Mode High Channel 5240 MHz Chain 2




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5350.000	44.85	6.43	51.28	74.00	22.72	Peak
2	5355.600	46.86	6.43	53.29	74.00	20.71	Peak

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
 Polarization: Horizontal
 Note: 5G WiFi B1 ac20 Mode Low Channel 5180 MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5140.080	48.50	5.79	54.29	74.00	19.71	Peak
2	5140.080	37.10	5.79	42.89	54.00	11.11	Average
3	5150.000	45.89	5.83	51.72	74.00	22.28	Peak
4	5150.000	34.78	5.83	40.61	54.00	13.39	Average

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: Vertical
Note: 5G WiFi B1 ac20 Mode Low Channel 5180 MHz




Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: Horizontal
Note: 5G WiFi B1 ac20 Mode High Channel 5240 MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5350.000	44.92	6.43	51.35	74.00	22.65	Peak
2	5392.320	47.39	6.45	53.84	74.00	20.16	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: Vertical
Note: 5G WiFi B1 ac20 Mode High Channel 5240 MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5350.000	45.12	6.43	51.55	74.00	22.45	Peak
2	5394.040	47.02	6.45	53.47	74.00	20.53	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
Polarization: Horizontal
Note: 5G WiFi B1 ac40 Mode Low Channel 5190 MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5148.552	48.68	5.82	54.50	74.00	19.50	Peak
2	5148.552	35.05	5.82	40.87	54.00	13.13	Average
3	5150.000	47.38	5.83	53.21	74.00	20.79	Peak
4	5150.000	38.03	5.83	43.86	54.00	10.14	Average

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz
 Polarization: Vertical
 Note: 5G WiFi B1 ac40 Mode Low Channel 5190 MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5116.200	48.31	5.68	53.99	74.00	20.01	Peak
2	5150.000	45.95	5.83	51.78	74.00	22.22	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: Horizontal
Note: 5G WiFi B1 ac40 Mode High Channel 5230 MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5350.000	46.96	6.43	53.39	74.00	20.61	Peak
2	5396.360	47.31	6.45	53.76	74.00	20.24	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: Vertical
Note: 5G WiFi B1 ac40 Mode High Channel 5230 MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5350.000	45.56	6.43	51.99	74.00	22.01	Peak
2	5394.720	47.10	6.45	53.55	74.00	20.45	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:10kHz
Polarization: Horizontal
Note: 5G WiFi B1 ac80 Mode Middle Channel 5210 MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5149.500	50.69	5.83	56.52	74.00	17.48	Peak
2	5149.500	39.38	5.83	45.21	54.00	8.79	Average
3	5150.000	50.13	5.83	55.96	74.00	18.04	Peak
4	5150.000	38.31	5.83	44.14	54.00	9.86	Average
5	5350.000	44.91	6.43	51.34	74.00	22.66	Peak
6	5350.000	34.29	6.43	40.72	54.00	13.28	Average
7	5377.140	46.84	6.44	53.28	74.00	20.72	Peak
8	5377.140	33.91	6.44	40.35	54.00	13.65	Average

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:10kHz
 Polarization: Vertical
 Note: 5G WiFi B1 ac80 Mode Middle Channel 5210 MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5137.800	49.22	5.78	55.00	74.00	19.00	Peak
2	5137.800	37.28	5.78	43.06	54.00	10.94	Average
3	5150.000	45.96	5.83	51.79	74.00	22.21	Peak
4	5150.000	36.29	5.83	42.12	54.00	11.88	Average
5	5350.000	45.83	6.43	52.26	74.00	21.74	Peak
6	5350.000	34.07	6.43	40.50	54.00	13.50	Average
7	5393.940	48.53	6.45	54.98	74.00	19.02	Peak
8	5393.940	33.92	6.45	40.37	54.00	13.63	Average

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
Polarization: Horizontal
Note: 5G WiFi B1 ax20 Mode Low Channel 5180 MHz




Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: Vertical
Note: 5G WiFi B1 ax20 Mode Low Channel 5180 MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5147.120	47.70	5.82	53.52	74.00	20.48	Peak
2	5150.000	46.06	5.83	51.89	74.00	22.11	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: Horizontal
Note: 5G WiFi B1 ax20 Mode High Channel 5240 MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5350.000	44.88	6.43	51.31	74.00	22.69	Peak
2	5374.160	46.96	6.44	53.40	74.00	20.60	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: Vertical
Note: 5G WiFi B1 ax20 Mode High Channel 5240 MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5350.000	44.41	6.43	50.84	74.00	23.16	Peak
2	5359.800	47.09	6.44	53.53	74.00	20.47	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
Polarization: Horizontal
Note: 5G WiFi B1 ax40 Mode Low Channel 5190 MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5149.176	49.27	5.83	55.10	74.00	18.90	Peak
2	5149.176	37.14	5.83	42.97	54.00	11.03	Average
3	5150.000	47.94	5.83	53.77	74.00	20.23	Peak
4	5150.000	37.83	5.83	43.66	54.00	10.34	Average

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: Vertical
Note: 5G WiFi B1 ax40 Mode Low Channel 5190 MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5143.056	48.16	5.80	53.96	74.00	20.04	Peak
2	5150.000	45.94	5.83	51.77	74.00	22.23	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: Horizontal
Note: 5G WiFi B1 ax40 Mode High Channel 5230 MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5350.000	45.99	6.43	52.42	74.00	21.58	Peak
2	5378.680	47.27	6.45	53.72	74.00	20.28	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz
Polarization: Vertical
Note: 5G WiFi B1 ax40 Mode High Channel 5230 MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5350.000	45.09	6.43	51.52	74.00	22.48	Peak
2	5368.560	46.90	6.44	53.34	74.00	20.66	Peak

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
 Polarization: Horizontal
 Note: 5G WiFi B1 ax80 Mode Middle Channel 5210 MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5134.260	50.27	5.77	56.04	74.00	17.96	Peak
2	5134.260	37.76	5.77	43.53	54.00	10.47	Average
3	5150.000	49.30	5.83	55.13	74.00	18.87	Peak
4	5150.000	39.46	5.83	45.29	54.00	8.71	Average
5	5350.000	44.23	6.43	50.66	74.00	23.34	Peak
6	5350.000	34.14	6.43	40.57	54.00	13.43	Average
7	5382.180	46.94	6.44	53.38	74.00	20.62	Peak
8	5382.180	33.93	6.44	40.37	54.00	13.63	Average

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz; AV trace RBW:1MHz; VBW:5kHz
 Polarization: Vertical
 Note: 5G WiFi B1 ax80 Mode Middle Channel 5210 MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5145.960	48.59	5.81	54.40	74.00	19.60	Peak
2	5145.960	35.78	5.81	41.59	54.00	12.41	Average
3	5150.000	47.92	5.83	53.75	74.00	20.25	Peak
4	5150.000	36.65	5.83	42.48	54.00	11.52	Average
5	5350.000	45.19	6.43	51.62	74.00	22.38	Peak
6	5350.000	33.22	6.43	39.65	54.00	14.35	Average
7	5358.240	47.03	6.43	53.46	74.00	20.54	Peak
8	5358.240	33.06	6.43	39.49	54.00	14.51	Average

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz;
 Polarization: Horizontal
 Note: 5G WiFi B4 a Mode Low Channel 5745 MHz Chain 0




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5646.720	48.44	6.83	55.27	68.20	12.93	Peak
2	5650.000	47.21	6.83	54.04	68.20	14.16	Peak
3	5700.000	46.33	6.81	53.14	105.20	52.06	Peak
4	5720.000	46.12	6.83	52.95	110.80	57.85	Peak
5	5725.000	47.37	6.83	54.20	122.20	68.00	Peak

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz;
 Polarization: Vertical
 Note: 5G WiFi B4 a Mode Low Channel 5745 MHz Chain 0




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5614.496	47.94	6.82	54.76	68.20	13.44	Peak
2	5650.000	45.99	6.83	52.82	68.20	15.38	Peak
3	5700.000	45.43	6.81	52.24	105.20	52.96	Peak
4	5720.000	45.98	6.83	52.81	110.80	57.99	Peak
5	5725.000	46.04	6.83	52.87	122.20	69.33	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz;
Polarization: Horizontal
Note: 5G WiFi B4 a Mode High Channel 5825 MHz Chain 0




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5850.000	45.89	6.92	52.81	122.20	69.39	Peak
2	5855.000	46.40	6.94	53.34	110.80	57.46	Peak
3	5875.000	46.94	7.02	53.96	105.20	51.24	Peak
4	5925.000	45.97	7.17	53.14	68.20	15.06	Peak
5	5948.976	48.55	7.24	55.79	68.20	12.41	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz;
Polarization: Vertical
Note: 5G WiFi B4 a Mode High Channel 5825 MHz Chain 0




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5850.000	45.94	6.92	52.86	122.20	69.34	Peak
2	5855.000	46.76	6.94	53.70	110.80	57.10	Peak
3	5875.000	45.84	7.02	52.86	105.20	52.34	Peak
4	5925.000	46.22	7.17	53.39	68.20	14.81	Peak
5	5933.712	48.17	7.20	55.37	68.20	12.83	Peak

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz;
 Polarization: Horizontal
 Note: 5G WiFi B4 a Mode Low Channel 5745 MHz Chain 1




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5643.232	48.07	6.83	54.90	68.20	13.30	Peak
2	5650.000	46.56	6.83	53.39	68.20	14.81	Peak
3	5700.000	46.68	6.81	53.49	105.20	51.71	Peak
4	5720.000	47.53	6.83	54.36	110.80	56.44	Peak
5	5725.000	47.34	6.83	54.17	122.20	68.03	Peak

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz;
 Polarization: Vertical
 Note: 5G WiFi B4 a Mode Low Channel 5745 MHz Chain 1




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5609.952	47.81	6.83	54.64	68.20	13.56	Peak
2	5650.000	45.26	6.83	52.09	68.20	16.11	Peak
3	5700.000	46.33	6.81	53.14	105.20	52.06	Peak
4	5720.000	45.82	6.83	52.65	110.80	58.15	Peak
5	5725.000	46.15	6.83	52.98	122.20	69.22	Peak

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz;
 Polarization: Horizontal
 Note: 5G WiFi B4 a Mode High Channel 5825 MHz Chain 1




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5850.000	47.76	6.92	54.68	122.20	67.52	Peak
2	5855.000	46.46	6.94	53.40	110.80	57.40	Peak
3	5875.000	46.65	7.02	53.67	105.20	51.53	Peak
4	5925.000	46.38	7.17	53.55	68.20	14.65	Peak
5	5926.288	47.98	7.18	55.16	68.20	13.04	Peak

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz;
 Polarization: Vertical
 Note: 5G WiFi B4 a Mode High Channel 5825 MHz Chain 1




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5850.000	46.54	6.92	53.46	122.20	68.74	Peak
2	5855.000	45.70	6.94	52.64	110.80	58.16	Peak
3	5875.000	46.26	7.02	53.28	105.20	51.92	Peak
4	5925.000	45.16	7.17	52.33	68.20	15.87	Peak
5	5943.440	48.22	7.21	55.43	68.20	12.77	Peak

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz;
 Polarization: Horizontal
 Note: 5G WiFi B4 a Mode Low Channel 5745 MHz Chain 2




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5624.960	48.65	6.82	55.47	68.20	12.73	Peak
2	5650.000	45.19	6.83	52.02	68.20	16.18	Peak
3	5700.000	45.91	6.81	52.72	105.20	52.48	Peak
4	5720.000	46.29	6.83	53.12	110.80	57.68	Peak
5	5725.000	46.78	6.83	53.61	122.20	68.59	Peak

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz;
 Polarization: Vertical
 Note: 5G WiFi B4 a Mode Low Channel 5745 MHz Chain 2




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5624.992	48.60	6.82	55.42	68.20	12.78	Peak
2	5650.000	45.59	6.83	52.42	68.20	15.78	Peak
3	5700.000	47.05	6.81	53.86	105.20	51.34	Peak
4	5720.000	46.37	6.83	53.20	110.80	57.60	Peak
5	5725.000	46.75	6.83	53.58	122.20	68.62	Peak

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz;
 Polarization: Horizontal
 Note: 5G WiFi B4 a Mode High Channel 5825 MHz Chain 2




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5850.000	46.44	6.92	53.36	122.20	68.84	Peak
2	5855.000	46.80	6.94	53.74	110.80	57.06	Peak
3	5875.000	46.61	7.02	53.63	105.20	51.57	Peak
4	5925.000	46.34	7.17	53.51	68.20	14.69	Peak
5	5944.912	49.40	7.23	56.63	68.20	11.57	Peak

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz;
 Polarization: Vertical
 Note: 5G WiFi B4 a Mode High Channel 5825 MHz Chain 2




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5850.000	47.18	6.92	54.10	122.20	68.10	Peak
2	5855.000	46.70	6.94	53.64	110.80	57.16	Peak
3	5875.000	46.56	7.02	53.58	105.20	51.62	Peak
4	5925.000	46.15	7.17	53.32	68.20	14.88	Peak
5	5944.784	48.50	7.23	55.73	68.20	12.47	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz;
Polarization: Horizontal
Note: 5G WiFi B4 ac20 Mode Low Channel 5745 MHz




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5638.208	49.45	6.82	56.27	68.20	11.93	Peak
2	5650.000	48.13	6.83	54.96	68.20	13.24	Peak
3	5700.000	46.68	6.81	53.49	105.20	51.71	Peak
4	5720.000	47.66	6.83	54.49	110.80	56.31	Peak
5	5725.000	51.25	6.83	58.08	122.20	64.12	Peak

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz;
 Polarization: Vertical
 Note: 5G WiFi B4 ac20 Mode Low Channel 5745 MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5611.968	48.91	6.83	55.74	68.20	12.46	Peak
2	5650.000	45.81	6.83	52.64	68.20	15.56	Peak
3	5700.000	47.10	6.81	53.91	105.20	51.29	Peak
4	5720.000	46.86	6.83	53.69	110.80	57.11	Peak
5	5725.000	47.10	6.83	53.93	122.20	68.27	Peak

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz;
 Polarization: Horizontal
 Note: 5G WiFi B4 ac20 Mode High Channel 5825 MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5850.000	48.06	6.92	54.98	122.20	67.22	Peak
2	5855.000	47.44	6.94	54.38	110.80	56.42	Peak
3	5875.000	47.03	7.02	54.05	105.20	51.15	Peak
4	5925.000	46.35	7.17	53.52	68.20	14.68	Peak
5	5928.496	49.30	7.18	56.48	68.20	11.72	Peak

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz;
 Polarization: Vertical
 Note: 5G WiFi B4 ac20 Mode High Channel 5825 MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5850.000	46.21	6.92	53.13	122.20	69.07	Peak
2	5855.000	47.02	6.94	53.96	110.80	56.84	Peak
3	5875.000	46.51	7.02	53.53	105.20	51.67	Peak
4	5925.000	46.19	7.17	53.36	68.20	14.84	Peak
5	5944.880	47.90	7.23	55.13	68.20	13.07	Peak

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz;
 Polarization: Horizontal
 Note: 5G WiFi B4 ac40 Mode Low Channel 5755 MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5638.232	48.69	6.82	55.51	68.20	12.69	Peak
2	5650.000	46.49	6.83	53.32	68.20	14.88	Peak
3	5700.000	46.65	6.81	53.46	105.20	51.74	Peak
4	5720.000	48.73	6.83	55.56	110.80	55.24	Peak
5	5725.000	53.84	6.83	60.67	122.20	61.53	Peak

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz;
 Polarization: Vertical
 Note: 5G WiFi B4 ac40 Mode Low Channel 5755 MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5644.892	48.22	6.83	55.05	68.20	13.15	Peak
2	5650.000	46.31	6.83	53.14	68.20	15.06	Peak
3	5700.000	46.13	6.81	52.94	105.20	52.26	Peak
4	5720.000	47.25	6.83	54.08	110.80	56.72	Peak
5	5725.000	51.48	6.83	58.31	122.20	63.89	Peak

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz;
 Polarization: Horizontal
 Note: 5G WiFi B4 ac40 Mode High Channel 5795 MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5850.000	48.05	6.92	54.97	122.20	67.23	Peak
2	5855.000	48.98	6.94	55.92	110.80	54.88	Peak
3	5875.000	46.66	7.02	53.68	105.20	51.52	Peak
4	5925.000	46.22	7.17	53.39	68.20	14.81	Peak
5	5930.956	48.40	7.18	55.58	68.20	12.62	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz;
Polarization: Vertical
Note: 5G WiFi B4 ac40 Mode High Channel 5795 MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5850.000	47.94	6.92	54.86	122.20	67.34	Peak
2	5855.000	46.22	6.94	53.16	110.80	57.64	Peak
3	5875.000	46.37	7.02	53.39	105.20	51.81	Peak
4	5925.000	45.86	7.17	53.03	68.20	15.17	Peak
5	5949.568	47.90	7.24	55.14	68.20	13.06	Peak

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz;
 Polarization: Horizontal
 Note: 5G WiFi B4 ac80 Mode Middle Channel 5775 MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5646.340	48.90	6.83	55.73	68.20	12.47	Peak
2	5650.000	46.57	6.83	53.40	68.20	14.80	Peak
3	5700.000	52.29	6.81	59.10	105.20	46.10	Peak
4	5720.000	54.77	6.83	61.60	110.80	49.20	Peak
5	5725.000	54.24	6.83	61.07	122.20	61.13	Peak
6	5850.000	51.41	6.92	58.33	122.20	63.87	Peak
7	5855.000	50.75	6.94	57.69	110.80	53.11	Peak
8	5875.000	48.32	7.02	55.34	105.20	49.86	Peak
9	5925.000	45.84	7.17	53.01	68.20	15.19	Peak
10	5948.110	48.33	7.23	55.56	68.20	12.64	Peak

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz;
 Polarization: Vertical
 Note: 5G WiFi B4 ac80 Mode Middle Channel 5775 MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5641.510	48.11	6.83	54.94	68.20	13.26	Peak
2	5650.000	46.14	6.83	52.97	68.20	15.23	Peak
3	5700.000	49.14	6.81	55.95	105.20	49.25	Peak
4	5720.000	52.50	6.83	59.33	110.80	51.47	Peak
5	5725.000	52.90	6.83	59.73	122.20	62.47	Peak
6	5850.000	50.12	6.92	57.04	122.20	65.16	Peak
7	5855.000	50.84	6.94	57.78	110.80	53.02	Peak
8	5875.000	47.42	7.02	54.44	105.20	50.76	Peak
9	5925.000	46.51	7.17	53.68	68.20	14.52	Peak
10	5930.120	47.94	7.18	55.12	68.20	13.08	Peak

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz;
 Polarization: Horizontal
 Note: 5G WiFi B4 ax20 Mode Low Channel 5745 MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5633.280	48.64	6.82	55.46	68.20	12.74	Peak
2	5650.000	46.56	6.83	53.39	68.20	14.81	Peak
3	5700.000	46.06	6.81	52.87	105.20	52.33	Peak
4	5720.000	48.57	6.83	55.40	110.80	55.40	Peak
5	5725.000	48.72	6.83	55.55	122.20	66.65	Peak

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz;
 Polarization: Vertical
 Note: 5G WiFi B4 ax20 Mode Low Channel 5745 MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5625.152	48.47	6.83	55.30	68.20	12.90	Peak
2	5650.000	45.97	6.83	52.80	68.20	15.40	Peak
3	5700.000	46.96	6.81	53.77	105.20	51.43	Peak
4	5720.000	46.50	6.83	53.33	110.80	57.47	Peak
5	5725.000	47.54	6.83	54.37	122.20	67.83	Peak

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz;
 Polarization: Horizontal
 Note: 5G WiFi B4 ax20 Mode High Channel 5825 MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5850.000	49.50	6.92	56.42	122.20	65.78	Peak
2	5855.000	47.53	6.94	54.47	110.80	56.33	Peak
3	5875.000	46.15	7.02	53.17	105.20	52.03	Peak
4	5925.000	46.43	7.17	53.60	68.20	14.60	Peak
5	5927.504	48.71	7.18	55.89	68.20	12.31	Peak

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz;
 Polarization: Vertical
 Note: 5G WiFi B4 ax20 Mode High Channel 5825 MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5850.000	47.43	6.92	54.35	122.20	67.85	Peak
2	5855.000	46.00	6.94	52.94	110.80	57.86	Peak
3	5875.000	46.25	7.02	53.27	105.20	51.93	Peak
4	5925.000	45.46	7.17	52.63	68.20	15.57	Peak
5	5937.936	47.48	7.21	54.69	68.20	13.51	Peak

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz;
 Polarization: Horizontal
 Note: 5G WiFi B4 ax40 Mode Low Channel 5755 MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5642.948	48.91	6.83	55.74	68.20	12.46	Peak
2	5650.000	46.83	6.83	53.66	68.20	14.54	Peak
3	5700.000	47.42	6.81	54.23	105.20	50.97	Peak
4	5720.000	48.32	6.83	55.15	110.80	55.65	Peak
5	5725.000	53.80	6.83	60.63	122.20	61.57	Peak

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz;
 Polarization: Vertical
 Note: 5G WiFi B4 ax40 Mode Low Channel 5755 MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5634.884	49.67	6.83	56.50	68.20	11.70	Peak
2	5650.000	47.04	6.83	53.87	68.20	14.33	Peak
3	5700.000	48.02	6.81	54.83	105.20	50.37	Peak
4	5720.000	48.41	6.83	55.24	110.80	55.56	Peak
5	5725.000	52.48	6.83	59.31	122.20	62.89	Peak

Project No: 2603T12344E-RF
Tester: HuaYuan Miao
Condition: PK trace RBW:1MHz; VBW:3MHz;
Polarization: Horizontal
Note: 5G WiFi B4 ax40 Mode High Channel 5795 MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5850.000	50.31	6.92	57.23	122.20	64.97	Peak
2	5855.000	48.84	6.94	55.78	110.80	55.02	Peak
3	5875.000	50.52	7.02	57.54	105.20	47.66	Peak
4	5925.000	46.12	7.17	53.29	68.20	14.91	Peak
5	5947.408	48.20	7.24	55.44	68.20	12.76	Peak

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz;
 Polarization: Vertical
 Note: 5G WiFi B4 ax40 Mode High Channel 5795 MHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5850.000	46.86	6.92	53.78	122.20	68.42	Peak
2	5855.000	47.68	6.94	54.62	110.80	56.18	Peak
3	5875.000	45.85	7.02	52.87	105.20	52.33	Peak
4	5925.000	45.82	7.17	52.99	68.20	15.21	Peak
5	5937.796	48.26	7.21	55.47	68.20	12.73	Peak

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz;
 Polarization: Horizontal
 Note: 5G WiFi B4 ax80 Mode Middle Channel 5775 MHz



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	5647.250	48.65	6.84	55.49	68.20	12.71	Peak
2	5650.000	46.36	6.83	53.19	68.20	15.01	Peak
3	5700.000	51.45	6.81	58.26	105.20	46.94	Peak
4	5720.000	56.95	6.83	63.78	110.80	47.02	Peak
5	5725.000	58.00	6.83	64.83	122.20	57.37	Peak
6	5850.000	56.06	6.92	62.98	122.20	59.22	Peak
7	5855.000	54.92	6.94	61.86	110.80	48.94	Peak
8	5875.000	51.25	7.02	58.27	105.20	46.93	Peak
9	5925.000	47.93	7.17	55.10	68.20	13.10	Peak
10	5940.480	48.48	7.21	55.69	68.20	12.51	Peak

Project No: 2603T12344E-RF
 Tester: HuaYuan Miao
 Condition: PK trace RBW:1MHz; VBW:3MHz;
 Polarization: Vertical
 Note: 5G WiFi B4 ax80 Mode Middle Channel 5775 MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5633.180	48.20	6.82	55.02	68.20	13.18	Peak
2	5650.000	45.49	6.83	52.32	68.20	15.88	Peak
3	5700.000	48.22	6.81	55.03	105.20	50.17	Peak
4	5720.000	51.14	6.83	57.97	110.80	52.83	Peak
5	5725.000	50.72	6.83	57.55	122.20	64.65	Peak
6	5850.000	49.92	6.92	56.84	122.20	65.36	Peak
7	5855.000	49.90	6.94	56.84	110.80	53.96	Peak
8	5875.000	47.05	7.02	54.07	105.20	51.13	Peak
9	5925.000	46.94	7.17	54.11	68.20	14.09	Peak
10	5932.500	48.47	7.20	55.67	68.20	12.53	Peak

4.3 RF Conducted Data

Please refer to Annex "Appendix A" for detail test data.

5. EUT PHOTOGRAPHS

Please refer to the attachment 2603T12344E-RF-EXP EUT EXTERNAL PHOTOGRAPHS and 2603T12344E-RF-INP EUT INTERNAL PHOTOGRAPHS.

6. TEST SETUP PHOTOGRAPHS

Please refer to the attachment 2603T12344E-RF-00B-TSP TEST SETUP PHOTOGRAPHS.

===== END OF REPORT =====