



Radio Frequency Exposure

Applicant : CHENG UEI PRECISION INDUSTRY CO., LTD.

Address : No.18, Chung Shan Road, Tu Cheng District, New Taipei City, Taiwan,
R.O.C.

Equipment : Wireless Chime

Model No. : CW01, W01D1, C-SA

Trade Name : N/A

FCC ID : M6E-CSA

I HEREBY CERTIFY THAT:

The sample was received May 12, 2026 and the testing was completed on Jun. 04, 2026 at Cerpass Technology Corp. The test result refers exclusively to the test presented test model / sample. Without written approval of Cerpass Technology Corp., the test report shall not be reproduced except in full.

Approved by:

Mark Liao / Supervisor

Laboratory Accreditation:

Cerpass Technology Corporation Test Laboratory





Contents

1. Summary of Test Procedure and Test Results	4
1.1 Applicable Standards	4
2. Test Configuration of Equipment under Test.....	5
2.1 Feature of Equipment	5
2.2 General Information of Test.....	6
2.3 Measurement Uncertainty.....	7
3. Test Equipment and Ancillaries Used for Tests.....	8
4. Radio Frequency Exposure	9



History of this test report

Report No	Issued Date	Description
26050086-TRDFCC03	Jun. 09, 2026	Initial Issue



1. Summary of Test Procedure and Test Results

1.1 Applicable Standards

FCC Rules and Regulations Part 2.1091

FCC Rule	Description of Test	Result
2.1091	Radio Frequency Exposure	PASS
*The lab has reduced the uncertainty risk factor from test equipment, environment and staff technicians which according to the standard on contract. Therefore, the test result will only be determined by standard requirement, measurement uncertainty evaluation is not considered.		



2. Test Configuration of Equipment under Test

2.1 Feature of Equipment

Equipment	Wireless Chime
Model Name	CW01, W01D1, C-SA
Model Discrepancy	The models are identical to each other except for model name and appearance color.
Frequency Range	BLE/ WIFI 2.4G: 2400MHz-2483.5MHz
Modulation Type	BLE: GFSK 2.4GHz 802.11b: CCK, DQPSK, DBPSK 802.11g/n: BPSK, QPSK, 16QAM, 64QAM 802.11ax: BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM
Data Rate	BLE: GFSK: 1Mbps WIFI 2.4GHz: 802.11b: 1, 2, 5.5, 11Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54Mbps 802.11n: MCS0-MCS7, HT20 802.11ax: MCS0-MCS11, HE20
EUT Power Rating:	100-240VAC/0.5A 50/60Hz

Note: For more details, please refer to the User's manual of the EUT.

**2.2 General Information of Test**

Organization	Cerpass Technology Corp.	
Test Site	Cerpass Technology Corporation Test Laboratory Address: No.10, Ln. 2, Lianfu St., Luzhu Dist., Taoyuan City 33848, Taiwan (R.O.C.) Tel:+886-3-3226-888 Fax:+886-3-3226-881	
	FCC	TW1439, TW1079
	IC	4934E-1, 4934E-2
Frequency Range Investigated:	Conducted: from 150kHz to 30 MHz Radiation: from 9kHz to 25,000MHz	
Test Distance:	The test distance of radiated emission from antenna to EUT is 3 M.	



2.3 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)).

Measurement Item	Uncertainty
AC Power Line Conduction(150kHz~30MHz)	±3.2dB
Radiated Spurious Emission(9kHz~30MHz)	±3.4dB
Radiated Spurious Emission(30MHz~1GHz)	±5.2dB
Radiated Spurious Emission(1GHz~25GHz)	±5.2dB
Conducted Spurious Emission	±2.1dB
6dB Bandwidth	±4.4%
20dB Bandwidth	±4.5%
Occupied Bandwidth	±4.4%
Peak Output Power(Conducted Power Meter)	±1.1dB
Dwell Time / Deactivation Time	±3.5%
Power Spectral Density	±2.0dB
Duty Cycle	±3.5%



3. Test Equipment and Ancillaries Used for Tests

Test Item	RF Conducted				
Test Site	RFCON01-NK				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
EXA Signal Analyzer	KEYSIGHT	N9010A	MY54200207	2026/04/01	2027/03/30
Attenuator	AGILENT	8491B	MY39250703	2026/01/29	2027/01/28
Power Meter	Anritsu	ML2495A	1224005	2026/01/27	2027/01/26
Power Sensor	Anritsu	MA2411B	1207295	2026/01/27	2027/01/26



4. Radio Frequency Exposure

Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation)
Exposure classification	☐ Occupational/Controlled exposure (S = 5mW/cm ²) ☒ General Population/Uncontrolled exposure (S=1mW/cm ²)
Antenna diversity	☒ Single antenna ☐ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Evaluation applied	☒ MPE Evaluation* ☐ SAR Evaluation ☐ N/A

TEST RESULTS

No non-compliance noted.

Calculation

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{3770}$

Where E = Field strength in Volts / meter
 P = Power in Watts
 G = Numeric antenna gain
 d = Distance in meters
 S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where d = Distance in cm
 P = Power in mW
 G = Numeric antenna gain
 S = Power density in mW / cm²

**Maximum Permissible Exposure****Bluetooth**

Channel Frequency (MHz)	Max. Conducted output power (dBm)	Max. Tune up power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2402-2480 (BLE)	7.760	9.760	2.66	20	0.003	1

Wlan

Channel Frequency (MHz)	Max. Conducted output power (dBm)	Max. Tune up power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2412-2462	26.17	28.17	2.66	20	0.241	1

Note: BT and 2.4G WIFI can't transmit simultaneously.

Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

----- THE END OF REPORT-----