

P08 802.11g_Ch11_Top Side_0cm_Ant 0

DUT: Tablet;

Communication System: UID 0, WiFi (0); Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2462$ MHz; $\sigma = 1.989$ S/m; $\epsilon_r = 53.131$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.5 °C; Liquid Temperature : 22.0 °C

DASY Configuration:

- Probe: EX3DV4 - SN3753; ConvF(7.27, 7.27, 7.27); Calibrated: 5/5/2017;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = -19.0, 31.0$
- Electronics: DAE4 Sn1305; Calibrated: 4/25/2017
- Phantom: ELI V5.0 (20deg probe tilt); Type: QD OVA 002 AA; Serial: 1240
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373)

Area Scan (5x28x1): Measurement grid: $dx=12$ mm, $dy=12$ mm

Maximum value of SAR (measured) = 0.952 W/kg


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 9.915 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 1.44 W/kg

SAR(1 g) = 0.744 W/kg; SAR(10 g) = 0.333 W/kg

Maximum value of SAR (measured) = 1.13 W/kg



P12 802.11b_Ch11_Right Side_0cm_Ant 1**DUT: Tablet;**

Communication System: UID 0, WiFi (0); Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2462$ MHz; $\sigma = 1.989$ S/m; $\epsilon_r = 53.131$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.5 °C; Liquid Temperature : 22.0 °C

DASY Configuration:

- Probe: EX3DV4 - SN3753; ConvF(7.27, 7.27, 7.27); Calibrated: 5/5/2017;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = -19.0, 31.0$
- Electronics: DAE4 Sn1305; Calibrated: 4/25/2017
- Phantom: ELI V5.0 (20deg probe tilt); Type: QD OVA 002 AA; Serial: 1240
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373)

Area Scan (5x21x1): Measurement grid: $dx=12$ mm, $dy=12$ mm

Maximum value of SAR (measured) = 0.137 W/kg


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 5.006 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 0.192 W/kg

SAR(1 g) = 0.103 W/kg; SAR(10 g) = 0.050 W/kg

Maximum value of SAR (measured) = 0.150 W/kg



P32 802.11a_Ch52_Top Face_0cm_Ant 0

DUT: Tablet;

Communication System: UID 0, WiFi (0); Frequency: 5260 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5260$ MHz; $\sigma = 5.424$ S/m; $\epsilon_r = 47.523$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.8 °C; Liquid Temperature : 22.6 °C

DASY Configuration:

- Probe: EX3DV4 - SN3753; ConvF(4.87, 4.87, 4.87); Calibrated: 5/5/2017;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = -19.0, 23.0$
- Electronics: DAE4 Sn1305; Calibrated: 4/25/2017
- Phantom: ELI V5.0 (20deg probe tilt); Type: QD OVA 002 AA; Serial: 1240
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373)

Area Scan (10x36x1): Measurement grid: $dx=10$ mm, $dy=10$ mm

Maximum value of SAR (measured) = 0.942 W/kg


Zoom Scan (7x7x12)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=2$ mm

Reference Value = 3.586 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 2.54 W/kg

SAR(1 g) = 0.689 W/kg; SAR(10 g) = 0.225 W/kg

Maximum value of SAR (measured) = 1.32 W/kg



P36 802.11a_Ch52_Right Side_0cm_Ant 1

DUT: Tablet;

Communication System: UID 0, WiFi (0); Frequency: 5260 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5260$ MHz; $\sigma = 5.424$ S/m; $\epsilon_r = 47.523$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.8 °C; Liquid Temperature : 22.6 °C

DASY Configuration:

- Probe: EX3DV4 - SN3753; ConvF(4.87, 4.87, 4.87); Calibrated: 5/5/2017;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = -19.0, 23.0$
- Electronics: DAE4 Sn1305; Calibrated: 4/25/2017
- Phantom: ELI V5.0 (20deg probe tilt); Type: QD OVA 002 AA; Serial: 1240
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373)

Area Scan (7x22x1): Measurement grid: $dx=10$ mm, $dy=10$ mm

Maximum value of SAR (measured) = 1.52 W/kg


Zoom Scan (7x7x12)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=2$ mm

Reference Value = 2.782 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 4.38 W/kg

SAR(1 g) = 1.13 W/kg; SAR(10 g) = 0.393 W/kg

Maximum value of SAR (measured) = 2.24 W/kg



P42 802.11a_Ch116_Top Face_0cm_Ant 0

DUT: Tablet;

Communication System: UID 0, WiFi (0); Frequency: 5580 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5580$ MHz; $\sigma = 5.867$ S/m; $\epsilon_r = 46.892$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.8 °C; Liquid Temperature : 22.6 °C

DASY Configuration:

- Probe: EX3DV4 - SN3753; ConvF(4.27, 4.27, 4.27); Calibrated: 5/5/2017;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = -19.0, 23.0$
- Electronics: DAE4 Sn1305; Calibrated: 4/25/2017
- Phantom: ELI V5.0 (20deg probe tilt); Type: QD OVA 002 AA; Serial: 1240
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373)

Area Scan (9x34x1): Measurement grid: $dx=10$ mm, $dy=10$ mm

Maximum value of SAR (measured) = 2.02 W/kg


Zoom Scan (7x7x12)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=2$ mm

Reference Value = 3.374 V/m; Power Drift = -0.16 dB

Peak SAR (extrapolated) = 4.17 W/kg

SAR(1 g) = 1.05 W/kg; SAR(10 g) = 0.341 W/kg

Maximum value of SAR (measured) = 2.11 W/kg



P46 802.11a_Ch116_Right Side_0cm_Ant 1

DUT: Tablet;

Communication System: UID 0, WiFi (0); Frequency: 5580 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5580$ MHz; $\sigma = 5.867$ S/m; $\epsilon_r = 46.892$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.8 °C; Liquid Temperature : 22.6 °C

DASY Configuration:

- Probe: EX3DV4 - SN3753; ConvF(4.27, 4.27, 4.27); Calibrated: 5/5/2017;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = -19.0, 23.0$
- Electronics: DAE4 Sn1305; Calibrated: 4/25/2017
- Phantom: ELI V5.0 (20deg probe tilt); Type: QD OVA 002 AA; Serial: 1240
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373)

Area Scan (9x25x1): Measurement grid: $dx=10$ mm, $dy=10$ mm

Maximum value of SAR (measured) = 1.04 W/kg


Zoom Scan (7x7x12)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=2$ mm

Reference Value = 3.402 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 2.87 W/kg

SAR(1 g) = 0.739 W/kg; SAR(10 g) = 0.269 W/kg

Maximum value of SAR (measured) = 1.42 W/kg



P52 802.11a_Ch165_Top Face_0cm_Ant 0**DUT: Tablet;**


Communication System: UID 0, WiFi (0); Frequency: 5825 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 5825$ MHz; $\sigma = 6.24$ S/m; $\epsilon_r = 46.225$; $\rho = 1000$ kg/m³
Ambient Temperature : 22.7 °C; Liquid Temperature : 22.0 °C

DASY Configuration:

- Probe: EX3DV4 - SN3753; ConvF(4.52, 4.52, 4.52); Calibrated: 5/5/2017;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = -19.0, 23.0$
- Electronics: DAE4 Sn1305; Calibrated: 4/25/2017
- Phantom: ELI V5.0 (20deg probe tilt); Type: QD OVA 002 AA; Serial: 1240
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373)

Area Scan (9x34x1): Measurement grid: $dx=10$ mm, $dy=10$ mm
Maximum value of SAR (measured) = 2.31 W/kg

Zoom Scan (7x7x12)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=2$ mm
Reference Value = 6.726 V/m; Power Drift = -0.17 dB
Peak SAR (extrapolated) = 4.68 W/kg
SAR(1 g) = 1.1 W/kg; SAR(10 g) = 0.368 W/kg
Maximum value of SAR (measured) = 2.39 W/kg



P102 802.11a_Ch161_Right Side_0cm_Ant 1

DUT: Tablet;

Communication System: UID 0, WiFi (0); Frequency: 5805 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 5805$ MHz; $\sigma = 6.24$ S/m; $\epsilon_r = 46.286$; $\rho = 1000$ kg/m³
Ambient Temperature : 22.7 °C; Liquid Temperature : 22.0 °C

DASY Configuration:

- Probe: EX3DV4 - SN3753; ConvF(4.52, 4.52, 4.52); Calibrated: 5/5/2017;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = -19.0, 23.0$
- Electronics: DAE4 Sn1305; Calibrated: 4/25/2017
- Phantom: ELI V5.0 (20deg probe tilt); Type: QD OVA 002 AA; Serial: 1240
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7373)

Area Scan (10x25x1): Measurement grid: $dx=10$ mm, $dy=10$ mm
Maximum value of SAR (measured) = 1.93 W/kg

Zoom Scan (7x7x12)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=2$ mm
Reference Value = 4.845 V/m; Power Drift = 0.01 dB
Peak SAR (extrapolated) = 3.93 W/kg
SAR(1 g) = 1.04 W/kg; SAR(10 g) = 0.438 W/kg
Maximum value of SAR (measured) = 1.98 W/kg

