

FCC ID: MBPCLOUD3700F-001

Test Report # 4035-1  
Dated: 5/26/2014

# Intentional Radiator Test Report

Test Standards:  
FCC Part 15.225 (Subpart C – Intentional Radiators)  
Industry Canada RSS-210, Issue 8

Prepared For:  
Identive Group, Inc.  
1900 Carnegie Ave, Bldg B  
Santa Ana, CA 92705

Product Name :  
Contactless RFID Smartcard Reader


Model Name :  
CLOUD 3700F

Application Purpose : Original

Prepared by:

EMCE Engineering, Inc.  
44366 S. Grimmer Blvd.  
Fremont, CA 94538  
USA

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the EMCE Engineering, Inc.




FCC ID: MBPCLOUD3700F-001

Test Report # 4035-1  
Dated: 5/26/2014


## **Revision History**

| Rev. | Issue Date | Description   |
|------|------------|---------------|
| 0    | 5/26/2014  | Initial Issue |



## TABLE OF CONTENTS

|                                         |           |
|-----------------------------------------|-----------|
| <b>1. GENERAL INFORMATION</b>           | <b>4</b>  |
| <b>2. EUT AND ACCESSORY INFORMATION</b> | <b>5</b>  |
| <b>3. SUMMARY OF TEST RESULTS</b>       | <b>6</b>  |
| <b>4. MODIFICATIONS</b>                 | <b>7</b>  |
| <b>5. TEST RESULTS</b>                  | <b>8</b>  |
| <b>6. TEST EQUIPMENT</b>                | <b>27</b> |




## 1.0 GENERAL INFORMATION

|                              |                                                                                                                                                                                                                           |
|------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Laboratory:             | EMCE Engineering<br>44366 S. Grimmer Blvd.<br>Fremont, CA 94538<br>USA<br>Tel: 510-490-4307, Fax: 510-490-3441<br>bob@universalcompliance.com<br>FCC registration number : 743299<br>Test Site : FCC : US5291, IC : 3324A |
| Applicant Name :             | Identive Group, Inc.<br>1900 Carnegie Ave, Bldg B<br>Santa Ana, CA 92705<br>Tel: 925-217-3257<br>Contact Person: Robert Poddar                                                                                            |
| Application Purpose :        | Original                                                                                                                                                                                                                  |
| EUT Description              | RFID                                                                                                                                                                                                                      |
| Product Name                 | Contactless RFID Smartcard Reader                                                                                                                                                                                         |
| Model Name :                 | CLOUD 3700F                                                                                                                                                                                                               |
| Applied Standards :          | 47 CFR §15.207, 15.209, 15.225: 2010 &<br>Canadian Standards RSS-GEN Issue 3, RSS-210 Issue 8                                                                                                                             |
| FCC ID :                     | MBPCLOUD 3700F-001                                                                                                                                                                                                        |
| IC :                         | 7485A-CLOUD 3700F-001                                                                                                                                                                                                     |
| RF Operating Frequency (ies) | 13.56MHz                                                                                                                                                                                                                  |
| Modulation                   | ASK                                                                                                                                                                                                                       |
| Emission Designator          | 13K6K1D                                                                                                                                                                                                                   |
| Receipt of EUT :             | 4/10/14                                                                                                                                                                                                                   |
| Date of Testing :            | 4/10/14 – 5/21/14                                                                                                                                                                                                         |
| Date of Report :             | 5/26/14                                                                                                                                                                                                                   |

The tests listed in this report have been completed to demonstrate compliance to the CFR 47 Section 15.225, as well as Industry Canada Radio Standard RSS-210, Issue 8.


Contents approved:

|                                                                                     |
|-------------------------------------------------------------------------------------|
|  |
| Name: Bob Cole<br>Title: President                                                  |



## 2.0 EUT AND ACCESSORY INFORMATION


| EUT               |                                   |                            |                |                           |
|-------------------|-----------------------------------|----------------------------|----------------|---------------------------|
| Model name:       | CLOUD 3700F                       |                            |                |                           |
| Description:      | Contactless RFID Smartcard Reader |                            |                |                           |
| Manufacturer:     | Identive Group, Inc.              |                            |                |                           |
| Support Equipment |                                   |                            |                |                           |
| Description       | Model Number                      | Serial Number              | Manufacturer   | Power Cable Description   |
| Netbook PC        | Acer Aspire                       | NUSH6AA0012410<br>25337600 | Acer           | Unshielded /<br>1.5 Meter |
|                   |                                   |                            |                |                           |
|                   |                                   |                            |                |                           |
|                   |                                   |                            |                |                           |
| Cable Description |                                   |                            |                |                           |
| From              | To                                | Length (Meters)            | Shielded (Y/N) | Ferrite Loaded (Y/N)      |
| EUT               | Netbook                           | 0.5                        | Y              | N                         |



### 3.0 SUMMARY OF TEST RESULTS

| Test Standard                                                                                     |                 | Description                                                      | Pass / Fail |
|---------------------------------------------------------------------------------------------------|-----------------|------------------------------------------------------------------|-------------|
| 47 CFR Part 15.225: 2010                                                                          | RSS 210 Issue 8 |                                                                  |             |
| 15.203                                                                                            |                 | Antenna Requirement                                              | Pass        |
| 15.207(a)                                                                                         | RSS Gen(7.2.2)  | Conducted Emissions Voltage                                      | Pass        |
| 15.225(a)                                                                                         | RSS210(A2.6)    | Limit in the band of 13.553 – 13.567 MHz                         | Pass        |
| 15.225(b)                                                                                         | RSS210(A2.6)    | Limit in the band of 13.410 – 13.553 MHz and 13.567 – 13.710 MHz | Pass        |
| 15.225(c)                                                                                         | RSS210(A2.6)    | Limit in the band of 13.110 – 13.410 MHz and 13.710 – 14.010 MHz | Pass        |
| 15.225(d), 15.209                                                                                 | RSS210(A2.6)    | Limit outside the band of 13.110 – 14.010 MHz                    | Pass        |
| 15.225(e)                                                                                         | RSS210(A2.6)    | Frequency Stability                                              | Pass        |
|                                                                                                   | RSS-210(5.9.1)  | Occupied Bandwidth                                               | Pass        |
| ANSI C63.4: 2009/ RSS-Gen Issue 3                                                                 |                 |                                                                  |             |
| PS: All measurement uncertainties are not taken into consideration for all presented test result. |                 |                                                                  |             |

PASS      The EUT passed that particular test.  
FAIL      The EUT failed that particular test.  
008      Not Applicable due to product type.




FCC ID: MBPCLOUD3700F-001

Test Report # 4035-1  
Dated: 5/26/2014

## 4.0 MODIFICATIONS

There were no modifications.



## 5.0 TEST RESULTS


### 5.1 Antenna Requirement

**Requirement(s):** 47 CFR §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Antenna requirement must meet at least one of the following:

- a) Antenna must be permanently attached to the device.
  - b) Antenna must use a unique type of connector to attach to the device.
  - c) Device must be professionally installed. Installer shall be responsible for ensuring that the correct antenna is employed with the device.
- 
- 1) The RFID antenna is integral to the main board permanently to the device which meets the requirement (See Internal Photographs submitted as another Exhibit).



## 5.2 Conducted Emissions Voltage

Requirement(s): 47 CFR §15.207

Requirement:

| Frequency of emission (MHz) | Conducted limit (dBμV) |           |
|-----------------------------|------------------------|-----------|
|                             | Quasi-peak             | Average   |
| 0.15–0.5                    | 66 to 56*              | 56 to 46* |
| 0.5–5                       | 56                     | 46        |
| 5–30                        | 60                     | 50        |

\*Decreases with the logarithm of the frequency.


### Procedures:

1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR and Average detectors, are reported. All other emissions were relatively insignificant.
2. "Ave" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
3. Conducted Emissions Measurement Uncertainty  
All test measurements carried out are traceable to national standards. The uncertainty of measurement at a confidence level of approximately 95% (in the case where distributions normal), with a coverage factor of 2, in the range 9kHz – 30MHz (Average & Quasi-peak) ±3.5dB.
4. Environmental Conditions      Temperature      24°C  
                                                 Relative Humidity      45%  
                                                 Atmospheric Pressure      1010mbar

Test Date : 4/13/2014

Tested By : Bob Cole

**Results:** Pass



FCC ID: MBPCLOUD3700F-001

Test Report # 4035-1  
Dated: 5/26/2014

**FCC Part 15.207 Line Conducted Emissions**  
**120V / 60 Hz - Line 1**  
**150kHz – 30 MHz**

Test Location: EMCE Engineering • 44366 S. Grimmer Blvd • Fremont, CA 94538 •

Customer: **Identiv GmbH**  
Specification: **EN55022 B COND [QP]**  
Work Order #: **4031**  
Test Type: **Conducted Emissions**  
Equipment: **RFID USB Smartcard Reader**  
Manufacturer: **Identiv GmbH**  
Model: **CLOUD 3700F**  
S/N: **008**

Date: 4/13/2014  
Time: 2:35:33 PM  
Sequence#: 3  
Tested By: Bob Cole  
120V/600Hz

**Test Equipment:**

| Function                           | S/N             | Calibration Date | Cal Due Date | Asset # |
|------------------------------------|-----------------|------------------|--------------|---------|
| EMITest<br>Measurement<br>Software | v4.01 Build 195 | 05/01/2012       | 05/01/2014   | 610     |
| HP 8566B Spectrum<br>Analyzer      | 3014A06947      | 05/02/2012       | 05/02/2014   | 598     |
| HP 85650A Quasi<br>Peak Adapter    | 3145A01673      | 05/02/2013       | 05/02/2014   | 003     |
| EMCO 3810-2 LISN                   | 4576            | 05/17/2012       | 05/17/2014   | 007     |

**Equipment Under Test (\* = EUT):**

| Function                      | Manufacturer | Model #     | S/N |
|-------------------------------|--------------|-------------|-----|
| RFID USB Smartcard<br>Reader* | Identiv GmbH | CLOUD 3700F | 008 |

**Support Devices:**

| Function  | Manufacturer | Model #            | S/N                        |
|-----------|--------------|--------------------|----------------------------|
| Laptop PC | Acer         | Aspire One725-0687 | NUSH6AA0012410253376<br>00 |


**Test Conditions / Notes:**

Host Laptop Acer Aspire One725-0687  
EUT USB Cable connected to LEFT side of Lap Top  
NO Ferrite on EUT USB Cable

**Transducer Legend:**

|                 |                                   |
|-----------------|-----------------------------------|
| T1=25' LMR #001 | T2=EMCO 3810-2 LISN S/N 9807-1988 |
|-----------------|-----------------------------------|

Ext Attn: 0 dB



FCC ID: MBPCLOUD3700F-001

Test Report # 4035-1  
Dated: 5/26/2014


**Measurement Data:**


Reading listed by margin.

Test Lead: Line 1

| # | Freq<br>MHz | Rdng<br>dBμV | T1<br>dB | T2<br>dB |  | Dist<br>dB | Table | Corr<br>dBμV | Spec<br>dBμV | Margin<br>dB | Polar<br>Ant |
|---|-------------|--------------|----------|----------|--|------------|-------|--------------|--------------|--------------|--------------|
| 1 | 614.098k    | 39.0         | +0.0     | +0.7     |  |            | +0.0  | 39.7         | 56.0         | -16.3        | Line         |
| 2 | 151.358k    | 46.1         | +0.0     | +1.1     |  |            | +0.0  | 47.2         | 65.9         | -18.7        | Line         |
| 3 | 863.068k    | 36.1         | +0.0     | +0.5     |  |            | +0.0  | 36.6         | 56.0         | -19.4        | Line         |
| 4 | 1.053M      | 32.4         | +0.0     | +0.5     |  |            | +0.0  | 32.9         | 56.0         | -23.1        | Line         |
| 5 | 673.351k    | 32.1         | +0.0     | +0.6     |  |            | +0.0  | 32.7         | 56.0         | -23.3        | Line         |
| 6 | 682.771k    | 32.1         | +0.0     | +0.6     |  |            | +0.0  | 32.7         | 56.0         | -23.3        | Line         |

EMCE Engineering Date: 4/13/2014 Time: 2:15:32 PM Identive, Inc. WO#: 4031  
EN55022 B COND [QP] Test Lead: Line 1 120V 60Hz Sequence#: 1 Ext ATTN: 0 dB





FCC ID: MBPCLOUD3700F-001

Test Report # 4035-1  
Dated: 5/26/2014

**FCC Part 15.207 Line Conducted Emissions**  
**120V / 60 Hz - Line 2**  
**150kHz – 30 MHz**

Test Location: EMCE Engineering • 44366 S. Grimmer Blvd • Fremont, CA 94538 •

Customer: **Identiv GmbH**  
Specification: **EN55022 B COND [QP]**Work Order #: **4031**

Date: 4/13/2014

Test Type: **Conducted Emissions**

Time: 2:24:18 PM

Equipment: **RFID USB Smartcard Reader**

Sequence#: 2

Manufacturer: Identiv GmbH

Tested By: Bob Cole

Model: CLOUD 3700F

120V 60Hz

S/N: 008

**Test Equipment:**

| Function                     | S/N             | Calibration Date | Cal Due Date | Asset # |
|------------------------------|-----------------|------------------|--------------|---------|
| EMITest Measurement Software | v4.01 Build 195 | 05/01/2012       | 05/01/2014   | 610     |
| HP 8566B Spectrum Analyzer   | 3014A06947      | 05/02/2012       | 05/02/2014   | 598     |
| HP 85650A Quasi Peak Adapter | 3145A01673      | 05/02/2013       | 05/02/2014   | 003     |
| EMCO 3810-2 LISN             | 4576            | 05/17/2012       | 05/17/2014   | 007     |

**Equipment Under Test (\* = EUT):**

| Function                   | Manufacturer | Model #     | S/N |
|----------------------------|--------------|-------------|-----|
| RFID USB Smartcard Reader* | Identiv GmbH | CLOUD 3700F | 008 |

**Support Devices:**

| Function  | Manufacturer | Model #            | S/N                    |
|-----------|--------------|--------------------|------------------------|
| Laptop PC | Acer         | Aspire One725-0687 | NUSH6AA001241025337600 |


**Test Conditions / Notes:**

Host Laptop Acer Aspire One725-0687  
EUT USB Cable connected to LEFT side of Lap Top  
NO Ferrite on EUT USB Cable

**Transducer Legend:**

T1=25' LMR #001 T2=EMCO 3810-2 LISN S/N 9807-1988

Ext Attn: 0 dB




FCC ID: MBPCLOUD3700F-001


Test Report # 4035-1  
Dated: 5/26/2014**Measurement Data:** Reading listed by margin.

Test Lead: Line 2

| # | Freq<br>MHz | Rdng<br>dB $\mu$ V | T1<br>dB | T2<br>dB | dB | dB | Dist<br>Table | Corr<br>dB $\mu$ V | Spec<br>dB $\mu$ V | Margin<br>dB | Polar<br>Ant |
|---|-------------|--------------------|----------|----------|----|----|---------------|--------------------|--------------------|--------------|--------------|
| 1 | 594.949k    | 38.8               | +0.0     | +0.7     |    |    | +0.0          | 39.5               | 56.0               | -16.5        | Line         |
| 2 | 863.068k    | 38.1               | +0.0     | +0.5     |    |    | +0.0          | 38.6               | 56.0               | -17.4        | Line         |
| 3 | 176.304k    | 46.1               | +0.0     | +1.1     |    |    | +0.0          | 47.2               | 64.7               | -17.5        | Line         |
| 4 | 150.339k    | 46.7               | +0.0     | +1.1     |    |    | +0.0          | 47.8               | 66.0               | -18.2        | Line         |
| 5 | 704.345k    | 32.0               | +0.0     | +0.6     |    |    | +0.0          | 32.6               | 56.0               | -23.4        | Line         |
| 6 | 1.453M      | 31.9               | +0.0     | +0.6     |    |    | +0.0          | 32.5               | 56.0               | -23.5        | Line         |

EMCE Engineering Date: 4/13/2014 Time: 2:24:18 PM Identive, Inc. WO#: 4031  
EN55022 B COND [QP] Test Lead: Line 2 120V 60Hz Sequence#: 2 Ext ATTN: 0 dB





### 5.3 Radiated Emission < 30MHz (9kHz - 30MHz, H-Field)

**Requirement(s):** 47 CFR §15.225 & RSS-210 (A2.6) & RSS-310 (3.7)

**Procedures:** For < 30MHz, Radiated emissions were measured according to ANSI C63.4. The EUT was set to transmit at the highest output power. The EUT was set 3 meter away from the measuring antenna. The loop antenna was positioned 1 meter above the ground from the centre of the loop. The measuring bandwidth was set to 10 kHz. (Note: During testing the receive antenna was rotated about its axis to maximize the emission from the EUT.)

The limit is converted from microvolt/meter to decibel microvolt/meter.


**Sample Calculation:** Corrected Amplitude = Raw Amplitude (dBμV/m) + ACF (dB) + Cable Loss (dB) – Distance Correction Factor

1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR detectors, are reported. All other emissions were relatively insignificant.
2. A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
3. Radiated Emissions Measurement Uncertainty  
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, is +/-6dB.
4. Environmental Conditions      Temperature                      24°C  
                                                 Relative Humidity                      45%  
                                                 Atmospheric Pressure                      1010mbar

Test Date : 4/14/2014

Tested By : Bob Cole

**Results:** Pass



FCC ID: MBPCLOUD3700F-001

Test Report # 4035-1  
Dated: 5/26/2014

## FCC Part 15.209 Radiated Emissions 9 kHz – 30 MHz

Test Location: EMCE Engineering 44366 S. Grimmer Blvd Fremont, CA 94538

Customer: **Identiv GmbH**  
Specification: **15.209 9k-30M FCC Limits 10M**  
Work Order #: **4031**  
Test Type: **Radiated Scan**  
Equipment: **Contact/Contactless Card Reader**  
Manufacturer: Identiv GmbH  
Model: Cloud 4000  
S/N: 008

Date: 4/14/2014  
Time: 9:18:45 AM  
Sequence#: 1  
Tested By: Bob Cole

**Test Equipment:**

| Function                     | S/N             | Calibration Date | Cal Due Date | Asset # |
|------------------------------|-----------------|------------------|--------------|---------|
| HP 8593EM                    | 3497A5703       | 05/01/2012       | 05/01/2014   | 609     |
| HP 8447D PreAmp              | 2443A03587      | 05/01/2013       | 05/01/2014   | 008     |
| Empire Devices Loop Antenna  | 000114          | 01/15/2014       | 01/15/2015   | 114     |
| EMITest Measurement Software | v4.01 Build 195 | 05/01/2012       | 05/01/2014   | 610     |

**Equipment Under Test (\* = EUT):**

| Function                  | Manufacturer | Model #     | S/N |
|---------------------------|--------------|-------------|-----|
| RFID USB Smartcard Reader | Identiv GmbH | CLOUD 3700F | 008 |

**Support Devices:**

| Function  | Manufacturer | Model #            | S/N                    |
|-----------|--------------|--------------------|------------------------|
| Laptop PC | Acer         | Aspire One725-0687 | NUSH6AA001241025337600 |


**Test Conditions / Notes:**

|                                             |
|---------------------------------------------|
| Host Laptop: Acer Aspire One725-0687        |
| EUT: CLOUD 3700F RFID USB Smart Card Reader |


**Transducer Legend:**


|                           |                 |
|---------------------------|-----------------|
| T1=8447 Pre-Amp Asset 377 | T2=25' LMR #001 |
| T3=LP-105 Loop Factors    |                 |

Ext Attn: 0 dB



Date: 4/14/2014 Time: 9:18:45 AM Identive, Inc. WO#: 4031  
15.209 9k-30M FCC Limits 10M Test Distance: 3 Meters Sequence#: 1 Ext ATTN: 0 dB





## 5.4 Radiated Emissions > 30 MHz (30MHz – 1 GHz, E-Field)

**Requirement(s):** 47 CFR §15.209; 47 CFR §15.225(d) & RSS-210 (A2.6)

**Procedures:** For > 30MHz, Radiated emissions were measured according to ANSI C63.4. The EUT was set to transmit at the highest output power. The EUT was set 10 meter away from the measuring antenna. The Log periodic antenna was positioned 1 meter above the ground from the centre of the antenna. The measuring bandwidth was set to 120 kHz. (Note: During testing the receive antenna was raised from 1~4 meters to maximize the emission from the EUT.)

The limit is converted from microvolt/meter to decibel microvolt/meter.


Sample Calculation: Corrected Amplitude = Raw Amplitude (dBμV/m) + ACF (dB) + Cable Loss(dB) – Distance Correction Factor

1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR detectors, are reported. All other emissions were relatively insignificant.
2. A “-ve” margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
3. Radiated Emissions Measurement Uncertainty  
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, is +/-6dB.
4. Environmental Conditions      Temperature                      24°C  
                                                 Relative Humidity                  45%  
                                                 Atmospheric Pressure              1010mbar

Test Date : 4/14/2014

Tested By : Bob Cole

**Results:** Pass



FCC ID: MBPCLOUD3700F-001

Test Report # 4035-1  
Dated: 5/26/2014

## FCC Part 15B Radiated Emissions 30 MHz – 1 GHz

Test Location: EMCE Engineering • 44366 S. Grimmer Blvd • Fremont, CA 94538 •

Customer: **Identiv GmbH**  
Specification: **EN55022B RADIATED**  
Work Order #: **4031**  
Test Type: **Maximized Emissions**  
Equipment: **RFID USB Smartcard Reader**  
Manufacturer: **Identiv GmbH**  
Model: **CLOUD 3700F**  
S/N: **008**

Date: 4/14/2014  
Time: 10:30:00  
Sequence#: 3  
Tested By: Bob Cole

**Test Equipment:**

| Function                     | S/N             | Calibration Date | Cal Due Date | Asset # |
|------------------------------|-----------------|------------------|--------------|---------|
| HP 8566B Spectrum Analyzer   | 3014A06947      | 05/02/2012       | 05/02/2014   | 598     |
| HP 85650A Quasi Peak Adapter | 3145A01673      | 05/02/2013       | 05/02/2014   | 003     |
| HP 8447D PreAmp              | 2443A03587      | 05/01/2013       | 05/01/2014   | 008     |
| Sunol Sciences JB6 Antenna   | 1090            | 08/14/2012       | 08/14/2014   | 701     |
| EMITest Measurement Software | v4.01 Build 195 | 05/01/2012       | 05/01/2014   | 610     |

**Equipment Under Test (\* = EUT):**

| Function                   | Manufacturer | Model #     | S/N |
|----------------------------|--------------|-------------|-----|
| RFID USB Smartcard Reader* | Identiv GmbH | CLOUD 3700F | 008 |

**Support Devices:**

| Function  | Manufacturer | Model #            | S/N                    |
|-----------|--------------|--------------------|------------------------|
| Laptop PC | Acer         | Aspire One725-0687 | NUSH6AA001241025337600 |


**Test Conditions / Notes:**

|                                             |
|---------------------------------------------|
| Host Laptop: Acer Aspire One725-0687        |
| EUT: CLOUD 3700F RFID USB Smart Card Reader |


**Transducer Legend:**

|                                   |                              |
|-----------------------------------|------------------------------|
| T1=8447 Pre-Amp Asset 377         | T2=Sunol JB6 S/N A42610 2012 |
| T3=100' LMR 900 Rad Cable 12-2013 |                              |

Ext Attn: 0 dB




| <b>Measurement Data:</b> |             | Reading listed by margin. |          |          |          |    | Test Distance: 10 Meters |                |                |              |              |
|--------------------------|-------------|---------------------------|----------|----------|----------|----|--------------------------|----------------|----------------|--------------|--------------|
| #                        | Freq<br>MHz | Rdng<br>dBµV              | T1<br>dB | T2<br>dB | T3<br>dB | dB | Dist<br>Table            | Corr<br>dBµV/m | Spec<br>dBµV/m | Margin<br>dB | Polar<br>Ant |
| 1                        | 54.361M     | 42.5                      | +26.8    | +7.8     | +0.0     |    | +0.0                     | 23.5           | 30.0           | -6.5         | Vert         |
|                          | QP          |                           |          |          |          |    | 250                      |                |                |              | 140          |
| ^                        | 54.359M     | 48.6                      | +26.8    | +7.8     | +0.0     |    | +0.0                     | 29.6           | 30.0           | -0.4         | Vert         |
|                          |             |                           |          |          |          |    | 250                      |                |                |              | 140          |
| 3                        | 125.978M    | 36.1                      | +26.7    | +14.2    | -0.1     |    | +0.0                     | 23.5           | 30.0           | -6.5         | Vert         |
| 4                        | 216.945M    | 38.1                      | +26.9    | +11.7    | +0.2     |    | +0.0                     | 23.1           | 30.0           | -6.9         | Horiz        |
| 5                        | 118.276M    | 36.7                      | +26.7    | +13.0    | -0.1     |    | +0.0                     | 22.9           | 30.0           | -7.1         | Vert         |
|                          |             |                           |          |          |          |    | 109                      |                |                |              | 152          |
| 6                        | 129.012M    | 35.4                      | +26.7    | +14.1    | -0.1     |    | +0.0                     | 22.7           | 30.0           | -7.3         | Vert         |
|                          |             |                           |          |          |          |    | 153                      |                |                |              | 162          |
| 7                        | 328.500M    | 40.9                      | +27.0    | +15.0    | +0.5     |    | +0.0                     | 29.4           | 37.0           | -7.6         | Vert         |
|                          |             |                           |          |          |          |    | 142                      |                |                |              | 109          |
| 8                        | 54.349M     | 41.4                      | +26.8    | +7.8     | +0.0     |    | +0.0                     | 22.4           | 30.0           | -7.6         | Horiz        |
| 9                        | 108.473M    | 37.6                      | +26.8    | +10.9    | +0.0     |    | +0.0                     | 21.7           | 30.0           | -8.3         | Vert         |
|                          |             |                           |          |          |          |    | 214                      |                |                |              | 103          |
| 10                       | 332.410M    | 37.7                      | +27.0    | +15.1    | +0.5     |    | +0.0                     | 26.3           | 37.0           | -10.7        | Vert         |
|                          | QP          |                           |          |          |          |    | 140                      |                |                |              | 115          |
| ^                        | 332.413M    | 42.5                      | +27.0    | +15.1    | +0.5     |    | +0.0                     | 31.1           | 37.0           | -5.9         | Vert         |
|                          |             |                           |          |          |          |    | 140                      |                |                |              | 115          |
| 12                       | 280.482M    | 34.2                      | +27.0    | +13.9    | +0.4     |    | +0.0                     | 21.5           | 37.0           | -15.5        | Horiz        |
| 13                       | 275.347M    | 33.9                      | +27.0    | +13.8    | +0.4     |    | +0.0                     | 21.1           | 37.0           | -15.9        | Horiz        |
| 14                       | 81.402M     | 33.3                      | +27.0    | +7.4     | -0.1     |    | +0.0                     | 13.6           | 30.0           | -16.4        | Horiz        |




FCC ID: MBPCLOUD3700F-001

Test Report # 4035-1  
Dated: 5/26/2014

EMCE Engineering Date: 4/14/2014 Time: 10:30:00 Identive, Inc. WO#: 4031  
EN55022B RADIATED Test Distance: 10 Meters Sequence#: 3 Ext ATTN: 0 dB





## 5.5 Frequency Stability

**Requirement(s):** 47 CFR §15.225(e) & RSS-210 (A2.6)

**Procedures:** Frequency Stability was measured according to 47 CFR §2.1055. Measurement was taken with spectrum analyzer. The spectrum analyzer bandwidth and span was set to read in hertz. A voltmeter was used to monitor when varying the voltage.

Limit:  $\pm 0.01\%$  of 13.5589 MHz = 1355 Hz

|                          |                      |          |
|--------------------------|----------------------|----------|
| Environmental Conditions | Temperature          | 24°C     |
|                          | Relative Humidity    | 45%      |
|                          | Atmospheric Pressure | 1010mbar |

Test Date : 4/17/2014


Tested By : Bob Cole

**Results:** Pass

**Frequency Stability versus Temperature:** The Frequency tolerance of the carrier signal shall be maintained within  $\pm 0.01\%$  of the operating frequency over a temperature variation of -20°C to +50°C at normal supply voltage.

Reference Frequency: 13.559948 MHz at -20°C and +50°C


| Temperature (°C) | Measured Freq. (MHz)  | Freq. Drift (Hz) | Freq. Deviation (Limit: 0.01%) | Pass/Fail |
|------------------|-----------------------|------------------|--------------------------------|-----------|
| 50               | 13.559829             | 119              | <0.01                          | Pass      |
| 40               | 13.559874             | 74               | <0.01                          | Pass      |
| 30               | 13.559888             | 60               | <0.01                          | Pass      |
| 20               | Reference (13.56 MHz) |                  |                                |           |
| 10               | 13.559982             | 34               | <0.01                          | Pass      |
| 0                | 13.559982             | 34               | <0.01                          | Pass      |
| -10              | 13.559910             | 37               | <0.01                          | Pass      |
| -20              | 13.559877             | 71               | <0.01                          | Pass      |



**Frequency Stability versus Input Voltage:** The Frequency tolerance of the carrier signal shall be maintained within  $\pm 0.01\%$ , the frequency of the transmitter was measured at 85% and at 115% of the rated power supply voltage at 20°C environmental temperature.

Carrier Frequency: 13.55489 MHz at 20°C at 5VDC

| Measured Voltage $\pm 15\%$ of nominal (DC) | Measured Freq. (MHz) | Freq. Drift (Hz) | Freq. Deviation (Limit: 0.01%) | Pass/Fail |
|---------------------------------------------|----------------------|------------------|--------------------------------|-----------|
| 4.25                                        | 13.559492            | 3                | <0.01                          | Pass      |
| 5.75                                        | 13.559494            | 6                | <0.01                          | Pass      |



## 5.6 Fundamental Field Strength Test Result

1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR detectors, are reported. All other emissions were relatively insignificant.
2. A “-ve” margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
3. Radiated Emissions Measurement Uncertainty  
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, is +/-6dB.
4. Environmental Conditions      Temperature                      24°C  
                                                 Relative Humidity                      45%  
                                                 Atmospheric Pressure                      1010mbar


Test Date : 4/13/2014

Tested By : Bob Cole

### Test Requirement:

13.56MHz

- (a) The field strength of any emissions within the band 13.553–13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.
- (b) Within the bands 13.410–13.553 MHz and 13.567–13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.
- (c) Within the bands 13.110–13.410 MHz and 13.710–14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.



FCC ID: MBPCLOUD3700F-001

Test Report # 4035-1  
Dated: 5/26/2014

## Peak Output Power Per CFR 47, Section 15.225 and RSS-210 Issue 8 A2.6

Test Location: EMCE Engineering • 44366 S. Grimmer Blvd • Fremont, CA 94538 •

Customer: **Identiv GmbH**  
Specification: **RFID FCC Mask 3 Meter**  
Work Order #: **4031**  
Test Type: **Radiated Scan**  
Equipment: **RFID USB Smartcard Reader**  
Manufacturer: Identiv GmbH  
Model: CLOUD 3700F  
S/N: 008

Date: 4/13/2014  
Time: 3:05:45 PM  
Sequence#: 1  
Tested By: Bob Cole

### Test Equipment:

| Function                    | S/N        | Calibration Date | Cal Due Date | Asset # |
|-----------------------------|------------|------------------|--------------|---------|
| HP 8593EM                   | 3497A5703  | 02/17/2012       | 02/17/2014   | 609     |
| HP 8447D PreAmp             | 2443A03587 | 05/01/2013       | 05/01/2014   | 008     |
| Empire Devices Loop Antenna | 000114     | 01/15/2014       | 01/15/2015   | 114     |

### Equipment Under Test (\* = EUT):

| Function                   | Manufacturer | Model #     | S/N |
|----------------------------|--------------|-------------|-----|
| RFID USB Smartcard Reader* | Identiv GmbH | CLOUD 3700F | 008 |

### Support Devices:

| Function  | Manufacturer | Model #            | S/N                    |
|-----------|--------------|--------------------|------------------------|
| Laptop PC | Acer         | Aspire One725-0687 | NUSH6AA001241025337600 |


### Test Conditions / Notes:

Host Laptop: Aspire One725-0687  
EUT: CLOUD 3700F RFID USB Smart Card Reader

### Transducer Legend:

T1=25' LMR #001  
T2=8447 Pre-Amp Asset 377  
T3=LP-105 Loop Factors


Ext Attn: 0 dB




FCC ID: MBPCLOUD3700F-001

Test Report # 4035-1  
Dated: 5/26/2014

EMCE Engineering Date: 4/13/2014 Time: 3:05:45 PM Identive, Inc. WO#: 4031  
RFID FCC Mask 3 Meter Test Distance: 3 Meters Sequence#: 1 Ext ATTN: 0 dB



| Frequency (MHz) | Corrected Amplitude Reading (dBuV/m @ 3M) |
|-----------------|-------------------------------------------|
| 13.558          | 60.3                                      |



## 5.7 Occupied Bandwidth

**Requirement(s):** RSS-210 (5.9.1)

**Procedures:** Occupied Bandwidth was measured according to RSS-210 (5.9.1). Measurement was taken with spectrum analyzer. The spectrum analyzer bandwidth and span was set to read in hertz.


|                          |                      |          |
|--------------------------|----------------------|----------|
| Environmental Conditions | Temperature          | 24°C     |
|                          | Relative Humidity    | 45%      |
|                          | Atmospheric Pressure | 1010mbar |


Test Date : 5/21/2014

Tested By : Bob Cole

**Results:** Pass

| Frequency   | Occupied Bandwidth (99%) |
|-------------|--------------------------|
| 13.5589 MHz | 13.60 KHz                |





## 6.0 TEST EQUIPMENT

| DESCRIPTION & MANUFACTURER                      | MODEL NO.       | SERIAL NO.  | CAL. DATE | CAL. DUE DATE |
|-------------------------------------------------|-----------------|-------------|-----------|---------------|
| Spectrum Analyzer<br>Hewlett-Packard            | 8566B           | 3014A06947  | 5/2/12    | 5/2/14        |
| Quasi-Peak Adapter<br>Hewlett-Packard           | 85650A          | 3145A01673  | 5/2/13    | 5/2/15        |
| EMI Analyzer System<br>Hewlett-Packard          | 8593EM          | 3497A5703   | 5/17/12   | 5/17/14       |
| Signal Analyzer<br>Rohde-Schwarz                | FSV7            | 1321.3008K7 | 3/10/14   | 3/10/16       |
| HP 84125 EMI Measurement<br>System              | 84125B          | US36432003  | 5/1 /13   | 5/1/15        |
| Pre-Amplifier(100KHz-1.3GHz)<br>Hewlett-Packard | 8447D           | 2443A03587  | 5/1/13    | 5/1/15        |
| LISN(9KHz-30MHz)<br>EMCO                        | 3810-2          | 9807-1988   | 5/17/12   | 5/17/14       |
| LISN(9KHz-30MHz)<br>EMCO                        | 3810-2          | 4576        | 5/17/12   | 5/17/14       |
| BiConiLog Antenna<br>Sunol Sciences             | JB6             | 1090        | 8/14/12   | 8/14/14       |
| Loop Antenna<br>Empire Devices                  | LP105           | 000114      | 1/15/14   | 1/15/16       |
| Webber<br>Temperature Chamber                   | WE4-100-<br>200 | 3-60-32     | 8/15/13   | 8/15/15       |
| RF Signal Cable<br>Murata                       | 25' LMR         | N/A         | 5/10 /13  | 5/10 /15      |
| RF Signal Cable<br>EMCE                         | 100' LMR        | N/A         | 5/1 /13   | 5/1 /15       |