

PACT

Versatile & Cost effective Physical Access Terminals

US Headquarters
SCM Microsystems Inc.
466 Kato Terrace
Fremont, CA 94539 USA
email: adapter@scmmicro.com
Phone +1 510 360 2300
Fax +1 510 360 0211

European Headquarters
SCM Microsystems GmbH
Oskar-Messter-Str. 13
D-85737 Ismaning, Germany
email: sales@scmmicro.de
Phone +49 89 9595 5000
Fax +49 89 9595 5555

SCM Microsystems Japan, Inc.
8F Hirakawacho Ronstate, 2-11-1,
Hirakawa-cho, Chiyoda-ku,
Tokyo, Japan 102-0093
email: sales@scmmicro.co.jp
Phone +81 3 3511 8511
Fax +81 3 3511 8516

SCM Microsystems GmbH
ZE Athélie II
216, avenue du Serpolet
13704 La Ciotat Cedex - France
email: sales@scmmicro.fr
Phone +33 442 838 000
Fax +33 442 838 001

SCM Microsystems (Asia) Pte. Ltd.
25 Serangoon North Ave 5
#06-00 Keppel DigiHub
Singapore 554914
email: sales@scmmicro.com.sg
Phone +65 6551 5233
Fax +65 6483 0210

SCM Microsystems India Pvt. Ltd.
Module No. 0506, 0507 & 0508
D' Block South, 5th Floor
Tidel Park, 4 Canal Bank Road
Taramani
Chennai 600113, India
email: sales@scmmicro.co.in
Phone +91 44 2254 0020
Fax +91 44 2254 0029



Technical Data

Host Interface	• Wiegand / Mag Stripe (CLK/Data) • RS485 (2 or 4 wires) • 3 Relay inputs to set reader state
Smart Card Interface	• T=0, T=1 protocol support (5V card) • Communication speed up to 115,200 bps
Smart Card Connector	• 8 contacts - ISO location • Landing contact, 500,000 insertions
Contactless	• ISO14443 Type A and B (13.56MHz) • Support ISO14443 Part 1 to 4 • Operating distance: 1 inch • Communication speed: 424 Kbps • Internal 3DES for card authentication (DESFire)
Keypad	• Standard telephone layout (0-9, clear, enter) • Robust hard cap, silicon keypad
Human Interface	• 1 LED beam (green and red) for access information (granted or denied) • 1 LED per type of media (contact, contactless, PINPAD) to indicate the type of requested operation • Buzzer for user acoustic feedback
Application	• Full SDK available • Field Secure firmware upgrade
Operating Temperature	• Indoor: 0° to 50° Celsius • Outdoor: -25° to 65° Celsius
Operating Humidity	• Indoor: 20% to 90% RH non-condensing • Outdoor: 5% to 95% RH non-condensing
Dimensions	• LVH 148 x 84 x 46 mm • Mounting - fits into a single junction box
Power	• 12V DC - 400 mA
Approvals	• FCC Class B part 15, UL, CE

Overview

Leveraging proven experience in smart card and connectivity technologies, SCM Microsystems introduces a new product family dedicated to physical access.

To date SCM Microsystems has shipped several million smart card readers world wide to major enterprises, financial institutions and government agencies (over one million units to the US Department of Defense alone).

Taking advantage of this unique position and experience, SCM Microsystems is now introducing a new concept of versatile and cost effective physical access terminals.

PACT Benefits

- Designed and constructed to provide a wide variety of configuration options
- The same reader can be used with both Wiegand / Mag Stripe and RS485
- The same reader supports contact and contactless with or without PINPAD
- Flexible SDK allowing integrators to develop their own applications and differentiate themselves
- The SDK together with the on-board flash allow seamless reconfiguration of the reader and prevent obsolescence

The SCM Microsystems' Advantage

SCM Microsystems brings over a decade of experience in ASIC and smart card reader development to this unique product, including:

- More than 80 patents
- Support for all current and emerging international standards
- Customer base of global, top tier PC OEMs, systems integrators and smart card industry leaders
- Industry endorsed SmartOS™ middleware
- Direct significant long-term relationships with all leading smart card manufacturers and application providers
- High quality mass production capability



SCM
MICROSYSTEMS
www.scmmicro.com

PACT

Indoor & Outdoor



Contactless



Contactless/PINPAD

Indoor



Contact/PINPAD



Contact/Contactless/PINPAD

	Wiegand / Mag Stripe RS485	Optional SAM	Indoor	Outdoor
CL	●	●	●	●
CL/Pinpad	●	●	●	●
CT/CL/Pinpad	● ⁽¹⁾		●	
CT/Pinpad	● ⁽¹⁾		●	

CL: contactless smart card (ISO14443)

CT: contact smart card (ISO7816)

Note 1: contact card is only available with RS485

Please contact your local SCM Microsystems representative for availability and details.

