



11be(EHT320)_Puncturing_RU_(996+2x996)_TX_CH_31_Vertical_Peak



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5886.4	41.08	34.16	-16.84	58.40	88.20	29.80	Vertical
2	5921.24	46.66	34.26	-16.88	64.05	88.20	24.15	Vertical




11be(EHT320)_Puncturing_RU_(996+2x996)_TX_CH_31_Vertical_Average




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5897.32	26.98	34.19	-16.82	44.36	68.20	23.84	Vertical
2	5916.56	28.29	34.25	-16.86	45.68	68.20	22.52	Vertical

11be(EHT320)_Puncturing_RU_(996+2x996)_TX_CH_191_Horizontal_Peak



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7133.76	42.34	36.30	-17.50	61.14	88.20	27.06	Horizontal
2	7168.86	42.48	36.30	-17.70	61.08	88.20	27.12	Horizontal


11be(EHT320)_Puncturing_RU_(996+2x996)_TX_CH_191_Horizontal_Average



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7135.92	30.45	36.30	-17.51	49.24	68.20	18.96	Horizontal
2	7143.48	29.82	36.30	-17.56	48.56	68.20	19.64	Horizontal




11be(EHT320)_Puncturing_RU_(996+2x996)_TX_CH_191_Vertical_Peak



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7133.76	46.64	36.30	-17.50	65.44	88.20	22.76	Vertical
2	7152.12	48.61	36.30	-17.61	67.30	88.20	20.90	Vertical


11be(EHT320)_Puncturing_RU_(996+2x996)_TX_CH_191_Vertical_Average



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7134.84	34.12	36.30	-17.51	52.91	68.20	15.29	Vertical
2	7141.86	33.80	36.30	-17.55	52.55	68.20	15.65	Vertical




11be(EHT320)_Puncturing_RU_(484+2x996)_TX_CH_31_Horizontal_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5905.64	38.68	34.22	-16.83	56.07	88.20	32.13	Horizontal
2	5921.76	38.99	34.27	-16.88	56.38	88.20	31.82	Horizontal

11be(EHT320)_Puncturing_RU_(484+2x996)_TX_CH_31_Horizontal_Average




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5884.32	26.01	34.15	-16.84	43.32	68.20	24.88	Horizontal
2	5916.04	27.24	34.25	-16.86	44.63	68.20	23.57	Horizontal

11be(EHT320)_Puncturing_RU_(484+2x996)_TX_CH_31_Vertical_Peak



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5899.4	42.57	34.20	-16.81	59.96	88.20	28.24	Vertical
2	5918.12	42.37	34.25	-16.87	59.76	88.20	28.44	Vertical


11be(EHT320)_Puncturing_RU_(484+2x996)_TX_CH_31_Vertical_Average



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5896.8	27.87	34.19	-16.82	45.24	68.20	22.96	Vertical
2	5916.56	29.12	34.25	-16.86	46.51	68.20	21.69	Vertical




11be(EHT320)_Puncturing_RU_(484+2x996)_TX_CH_191_Horizontal_Peak



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7135.92	42.81	36.30	-17.51	61.60	88.20	26.60	Horizontal
2	7151.04	44.37	36.30	-17.60	63.07	88.20	25.13	Horizontal




11be(EHT320)_Puncturing_RU_(484+2x996)_TX_CH_191_Horizontal_Average



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7135.38	33.21	36.30	-17.51	52.00	68.20	16.20	Horizontal
2	7156.98	32.57	36.30	-17.63	51.24	68.20	16.96	Horizontal




11be(EHT320)_Puncturing_RU_(484+2x996)_TX_CH_191_Vertical_Peak



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7132.14	46.60	36.30	-17.49	65.41	88.20	22.79	Vertical
2	7139.7	46.13	36.30	-17.54	64.89	88.20	23.31	Vertical



11be(EHT320)_Puncturing_RU_(484+2x996)_TX_CH_191_Veritical_Average



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7132.68	35.78	36.30	-17.50	54.58	68.20	13.62	Vertical
2	7156.44	35.05	36.30	-17.63	53.72	68.20	14.48	Vertical



7.5 In-Band Emissions

Test Requirement 47 CFR Part 15, Subpart E 15.407 (b)

Test Method: ANSI C63.10 (2020) Section 12.6

Limit:

For transmitters operating within the 5.925–7.125 GHz bands: Power spectral density must be suppressed by 20 dB at 1 MHz outside of channel edge, by 28 dB at one channel bandwidth from the channel center, and by 40 dB at one- and one-half times the channel bandwidth away from channel center. At frequencies between one megahertz outside an unlicensed device's channel edge and one channel bandwidth from the center of the channel, the limits must be linearly interpolated between 20 dB and 28 dB suppression, and at frequencies between one and one- and one-half times an unlicensed device's channel bandwidth, the limits must be linearly interpolated between 28 dB and 40 dB suppression. Emissions removed from the channel center by more than one- and one-half times the channel bandwidth must be suppressed by at least 40 dB.

7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 20.4 °C


Humidity: 52.2 % RH

Atmospheric Pressure: 1001 mbar

7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	09	TX mode (U-NII-5) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	10	TX mode (U-NII-6) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	11	TX mode (U-NII-7) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	12	TX mode (U-NII-8) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.

7.5.3 Test Setup Diagram



7.5.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.6 Contention-based Protocol

Test Requirement 47 CFR Part 15, Subpart E 15.407 (d)(6)

Test Method: KDB 987594 D02

Limit:

Unlicensed low-power indoor devices must detect co-channel radio frequency power that is at least -62 dBm or lower. Upon detection of energy in the band, unlicensed low power indoor devices must vacate the channel (in which incumbent signal is transmitted) and stay off the incumbent channel as long as detected radio frequency power is equal to or greater than the threshold (-62 dBm). The -62 dBm (or lower) threshold is referenced to a 0 dBi antenna gain. To ensure incumbent operations are reliably detected in the band, low power indoor devices must detect RF energy throughout their intended operating channel. For example, an 802.11 device that plans to transmit a 40 MHz- wide signal (on a primary 20 MHz channel and a secondary 20 MHz channel) must detect energy throughout the entire 40 MHz channel. Additionally, low-power indoor devices must detect co-channel energy with 90% or greater certainty.

7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 20.4 °C


Humidity: 52.2 % RH

Atmospheric Pressure: 1001 mbar

7.6.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	05	Normal operating_Keep the EUT communication with the companion device.

7.6.3 Test Setup Diagram



7.6.4 Measurement Procedure and Data

Detection Level= Injected AWGN Power(dBm)- Antenna Gain(dBi)+ Path Loss(dB)

Please Refer to Appendix for Details

7.7 Duty Cycle

Test Requirement ANSI C63.10 (2020) Section 12.2

Test Method: ANSI C63.10 (2020) Section 12.2

7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 20.4 °C


Humidity: 52.2 % RH

Atmospheric Pressure: 1001 mbar

7.7.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	09	TX mode (U-NII-5) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	10	TX mode (U-NII-6) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	11	TX mode (U-NII-7) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	12	TX mode (U-NII-8) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.

7.7.3 Test Setup Diagram



7.7.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.8 99% Bandwidth

Test Requirement ANSI C63.10 (2020) Section 12.5.3

Test Method: ANSI C63.10 (2020) Section 12.5.3

7.8.1 E.U.T. Operation

Operating Environment:

Temperature: 20.4 °C


Humidity: 52.2 % RH

Atmospheric Pressure: 1001 mbar

7.8.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	09	TX mode (U-NII-5) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	10	TX mode (U-NII-6) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	11	TX mode (U-NII-7) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	12	TX mode (U-NII-8) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.

7.8.3 Test Setup Diagram



7.8.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.9 26dB Emission bandwidth

Test Requirement 47 CFR Part 15, Subpart E 15.407 (a)

Test Method: ANSI C63.10 (2020) Section 12.5.2

7.9.1 E.U.T. Operation

Operating Environment:

Temperature: 20.4 °C


Humidity: 52.2 % RH

Atmospheric Pressure: 1001 mbar

7.9.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	09	TX mode (U-NII-5) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	10	TX mode (U-NII-6) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	11	TX mode (U-NII-7) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	12	TX mode (U-NII-8) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.

7.9.3 Test Setup Diagram



7.9.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.10 Maximum Conducted output power

Test Requirement 47 CFR Part 15, Subpart E 15.407 (a)

Test Method: ANSI C63.10 (2020) Section 12.4

Limit:

Device Type	Frequency Range (MHz)	EIRP Limit (dBm)	EIRP PSD Limit(dBm/MHz)
LPI AP/ Subordinate	5925-7125	≤ 30	≤ 5
LPI Client Device And Dual Client controlled by LPI AP/ Subordinate	5925-7125	≤ 24	≤ -1
Dual Client controlled by Standard Power AP	5925-6425; 6525-6875	30 max & 6dB below Std. AP	17 max & 6dB below Std. AP
Standard Power AP And Fixed Client Devices	5925-6425; 6525-6875	≤ 36 (21dBm for elevation angle greater than 30 degrees above the horizon)	≤ 23
Standard Client Devices	5925-6425; 6525-6875	30 max & 6dB below Std. AP	17 max & 6dB below Std. AP
Very Low-Power Devices	5925-6425; 6525-6875	≤ 14	≤ -5 shall demonstrate the TPC capability to operate at least 6 dB below the maximum EIRP PSD value of -5 dBm/MHz.

7.10.1 E.U.T. Operation

Operating Environment:

Temperature: 20.4 °C


Humidity: 52.2 % RH

Atmospheric Pressure: 1001 mbar

7.10.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	09	TX mode (U-NII-5) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	10	TX mode (U-NII-6) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	11	TX mode (U-NII-7) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	12	TX mode (U-NII-8) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.

7.10.3 Test Setup Diagram



7.10.4 Measurement Procedure and Data

Note: Since the verify power the same operating range bandwidth and smaller power can be covered by the higher power.

AV Output power Level = Reading level + Cable loss + DCCF

Please Refer to Appendix for Details

7.11 Peak Power spectrum density

Test Requirement 47 CFR Part 15, Subpart E 15.407 (a)

Test Method: ANSI C63.10 (2020) Section 12.6

Limit:

Device Type	Frequency Range (MHz)	EIRP Limit (dBm)	EIRP PSD Limit(dBm/MHz)
LPI AP/ Subordinate	5925-7125	≤ 30	≤ 5
LPI Client Device And Dual Client controlled by LPI AP/ Subordinate	5925-7125	≤ 24	≤ -1
Dual Client controlled by Standard Power AP	5925-6425; 6525-6875	30 max & 6dB below Std. AP	17 max & 6dB below Std. AP
Standard Power AP And Fixed Client Devices	5925-6425; 6525-6875	≤ 36 (21dBm for elevation angle greater than 30 degrees above the horizon)	≤ 23
Standard Client Devices	5925-6425; 6525-6875	30 max & 6dB below Std. AP	17 max & 6dB below Std. AP
Very Low-Power Devices	5925-6425; 6525-6875	≤ 14	≤ -5 shall demonstrate the TPC capability to operate at least 6 dB below the maximum EIRP PSD value of -5 dBm/MHz.

7.11.1 E.U.T. Operation

Operating Environment:

Temperature: 20.4 °C


Humidity: 52.2 % RH

Atmospheric Pressure: 1001 mbar

7.11.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	09	TX mode (U-NII-5) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	10	TX mode (U-NII-6) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	11	TX mode (U-NII-7) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	12	TX mode (U-NII-8) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.

7.11.3 Test Setup Diagram



7.11.4 Measurement Procedure and Data

RBW conversion factor from 300kHz to 500kHz (2.22dB) for UNII Band 3 has been considered.

Please Refer to Appendix for Details



Report No.: SUCR251000101104

Page: 275 of 921

8 Test Setup Photo

Refer to Appendix - Test Setup Photo for WLAN

9 EUT Constructional Details (EUT Photos)

Refer to Appendix - External Photos for SUCR2510001011MO and Appendix - Internal Photos for SUCR2510001011MO



10 Appendix

WIFI 7:

1. Duty Cycle

1.1 Test Result

1.1.1 Ant1

Ant1										
ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
NTNV	802.11be (EHT20)	MIMO	5955	SU	/	5.453	5.643	96.63	0.15	2.17
	802.11be (EHT40)	MIMO	5965	SU	/	5.452	5.642	96.63	0.15	0.76
	802.11be (EHT80)	MIMO	5985	SU	/	5.452	5.634	96.77	0.14	2.07
	802.11be (EHT160)	MIMO	6025	SU	/	5.452	5.634	96.77	0.14	2.21
	802.11be (EHT320)	MIMO	6105	SU	/	5.456	5.472	99.71	0.01	0.04



2. Bandwidth

2.1 Test Result

2.1.1 OBW

ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	99% Occupied Bandwidth (MHz)		Verdict
							Result	Limit	
NTNV	802.11be (EHT20)	MIMO	5955	SU	/	1	19.388	<=320	Pass
			6175	SU	/	1	19.403	<=320	Pass
			6415	SU	/	1	19.399	<=320	Pass
	802.11be (EHT40)	MIMO	5965	SU	/	1	38.516	<=320	Pass
			6165	SU	/	1	38.529	<=320	Pass
			6405	SU	/	1	38.734	<=320	Pass
	802.11be (EHT80)	MIMO	5985	SU	/	1	78.352	<=320	Pass
			6145	SU	/	1	78.704	<=320	Pass
			6385	SU	/	1	78.598	<=320	Pass
	802.11be (EHT160)	MIMO	6025	SU	/	1	157.528	<=320	Pass
			6185	SU	/	1	158.084	<=320	Pass
			6345	SU	/	1	158.126	<=320	Pass
	802.11be (EHT320)	MIMO	6105	SU	/	1	315.687	<=320	Pass
			6265	SU	/	1	315.334	<=320	Pass

2.1.2 26dB BW

ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	26dB Bandwidth (MHz)		Verdict
							Result	Limit	
NTNV	802.11be (EHT20)	MIMO	5955	SU	/	1	23.271	/	Pass
			6175	SU	/	1	23.671	/	Pass
			6415	SU	/	1	22.462	/	Pass
	802.11be (EHT40)	MIMO	5965	SU	/	1	43.367	/	Pass
			6165	SU	/	1	43.156	/	Pass
			6405	SU	/	1	43.430	/	Pass
	802.11be (EHT80)	MIMO	5985	SU	/	1	86.971	/	Pass
			6145	SU	/	1	89.896	/	Pass
			6385	SU	/	1	87.238	/	Pass
	802.11be (EHT160)	MIMO	6025	SU	/	1	172.798	/	Pass
			6185	SU	/	1	174.968	/	Pass
			6345	SU	/	1	172.122	/	Pass
	802.11be (EHT320)	MIMO	6105	SU	/	1	338.320	/	Pass
			6265	SU	/	1	340.237	/	Pass

2.1.3 OBW

ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	99% Occupied Bandwidth (MHz)		Verdict
							Result	Limit	
NTNV	802.11be	MIMO	6435	SU	/	1	19.331	<=320	Pass



	(EHT20)		6475	SU	/	1	19.396	<=320	Pass
			6515	SU	/	1	19.358	<=320	Pass
	802.11be (EHT40)	MIMO	6445	SU	/	1	38.489	<=320	Pass
			6485	SU	/	1	38.554	<=320	Pass
	802.11be (EHT80)	MIMO	6465	SU	/	1	78.798	<=320	Pass

2.1.4 26dB BW

ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	26dB Bandwidth (MHz)		Verdict
							Result	Limit	
NTNV	802.11be (EHT20)	MIMO	6435	SU	/	1	22.483	/	Pass
			6475	SU	/	1	22.817	/	Pass
			6515	SU	/	1	22.809	/	Pass
	802.11be (EHT40)	MIMO	6445	SU	/	1	43.771	/	Pass
			6485	SU	/	1	44.303	/	Pass
	802.11be (EHT80)	MIMO	6465	SU	/	1	87.476	/	Pass

2.1.5 OBW

ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	99% Occupied Bandwidth (MHz)		Verdict
							Result	Limit	
NTNV	802.11be (EHT20)	MIMO	6535	SU	/	1	19.377	<=320	Pass
			6695	SU	/	1	19.357	<=320	Pass
			6855	SU	/	1	19.404	<=320	Pass
	802.11be (EHT40)	MIMO	6565	SU	/	1	38.508	<=320	Pass
			6685	SU	/	1	38.512	<=320	Pass
			6845	SU	/	1	38.569	<=320	Pass
	802.11be (EHT80)	MIMO	6625	SU	/	1	78.844	<=320	Pass
			6705	SU	/	1	78.549	<=320	Pass
			6785	SU	/	1	78.605	<=320	Pass
	802.11be (EHT160)	MIMO	6665	SU	/	1	158.377	<=320	Pass

2.1.6 26dB BW

ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	26dB Bandwidth (MHz)		Verdict
							Result	Limit	
NTNV	802.11be (EHT20)	MIMO	6535	SU	/	1	22.937	/	Pass
			6695	SU	/	1	22.833	/	Pass
			6855	SU	/	1	23.119	/	Pass
	802.11be (EHT40)	MIMO	6565	SU	/	1	44.536	/	Pass
			6685	SU	/	1	44.073	/	Pass
			6845	SU	/	1	43.555	/	Pass
	802.11be (EHT80)	MIMO	6625	SU	/	1	89.830	/	Pass
			6705	SU	/	1	88.676	/	Pass
			6785	SU	/	1	89.489	/	Pass
	802.11be	MIMO	6665	SU	/	1	170.292	/	Pass



	(EHT160)								
--	----------	--	--	--	--	--	--	--	--

2.1.7 OBW

ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	99% Occupied Bandwidth (MHz)		Verdict
							Result	Limit	
NTNV	802.11be (EHT20)	MIMO	6895	SU	/	1	19.388	<=320	Pass
			6995	SU	/	1	19.373	<=320	Pass
			7115	SU	/	1	19.388	<=320	Pass
	802.11be (EHT40)	MIMO	6925	SU	/	1	38.633	<=320	Pass
			7005	SU	/	1	38.680	<=320	Pass
			7085	SU	/	1	38.633	<=320	Pass
	802.11be (EHT80)	MIMO	6945	SU	/	1	78.688	<=320	Pass
			7025	SU	/	1	78.692	<=320	Pass
	802.11be (EHT160)	MIMO	6985	SU	/	1	158.201	<=320	Pass

2.1.8 26dB BW

ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	26dB Bandwidth (MHz)		Verdict
							Result	Limit	
NTNV	802.11be (EHT20)	MIMO	6895	SU	/	1	22.820	/	Pass
			6995	SU	/	1	22.253	/	Pass
			7115	SU	/	1	22.681	/	Pass
	802.11be (EHT40)	MIMO	6925	SU	/	1	43.947	/	Pass
			7005	SU	/	1	43.533	/	Pass
			7085	SU	/	1	43.829	/	Pass
	802.11be (EHT80)	MIMO	6945	SU	/	1	89.385	/	Pass
			7025	SU	/	1	89.596	/	Pass
	802.11be (EHT160)	MIMO	6985	SU	/	1	171.566	/	Pass

2.1.9 OBW

ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	99% Occupied Bandwidth (MHz)		Verdict
							Result	Limit	
NTNV	802.11be (EHT20)	MIMO	6875	SU	/	1	19.434	<=320	Pass
	802.11be (EHT40)	MIMO	6885	SU	/	1	38.707	<=320	Pass
	802.11be (EHT80)	MIMO	6865	SU	/	1	78.855	<=320	Pass
	802.11be (EHT160)	MIMO	6825	SU	/	1	157.926	<=320	Pass
	802.11be (EHT320)	MIMO	6745	SU	/	1	317.528	<=320	Pass
			6905	SU	/	1	314.738	<=320	Pass

2.1.10 26dB BW

ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	26dB Bandwidth (MHz)		Verdict
							Result	Limit	
NTNV	802.11be (EHT20)	MIMO	6875	SU	/	1	22.981	/	Pass
	802.11be (EHT40)	MIMO	6885	SU	/	1	43.962	/	Pass
	802.11be (EHT80)	MIMO	6865	SU	/	1	89.112	/	Pass
	802.11be (EHT160)	MIMO	6825	SU	/	1	170.629	/	Pass
	802.11be (EHT320)	MIMO	6745	SU	/	1	338.824	/	Pass
			6905	SU	/	1	337.573	/	Pass

2.1.11 OBW

ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	99% Occupied Bandwidth (MHz)		Verdict
							Result	Limit	
NTNV	802.11be (EHT40)	MIMO	6525	SU	/	1	38.539	<=320	Pass
	802.11be (EHT80)	MIMO	6545	SU	/	1	78.586	<=320	Pass
	802.11be (EHT160)	MIMO	6505	SU	/	1	157.897	<=320	Pass
	802.11be (EHT320)	MIMO	6585	SU	/	1	318.498	<=320	Pass

2.1.12 26dB BW

ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	26dB Bandwidth (MHz)		Verdict
							Result	Limit	
NTNV	802.11be (EHT40)	MIMO	6525	SU	/	1	42.981	/	Pass
	802.11be (EHT80)	MIMO	6545	SU	/	1	88.382	/	Pass
	802.11be (EHT160)	MIMO	6505	SU	/	1	175.211	/	Pass
	802.11be (EHT320)	MIMO	6585	SU	/	1	549.389	/	Pass

2.1.13 OBW

ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	99% Occupied Bandwidth (MHz)		Verdict
							Result	Limit	
NTNV	802.11be (EHT320)	MIMO	6425	SU	/	1	315.725	<=320	Pass

2.1.14 26dB BW

ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	26dB Bandwidth (MHz)		Verdict
							Result	Limit	




Report No.: SUCR251000101104

Page: 281 of 921


NTNV	802.11be (EHT320)	MIMO	6425	SU	/	1	337.541	/	Pass
------	----------------------	------	------	----	---	---	---------	---	------

2.2 Test Graph


2.2.1 OBW




802.11be(EHT20) HCH 6415MHz SU / Ant1 NTN




802.11be(EHT40) LCH 5965MHz SU / Ant1 NTN




802.11be(EHT40) MCH 6165MHz SU / Ant1 NTVN




802.11be(EHT40) HCH 6405MHz SU / Ant1 NTVN




802.11be(EHT80) LCH 5985MHz SU / Ant1_NTNV




802.11be(EHT80) MCH 6145MHz SU / Ant1_NTNV




802.11be(EHT80) HCH 6385MHz SU / Ant1 NTN




802.11be(EHT160) LCH 6025MHz SU / Ant1 NTN




802.11be(EHT160) MCH 6185MHz SU / Ant1 NTN




802.11be(EHT160) HCH 6345MHz SU / Ant1 NTN




802.11be(EHT320) LCH 6105MHz SU / Ant1 NTN




802.11be(EHT320) HCH 6265MHz SU / Ant1 NTN




2.2.2 26dB BW




802.11be(EHT20) HCH 6415MHz SU / Ant1 NTN




802.11be(EHT40) LCH 5965MHz SU / Ant1 NTN




802.11be(EHT40) MCH 6165MHz SU / Ant1 NTN




802.11be(EHT40) HCH 6405MHz SU / Ant1 NTN




802.11be(EHT80) LCH 5985MHz SU / Ant1_NTNV




802.11be(EHT80) MCH 6145MHz SU / Ant1_NTNV




802.11be(EHT80) HCH 6385MHz SU / Ant1 NTNV




802.11be(EHT160) LCH 6025MHz SU / Ant1 NTNV




802.11be(EHT160)_MCH_6185MHz_SU / Ant1_NTNV




802.11be(EHT160)_HCH_6345MHz_SU / Ant1_NTNV




802.11be(EHT320) LCH 6105MHz SU / Ant1 NTN




802.11be(EHT320) HCH 6265MHz SU / Ant1 NTN




2.2.3 OBW




802.11be(EHT20) HCH 6515MHz SU / Ant1 NTN




802.11be(EHT40) LCH 6445MHz SU / Ant1 NTN




802.11be(EHT40) MCH 6485MHz SU / Ant1 NTV




802.11be(EHT80) LCH 6465MHz SU / Ant1 NTV




2.2.4 26dB BW




802.11be(EHT20) HCH 6515MHz SU / Ant1 NTN




802.11be(EHT40) LCH 6445MHz SU / Ant1 NTN




802.11be(EHT40) MCH 6485MHz SU / Ant1 NTN




802.11be(EHT80) LCH 6465MHz SU / Ant1 NTN




2.2.5 OBW




802.11be(EHT20) HCH 6855MHz SU / Ant1 NTN




802.11be(EHT40) LCH 6565MHz SU / Ant1 NTN




802.11be(EHT40) MCH 6685MHz SU / Ant1 NTVN




802.11be(EHT40) HCH 6845MHz SU / Ant1 NTVN




802.11be(EHT80) LCH 6625MHz SU / Ant1_NTNV




802.11be(EHT80) MCH 6705MHz SU / Ant1_NTNV




802.11be(EHT80) HCH 6785MHz SU / Ant1 NTNV




802.11be(EHT160) MCH 6665MHz SU / Ant1 NTNV




2.2.6 26dB BW




802.11be(EHT20) HCH 6855MHz SU / Ant1 NTN




802.11be(EHT40) LCH 6565MHz SU / Ant1 NTN




802.11be(EHT40) MCH 6685MHz SU / Ant1 NTN




802.11be(EHT40) HCH 6845MHz SU / Ant1 NTN




802.11be(EHT80) LCH 6625MHz SU / Ant1_NTNV




802.11be(EHT80) MCH 6705MHz SU / Ant1_NTNV




802.11be(EHT80) HCH 6785MHz SU / Ant1 NTN




802.11be(EHT160) MCH 6665MHz SU / Ant1 NTN




2.2.7 OBW




802.11be(EHT20) HCH 7115MHz SU / Ant1 NTN




802.11be(EHT40) LCH 6925MHz SU / Ant1 NTN




802.11be(EHT40) MCH 7005MHz SU / Ant1 NTVN




802.11be(EHT40) HCH 7085MHz SU / Ant1 NTVN




802.11be(EHT80) LCH 6945MHz SU / Ant1_NTNV




802.11be(EHT80) HCH 7025MHz SU / Ant1_NTNV




802.11be(EHT160)_MCH_6985MHz_SU / _Ant1_NTNV




2.2.8 26dB BW




802.11be(EHT20) HCH 7115MHz SU / Ant1 NTN




802.11be(EHT40) LCH 6925MHz SU / Ant1 NTN




802.11be(EHT40) MCH 7005MHz SU / Ant1 NTN




802.11be(EHT40) HCH 7085MHz SU / Ant1 NTN




802.11be(EHT80) LCH 6945MHz SU / Ant1_NTNV




802.11be(EHT80) HCH 7025MHz SU / Ant1_NTNV




802.11be(EHT160)_MCH_6985MHz_SU / _Ant1_NTNV




2.2.9 OBW




802.11be(EHT80) HCH 6865MHz SU / Ant1 NTNV




802.11be(EHT160) HCH 6825MHz SU / Ant1 NTNV




802.11be(EHT320) LCH 6745MHz SU / Ant1 NTN




802.11be(EHT320) HCH 6905MHz SU / Ant1 NTN




2.2.10 26dB BW




802.11be(EHT80) HCH 6865MHz SU / Ant1 NTN




802.11be(EHT160) HCH 6825MHz SU / Ant1 NTN




802.11be(EHT320) LCH 6745MHz SU / Ant1 NTN




802.11be(EHT320) HCH 6905MHz SU / Ant1 NTN




2.2.11 OBW




802.11be(EHT160) HCH 6505MHz SU / Ant1 NTN




802.11be(EHT320) MCH 6585MHz SU / Ant1 NTN




2.2.12 26dB BW




802.11be(EHT160) HCH 6505MHz SU / Ant1 NTN




802.11be(EHT320) MCH 6585MHz SU / Ant1 NTN



2.2.13 OBW



2.2.14 26dB BW



3. Maximum Conducted Output Power

3.1 Test Result

3.1.1 Power

ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	Maximum Average Conducted Output Power (dBm)				Verdict
						ANT1	ANT2	MIMO	Limit	
NTNV	802.11be (EHT20)	MIMO	5955	SU	/	5.34	5.44	8.40	/	Pass
				RU26+52	/	0.86	0.87	3.88	/	Pass
				RU26+106	/	2.25	2.23	5.25	/	Pass
			6175	SU	/	5.01	5.00	8.02	/	Pass
				RU26+52	/	-0.44	-0.47	2.56	/	Pass
				RU26+106	/	1.53	1.50	4.53	/	Pass
			6415	SU	/	5.71	5.23	8.49	/	Pass
				RU26+52	/	0.59	0.48	3.55	/	Pass
				RU26+106	/	2.98	2.96	5.98	/	Pass
	802.11be (EHT40)	MIMO	5965	SU	/	7.94	7.14	10.57	/	Pass
			6165	SU	/	7.89	7.45	10.69	/	Pass
			6405	SU	/	8.17	7.68	10.94	/	Pass
	802.11be (EHT80)	MIMO	5985	SU	/	11.60	11.11	14.37	/	Pass
				RU242+484	/	9.78	9.78	12.79	/	Pass
				P-20M-RU242+484	/	9.89	9.88	12.90	/	Pass
			6145	SU	/	10.13	9.49	12.83	/	Pass
				RU242+484	/	8.73	8.72	11.74	/	Pass
				P-20M-RU242+484	/	8.75	8.76	11.77	/	Pass
			6385	SU	/	12.26	11.70	15.00	/	Pass
				RU242+484	/	9.23	9.72	12.49	/	Pass
				P-20M-RU242+484	/	9.71	9.69	12.71	/	Pass
	802.11be (EHT160)	MIMO	6025	SU	/	14.17	13.88	17.04	/	Pass
				RU484+996	/	11.09	11.11	14.11	/	Pass
				P-40M-RU484+996	/	11.11	11.12	14.13	/	Pass
			6185	SU	/	14.30	13.94	17.13	/	Pass
				RU484+996	/	11.20	11.15	14.19	/	Pass
				P-40M-RU484+996	/	11.15	11.15	14.16	/	Pass
			6345	SU	/	14.58	14.18	17.39	/	Pass
				RU484+996	/	11.52	11.51	14.53	/	Pass
				P-40M-RU484+996	/	11.50	11.52	14.52	/	Pass
	802.11be (EHT320)	MIMO	6105	RU996+2X996	/	14.32	14.39	17.37	/	Pass
				SU	/	15.21	14.77	18.01	/	Pass
				RU484+2X996	/	14.29	14.79	17.56	/	Pass
				P-80M-RU2X996+996	/	14.35	14.09	17.23	/	Pass
				P-80+40M-RU484+996+996	/	14.08	13.88	16.99	/	Pass
			6265	RU996+2X996	/	14.55	14.98	17.78	/	Pass
				SU	/	17.49	16.89	20.21	/	Pass
				RU484+2X996	/	14.87	14.60	17.75	/	Pass
				P-80M-RU2X996+996	/	14.68	14.99	17.85	/	Pass
				P-80+40M-RU484+996+996	/	14.60	14.42	17.52	/	Pass

3.1.2 EIRP

ENV	Mode	TX	Frequency	RU	RU	E.I.R.P (dBm)	Verdict
-----	------	----	-----------	----	----	---------------	---------

		Type	(MHz)		Pos	ANT1	ANT2	MIMO	Limit	
NTNV	802.11be (EHT20)	MIMO	5955	SU	/	9.64	9.64	12.70	<=30	Pass
				RU26+52	/	5.16	5.07	8.18	<=30	Pass
				RU26+106	/	6.55	6.43	9.55	<=30	Pass
			6175	SU	/	9.31	9.20	12.32	<=30	Pass
				RU26+52	/	3.86	3.73	6.86	<=30	Pass
				RU26+106	/	5.83	5.70	8.83	<=30	Pass
			6415	SU	/	10.01	9.43	12.79	<=30	Pass
				RU26+52	/	4.89	4.68	7.85	<=30	Pass
				RU26+106	/	7.28	7.16	10.28	<=30	Pass
	802.11be (EHT40)	MIMO	5965	SU	/	12.24	11.34	14.87	<=30	Pass
			6165	SU	/	12.19	11.65	14.99	<=30	Pass
			6405	SU	/	12.47	11.88	15.24	<=30	Pass
	802.11be (EHT80)	MIMO	5985	SU	/	15.90	15.31	18.67	<=30	Pass
				RU242+484	/	14.08	13.98	17.09	<=30	Pass
				P-20M-RU242+484	/	14.19	14.08	17.20	<=30	Pass
			6145	SU	/	14.43	13.69	17.13	<=30	Pass
				RU242+484	/	13.03	12.92	16.04	<=30	Pass
				P-20M-RU242+484	/	13.05	12.96	16.07	<=30	Pass
			6385	SU	/	16.56	15.90	19.30	<=30	Pass
				RU242+484	/	13.53	13.92	16.79	<=30	Pass
				P-20M-RU242+484	/	14.01	13.89	17.01	<=30	Pass
	802.11be (EHT160)	MIMO	6025	SU	/	18.47	18.08	21.34	<=30	Pass
				RU484+996	/	15.39	15.31	18.41	<=30	Pass
				P-40M-RU484+996	/	15.41	15.32	18.43	<=30	Pass
			6185	SU	/	18.60	18.14	21.43	<=30	Pass
				RU484+996	/	15.50	15.35	18.49	<=30	Pass
				P-40M-RU484+996	/	15.45	15.35	18.46	<=30	Pass
			6345	SU	/	18.88	18.38	21.69	<=30	Pass
				RU484+996	/	15.82	15.71	18.83	<=30	Pass
				P-40M-RU484+996	/	15.80	15.72	18.82	<=30	Pass
	802.11be (EHT320)	MIMO	6105	RU996+2X996	/	18.62	18.59	21.67	<=30	Pass
				SU	/	19.51	18.97	22.31	<=30	Pass
				RU484+2X996	/	18.59	18.99	21.86	<=30	Pass
			6265	P-80M-RU2X996+996	/	18.65	18.29	21.53	<=30	Pass
				P-80+40M-RU484+996+996	/	18.38	18.08	21.29	<=30	Pass
				RU996+2X996	/	18.85	19.18	22.08	<=30	Pass
			6265	SU	/	21.79	21.09	24.51	<=30	Pass
				RU484+2X996	/	19.17	18.80	22.05	<=30	Pass
				P-80M-RU2X996+996	/	18.98	19.19	22.15	<=30	Pass
				P-80+40M-RU484+996+996	/	18.90	18.62	21.82	<=30	Pass

3.1.3 Power

ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	Maximum Average Conducted Output Power (dBm)				Verdict
						ANT1	ANT2	MIMO	Limit	
NTNV	802.11be (EHT20)	MIMO	6435	SU	/	5.54	5.06	8.32	/	Pass
				RU26+52	/	0.50	0.52	3.52	/	Pass
				RU26+106	/	2.85	2.70	5.79	/	Pass
			6475	SU	/	5.64	5.15	8.41	/	Pass
				RU26+52	/	0.37	0.37	3.38	/	Pass
				RU26+106	/	2.73	2.68	5.72	/	Pass
			6515	SU	/	6.01	5.56	8.80	/	Pass
				RU26+52	/	0.70	0.70	3.71	/	Pass
				RU26+106	/	-1.02	-1.03	1.99	/	Pass

	802.11be (EHT40)	MIMO	6445	SU	/	8.14	7.77	10.97	/	Pass
			6485	SU	/	8.56	7.96	11.28	/	Pass
	802.11be (EHT80)	MIMO	6465	SU	/	12.24	11.78	15.03	/	Pass
				RU242+484	/	9.44	9.44	12.45	/	Pass
				P-20M-RU242+484	/	9.46	9.45	12.47	/	Pass

3.1.4 EIRP

ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	E.I.R.P (dBm)				Verdict
						ANT1	ANT2	MIMO	Limit	
NTNV	802.11be (EHT20)	MIMO	6435	SU	/	7.74	6.86	10.52	<=30	Pass
				RU26+52	/	2.70	2.32	5.72	<=30	Pass
				RU26+106	/	5.05	4.50	7.99	<=30	Pass
			6475	SU	/	7.84	6.95	10.61	<=30	Pass
				RU26+52	/	2.57	2.17	5.58	<=30	Pass
				RU26+106	/	4.93	4.48	7.92	<=30	Pass
			6515	SU	/	8.21	7.36	11.00	<=30	Pass
				RU26+52	/	2.90	2.50	5.91	<=30	Pass
				RU26+106	/	1.18	0.77	4.19	<=30	Pass
	802.11be (EHT40)	MIMO	6445	SU	/	10.34	9.57	13.17	<=30	Pass
			6485	SU	/	10.76	9.76	13.48	<=30	Pass
	802.11be (EHT80)	MIMO	6465	SU	/	14.44	13.58	17.23	<=30	Pass
				RU242+484	/	11.64	11.24	14.65	<=30	Pass
				P-20M-RU242+484	/	11.66	11.25	14.67	<=30	Pass

3.1.5 Power

ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	Maximum Average Conducted Output Power (dBm)				Verdict
						ANT1	ANT2	MIMO	Limit	
NTNV	802.11be (EHT20)	MIMO	6535	SU	/	6.00	5.51	8.77	/	Pass
				RU26+52	/	-1.09	-1.02	1.96	/	Pass
				RU26+106	/	2.39	2.40	5.41	/	Pass
			6695	SU	/	6.08	5.51	8.81	/	Pass
				RU26+52	/	0.23	0.23	3.24	/	Pass
				RU26+106	/	-0.15	-0.16	2.86	/	Pass
			6855	SU	/	5.38	4.90	8.16	/	Pass
				RU26+52	/	-0.69	-0.74	2.30	/	Pass
				RU26+106	/	-0.89	-0.87	2.13	/	Pass
	802.11be (EHT40)	MIMO	6565	SU	/	8.73	8.27	11.52	/	Pass
			6685	SU	/	8.70	8.17	11.45	/	Pass
			6845	SU	/	8.52	8.09	11.32	/	Pass
	802.11be (EHT80)	MIMO	6625	SU	/	11.91	11.53	14.73	/	Pass
				RU242+484	/	9.40	9.38	12.40	/	Pass
				P-20M-RU242+484	/	9.38	9.37	12.39	/	Pass
			6705	SU	/	11.91	11.41	14.68	/	Pass
				RU242+484	/	8.92	8.92	11.93	/	Pass
				P-20M-RU242+484	/	8.92	8.93	11.94	/	Pass
			6785	SU	/	11.75	11.19	14.49	/	Pass
				RU242+484	/	8.92	8.90	11.92	/	Pass
				P-20M-RU242+484	/	8.89	8.90	11.91	/	Pass
	802.11be (EHT160)	MIMO	6665	SU	/	14.81	14.33	17.59	/	Pass
				RU484+996	/	12.27	12.31	15.30	/	Pass
				P-40M-RU484+996	/	12.27	12.26	15.28	/	Pass

3.1.6 EIRP

ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	E.I.R.P (dBm)				Verdict
						ANT1	ANT2	MIMO	Limit	
NTNV	802.11be (EHT20)	MIMO	6535	SU	/	8.50	8.61	11.87	<=30	Pass
				RU26+52	/	1.41	2.08	5.06	<=30	Pass
				RU26+106	/	4.89	5.50	8.51	<=30	Pass
			6695	SU	/	8.58	8.61	11.91	<=30	Pass
				RU26+52	/	2.73	3.33	6.34	<=30	Pass
				RU26+106	/	2.35	2.94	5.96	<=30	Pass
			6855	SU	/	7.88	8.00	11.26	<=30	Pass
				RU26+52	/	1.81	2.36	5.40	<=30	Pass
				RU26+106	/	1.61	2.23	5.23	<=30	Pass
	802.11be (EHT40)	MIMO	6565	SU	/	11.23	11.37	14.62	<=30	Pass
			6685	SU	/	11.20	11.27	14.55	<=30	Pass
			6845	SU	/	11.02	11.19	14.42	<=30	Pass
	802.11be (EHT80)	MIMO	6625	SU	/	14.41	14.63	17.83	<=30	Pass
				RU242+484	/	11.90	12.48	15.50	<=30	Pass
				P-20M-RU242+484	/	11.88	12.47	15.49	<=30	Pass
			6705	SU	/	14.41	14.51	17.78	<=30	Pass
				RU242+484	/	11.42	12.02	15.03	<=30	Pass
				P-20M-RU242+484	/	11.42	12.03	15.04	<=30	Pass
			6785	SU	/	14.25	14.29	17.59	<=30	Pass
				RU242+484	/	11.42	12.00	15.02	<=30	Pass
				P-20M-RU242+484	/	11.39	12.00	15.01	<=30	Pass
	802.11be (EHT160)	MIMO	6665	SU	/	17.31	17.43	20.69	<=30	Pass
				RU484+996	/	14.77	15.41	18.40	<=30	Pass
				P-40M-RU484+996	/	14.77	15.36	18.38	<=30	Pass

3.1.7 Power

ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	Maximum Average Conducted Output Power (dBm)				Verdict
						ANT1	ANT2	MIMO	Limit	
NTNV	802.11be (EHT20)	MIMO	6895	SU	/	5.93	4.36	8.23	/	Pass
				RU26+52	/	0.15	0.17	3.17	/	Pass
				RU26+106	/	0.12	0.11	3.13	/	Pass
			6995	SU	/	5.82	5.31	8.58	/	Pass
				RU26+52	/	1.01	1.02	4.03	/	Pass
				RU26+106	/	1.49	1.52	4.52	/	Pass
			7115	SU	/	2.06	1.92	5.00	/	Pass
				RU26+52	/	-0.14	-0.14	2.87	/	Pass
				RU26+106	/	1.98	1.89	4.95	/	Pass
	802.11be (EHT40)	MIMO	6925	SU	/	8.64	7.95	11.32	/	Pass
			7005	SU	/	8.27	7.82	11.06	/	Pass
			7085	SU	/	8.17	7.62	10.91	/	Pass
	802.11be (EHT80)	MIMO	6945	SU	/	11.63	11.20	14.43	/	Pass
				RU242+484	/	9.18	9.18	12.19	/	Pass
				P-20M-RU242+484	/	9.17	9.19	12.19	/	Pass
			7025	SU	/	11.55	11.02	14.30	/	Pass
				RU242+484	/	9.04	8.99	12.03	/	Pass
				P-20M-RU242+484	/	8.98	8.97	11.99	/	Pass
	802.11be	MIMO	6985	SU	/	14.45	13.91	17.20	/	Pass

	(EHT160)			RU484+996	/	10.24	10.25	13.26	/	Pass
				P-40M-RU484+996	/	10.32	10.29	13.32	/	Pass

3.1.8 EIRP

ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	E.I.R.P (dBm)				Verdict
						ANT1	ANT2	MIMO	Limit	
NTNV	802.11be (EHT20)	MIMO	6895	SU	/	9.23	5.66	11.53	<=30	Pass
				RU26+52	/	3.45	1.47	6.47	<=30	Pass
				RU26+106	/	3.42	1.41	6.43	<=30	Pass
			6995	SU	/	9.12	6.61	11.88	<=30	Pass
				RU26+52	/	4.31	2.32	7.33	<=30	Pass
				RU26+106	/	4.79	2.82	7.82	<=30	Pass
			7115	SU	/	5.36	3.22	8.20	<=30	Pass
				RU26+52	/	3.16	1.16	6.17	<=30	Pass
				RU26+106	/	5.28	3.19	8.25	<=30	Pass
	802.11be (EHT40)	MIMO	6925	SU	/	11.94	9.25	14.62	<=30	Pass
			7005	SU	/	11.57	9.12	14.36	<=30	Pass
			7085	SU	/	11.47	8.92	14.21	<=30	Pass
	802.11be (EHT80)	MIMO	6945	SU	/	14.93	12.50	17.73	<=30	Pass
				RU242+484	/	12.48	10.48	15.49	<=30	Pass
				P-20M-RU242+484	/	12.47	10.49	15.49	<=30	Pass
			7025	SU	/	14.85	12.32	17.60	<=30	Pass
				RU242+484	/	12.34	10.29	15.33	<=30	Pass
				P-20M-RU242+484	/	12.28	10.27	15.29	<=30	Pass
	802.11be (EHT160)	MIMO	6985	SU	/	17.75	15.21	20.50	<=30	Pass
				RU484+996	/	13.54	11.55	16.56	<=30	Pass
				P-40M-RU484+996	/	13.62	11.59	16.62	<=30	Pass

3.1.9 Power

ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	Maximum Average Conducted Output Power (dBm)				Verdict
						ANT1	ANT2	MIMO	Limit	
NTNV	802.11be (EHT20)	MIMO	6875	SU	/	6.17	5.55	8.88	/	Pass
				RU26+52	/	0.51	0.52	3.53	/	Pass
				RU26+106	/	2.46	2.52	5.50	/	Pass
	802.11be (EHT40)	MIMO	6885	SU	/	8.30	7.77	11.05	/	Pass
				SU	/	11.90	11.36	14.65	/	Pass
	802.11be (EHT80)	MIMO	6865	RU242+484	/	9.97	9.95	12.97	/	Pass
				P-20M-RU242+484	/	9.97	9.96	12.98	/	Pass
				SU	/	14.22	13.66	16.96	/	Pass
	802.11be (EHT160)	MIMO	6825	RU484+996	/	11.91	11.97	14.95	/	Pass
				P-40M-RU484+996	/	11.96	11.96	14.97	/	Pass
				RU996+2X996	/	15.76	15.39	18.59	/	Pass
	802.11be (EHT320)	MIMO	6745	SU	/	16.76	16.35	19.57	/	Pass
				RU484+2X996	/	14.72	14.89	17.82	/	Pass
				P-80M-RU2X996+996	/	15.10	15.14	18.13	/	Pass
				P-80+40M-RU484+996+996	/	14.70	14.86	17.79	/	Pass
				RU996+2X996	/	13.16	13.56	16.37	/	Pass
			6905	SU	/	16.67	16.00	19.36	/	Pass
				RU484+2X996	/	13.77	13.98	16.89	/	Pass
				P-80M-RU2X996+996	/	13.51	13.00	16.27	/	Pass

				P-80+40M-RU484+996+996	/	13.67	13.66	16.68	/	Pass
--	--	--	--	------------------------	---	-------	-------	-------	---	------

3.1.10 EIRP

ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	E.I.R.P (dBm)				Verdict
						ANT1	ANT2	MIMO	Limit	
NTNV	802.11be (EHT20)	MIMO	6875	SU	/	9.47	6.85	12.18	<=30	Pass
				RU26+52	/	3.81	1.82	6.83	<=30	Pass
				RU26+106	/	5.76	3.82	8.80	<=30	Pass
	802.11be (EHT40)	MIMO	6885	SU	/	11.60	9.07	14.35	<=30	Pass
				SU	/	15.20	12.66	17.95	<=30	Pass
	802.11be (EHT80)	MIMO	6865	RU242+484	/	13.27	11.25	16.27	<=30	Pass
				P-20M-RU242+484	/	13.27	11.26	16.28	<=30	Pass
				SU	/	17.52	14.96	20.26	<=30	Pass
	802.11be (EHT160)	MIMO	6825	RU484+996	/	15.21	13.27	18.25	<=30	Pass
				P-40M-RU484+996	/	15.26	13.26	18.27	<=30	Pass
				RU996+2X996	/	19.06	16.69	21.89	<=30	Pass
	802.11be (EHT320)	MIMO	6745	SU	/	20.06	17.65	22.87	<=30	Pass
				RU484+2X996	/	18.02	16.19	21.12	<=30	Pass
				P-80M-RU2X996+996	/	18.40	16.44	21.43	<=30	Pass
				P-80+40M-RU484+996+996	/	18.00	16.16	21.09	<=30	Pass
			6905	RU996+2X996	/	16.46	14.86	19.67	<=30	Pass
				SU	/	19.97	17.30	22.66	<=30	Pass
				RU484+2X996	/	17.07	15.28	20.19	<=30	Pass
				P-80M-RU2X996+996	/	16.81	14.30	19.57	<=30	Pass
				P-80+40M-RU484+996+996	/	16.97	14.96	19.98	<=30	Pass

3.1.11 Power

ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	Maximum Average Conducted Output Power (dBm)				Verdict
						ANT1	ANT2	MIMO	Limit	
NTNV	802.11be (EHT40)	MIMO	6525	SU	/	8.63	8.09	11.38	/	Pass
	802.11be (EHT80)	MIMO	6545	SU	/	12.02	11.56	14.81	/	Pass
				RU242+484	/	10.56	10.56	13.57	/	Pass
				P-20M-RU242+484	/	10.56	10.57	13.58	/	Pass
	802.11be (EHT160)	MIMO	6505	SU	/	14.92	14.43	17.69	/	Pass
				RU484+996	/	12.58	12.59	15.60	/	Pass
				P-40M-RU484+996	/	12.56	12.54	15.56	/	Pass
	802.11be (EHT320)	MIMO	6585	RU996+2X996	/	15.47	15.50	18.50	/	Pass
				SU	/	17.29	16.88	20.10	/	Pass
				RU484+2X996	/	14.77	14.75	17.77	/	Pass
				P-80M-RU2X996+996	/	15.24	15.46	18.36	/	Pass
				P-80+40M-RU484+996+996	/	14.70	14.53	17.63	/	Pass

3.1.12 EIRP

ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	E.I.R.P (dBm)				Verdict
						ANT1	ANT2	MIMO	Limit	
NTNV	802.11be (EHT40)	MIMO	6525	SU	/	11.13	11.19	14.48	<=30	Pass

	802.11be (EHT80)	MIMO	6545	SU	/	14.52	14.66	17.91	<=30	Pass
				RU242+484	/	13.06	13.66	16.67	<=30	Pass
				P-20M-RU242+484	/	13.06	13.67	16.68	<=30	Pass
	802.11be (EHT160)	MIMO	6505	SU	/	17.42	17.53	20.79	<=30	Pass
				RU484+996	/	15.08	15.69	18.70	<=30	Pass
				P-40M-RU484+996	/	15.06	15.64	18.66	<=30	Pass
	802.11be (EHT320)	MIMO	6585	RU996+2X996	/	17.97	18.60	21.60	<=30	Pass
				SU	/	19.79	19.98	23.20	<=30	Pass
				RU484+2X996	/	17.27	17.85	20.87	<=30	Pass
				P-80M-RU2X996+996	/	17.74	18.56	21.46	<=30	Pass
				P-80+40M-RU484+996+996	/	17.20	17.63	20.73	<=30	Pass

3.1.13 Power

ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	Maximum Average Conducted Output Power (dBm)				Verdict
						ANT1	ANT2	MIMO	Limit	
NTNV	802.11be (EHT320)	MIMO	6425	RU996+2X996	/	15.21	14.85	18.04	/	Pass
				SU	/	17.07	16.59	19.85	/	Pass
				RU484+2X996	/	14.59	14.60	17.61	/	Pass
				P-80M-RU2X996+996	/	14.69	14.87	17.79	/	Pass
				P-80+40M-RU484+996+996	/	14.57	14.44	17.52	/	Pass

3.1.14 EIRP

ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	E.I.R.P (dBm)				Verdict
						ANT1	ANT2	MIMO	Limit	
NTNV	802.11be (EHT320)	MIMO	6425	RU996+2X996	/	17.71	17.95	21.14	<=30	Pass
				SU	/	19.57	19.69	22.95	<=30	Pass
				RU484+2X996	/	17.09	17.70	20.71	<=30	Pass
				P-80M-RU2X996+996	/	17.19	17.97	20.89	<=30	Pass
				P-80+40M-RU484+996+996	/	17.07	17.54	20.62	<=30	Pass

4. Maximum Power Spectral Density

4.1 Test Result

4.1.1 PSD

ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	Maximum PSD (dBm/MHz)				Verdict
						ANT1	ANT2	MIMO	Limit	
NTNV	802.11be (EHT20)	MIMO	5955	SU	/	-6.41	-5.90	-3.43	/	Pass
				RU26+52	/	-6.89	-6.88	-3.88	/	Pass
				RU26+106	/	-7.63	-7.56	-4.61	/	Pass
			6175	SU	/	-7.26	-7.27	-4.26	/	Pass
				RU26+52	/	-8.02	-7.97	-4.98	/	Pass
				RU26+106	/	-8.06	-8.11	-5.08	/	Pass
			6415	SU	/	-6.22	-6.47	-3.33	/	Pass
				RU26+52	/	-7.06	-7.00	-4.02	/	Pass
				RU26+106	/	-6.78	-6.79	-3.79	/	Pass
	802.11be (EHT40)	MIMO	5965	SU	/	-6.26	-6.95	-3.76	/	Pass
			6165	SU	/	-6.80	-7.24	-4.10	/	Pass
			6405	SU	/	-6.27	-6.73	-3.75	/	Pass
	802.11be (EHT80)	MIMO	5985	SU	/	-6.56	-6.98	-3.77	/	Pass
				RU242+484	/	-6.92	-6.90	-3.91	/	Pass
				P-20M-RU242+484	/	-6.82	-6.87	-3.87	/	Pass
			6145	SU	/	-6.61	-6.85	-3.72	/	Pass
				RU242+484	/	-8.00	-8.10	-5.09	/	Pass
				P-20M-RU242+484	/	-8.12	-8.12	-5.15	/	Pass
			6385	SU	/	-5.97	-6.55	-3.26	/	Pass
				RU242+484	/	-7.64	-7.11	-4.40	/	Pass
				P-20M-RU242+484	/	-7.15	-7.18	-4.17	/	Pass
	802.11be (EHT160)	MIMO	6025	SU	/	-6.84	-7.16	-4.00	/	Pass
				RU484+996	/	-7.45	-7.39	-4.47	/	Pass
				P-40M-RU484+996	/	-7.38	-7.43	-4.42	/	Pass
			6185	SU	/	-6.66	-7.11	-3.88	/	Pass
				RU484+996	/	-8.07	-8.27	-5.23	/	Pass
				P-40M-RU484+996	/	-8.22	-8.20	-5.26	/	Pass
			6345	SU	/	-6.64	-7.01	-3.81	/	Pass
				RU484+996	/	-7.95	-7.98	-4.99	/	Pass
				P-40M-RU484+996	/	-7.92	-7.91	-4.95	/	Pass
	802.11be (EHT320)	MIMO	6105	RU996+2X996	/	-7.76	-7.29	-4.68	/	Pass
				SU	/	-5.60	-8.65	-3.85	/	Pass
				RU484+2X996	/	-6.68	-6.94	-3.88	/	Pass
				P-80M-RU2X996+996	/	-7.87	-7.76	-5.25	/	Pass
				P-80+40M-RU484+996+996	/	-7.37	-6.89	-4.55	/	Pass
			6265	RU996+2X996	/	-7.12	-6.59	-3.94	/	Pass
				SU	/	-6.13	-6.47	-3.52	/	Pass
				RU484+2X996	/	-6.22	-6.75	-3.75	/	Pass
				P-80M-RU2X996+996	/	-7.72	-7.67	-4.74	/	Pass
				P-80+40M-RU484+996+996	/	-6.80	-6.91	-4.04	/	Pass

4.1.2 E.I.R.PSD

ENV	Mode	TX	Frequency	RU	RU	Maximum E.I.R.PSD (dBm/MHz)	Verdict
-----	------	----	-----------	----	----	-----------------------------	---------

		Type	(MHz)		Pos	ANT1	ANT2	MIMO	Limit	
NTNV	802.11be (EHT20)	MIMO	5955	SU	/	-2.11	-1.70	3.83	<=5	Pass
				RU26+52	/	-2.59	-2.68	3.38	<=5	Pass
				RU26+106	/	-3.33	-3.36	2.65	<=5	Pass
			6175	SU	/	-2.96	-3.07	3.00	<=5	Pass
				RU26+52	/	-3.72	-3.77	2.28	<=5	Pass
				RU26+106	/	-3.76	-3.91	2.18	<=5	Pass
			6415	SU	/	-1.92	-2.27	3.93	<=5	Pass
				RU26+52	/	-2.76	-2.80	3.24	<=5	Pass
				RU26+106	/	-2.48	-2.59	3.47	<=5	Pass
	802.11be (EHT40)	MIMO	5965	SU	/	-1.96	-2.75	3.50	<=5	Pass
			6165	SU	/	-2.50	-3.04	3.16	<=5	Pass
			6405	SU	/	-1.97	-2.53	3.51	<=5	Pass
	802.11be (EHT80)	MIMO	5985	SU	/	-2.26	-2.78	3.49	<=5	Pass
				RU242+484	/	-2.62	-2.70	3.35	<=5	Pass
				P-20M-RU242+484	/	-2.52	-2.67	3.39	<=5	Pass
			6145	SU	/	-2.31	-2.65	3.54	<=5	Pass
				RU242+484	/	-3.70	-3.90	2.17	<=5	Pass
				P-20M-RU242+484	/	-3.82	-3.92	2.11	<=5	Pass
			6385	SU	/	-1.67	-2.35	4.00	<=5	Pass
				RU242+484	/	-3.34	-2.91	2.86	<=5	Pass
				P-20M-RU242+484	/	-2.85	-2.98	3.09	<=5	Pass
	802.11be (EHT160)	MIMO	6025	SU	/	-2.54	-2.96	3.26	<=5	Pass
				RU484+996	/	-3.15	-3.19	2.79	<=5	Pass
				P-40M-RU484+996	/	-3.08	-3.23	2.84	<=5	Pass
			6185	SU	/	-2.36	-2.91	3.38	<=5	Pass
				RU484+996	/	-3.77	-4.07	2.03	<=5	Pass
				P-40M-RU484+996	/	-3.92	-4.00	2.00	<=5	Pass
			6345	SU	/	-2.34	-2.81	3.45	<=5	Pass
				RU484+996	/	-3.65	-3.78	2.27	<=5	Pass
				P-40M-RU484+996	/	-3.62	-3.71	2.31	<=5	Pass
	802.11be (EHT320)	MIMO	6105	RU996+2X996	/	-3.46	-3.09	2.58	<=5	Pass
				SU	/	-1.30	-4.45	3.41	<=5	Pass
				RU484+2X996	/	-2.38	-2.74	3.38	<=5	Pass
				P-80M-RU2X996+996	/	-3.57	-3.56	2.01	<=5	Pass
			6265	P-80+40M-RU484+996+996	/	-3.07	-2.69	2.71	<=5	Pass
				RU996+2X996	/	-2.82	-2.39	3.32	<=5	Pass
				SU	/	-1.83	-2.27	3.74	<=5	Pass
				RU484+2X996	/	-1.92	-2.55	3.51	<=5	Pass
				P-80M-RU2X996+996	/	-3.42	-3.47	2.52	<=5	Pass
				P-80+40M-RU484+996+996	/	-2.50	-2.71	3.22	<=5	Pass

4.1.3 PSD

ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	Maximum PSD (dBm/MHz)				Verdict
						ANT1	ANT2	MIMO	Limit	
NTNV	802.11be (EHT20)	MIMO	6435	SU	/	-6.39	-6.73	-3.55	/	Pass
				RU26+52	/	-7.04	-7.01	-4.02	/	Pass
				RU26+106	/	-6.86	-6.88	-3.86	/	Pass
			6475	SU	/	-6.36	-6.66	-3.50	/	Pass
				RU26+52	/	-7.19	-7.13	-4.15	/	Pass
				RU26+106	/	-6.88	-6.89	-3.89	/	Pass
			6515	SU	/	-6.17	-6.66	-3.41	/	Pass
				RU26+52	/	-6.76	-6.76	-3.77	/	Pass
				RU26+106	/	-10.83	-10.79	-7.84	/	Pass
	802.11be	MIMO	6445	SU	/	-6.64	-6.81	-3.87	/	Pass

	(EHT40)		6485	SU	/	-5.84	-6.58	-3.37	/	Pass
	802.11be (EHT80)	MIMO	6465	SU	/	-6.08	-6.54	-3.31	/	Pass
				RU242+484	/	-7.62	-7.52	-4.58	/	Pass
				P-20M-RU242+484	/	-7.62	-7.56	-4.58	/	Pass

4.1.4 E.I.R.PSD

ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	Maximum E.I.R.PSD (dBm/MHz)				Verdict
						ANT1	ANT2	MIMO	Limit	
NTNV	802.11be (EHT20)	MIMO	6435	SU	/	-4.19	-4.93	1.46	<=5	Pass
				RU26+52	/	-4.84	-5.21	0.99	<=5	Pass
				RU26+106	/	-4.66	-5.08	1.15	<=5	Pass
			6475	SU	/	-4.16	-4.86	1.51	<=5	Pass
				RU26+52	/	-4.99	-5.33	0.86	<=5	Pass
				RU26+106	/	-4.68	-5.09	1.12	<=5	Pass
			6515	SU	/	-3.97	-4.86	1.60	<=5	Pass
				RU26+52	/	-4.56	-4.96	1.24	<=5	Pass
				RU26+106	/	-8.63	-8.99	-2.83	<=5	Pass
	802.11be (EHT40)	MIMO	6445	SU	/	-4.44	-5.01	1.14	<=5	Pass
			6485	SU	/	-3.64	-4.78	1.64	<=5	Pass
	802.11be (EHT80)	MIMO	6465	SU	/	-3.88	-4.74	1.70	<=5	Pass
				RU242+484	/	-5.42	-5.72	0.43	<=5	Pass
				P-20M-RU242+484	/	-5.42	-5.76	0.43	<=5	Pass

4.1.5 PSD

ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	Maximum PSD (dBm/MHz)				Verdict
						ANT1	ANT2	MIMO	Limit	
NTNV	802.11be (EHT20)	MIMO	6535	SU	/	-6.18	-6.66	-3.42	/	Pass
				RU26+52	/	-8.62	-8.59	-5.60	/	Pass
				RU26+106	/	-7.20	-7.21	-4.20	/	Pass
			6695	SU	/	-6.01	-6.39	-3.21	/	Pass
				RU26+52	/	-7.40	-7.47	-4.43	/	Pass
				RU26+106	/	-9.70	-9.69	-6.69	/	Pass
			6855	SU	/	-6.83	-7.32	-4.07	/	Pass
				RU26+52	/	-8.31	-8.41	-5.35	/	Pass
				RU26+106	/	-10.52	-10.53	-7.53	/	Pass
	802.11be (EHT40)	MIMO	6565	SU	/	-5.98	-6.42	-3.33	/	Pass
			6685	SU	/	-6.00	-6.50	-3.47	/	Pass
			6845	SU	/	-6.01	-6.45	-3.43	/	Pass
	802.11be (EHT80)	MIMO	6625	SU	/	-6.34	-6.71	-3.53	/	Pass
				RU242+484	/	-7.44	-7.42	-4.45	/	Pass
				P-20M-RU242+484	/	-7.40	-7.41	-4.47	/	Pass
			6705	SU	/	-6.50	-6.98	-3.73	/	Pass
				RU242+484	/	-7.96	-7.95	-5.02	/	Pass
				P-20M-RU242+484	/	-7.94	-7.98	-4.98	/	Pass
			6785	SU	/	-6.33	-6.87	-3.59	/	Pass
				RU242+484	/	-7.77	-7.75	-4.77	/	Pass
				P-20M-RU242+484	/	-7.81	-7.76	-4.78	/	Pass
	802.11be (EHT160)	MIMO	6665	SU	/	-6.40	-6.86	-3.61	/	Pass
				RU484+996	/	-7.00	-6.92	-4.02	/	Pass
				P-40M-RU484+996	/	-6.94	-6.95	-3.94	/	Pass

4.1.6 E.I.R.PSD

ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	Maximum E.I.R.PSD (dBm/MHz)				Verdict
						ANT1	ANT2	MIMO	Limit	
NTNV	802.11be (EHT20)	MIMO	6535	SU	/	-3.68	-3.56	2.40	<=5	Pass
				RU26+52	/	-6.12	-5.49	0.22	<=5	Pass
				RU26+106	/	-4.70	-4.11	1.62	<=5	Pass
			6695	SU	/	-3.51	-3.29	2.61	<=5	Pass
				RU26+52	/	-4.90	-4.37	1.39	<=5	Pass
				RU26+106	/	-7.20	-6.59	-0.87	<=5	Pass
			6855	SU	/	-4.33	-4.22	1.75	<=5	Pass
				RU26+52	/	-5.81	-5.31	0.47	<=5	Pass
				RU26+106	/	-8.02	-7.43	-1.71	<=5	Pass
	802.11be (EHT40)	MIMO	6565	SU	/	-3.48	-3.32	2.49	<=5	Pass
			6685	SU	/	-3.50	-3.40	2.35	<=5	Pass
			6845	SU	/	-3.51	-3.35	2.39	<=5	Pass
	802.11be (EHT80)	MIMO	6625	SU	/	-3.84	-3.61	2.29	<=5	Pass
				RU242+484	/	-4.94	-4.32	1.37	<=5	Pass
				P-20M-RU242+484	/	-4.90	-4.31	1.35	<=5	Pass
			6705	SU	/	-4.00	-3.88	2.09	<=5	Pass
				RU242+484	/	-5.46	-4.85	0.80	<=5	Pass
				P-20M-RU242+484	/	-5.44	-4.88	0.84	<=5	Pass
			6785	SU	/	-3.83	-3.77	2.23	<=5	Pass
				RU242+484	/	-5.27	-4.65	1.05	<=5	Pass
				P-20M-RU242+484	/	-5.31	-4.66	1.04	<=5	Pass
	802.11be (EHT160)	MIMO	6665	SU	/	-3.90	-3.76	2.21	<=5	Pass
				RU484+996	/	-4.50	-3.82	1.80	<=5	Pass
				P-40M-RU484+996	/	-4.44	-3.85	1.88	<=5	Pass

4.1.7 PSD

ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	Maximum PSD (dBm/MHz)				Verdict
						ANT1	ANT2	MIMO	Limit	
NTNV	802.11be (EHT20)	MIMO	6895	SU	/	-6.27	-7.85	-4.01	/	Pass
				RU26+52	/	-7.47	-7.46	-4.46	/	Pass
				RU26+106	/	-9.46	-9.48	-6.48	/	Pass
			6995	SU	/	-6.28	-6.78	-3.52	/	Pass
				RU26+52	/	-6.68	-6.63	-3.67	/	Pass
				RU26+106	/	-8.16	-8.12	-5.15	/	Pass
			7115	SU	/	-6.09	-6.92	-3.51	/	Pass
				RU26+52	/	-7.71	-7.75	-4.73	/	Pass
				RU26+106	/	-7.90	-7.78	-4.86	/	Pass
	802.11be (EHT40)	MIMO	6925	SU	/	-6.04	-6.65	-3.59	/	Pass
			7005	SU	/	-6.20	-6.81	-3.63	/	Pass
			7085	SU	/	-6.45	-6.92	-3.81	/	Pass
	802.11be (EHT80)	MIMO	6945	SU	/	-6.74	-7.19	-3.97	/	Pass
				RU242+484	/	-7.59	-7.50	-4.55	/	Pass
				P-20M-RU242+484	/	-7.49	-7.46	-4.52	/	Pass
			7025	SU	/	-6.68	-7.21	-3.93	/	Pass
				RU242+484	/	-7.81	-7.86	-4.82	/	Pass
				P-20M-RU242+484	/	-7.88	-7.85	-4.88	/	Pass
	802.11be (EHT160)	MIMO	6985	SU	/	-6.62	-7.18	-3.89	/	Pass
				RU484+996	/	-8.38	-8.40	-5.40	/	Pass
				P-40M-RU484+996	/	-8.28	-8.30	-5.31	/	Pass

4.1.8 E.I.R.PSD

ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	Maximum E.I.R.PSD (dBm/MHz)				Verdict
						ANT1	ANT2	MIMO	Limit	
NTNV	802.11be (EHT20)	MIMO	6895	SU	/	-2.97	-6.55	1.36	<=5	Pass
				RU26+52	/	-4.17	-6.16	0.91	<=5	Pass
				RU26+106	/	-6.16	-8.18	-1.11	<=5	Pass
			6995	SU	/	-2.98	-5.48	1.85	<=5	Pass
				RU26+52	/	-3.38	-5.33	1.70	<=5	Pass
				RU26+106	/	-4.86	-6.82	0.22	<=5	Pass
			7115	SU	/	-2.79	-5.62	1.86	<=5	Pass
				RU26+52	/	-4.41	-6.45	0.64	<=5	Pass
				RU26+106	/	-4.60	-6.48	0.51	<=5	Pass
	802.11be (EHT40)	MIMO	6925	SU	/	-2.74	-5.35	1.78	<=5	Pass
			7005	SU	/	-2.90	-5.51	1.74	<=5	Pass
			7085	SU	/	-3.15	-5.62	1.56	<=5	Pass
	802.11be (EHT80)	MIMO	6945	SU	/	-3.44	-5.89	1.40	<=5	Pass
				RU242+484	/	-4.29	-6.20	0.82	<=5	Pass
				P-20M-RU242+484	/	-4.19	-6.16	0.85	<=5	Pass
			7025	SU	/	-3.38	-5.91	1.44	<=5	Pass
				RU242+484	/	-4.51	-6.56	0.55	<=5	Pass
				P-20M-RU242+484	/	-4.58	-6.55	0.49	<=5	Pass
	802.11be (EHT160)	MIMO	6985	SU	/	-3.32	-5.88	1.48	<=5	Pass
				RU484+996	/	-5.08	-7.10	-0.03	<=5	Pass
				P-40M-RU484+996	/	-4.98	-7.00	0.06	<=5	Pass

4.1.9 PSD

ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	Maximum PSD (dBm/MHz)				Verdict
						ANT1	ANT2	MIMO	Limit	
NTNV	802.11be (EHT20)	MIMO	6875	SU	/	-6.09	-6.70	-3.37	/	Pass
				RU26+52	/	-6.88	-6.88	-3.88	/	Pass
				RU26+106	/	-7.02	-7.02	-4.07	/	Pass
	802.11be (EHT40)	MIMO	6885	SU	/	-6.29	-6.87	-3.73	/	Pass
				SU	/	-6.27	-6.80	-3.53	/	Pass
	802.11be (EHT80)	MIMO	6865	RU242+484	/	-6.81	-6.81	-3.82	/	Pass
				P-20M-RU242+484	/	-6.83	-6.83	-3.85	/	Pass
				SU	/	-6.52	-7.09	-3.79	/	Pass
	802.11be (EHT160)	MIMO	6825	RU484+996	/	-7.40	-7.55	-4.46	/	Pass
				P-40M-RU484+996	/	-7.35	-7.45	-4.45	/	Pass
				RU996+2X996	/	-7.13	-6.37	-4.02	/	Pass
	802.11be (EHT320)	MIMO	6745	SU	/	-6.07	-6.35	-3.27	/	Pass
				RU484+2X996	/	-6.41	-6.43	-3.56	/	Pass
				P-80M-RU2X996+996	/	-7.20	-7.23	-4.33	/	Pass
				P-80+40M-RU484+996+996	/	-6.54	-6.87	-3.71	/	Pass
				RU996+2X996	/	-8.23	-8.11	-5.36	/	Pass
			6905	SU	/	-6.16	-7.19	-3.79	/	Pass
				RU484+2X996	/	-7.56	-8.01	-4.79	/	Pass
				P-80M-RU2X996+996	/	-8.03	-8.11	-5.24	/	Pass
				P-80+40M-RU484+996+996	/	-7.22	-7.57	-4.60	/	Pass
				RU996+2X996	/	-8.23	-8.11	-5.36	/	Pass

4.1.10 E.I.R.PSD

ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	Maximum E.I.R.PSD (dBm/MHz)				Verdict
						ANT1	ANT2	MIMO	Limit	
NTNV	802.11be (EHT20)	MIMO	6875	SU	/	-2.79	-5.40	2.45	<=5	Pass
				RU26+52	/	-3.58	-5.58	1.94	<=5	Pass
				RU26+106	/	-3.72	-5.72	1.75	<=5	Pass
	802.11be (EHT40)	MIMO	6885	SU	/	-2.99	-5.57	2.09	<=5	Pass
				SU	/	-2.97	-5.50	2.29	<=5	Pass
	802.11be (EHT80)	MIMO	6865	RU242+484	/	-3.51	-5.51	2.00	<=5	Pass
				P-20M-RU242+484	/	-3.53	-5.53	1.97	<=5	Pass
				SU	/	-3.22	-5.79	2.03	<=5	Pass
	802.11be (EHT160)	MIMO	6825	RU484+996	/	-4.10	-6.25	1.36	<=5	Pass
				P-40M-RU484+996	/	-4.05	-6.15	1.37	<=5	Pass
				RU996+2X996	/	-3.83	-5.07	1.80	<=5	Pass
			6745	SU	/	-2.77	-5.05	2.55	<=5	Pass
				RU484+2X996	/	-3.11	-5.13	2.26	<=5	Pass
				P-80M-RU2X996+996	/	-3.90	-5.93	1.49	<=5	Pass
				P-80+40M-RU484+996+996	/	-3.24	-5.57	2.11	<=5	Pass
				RU996+2X996	/	-4.93	-6.81	0.46	<=5	Pass
				SU	/	-2.86	-5.89	2.03	<=5	Pass
				RU484+2X996	/	-4.26	-6.71	1.03	<=5	Pass
				P-80M-RU2X996+996	/	-4.73	-6.81	0.58	<=5	Pass
				P-80+40M-RU484+996+996	/	-3.92	-6.27	1.22	<=5	Pass
			6905	SU	/	-2.86	-5.89	2.03	<=5	Pass
				RU484+2X996	/	-4.26	-6.71	1.03	<=5	Pass
				P-80M-RU2X996+996	/	-4.73	-6.81	0.58	<=5	Pass
				P-80+40M-RU484+996+996	/	-3.92	-6.27	1.22	<=5	Pass

4.1.11 PSD

ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	Maximum PSD (dBm/MHz)				Verdict
						ANT1	ANT2	MIMO	Limit	
NTNV	802.11be (EHT40)	MIMO	6525	SU	/	-5.99	-6.46	-3.46	/	Pass
	802.11be (EHT80)	MIMO	6545	SU	/	-6.39	-6.88	-3.62	/	Pass
				RU242+484	/	-6.40	-6.38	-3.39	/	Pass
				P-20M-RU242+484	/	-6.33	-6.38	-3.36	/	Pass
	802.11be (EHT160)	MIMO	6505	SU	/	-6.27	-6.73	-3.49	/	Pass
				RU484+996	/	-6.74	-6.73	-3.74	/	Pass
				P-40M-RU484+996	/	-6.77	-6.83	-3.80	/	Pass
	802.11be (EHT320)	MIMO	6585	RU996+2X996	/	-6.19	-6.88	-3.77	/	Pass
				SU	/	-6.09	-6.71	-3.43	/	Pass
				RU484+2X996	/	-6.79	-6.44	-3.90	/	Pass
				P-80M-RU2X996+996	/	-6.45	-6.66	-3.90	/	Pass
				P-80+40M-RU484+996+996	/	-6.72	-6.29	-3.49	/	Pass

4.1.12 E.I.R.PSD

ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	Maximum E.I.R.PSD (dBm/MHz)				Verdict
						ANT1	ANT2	MIMO	Limit	
NTNV	802.11be (EHT40)	MIMO	6525	SU	/	-3.49	-3.36	2.36	<=5	Pass
	802.11be (EHT80)	MIMO	6545	SU	/	-3.89	-3.78	2.20	<=5	Pass
				RU242+484	/	-3.90	-3.28	2.43	<=5	Pass
				P-20M-RU242+484	/	-3.83	-3.28	2.46	<=5	Pass
				SU	/	-3.77	-3.63	2.33	<=5	Pass
	802.11be (EHT160)	MIMO	6505	RU484+996	/	-4.24	-3.63	2.08	<=5	Pass
				P-40M-RU484+996	/	-4.27	-3.73	2.02	<=5	Pass



Report No.: SUCR251000101104

Page: 347 of 921

	802.11be (EHT320)	MIMO	6585	RU996+2X996	/	-3.69	-3.78	2.05	<=5	Pass
				SU	/	-3.59	-3.61	2.39	<=5	Pass
				RU484+2X996	/	-4.29	-3.34	1.92	<=5	Pass
				P-80M-RU2X996+996	/	-3.95	-3.56	1.92	<=5	Pass
				P-80+40M-RU484+996+996	/	-4.22	-3.19	2.33	<=5	Pass

4.1.13 PSD


ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	Maximum PSD (dBm/MHz)				Verdict
						ANT1	ANT2	MIMO	Limit	
NTNV	802.11be (EHT320)	MIMO	6425	RU996+2X996	/	-7.17	-7.19	-4.57	/	Pass
				SU	/	-6.38	-6.85	-3.88	/	Pass
				RU484+2X996	/	-7.14	-7.12	-4.33	/	Pass
				P-80M-RU2X996+996	/	-7.02	-7.06	-4.27	/	Pass
				P-80+40M-RU484+996+996	/	-6.95	-7.41	-4.31	/	Pass

4.1.14 E.I.R.PSD


ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	Maximum E.I.R.PSD (dBm/MHz)				Verdict
						ANT1	ANT2	MIMO	Limit	
NTNV	802.11be (EHT320)	MIMO	6425	RU996+2X996	/	-4.67	-4.09	2.69	<=5	Pass
				SU	/	-3.88	-3.75	3.38	<=5	Pass
				RU484+2X996	/	-4.64	-4.02	2.93	<=5	Pass
				P-80M-RU2X996+996	/	-4.52	-3.96	2.99	<=5	Pass
				P-80+40M-RU484+996+996	/	-4.45	-4.31	2.95	<=5	Pass

4.2 Test Graph


4.2.1 PSD




802.11be(EHT20) LCH 5955MHz SU / MIMO NTN




802.11be(EHT20) LCH 5955MHz 26+52 / Ant1 NTN




802.11be(EHT20) LCH 5955MHz 26+52 / Ant2 NTN




802.11be(EHT20) LCH 5955MHz 26+52 / MIMO NTN




802.11be(EHT20) LCH 5955MHz 26+106 / Ant1 NTN




802.11be(EHT20) LCH 5955MHz 26+106 / Ant2 NTN




802.11be(EHT20) LCH 5955MHz 26+106 / MIMO NTN




802.11be(EHT20) MCH 6175MHz SU / Ant1 NTN




802.11be(EHT20) MCH 6175MHz SU / Ant2 NTN




802.11be(EHT20) MCH 6175MHz SU / MIMO NTN




802.11be(EHT20) MCH_6175MHz_26+52 / Ant1 NTNv




802.11be(EHT20) MCH_6175MHz_26+52 / Ant2 NTNv




802.11be(EHT20) MCH 6175MHz 26+52 / MIMO NTN




802.11be(EHT20) MCH 6175MHz 26+106 / Ant1 NTN




802.11be(EHT20) MCH 6175MHz 26+106 / Ant2 NTN




802.11be(EHT20) MCH 6175MHz 26+106 / MIMO NTN




802.11be(EHT20) HCH 6415MHz SU / Ant1 NTN




802.11be(EHT20) HCH 6415MHz SU / Ant2 NTN




802.11be(EHT20) HCH 6415MHz SU / MIMO NTN




802.11be(EHT20) HCH 6415MHz 26+52 / Ant1 NTN




802.11be(EHT20) HCH 6415MHz 26+52 / Ant2 NTN




802.11be(EHT20) HCH 6415MHz 26+52 / MIMO NTN




802.11be(EHT20) HCH 6415MHz 26+106 / Ant1 NTN




802.11be(EHT20) HCH 6415MHz 26+106 / Ant2 NTN




802.11be(EHT20) HCH 6415MHz 26+106 / MIMO NTV




802.11be(EHT40) LCH 5965MHz SU / Ant1 NTV




802.11be(EHT40) LCH 5965MHz SU / Ant2 NTN




802.11be(EHT40) LCH 5965MHz SU / MIMO NTN




802.11be(EHT40) MCH 6165MHz SU / Ant1 NTN




802.11be(EHT40) MCH 6165MHz SU / Ant2 NTN




802.11be(EHT40) MCH 6165MHz SU / MIMO NTN




802.11be(EHT40) HCH 6405MHz SU / Ant1 NTN




802.11be(EHT40) HCH 6405MHz SU / Ant2 NTN




802.11be(EHT40) HCH 6405MHz SU / MIMO NTN




802.11be(EHT80) LCH 5985MHz SU / Ant1 NTN




802.11be(EHT80) LCH 5985MHz SU / Ant2 NTN




802.11be(EHT80) LCH 5985MHz SU / MIMO NTN




802.11be(EHT80) LCH 5985MHz 242+484 / Ant1 NTN




802.11be(EHT80) LCH 5985MHz 242+484 / Ant2 NTN




802.11be(EHT80) LCH 5985MHz 242+484 / MIMO NTN




802.11be(EHT80) LCH 5985MHz P-20M-RU242+484 / Ant1 NTN



802.11be(EHT80) LCH 5985MHz P-20M-RU242+484 / Ant2 NTN



802.11be(EHT80) LCH 5985MHz P-20M-RU242+484 / MIMO NTN



802.11be(EHT80) MCH 6145MHz SU / Ant1 NTN

