



MPE/RF EXPOSURE REPORT

FCC CFR 47 Part 1.1310

Report No; DIGI140-U7A Rev B

Company: Digi International Inc.

Model: XBP9XR

MPE/RF EXPOSURE REPORT

Company: Digi International Inc.

Model: XBP9XR

To: FCC CFR 47 Part 1.1310

Report Serial No.: DIGI140-U7A Rev B

This report supersedes: NONE

Applicant: Digi International Inc.
9350 Excelsior Blvd, Suite 700
Hopkins,
Minnesota 55343
United States of America

Issue Date: 17th September 2026

This Report is Issued Under the Authority of:

MiCOM Labs, Inc.
575 Boulder Court
Pleasanton California 94566
USA
Phone: +1 (925) 462-0304
Fax: +1 (925) 462-0306
www.micomlabs.com



MiCOM Labs is an ISO 17025 Accredited Testing Laboratory

1. MAXIMUM PERMISSABLE EXPOSURE

Calculations for Maximum Permissible Exposure Levels

Power Density = P_d (mW/cm²) = $EIRP / (4 * \pi * d^2)$

$EIRP = P * G$

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

Numeric Gain = $10^{(G \text{ (dBi)}/10)}$

The following assessment is made for the lowest gain antenna and antennas with gain greater than 6 dBi. that are used with the Digi XBP9XR.

Freq. Band (MHz)	Transmit Frequency (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Conducted Output Power (dBm)	Output Power (mW)	Power Density Limit (mW/cm ²)	Calculated Power Density (mW/cm ²) @ 20cm	Power Density Ratio	Min Calculated safe distance for Limit (cm)
902.0 – 928.0	902.5	0.80	1.20	29.98	995.41	0.60	0.238	0.396	12.58
902.0 – 928.0	902.5	8.00	6.31	28.00	630.96	0.60	0.792	1.316	22.95
902.0 – 928.0	902.5	15.00	31.62	21.00	125.89	0.60	0.792	1.316	22.95

Summary; Equipment does not meet the RF exposure requirements at a minimum separation distance of 20 cm when antennas with gain greater than 6 dBi are used.

Calculation for greater separation distance of 23 cm.

Freq. Band (MHz)	Transmit Frequency (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Conducted Output Power (dBm)	Output Power (mW)	Power Density Limit (mW/cm ²)	Calculated Power Density (mW/cm ²) @ 23 cm	Power Density Ratio
902.0 – 928.0	902.5	8.00	6.31	28.00	630.96	0.60	0.599	0.995
902.0 – 928.0	902.5	15.00	31.62	21.00	125.89	0.60	0.599	0.995

Conclusion; A minimum separation distance of 23 cm is required to meet the RF exposure requirements as defined in Table 1 of FCC §1.1310 when using antennas over 6 dBi.

Specification - Maximum Permissible Exposure Limits

The Limits are defined in Table 1 of FCC §1.1310.

The Limits for General Population/Uncontrolled Exposure apply.

Table 1 to [§ 1.1310\(e\)\(1\)](#)—Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(ii) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1.0	<30



575 Boulder Court
Pleasanton, California 94566, USA
Tel: +1 (925) 462 0304
Fax: +1 (925) 462 0306
www.micomlabs.com