


85L232SI120S REV 2A

ECN

1.375 X 8

12/18/00



Luxline

ELECTRONIC INSTANT START BALLAST
 • POWER FACTOR ABOVE 90% • SOUND RATED A
 MINIMUM STARTING TEMPERATURE: 0°F
 INSTALL IN ACCORDANCE WITH NATIONAL
 AND LOCAL ELECTRICAL CODES

2


CAT. NO. L232SI120S
 NO PCB'S
 CLASS P

120 VOLTS
 60 HZ
 0.49 AMPS
 FCC ID: MKGLUXLINE
 LISTED BALLAST
 TYPE 1 US DOOR

FOR USE WITH (2) F8T8 OR (2) F8T8 LAMPS

08L232SI120S REV 2A

SL LIGHTING
 EL PASO, TX USA
 1-800-455-7280
 ASSEMBLED IN MEXICO



Luxline

ELECTRONIC INSTANT START BALLAST
 • POWER FACTOR ABOVE 90% • SOUND RATED A
 MINIMUM STARTING TEMPERATURE: 0°F
 INSTALL IN ACCORDANCE WITH NATIONAL
 AND LOCAL ELECTRICAL CODES

2

CAT. NO. L232SI120S
 NO PCB'S
 CLASS P

120 VOLTS
 60 HZ
 0.49 AMPS
 FCC ID: MKGLUXLINE
 LISTED BALLAST
 TYPE 1 US DOOR

FOR USE WITH (2) F8T8 OR (2) F8T8 LAMPS

08L232SI120S REV 2A

SL LIGHTING
 EL PASO, TX USA
 1-800-455-7280
 ASSEMBLED IN MEXICO