

*FCC PART 15, SUBPART B and C
TEST REPORT**for***TRANSMITTER****MODEL: TXM-PT911**

Prepared for

MYTEK KOREA COMPANY
4FL. SHINKUMCHON, TELEPHONE OFFICE #1093,
DOKSHAN 1 DONG, KUMCHON-GU, SEOUL, KOREA

Prepared by: _____

KYLE FUJIMOTO

Approved by: _____

MICHAEL CHRISTENSEN

COMPATIBLE ELECTRONICS INC.
114 OLINDA DRIVE
BREA, CALIFORNIA 92823
(714) 579-0500

DATE: APRIL 24, 2003

	REPORT BODY	APPENDICES					TOTAL
		<i>A</i>	<i>B</i>	<i>C</i>	<i>D</i>	<i>E</i>	
PAGES	16	2	2	2	10	15	47

This report shall not be reproduced except in full, without the written approval of Compatible Electronics.



TABLE OF CONTENTS

Section / Title	PAGE
GENERAL REPORT SUMMARY	4
SUMMARY OF TEST RESULTS	4
1. PURPOSE	5
2. ADMINISTRATIVE DATA	6
2.1 Location of Testing	6
2.2 Traceability Statement	6
2.3 Cognizant Personnel	6
2.4 Date Test Sample was Received	6
2.5 Disposition of the Test Sample	6
2.6 Abbreviations and Acronyms	6
3. APPLICABLE DOCUMENTS	7
4. Description of Test Configuration	8
4.1 Description of Test Configuration - EMI	8
4.1.1 Cable Construction and Termination	9
5. LISTS OF EUT, ACCESSORIES AND TEST EQUIPMENT	10
5.1 EUT and Accessory List	10
5.2 EMI Test Equipment (Lab X)	11
6. TEST SITE DESCRIPTION	12
6.1 Test Facility Description	12
6.2 EUT Mounting, Bonding and Grounding	12
7. Test Procedures	13
7.1 Radiated Emissions (Spurious and Harmonics) Test	13
7.2 Bandwidth of the Fundamental	15
8. CONCLUSIONS	16



LIST OF APPENDICES

APPENDIX	TITLE
A	Laboratory Recognitions
B	Modifications to the EUT
C	Additional Models Covered Under This Report
D	Diagrams, Charts, and Photos • Test Setup Diagrams • Radiated Emissions Photos • Antenna and Effective Gain Factors
E	Data Sheets

LIST OF FIGURES

FIGURE	TITLE
1	Plot Map And Layout of Radiated Site



GENERAL REPORT SUMMARY

This electromagnetic emission test report is generated by Compatible Electronics Inc., which is an independent testing and consulting firm. The test report is based on testing performed by Compatible Electronics personnel according to the measurement procedures described in the test specifications given below and in the "Test Procedures" section of this report.

The measurement data and conclusions appearing herein relate only to the sample tested and this report may not be reproduced without the written permission of Compatible Electronics, unless done so in full.

This report must not be used to claim product endorsement by NVLAP or any other agency of the U.S. Government.

Device Tested: Transmitter
Model: TXM-PT911
S/N: N/A

Product Description: See Expository Statement.

Modifications: The EUT was not modified during the testing.

Manufacturer: Mytek Korea Company
4FL, Shinkumchon, Telephone Office #1093,
Dokshan 1 Dong, Kumchon-Gu, Seoul, Korea

Test Date: February 12, 2002

Test Specifications: EMI requirements
CFR Title 47, Part 15 Subpart B; and Subpart C, Sections 15.205, 15.209, and 15.231

Test Procedure: ANSI C63.4: 1992

Test Deviations: The test procedure was not deviated from during the testing.


SUMMARY OF TEST RESULTS

TEST	DESCRIPTION	RESULTS
1	Conducted RF Emissions, 450 kHz - 30 MHz	This test was not performed because the EUT operates on battery power only and cannot be plugged into the AC public mains.
2	Radiated RF Emissions, 10 kHz - 4400 MHz	Complies with the Class B limits of CFR Title 47, Part 15, Subpart B; and Subpart C, sections 15.205, 15.209, and 15.231.



1. PURPOSE

This document is a qualification test report based on the Electromagnetic Interference (EMI) tests performed on the Transmitter Model: TXM-PT911. The EMI measurements were performed according to the measurement procedure described in ANSI C63.4: 1992. The tests were performed in order to determine whether the electromagnetic emissions from the equipment under test, referred to as EUT hereafter, are within the Class B specification limits defined by CFR Title 47, Part 15, Subpart B; and Subpart C, sections 15.205, 15.209, and 15.231.



2. ADMINISTRATIVE DATA

2.1 Location of Testing

The EMI tests described herein were performed at the test facility of Compatible Electronics, 114 Olinda Drive, Brea, California 92823.

2.2 Traceability Statement

The calibration certificates of all test equipment used during the test are on file at the location of the test. The calibration is traceable to the National Institute of Standards and Technology (NIST).

2.3 Cognizant Personnel

Mytek Korea Company

Timothy Choi Director

Compatible Electronics, Inc.

Kyle Fujimoto Test Engineer

Michael Christensen Test Engineer

2.4 Date Test Sample was Received

The test sample was received on February 12, 2002.

2.5 Disposition of the Test Sample

The sample has not been returned to Mytek Korea Company as of February 12, 2002.

2.6 Abbreviations and Acronyms

The following abbreviations and acronyms may be used in this document.

RF	Radio Frequency
EMI	Electromagnetic Interference
EUT	Equipment Under Test
P/N	Part Number
S/N	Serial Number
HP	Hewlett Packard
ITE	Information Technology Equipment
CML	Corrected Meter Limit
LISN	Line Impedance Stabilization Network



3. APPLICABLE DOCUMENTS

The following documents are referenced or used in the preparation of this EMI Test Report.

SPEC	TITLE
CFR Title 47, Part 15	FCC Rules – Radio frequency devices (including digital devices)
ANSI C63.4 1992	Methods of measurement of radio-noise emissions from low-voltage electrical and electronic equipment in the range of 9 kHz to 40 GHz



4. DESCRIPTION OF TEST CONFIGURATION

4.1 Description of Test Configuration - EMI

Setup and operation of the equipment under test.

Specifics of the EUT and Peripherals Tested

The Transmitter Model: TXM-PT911 (EUT) was tested as a stand alone unit. The EUT was tested in three orthogonal axis. The EUT was continuously transmitting. The antenna is a PCB trace on the EUT. The EUT turns off as soon as the button is released on the EUT.

The final radiated data was taken in the mode above. Please see Appendix E for the data sheets.



4.1.1 Cable Construction and Termination

There are no external cables connected to the EUT.



5. LISTS OF EUT, ACCESSORIES AND TEST EQUIPMENT**5.1 EUT and Accessory List**

EQUIPMENT	MANUFACTURER	MODEL NUMBER	SERIAL NUMBER	FCC ID
TRANSMITTER (EUT)	MYTEK KOREA COMPANY	TXM-PT911	N/A	MKYTXPT911



5.2 EMI Test Equipment

EQUIPMENT TYPE	MANU-FACTURER	MODEL NUMBER	SERIAL NUMBER	CAL. DATE	CAL. DUE DATE
Radiated Emissions Data Capture Program	Compatible Electronics	2.0	N/A	N/A	N/A
Spectrum Analyzer – Main Section	Hewlett Packard	8566B	2634A02962	February 8, 2002	February 8, 2003
Spectrum Analyzer – Display Section	Hewlett Packard	85662A	2517A09947	February 8, 2002	February 8, 2003
Spectrum Analyzer – Quasi-Peak Adapter	Hewlett Packard	85650A	2811A01362	February 8, 2002	February 8, 2003
Preamplifier	Com Power	PA-102	1017	December 31, 2001	December 31, 2002
Biconical Antenna	Com Power	AB-100	1548	October 11, 2001	October 11, 2002
Log Periodic Antenna	Com Power	AL-100	16089	October 11, 2001	October 11, 2002
Antenna Mast	Com Power	AM-100	N/A	N/A	N/A
Turntable	Com Power	TT-100	N/A	N/A	N/A
Computer	Hewlett Packard	4530	US91912319	N/A	N/A
Monitor	Hewlett Packard	D5258A	TW74500641	N/A	N/A
Microwave Preamplifier	Com-Power	PA-122	25195	January 7, 2002	January 7, 2003
Horn Antenna	Com-Power	DRG-118/A	1053	January 13, 2002	January 13, 2004
Loop Antenna	Com-Power	AL-130	17070	May 21, 2001	May 21, 2002



6. TEST SITE DESCRIPTION**6.1 Test Facility Description**

Please refer to section 2.1 and 7.1 of this report for EMI test location.

6.2 EUT Mounting, Bonding and Grounding

The EUT was mounted on a 1.0 by 1.5 meter non-conductive table 0.8 meters above the ground plane.

The EUT was not grounded.



7. TEST PROCEDURES

The following sections describe the test methods and the specifications for the tests. Test results are also included in this section.

7.1 Radiated Emissions (Spurious and Harmonics) Test

The spectrum analyzer was used as a measuring meter along with the quasi-peak adapter. Amplifiers were used to increase the sensitivity of the instrument. The Com Power Preamplifier Model: PA-102 was used for frequencies from 30 MHz to 1 GHz, and the Com-Power Microwave Preamplifier Model: PA-122 was used for frequencies above 1 GHz. The spectrum analyzer was used in the peak detect mode with the "Max Hold" feature activated. In this mode, the spectrum analyzer records the highest measured reading over all the sweeps.

The measurement bandwidths and transducers used for the radiated emissions test were:

FREQUENCY RANGE	EFFECTIVE MEASUREMENT BANDWIDTH	TRANSDUCER
9 kHz to 150 kHz	200 Hz	Active Loop Antenna
150 kHz to 30 MHz	9 kHz	Active Loop Antenna
30 MHz to 300 MHz	120 kHz	Biconical Antenna
300 MHz to 1 GHz	120 kHz	Log Periodic Antenna
1 GHz to 4.40 GHz	1 MHz	Horn Antenna

The open field test site of Compatible Electronics, Inc. was used for radiated emission testing. This test site is set up according to ANSI C63.4: 1992. Please see section 6.2 of this report for mounting, bonding and grounding of the EUT. The turntable supporting the EUT is remote controlled using a motor. The turntable permits EUT rotation of 360 degrees in order to maximize emissions. Also, the antenna mast allows height variation of the antenna from 1 meter to 4 meters. Data was collected in the worst case (highest emission) configuration of the EUT. At each reading, the EUT was rotated 360 degrees and the antenna height was varied from 1 to 4 meters (for E field radiated field strength). The gunsight method was used when measuring with the horn antenna in order to ensure accurate results. The loop antenna was also rotated in the horizontal and vertical axis in order to ensure accurate results.



Radiated Emissions (Spurious and Harmonics) Test (con't)

The presence of ambient signals was verified by turning the EUT off. In case an ambient signal was detected, the measurement bandwidth was reduced temporarily and verification was made that an additional adjacent peak did not exist. This ensures that the ambient signal does not hide any emissions from the EUT. The EUT was tested at a 3 meter test distance to obtain final test data. The final qualification data sheets are located in Appendix E.



7.2 Bandwidth of the Fundamental

The -20 dB bandwidth was checked to see that it was within 0.25% of the fundamental frequency for the EUT. A data sheet of the -20 dB bandwidth is located in Appendix E.



8. CONCLUSIONS

The Transmitter Model: TXM-PT911 meets all of the Class B specification limits defined in CFR Title 47, Part 15, Subpart B; and Subpart C, sections 15.205, 15.209, and 15.231.



APPENDIX A

LABORATORY RECOGNITIONS



LABORATORY RECOGNITIONS

Compatible Electronics has the following agency accreditations:

National Voluntary Laboratory Accreditation Program - Lab Code: 200528-0

Voluntary Control Council for Interference - Registration Numbers: R-983, C-1026, R-984 and C-1027

Bureau of Standards and Metrology Inspection - Reference Number: SL2-IN-E-1031

Conformity Assessment Body for the EMC Directive Under the US/EU MRA Appointed by NIST

Compatible Electronics is recognized or on file with the following agencies:

Federal Communications Commission

Industry Canada

Radio-Frequency Technologies (Competent Body)



APPENDIX B

MODIFICATIONS TO THE EUT




MODIFICATIONS TO THE EUT

The modifications listed below were made to the EUT to pass FCC 15.231 or FCC Class B specifications.

All the rework described below was implemented during the test in a method that could be reproduced in all the units by the manufacturer.

No modifications were made to the EUT during the testing.



APPENDIX C

***ADDITIONAL MODELS COVERED
UNDER THIS REPORT***



ADDITIONAL MODELS COVERED UNDER THIS REPORT

USED FOR THE PRIMARY TEST

Transmitter
Model: TXM-PT911
S/N: N/A

There were no additional models covered under this report.




APPENDIX D

DIAGRAMS, CHARTS, AND PHOTOS




FIGURE 1: PLOT MAP AND LAYOUT OF RADIATED SITE

OPEN LAND > 15 METERS



OPEN LAND > 15 METERS



COM-POWER AB-100

BICONICAL ANTENNA

S/N: 01548

CALIBRATION DATE: OCTOBER 11, 2001

FREQUENCY (MHz)	FACTOR (dB)	FREQUENCY (MHz)	FACTOR (dB)
30	13.70	120	11.00
35	13.70	125	11.20
40	11.80	140	12.50
45	12.30	150	13.20
50	11.00	160	13.50
60	10.40	175	14.60
70	8.60	180	14.40
80	8.30	200	15.90
90	8.30	250	17.60
100	8.80	300	19.90



COM-POWER AL-100

LOG PERIODIC ANTENNA

S/N: 16089

CALIBRATION DATE: OCTOBER 11, 2001

FREQUENCY (MHz)	FACTOR (dB)	FREQUENCY (MHz)	FACTOR (dB)
300	14.10	700	20.60
400	15.10	800	22.40
500	16.60	900	22.70
600	19.90	1000	26.50



COM-POWER PA-102**PREAMPLIFIER**

S/N: 1017

CALIBRATION DATE: DECEMBER 31, 2001

FREQUENCY (MHz)	FACTOR (dB)	FREQUENCY (MHz)	FACTOR (dB)
30	38.5	300	38.5
40	38.5	350	38.4
50	38.5	400	38.2
60	38.5	450	37.8
70	38.5	500	38.0
80	38.5	550	38.2
90	38.3	600	38.2
100	38.3	650	38.0
125	38.6	700	38.1
150	38.5	750	37.7
175	38.4	800	37.4
200	38.5	850	37.9
225	38.5	900	37.2
250	38.4	950	36.8
275	38.4	1000	37.3




COM-POWER PA-122
MICROWAVE PREAMPLIFIER

S/N: 25195

CALIBRATION DATE: JANUARY 7, 2002

FREQUENCY (GHz)	FACTOR (dB)	FREQUENCY (GHz)	FACTOR (dB)
1.0	33.7	9.5	31.8
1.1	33.4	10.0	32.2
1.2	33.1	11.0	31.4
1.3	33.1	12.0	30.2
1.4	33.2	13.0	32.9
1.5	32.5	14.0	33.9
1.6	32.7	15.0	32.4
1.7	32.3	16.0	32.2
1.8	32.3	17.0	31.5
1.9	31.4	18.0	32.2
2.0	32.8	19.0	31.2
2.5	33.3	20.0	31.3
3.0	31.7	21.0	31.7
3.5	31.6	22.0	29.7
4.0	31.2		
4.5	31.2		
5.0	31.0		
5.5	31.3		
6.0	32.1		
6.5	32.1		
7.0	31.8		
7.5	32.0		
8.0	33.1		
8.5	32.0		
9.0	30.8		



ANTENNA RESEARCH DRG-118/A**HORN ANTENNA**

S/N: 1053

CALIBRATION DATE: JANUARY 13, 2002

FREQUENCY (GHz)	FACTOR (dB)	FREQUENCY (GHz)	FACTOR (dB)
1.0	25.5	9.5	39.1
1.5	26.6	10.0	39.7
2.0	29.4	10.5	40.9
2.5	30.4	11.0	40.7
3.0	31.2	11.5	42.4
3.5	32.3	12.0	42.6
4.0	32.9	12.5	42.4
4.5	33.0	13.0	41.5
5.0	34.8	13.5	41.0
5.5	35.2	14.0	40.5
6.0	36.4	14.5	43.6
6.5	36.6	15.0	43.7
7.0	38.8	15.5	43.3
7.5	38.8	16.0	42.8
8.0	38.0	16.5	43.0
8.5	38.1	17.0	42.7
9.0	39.9	17.5	44.0
		18.0	41.8



COM-POWER AL-130**LOOP ANTENNA**

S/N: 17070

CALIBRATION DATE: MAY 21, 2001

FREQUENCY (MHz)	MAGNETIC (dB/m)	ELECTRIC (dB/m)
0.009	-40.4	11.0
0.01	-40.3	11.1
0.02	-41.2	10.1
0.05	-41.6	9.8
0.07	-41.4	10.0
0.1	-41.7	9.7
0.2	-44.0	7.5
0.3	-41.6	9.9
0.5	-41.3	9.9
0.7	-41.4	10.1
1	-40.9	10.6
2	-40.6	11.2
3	-40.5	11.0
4	-40.8	10.7
5	-40.2	11.3
10	-40.7	10.8
15	-41.4	10.2
20	-41.6	10.1
25	-41.7	9.8
30	-42.9	8.4





FRONT VIEW

MYTEK KOREA COMPANY
TRANSMITTER
MODEL: TXM-PT911

FCC SUBPART B AND C - RADIATED EMISSIONS – 02-12-02

**PHOTOGRAPH SHOWING THE EUT CONFIGURATION
FOR MAXIMUM EMISSIONS**





REAR VIEW

MYTEK KOREA COMPANY
TRANSMITTER
MODEL: TXM-PT911
FCC SUBPART B AND C - RADIATED EMISSIONS – 02-12-02

**PHOTOGRAPH SHOWING THE EUT CONFIGURATION
FOR MAXIMUM EMISSIONS**



APPENDIX E

DATA SHEETS



RADIATED EMISSIONS

DATA SHEETS



RADIATED EMISSIONS (FCC SECTION 15.205 AND 15.231)

COMPANY	MYTEK KOREA	DATE	2/12/02
EUT	TRANSMITTER	DUTY CYCLE	21.90 %
MODEL	TXM-PT911	PEAK TO AVG	-13.19 dB
S/N	N/A	TEST DIST.	3 METERS
TEST ENGINEER	KYLE FUJIMOTO	LAB	D

Frequency MHz	Peak Reading (dBuV)	Average (A) or Quasi- Peak (QP)	Antenna Polar. (V or H)	Antenna Height (meters)	EUT Azimuth (degrees)	EUT Axis (X,Y,Z)	EUT Tx Channel	Antenna Factor (dB)	Cable Loss (dB)	Amplifier Gain (dB)	*Corrected Reading (dBuV/m)	Delta ** (dB)	Spec Limit (dBuV/m)	Comments
433.9200	60.5	47.4 A	H	1.0	0	X	LOW	15.6	3.8	0.0	66.8	-14.0	80.8	
433.9200	57.7	44.6 A	H	1.0	0	Y	LOW	15.6	3.8	0.0	64.0	-16.8	80.8	
433.9200	54.2	41.1 A	H	1.0	0	Z	LOW	15.6	3.8	0.0	60.5	-20.3	80.8	
433.9200	51.4	38.3 A	V	1.0	0	X	LOW	15.6	3.8	0.0	57.7	-23.1	80.8	
433.9200	61.1	48.0 A	V	1.0	90	Y	LOW	15.6	3.8	0.0	67.4	-13.4	80.8	
433.9200	58.4	45.3 A	V	1.0	0	Z	LOW	15.6	3.8	0.0	64.7	-16.1	80.8	

* CORRECTED READING = METER READING + ANTENNA FACTOR + CABLE LOSS - AMPLIFIER GAIN
 ** DELTA = SPEC LIMIT - CORRECTED READING

RADIATED EMISSIONS (FCC SECTION 15.205 AND 15.231)

COMPANY	MYTEK KOREA	DATE	2/12/02
EUT	TRANSMITTER	DUTY CYCLE	21.90 %
MODEL	TXM-PT911	PEAK TO AVG	-13.19 dB
S/N	N/A	TEST DIST.	3 METERS
TEST ENGINEER	KYLE FUJIMOTO	LAB	D

Frequency MHz	Peak Reading (dBuV)	Average (A) or Quasi- Peak (QP)	Antenna Polar. (V or H)	Antenna Height (meters)	EUT Azimuth (degrees)	EUT Axis (X,Y,Z)	EUT Tx Channel	Antenna Factor (dB)	Cable Loss (dB)	Amplifier Gain (dB)	*Corrected Reading (dBuV/m)	Delta ** (dB)	Spec Limit (dBuV/m)	Comments
867.8400	70.9	57.8 A	H	1.0	45	X	LOW	22.6	5.3	37.7	48.0	-12.8	60.8	
867.8400	68.8	55.7 A	H	1.0	0	Y	LOW	22.6	5.3	37.7	45.9	-14.9	60.8	
867.8400	67.4	54.3 A	H	1.0	90	Z	LOW	22.6	5.3	37.7	44.5	-16.3	60.8	
867.8400	61.5	48.4 A	V	1.0	90	X	LOW	22.6	5.3	37.7	38.6	-22.2	60.8	
867.8400	71.3	58.2 A	V	1.0	90	Y	LOW	22.6	5.3	37.7	48.4	-12.4	60.8	
867.8400	71.6	58.5 A	V	1.0	180	Z	LOW	22.6	5.3	37.7	48.7	-12.1	60.8	

* CORRECTED READING = METER READING + ANTENNA FACTOR + CABLE LOSS - AMPLIFIER GAIN
 ** DELTA = SPEC LIMIT - CORRECTED READING

RADIATED EMISSIONS (FCC SECTION 15.205 AND 15.231)

COMPANY	MYTEK KOREA	DATE	2/12/02
EUT	TRANSMITTER	DUTY CYCLE	21.90 %
MODEL	TXM-PT911	PEAK TO AVG	-13.19 dB
S/N	N/A	TEST DIST.	3 METERS
TEST ENGINEER	KYLE FUJIMOTO	LAB	D

Frequency MHz	Peak Reading (dBuV)	Average (A) or Quasi- Peak (QP)	Antenna Polar. (V or H)	Antenna Height (meters)	EUT Azimuth (degrees)	EUT Axis (X,Y,Z)	EUT Tx Channel	Antenna Factor (dB)	Cable Loss (dB)	Amplifier Gain (dB)	*Corrected Reading (dBuV/m)	Delta ** (dB)	Spec Limit (dBuV/m)	Comments
1301.7600	65.5	52.4 A	H	1.0	0	X	LOW	26.2	2.7	33.1	48.2	-5.8	54.0	
1301.7600	63.3	50.2 A	H	2.0	0	Y	LOW	26.2	2.7	33.1	46.0	-8.0	54.0	
1301.7600	61.8	48.7 A	H	1.0	0	Z	LOW	26.2	2.7	33.1	44.5	-9.5	54.0	
1301.7600	54.0	40.9 A	V	1.0	0	X	LOW	26.2	2.7	33.1	36.7	-17.3	54.0	
1301.7600	55.1	42.0 A	V	1.0	270	Y	LOW	26.2	2.7	33.1	37.8	-16.2	54.0	
1301.7600	61.2	48.1 A	V	1.0	0	Z	LOW	26.2	2.7	33.1	43.9	-10.1	54.0	

* CORRECTED READING = METER READING + ANTENNA FACTOR + CABLE LOSS - AMPLIFIER GAIN
 ** DELTA = SPEC LIMIT - CORRECTED READING

RADIATED EMISSIONS (FCC SECTION 15.205 AND 15.231)

COMPANY	MYTEK KOREA	DATE	2/12/02
EUT	TRANSMITTER	DUTY CYCLE	21.90 %
MODEL	TXM-PT911	PEAK TO AVG	-13.19 dB
S/N	N/A	TEST DIST.	3 METERS
TEST ENGINEER	KYLE FUJIMOTO	LAB	D

Frequency MHz	Peak Reading (dBuV)	Average (A) or Quasi- Peak (QP)	Antenna Polar. (V or H)	Antenna Height (meters)	EUT Azimuth (degrees)	EUT Axis (X,Y,Z)	EUT Tx Channel	Antenna Factor (dB)	Cable Loss (dB)	Amplifier Gain (dB)	*Corrected Reading (dBuV/m)	Delta ** (dB)	Spec Limit (dBuV/m)	Comments
1735.6800	68.9	55.8 A	H	1.0	270	X	LOW	27.9	3.3	32.3	54.8	-6.0	60.8	
1735.6800	68.6	55.5 A	H	1.0	0	Y	LOW	27.9	3.3	32.3	54.5	-6.3	60.8	
1735.6800	71.1	58.0 A	H	1.0	0	Z	LOW	27.9	3.3	32.3	57.0	-3.8	60.8	
1735.6800	67.1	54.0 A	V	3.0	0	X	LOW	27.9	3.3	32.3	53.0	-7.8	60.8	
1735.6800	69.5	56.4 A	V	1.0	270	Y	LOW	27.9	3.3	32.3	55.4	-5.4	60.8	
1735.6800	64.7	51.6 A	V	1.0	90	Z	LOW	27.9	3.3	32.3	50.6	-10.2	60.8	

* CORRECTED READING = METER READING + ANTENNA FACTOR + CABLE LOSS - AMPLIFIER GAIN
 ** DELTA = SPEC LIMIT - CORRECTED READING

PAGE 4

RADIATED EMISSIONS (FCC SECTION 15.205 AND 15.231)

COMPANY	MYTEK KOREA	DATE	2/12/02
EUT	TRANSMITTER	DUTY CYCLE	21.90 %
MODEL	TXM-PT911	PEAK TO AVG	-13.19 dB
S/N	N/A	TEST DIST.	3 METERS
TEST ENGINEER	KYLE FUJIMOTO	LAB	D

Frequency MHz	Peak Reading (dBuV)	Average (A) or Quasi- Peak (QP)	Antenna Polar. (V or H)	Antenna Height (meters)	EUT Azimuth (degrees)	EUT Axis (X,Y,Z)	EUT Tx Channel	Antenna Factor (dB)	Cable Loss (dB)	Amplifier Gain (dB)	*Corrected Reading (dBuV/m)	Delta ** (dB)	Spec Limit (dBuV/m)	Comments
2169.6000	69.3	56.2 A	H	2.0	0	X	LOW	29.7	3.5	32.4	57.0	-3.8	60.8	
2169.6000	66.0	52.9 A	H	2.0	0	Y	LOW	29.7	3.5	32.4	53.7	-7.1	60.8	
2169.6000	65.3	52.2 A	H	2.0	180	Z	LOW	29.7	3.5	32.4	53.0	-7.8	60.8	
2169.6000	66.7	53.6 A	V	2.0	0	X	LOW	29.7	3.5	32.4	54.4	-6.4	60.8	
2169.6000	68.8	55.7 A	V	2.0	0	Y	LOW	29.7	3.5	32.4	56.5	-4.3	60.8	
2169.6000	67.7	54.6 A	V	1.0	0	Z	LOW	29.7	3.5	32.4	55.4	-5.4	60.8	

* CORRECTED READING = METER READING + ANTENNA FACTOR + CABLE LOSS - AMPLIFIER GAIN
 ** DELTA = SPEC LIMIT - CORRECTED READING

RADIATED EMISSIONS (FCC SECTION 15.205 AND 15.231)

COMPANY	MYTEK KOREA	DATE	2/12/02
EUT	TRANSMITTER	DUTY CYCLE	21.90 %
MODEL	TXM-PT911	PEAK TO AVG	-13.19 dB
S/N	N/A	TEST DIST.	3 METERS
TEST ENGINEER	KYLE FUJIMOTO	LAB	D

Frequency MHz	Peak Reading (dBuV)	Average (A) or Quasi- Peak (QP)	Antenna Polar. (V or H)	Antenna Height (meters)	EUT Azimuth (degrees)	EUT Axis (X,Y,Z)	EUT Tx Channel	Antenna Factor (dB)	Cable Loss (dB)	Amplifier Gain (dB)	*Corrected Reading (dBuV/m)	Delta ** (dB)	Spec Limit (dBuV/m)	Comments
2603.5200	63.9	50.8 A	H	2.0	270	X	LOW	30.6	3.5	33.0	51.9	-8.9	60.8	
2603.5200	61.7	48.6 A	H	1.0	0	Y	LOW	30.6	3.5	33.0	49.7	-11.1	60.8	
2603.5200	59.3	46.2 A	H	1.0	0	Z	LOW	30.6	3.5	33.0	47.3	-13.5	60.8	
2603.5200	53.6	40.5 A	V	1.0	270	X	LOW	30.6	3.5	33.0	41.6	-19.2	60.8	
2603.5200	56.2	43.1 A	V	1.0	270	Y	LOW	30.6	3.5	33.0	44.2	-16.6	60.8	
2603.5200	59.1	46.0 A	V	1.0	0	Z	LOW	30.6	3.5	33.0	47.1	-13.7	60.8	

* CORRECTED READING = METER READING + ANTENNA FACTOR + CABLE LOSS - AMPLIFIER GAIN
 ** DELTA = SPEC LIMIT - CORRECTED READING

RADIATED EMISSIONS (FCC SECTION 15.205 AND 15.231)

COMPANY	MYTEK KOREA	DATE	2/12/02
EUT	TRANSMITTER	DUTY CYCLE	21.90 %
MODEL	TXM-PT911	PEAK TO AVG	-13.19 dB
S/N	N/A	TEST DIST.	3 METERS
TEST ENGINEER	KYLE FUJIMOTO	LAB	D

Frequency MHz	Peak Reading (dBuV)	Average (A) or Quasi- Peak (QP)	Antenna Polar. (V or H)	Antenna Height (meters)	EUT Azimuth (degrees)	EUT Axis (X,Y,Z)	EUT Tx Channel	Antenna Factor (dB)	Cable Loss (dB)	Amplifier Gain (dB)	*Corrected Reading (dBuV/m)	Delta ** (dB)	Spec Limit (dBuV/m)	Comments	
3037.4400	64.9	51.8	A	H	1.0	0	X	LOW	31.3	4.0	31.7	55.4	-5.4	60.8	
3037.4400	59.6	46.5	A	H	2.0	0	Y	LOW	31.3	4.0	31.7	50.1	-10.7	60.8	
3037.4400	55.8	42.7	A	H	1.0	0	Z	LOW	31.3	4.0	31.7	46.3	-14.5	60.8	
3037.4400	41.1	28.0	A	V	1.0	0	X	LOW	31.3	4.0	31.7	31.6	-29.2	60.8	
3037.4400	39.2	26.1	A	V	1.0	0	Y	LOW	31.3	4.0	31.7	29.7	-31.1	60.8	
3037.4400	43.5	30.4	A	V	1.5	270	Z	LOW	31.3	4.0	31.7	34.0	-26.8	60.8	

* CORRECTED READING = METER READING + ANTENNA FACTOR + CABLE LOSS - AMPLIFIER GAIN
 ** DELTA = SPEC LIMIT - CORRECTED READING

RADIATED EMISSIONS (FCC SECTION 15.205 AND 15.231)

COMPANY	MYTEK KOREA	DATE	2/12/02
EUT	TRANSMITTER	DUTY CYCLE	21.90 %
MODEL	TXM-PT911	PEAK TO AVG	-13.19 dB
S/N	N/A	TEST DIST.	3 METERS
TEST ENGINEER	KYLE FUJIMOTO	LAB	D

Frequency MHz	Peak Reading (dBuV)	Average (A) or Quasi- Peak (QP)	Antenna Polar. (V or H)	Antenna Height (meters)	EUT Azimuth (degrees)	EUT Axis (X,Y,Z)	EUT Tx Channel	Antenna Factor (dB)	Cable Loss (dB)	Amplifier Gain (dB)	*Corrected Reading (dBuV/m)	Delta ** (dB)	Spec Limit (dBuV/m)	Comments	
3471.3600	57.1	44.0	A	H	1.0	0	X	LOW	32.2	4.9	31.6	49.6	-11.2	60.8	
3471.3600	59.3	46.2	A	H	2.0	0	Y	LOW	32.2	4.9	31.6	51.8	-9.0	60.8	
3471.3600	56.9	43.8	A	H	1.0	0	Z	LOW	32.2	4.9	31.6	49.4	-11.4	60.8	
3471.3600	39.6	26.5	A	V	1.0	0	X	LOW	32.2	4.9	31.6	32.1	-28.7	60.8	
3471.3600	40.0	26.9	A	V	2.0	90	Y	LOW	32.2	4.9	31.6	32.5	-28.3	60.8	
3471.3600	43.7	30.6	A	V	1.0	0	Z	LOW	32.2	4.9	31.6	36.2	-24.6	60.8	

* CORRECTED READING = METER READING + ANTENNA FACTOR + CABLE LOSS - AMPLIFIER GAIN
 ** DELTA = SPEC LIMIT - CORRECTED READING

RADIATED EMISSIONS (FCC SECTION 15.205 AND 15.231)

COMPANY	MYTEK KOREA	DATE	2/12/02
EUT	TRANSMITTER	DUTY CYCLE	21.90 %
MODEL	TXM-PT911	PEAK TO AVG	-13.19 dB
S/N	N/A	TEST DIST.	3 METERS
TEST ENGINEER	KYLE FUJIMOTO	LAB	D

Frequency MHz	Peak Reading (dBuV)	Average (A) or Quasi- Peak (QP)	Antenna Polar. (V or H)	Antenna Height (meters)	EUT Azimuth (degrees)	EUT Axis (X,Y,Z)	EUT Tx Channel	Antenna Factor (dB)	Cable Loss (dB)	Amplifier Gain (dB)	*Corrected Reading (dBuV/m)	Delta ** (dB)	Spec Limit (dBuV/m)	Comments	
3905.2800	45.7	32.6	A	H	1.0	0	X	LOW	32.8	4.7	31.3	38.8	-15.2	54.0	
3905.2800	49.8	36.7	A	H	3.0	0	Y	LOW	32.8	4.7	31.3	42.9	-11.1	54.0	
3905.2800	46.1	33.0	A	H	1.0	0	Z	LOW	32.8	4.7	31.3	39.2	-14.8	54.0	
3905.2800	42.0	28.9	A	V	1.0	0	X	LOW	32.8	4.7	31.3	35.1	-18.9	54.0	
3905.2800	41.6	28.5	A	V	1.0	0	Y	LOW	32.8	4.7	31.3	34.7	-19.3	54.0	
3905.2800	43.5	30.4	A	V	1.5	0	Z	LOW	32.8	4.7	31.3	36.6	-17.4	54.0	

* CORRECTED READING = METER READING + ANTENNA FACTOR + CABLE LOSS - AMPLIFIER GAIN
 ** DELTA = SPEC LIMIT - CORRECTED READING

RADIATED EMISSIONS (FCC SECTION 15.205 AND 15.231)

COMPANY	MYTEK KOREA	DATE	2/12/02
EUT	TRANSMITTER	DUTY CYCLE	21.90 %
MODEL	TXM-PT911	PEAK TO AVG	-13.19 dB
S/N	N/A	TEST DIST.	3 METERS
TEST ENGINEER	KYLE FUJIMOTO	LAB	D

Frequency MHz	Peak Reading (dBuV)	Average (A) or Quasi- Peak (QP)	Antenna Polar. (V or H)	Antenna Height (meters)	EUT Azimuth (degrees)	EUT Axis (X,Y,Z)	EUT Tx Channel	Antenna Factor (dB)	Cable Loss (dB)	Amplifier Gain (dB)	*Corrected Reading (dBuV/m)	Delta ** (dB)	Spec Limit (dBuV/m)	Comments
4339.2000	37.8	24.7 A	H	1.0	270	X	LOW	33.6	5.5	31.2	32.6	-21.4	54.0	
4339.2000	37.7	24.6 A	H	1.0	0	Y	LOW	33.6	5.5	31.2	32.5	-21.5	54.0	
4339.2000	39.1	26.0 A	H	1.0	0	Z	LOW	33.6	5.5	31.2	33.9	-20.1	54.0	
4339.2000	36.9	23.8 A	V	1.0	0	X	LOW	33.6	5.5	31.2	31.7	-22.3	54.0	
4339.2000	41.6	28.5 A	V	1.0	0	Y	LOW	33.6	5.5	31.2	36.4	-17.6	54.0	
4339.2000	42.3	29.2 A	V	1.0	0	Z	LOW	33.6	5.5	31.2	37.1	-16.9	54.0	

* CORRECTED READING = METER READING + ANTENNA FACTOR + CABLE LOSS - AMPLIFIER GAIN
 ** DELTA = SPEC LIMIT - CORRECTED READING

Page: 1 of 1

Test location: Compatible Electronics

Customer : MYTEK KOREA

Date : 2/12/2002

Manufacturer : MYTEK KOREA

Time : 16.42

EUT name : TRANSMITTER

Model : TXM-PT911

Specification: Fcc_B Test distance: 3.0 mtrs Lab: D

Distance correction factor($20 \cdot \log(\text{test}/\text{spec})$) : 0.00

Test Mode :

SPURIOUS EMISSIONS -- 10 kHz TO 4400 MHz

HORIZONTAL AND VERTICAL POLARIZATION

TEMPERATURE 76 DEGREES F., RELATIVE HUMIDITY 11%

TESTED BY: KYLE FUJIMOTO

NO SPURIOUS EMISSIONS FOUND FROM THE EUT FROM 10 kHz TO 1000 MHz
IN EITHER POLARIZATION



-20 dB BANDWIDTH

DATA SHEET



hp -20 dB BANDWIDTH OF FUNDAMENTAL
REF 97.0 dB μ V ATTN 0 dB

MKR Δ 483 kHz
1.50 dB

10 dB/

DL
61.1
dB μ V

MARKER Δ
483 kHz
1.50 dB

CORR'D

CENTER 433.66 MHz
RES BW 1 MHz

VBW 1 MHz

SPAN 1.00 MHz
SWP 20.0 msec

