July 25, 2025

FCC ID: MMFTPURID2100

To whom it may concern,

We, UL Japan, Inc, hereby declare that UHF RFID Module, model: TPURID2100 (FCC ID: MMFTPURID2100) of SATO CORPORATION is exempt from RF exposure SAR evaluation because the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula according to the Code of Federal Regulation title 47 section 1.1307(b)(3)(i)(B). This method is used at separation distances *d* (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive) for single RF sources. P_{th} is given by:

$$P_{th}\ (\mathrm{mW}) = \begin{cases} ERP_{20\ \mathrm{cm}}\ (d\ /\ 20\ \mathrm{cm})^{x} & d \leq 20\ \mathrm{cm} \\ ERP_{20\ \mathrm{cm}} & 20\ \mathrm{cm}\ <\ d\ \leq\ 40\ \mathrm{cm} \end{cases}$$

Where

$$x = -\log_{10}\left(\frac{60}{ERP_{20\ \mathrm{cm}}\sqrt{f}}\right) \text{and } f \text{ is in GHz}$$

$$ERP_{20\ \mathrm{cm}}\ (\mathrm{mW}) = \begin{cases} 2040f & 0.3\ \mathrm{GHz} \leq f < 1.5\ \mathrm{GHz} \\ 3060 & 1.5\ \mathrm{GHz} \leq f \leq 6\ \mathrm{GHz} \end{cases}$$

When the minimum separation distance is shorter than 0.5 cm, 0.5 cm is applied.

The SAR evaluation exemption threshold is calculated as below.

Pth (mW)	1891.6
f (GHz)	0.9273
ERP $_{20\ \mathrm{cm}}$ (mW)	1891.6
d (cm)	20.0

Conducted Power	(dBm)	30.00
	(mW)	1000.00
Antenna Gain (dBi)		-15.02
EIRP (dBm)		14.98
ERP	(dBm)	12.84
	(mW)	19.23

The Maximum time-averaged power or ERP whichever greater is 1000 mW.
(Rounded up to two decimals place)

Thank you for your attention to this matter.

K. Takeyama

Kazutaka Takeyama
Leader

UL Japan, Inc. Shonan EMC Lab.
1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 Japan
T: +81-463-50-6400