

# TEST REPORT

**Application No.:** GZCR2309000966AT  
**Applicant:** DOREL JUVENILE GROUP  
**Address of Applicant:** 2525 State Street Columbus Indiana United States  
**Manufacturer:** DOREL JUVENILE GROUP  
**Address of Manufacturer:** 2525 State Street Columbus Indiana United States  
**Factory:** Hangzhou Meari Technology Co., Ltd  
**Address of Factory:** Room 604-605, Building 1, No.768 Jianghong Road, Changhe street, Binjiang District, Hangzhou City, Zhejiang, China

### Equipment Under Test (EUT):

**EUT Name:** See Pro 360° Baby Monitor (Camera unit)  
**Model No.:** MO183  
**Trade Mark:** MAXI·COSI  
**Standard(s) :** 47 CFR Part 15, Subpart C 15.247  
**Date of Receipt:** 2023-09-18  
**Date of Test:** 2023-09-22 to 2023-11-02  
**Date of Issue:** 2023-11-07

|                     |              |
|---------------------|--------------|
| <b>Test Result:</b> | <b>Pass*</b> |
|---------------------|--------------|

\* In the configuration tested, the EUT complied with the standards specified above.

*Ricky Liu*

Ricky Liu  
Manager



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

| Revision Record |                  |            |          |
|-----------------|------------------|------------|----------|
| Version         | Report No.       | Date       | Remark   |
| 01              | GZCR230900096603 | 2023-11-07 | Original |
|                 |                  |            |          |
|                 |                  |            |          |

|                         |  |                              |  |
|-------------------------|--|------------------------------|--|
| Authorized for issue by |  |                              |  |
|                         |  | Kevin Zhang                  |  |
|                         |  | Kevin Zhang/Project Engineer |  |
|                         |  | Vico Cui                     |  |
|                         |  | Vico Cui/Reviewer            |  |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

## 2 Test Summary

| Radio Spectrum Technical Requirement |                                  |        |                                                 |        |
|--------------------------------------|----------------------------------|--------|-------------------------------------------------|--------|
| Item                                 | Standard                         | Method | Requirement                                     | Result |
| Antenna Requirement                  | 47 CFR Part 15, Subpart C 15.247 | N/A    | 47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4) | Pass   |

| Radio Spectrum Matter Part                            |                                  |                                      |                                           |        |
|-------------------------------------------------------|----------------------------------|--------------------------------------|-------------------------------------------|--------|
| Item                                                  | Standard                         | Method                               | Requirement                               | Result |
| Conducted Emissions at AC Power Line (150kHz-30MHz)   | 47 CFR Part 15, Subpart C 15.247 | ANSI C63.10 (2013) Section 6.2       | 47 CFR Part 15, Subpart C 15.207          | Pass   |
| Conducted Peak Output Power                           |                                  | ANSI C63.10 (2013) Section 11.9.2    | 47 CFR Part 15, Subpart C 15.247(b)(3)    | Pass   |
| Minimum 6dB Bandwidth                                 |                                  | ANSI C63.10 (2013) Section 11.8.1    | 47 CFR Part 15, Subpart C 15.247a(2)      | Pass   |
| Power Spectrum Density                                |                                  | ANSI C63.10 (2013) Section 11.10.2   | 47 CFR Part 15, Subpart C 15.247(e)       | Pass   |
| Conducted Band Edges Measurement                      |                                  | ANSI C63.10 (2013) Section 11.13.3.2 | 47 CFR Part 15, Subpart C 15.247(d)       | Pass   |
| Conducted Spurious Emissions                          |                                  | ANSI C63.10 (2013) Section 11.11     | 47 CFR Part 15, Subpart C 15.247(d)       | Pass   |
| Radiated Emissions which fall in the restricted bands |                                  | ANSI C63.10 (2013) Section 11.12     | 47 CFR Part 15, Subpart C 15.205 & 15.209 | Pass** |
| Radiated Spurious Emissions Below 1GHz                |                                  | ANSI C63.10 (2013) Section 6.4,6.5   | 47 CFR Part 15, Subpart C 15.205 & 15.209 | Pass   |
| Radiated Spurious Emissions Above 1GHz                |                                  | ANSI C63.10 (2013) Section 6.6       | 47 CFR Part 15, Subpart C 15.205 & 15.209 | Pass** |

**Note:**

E.U.T./EUT means Equipment Under Test.

Pass means the test result passed the test standard requirement, please find the detailed decision rule in the report relative section.

\*\* : The EUT passed the Radiated Emissions which fall in the restricted bands and Radiated Spurious Emissions Above 1GHz test after modifications.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

## 3 Contents

|                                                              | Page |
|--------------------------------------------------------------|------|
| 1 Cover Page .....                                           | 1    |
| 2 Test Summary .....                                         | 3    |
| 3 Contents .....                                             | 4    |
| 4 General Information.....                                   | 6    |
| 4.1 Details of E.U.T. ....                                   | 6    |
| 4.2 Description of Support Units .....                       | 6    |
| 4.3 Measurement Uncertainty .....                            | 7    |
| 4.4 Test Location.....                                       | 7    |
| 4.5 Test Facility .....                                      | 8    |
| 4.6 Deviation from Standards.....                            | 8    |
| 4.7 Abnormalities from Standard Conditions .....             | 8    |
| 5 Equipment List .....                                       | 9    |
| 6 Radio Spectrum Technical Requirement .....                 | 12   |
| 6.1 Antenna Requirement .....                                | 12   |
| 6.1.1 Test Requirement: .....                                | 12   |
| 6.1.2 Conclusion .....                                       | 12   |
| 7 Radio Spectrum Matter Test Results .....                   | 13   |
| 7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)..... | 13   |
| 7.1.1 E.U.T. Operation .....                                 | 13   |
| 7.1.2 Test Mode Description .....                            | 13   |
| 7.1.3 Test Setup Diagram.....                                | 14   |
| 7.1.4 Measurement Procedure and Data.....                    | 14   |
| 7.2 Conducted Peak Output Power.....                         | 17   |
| 7.2.1 E.U.T. Operation .....                                 | 17   |
| 7.2.2 Test Mode Description .....                            | 17   |
| 7.2.3 Test Setup Diagram .....                               | 18   |
| 7.2.4 Measurement Procedure and Data.....                    | 18   |
| 7.3 Minimum 6dB Bandwidth .....                              | 19   |
| 7.3.1 E.U.T. Operation .....                                 | 19   |
| 7.3.2 Test Mode Description .....                            | 19   |
| 7.3.3 Test Setup Diagram .....                               | 19   |
| 7.3.4 Measurement Procedure and Data.....                    | 19   |
| 7.4 Power Spectrum Density.....                              | 20   |
| 7.4.1 E.U.T. Operation .....                                 | 20   |
| 7.4.2 Test Mode Description .....                            | 20   |
| 7.4.3 Test Setup Diagram .....                               | 20   |
| 7.4.4 Measurement Procedure and Data.....                    | 20   |
| 7.5 Conducted Band Edges Measurement .....                   | 21   |
| 7.5.1 E.U.T. Operation .....                                 | 21   |
| 7.5.2 Test Mode Description .....                            | 21   |
| 7.5.3 Test Setup Diagram .....                               | 22   |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

|       |                                                             |    |
|-------|-------------------------------------------------------------|----|
| 7.5.4 | Measurement Procedure and Data.....                         | 22 |
| 7.6   | Conducted Spurious Emissions .....                          | 23 |
| 7.6.1 | E.U.T. Operation .....                                      | 23 |
| 7.6.2 | Test Mode Description .....                                 | 23 |
| 7.6.3 | Test Setup Diagram .....                                    | 24 |
| 7.6.4 | Measurement Procedure and Data.....                         | 24 |
| 7.7   | Radiated Emissions which fall in the restricted bands ..... | 25 |
| 7.7.1 | E.U.T. Operation .....                                      | 25 |
| 7.7.2 | Test Mode Description .....                                 | 25 |
| 7.7.3 | Test Setup Diagram .....                                    | 26 |
| 7.7.4 | Measurement Procedure and Data.....                         | 26 |
| 7.8   | Radiated Spurious Emissions Below 1GHz .....                | 39 |
| 7.8.1 | E.U.T. Operation .....                                      | 39 |
| 7.8.2 | Test Mode Description .....                                 | 39 |
| 7.8.3 | Test Setup Diagram .....                                    | 40 |
| 7.8.4 | Measurement Procedure and Data.....                         | 40 |
| 7.9   | Radiated Spurious Emissions Above 1GHz.....                 | 49 |
| 7.9.1 | E.U.T. Operation .....                                      | 49 |
| 7.9.2 | Test Mode Description .....                                 | 49 |
| 7.9.3 | Test Setup Diagram .....                                    | 49 |
| 7.9.4 | Measurement Procedure and Data.....                         | 50 |
| 8     | Test Setup Photo .....                                      | 75 |
| 9     | EUT Constructional Details (EUT Photos) .....               | 76 |
| 10    | Appendix.....                                               | 77 |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

## 4 General Information

### 4.1 Details of E.U.T.

Power supply: DC 5 V for camera powered by AC/DC adapter as below:  
Model: TPA-97050100VW01  
Input: AC 100-240 V, 50/60 Hz, 0.15A  
Output: DC 5 V, 1 A

Cable(s): Type C input ports with 2m unshielded cables  
SD card ports

Test Voltage: AC 120 V, 60 Hz

Antenna Number: 2 (one for 902 MHz to 925 MHz RF and the other for 2.4/5 GHz Wi-Fi)  
For 2.4 GHz Wi-Fi

Operation Frequency: 802.11b/g/n(HT20): 2412MHz to 2462MHz

Modulation Type: 802.11b: DSSS (CCK, DQPSK, DBPSK);802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)

Number of Channels: 802.11b/g/n(HT20):11

Channel Spacing: 5MHz

Antenna Type: Integral Antenna

Antenna Gain: 2.25 dBi

For 902 MHz to 925 MHz RF

Operation Frequency: 905 MHz to 925 MHz

Modulation Type: 802.11ah: OFDM (64QAM, 16QAM, QPSK, BPSK)

Number of Channels: 11

Channel Spacing: 5 MHz

Antenna Type: Integral Antenna

Antenna Gain: -0.76 dBi

### 4.2 Description of Support Units

| Description        | Manufacturer | Model No.     | Serial No. |
|--------------------|--------------|---------------|------------|
| Note Book Computer | LENOVO       | ThinkPad T490 | PF1D1MVJ   |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

### 4.3 Measurement Uncertainty

| Test Item                                                                                                                                                                                                                                                                                                                    | Measurement Uncertainty                                                                                             |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| Conducted Emissions at AC Power Line (150kHz-30MHz)                                                                                                                                                                                                                                                                          | ±2.76dB                                                                                                             |
| Conducted Peak Output Power                                                                                                                                                                                                                                                                                                  | ± 0.75dB                                                                                                            |
| Minimum 6dB Bandwidth                                                                                                                                                                                                                                                                                                        | ± 3%                                                                                                                |
| Power Spectrum Density                                                                                                                                                                                                                                                                                                       | ± 2.84dB                                                                                                            |
| Conducted Band Edges Measurement                                                                                                                                                                                                                                                                                             | ± 0.75dB                                                                                                            |
| Conducted Spurious Emissions                                                                                                                                                                                                                                                                                                 | ± 0.75dB                                                                                                            |
| Radiated Emissions which fall in the restricted bands                                                                                                                                                                                                                                                                        | ±5.00dB (30MHz-1GHz; 3m);±4.38dB (30MHz-1GHz; 10m);± 5.12dB (1GHz-6GHz); ±5.38dB (6GHz-18GHz); ±5.61dB(18GHz-40GHz) |
| Radiated Spurious Emissions Below 1GHz                                                                                                                                                                                                                                                                                       | ±5.00dB (3m); ±4.38dB (10m)                                                                                         |
| Radiated Spurious Emissions Above 1GHz                                                                                                                                                                                                                                                                                       | ±5.12dB (1GHz-6GHz); ±5.38dB (6GHz-18GHz); ±5.61dB(18GHz-40GHz)                                                     |
| <b>Remark:</b><br>The $U_{lab}$ (lab Uncertainty) is less than $U_{ETSI}$ (ETSI Uncertainty), so the test results<br>– compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;<br>– non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit. |                                                                                                                     |

### 4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou Branch EMC Laboratory,  
198 Kezhu Road, Sciencetech Park, Guangzhou Economic & Technology Development District,  
Guangzhou, China 510663

Tel: +86 20 82155555

Fax: +86 20 82075059

No tests were sub-contracted.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

## 4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **ACMA**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian/New Zealand Regulatory Compliance Mark (RCM).

- **SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FIMKO**

Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.

- **FCC Recognized Accredited Test Firm(Registration No.: 486818)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been accredited and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation Number: CN5016, Test Firm Registration Number: 486818.

- **ISED (Registration No.: 4620B, CAB identifier: CN0052)**

SGS-CSTC Standards Technical Services Co., Ltd., has been registered by Innovation Science and Economic Development Canada for Wireless Device Testing laboratories to test to Canadian radio equipment requirements. Registration No. 4620B, CAB identifier: CN0052.

- **VCCI (Registration No.: R-12460, C-12584, G-20107 and T-11179)**

The 10m Semi-anechoic chamber, 966 Anechoic Chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-12460, C-12584, G-20107 and T-11179 respectively.

- **CBTL (Lab Code: TL129)**

SGS-CSTC Standards Technical Services Co., Ltd., E&E Laboratory has been assessed and fully comply with the requirements of ISO/IEC 17025:2017, the Basic Rules, IECEE 01 and Rules of procedure IECEE 02, and the relevant IECEE CB-Scheme Operational documents.

## 4.6 Deviation from Standards

None

## 4.7 Abnormalities from Standard Conditions

The EUT passed the Radiated Emissions which fall in the restricted bands and Radiated Spurious Emissions Above 1GHz test after modifications.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

## 5 Equipment List

| Conducted Emissions at AC Power Line (150kHz-30MHz) |                   |                |               |            |              |
|-----------------------------------------------------|-------------------|----------------|---------------|------------|--------------|
| Equipment                                           | Manufacturer      | Model No.      | Inventory No. | Cal Date   | Cal Due Date |
| Coaxial Cable                                       | HangTianXing      | 2m             | EMC0107       | 2023-08-04 | 2024-08-03   |
| Shielding Room                                      | ChangZhou ZhongYu | 8m x 3m x 3.8m | EMC0306       | 2022-10-16 | 2025-10-15   |
| Two-Line V-Network-GZ                               | Rohde & Schwarz   | ENV216         | EMC2135       | 2023-09-08 | 2024-09-07   |
| EMI Test Receiver (9kHz-3.6GHz)                     | Rohde & Schwarz   | ESR3           | EMC2221       | 2023-05-19 | 2024-05-18   |
| Test Software E3r                                   | Audix             | Ver.6.11812    | GZE100-77     | N/A        | N/A          |

| Conducted Peak Output Power      |              |           |               |            |              |
|----------------------------------|--------------|-----------|---------------|------------|--------------|
| Equipment                        | Manufacturer | Model No. | Inventory No. | Cal Date   | Cal Due Date |
| MI CABLE                         | SGS-EMC      | 0.8M      | EMC2137       | 2021-11-02 | 2023-11-01   |
| EXA Signal Analyzer (10Hz-44GHz) | Keysight     | N9010A    | EMC2138       | 2023-08-23 | 2024-08-22   |
| 4X4 Power sensor Unit            | TST          | TSPS2023R | EMC2226       | 2023-08-23 | 2024-08-22   |
| Test Software                    | TST          | V2.0      | GZE100-78     | N/A        | N/A          |

| Minimum 6dB Bandwidth            |              |           |               |            |              |
|----------------------------------|--------------|-----------|---------------|------------|--------------|
| Equipment                        | Manufacturer | Model No. | Inventory No. | Cal Date   | Cal Due Date |
| MI CABLE                         | SGS-EMC      | 0.8M      | EMC2137       | 2021-11-02 | 2023-11-01   |
| EXA Signal Analyzer (10Hz-44GHz) | Keysight     | N9010A    | EMC2138       | 2023-08-23 | 2024-08-22   |
| 4X4 Power sensor Unit            | TST          | TSPS2023R | EMC2226       | 2023-08-23 | 2024-08-22   |
| Test Software                    | TST          | V2.0      | GZE100-78     | N/A        | N/A          |

| Power Spectrum Density           |              |           |               |            |              |
|----------------------------------|--------------|-----------|---------------|------------|--------------|
| Equipment                        | Manufacturer | Model No. | Inventory No. | Cal Date   | Cal Due Date |
| MI CABLE                         | SGS-EMC      | 0.8M      | EMC2137       | 2021-11-02 | 2023-11-01   |
| EXA Signal Analyzer (10Hz-44GHz) | Keysight     | N9010A    | EMC2138       | 2023-08-23 | 2024-08-22   |
| 4X4 Power sensor Unit            | TST          | TSPS2023R | EMC2226       | 2023-08-23 | 2024-08-22   |
| Test Software                    | TST          | V2.0      | GZE100-78     | N/A        | N/A          |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

| Conducted Band Edges Measurement |              |           |               |            |              |
|----------------------------------|--------------|-----------|---------------|------------|--------------|
| Equipment                        | Manufacturer | Model No. | Inventory No. | Cal Date   | Cal Due Date |
| MI CABLE                         | SGS-EMC      | 0.8M      | EMC2137       | 2021-11-02 | 2023-11-01   |
| EXA Signal Analyzer (10Hz-44GHz) | Keysight     | N9010A    | EMC2138       | 2023-08-23 | 2024-08-22   |
| 4X4 Power sensor Unit            | TST          | TSPS2023R | EMC2226       | 2023-08-23 | 2024-08-22   |
| Test Software                    | TST          | V2.0      | GZE100-78     | N/A        | N/A          |

| Conducted Spurious Emissions     |              |           |               |            |              |
|----------------------------------|--------------|-----------|---------------|------------|--------------|
| Equipment                        | Manufacturer | Model No. | Inventory No. | Cal Date   | Cal Due Date |
| MI CABLE                         | SGS-EMC      | 0.8M      | EMC2137       | 2021-11-02 | 2023-11-01   |
| EXA Signal Analyzer (10Hz-44GHz) | Keysight     | N9010A    | EMC2138       | 2023-08-23 | 2024-08-22   |
| 4X4 Power sensor Unit            | TST          | TSPS2023R | EMC2226       | 2023-08-23 | 2024-08-22   |
| Test Software                    | TST          | V2.0      | GZE100-78     | N/A        | N/A          |

| Radiated Emissions which fall in the restricted bands |                             |               |               |            |              |
|-------------------------------------------------------|-----------------------------|---------------|---------------|------------|--------------|
| Equipment                                             | Manufacturer                | Model No.     | Inventory No. | Cal Date   | Cal Due Date |
| 1GHz-26.5 GHz Pre-Amplifier                           | Agilent                     | 8449B         | EMC0521       | 2022-12-16 | 2023-12-15   |
| EMI Test Receiver (10Hz-26.5GHz)                      | Rohde & Schwarz             | ESIB26        | EMC0522       | 2022-12-16 | 2023-12-15   |
| Chamber cable (Above 1GHz)                            | Scoflex                     | KMKM-8.0m     | EMC0545       | 2022-08-24 | 2024-08-23   |
| Horn Antenna (1GHz-18GHz)                             | SCHWARZBECK MESS-ELEKTRONIK | BBHA 9120D    | EMC2026       | 2022-09-23 | 2025-09-22   |
| Horn Antenna (14-40GHz)                               | SCHWARZBECK                 | BBHA 9170     | EMC2041       | 2023-06-18 | 2026-06-17   |
| EXA Signal Analyzer (10Hz-44GHz)                      | Keysight                    | N9010A        | EMC2138       | 2023-08-23 | 2024-08-22   |
| MXE EMI Receiver (10Hz-8.4GHz)                        | Keysight                    | N9038A        | EMC2139       | 2023-10-20 | 2024-10-19   |
| 966 Anechoic Chamber                                  | C.R.T                       | 9m x 6m x 6m  | EMC2142       | 2020-12-20 | 2023-12-19   |
| Test Software E3                                      | Audix                       | Ver.6.120110a | GZE100-61     | N/A        | N/A          |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

| Radiated Spurious Emissions Below 1GHz |                       |               |               |            |              |
|----------------------------------------|-----------------------|---------------|---------------|------------|--------------|
| Equipment                              | Manufacturer          | Model No.     | Inventory No. | Cal Date   | Cal Due Date |
| 966 Anechoic Chamber                   | Shenzhen C.R.T        | CRTSGSSAC966  | EMC2230       | 2022-04-12 | 2025-04-11   |
| EMI Test Receiver(1Hz-8GHz)            | Rohde & Schwarz       | ESW8          | EMC2229       | 2023-02-20 | 2024-02-19   |
| Amplifier(9k-1000MHz)                  | SONOMA                | 310           | EMC2237       | 2023-04-13 | 2024-04-12   |
| TRILOG Broadband Antenna (25M-2GHz)    | SCHWRZBECK            | VULB 9168     | EMC2238       | 2022-04-20 | 2025-04-19   |
| Coaxial Cable                          | Mirco-COAX UTIFLEX ve | LA2-C125-8000 | EMC2239       | 2023-06-14 | 2025-06-13   |
| Test Software E3                       | Audix                 | Ver.6.191211  | GZE100-81     | N/A        | N/A          |
| Active Loop Antenna-RED                | ETS-Lindgren          | 6502          | EMC2190       | 2022-04-06 | 2024-04-05   |

| Radiated Spurious Emissions Above 1GHz |                             |               |               |            |              |
|----------------------------------------|-----------------------------|---------------|---------------|------------|--------------|
| Equipment                              | Manufacturer                | Model No.     | Inventory No. | Cal Date   | Cal Due Date |
| 1GHz-26.5 GHz Pre-Amplifier            | Agilent                     | 8449B         | EMC0521       | 2022-12-16 | 2023-12-15   |
| EMI Test Receiver (10Hz-26.5GHz)       | Rohde & Schwarz             | ESIB26        | EMC0522       | 2022-12-16 | 2023-12-15   |
| Chamber cable (Above 1GHz)             | Scoflex                     | KMKM-8.0m     | EMC0545       | 2022-08-24 | 2024-08-23   |
| Horn Antenna (1GHz-18GHz)              | SCHWARZBECK MESS-ELEKTRONIK | BBHA 9120D    | EMC2026       | 2022-09-23 | 2025-09-22   |
| Horn Antenna (14-40GHz)                | SCHWARZBECK                 | BBHA 9170     | EMC2041       | 2023-06-18 | 2026-06-17   |
| 2.4GHz Filter                          | Micro-Tronics               | BRM 50702     | EMC2069       | 2022-12-16 | 2023-12-15   |
| EXA Signal Analyzer (10Hz-44GHz)       | Keysight                    | N9010A        | EMC2138       | 2023-08-23 | 2024-08-22   |
| MXE EMI Receiver (10Hz-8.4GHz)         | Keysight                    | N9038A        | EMC2139       | 2023-10-20 | 2024-10-19   |
| 966 Anechoic Chamber                   | C.R.T                       | 9m x 6m x 6m  | EMC2142       | 2020-12-20 | 2023-12-19   |
| Test Software E3                       | Audix                       | Ver.6.120110a | GZE100-61     | N/A        | N/A          |

| General used equipment |              |          |              |            |              |
|------------------------|--------------|----------|--------------|------------|--------------|
| Equipment              | Manufacturer | Model No | Inventory No | Cal Date   | Cal Due Date |
| DMM                    | Fluke        | 73       | EMC0006      | 2023-06-11 | 2024-06-10   |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

## 6 Radio Spectrum Technical Requirement

### 6.1 Antenna Requirement

#### 6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

#### 6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is -0.76 dBi for 905-925MHz RF and 2.25 dBi for 2.4 GHz Wi-Fi.

Antenna location: Refer to internal photo.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

## 7 Radio Spectrum Matter Test Results

### 7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207

Test Method: ANSI C63.10 (2013) Section 6.2

Limit:

| Frequency of emission<br>(MHz)                                         | Conducted limit (dBμV) |           |
|------------------------------------------------------------------------|------------------------|-----------|
|                                                                        | Quasi-peak             | Average   |
| 0.15-0.5                                                               | 66 to 56*              | 56 to 46* |
| 0.5-5                                                                  | 56                     | 46        |
| 5-30                                                                   | 60                     | 50        |
| *Decreases with the logarithm of the frequency.                        |                        |           |
| Detector: Peak for pre-scan (9kHz resolution bandwidth) 0.15M to 30MHz |                        |           |

#### 7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 24.8 °C

Humidity: 55.8 % RH

Atmospheric Pressure: 1000 mbar

#### 7.1.2 Test Mode Description

| Pre-scan /<br>Final test | Mode<br>Code | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|--------------------------|--------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Final test               | 00           | TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report. |
| Final test               | 10           | Charge + TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6.5Mbps is the worst case of IEEE 802.11ah, final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report for camera.                                                                                            |




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)



Test Mode: 00 & 10; Line: Live line



Pol : LINE  
Mode :  
Model :  
Power :


|    | Frequency<br>MHz | Read<br>Level<br>dBuV | Cable<br>Loss<br>dB | LISN<br>Factor<br>dB | Measured<br>Level<br>dBuV | Limit<br>Line<br>dBuV | Over<br>Limit<br>dB | Remark  |
|----|------------------|-----------------------|---------------------|----------------------|---------------------------|-----------------------|---------------------|---------|
| 1  | 0.192            | 21.55                 | 0.04                | 9.61                 | 31.20                     | 53.93                 | -22.73              | Average |
| 2  | 0.192            | 36.20                 | 0.04                | 9.61                 | 45.85                     | 63.93                 | -18.08              | QP      |
| 3  | 0.256            | 24.79                 | 0.04                | 9.61                 | 34.44                     | 51.56                 | -17.12              | Average |
| 4  | 0.256            | 36.33                 | 0.04                | 9.61                 | 45.98                     | 61.56                 | -15.58              | QP      |
| 5  | 0.601            | 31.78                 | 0.06                | 9.61                 | 41.45                     | 46.00                 | -4.55               | Average |
| 6  | 0.601            | 43.20                 | 0.06                | 9.61                 | 52.87                     | 56.00                 | -3.13               | QP      |
| 7  | 1.197            | 25.30                 | 0.08                | 9.60                 | 34.98                     | 46.00                 | -11.02              | Average |
| 8  | 1.197            | 37.68                 | 0.08                | 9.60                 | 47.36                     | 56.00                 | -8.64               | QP      |
| 9  | 2.636            | 25.88                 | 0.15                | 9.62                 | 35.65                     | 46.00                 | -10.35              | Average |
| 10 | 2.636            | 35.95                 | 0.15                | 9.62                 | 45.72                     | 56.00                 | -10.28              | QP      |
| 11 | 5.993            | 21.87                 | 0.21                | 9.66                 | 31.74                     | 50.00                 | -18.26              | Average |
| 12 | 5.993            | 33.19                 | 0.21                | 9.66                 | 43.06                     | 60.00                 | -16.94              | QP      |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 00 & 10; Line: Neutral Line



Pol : NEUTRAL  
Mode :  
Model :  
Power :

|    | Frequency<br>MHz | Read<br>Level<br>dBuV | Cable<br>Loss<br>dB | LISN<br>Factor<br>dB | Measured<br>Level<br>dBuV | Limit<br>Line<br>dBuV | Over<br>Limit<br>dB | Remark  |
|----|------------------|-----------------------|---------------------|----------------------|---------------------------|-----------------------|---------------------|---------|
| 1  | 0.168            | 21.31                 | 0.04                | 9.60                 | 30.95                     | 55.08                 | -24.13              | Average |
| 2  | 0.168            | 39.91                 | 0.04                | 9.60                 | 49.55                     | 65.08                 | -15.53              | QP      |
| 3  | 0.255            | 20.73                 | 0.04                | 9.61                 | 30.38                     | 51.60                 | -21.22              | Average |
| 4  | 0.255            | 35.45                 | 0.04                | 9.61                 | 45.10                     | 61.60                 | -16.50              | QP      |
| 5  | 0.354            | 20.76                 | 0.05                | 9.62                 | 30.43                     | 48.87                 | -18.44              | Average |
| 6  | 0.354            | 34.44                 | 0.05                | 9.62                 | 44.11                     | 58.87                 | -14.76              | QP      |
| 7  | 0.598            | 22.32                 | 0.06                | 9.62                 | 32.00                     | 46.00                 | -14.00              | Average |
| 8  | 0.598            | 37.53                 | 0.06                | 9.62                 | 47.21                     | 56.00                 | -8.79               | QP      |
| 9  | 4.622            | 17.71                 | 0.19                | 9.65                 | 27.55                     | 46.00                 | -18.45              | Average |
| 10 | 4.622            | 29.92                 | 0.19                | 9.65                 | 39.76                     | 56.00                 | -16.24              | QP      |
| 11 | 6.186            | 18.36                 | 0.21                | 9.67                 | 28.24                     | 50.00                 | -21.76              | Average |
| 12 | 6.186            | 27.01                 | 0.21                | 9.67                 | 36.89                     | 60.00                 | -23.11              | QP      |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

## 7.2 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)

Test Method: ANSI C63.10 (2013) Section 11.9.2

Limit:

| Frequency range(MHz) | Output power of the intentional radiator(watt)         |
|----------------------|--------------------------------------------------------|
| 902-928              | 1 for $\geq 50$ hopping channels                       |
|                      | 0.25 for $25 \leq$ hopping channels $< 50$             |
|                      | 1 for digital modulation                               |
| 2400-2483.5          | 1 for $\geq 75$ non-overlapping hopping channels       |
|                      | 0.125 for all other frequency hopping systems          |
|                      | 1 for digital modulation                               |
| 5725-5850            | 1 for frequency hopping systems and digital modulation |

### 7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 24.0 °C

Humidity: 64.6 % RH

Atmospheric Pressure: 1007 mbar

### 7.2.2 Test Mode Description


| Pre-scan /<br>Final test | Mode<br>Code | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|--------------------------|--------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Final test               | 00           | TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report. |
| Final test               | 09           | TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6.5Mbps is the worst case of IEEE 802.11ah, final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.                                                                                                                |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

### 7.2.3 Test Setup Diagram



### 7.2.4 Measurement Procedure and Data

Note: Since the verify power the same operating range bandwidth and smaller power can be covered by the higher power.

Please Refer to Appendix for Details



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

### 7.3 Minimum 6dB Bandwidth

|                  |                                      |
|------------------|--------------------------------------|
| Test Requirement | 47 CFR Part 15, Subpart C 15.247a(2) |
| Test Method:     | ANSI C63.10 (2013) Section 11.8.1    |
| Limit:           | ≥500 kHz                             |

#### 7.3.1 E.U.T. Operation


Operating Environment:

Temperature: 24.0 °C Humidity: 64.6 % RH Atmospheric Pressure: 1007 mbar

#### 7.3.2 Test Mode Description

| Pre-scan /<br>Final test | Mode<br>Code | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|--------------------------|--------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Final test               | 00           | TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report. |
| Final test               | 09           | TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6.5Mbps is the worst case of IEEE 802.11ah, final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.                                                                                                                |

#### 7.3.3 Test Setup Diagram



#### 7.3.4 Measurement Procedure and Data

Please Refer to Appendix for Details



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

### 7.4 Power Spectrum Density

|                  |                                                                             |
|------------------|-----------------------------------------------------------------------------|
| Test Requirement | 47 CFR Part 15, Subpart C 15.247(e)                                         |
| Test Method:     | ANSI C63.10 (2013) Section 11.10.2                                          |
| Limit:           | ≤8dBm in any 3 kHz band during any time interval of continuous transmission |

#### 7.4.1 E.U.T. Operation


Operating Environment:

Temperature: 24.0 °C Humidity: 64.6 % RH Atmospheric Pressure: 1007 mbar

#### 7.4.2 Test Mode Description

| Pre-scan /<br>Final test | Mode<br>Code | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|--------------------------|--------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Final test               | 00           | TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report. |
| Final test               | 09           | TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6.5Mbps is the worst case of IEEE 802.11ah, final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.                                                                                                                |

#### 7.4.3 Test Setup Diagram



#### 7.4.4 Measurement Procedure and Data

Please Refer to Appendix for Details



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

### 7.5 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2013) Section 11.13.3.2

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

#### 7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 24.0 °C Humidity: 64.6 % RH Atmospheric Pressure: 1007 mbar

#### 7.5.2 Test Mode Description


| Pre-scan /<br>Final test | Mode<br>Code | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|--------------------------|--------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Final test               | 00           | TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report. |
| Final test               | 09           | TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6.5Mbps is the worst case of IEEE 802.11ah, final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.                                                                                                                |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

### 7.5.3 Test Setup Diagram



### 7.5.4 Measurement Procedure and Data

Please Refer to Appendix for Details



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

### 7.6 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2013) Section 11.11

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

#### 7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 24.0 °C

Humidity: 64.6 % RH

Atmospheric Pressure: 1007 mbar

#### 7.6.2 Test Mode Description


| Pre-scan /<br>Final test | Mode<br>Code | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|--------------------------|--------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Final test               | 00           | TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report. |
| Final test               | 09           | TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6.5Mbps is the worst case of IEEE 802.11ah, final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.                                                                                                                |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

### 7.6.3 Test Setup Diagram



### 7.6.4 Measurement Procedure and Data

Please Refer to Appendix for Details



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

### 7.7 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 11.12

Limit:

Test Distance: 3 m

| Frequency (MHz) | Field strength (microvolts/meter) | Measurement distance(meters) |
|-----------------|-----------------------------------|------------------------------|
| 0.009-0.490     | 2400/F(kHz)                       | 300                          |
| 0.490-1.705     | 24000/F(kHz)                      | 30                           |
| 1.705-30.0      | 30                                | 30                           |
| 30-88           | 100                               | 3                            |
| 88-216          | 150                               | 3                            |
| 216-960         | 200                               | 3                            |
| Above 960       | 500                               | 3                            |

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

#### 7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 24.0 °C

Humidity: 54.0 % RH

Atmospheric Pressure: 1016 mbar

#### 7.7.2 Test Mode Description

**Pre-scan / Mode**  
**Final test Code Description**

**Final test 00** TX mode\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.


**Final test 09** TX mode\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6.5Mbps is the worst case of IEEE 802.11ah, final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report for camera. Please refer to the section 7.8 for test data.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

### 7.7.3 Test Setup Diagram



### 7.7.4 Measurement Procedure and Data

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor


Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 00; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)


|     | Freq     | ReadAntenna | Cable  | Preamp | Limit  | Over   |        |           |               |
|-----|----------|-------------|--------|--------|--------|--------|--------|-----------|---------------|
|     | MHz      | Level       | Factor | Loss   | Factor | Line   | Limit  | Pol/Phase | Remark        |
|     | MHz      | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB        |               |
| 1   | 2376.090 | 52.87       | 27.66  | 3.76   | 37.77  | 46.52  | 74.00  | -27.48    | VERTICAL Peak |
| 2   | 2390.000 | 51.88       | 27.68  | 3.77   | 37.76  | 45.57  | 74.00  | -28.43    | VERTICAL Peak |
| 3 * | 2412.000 | 110.00      | 27.74  | 3.79   | 37.76  | 103.77 | 74.00  | 29.77     | VERTICAL Peak |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 00; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)


|     | Freq     | ReadAntenna | Cable  | Preamp | Limit  | Over   |        |        |                 |
|-----|----------|-------------|--------|--------|--------|--------|--------|--------|-----------------|
|     |          | Level       | Factor | Loss   | Factor | Level  | Line   | Limit  | Pol/Phase       |
|     | MHz      | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB     | Remark          |
| 1   | 2340.973 | 56.46       | 27.57  | 3.73   | 37.78  | 49.98  | 74.00  | -24.02 | HORIZONTAL Peak |
| 2   | 2390.000 | 50.63       | 27.68  | 3.77   | 37.76  | 44.32  | 74.00  | -29.68 | HORIZONTAL Peak |
| 3 * | 2412.000 | 110.36      | 27.74  | 3.79   | 37.76  | 104.13 | 74.00  | 30.13  | HORIZONTAL Peak |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 00; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:High



Trace: (Discrete)


|     | Freq     | ReadAntenna | Cable  | Preamp |        | Limit  | Over   |        |           |        |
|-----|----------|-------------|--------|--------|--------|--------|--------|--------|-----------|--------|
|     | MHz      | Level       | Factor | Loss   | Factor | Level  | Line   | Limit  | Pol/Phase | Remark |
|     | MHz      | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB     |           |        |
| 1 * | 2462.000 | 106.49      | 27.82  | 3.81   | 37.74  | 100.38 | 74.00  | 26.38  | VERTICAL  | Peak   |
| 2   | 2483.500 | 51.15       | 27.85  | 3.82   | 37.73  | 45.09  | 74.00  | -28.91 | VERTICAL  | Peak   |
| 3   | 2491.378 | 52.71       | 27.86  | 3.83   | 37.73  | 46.67  | 74.00  | -27.33 | VERTICAL  | Peak   |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 00; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:High



Trace: (Discrete)


|     | Freq     | ReadAntenna | Cable | Preamp | Limit | Over   |           |                        |
|-----|----------|-------------|-------|--------|-------|--------|-----------|------------------------|
|     |          | Level       | Loss  | Factor | Line  | Limit  | Pol/Phase | Remark                 |
|     | MHz      | dBuV        | dB/m  | dB     | dB    | dBuV/m | dB        |                        |
| 1 * | 2462.000 | 107.88      | 27.82 | 3.81   | 37.74 | 101.77 | 74.00     | 27.77 HORIZONTAL Peak  |
| 2   | 2483.500 | 53.17       | 27.85 | 3.82   | 37.73 | 47.11  | 74.00     | -26.89 HORIZONTAL Peak |
| 3   | 2492.486 | 53.11       | 27.86 | 3.83   | 37.72 | 47.08  | 74.00     | -26.92 HORIZONTAL Peak |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 00; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)


|     | Freq     | ReadAntenna | Cable  | Preamp |        | Limit  | Over   |        |           |        |
|-----|----------|-------------|--------|--------|--------|--------|--------|--------|-----------|--------|
|     | MHz      | Level       | Factor | Loss   | Factor | Level  | Line   | Limit  | Pol/Phase | Remark |
|     | MHz      | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB     |           |        |
| 1   | 2341.210 | 54.36       | 27.57  | 3.73   | 37.78  | 47.88  | 74.00  | -26.12 | VERTICAL  | Peak   |
| 2   | 2390.000 | 54.66       | 27.68  | 3.77   | 37.76  | 48.35  | 74.00  | -25.65 | VERTICAL  | Peak   |
| 3 * | 2412.000 | 109.20      | 27.74  | 3.79   | 37.76  | 102.97 | 74.00  | 28.97  | VERTICAL  | Peak   |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 00; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)


|     | Freq     | ReadAntenna | Cable  | Preamp |        | Limit  | Over   |        |                 |
|-----|----------|-------------|--------|--------|--------|--------|--------|--------|-----------------|
|     |          | Level       | Factor | Loss   | Factor | Level  | Line   | Limit  | Pol/Phase       |
|     | MHz      | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB     | Remark          |
| 1   | 2357.869 | 56.08       | 27.62  | 3.75   | 37.78  | 49.67  | 74.00  | -24.33 | HORIZONTAL Peak |
| 2   | 2390.000 | 52.52       | 27.68  | 3.77   | 37.76  | 46.21  | 74.00  | -27.79 | HORIZONTAL Peak |
| 3 * | 2412.000 | 109.37      | 27.74  | 3.79   | 37.76  | 103.14 | 74.00  | 29.14  | HORIZONTAL Peak |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 00; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:High



Trace: (Discrete)


|     | Freq     | ReadAntenna | Cable  | Preamp |        | Limit  | Over   |       |           |         |
|-----|----------|-------------|--------|--------|--------|--------|--------|-------|-----------|---------|
|     | MHz      | Level       | Factor | Loss   | Factor | Level  | Line   | Limit | Pol/Phase | Remark  |
|     | MHz      | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB    |           |         |
| 1 * | 2462.000 | 109.26      | 27.82  | 3.81   | 37.74  | 103.15 | 74.00  | 29.15 | VERTICAL  | Peak    |
| 2   | 2483.500 | 59.60       | 27.85  | 3.82   | 37.73  | 53.54  | 54.00  | -0.46 | VERTICAL  | Average |
| 3   | 2483.500 | 73.20       | 27.85  | 3.82   | 37.73  | 67.14  | 74.00  | -6.86 | VERTICAL  | Peak    |
| 4   | 2483.890 | 57.28       | 27.85  | 3.82   | 37.73  | 51.22  | 54.00  | -2.78 | VERTICAL  | Average |
| 5   | 2483.890 | 72.25       | 27.85  | 3.82   | 37.73  | 66.19  | 74.00  | -7.81 | VERTICAL  | Peak    |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 00; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:High



Trace: (Discrete)


|     | Freq     | Read Level | Antenna Factor | Cable Loss | Preamplifier Factor | Level  | Limit Line | Over Limit | Pol/Phase  | Remark  |
|-----|----------|------------|----------------|------------|---------------------|--------|------------|------------|------------|---------|
|     | MHz      | dBuV       | dB/m           | dB         | dB                  | dBuV/m | dBuV/m     | dB         |            |         |
| 1 * | 2462.000 | 106.05     | 27.82          | 3.81       | 37.74               | 99.94  | 74.00      | 25.94      | HORIZONTAL | Peak    |
| 2   | 2483.500 | 59.23      | 27.85          | 3.82       | 37.73               | 53.17  | 54.00      | -0.83      | HORIZONTAL | Average |
| 3   | 2483.500 | 69.12      | 27.85          | 3.82       | 37.73               | 63.06  | 74.00      | -10.94     | HORIZONTAL | Peak    |
| 4   | 2483.990 | 57.41      | 27.85          | 3.82       | 37.73               | 51.35  | 54.00      | -2.65      | HORIZONTAL | Average |
| 5   | 2483.990 | 68.82      | 27.85          | 3.82       | 37.73               | 62.76  | 74.00      | -11.24     | HORIZONTAL | Peak    |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 00; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)


|     | Freq     | ReadAntenna | Cable  | Preamp | Limit  | Over   |        |           |          |
|-----|----------|-------------|--------|--------|--------|--------|--------|-----------|----------|
|     | MHz      | Level       | Factor | Loss   | Factor | Line   | Limit  | Pol/Phase | Remark   |
|     | MHz      | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB        |          |
| 1   | 2388.154 | 55.25       | 27.68  | 3.77   | 37.77  | 48.93  | 54.00  | -5.07     | VERTICAL |
| 2   | 2388.154 | 67.75       | 27.68  | 3.77   | 37.77  | 61.43  | 74.00  | -12.57    | VERTICAL |
| 3   | 2390.000 | 59.59       | 27.68  | 3.77   | 37.76  | 53.28  | 54.00  | -0.72     | VERTICAL |
| 4   | 2390.000 | 68.23       | 27.68  | 3.77   | 37.76  | 61.92  | 74.00  | -12.08    | VERTICAL |
| 5 * | 2412.000 | 109.37      | 27.74  | 3.79   | 37.76  | 103.14 | 74.00  | 29.14     | VERTICAL |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 00; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)


|     | Freq     | ReadAntenna | Cable  | Preamp |        | Limit  | Over   |        |            |         |
|-----|----------|-------------|--------|--------|--------|--------|--------|--------|------------|---------|
|     | MHz      | Level       | Factor | Loss   | Factor | Level  | Line   | Limit  | Pol/Phase  | Remark  |
|     | MHz      | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB     |            |         |
| 1   | 2387.186 | 55.99       | 27.68  | 3.77   | 37.77  | 49.67  | 54.00  | -4.33  | HORIZONTAL | Average |
| 2   | 2387.186 | 64.76       | 27.68  | 3.77   | 37.77  | 58.44  | 74.00  | -15.56 | HORIZONTAL | Peak    |
| 3   | 2390.332 | 58.87       | 27.68  | 3.77   | 37.76  | 52.56  | 54.00  | -1.44  | HORIZONTAL | Average |
| 4   | 2390.332 | 64.60       | 27.68  | 3.77   | 37.76  | 58.29  | 74.00  | -15.71 | HORIZONTAL | Peak    |
| 5 * | 2412.000 | 107.88      | 27.74  | 3.79   | 37.76  | 101.65 | 74.00  | 27.65  | HORIZONTAL | Peak    |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 00; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High



Trace: (Discrete)


|     |          | ReadAntenna |        | Cable | Preamp |        | Limit  | Over   |           |         |
|-----|----------|-------------|--------|-------|--------|--------|--------|--------|-----------|---------|
|     | Freq     | Level       | Factor | Loss  | Factor | Level  | Line   | Limit  | Pol/Phase | Remark  |
|     | MHz      | dBuV        | dB/m   | dB    | dB     | dBuV/m | dBuV/m | dB     |           |         |
| 1 * | 2462.000 | 108.05      | 27.82  | 3.81  | 37.74  | 101.94 | 74.00  | 27.94  | VERTICAL  | Peak    |
| 2   | 2483.500 | 59.46       | 27.85  | 3.82  | 37.73  | 53.40  | 54.00  | -0.60  | VERTICAL  | Average |
| 3   | 2483.500 | 69.75       | 27.85  | 3.82  | 37.73  | 63.69  | 74.00  | -10.31 | VERTICAL  | Peak    |
| 4   | 2486.651 | 57.66       | 27.85  | 3.82  | 37.73  | 51.60  | 54.00  | -2.40  | VERTICAL  | Average |
| 5   | 2486.651 | 69.57       | 27.85  | 3.82  | 37.73  | 63.51  | 74.00  | -10.49 | VERTICAL  | Peak    |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 00; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High



Trace: (Discrete)

|     | Freq     | ReadAntenna | Cable  | Preamp | Level  | Limit  | Over   | Pol/Phase | Remark             |
|-----|----------|-------------|--------|--------|--------|--------|--------|-----------|--------------------|
|     | MHz      | Level       | Factor | Loss   | Factor | Line   | Limit  |           |                    |
|     | MHz      | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB        |                    |
| 1 * | 2462.000 | 106.06      | 27.82  | 3.81   | 37.74  | 99.95  | 74.00  | 25.95     | HORIZONTAL Peak    |
| 2   | 2483.500 | 59.73       | 27.85  | 3.82   | 37.73  | 53.67  | 54.00  | -0.33     | HORIZONTAL Average |
| 3   | 2483.500 | 67.26       | 27.85  | 3.82   | 37.73  | 61.20  | 74.00  | -12.80    | HORIZONTAL Peak    |
| 4   | 2484.191 | 56.37       | 27.85  | 3.82   | 37.73  | 50.31  | 54.00  | -3.69     | HORIZONTAL Average |
| 5   | 2484.191 | 66.84       | 27.85  | 3.82   | 37.73  | 60.78  | 74.00  | -13.22    | HORIZONTAL Peak    |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

## 7.8 Radiated Spurious Emissions Below 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 &amp; 15.209

Test Method: ANSI C63.10 (2013) Section 6.4,6.5

Limit:

Test Distance: 3 m

| Frequency (MHz) | Field strength (microvolts/meter) | Measurement distance(meters) |
|-----------------|-----------------------------------|------------------------------|
| 0.009-0.490     | 2400/F(kHz)                       | 300                          |
| 0.490-1.705     | 24000/F(kHz)                      | 30                           |
| 1.705-30.0      | 30                                | 30                           |
| 30-88           | 100                               | 3                            |
| 88-216          | 150                               | 3                            |
| 216-960         | 200                               | 3                            |
| 960-1000        | 500                               | 3                            |

### 7.8.1 E.U.T. Operation

Operating Environment:

Temperature: 23.4 °C

Humidity: 55.6 % RH

Atmospheric Pressure: 1000 mbar

### 7.8.2 Test Mode Description

| Pre-scan /<br>Final test | Mode<br>Code | Description |
|--------------------------|--------------|-------------|
|--------------------------|--------------|-------------|

|            |    |                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|------------|----|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Final test | 00 | TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report. |
|------------|----|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|


|            |    |                                                                                                                                                                                                                                                                                                                                               |
|------------|----|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Final test | 09 | TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6.5Mbps is the worst case of IEEE 802.11ah, final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report. |
|------------|----|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

### 7.8.3 Test Setup Diagram



### 7.8.4 Measurement Procedure and Data

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark:


- Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
- Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- The disturbance below 1GHz was very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 00; Polarity: Horizontal



Site : 966 Chamber  
Job :  
Model :  
Power :  
Test Mode :

|   | Freq    | Read Level | Antenna Factor | Cable Loss | Preamplifier Factor | Measured Level | Limit Line | Over Limit | Pol/Phase  | Remark |
|---|---------|------------|----------------|------------|---------------------|----------------|------------|------------|------------|--------|
|   | MHz     | dBuV       | dB/m           | dB         | dB                  | dBuV/m         | dBuV/m     | dB         |            |        |
| 1 | 107.510 | 42.47      | 15.78          | 0.56       | 32.80               | 26.01          | 43.52      | -17.51     | HORIZONTAL | QP     |
| 2 | 224.519 | 58.39      | 15.95          | 0.82       | 32.80               | 42.36          | 46.02      | -3.66      | HORIZONTAL | QP     |
| 3 | 263.819 | 47.22      | 17.96          | 0.93       | 32.80               | 33.31          | 46.02      | -12.71     | HORIZONTAL | QP     |
| 4 | 614.000 | 33.73      | 25.92          | 1.44       | 32.89               | 28.20          | 46.02      | -17.82     | HORIZONTAL | QP     |
| 5 | 909.667 | 107.20     | 29.52          | 1.76       | 31.55               | 106.93         | 46.02      | 60.91      | HORIZONTAL | Peak   |
| 6 | 960.000 | 32.46      | 29.74          | 1.82       | 30.98               | 33.04          | 46.02      | -12.98     | HORIZONTAL | QP     |
| 7 | 972.337 | 44.25      | 29.82          | 1.83       | 30.86               | 45.04          | 53.98      | -8.94      | HORIZONTAL | QP     |


The port 5 is the fundamental frequency of wireless function of monitor and camera.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 00; Polarity: Vertical



Site : 966 Chamber  
Job :  
Model :  
Power :  
Test Mode :

|   | Freq    | Read Level | Antenna Factor | Cable Loss | Preamplifier Factor | Measured Level | Limit Line | Over Limit | Pol/Phase | Remark |
|---|---------|------------|----------------|------------|---------------------|----------------|------------|------------|-----------|--------|
|   | MHz     | dBuV       | dB/m           | dB         | dB                  | dBuV/m         | dBuV/m     | dB         |           |        |
| 1 | 61.778  | 36.93      | 18.47          | 0.42       | 32.80               | 23.02          | 40.00      | -16.98     | VERTICAL  | QP     |
| 2 | 128.113 | 46.87      | 17.91          | 0.61       | 32.80               | 32.59          | 43.52      | -10.93     | VERTICAL  | QP     |
| 3 | 225.308 | 57.61      | 15.95          | 0.82       | 32.80               | 41.58          | 46.02      | -4.44      | VERTICAL  | QP     |
| 4 | 614.000 | 33.69      | 25.92          | 1.44       | 32.89               | 28.16          | 46.02      | -17.86     | VERTICAL  | QP     |
| 5 | 909.667 | 107.58     | 29.52          | 1.76       | 31.55               | 107.31         | 46.02      | 61.29      | VERTICAL  | Peak   |
| 6 | 960.000 | 33.07      | 29.74          | 1.82       | 30.98               | 33.65          | 46.02      | -12.37     | VERTICAL  | QP     |
| 7 | 975.753 | 45.34      | 29.89          | 1.83       | 30.83               | 46.23          | 53.98      | -7.75      | VERTICAL  | QP     |


The port 5 is the fundamental frequency of wireless function of monitor and camera.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 09; Polarity: Vertical; Modulation:802.11ah; Bandwidth:2MHz; Channel:Low



Site : 966 Chamber  
Job :  
Model :  
Power :  
Test Mode : 905

|   | Freq    | Read Level | Antenna Factor | Cable Loss | Preamplifier | Measured Level | Limit Line | Over Limit | Pol/Phase | Remark |
|---|---------|------------|----------------|------------|--------------|----------------|------------|------------|-----------|--------|
|   | MHz     | dBuV       | dB/m           | dB         | dB           | dBuV/m         | dBuV/m     | dB         |           |        |
| 1 | 39.437  | 34.48      | 19.09          | 0.35       | 32.83        | 21.09          | 40.00      | -18.91     | VERTICAL  | QP     |
| 2 | 128.563 | 46.84      | 17.98          | 0.62       | 32.80        | 32.64          | 43.52      | -10.88     | VERTICAL  | QP     |
| 3 | 225.308 | 57.40      | 15.95          | 0.82       | 32.80        | 41.37          | 46.02      | -4.65      | VERTICAL  | QP     |
| 4 | 614.000 | 33.25      | 25.92          | 1.44       | 32.89        | 27.72          | 46.02      | -18.30     | VERTICAL  | QP     |
| 5 | 905.000 | 107.14     | 29.47          | 1.76       | 31.57        | 106.80         | 46.02      | 60.78      | VERTICAL  | Peak   |
| 6 | 960.000 | 33.03      | 29.74          | 1.82       | 30.98        | 33.61          | 46.02      | -12.41     | VERTICAL  | QP     |
| 7 | 975.753 | 45.72      | 29.89          | 1.83       | 30.83        | 46.61          | 53.98      | -7.37      | VERTICAL  | QP     |


The port 5 is the fundamental frequency of wireless function of monitor and camera.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 09; Polarity: Horizontal; Modulation:802.11ah; Bandwidth:2MHz; Channel:Low



Site : 966 Chamber  
Job :  
Model :  
Power :  
Test Mode : 905

|   | Freq    | Read Level | Antenna Factor | Cable Loss | Preamplifier Factor | Measured Level | Limit Line | Over Limit | Pol/Phase  | Remark |
|---|---------|------------|----------------|------------|---------------------|----------------|------------|------------|------------|--------|
|   | MHz     | dBuV       | dB/m           | dB         | dB                  | dBuV/m         | dBuV/m     | dB         |            |        |
| 1 | 107.134 | 41.47      | 15.78          | 0.56       | 32.80               | 25.01          | 43.52      | -18.51     | HORIZONTAL | QP     |
| 2 | 224.748 | 58.30      | 15.95          | 0.82       | 32.80               | 42.27          | 46.02      | -3.75      | HORIZONTAL | QP     |
| 3 | 263.819 | 46.50      | 17.96          | 0.93       | 32.80               | 32.59          | 46.02      | -13.43     | HORIZONTAL | QP     |
| 4 | 614.000 | 34.35      | 25.92          | 1.44       | 32.89               | 28.82          | 46.02      | -17.20     | HORIZONTAL | QP     |
| 5 | 905.000 | 108.51     | 29.47          | 1.76       | 31.57               | 108.17         | 46.02      | 62.15      | HORIZONTAL | Peak   |
| 6 | 960.000 | 31.95      | 29.74          | 1.82       | 30.98               | 32.53          | 46.02      | -13.49     | HORIZONTAL | QP     |
| 7 | 975.753 | 44.64      | 29.89          | 1.83       | 30.83               | 45.53          | 53.98      | -8.45      | HORIZONTAL | QP     |


The port 5 is the fundamental frequency of wireless function of monitor and camera.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 09; Polarity: Vertical; Modulation:802.11ah; Bandwidth:2MHz; Channel:middle



Site : 966 Chamber  
Job :  
Model :  
Power :  
Test Mode : 915

|   | Freq    | Read Level | Antenna Factor | Cable Loss | Preamplifier Factor | Measured Level | Limit Line | Over Limit | Pol/Phase | Remark |
|---|---------|------------|----------------|------------|---------------------|----------------|------------|------------|-----------|--------|
|   | MHz     | dBuV       | dB/m           | dB         | dB                  | dBuV/m         | dBuV/m     | dB         |           |        |
| 1 | 39.437  | 34.48      | 19.09          | 0.35       | 32.83               | 21.09          | 40.00      | -18.91     | VERTICAL  | QP     |
| 2 | 128.563 | 46.84      | 17.98          | 0.62       | 32.80               | 32.64          | 43.52      | -10.88     | VERTICAL  | QP     |
| 3 | 225.308 | 57.40      | 15.95          | 0.82       | 32.80               | 41.37          | 46.02      | -4.65      | VERTICAL  | QP     |
| 4 | 614.000 | 33.25      | 25.92          | 1.44       | 32.89               | 27.72          | 46.02      | -18.30     | VERTICAL  | QP     |
| 5 | 915.000 | 107.05     | 29.50          | 1.77       | 31.52               | 106.80         | 46.02      | 60.78      | VERTICAL  | Peak   |
| 6 | 960.000 | 33.03      | 29.74          | 1.82       | 30.98               | 33.61          | 46.02      | -12.41     | VERTICAL  | QP     |
| 7 | 975.753 | 45.72      | 29.89          | 1.83       | 30.83               | 46.61          | 53.98      | -7.37      | VERTICAL  | QP     |


The port 5 is the fundamental frequency of wireless function of monitor and camera.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 09; Polarity: Horizontal; Modulation:802.11ah; Bandwidth:2MHz; Channel:middle



Site : 966 Chamber  
Job :  
Model :  
Power :  
Test Mode : 915

|   | Freq    | Read Level | Antenna Factor | Cable Loss | Preamplifier Factor | Measured Level | Limit Line | Over Limit | Pol/Phase  | Remark |
|---|---------|------------|----------------|------------|---------------------|----------------|------------|------------|------------|--------|
|   | MHz     | dBuV       | dB/m           | dB         | dB                  | dBuV/m         | dBuV/m     | dB         |            |        |
| 1 | 107.134 | 41.47      | 15.78          | 0.56       | 32.80               | 25.01          | 43.52      | -18.51     | HORIZONTAL | QP     |
| 2 | 224.748 | 58.30      | 15.95          | 0.82       | 32.80               | 42.27          | 46.02      | -3.75      | HORIZONTAL | QP     |
| 3 | 263.819 | 46.50      | 17.96          | 0.93       | 32.80               | 32.59          | 46.02      | -13.43     | HORIZONTAL | QP     |
| 4 | 614.000 | 34.35      | 25.92          | 1.44       | 32.89               | 28.82          | 46.02      | -17.20     | HORIZONTAL | QP     |
| 5 | 915.000 | 106.51     | 29.50          | 1.77       | 31.52               | 106.26         | 46.02      | 60.24      | HORIZONTAL | Peak   |
| 6 | 960.000 | 31.95      | 29.74          | 1.82       | 30.98               | 32.53          | 46.02      | -13.49     | HORIZONTAL | QP     |
| 7 | 975.753 | 44.64      | 29.89          | 1.83       | 30.83               | 45.53          | 53.98      | -8.45      | HORIZONTAL | QP     |


The port 5 is the fundamental frequency of wireless function of monitor and camera.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 09; Polarity: Vertical; Modulation:802.11ah; Bandwidth:2MHz; Channel:High



Site : 966 Chamber  
Job :  
Model :  
Power :  
Test Mode : 925

|   | Freq    | Read Level | Antenna Factor | Cable Loss | Preamplifier Factor | Measured Level | Limit Line | Over Limit | Pol/Phase | Remark |
|---|---------|------------|----------------|------------|---------------------|----------------|------------|------------|-----------|--------|
|   | MHz     | dBuV       | dB/m           | dB         | dB                  | dBuV/m         | dBuV/m     | dB         |           |        |
| 1 | 39.437  | 34.48      | 19.09          | 0.35       | 32.83               | 21.09          | 40.00      | -18.91     | VERTICAL  | QP     |
| 2 | 128.563 | 46.84      | 17.98          | 0.62       | 32.80               | 32.64          | 43.52      | -10.88     | VERTICAL  | QP     |
| 3 | 225.308 | 57.40      | 15.95          | 0.82       | 32.80               | 41.37          | 46.02      | -4.65      | VERTICAL  | QP     |
| 4 | 614.000 | 33.25      | 25.92          | 1.44       | 32.89               | 27.72          | 46.02      | -18.30     | VERTICAL  | QP     |
| 5 | 925.000 | 107.07     | 29.49          | 1.76       | 31.56               | 106.76         | 46.02      | 60.74      | VERTICAL  | Peak   |
| 6 | 960.000 | 33.03      | 29.74          | 1.82       | 30.98               | 33.61          | 46.02      | -12.41     | VERTICAL  | QP     |
| 7 | 975.753 | 45.72      | 29.89          | 1.83       | 30.83               | 46.61          | 53.98      | -7.37      | VERTICAL  | QP     |


The port 5 is the fundamental frequency of wireless function of monitor and camera.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 09; Polarity: Vertical; Modulation:802.11ah; Bandwidth:2MHz; Channel:High



Site : 966 Chamber  
Job :  
Model :  
Power :  
Test Mode : 925

|   | Freq    | Read Level | Antenna Factor | Cable Loss | Preamplifier Factor | Measured Level | Limit Line | Over Limit | Pol/Phase  | Remark |
|---|---------|------------|----------------|------------|---------------------|----------------|------------|------------|------------|--------|
|   | MHz     | dBuV       | dB/m           | dB         | dB                  | dBuV/m         | dBuV/m     | dB         |            |        |
| 1 | 107.134 | 41.47      | 15.78          | 0.56       | 32.80               | 25.01          | 43.52      | -18.51     | HORIZONTAL | QP     |
| 2 | 224.748 | 58.30      | 15.95          | 0.82       | 32.80               | 42.27          | 46.02      | -3.75      | HORIZONTAL | QP     |
| 3 | 263.819 | 46.50      | 17.96          | 0.93       | 32.80               | 32.59          | 46.02      | -13.43     | HORIZONTAL | QP     |
| 4 | 614.000 | 34.35      | 25.92          | 1.44       | 32.89               | 28.82          | 46.02      | -17.20     | HORIZONTAL | QP     |
| 5 | 925.000 | 107.52     | 29.49          | 1.76       | 31.56               | 107.21         | 46.02      | 61.19      | HORIZONTAL | Peak   |
| 6 | 960.000 | 31.95      | 29.74          | 1.82       | 30.98               | 32.53          | 46.02      | -13.49     | HORIZONTAL | QP     |
| 7 | 975.753 | 44.64      | 29.89          | 1.83       | 30.83               | 45.53          | 53.98      | -8.45      | HORIZONTAL | QP     |

The port 5 is the fundamental frequency of wireless function of monitor and camera.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

### 7.9 Radiated Spurious Emissions Above 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.6

Limit:

| Frequency (MHz) | Field strength (microvolts/meter) | Measurement distance(meters) |
|-----------------|-----------------------------------|------------------------------|
| Above 1000      | 500                               | 3                            |

#### 7.9.1 E.U.T. Operation

Operating Environment:

Temperature: 23.9 °C Humidity: 53.9 % RH Atmospheric Pressure: 1016 mbar


#### 7.9.2 Test Mode Description

**Pre-scan / Mode**  
**Final test Code Description**

**Final test 00** TX mode\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.

**Final test 09** TX mode\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6.5Mbps is the worst case of IEEE 802.11ah, final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.

#### 7.9.3 Test Setup Diagram



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

## 7.9.4 Measurement Procedure and Data

- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:


1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 1GHz to 25GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 00; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)


|   | Freq     | ReadAntenna | Cable  | Preamp | Level  | Limit  | Over   | Pol/Phase | Remark        |
|---|----------|-------------|--------|--------|--------|--------|--------|-----------|---------------|
|   | MHz      | Level       | Factor | Loss   | Factor | Line   | Limit  |           |               |
|   | MHz      | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB        |               |
| 1 | 1238.483 | 57.09       | 23.59  | 2.68   | 37.98  | 45.38  | 74.00  | -28.62    | VERTICAL peak |
| 2 | 4405.090 | 44.76       | 33.74  | 4.79   | 36.82  | 46.47  | 74.00  | -27.53    | VERTICAL peak |
| 3 | 4824.000 | 43.95       | 34.16  | 5.16   | 36.87  | 46.40  | 74.00  | -27.60    | VERTICAL peak |
| 4 | 6717.762 | 44.97       | 34.42  | 6.87   | 37.05  | 49.21  | 74.00  | -24.79    | VERTICAL peak |
| 5 | 7236.000 | 39.51       | 35.78  | 6.90   | 37.14  | 45.05  | 74.00  | -28.95    | VERTICAL peak |
| 6 | 9648.000 | 38.36       | 38.70  | 7.65   | 37.02  | 47.69  | 74.00  | -26.31    | VERTICAL peak |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 00; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)


|   | Freq     | ReadAntenna | Cable  | Preamp |        | Limit  | Over   |        |            |        |
|---|----------|-------------|--------|--------|--------|--------|--------|--------|------------|--------|
|   | MHz      | Level       | Factor | Loss   | Factor | Level  | Line   | Limit  | Pol/Phase  | Remark |
|   | MHz      | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB     |            |        |
| 1 | 1224.247 | 63.60       | 23.42  | 2.63   | 37.98  | 51.67  | 74.00  | -22.33 | HORIZONTAL | peak   |
| 2 | 4405.090 | 45.54       | 33.74  | 4.79   | 36.82  | 47.25  | 74.00  | -26.75 | HORIZONTAL | peak   |
| 3 | 4824.000 | 45.58       | 34.16  | 5.16   | 36.87  | 48.03  | 74.00  | -25.97 | HORIZONTAL | peak   |
| 4 | 6717.762 | 45.79       | 34.42  | 6.87   | 37.05  | 50.03  | 74.00  | -23.97 | HORIZONTAL | peak   |
| 5 | 7236.000 | 40.13       | 35.78  | 6.90   | 37.14  | 45.67  | 74.00  | -28.33 | HORIZONTAL | peak   |
| 6 | 9648.000 | 39.01       | 38.70  | 7.65   | 37.02  | 48.34  | 74.00  | -25.66 | HORIZONTAL | peak   |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 00; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:middle



Trace: (Discrete)


|   | Freq     | ReadAntenna | Cable  | Preamp | Level  | Limit  | Over   |           |               |
|---|----------|-------------|--------|--------|--------|--------|--------|-----------|---------------|
|   | MHz      | Level       | Factor | Loss   | Factor | Line   | Limit  | Pol/Phase | Remark        |
|   | MHz      | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB        |               |
| 1 | 1224.247 | 62.73       | 23.42  | 2.63   | 37.98  | 50.80  | 74.00  | -23.20    | VERTICAL peak |
| 2 | 3261.418 | 53.14       | 28.89  | 4.50   | 37.10  | 49.43  | 74.00  | -24.57    | VERTICAL peak |
| 3 | 4874.000 | 44.50       | 34.15  | 5.22   | 36.87  | 47.00  | 74.00  | -27.00    | VERTICAL peak |
| 4 | 5239.274 | 48.19       | 33.45  | 5.45   | 36.94  | 50.15  | 74.00  | -23.85    | VERTICAL peak |
| 5 | 7311.000 | 40.91       | 36.00  | 6.83   | 37.15  | 46.59  | 74.00  | -27.41    | VERTICAL peak |
| 6 | 9748.000 | 38.21       | 38.81  | 7.65   | 37.01  | 47.66  | 74.00  | -26.34    | VERTICAL peak |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 00; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:middle



Trace: (Discrete)


|   | Freq     | ReadAntenna | Cable  | Preamp |        | Limit  | Over   |        |                 |
|---|----------|-------------|--------|--------|--------|--------|--------|--------|-----------------|
|   | MHz      | Level       | Factor | Loss   | Factor | Level  | Line   | Limit  | Pol/Phase       |
|   | MHz      | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB     |                 |
| 1 | 1196.264 | 63.18       | 23.14  | 2.55   | 37.99  | 50.88  | 74.00  | -23.12 | HORIZONTAL peak |
| 2 | 4482.150 | 45.56       | 34.12  | 4.78   | 36.83  | 47.63  | 74.00  | -26.37 | HORIZONTAL peak |
| 3 | 4874.000 | 46.12       | 34.15  | 5.22   | 36.87  | 48.62  | 74.00  | -25.38 | HORIZONTAL peak |
| 4 | 5239.274 | 49.17       | 33.45  | 5.45   | 36.94  | 51.13  | 74.00  | -22.87 | HORIZONTAL peak |
| 5 | 7311.000 | 40.94       | 36.00  | 6.83   | 37.15  | 46.62  | 74.00  | -27.38 | HORIZONTAL peak |
| 6 | 9748.000 | 38.13       | 38.81  | 7.65   | 37.01  | 47.58  | 74.00  | -26.42 | HORIZONTAL peak |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 00; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:High



Trace: (Discrete)


|   | Freq     | ReadAntenna | Cable | Preamp |       | Limit  | Over   |           |               |
|---|----------|-------------|-------|--------|-------|--------|--------|-----------|---------------|
|   |          | Level       | Loss  | Factor | Level | Line   | Limit  | Pol/Phase | Remark        |
|   | MHz      | dBuV        | dB/m  | dB     | dB    | dBuV/m | dBuV/m | dB        |               |
| 1 | 1217.190 | 60.46       | 23.34 | 2.61   | 37.98 | 48.43  | 74.00  | -25.57    | VERTICAL peak |
| 2 | 3280.326 | 53.38       | 28.91 | 4.52   | 37.10 | 49.71  | 74.00  | -24.29    | VERTICAL peak |
| 3 | 4924.000 | 44.42       | 34.15 | 5.26   | 36.88 | 46.95  | 74.00  | -27.05    | VERTICAL peak |
| 4 | 6954.852 | 45.14       | 35.04 | 7.10   | 37.09 | 50.19  | 74.00  | -23.81    | VERTICAL peak |
| 5 | 7386.000 | 39.87       | 36.23 | 6.75   | 37.16 | 45.69  | 74.00  | -28.31    | VERTICAL peak |
| 6 | 9848.000 | 40.91       | 38.88 | 7.66   | 37.01 | 50.44  | 74.00  | -23.56    | VERTICAL peak |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 00; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:High



Trace: (Discrete)


|   | Freq     | ReadAntenna | Cable  | Preamp | Level  | Limit  | Over   | Pol/Phase | Remark          |
|---|----------|-------------|--------|--------|--------|--------|--------|-----------|-----------------|
|   | MHz      | Level       | Factor | Loss   | Factor | Line   | Limit  |           |                 |
|   |          | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB        |                 |
| 1 | 1217.190 | 62.80       | 23.34  | 2.61   | 37.98  | 50.77  | 74.00  | -23.23    | HORIZONTAL peak |
| 2 | 4430.628 | 46.05       | 33.87  | 4.79   | 36.83  | 47.88  | 74.00  | -26.12    | HORIZONTAL peak |
| 3 | 4924.000 | 44.60       | 34.15  | 5.26   | 36.88  | 47.13  | 74.00  | -26.87    | HORIZONTAL peak |
| 4 | 5300.200 | 50.03       | 33.17  | 5.51   | 36.95  | 51.76  | 74.00  | -22.24    | HORIZONTAL peak |
| 5 | 7386.000 | 39.84       | 36.23  | 6.75   | 37.16  | 45.66  | 74.00  | -28.34    | HORIZONTAL peak |
| 6 | 9848.000 | 40.63       | 38.88  | 7.66   | 37.01  | 50.16  | 74.00  | -23.84    | HORIZONTAL peak |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 00; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)


|   | Freq     | ReadAntenna | Cable  | Preamp | Level  | Limit  | Over   | Pol/Phase | Remark        |
|---|----------|-------------|--------|--------|--------|--------|--------|-----------|---------------|
|   | MHz      | Level       | Factor | Loss   | Factor | Line   | Limit  |           |               |
|   | MHz      | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB        |               |
| 1 | 1245.663 | 53.20       | 23.65  | 2.70   | 37.98  | 41.57  | 74.00  | -32.43    | VERTICAL peak |
| 2 | 4379.699 | 46.13       | 33.59  | 4.80   | 36.82  | 47.70  | 74.00  | -26.30    | VERTICAL peak |
| 3 | 4824.000 | 44.99       | 34.16  | 5.16   | 36.87  | 47.44  | 74.00  | -26.56    | VERTICAL peak |
| 4 | 5780.300 | 49.61       | 32.66  | 5.76   | 36.99  | 51.04  | 74.00  | -22.96    | VERTICAL peak |
| 5 | 7236.000 | 41.46       | 35.78  | 6.90   | 37.14  | 47.00  | 74.00  | -27.00    | VERTICAL peak |
| 6 | 9648.000 | 39.96       | 38.70  | 7.65   | 37.02  | 49.29  | 74.00  | -24.71    | VERTICAL peak |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 00; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)


|   | Freq     | ReadAntenna | Cable  | Preamp | Level  | Limit  | Over   | Pol/Phase | Remark          |
|---|----------|-------------|--------|--------|--------|--------|--------|-----------|-----------------|
|   | MHz      | Level       | Factor | Loss   | Factor | Line   | Limit  |           |                 |
|   | MHz      | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB        |                 |
| 1 | 1252.885 | 52.11       | 23.71  | 2.72   | 37.98  | 40.56  | 74.00  | -33.44    | HORIZONTAL peak |
| 2 | 4482.150 | 45.01       | 34.12  | 4.78   | 36.83  | 47.08  | 74.00  | -26.92    | HORIZONTAL peak |
| 3 | 4824.000 | 45.15       | 34.16  | 5.16   | 36.87  | 47.60  | 74.00  | -26.40    | HORIZONTAL peak |
| 4 | 5763.617 | 48.32       | 32.66  | 5.75   | 36.99  | 49.74  | 74.00  | -24.26    | HORIZONTAL peak |
| 5 | 7236.000 | 41.39       | 35.78  | 6.90   | 37.14  | 46.93  | 74.00  | -27.07    | HORIZONTAL peak |
| 6 | 9648.000 | 38.99       | 38.70  | 7.65   | 37.02  | 48.32  | 74.00  | -25.68    | HORIZONTAL peak |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 00; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:middle




|   | Freq     | ReadAntenna | Cable  | Preamp |        | Limit  | Over   |        |           |        |
|---|----------|-------------|--------|--------|--------|--------|--------|--------|-----------|--------|
|   |          | Level       | Factor | Loss   | Factor | Level  | Line   | Limit  | Pol/Phase | Remark |
|   | MHz      | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB     |           |        |
| 1 | 1238.483 | 56.97       | 23.59  | 2.68   | 37.98  | 45.26  | 74.00  | -28.74 | VERTICAL  | peak   |
| 2 | 3280.326 | 50.83       | 28.91  | 4.52   | 37.10  | 47.16  | 74.00  | -26.84 | VERTICAL  | peak   |
| 3 | 4874.000 | 49.25       | 34.15  | 5.22   | 36.87  | 51.75  | 74.00  | -22.25 | VERTICAL  | peak   |
| 4 | 6874.906 | 45.37       | 34.88  | 7.04   | 37.07  | 50.22  | 74.00  | -23.78 | VERTICAL  | peak   |
| 5 | 7311.000 | 45.86       | 36.00  | 6.83   | 37.15  | 51.54  | 74.00  | -22.46 | VERTICAL  | peak   |
| 6 | 9748.000 | 37.60       | 38.81  | 7.65   | 37.01  | 47.05  | 74.00  | -26.95 | VERTICAL  | peak   |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 00; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:middle



Trace: (Discrete)


|   | Freq     | ReadAntenna | Cable  | Preamp |        | Limit  | Over   |        |            |        |
|---|----------|-------------|--------|--------|--------|--------|--------|--------|------------|--------|
|   |          | Level       | Factor | Loss   | Factor | Level  | Line   | Limit  | Pol/Phase  | Remark |
|   | MHz      | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB     |            |        |
| 1 | 1267.454 | 51.73       | 23.81  | 2.75   | 37.98  | 40.31  | 74.00  | -33.69 | HORIZONTAL | peak   |
| 2 | 4430.628 | 44.99       | 33.87  | 4.79   | 36.83  | 46.82  | 74.00  | -27.18 | HORIZONTAL | peak   |
| 3 | 4874.000 | 49.58       | 34.15  | 5.22   | 36.87  | 52.08  | 74.00  | -21.92 | HORIZONTAL | peak   |
| 4 | 6835.278 | 44.91       | 34.79  | 7.01   | 37.07  | 49.64  | 74.00  | -24.36 | HORIZONTAL | peak   |
| 5 | 7311.000 | 41.34       | 36.00  | 6.83   | 37.15  | 47.02  | 74.00  | -26.98 | HORIZONTAL | peak   |
| 6 | 9748.000 | 37.54       | 38.81  | 7.65   | 37.01  | 46.99  | 74.00  | -27.01 | HORIZONTAL | peak   |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 00; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:High



Trace: (Discrete)


|   | Freq     | ReadAntenna | Cable | Preamp | Limit | Over   |           |        |               |
|---|----------|-------------|-------|--------|-------|--------|-----------|--------|---------------|
|   |          | Level       | Loss  | Factor | Line  | Limit  | Pol/Phase | Remark |               |
|   | MHz      | dBuV        | dB/m  | dB     | dB    | dBuV/m | dB        |        |               |
| 1 | 1224.247 | 63.44       | 23.42 | 2.63   | 37.98 | 51.51  | 74.00     | -22.49 | VERTICAL peak |
| 2 | 4495.125 | 45.47       | 34.17 | 4.78   | 36.83 | 47.59  | 74.00     | -26.41 | VERTICAL peak |
| 3 | 4924.000 | 46.98       | 34.15 | 5.26   | 36.88 | 49.51  | 74.00     | -24.49 | VERTICAL peak |
| 4 | 6874.906 | 44.89       | 34.88 | 7.04   | 37.07 | 49.74  | 74.00     | -24.26 | VERTICAL peak |
| 5 | 7386.000 | 41.03       | 36.23 | 6.75   | 37.16 | 46.85  | 74.00     | -27.15 | VERTICAL peak |
| 6 | 9848.000 | 39.65       | 38.88 | 7.66   | 37.01 | 49.18  | 74.00     | -24.82 | VERTICAL peak |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 00; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:High



Trace: (Discrete)


|   | Freq     | ReadAntenna | Cable  | Preamp | Level  | Limit  | Over   |           |                 |
|---|----------|-------------|--------|--------|--------|--------|--------|-----------|-----------------|
|   | MHz      | Level       | Factor | Loss   | Factor | Line   | Limit  | Pol/Phase | Remark          |
|   | MHz      | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB        |                 |
| 1 | 1217.190 | 62.68       | 23.34  | 2.61   | 37.98  | 50.65  | 74.00  | -23.35    | HORIZONTAL peak |
| 2 | 4482.150 | 45.64       | 34.12  | 4.78   | 36.83  | 47.71  | 74.00  | -26.29    | HORIZONTAL peak |
| 3 | 4924.000 | 47.20       | 34.15  | 5.26   | 36.88  | 49.73  | 74.00  | -24.27    | HORIZONTAL peak |
| 4 | 5239.274 | 48.25       | 33.45  | 5.45   | 36.94  | 50.21  | 74.00  | -23.79    | HORIZONTAL peak |
| 5 | 7386.000 | 41.47       | 36.23  | 6.75   | 37.16  | 47.29  | 74.00  | -26.71    | HORIZONTAL peak |
| 6 | 9848.000 | 40.49       | 38.88  | 7.66   | 37.01  | 50.02  | 74.00  | -23.98    | HORIZONTAL peak |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 00; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)


|   | Freq     | ReadAntenna | Cable  | Preamp | Level  | Limit  | Over   |           |               |
|---|----------|-------------|--------|--------|--------|--------|--------|-----------|---------------|
|   | MHz      | Level       | Factor | Loss   | Factor | Line   | Limit  | Pol/Phase | Remark        |
|   | MHz      | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB        |               |
| 1 | 1238.483 | 58.45       | 23.59  | 2.68   | 37.98  | 46.74  | 74.00  | -27.26    | VERTICAL peak |
| 2 | 4456.315 | 45.58       | 34.00  | 4.79   | 36.83  | 47.54  | 74.00  | -26.46    | VERTICAL peak |
| 3 | 4824.000 | 44.78       | 34.16  | 5.16   | 36.87  | 47.23  | 74.00  | -26.77    | VERTICAL peak |
| 4 | 5713.856 | 50.24       | 32.65  | 5.71   | 36.98  | 51.62  | 74.00  | -22.38    | VERTICAL peak |
| 5 | 7236.000 | 43.25       | 35.78  | 6.90   | 37.14  | 48.79  | 74.00  | -25.21    | VERTICAL peak |
| 6 | 9648.000 | 39.52       | 38.70  | 7.65   | 37.02  | 48.85  | 74.00  | -25.15    | VERTICAL peak |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)


Test Mode: 00; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 00; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:middle



Trace: (Discrete)


|   | Freq     | ReadAntenna | Cable  | Preamp |        | Limit  | Over   |        |           |        |
|---|----------|-------------|--------|--------|--------|--------|--------|--------|-----------|--------|
|   | MHz      | Level       | Factor | Loss   | Factor | Level  | Line   | Limit  | Pol/Phase | Remark |
|   | MHz      | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB     |           |        |
| 1 | 1238.483 | 57.99       | 23.59  | 2.68   | 37.98  | 46.28  | 74.00  | -27.72 | VERTICAL  | peak   |
| 2 | 4495.125 | 44.98       | 34.17  | 4.78   | 36.83  | 47.10  | 74.00  | -26.90 | VERTICAL  | peak   |
| 3 | 4874.000 | 43.44       | 34.15  | 5.22   | 36.87  | 45.94  | 74.00  | -28.06 | VERTICAL  | peak   |
| 4 | 5713.856 | 48.45       | 32.65  | 5.71   | 36.98  | 49.83  | 74.00  | -24.17 | VERTICAL  | peak   |
| 5 | 7311.000 | 44.26       | 36.00  | 6.83   | 37.15  | 49.94  | 74.00  | -24.06 | VERTICAL  | peak   |
| 6 | 9748.000 | 37.53       | 38.81  | 7.65   | 37.01  | 46.98  | 74.00  | -27.02 | VERTICAL  | peak   |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 00; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:middle



Trace: (Discrete)


|   | Freq     | ReadAntenna | Cable  | Preamp | Level  | Limit  | Over   | Pol/Phase | Remark          |
|---|----------|-------------|--------|--------|--------|--------|--------|-----------|-----------------|
|   | MHz      | Level       | Factor | Loss   | Factor | Line   | Limit  |           |                 |
|   | MHz      | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB        |                 |
| 1 | 1238.483 | 62.55       | 23.59  | 2.68   | 37.98  | 50.84  | 74.00  | -23.16    | HORIZONTAL peak |
| 2 | 4405.090 | 45.44       | 33.74  | 4.79   | 36.82  | 47.15  | 74.00  | -26.85    | HORIZONTAL peak |
| 3 | 4874.000 | 44.11       | 34.15  | 5.22   | 36.87  | 46.61  | 74.00  | -27.39    | HORIZONTAL peak |
| 4 | 5239.274 | 47.92       | 33.45  | 5.45   | 36.94  | 49.88  | 74.00  | -24.12    | HORIZONTAL peak |
| 5 | 7311.000 | 43.90       | 36.00  | 6.83   | 37.15  | 49.58  | 74.00  | -24.42    | HORIZONTAL peak |
| 6 | 9748.000 | 38.53       | 38.81  | 7.65   | 37.01  | 47.98  | 74.00  | -26.02    | HORIZONTAL peak |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 00; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High



Trace: (Discrete)


|   | Freq     | ReadAntenna | Cable  | Preamp | Level  | Limit  | Over   |           |               |
|---|----------|-------------|--------|--------|--------|--------|--------|-----------|---------------|
|   | MHz      | Level       | Factor | Loss   | Factor | Line   | Limit  | Pol/Phase | Remark        |
|   | MHz      | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB        |               |
| 1 | 1217.190 | 58.80       | 23.34  | 2.61   | 37.98  | 46.77  | 74.00  | -27.23    | VERTICAL peak |
| 2 | 4482.150 | 44.59       | 34.12  | 4.78   | 36.83  | 46.66  | 74.00  | -27.34    | VERTICAL peak |
| 3 | 4924.000 | 43.89       | 34.15  | 5.26   | 36.88  | 46.42  | 74.00  | -27.58    | VERTICAL peak |
| 4 | 6717.762 | 46.05       | 34.42  | 6.87   | 37.05  | 50.29  | 74.00  | -23.71    | VERTICAL peak |
| 5 | 7386.000 | 40.96       | 36.23  | 6.75   | 37.16  | 46.78  | 74.00  | -27.22    | VERTICAL peak |
| 6 | 9848.000 | 39.47       | 38.88  | 7.66   | 37.01  | 49.00  | 74.00  | -25.00    | VERTICAL peak |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 00; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High



Trace: (Discrete)


|   | Freq     | ReadAntenna | Cable  | Preamp | Limit  | Over   |        |        |                 |
|---|----------|-------------|--------|--------|--------|--------|--------|--------|-----------------|
|   | MHz      | Level       | Factor | Loss   | Factor | Level  | Line   | Limit  | Pol/Phase       |
|   | MHz      | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB     |                 |
| 1 | 1252.885 | 61.94       | 23.71  | 2.72   | 37.98  | 50.39  | 74.00  | -23.61 | HORIZONTAL peak |
| 2 | 4405.090 | 45.29       | 33.74  | 4.79   | 36.82  | 47.00  | 74.00  | -27.00 | HORIZONTAL peak |
| 3 | 4924.000 | 43.72       | 34.15  | 5.26   | 36.88  | 46.25  | 74.00  | -27.75 | HORIZONTAL peak |
| 4 | 5239.274 | 50.09       | 33.45  | 5.45   | 36.94  | 52.05  | 74.00  | -21.95 | HORIZONTAL peak |
| 5 | 7386.000 | 40.57       | 36.23  | 6.75   | 37.16  | 46.39  | 74.00  | -27.61 | HORIZONTAL peak |
| 6 | 9848.000 | 39.16       | 38.88  | 7.66   | 37.01  | 48.69  | 74.00  | -25.31 | HORIZONTAL peak |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 09; Polarity: Vertical; Modulation:802.11ah; Bandwidth:2MHz; Channel:Low




|   | Freq     | ReadAntenna Level | Antenna Factor | Cable Loss | Preamplifier Factor | Level  | Limit Line | Over Limit | Pol/Phase | Remark |
|---|----------|-------------------|----------------|------------|---------------------|--------|------------|------------|-----------|--------|
|   | MHz      | dBuV              | dB/m           | dB         | dB                  | dBuV/m | dBuV/m     | dB         |           |        |
| 1 | 1692.231 | 46.97             | 25.09          | 3.07       | 37.93               | 37.20  | 74.00      | -36.80     | VERTICAL  | peak   |
| 2 | 1810.000 | 46.18             | 25.90          | 3.24       | 37.91               | 37.41  | 74.00      | -36.59     | VERTICAL  | peak   |
| 3 | 2715.000 | 46.98             | 28.22          | 4.03       | 37.61               | 41.62  | 74.00      | -32.38     | VERTICAL  | peak   |
| 4 | 3620.000 | 44.62             | 29.33          | 4.69       | 36.92               | 41.72  | 74.00      | -32.28     | VERTICAL  | peak   |
| 5 | 4560.559 | 45.44             | 34.17          | 4.83       | 36.84               | 47.60  | 74.00      | -26.40     | VERTICAL  | peak   |
| 6 | 6914.763 | 43.97             | 34.97          | 7.08       | 37.08               | 48.94  | 74.00      | -25.06     | VERTICAL  | peak   |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 09; Polarity: Horizontal; Modulation:802.11ah; Bandwidth:2MHz; Channel:Low



Trace: (Discrete)


|   | Freq     | ReadAntenna | Cable  | Preamp | Level  | Limit  | Over   |           |                 |
|---|----------|-------------|--------|--------|--------|--------|--------|-----------|-----------------|
|   | MHz      | Level       | Factor | Loss   | Factor | Line   | Limit  | Pol/Phase | Remark          |
|   | MHz      | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB        |                 |
| 1 | 1238.483 | 65.65       | 23.59  | 2.68   | 37.98  | 53.94  | 74.00  | -20.06    | HORIZONTAL peak |
| 2 | 1810.000 | 50.64       | 25.90  | 3.24   | 37.91  | 41.87  | 74.00  | -32.13    | HORIZONTAL peak |
| 3 | 2715.000 | 47.31       | 28.22  | 4.03   | 37.61  | 41.95  | 74.00  | -32.05    | HORIZONTAL peak |
| 4 | 3620.000 | 46.75       | 29.33  | 4.69   | 36.92  | 43.85  | 74.00  | -30.15    | HORIZONTAL peak |
| 5 | 4804.110 | 44.39       | 34.16  | 5.15   | 36.86  | 46.84  | 74.00  | -27.16    | HORIZONTAL peak |
| 6 | 6914.763 | 44.65       | 34.97  | 7.08   | 37.08  | 49.62  | 74.00  | -24.38    | HORIZONTAL peak |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 09; Polarity: Vertical; Modulation:802.11ah; Bandwidth:2MHz; Channel:middle




|   | Freq     | ReadAntenna | Cable  | Preamp |        | Limit  | Over   |        |           |        |
|---|----------|-------------|--------|--------|--------|--------|--------|--------|-----------|--------|
|   | MHz      | Level       | Factor | Loss   | Factor | Level  | Line   | Limit  | Pol/Phase | Remark |
|   | MHz      | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB     |           |        |
| 1 | 1653.550 | 47.61       | 24.89  | 3.03   | 37.93  | 37.60  | 74.00  | -36.40 | VERTICAL  | peak   |
| 2 | 1830.000 | 46.07       | 25.98  | 3.26   | 37.91  | 37.40  | 74.00  | -36.60 | VERTICAL  | peak   |
| 3 | 2745.000 | 46.21       | 28.30  | 4.08   | 37.59  | 41.00  | 74.00  | -33.00 | VERTICAL  | peak   |
| 4 | 3660.000 | 44.89       | 29.47  | 4.71   | 36.91  | 42.16  | 74.00  | -31.84 | VERTICAL  | peak   |
| 5 | 4586.999 | 44.80       | 34.17  | 4.85   | 36.84  | 46.98  | 74.00  | -27.02 | VERTICAL  | peak   |
| 6 | 6995.172 | 44.17       | 35.11  | 7.13   | 37.09  | 49.32  | 74.00  | -24.68 | VERTICAL  | peak   |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 09; Polarity: Horizontal; Modulation:802.11ah; Bandwidth:2MHz; Channel:middle



Trace: (Discrete)


|   | Freq     | ReadAntenna | Cable  | Preamp | Level  | Limit  | Over   | Pol/Phase | Remark          |
|---|----------|-------------|--------|--------|--------|--------|--------|-----------|-----------------|
|   | MHz      | Level       | Factor | Loss   | Factor | Line   | Limit  |           |                 |
|   | MHz      | dBuV        | dB/m   | dB     | dB     | dBuV/m | dBuV/m | dB        |                 |
| 1 | 1289.627 | 48.44       | 23.92  | 2.79   | 37.98  | 37.17  | 74.00  | -36.83    | HORIZONTAL peak |
| 2 | 1830.000 | 44.86       | 25.98  | 3.26   | 37.91  | 36.19  | 74.00  | -37.81    | HORIZONTAL peak |
| 3 | 2745.000 | 46.40       | 28.30  | 4.08   | 37.59  | 41.19  | 74.00  | -32.81    | HORIZONTAL peak |
| 4 | 3660.000 | 43.24       | 29.47  | 4.71   | 36.91  | 40.51  | 74.00  | -33.49    | HORIZONTAL peak |
| 5 | 4613.592 | 44.60       | 34.17  | 4.88   | 36.84  | 46.81  | 74.00  | -27.19    | HORIZONTAL peak |
| 6 | 6640.542 | 44.96       | 34.17  | 6.77   | 37.04  | 48.86  | 74.00  | -25.14    | HORIZONTAL peak |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 09; Polarity: Vertical; Modulation:802.11ah; Bandwidth:2MHz; Channel:High



Trace: (Discrete)


|   | Freq     | ReadAntenna | Cable | Preamp |       | Limit  | Over   |           |               |
|---|----------|-------------|-------|--------|-------|--------|--------|-----------|---------------|
|   | MHz      | Level       | Loss  | Factor | Level | Line   | Limit  | Pol/Phase | Remark        |
|   | MHz      | dBuV        | dB/m  | dB     | dB    | dBuV/m | dBuV/m | dB        |               |
| 1 | 1319.794 | 48.43       | 24.04 | 2.82   | 37.97 | 37.32  | 74.00  | -36.68    | VERTICAL peak |
| 2 | 1850.000 | 46.72       | 26.05 | 3.27   | 37.91 | 38.13  | 74.00  | -35.87    | VERTICAL peak |
| 3 | 2775.000 | 44.96       | 28.39 | 4.12   | 37.55 | 39.92  | 74.00  | -34.08    | VERTICAL peak |
| 4 | 3700.000 | 44.44       | 29.65 | 4.74   | 36.89 | 41.94  | 74.00  | -32.06    | VERTICAL peak |
| 5 | 4721.515 | 44.80       | 34.16 | 5.02   | 36.85 | 47.13  | 74.00  | -26.87    | VERTICAL peak |
| 6 | 6954.852 | 44.27       | 35.04 | 7.10   | 37.09 | 49.32  | 74.00  | -24.68    | VERTICAL peak |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 09; Polarity: Horizontal; Modulation:802.11ah; Bandwidth:2MHz; Channel:High



Trace: (Discrete)

|   | Freq     | ReadAntenna | Cable | Preamp |       | Limit  | Over   |           |                 |
|---|----------|-------------|-------|--------|-------|--------|--------|-----------|-----------------|
|   | Level    | Factor      | Loss  | Factor | Level | Line   | Limit  | Pol/Phase | Remark          |
|   | MHz      | dBuV        | dB/m  | dB     | dB    | dBuV/m | dBuV/m | dB        |                 |
| 1 | 1644.019 | 46.57       | 24.84 | 3.03   | 37.93 | 36.51  | 74.00  | -37.49    | HORIZONTAL peak |
| 2 | 1850.000 | 45.55       | 26.05 | 3.27   | 37.91 | 36.96  | 74.00  | -37.04    | HORIZONTAL peak |
| 3 | 2775.000 | 44.33       | 28.39 | 4.12   | 37.55 | 39.29  | 74.00  | -34.71    | HORIZONTAL peak |
| 4 | 3700.000 | 43.19       | 29.65 | 4.74   | 36.89 | 40.69  | 74.00  | -33.31    | HORIZONTAL peak |
| 5 | 4586.999 | 44.01       | 34.17 | 4.85   | 36.84 | 46.19  | 74.00  | -27.81    | HORIZONTAL peak |
| 6 | 6914.763 | 43.46       | 34.97 | 7.08   | 37.08 | 48.43  | 74.00  | -25.57    | HORIZONTAL peak |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

## 8 Test Setup Photo

Refer to Appendix - Test Setup Photo for GZCR230900096603



## 9 EUT Constructional Details (EUT Photos)

Refer to External and Internal Photos for GZCR2309000966AT



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

## 10 Appendix

### 1. Duty Cycle

#### 1.1 Ant1

##### 1.1.1 Test Result

| Ant1           |         |                 |           |             |                |                                   |                       |
|----------------|---------|-----------------|-----------|-------------|----------------|-----------------------------------|-----------------------|
| Mode           | TX Type | Frequency (MHz) | T_on (ms) | Period (ms) | Duty Cycle (%) | Duty Cycle Correction Factor (dB) | Max. DC Variation (%) |
| 802.11b        | SISO    | 2412            | 100.000   | 100.000     | 100.00         | 0.00                              | 0.00                  |
|                |         | 2437            | 100.000   | 100.000     | 100.00         | 0.00                              | 0.00                  |
|                |         | 2462            | 100.000   | 100.000     | 100.00         | 0.00                              | 0.00                  |
| 802.11g        | SISO    | 2412            | 100.000   | 100.000     | 100.00         | 0.00                              | 0.00                  |
|                |         | 2437            | 100.000   | 100.000     | 100.00         | 0.00                              | 0.00                  |
|                |         | 2462            | 100.000   | 100.000     | 100.00         | 0.00                              | 0.00                  |
| 802.11n (HT20) | SISO    | 2412            | 100.000   | 100.000     | 100.00         | 0.00                              | 0.00                  |
|                |         | 2437            | 100.000   | 100.000     | 100.00         | 0.00                              | 0.00                  |
|                |         | 2462            | 100.000   | 100.000     | 100.00         | 0.00                              | 0.00                  |


| Ant2 |         |                 |           |             |                |                                   |                       |
|------|---------|-----------------|-----------|-------------|----------------|-----------------------------------|-----------------------|
| Mode | TX Type | Frequency (MHz) | T_on (ms) | Period (ms) | Duty Cycle (%) | Duty Cycle Correction Factor (dB) | Max. DC Variation (%) |
| 11ah | SISO    | 905             | 0.762     | 6.999       | 10.89          | 9.63                              | 0.12                  |
|      |         | 915             | 0.763     | 7.001       | 10.90          | 9.63                              | 0.11                  |
|      |         | 925             | 0.764     | 6.999       | 10.92          | 9.62                              | 0.07                  |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)


### 1.1.2 Test Graph




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

### 802.11b\_HCH\_2462MHz\_Ant1 (SISO)\_NTNV




### 802.11g\_LCH\_2412MHz\_Ant1 (SISO)\_NTNV




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

### 802.11g\_MCH\_2437MHz\_Ant1 (SISO)\_NTNV




### 802.11g\_HCH\_2462MHz\_Ant1 (SISO)\_NTNV




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

### 802.11n(HT20)\_LCH\_2412MHz\_Ant1 (SISO)\_NTNV




### 802.11n(HT20)\_MCH\_2437MHz\_Ant1 (SISO)\_NTNV




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

### 802.11n(HT20)\_HCH\_2462MHz\_Ant1 (SISO)\_NTNV




### 11ah\_LCH\_905MHz\_Ant2\_NTNV




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

### 11ah\_MCH\_915MHz\_Ant2\_NTNV



### 11ah\_HCH\_925MHz\_Ant2\_NTNV



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

## 2. Bandwidth

### 2.1 6dB BW

#### 2.1.1 Test Result

| Mode           | TX Type | Frequency (MHz) | ANT | 6dB Bandwidth (MHz) |            | Verdict |
|----------------|---------|-----------------|-----|---------------------|------------|---------|
|                |         |                 |     | Result              | Limit      |         |
| 802.11b        | SISO    | 2412            | 1   | 9.759               | $\geq 0.5$ | Pass    |
|                |         | 2437            | 1   | 9.760               | $\geq 0.5$ | Pass    |
|                |         | 2462            | 1   | 9.760               | $\geq 0.5$ | Pass    |
| 802.11g        | SISO    | 2412            | 1   | 16.539              | $\geq 0.5$ | Pass    |
|                |         | 2437            | 1   | 16.542              | $\geq 0.5$ | Pass    |
|                |         | 2462            | 1   | 16.540              | $\geq 0.5$ | Pass    |
| 802.11n (HT20) | SISO    | 2412            | 1   | 17.756              | $\geq 0.5$ | Pass    |
|                |         | 2437            | 1   | 17.764              | $\geq 0.5$ | Pass    |
|                |         | 2462            | 1   | 17.768              | $\geq 0.5$ | Pass    |


| Mode | TX Type | Frequency (MHz) | ANT | 6dB Bandwidth (MHz) |            | Verdict |
|------|---------|-----------------|-----|---------------------|------------|---------|
|      |         |                 |     | Result              | Limit      |         |
| 11ah | SISO    | 905             | 2   | 1.777               | $\geq 0.5$ | Pass    |
|      |         | 915             | 2   | 1.791               | $\geq 0.5$ | Pass    |
|      |         | 925             | 2   | 1.800               | $\geq 0.5$ | Pass    |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)


### 2.2.2 Test Graph




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

### 802.11b\_HCH\_2462MHz\_Ant1 (SISO)\_NTNV




### 802.11g\_LCH\_2412MHz\_Ant1 (SISO)\_NTNV




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

### 802.11g\_MCH\_2437MHz\_Ant1 (SISO)\_NTNV



### 802.11g\_HCH\_2462MHz\_Ant1 (SISO)\_NTNV



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)