FCC Part 15
EMI TEST REPORT

of

E.U.T. : Wireless LAN CardBus PC Card (802.11b/g)

FCC ID. : MQ4WG2K4

MODEL : WG2400

for

APPLICANT : AboCom Systems Inc.

ADDRESS : 1F, No.21, R&D Rd.II, SBIP, Hsin-Chu, Taiwan, R.O.C.

Test Performed by

ELECTRONICS TESTING CENTER, TAIWAN
NO. 34, LIN 5, DING FU TSUN, LINKOU HSIANG
TAIPEI HSIEN, TAIWAN, R.O.C.
Tel : (02)26023052 Fax : (02)26010910
http://www.etc.org.tw ; e-mail: etcemi@seed.net.tw

Report Number : ET92R-08-073-03

TEST REPORT CERTIFICATION

Applicant : AboCom Systems Inc.
1F, No.21, R&D Rd.II, SBIP, Hsin-Chu, Taiwan, R.O.C.

Manufacturer : AboCom Systems Inc.
No. 77, Yu-Yih Rd., Chu-Nan Chen, Miao-Lih Hsuan 350, Taiwan, R.O.C.

Description of EUT :

a) Type of EUT : Wireless LAN CardBus PC Card (802.11b/g)

b) Trade Name : AboCom

c) Model No. : WG2400

d) Power Supply : From Notebook PC

Regulation Applied : FCC Rules and Regulations Part 15 Subpart B & C (2002)

I HEREBY CERTIFY THAT: The data shown in this report were made in accordance with the procedures given in ANSI C63.4, and the energy emitted by the device was founded to be within the limits applicable. I assume full responsibility for accuracy and completeness of these data.

Note: 1. The result of the testing report relate only to the item tested.
2. The testing report shall not be reproduced expect in full, without the written approval of ETC.

Issued Date : Sep. 03, 2003

Test Engineer : Tien Lu Liao
(Tien Lu Liao)

Approve & Authorized Signer : Will Yauo
Will Yauo, Manager
EMC Dept. II of ELECTRONICS
TESTING CENTER, TAIWAN

Table of Contents Page

1 GENERAL INFORMATION 1

1.1 Product Description 1
1.2 Characteristics of Device 1
1.3 Test Methodology 1
1.4 Test Facility 1

2 PROVISIONS APPLICABLE 2

2.1 Definition 2
2.2 Requirement for Compliance 3
2.3 Restricted Bands of Operation 5
2.4 Labeling Requirement 5
2.5 User Information 6

3. SYSTEM TEST CONFIGURATION 7

3.1 Justification 7
3.2 Devices for Tested System 7

4 RADIATED EMISSION MEASUREMENT 8

4.1 Applicable Standard 8
4.2 Measurement Procedure 8
4.3 Measuring Instrument 10
4.4 Radiated Emission Data 11
4.4.1 RF Portion 11
4.4.2 Radiated Eimssion of Restricted bands 17
4.4.3 Other Emission 21
4.5 Field Strength Calculation 22
4.6 Photos of Radiation Measuring Setup 23

5 CONDUCTED EMISSION MEASUREMENT 24

5.1 Standard Applicable 24
5.2 Measurement Procedure 24
5.3 Conducted Emission Data 25
5.4 Result Data Calculation 28
5.5 Conducted Measurement Equipment 29
5.6 Photos of Conduction Measuring Setup 30

6 ANTENNA REQUIREMENT 31

6.1 Standard Applicable 31
6.2 Antenna Construction and Directional Gain 31

7 EMISSION BANDWIDTH MEASUREMENT 32

7.1 Standard Applicable 32
7.2 Measurement Procedure 32
7.3 Measurement Equipment 32
7.4 Measurement Data 33

8 OUTPUT POWER MEASUREMENT 34

8.1 Standard Applicable 34
8.2 Measurement Procedure 34
8.3 Measurement Equipment 34
8.4 Measurement Data 35

9 100 KHZ BANDWIDTH OF BAND EDGES MEASUREMENT 36

9.1 Standard Applicable 36
9.2 Measurement Procedure 36
9.3 Measurement Equipment 36
9.4 Measurement Data 37

10 POWER DENSITY MEASUREMENT 38

10.1 Standard Applicable 38
10.2 Measurement Procedure 38
10.3 Measurement Equipment 38
10.4 Measurement Data 39

11. OUT-OF-BAND CONDUCTED EMISSION MEASUREMENT 40

11.1 Standard Applicable 40
11.2 Measurement Procedure 40
11.3 Measurement Equipment 40
11.4 Measurement Data 41

APPENDIX 1 : PLOTED DATAS OF POWER LINE CONDUCTED EMISSIONS 1

APPENDIX 2 : PLOTED DATAS OF EMISSIONS BANDWIDTH 14

APPENDIX 3 : PLOTED DATAS OF OUTPUT PEAK POWER 21

APPENDIX 4 : PLOTED DATAS OF BAND EDGE EMISSION 28

APPENDIX 5 : PLOTED DATAS OF POWER DENSITY 33

APPENDIX 6 : PLOTTED DATA FOR OUT-OF-BAND CONDUCTED EMISSION 40

1 GENERAL INFORMATION

1.1 Product Description

a) Type of EUT : Wireless LAN CardBus PC Card (802.11b/g)
b) Trade Name : AboCom
c) Model No. : WG2400
d) Power Supply : From Notebook PC

1.2 Characteristics of Device

The 802.11g Wireless 32bit CardBus PC Card is a device that lets you connect your notebook to a wireless local area network (LAN) is like a regular LAN, except that you can share information without looking for a place to plug in, and augment networks without installing or moving wires. Based on radio frequency (RF) technology, a wireless LAN transmits and receives data over the air, along with the quarantee to provide privacy and noninterference by the use of separate radio frequency.

1.3 Test Methodology

For Wireless LAN CardBus PC Card (802.11b/g), both conducted and radiated emissions were performed according to the procedures illustrated in ANSI C63.4 (1992) and for processing gain measurement is according to FCC Public Notice. Other required measurements were illustrated in separate sections of this test report for details.

1.4 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located on the roof top of Building at No. 34, Lin 5, Ding Fu Tsun, Linkou Hsiang, Taipei Hsien, Taiwan 244, R.O.C.
This site has been fully described in a report submitted to your toffice, and accepted in a letter dated Feb. 10, 2000.

2 PROVISIONS APPLICABLE

2.1 Definition

Unintentional radiator:

A device that intentionally generates and radio frequency energy for use within the device, or that sends radio frequency signals by conduction to associated equipment via connecting wiring, but which is not intended to emit RF energy by radiation or induction.

Class A Digital Device:

A digital device which is marketed for use in commercial or business environment; exclusive of a device which is market for use by the general public, or which is intended to be used in the home.

Class B Digital Device :

A digital device which is marketed for use in a residential environment notwithstanding use in a commercial, business of industrial environment. Example of such devices that are marketed for the general public.

Note : A manufacturer may also qualify a device intended to be marketed in a commercial, business, or industrial environment as a Class B digital device, and in fact is encouraged to do so, provided the device complies with the technical specifications for a Class B Digital Device. In the event that a particular type of device has been found to repeatedly cause harmful interference to radio communications, the Commission may classify such a digital device as a Class B Digital Device, Regardless of its intended use.

Intentional radiator:

A device that intentionally generates and emits radio frequency energy by radiation or induction.

2.2 Requirement for Compliance

(1) Conducted Emission Requirement

Except for Class A digital devices, for equpment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50ì H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the band edges.

Frequency MHz	Quasi Peak dB μ V	Average dB μ V
0.15 - 0.5	66-56*	56-46*
0.5 - 5.0	56	46
5.0 - 30.0	60	50

* Decreases with the logarithm of the frequency

(2) Radiated Emission Requirement

For unintentional device, according to § 15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency MHz	Distance Meters	Radiated dB μ V/m	Radiated μ V/m
30 - 88	3	40.0	100
88 - 216	3	43.5	150
216 - 960	3	46.0	200
Above 960	3	54.0	500

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table.

(3) Antenna Requirement

For intentional device, according to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

(4) Bandwidth Requirement

For direct sequence system, according to 15.247(a)(2), the minimum 6dB bandwidth shall be at least 500 kHz.

(5) Output Power Requirement

For direct sequence system, according to 15.247(b), the maximum peak output power of the transmitter shall not exceed 1 Watt. If transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(6) 100 kHz Bandwidth of Frequency Band Edges Requirement

According to 15.247(c), if any 100 kHz bandwidth outside these frequency bands, the radio frequency power that is produced by the modulation products of the spreading sequence, the information sequence and the carrier frequency shall be either at least 20 dB below that in any 100 kHz bandwidth within the band that contains the highest level of the desired power or shall not exceed the general levels specified in § 15.209(a), whichever results in the lesser attenuation.

(7) Power Density Requirement

According to 15.247(d), for direct sequence systems, the transmitted power density averaged over any 1 second interval shall not be greater than 8 dBm in any 3 kHz bandwidth within these bands.

2.3 Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below :

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42-16.423	399.9-410	4.5-5.15
0.495 - 0.505 **	16.69475 - 16.69525	608-614	5.35-5.46
2.1735 - 2.1905	16.80425 - 16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475 - 156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2655-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3360-4400	Above 38.6
13.36-13.41			

** : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

2.4 Labeling Requirement

The device shall bear the following statement in a conspicuous location on the device :

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions : (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

2.5 User Information

The users manual or instruction manual for an intentional or unintentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

For a Class B digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual.

The Federal Communications Commission Radio Frequency Interference Statement includes the following paragraph.

This equipment has been tested and found to comply with the limits for a Class B Digital Device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.

This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instruction may cause harmful interference to radio communication. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

-- Reorient or relocate the receiving antenna.

-- Increase the separation between the equipment and receiver.

-- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.

-- Consult the dealer or an experienced radio / TV technician for help.

3. SYSTEM TEST CONFIGURATION

3.1 Justification

For both radiated and conducted emissions below 1 GHz, the system was configured for testing in a typical fashion as a customer would normally use it. The peripherals other than EUT were connected in normally standing by situation. Measurement was performed under the condition that a computer program was exercised to simulate data communication of EUT, and the transmission rate was set to maximum allowed by EUT. Three highest emissions were verified with varying placement of the transmitting antenna connected to EUT to maximize the emission from EUT.

For conducted emissions, only measured on TX and RX operation, for the digital circuits portion also function normally whenever TX or RX is operated. For radiated emissions, whichever RF channel is operated, the digital circuits function identically. As the reason, measurement of radiated emissions from digital circuits is only performed with channel 7 by transmitting mode.

During the preliminary test, the worse case is the antenna with a cable, and data presented in this test report just shows the worse case.

3.2 Devices for Tested System

Device	Manufacture	Model / FCC ID.	Cable Description
Wireless LAN CardBus PC Card (802.11b/g) *	AboCom Systems Inc.	WG2400/ MQ4WG2K4	----
Printer	Hewlett-Packard	2225C+	1.2m Shielded Cable
Notebook PC	ASUS	L1400	1.8m Unshielded AC Power Cord

Remark "*" means equipment under test.

4 RADIATED EMISSION MEASUREMENT

4.1 Applicable Standard

For unintentional radiator, the radiated emission shall comply with § 15.109(a).
For intentional radiators, according to § 15.247 (a), operation under this provision is limited to frequency hopping and direct sequence spread spectrum, and the out band emission shall be comply with § 15.247 (c)

4.2 Measurement Procedure

1. Setup the configuration per figure 1 and 2 for frequencies measured below and above 1 GHz respectively.
2. For emission frequencies measured below 1 GHz, a pre-scan is performed in a shielded chamber to determine the accurate frequencies of higher emissions will be checked on a open test site. As the same purpose, for emission frequencies measured above 1 GHz, a pre-scan also be performed with a 1 meter measuring distance before final test.
3. For emission frequencies measured below and above 1 GHz, set the spectrum analyzer on a 100 kHz and 1 MHz resolution bandwidth respectively for each frequency measured in step 2.
4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0 ° to 360 ° with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading. A RF test receiver is also used to confirm emissions measured.
5. Repeat step 4 until all frequencies need to be measured were complete.
6. Repeat step 5 with search antenna in vertical polarized orientations.
7. Check the three frequencies of highest emission with varying the placement of cables associated with EUT to obtain the worse case and record the result.

Figure 1 : Frequencies measured below 1 GHz configuration



Figure 2 : Frequencies measured above 1 GHz configuration



4.3 Measuring Instrument

The following instrument are used for radiated emissions measurement:

Equipment	Manufacturer	Model No.	Next Cal. Due
Spectrum Analyzer	Hewlett-Packard	8568B	01/09/2004
Pre-selector	Hewlett-Packard	85685A	01/09/2004
Quasi Peak Detector	Hewlett-Packard	85650A	01/09/2004
Spectrum Analyzer	Adventest	R3271	09/08/2003
RF Test Receiver	Rohde & Schwarz	ESVS 30	08/05/2004
Horn Antenna	EMCO	3115	05/28/2004
Horn Antenna	EMCO	3116	01/10/2004
Log periodic Antenna	EMCO	3146	12/05/2003
Biconical Antenna	EMCO	3110B	11/05/2003
Preamplifier	Hewlett-Packard	8449B	05/28/2004
Preamplifier	Hewlett-Packard	8447D	09/29/2003
Spectrum Analyzer	Hewlett-Packard	8564E	04/16/2004

Measuring instrument setup in measured frequency band when specified detector function is used :

Frequency Band (MHz)	Instrument	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	RF Test Receiver	Quasi-Peak	120 kHz	N/A
	Spectrum Analyzer	Peak	100 kHz	100 kHz
Above 1000	Spectrum Analyzer	Peak	1 MHz	1 MHz
	Spectrum Analyzer	Average	1 MHz	300 Hz

4.4 Radiated Emission Data

4.4.1 RF Portion

A. 802.11b

a) Channel 1

Operation Mode : Receiving /Transmitting

Fundamental Frequency : 2412 MHz (Local Frequency : 2038 MHz)

Test Date : Aug. 24, 2003 Temperature : 23 ℃ Humidity : 70 %

Frequency (MHz)	Reading (dBuV) H Peak	H Ave	V Peak	V Ave	Factor (dB) Corr.	Result @3m (dBuV/m) Peak	Result Ave	Limit @3m (dBuV/m) Peak	Limit Ave.	Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
* 2038.000	---	---	---	---	-4.5	---	---	74.0	54.0	---	---	---
* 4076.000	---	---	---	---	2.0	---	---	74.0	54.0	---	---	---
* 6114.000	---	---	---	---	4.5	---	---	74.0	54.0	---	---	---
* 8152.000	---	---	---	---	6.5	---	---	74.0	54.0	---	---	---
* 10190.000	---	---	---	---	7.6	---	---	74.0	54.0	---	---	---
4824.108	---	---	47.3	39.5	2.6	49.9	42.1	74.0	54.0	-11.9	270	1.4
7236.162	---	---	---	---	5.8	---	---	74.0	54.0	---	---	---
9648.216	---	---	---	---	7.3	---	---	74.0	54.0	---	---	---
12060.270	---	---	---	---	9.2	---	---	74.0	54.0	---	---	---
14472.324	---	---	---	---	11.6	---	---	74.0	54.0	---	---	---
16884.378	---	---	---	---	12.1	---	---	74.0	54.0	---	---	---
19296.432	---	---	---	---	8.8	---	---	74.0	54.0	---	---	---
21708.486	---	---	---	---	9.8	---	---	74.0	54.0	---	---	---
24120.540	---	---	---	---	10.4	---	---	74.0	54.0	---	---	---

Note :

1. *Item of margin shown in above table refer to average limit.*
2. *It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark "***" means that Peak result is meet average limit.*
3. *Remark "---" means that the emissions level is too low to be measured.*
4. *Item "Margin" referred to Average limit while there is only peak result.*
5. *The expanded uncertainty of the radiated emission tests is 3.53 dB.*
6. *Remark "*" means the receiving local frequency and the harmonics.*

b) Channel 6

Operation Mode : Receiving / Transmitting

Fundamental Frequency : 2437 MHz (Local Frequency : 2063 MHz)

Test Date : Aug. 24, 2003 Temperature : 23 ℃ Humidity : 61 %

Frequency (MHz)	Reading (dBuV) H Peak	H Ave	V Peak	V Ave	Factor (dB) Corr.	Result @3m (dBuV/m) Peak	Result Ave	Limit @3m (dBuV/m) Peak	Limit Ave.	Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
* 2063.000	---	---	---	---	-4.4	---	---	74.0	54.0	---	---	---
* 4126.000	---	---	---	---	2.0	---	---	74.0	54.0	---	---	---
* 6189.000	---	---	---	---	4.5	---	---	74.0	54.0	---	---	---
* 8252.000	---	---	---	---	6.6	---	---	74.0	54.0	---	---	---
* 10315.000	---	---	---	---	7.7	---	---	74.0	54.0	---	---	---
4874.100	---	---	47.3	36.4	2.7	50.0	39.1	74.0	54.0	-14.9	270	1.4
7311.150	---	---	---	---	5.9	---	---	74.0	54.0	---	---	---
9748.200	---	---	---	---	7.3	---	---	74.0	54.0	---	---	---
12185.250	---	---	---	---	9.3	---	---	74.0	54.0	---	---	---
14622.300	---	---	---	---	11.6	---	---	74.0	54.0	---	---	---
17059.350	---	---	---	---	13.1	---	---	74.0	54.0	---	---	---
19496.400	---	---	---	---	8.5	---	---	74.0	54.0	---	---	---
21933.450	---	---	---	---	9.9	---	---	74.0	54.0	---	---	---
24370.500	---	---	---	---	10.7	---	---	74.0	54.0	---	---	---

Note :

1. *Item of margin shown in above table refer to average limit.*
2. *It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark "***" means that Peak result is meet average limit.*
3. *Remark "---" means that the emissions level is too low to be measured.*
4. *Item "Margin" referred to Average limit while there is only peak result.*
5. *The expanded uncertainty of the radiated emission tests is 3.53 dB.*
6. *Remark "*" means the receiving local frequency and the harmonics.*

c) Channel 11

Operation Mode : Receiving / Transmitting

Fundamental Frequency : 2462 MHz (Local Frequency : 2088 MHz)

Test Date : Aug. 24, 2003 Temperature : 23 ℃ Humidity : 70 %

Frequency (MHz)	Reading (dBuV) H Peak	H Ave	V Peak	V Ave	Factor (dB) Corr.	Result @3m (dBuV/m) Peak	Result Ave	Limit @3m (dBuV/m) Peak	Limit Ave.	Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
* 2088.000	---	---	---	---	-4.3	---	---	74.0	54.0	---	---	---
* 4176.000	---	---	---	---	2.0	---	---	74.0	54.0	---	---	---
* 6264.000	---	---	---	---	4.5	---	---	74.0	54.0	---	---	---
* 8352.000	---	---	---	---	6.7	---	---	74.0	54.0	---	---	---
* 10440.000	---	---	---	---	7.8	---	---	74.0	54.0	---	---	---
4924.175	---	---	47.1	39.4	2.8	49.9	42.2	74.0	54.0	-6.1	270	1.4
7386.263	---	---	---	---	6.0	---	---	74.0	54.0	---	---	---
9848.351	---	---	---	---	7.3	---	---	74.0	54.0	---	---	---
12310.439	---	---	---	---	9.3	---	---	74.0	54.0	---	---	---
14772.527	---	---	---	---	11.5	---	---	74.0	54.0	---	---	---
17234.615	---	---	---	---	14.3	---	---	74.0	54.0	---	---	---
19696.703	---	---	---	---	8.5	---	---	74.0	54.0	---	---	---
22158.791	---	---	---	---	10.0	---	---	74.0	54.0	---	---	---
24620.879	---	---	---	---	10.9	---	---	74.0	54.0	---	---	---

Note :

1. *Item of margin shown in above table refer to average limit.*
2. *It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark "***" means that Peak result is meet average limit.*
3. *Remark "---" means that the emissions level is too low to be measured.*
4. *Item "Margin" referred to Average limit while there is only peak result.*
5. *The expanded uncertainty of the radiated emission tests is 3.53 dB.*
6. *Remark "*" means the receiving local frequency and the harmonics.*

B. 802.11g

a) Channel 1

Operation Mode : Receiving /Transmitting

Fundamental Frequency : 2412 MHz (Local Frequency : 2038 MHz)

Test Date : Aug. 24, 2003 Temperature : 23 ℃ Humidity : 70 %

Frequency (MHz)	Reading (dBuV) H Peak	H Ave	V Peak	V Ave	Factor (dB) Corr.	Result @3m (dBuV/m) Peak	Result Ave	Limit @3m (dBuV/m) Peak	Limit Ave.	Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
* 2038.000	---	---	---	---	-4.5	---	---	74.0	54.0	---	---	---
* 4076.000	---	---	---	---	2.0	---	---	74.0	54.0	---	---	---
* 6114.000	---	---	---	---	4.5	---	---	74.0	54.0	---	---	---
* 8152.000	---	---	---	---	6.5	---	---	74.0	54.0	---	---	---
* 10190.000	---	---	---	---	7.6	---	---	74.0	54.0	---	---	---
4824.113	---	---	43.5	33.6	2.6	46.1	36.2	74.0	54.0	-17.8	270	1.4
7236.170	---	---	---	---	5.8	---	---	74.0	54.0	---	---	---
9648.226	---	---	---	---	7.3	---	---	74.0	54.0	---	---	---
12060.283	---	---	---	---	9.2	---	---	74.0	54.0	---	---	---
14472.339	---	---	---	---	11.6	---	---	74.0	54.0	---	---	---
16884.396	---	---	---	---	12.1	---	---	74.0	54.0	---	---	---
19296.452	---	---	---	---	8.8	---	---	74.0	54.0	---	---	---
21708.509	---	---	---	---	9.8	---	---	74.0	54.0	---	---	---
24120.565	---	---	---	---	10.4	---	---	74.0	54.0	---	---	---

Note :

1. *Item of margin shown in above table refer to average limit.*
2. *It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark "***" means that Peak result is meet average limit.*
3. *Remark "---" means that the emissions level is too low to be measured.*
4. *Item "Margin" referred to Average limit while there is only peak result.*
5. *The expanded uncertainty of the radiated emission tests is 3.53 dB.*
6. *Remark "*" means the receiving local frequency and the harmonics.*

b) Channel 6

Operation Mode : Receiving / Transmitting

Fundamental Frequency : 2437 MHz (Local Frequency : 2063 MHz)

Test Date : Aug. 24, 2003 Temperature : 23 ℃ Humidity : 61 %

Frequency (MHz)	Reading (dBuV) H Peak	H Ave	V Peak	V Ave	Factor (dB) Corr.	Result @3m (dBuV/m) Peak	Result Ave	Limit @3m (dBuV/m) Peak	Limit Ave.	Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
* 2063.000	---	---	---	---	-4.4	---	---	74.0	54.0	---	---	---
* 4126.000	---	---	---	---	2.0	---	---	74.0	54.0	---	---	---
* 6189.000	---	---	---	---	4.5	---	---	74.0	54.0	---	---	---
* 8252.000	---	---	---	---	6.6	---	---	74.0	54.0	---	---	---
* 10315.000	---	---	---	---	7.7	---	---	74.0	54.0	---	---	---
4874.101	---	---	44.3	33.2	2.7	47.0	35.9	74.0	54.0	-18.1	270	1.4
7311.152	---	---	---	---	5.9	---	---	74.0	54.0	---	---	---
9748.202	---	---	---	---	7.3	---	---	74.0	54.0	---	---	---
12185.253	---	---	---	---	9.3	---	---	74.0	54.0	---	---	---
14622.303	---	---	---	---	11.6	---	---	74.0	54.0	---	---	---
17059.354	---	---	---	---	13.1	---	---	74.0	54.0	---	---	---
19496.404	---	---	---	---	8.5	---	---	74.0	54.0	---	---	---
21933.455	---	---	---	---	9.9	---	---	74.0	54.0	---	---	---
24370.505	---	---	---	---	10.7	---	---	74.0	54.0	---	---	---

Note :

1. *Item of margin shown in above table refer to average limit.*
2. *It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark "***" means that Peak result is meet average limit.*
3. *Remark "---" means that the emissions level is too low to be measured.*
4. *Item "Margin" referred to Average limit while there is only peak result.*
5. *The expanded uncertainty of the radiated emission tests is 3.53 dB.*
6. *Remark "*" means the receiving local frequency and the harmonics.*

c) Channel 11

Operation Mode : Receiving / Transmitting

Fundamental Frequency : 2462 MHz (Local Frequency : 2088 MHz)

Test Date : Aug. 24, 2003 Temperature : 23 ℃ Humidity : 70 %

Frequency (MHz)	Reading (dBuV) H Peak	H Ave	V Peak	V Ave	Factor (dB) Corr.	Result @3m (dBuV/m) Peak	Result Ave	Limit @3m (dBuV/m) Peak	Limit Ave.	Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
* 2088.000	---	---	---	---	-4.3	---	---	74.0	54.0	---	---	---
* 4176.000	---	---	---	---	2.0	---	---	74.0	54.0	---	---	---
* 6264.000	---	---	---	---	4.5	---	---	74.0	54.0	---	---	---
* 8352.000	---	---	---	---	6.7	---	---	74.0	54.0	---	---	---
* 10440.000	---	---	---	---	7.8	---	---	74.0	54.0	---	---	---
4923.970	---	---	40.1	35.1	2.8	42.9	37.9	74.0	54.0	-16.1	270	1.4
7385.955	---	---	---	---	6.0	---	---	74.0	54.0	---	---	---
9847.940	---	---	---	---	7.3	---	---	74.0	54.0	---	---	---
12309.925	---	---	---	---	9.3	---	---	74.0	54.0	---	---	---
14771.910	---	---	---	---	11.5	---	---	74.0	54.0	---	---	---
17233.895	---	---	---	---	14.3	---	---	74.0	54.0	---	---	---
19695.880	---	---	---	---	8.5	---	---	74.0	54.0	---	---	---
22157.865	---	---	---	---	10.0	---	---	74.0	54.0	---	---	---
24619.850	---	---	---	---	10.9	---	---	74.0	54.0	---	---	---

Note :

1. *Item of margin shown in above table refer to average limit.*
2. *It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark "***" means that Peak result is meet average limit.*
3. *Remark "---" means that the emissions level is too low to be measured.*
4. *Item "Margin" referred to Average limit while there is only peak result.*
5. *The expanded uncertainty of the radiated emission tests is 3.53 dB.*
6. *Remark "*" means the receiving local frequency and the harmonics.*

4.4.2 Radiated Eimssion of Restricted bands

A. 802.11b

1. Operation Mode : Transmitting / Receiving

Test Date : Aug. 26, 2003 Temperature : 25 ℃ Humidity : 60 %

Frequency (MHz)	Reading (dBuV) H Peak	H Ave	V Peak	V Ave	Factor (dB) Corr.	Result @3m (dBuV/m) Peak	Ave	Limit @3m (dBuV/m) Peak	Ave.	Table Deg. (Deg.)	Ant. High (m)
1240.000	44.3	***	36.3	***	-9.1	35.2	***	74.0	54.0	203	1.1
1475.000	---	---	---	---	-8.8	---	---	74.0	54.0	---	---
1565.000	---	---	---	---	-7.3	---	---	74.0	54.0	---	---
1645.800	---	---	---	---	-6.8	---	---	74.0	54.0	---	---
1721.000	40.3	***	38.6	***	-6.4	33.9	***	74.0	54.0	96	1.3
1781.000	---	---	---	---	-6.2	---	---	74.0	54.0	---	---
2283.000	---	---	---	---	-3.6	---	---	74.0	54.0	---	---
2356.000	---	---	---	---	-3.3	---	---	74.0	54.0	---	---
2499.000	---	---	---	---	-2.7	---	---	74.0	54.0	---	---
2780.000	---	---	---	---	-1.8	---	---	74.0	54.0	---	---
2789.000	---	---	---	---	-1.8	---	---	74.0	54.0	---	---
3263.500	---	---	---	---	-0.6	---	---	74.0	54.0	---	---
3338.000	---	---	---	---	-0.4	---	---	74.0	54.0	---	---
3351.000	---	---	---	---	-0.4	---	---	74.0	54.0	---	---
3847.000	---	---	---	---	1.4	---	---	74.0	54.0	---	---
3951.000	---	---	---	---	1.8	---	---	74.0	54.0	---	---
4133.000	---	---	---	---	2.0	---	---	74.0	54.0	---	---
4353.000	---	---	---	---	2.0	---	---	74.0	54.0	---	---
4578.000	---	---	---	---	2.1	---	---	74.0	54.0	---	---
5017.000	---	---	---	---	2.9	---	---	74.0	54.0	---	---
5385.000	---	---	---	---	4.1	---	---	74.0	54.0	---	---
5446.000	---	---	---	---	4.2	---	---	74.0	54.0	---	---
7578.000	---	---	---	---	6.2	---	---	74.0	54.0	---	---
8235.000	---	---	---	---	6.6	---	---	74.0	54.0	---	---
8411.000	---	---	---	---	6.7	---	---	74.0	54.0	---	---
9073.000	---	---	---	---	7.0	---	---	74.0	54.0	---	---
9190.000	---	---	---	---	7.1	---	---	74.0	54.0	---	---
9384.000	---	---	---	---	7.2	---	---	74.0	54.0	---	---

2. Operation Mode : Transmitting / Receiving

Test Date : Aug. 28, 2003 Temperature : 25 ℃ Humidity : 60 %

Frequency (MHz)	Reading (dBuV) H Peak	H Ave	V Peak	V Ave	Factor (dB) Corr.	Result @3m (dBuV/m) Peak	Ave	Limit @3m (dBuV/m) Peak	Ave.	Table Deg. (Deg.)	Ant. High (m)
9470.000	---	---	---	---	7.2	---	---	74.0	54.0	---	---
10734.000	---	---	---	---	8.2	---	---	74.0	54.0	---	---
11524.000	---	---	---	---	9.1	---	---	74.0	54.0	---	---
12577.000	---	---	---	---	9.5	---	---	74.0	54.0	---	---
13390.000	---	---	---	---	10.8	---	---	74.0	54.0	---	---
14490.000	---	---	---	---	11.6	---	---	74.0	54.0	---	---
15799.000	---	---	---	---	8.3	---	---	74.0	54.0	---	---
16138.000	---	---	---	---	8.3	---	---	74.0	54.0	---	---
17998.000	---	---	---	---	8.4	---	---	74.0	54.0	---	---
20345.000	---	---	---	---	8.6	---	---	74.0	54.0	---	---
22356.000	---	---	---	---	9.7	---	---	74.0	54.0	---	---
22786.000	---	---	---	---	10.5	---	---	74.0	54.0	---	---
23945.000	---	---	---	---	10.4	---	---	74.0	54.0	---	---
31658.000	---	---	---	---	13.5	---	---	74.0	54.0	---	---
31768.000	---	---	---	---	13.7	---	---	74.0	54.0	---	---
36785.000	---	---	---	---	13.8	---	---	74.0	54.0	---	---

Note :

1. *Item of margin shown in above table refer to average limit.*
2. *It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark "***" means that Peak result is meet average limit.*
3. *Remark "---" means that the emissions level is too low to be measured.*
4. *Item "Margin" referred to Average limit while there is only peak result.*
5. *The expanded uncertainty of the radiated emission tests is 3.53 dB.*

B. 802.11g

1. Operation Mode : Transmitting / Receiving

Test Date : Aug. 26, 2003 Temperature : 25 ℃ Humidity : 60 %

Frequency (MHz)	Reading (dBuV) H Peak	H Ave	V Peak	V Ave	Factor (dB) Corr.	Result @3m (dBuV/m) Peak	Ave	Limit @3m (dBuV/m) Peak	Ave.	Table Deg. (Deg.)	Ant. High (m)
1138.000	43.2	***	34.5	***	-9.1	34.1	***	74.0	54.0	203	1.1
1475.000	---	---	---	---	-8.8	---	---	74.0	54.0	---	---
1527.000	---	---	---	---	-7.3	---	---	74.0	54.0	---	---
1645.800	---	---	---	---	-6.8	---	---	74.0	54.0	---	---
1722.300	39.2	***	38.7	***	-6.4	32.8	***	74.0	54.0	96	1.3
1780.000	---	---	---	---	-6.2	---	---	74.0	54.0	---	---
2215.000	---	---	---	---	-3.6	---	---	74.0	54.0	---	---
2356.000	---	---	---	---	-3.3	---	---	74.0	54.0	---	---
2498.000	---	---	---	---	-2.7	---	---	74.0	54.0	---	---
2788.000	---	---	---	---	-1.8	---	---	74.0	54.0	---	---
2815.000	---	---	---	---	-1.8	---	---	74.0	54.0	---	---
3265.000	---	---	---	---	-0.6	---	---	74.0	54.0	---	---
3338.000	---	---	---	---	-0.4	---	---	74.0	54.0	---	---
3354.000	---	---	---	---	-0.4	---	---	74.0	54.0	---	---
3849.000	---	---	---	---	1.4	---	---	74.0	54.0	---	---
3951.000	---	---	---	---	1.8	---	---	74.0	54.0	---	---
4133.000	---	---	---	---	2.0	---	---	74.0	54.0	---	---
4352.000	---	---	---	---	2.0	---	---	74.0	54.0	---	---
4579.000	---	---	---	---	2.1	---	---	74.0	54.0	---	---
5017.000	---	---	---	---	2.9	---	---	74.0	54.0	---	---
5382.000	---	---	---	---	4.1	---	---	74.0	54.0	---	---
5432.000	---	---	---	---	4.2	---	---	74.0	54.0	---	---
7568.000	---	---	---	---	6.2	---	---	74.0	54.0	---	---
8234.000	---	---	---	---	6.6	---	---	74.0	54.0	---	---
8411.000	---	---	---	---	6.7	---	---	74.0	54.0	---	---
9073.000	---	---	---	---	7.0	---	---	74.0	54.0	---	---
9190.000	---	---	---	---	7.1	---	---	74.0	54.0	---	---
9384.000	---	---	---	---	7.2	---	---	74.0	54.0	---	---

2. Operation Mode : Transmitting / Receiving

Test Date : Aug. 28, 2003 Temperature : 25 ℃ Humidity : 60 %

Frequency (MHz)	Reading (dBuV) H Peak	H Ave	V Peak	V Ave	Factor (dB) Corr.	Result @3m (dBuV/m) Peak	Ave	Limit @3m (dBuV/m) Peak	Ave.	Table Deg. (Deg.)	Ant. High (m)
9435.000	---	---	---	---	7.2	---	---	74.0	54.0	---	---
10689.000	---	---	---	---	8.2	---	---	74.0	54.0	---	---
11563.000	---	---	---	---	9.1	---	---	74.0	54.0	---	---
12567.000	---	---	---	---	9.5	---	---	74.0	54.0	---	---
13389.000	---	---	---	---	10.8	---	---	74.0	54.0	---	---
14490.000	---	---	---	---	11.6	---	---	74.0	54.0	---	---
15799.000	---	---	---	---	8.3	---	---	74.0	54.0	---	---
16038.000	---	---	---	---	8.3	---	---	74.0	54.0	---	---
17895.000	---	---	---	---	8.4	---	---	74.0	54.0	---	---
20356.000	---	---	---	---	8.6	---	---	74.0	54.0	---	---
21356.000	---	---	---	---	9.7	---	---	74.0	54.0	---	---
22783.000	---	---	---	---	10.5	---	---	74.0	54.0	---	---
23856.000	---	---	---	---	10.4	---	---	74.0	54.0	---	---
31586.000	---	---	---	---	13.5	---	---	74.0	54.0	---	---
31791.000	---	---	---	---	13.7	---	---	74.0	54.0	---	---
36856.000	---	---	---	---	13.8	---	---	74.0	54.0	---	---

Note :

1. *Item of margin shown in above table refer to average limit.*
2. *It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark "***" means that Peak result is meet average limit.*
3. *Remark "---" means that the emissions level is too low to be measured.*
4. *Item "Margin" referred to Average limit while there is only peak result.*
5. *The expanded uncertainty of the radiated emission tests is 3.53 dB.*

4.4.3 Other Emission

A. 802.11b

a) Emission frequencies below 1 GHz

Test Date : Aug. 24, 2003 Temperature : 23 ℃ Humidity : 61 %

Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result @3m (dBuV/m)	Limit @3m (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (m)
132.870	H	45.1	-11.3	33.8	43.5	-9.7	305	1.5
160.720	H/V	45.1	-9.5	35.6	43.5	-7.9	128	1.6
166.410	H/V	46.4	-9.2	37.2	43.5	-6.3	114	1.3
200.890	H/V	44.6	-7.0	37.6	43.5	-5.9	31	1.5
561.100	H	42.8	-5.2	37.6	46.0	-8.4	255	1.5
699.000	H	30.0	-1.0	29.0	46.0	-17.0	316	1.7

Note :

1. Remark "---" means that the emissions level is too low to be measured.

2. The expanded uncertainty of the radiated emission tests is 3.53 dB.

b) Emission frequencies above 1 GHz

Radiated emission frequencies above 1 GHz to 25 GHz were too low to be measured with a pre-amplifier of 35 dB.

B. 802.11g

a) Emission frequencies below 1 GHz

Test Date : Sep. 04, 2003 Temperature : 23 ℃ Humidity : 61 %

Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result @3m (dBuV/m)	Limit @3m (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (m)
40.260	H	37.7	-11.9	25.8	40.0	-14.2	305	1.5
59.700	H	42.5	-16.1	26.4	40.0	-13.6	128	1.6
81.300	H	47.7	-14.9	32.8	40.0	-7.2	114	1.3
133.680	V	49.8	-11.2	38.6	43.5	-4.9	31	1.5
160.680	V	48.9	-9.5	39.4	43.5	-4.1	255	1.5
258.960	V	38.3	-3.9	34.4	46.0	-11.6	114	1.3
430.900	V	43.1	-5.5	37.6	46.0	-8.4	31	1.5

Note :

1. Remark "---" means that the emissions level is too low to be measured.

2. The expanded uncertainty of the radiated emission tests is 3.53 dB.

b) Emission frequencies above 1 GHz

Radiated emission frequencies above 1 GHz to 25 GHz were too low to be measured with a pre-amplifier of 35 dB.

4.5 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor, High Pass Filter Loss(if used) and Cable Loss, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation calculation is as follows:

Result = Reading + Corrected Factor

where

Corrected Factor = Antenna FACTOR + Cable Loss + High Pass Filter Loss - Amplifier Gain

4.6 Photos of Radiation Measuring Setup

Please See Exhibit_F Test Setup Photos

5 CONDUCTED EMISSION MEASUREMENT

5.1 Standard Applicable

For unintentional and intentional device, Line Conducted Emission Limits are in accordance to § 15.107(a) and § 15.207(a) respectively. Both Limits are identical specification.

5.2 Measurement Procedure

1. Setup the configuration per figure 3.
2. A preliminary scan with a spectrum monitor is performed to identify the frequency of emission that has the highest amplitude relative to the limit by operating the EUT in selected modes of operation, typical cable positions, and with a typical system configuration.
3. Record the 6 or 8 highest emissions relative to the limit.
4. Measure each frequency obtained from step 3 by a test receiver set on quasi peak detector function, and then record the accuracy frequency and emission level. If all emissions measured in the specified band are attenuated more than 20 dB from the limit, this step would be ignored, and the peak detector function would be used.
5. Confirm the highest three emissions with variation of the EUT cable configuration and record the final data.
6. Repeat all above procedures on measuring each operation mode of EUT.

Figure 3 : Conducted emissions measurement configuration



5.3 Conducted Emission Data

A. 801.11b

a) Channel 1

Operation Mode : Transmitting / Receiving
Test Date : Aug. 26, 2003 Temperature : 23 ℃ Humidity: 58 %

Freq.	Meter Reading (dBì V)				Factor	Limit (dBì V)		Result (dBì V)			
	Q.P Value		AVG. Value			Q.P	AVG.	Q.P Value		AVG. Value	
(MHz)	N	L1	N	L1	(dB)	Value	Value	N	L1	N	L1
0.201	22.5	22.5	----	----	0.2	63.6	53.6	22.7	22.7	----	----
0.275	23.4	23.4	----	----	0.2	61.0	51.0	23.6	23.6	----	----
0.333	19.5	19.5	----	----	0.3	59.4	49.4	19.8	19.8	----	----
0.400	26.8	26.8	----	----	0.3	57.9	47.9	27.1	27.1	----	----
0.466	22.5	22.5	----	----	0.3	56.6	46.6	22.8	22.8	----	----
0.930	18.1	18.1	----	----	0.3	56.0	46.0	18.4	18.4	----	----

b) Channel 6

Operation Mode : Transmitting / Receiving
Test Date : Aug. 26, 2003 Temperature : 23 ℃ Humidity: 58 %

Freq.	Meter Reading (dBì V)				Factor	Limit (dBì V)		Result (dBì V)			
	Q.P Value		AVG. Value			Q.P	AVG.	Q.P Value		AVG. Value	
(MHz)	N	L1	N	L1	(dB)	Value	Value	N	L1	N	L1
0.193	32.3	42.0	----	----	0.2	63.9	53.9	32.5	42.2	----	----
0.205	28.2	42.7	----	----	0.2	63.4	53.4	28.4	42.9	----	----
0.267	28.4	40.7	----	----	0.2	61.2	51.2	28.6	40.9	----	----
1.461	12.6	29.2	----	----	0.4	56.0	46.0	13.0	29.6	----	----
1.727	15.5	29.0	----	----	0.4	56.0	46.0	15.9	29.4	----	----
1.926	10.2	28.6	----	----	0.5	56.0	46.0	10.7	29.1	----	----
2.059	15.1	28.7	----	----	0.5	56.0	46.0	15.6	29.2	----	----

c) Channel 11

Operation Mode : Transmitting / Receiving
Test Date : Aug. 24, 2003 Temperature : 23 ℃ Humidity: 58 %

Freq.	Meter Reading (dBì V)				Factor	Limit (dBì V)		Result (dBì V)			
	Q.P Value		AVG. Value			Q.P	AVG.	Q.P Value		AVG. Value	
(MHz)	N	L1	N	L1	(dB)	Value	Value	N	L1	N	L1
0.197	44.9	44.6	----	----	0.2	63.7	53.7	45.1	44.8	----	----
0.271	33.3	35.4	----	----	0.2	61.1	51.1	33.5	35.6	----	----
0.400	33.9	35.1	----	----	0.3	57.9	47.9	34.2	35.4	----	----
0.730	27.6	31.8	----	----	0.3	56.0	46.0	27.9	32.1	----	----
2.391	13.6	27.0	----	----	0.5	56.0	46.0	14.1	27.5	----	----
2.855	23.4	29.7	----	----	0.5	56.0	46.0	23.9	30.2	----	----

Note : 1. Please see appendix 1 for Plotted Data

2. The expanded uncertainty of the conducted emission tests is 2.45 dB.

B. 801.11g

a) Channel 1

Operation Mode : Transmitting / Receiving
Test Date : Aug. 26, 2003 Temperature : 23 ℃ Humidity: 58 %

Freq.	Meter Reading (dBì V)				Factor	Limit (dBì V)		Result (dBì V)			
	Q.P Value		AVG. Value			Q.P	AVG.	Q.P Value		AVG. Value	
(MHz)	N	L1	N	L1	(dB)	Value	Value	N	L1	N	L1
0.193	37.6	39.4	----	----	0.2	63.9	53.9	37.8	39.6	----	----
0.263	34.8	36.1	----	----	0.2	61.3	51.3	35.0	36.3	----	----
0.463	25.0	32.5	----	----	0.3	56.6	46.6	25.3	32.8	----	----
1.059	25.5	34.1	----	----	0.3	56.0	46.0	25.8	34.4	----	----
1.719	26.7	35.2	----	----	0.4	56.0	46.0	27.1	35.6	----	----
2.382	26.8	35.0	----	----	0.5	56.0	46.0	27.3	35.5	----	----

b) Channel 6

Operation Mode : Transmitting / Receiving
Test Date : Aug. 26, 2003 Temperature : 23 ℃ Humidity: 58 %

Freq.	Meter Reading (dBì V)				Factor	Limit (dBì V)		Result (dBì V)			
	Q.P Value		AVG. Value			Q.P	AVG.	Q.P Value		AVG. Value	
(MHz)	N	L1	N	L1	(dB)	Value	Value	N	L1	N	L1
0.193	39.8	39.9	----	----	0.2	63.9	53.9	40.0	40.1	----	----
0.267	35.3	35.0	----	----	0.2	61.2	51.2	35.5	35.2	----	----
0.664	25.2	29.7	----	----	0.3	56.0	46.0	25.5	30.0	----	----
1.191	26.8	34.3	----	----	0.3	56.0	46.0	27.1	34.6	----	----
2.117	27.7	35.3	----	----	0.5	56.0	46.0	28.2	35.8	----	----
12.578	31.0	30.9	----	----	1.0	60.0	50.0	32.0	31.9	----	----

c) Channel 11

Operation Mode : Transmitting / Receiving
Test Date : Aug. 24, 2003 Temperature : 23 ℃ Humidity: 58 %

Freq.	Meter Reading (dBì V)				Factor	Limit (dBì V)		Result (dBì V)			
	Q.P Value		AVG. Value			Q.P	AVG.	Q.P Value		AVG. Value	
(MHz)	N	L1	N	L1	(dB)	Value	Value	N	L1	N	L1
0.177	30.9	29.6	----	----	0.2	64.6	54.6	31.1	29.8	----	----
0.205	42.3	40.6	----	----	0.2	63.4	53.4	42.5	40.8	----	----
0.267	39.9	38.4	----	----	0.2	61.2	51.2	40.1	38.6	----	----
0.338	27.8	26.4	----	----	0.3	59.3	49.3	28.1	26.7	----	----
0.797	25.7	30.7	----	----	0.3	56.0	46.0	26.0	31.0	----	----
12.000	28.8	29.6	----	----	0.9	60.0	50.0	29.7	30.5	----	----

Note : 1. Please see appendix 1 for Plotted Data
2. The expanded uncertainty of the conducted emission tests is 2.45 dB.

5.4 Result Data Calculation

The result data is calculated by adding the LISN Factor to the measured reading. The basic equation with a sample calculation is as follows:

RESULT = READING + LISN FACTOR

Assume a receiver reading of 22.5 dB μ V is obtained, and LISN Factor is 0.1 dB, then the total of disturbance voltage is 22.6 dB μ V.

RESULT = 22.5 + 0.1 = 22.6 dB μ V
Level in μ V = Common Antilogarithm[(22.6 dB μ V)/20]
= 13.48 μ V

5.5 Conducted Measurement Equipment

The following test equipment are used during the conducted test .

Equipment	Manufacturer	Model No.	Next Cal. Due
EMI Test Receiver	Rohde and Schwarz	ESCS 30	11/27/2003
Line Impedance Stabilization network	Rohde and Schwarz	ESH2-Z5	09/02/2004
Monitor	IBM	E54	N.C.R.
Printer	HP	LaserJet 1000	N.C.R.
Shielded Room	Riken		N.C.R.
Computer	Acer	Veriton	N.C.R.
EMI Test Receiver	Rohde and Schwarz	ESCS 30	11/27/2003

5.6 Photos of Conduction Measuring Setup

Please See Exhibit_F Test Setup Photos

6 ANTENNA REQUIREMENT

6.1 Standard Applicable

For intentional device, according to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.
And according to § 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

6.2 Antenna Construction and Directional Gain

The antenna is designed to be permanently mounted on PCB. No consideration of replacement. Please see constraction Photos Of Exhibit B for details.

7 EMISSION BANDWIDTH MEASUREMENT

7.1 Standard Applicable

According to 15.247(a)(2), for direct sequence system, the minimum 6dB bandwidth shall be at least 500 kHz.

7.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 4 without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Figure 4: Emission bandwidth measurement configuration.



7.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Next Cal. Due
RF Test Receiver	Rohde & Schwarz	ESBI	05/25/2004
Plotter	Hewlett-Packard	7440A	N/A
Attenuator	Weinschel Engineering	AS3667	N/A

7.4 Measurement Data

Test Date : Aug. 26, 2003 Temperature : 25 ℃ Humidity: 60 %

A. 802.11b

a) Channel 01 : 6 dB Emission Bandwidth is 13.25 MHz
b) Channel 06 : 6 dB Emission Bandwidth is 13.67 MHz
c) Channel 11 : 6 dB Emission Bandwidth is 12.75 MHz

B. 802.11g

a) Channel 01 : 6 dB Emission Bandwidth is 16.33 MHz
b) Channel 06 : 6 dB Emission Bandwidth is 16.75 MHz
c) Channel 11 : 6 dB Emission Bandwidth is 16.67 MHz

Note : 1. Please see appendix 2 for Plotted Data
2. The expanded uncertainty of the emission bandwidth tests is 1500Hz.

8 OUTPUT POWER MEASUREMENT

8.1 Standard Applicable

For direct sequence system, according to 15.247(b), the maximum peak output power of the transmitter shall not exceed 1 Watt. If transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

8.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 5 without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 1 MHz and VBW to 3 MHz.
4. Use channel power function and record the level displayed.
5. Repeat above procedures until all frequencies measured were complete.

Figure 5: Output power and measurement configuration.



8.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Next Cal. Due
RF Test Receiver	Rohde & Schwarz	ESBI	05/25/2004
Plotter	Hewlett-Packard	7440A	N/A
Attenuator	Weinschel Engineering	AS3667	N/A

8.4 Measurement Data

Test Date : Aug. 16, 2003 Temperature : 25 ℃ Humidity: 60 %

A. 802.11b

a) Channel 01 : Output Peak Power is 15.7 dBm or **37.153** mW
b) Channel 06 : Output Peak Power is 15.3 dBm or **33.884** mW
c) Channel 11 : Output Peak Power is 14.0 dBm or **25.119** mW

B. 802.11g

a) Channel 01 : Output Peak Power is 11.4 dBm or **13.80** mW
b) Channel 06 : Output Peak Power is 11.0 dBm or **12.59** mW
c) Channel 11 : Output Peak Power is 9.9 dBm or **9.77** mW

Note : 1. Please see appendix 3 for Plotted Data
2. The expanded uncertainty of the output power tests is 2dB.

9 100 kHz BANDWIDTH OF BAND EDGES MEASUREMENT

9.1 Standard Applicable

According to 15.247(c), if any 100 kHz bandwidth outside these frequency bands, the radio frequency power that is produced by the modulation products of the spreading sequence, the information sequence and the carrier frequency shall be either at least 20 dB below that in any 100 kHz bandwidth within the band that contains the highest level of the desired power or shall not exceed the general levels specified in § 15.209(a), whichever results in the lesser attenuation.

9.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 5 without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Set both RBW of spectrum analyzer to 100kHz and VBW to 1 MHz with a convenient frequency span including 100kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

9.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Next Cal. Due
RF Test Receiver	Rohde & Schwarz	ESBI	05/25/2004
Attenuator	Weinschel Engineering	1	N/A
Plotter	Hewlett-Packard	7440A	N/A

9.4 Measurement Data

Test Date : Aug. 26, 2003 Temperature : 25 ℃ Humidity: 60 %

A. 802.11b

a) Lower Band Edge : maximum value is –37.33 dBm that is attenuated more than 20 dB
b) Upper Band Edge : maximum value is –50.00 dBm that is attenuated more than 20 dB

B. 802.11g

a) Lower Band Edge : maximum value is –37.50 dBm that is attenuated more than 20 dB
b) Upper Band Edge : maximum value is –50.17 dBm that is attenuated more than 20 dB

Note : 1. Please see appendix 4 for Plotted Data
2. The expanded uncertainty of the 100 khz bandwidth of band edges tests is 2dB.

10 POWER DENSITY MEASUREMENT

10.1 Standard Applicable

According to 15.247(d), for direct sequence systems, the transmitted power density averaged over any 1 second interval shall not be greater than 8 dBm in any 3 kHz bandwidth within these bands.

10.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 4 without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set EUT to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Adjust the center frequency of spectrum analyzer on highest level appearing on spectral display within a 300 kHz frequency span.
4. Set the spectrum analyzer on a 3 kHz resolution bandwidth and 300 kHz video bandwidth as well as max hold function.
5. Repeat above procedures until all measured frequencies were complete.

10.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Next Cal. Due
RF Test Receiver	Rohde & Schwarz	ESBI	05/25/2004
Attenuator	Weinschel Engineering	1	N/A
Plotter	Hewlett-Packard	7440A	N/A

10.4 Measurement Data

Test Date : Aug. 26, 2003 Temperature : 25 ℃ Humidity: 60 %

A. 802.11b

a) Channel 01 : Maximun Power Density of 3 kHz Bandwidth is –8.33 dBm
b) Channel 06 : Maximun Power Density of 3 kHz Bandwidth is –9.83 dBm
c) Channel 11 : Maximun Power Density of 3 kHz Bandwidth is –11.50 dBm

B. 802.11g

a) Channel 01 : Maximun Power Density of 3 kHz Bandwidth is –14.83 dBm
b) Channel 06 : Maximun Power Density of 3 kHz Bandwidth is –13.33 dBm
c) Channel 11 : Maximun Power Density of 3 kHz Bandwidth is –16.00 dBm

Note : 1. Please see appendix 5 for Plotted Data
2. The expanded uncertainty of the power density tests is 2dB.

11. OUT-OF-BAND CONDUCTED EMISSION MEASUREMENT

11.1 Standard Applicable

According to 15.247(c), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required.

11.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 4 without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Use the following spectrum analyzer settings:

   Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

   RBW = 100 kHz

   VBW ≥ RBW

   Sweep = auto

   Detector function = peak

   Trace = max hold.
4. Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded. Plot the result on the screen of spectrum analyzer.
5. Repeat above procedures until all measured frequencies were complete.

11.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Next Cal. Due
Spectrum Analyzer	Hewlett-Packard	8564E	04/13/2004
Attenuator	Weinschel Engineering	1	N/A
Plotter	Hewlett-Packard	7440A	N/A

11.4 Measurement Data

A. 802.11b

Model : Low power

Test Date : Aug. 26, 2003 Temperature : 25 ℃ Humidity: 60 %

a) 1 GHz to 5 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.
b) 5 GHz to 25 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.

Model : Mid power

Test Date : Aug. 26, 2003 Temperature : 25 ℃ Humidity: 60 %

a) 1 GHz to 5 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.
b) 5 GHz to 25 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.

Model : Hi power

Test Date : Aug. 26, 2003 Temperature : 25 ℃ Humidity: 60 %

c) 1 GHz to 5 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.
d) 5 GHz to 25 GHz frequency band: All emissions are attenuated more than 20dB from the carrier

B. 802.11g

Model : Low power

Test Date : Aug. 26, 2003 Temperature : 25 ℃ Humidity: 60 %

c) 1 GHz to 5 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.
d) 5 GHz to 25 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.

Model : Mid power

Test Date : Aug. 26, 2003 Temperature : 25 ℃ Humidity: 60 %

e) 1 GHz to 5 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.
f) 5 GHz to 25 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.

Model : Hi power

Test Date : Aug. 26, 2003 Temperature : 25 ℃ Humidity: 60 %

g) 1 GHz to 5 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.
h) 5 GHz to 25 GHz frequency band: All emissions are attenuated more than 20dB from the carrier

Note : 1. Please see appendix 6 for Plotted Data

2. The expanded uncertainty of the out-of-band conducted emission tests is 2dB.

Appendix 1 : Ploted Datas of Power Line Conducted Emissions

CONDUCTION EMISSION TEST

Peak Value

EUT:	WIRELESS NETOWORK CORD
Manuf:	
Op Cond:	
Operator:	CH LO
Test Spec:	
Comment:	
	N

Final Measurement:	Detector:	X QP
	Meas Time:	1sec
	Peaks:	8
	Acc Margin:	25 dB



CONDUCTION EMISSION TEST

Peak Value

EUT:	WIRELESS NETOWORK CORD
Manuf:	
Op Cond:	
Operator:	CH LO
Test Spec:	
Comment:	

L1

Final Measurement:	Detector:	X QP
	Meas Time:	1sec
	Peaks:	8
	Acc Margin:	25 dB



CONDUCTION EMISSION TEST

Peak Value

EUT: WIRELESS NETWORK CARD
Manuf:
Op Cond:
Operator:
Test Spec:
Comment:
N

Final Measurement:

Detector:	X QP
Meas Time:	1sec
Peaks:	8
Acc Margin:	25 dB



CONDUCTION EMISSION TEST

Peak Value

EUT: WIRELESS NETWORK CARD
Manuf:
Op Cond:
Operator:
Test Spec:
Comment:
L1

Final Measurement:

Detector:	X QP
Meas Time:	1sec
Peaks:	8
Acc Margin:	25 dB



CONDUCTION EMISSION TEST

Peak Value

EUT:	WIRELESS NETOWORK CORD
Manuf:	
Op Cond:	
Operator:	CH HI
Test Spec:	
Comment:	
	N

Final Measurement:	Detector:	X QP
	Meas Time:	1sec
	Peaks:	8
	Acc Margin:	25 dB



CONDUCTION EMISSION TEST

Peak Value

EUT:	WIRELESS NETOWORK CORD
Manuf:	
Op Cond:	
Operator:	CH HI
Test Spec:	
Comment:	
	L1

Prescan Measurement:	Detector:	X PK
	Meas Time:	see scan settings
	Peaks:	8
	Acc Margin:	25 dB



CONDUCTION EMISSION TEST

Peak Value

EUT:	WG-2400
Manuf:	
Op Cond:	CH LO
Operator:	
Test Spec:	
Comment:	
	N

Final Measurement:	Detector:	X QP
	Meas Time:	1sec
	Peaks:	8
	Acc Margin:	25 dB



CONDUCTION EMISSION TEST

Peak Value

EUT: WG-2400
Manuf:
Op Cond: CH LO
Operator:
Test Spec:
Comment:
L1

Final Measurement:

Detector:	X QP
Meas Time:	1sec
Peaks:	8
Acc Margin:	25 dB



CONDUCTION EMISSION TEST

Peak Value

EUT:	WG-2400
Manuf:	
Op Cond:	CH MID
Operator:	
Test Spec:	
Comment:	
	N

Final Measurement:	Detector:	X QP
	Meas Time:	1sec
	Peaks:	8
	Acc Margin:	25 dB



CONDUCTION EMISSION TEST

Peak Value

EUT:	WG-2400
Manuf:	
Op Cond:	CH MID
Operator:	
Test Spec:	
Comment:	
	L1

Final Measurement:	Detector:	X QP
	Meas Time:	1sec
	Peaks:	8
	Acc Margin:	25 dB



CONDUCTION EMISSION TEST

Peak Value

EUT:	WG-2400
Manuf:	
Op Cond:	CH HI
Operator:	
Test Spec:	
Comment:	
	N

Final Measurement:	Detector:	X QP
	Meas Time:	1sec
	Peaks:	8
	Acc Margin:	25 dB



CONDUCTION EMISSION TEST

Peak Value

EUT:	WG-2400
Manuf:	
Op Cond:	CH HI
Operator:	
Test Spec:	
Comment:	
	L1

Final Measurement:	Detector:	X QP
	Meas Time:	1sec
	Peaks:	8
	Acc Margin:	25 dB



Appendix 2 : Ploted Datas of Emissions Bandwidth


ATTEN 30dB
RL 20.0dBm
10dB/
ΔMKR -.50dB
13.25MHz
ΔMKR
13.25 MHz
-.50 dB
CENTER 2.412000GHz
*RBW 100KHz
*VBW 1.0MHz
SPAN 50.00MHz
SWP 50.0ms


ATTEN 30dB
RL 21.0dBm
10dB/
ΔMKR .16dB
13.67MHz
ΔMKR
13.67 MHz
.16 dB
D
R
CENTER 2.437000GHz
*RBW 100kHz
*VBW 1.0MHz
SPAN 50.00MHz
SWP 50.0ms


ATTEN 30dB
RL 21.0dBm
10dB/
ΔMKR -.34dB
12.75MHz
ΔMKR
12.75 MHz
-.34 dB
D
R
CENTER 2.46200GHz
*RBW 100kHz
*VBW 1.0MHz
SPAN 50.00MHz
SWP 50.0ms

*ATTEN 30dB
RL 22.0dBm
10dB/
ΔMKR -1.00dB
16.33MHz
ΔMKR
16.33 MHz
-1.00 dB
D
R
CENTER 2.41200GHz
*RBW 100kHz
*VBW 1.0MHz
SPAN 50.00MHz
*SWP 500ms


ATTEN 30dB
RL 22.0dBm
10dB/
ΔMKR .50dB
16.75MHz
ΔMKR
16.75 MHz
.50 dB
D
R
CENTER 2.43700GHz
*RBW 100kHz
*VBW 1.0MHz
SPAN 50.00MHz
*SWP 500ms


*ATTEN 30dB
RL 20.0dBm
10dB/
ΔMKR -3.17dB
16.67MHz
ΔMKR
16.67 MHz
-3.17 dB
CENTER 2.46200GHz
SPAN 50.00MHz
*RBW 100kHz
*VBW 1.0MHz
*SWP 500ms

Appendix 3 : Ploted Datas of Output Peak Power


ATTEN 30dB
RL 22.0dBm
10dB/
CHANNEL POWER
ACROSS 22.0MHz BW
TOTAL 15.7dBm
DENSITY -57.7dBm/Hz
R
CENTER 2.41200GHz
*RBW 1.0MHz
VBW 1.0MHz
SPAN 50.00MHz
SWP 50.0ms


ATTEN 30dB
RL 22.0dBm
10dB/
CHANNEL POWER
ACROSS 22.0MHz
TOTAL 15.3dBm
DENSITY -56.2dBm/HZ
CENTER 2.437000GHZ
*RBW 1.0MHZ
VBW 1.0MHZ
SPAN 50.00MHZ
SWP 50.0ms


ATTEN 30dB
RL 22.0dBm
10dB/
CHANNEL POWER
ACROSS 22.0MHz
TOTAL 14.0dBm
DENSITY -159.4dBm/Hz
CENTER 2.46200GHz
*RBW 1.0MHz
VBW 1.0MHz
SPAN 50.00MHz
SWP 50.0ms


*ATTEN 30dB
RL 20.0dBm
10dB/
CHANNEL POWER
ACROSS 22.0MHz BW
TOTAL 11.4dBm
DENSITY -62.0dBm/Hz
CENTER 2.4120GHz
*RBW 1.0MHz
VBW 1.0MHz
SPAN 50.00MHz
*SWP 500ms


*ATTEN 30dB
RL 20.0dBm
10dB/
CHANNEL POWER
ACROSS 22.0MHZ BW
TOTAL 11.0dBm
DENSITY -62.4dBm/HZ
CENTER 2.43700GHZ
*RBW 1.0MHZ
VBW 1.0MHZ
SPAN 50.00MHZ
*SWP 500ms


*ATTEN 30dB
RL 20.0dBm
10dB/
CHANNEL POWER
ACROSS 22.0MHz BW
TOTAL 9.9dBm
DENSITY -63.5dBm/Hz
CENTER 2.4620GHz
*RBW 1.0MHz
VBW 1.0MHz
SPAN 50.00MHz
*SWP 500ms

Appendix 4 : Ploted Datas of Band Edge Emission


ATTEN 30dB
RL 20.0dBm
10dB/
MKR -37.33dBm
2.39720GHz
MKR
2.39720 GHz
-37.33 dBm
START 2.38000GHz
*RBW 100kHz
*VBW 1.0MHz
STOP 2.42000GHz
SWP 50.0ms


ATTEN 30dB
RL 20.0dBm
10dB/
MKR -50.00dBm
2.483994GHz
MKR 2.4839 GHz
-50.00dBm
START 2.4580GHz
*RBW 100KHz
*VBW 1.0MHz
STOP 2.5200GHz
SWP 50.0ms


*ATTEN 30dB
RL 20.0dBm
10dB/
MKR -37.50dBm
2.40100GHz
MKR
2.40100 GHz
-37.50 dBm
START 2.38000GHz
*RBW 100KHz
*VBW 1.0MHz
STOP 2.42000GHz
SWP 50.0ms


*ATTEN 30dB
RL 20.0dBm
10dB/
MKR -50.17dBm
2.48348GHz
MKR
2.48348GHz
-50.17 dBm
D
START 2.45000GHz
*RBW 100KHz
*VBW 1.0MHz
STOP 2.52000GHz
SWP 50.0ms

Appendix 5 : Ploted Datas of Power Density


ATTEN 30dB
RL 21.0dBm
10dB/
MKR -8.33dBm
2.4090237GHz
MKR
2.4090237 GHz
CENTER 2.4090267GHz
*RBW 3.0KHz
*VBW 100KHz
SPAN 300.0KHz
*SWP 100sec


ATTEN 30dB
RL 21.0dBm
10dB/
MKR -9.83dBm
2.435011 2GHz
MKR
2.435011 2 GHz
-9.83 dBm
A
CENTER 2.435011 7GHz
*RBW 3.0KHz
*VBW 100KHz
SPAN 300.0KHz
*SWP 100sec


ATTEN 30dB
RL 21.0dBm
10dB/
MKR -11.50dBm
2.464536GHz
MKR
2.464536 GHz
-11.50 dBm
CENTER 2.464583GHz
*RBW 3.0KHz
*VBW 100KHz
SPAN 300.0KHz
*SWP 100sec


*ATTEN 30dB
RL 20.0dBm
10dB/
MKR -14.83dBm
2.417365GHz
CENTER 2.417345GHz
*RBW 3.0kHz
*VBW 100kHz
SPAN 300.0kHz
*SWP 100sec


ATTEN 30dB
RL 22.0dBm
10dB/
MKR -13.33dBm
2.4423493GHz
MKR
2.4423493 GHz
-13.33 dBm
CENTER 2.4423483GHz
*RBW 3.0kHz
*VBW 100kHz
SPAN 300.0kHz
*SWP 100sec


*ATTEN 30dB
RL 22.0dBm
10dB/
MKR -16.00dBm
2.463305 3GHz
MKR
2.463305 3 GHz
-16.00 dBm
A
CENTER 2.463293 3GHz
*RBW 3.0kHz
*VBW 100kHz
SPAN 300.0kHz
*SWP 100sec

Appendix 6 : Plotted Data for Out-of-Band Conducted Emission


ATTEN 30dB
RL 21.0dBm
10dB/
MKR 2.17dBm
2.407GHz
MKR
2.407 GHz
2.17 dBm
START 1.000GHz
*RBW 100KHz
*VBW 1.0MHz
STOP 5.000GHz
SWP 2.20sec


ATTEN 30dB
RL 24.00dBm
10dB/
MKR 23.976GHz
-146.00dBm
MKR
23.97 GHz
-146.00 dBm
START 5.000GHz
*RBW 100KHz
*VBW 1.0MHz
STOP 25.000GHz
SWP 11.0sec


ATTEN 30dB
RL 21.0dBm
10dB/
MKR 1.67dBm
2.433GHz
MKR
2.433 GHz
1.67 dBm
R
START 1.000GHz
*RBW 100KHz
*VBW 1.0MHz
STOP 5.000GHz
SWP 2.20sec


ATTEN 30dB
RL 21.0dBm
10dB/
MKR 24.00 GHz
-145.83 dBm
MKR -45.83dBm
24.00GHz
START 5.00GHz
*RBW 100KHz
*VBW 1.0MHz
STOP 25.00GHz
SWP 11.0sec


ATTEN 30dB
RL 21.0dBm
10dB/
MKR .17dBm
2.460GHz
MKR
2.460 GHz
.17 dBm
D
R
START 1.000GHz
*RBW 100KHz
*VBW 1.0MHz
STOP 5.000GHz
SWP 2.20sec


ATTEN 30dB
RL 21.0dBm
10dB/
MKR -44.00dBm
24.07GHz
MKR
24.07 GHz
-44.00 dBm
START 5.00GHz
*RBW 100KHz
*VBW 1.0MHz
STOP 25.00GHz
SWP 11.0sec


*ATTEN 30dB
RL 22.0dBm
10dB/
MKR -3.83dBm
2.413GHz
MEAS UNCAL
MKR
2.413 GHz
-3.83 dBm
D
R
START 1.000GHz
*RBW 100KHz
*VBW 1.0MHz
STOP 5.000GHz
*SWP 500ms


*ATTEN 30dB
RL 22.0dBm
10dB/
MKR -43.33dBm
24.00GHz
MKR
24.00 GHz
-43.33 dBm
START 5.00GHz
*RBW 100KHz
*VBW 1.0MHz
STOP 25.00GHz
SWP 11.0sec


*ATTEN 30dB
RL 22.0dBm
10dB/
MKR -5.50dBm
2.440GHz
MKR
2.440 GHz
-5.50 dBm
A
START 1.000GHz
*RBW 100KHz
*VBW 1.0MHz
STOP 5.000GHz
SWP 2.20sec


*ATTEN 30dB
RL 22.0dBm
10dB/
MKR -44.17dBm
23.97GHz
MKR
23.97 GHz
-44.17 dBm
A
START 5.00GHz
*RBW 100KHz
*VBW 1.0MHz
STOP 25.00GHz
SWP 11.0sec


*ATTEN 30dB
RL 22.0dBm
10dB/
MKR -6.17dBm
2.467GHz
MKR
2.467 GHz
-6.17 dBm
D
R
START 1.000GHz
*RBW 100KHz
*VBW 1.0MHz
STOP 5.000GHz
SWP 2.20sec


*ATTEN 30dB
RL 20.0dBm
10dB/
MKR -46.33dBm
24.70GHz
MKR
24.70 GHz
-46.33 dBm
START 5.00GHz
*RBW 100KHz
*VBW 1.0MHz
STOP 25.00GHz
SWP 11.0sec