P/N	189588000

NOTES

1.) SURFACE MATERIAL: PET 0.05mmTHK.(+/-10%) WITH BACK ACRYLIC ADHESIVE.
2.) PRINT: PERMANENT BLACK OPAQUE INK.
3.) FINISH: SURFACE WITH PET COATING.
4.) TOTAL THICKNESS TO BE 0.13±0.02mm.
5.) LINER SPEC: ROLL TYPE, GLASSING PAPER, 82 gw/㎡ (REF.) SURFACE WITH SILICON COATING.
6.) LABEL MARKING TO COMPLY WITH UL'S RECOGNIZED COMPONENT MARKING AND LABELING SYSTEMS. ALL LABEL MATERIAL AND ADHESIVE MUST BE UL COMPLIANT/CERTIFIED.
7.) FINISHED: MEET XAC's RoHs REQUIREMENT
8.) BLANK LABEL USE: P/N 241879000
9.) MODEL & H/N & P/N: TEXT HEIGHT 1.1MM
H/N: For Hardware Number(PCI Requirement)

TABLE 1

ITEM	MODEL	P/N	H/N
1	xCE-25C	002236020	CE25617EBBE6C1

REV LTR	DATE	EC No.	REV. DESCRIPTION	DESIGNER	APPROVED
1					

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE :
X. ` 0.35 ANGLE ± 0.5°
.X ` 0.20 RADIU R0.5
.XX ` 0.10
.XXX` 0.05

MATERIAL : SEE NOTE
FINISH : SEE NOTE

MODEL NO xCE-25

APPROVED	DATE
CHECKED	DATE
DESIGNER	DATE

0 ← mm → 20
DO NOT SCALE DRAWING
THIRD ANGLE PROJECTION
PAPER SIZE: A4

XAC A Partner You Can Trust — XAC Automation Corp.

TITLE
LABEL ASS'Y PRODUCT
XCE25MFI(ROHS)

DWG NO. 189588000C01 VER. C01