



MPE/RF EXPOSURE REPORT

FCC CFR 47 Part 1.1310

Report No.: SATE01-U2A Rev A MPE FCC

Company: SATEL OY

Model Name: SATEL-TR49 SnapOn

MPE/RF EXPOSURE REPORT

Company Name: SATEL OY

Model Name: SATEL-TR49 SnapOn

To: FCC CFR 47 Part 1.1310

Report Serial No.: SATE01-U2A Rev A MPE FCC

This report supersedes: NONE

Applicant: SATEL OY
Meriniitynkatu 17
Salo, 24100
Finland

Issue Date: 23rd September 2021

This Test Report is Issued Under the Authority of:

MiCOM Labs, Inc.
575 Boulder Court
Pleasanton California 94566
USA
Phone: +1 (925) 462-0304
Fax: +1 (925) 462-0306
www.micomlabs.com



MiCOM Labs is an ISO 17025 Accredited Testing Laboratory

1. MAXIMUM PERMISSABLE EXPOSURE

Calculations for Maximum Permissible Exposure Levels

$$\text{Power Density} = P_d (\text{mW/cm}^2) = \text{EIRP} / (4 * \pi * d^2)$$

$$\text{EIRP} = P * G$$

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

$$\text{Numeric Gain} = 10 ^ (G (\text{dBi}) / 10)$$

These calculations represent worst case in terms of the exposure levels: Table 1 of **FCC §1.1310** (E)(i) Limits for Occupational/Controlled Exposure.

Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Power Density (mW/cm ²) @ 20cm	Power Density Limit (mW/cm ²)	Min Calculated safe distance for Limit (cm)	Calculated Power Density (mW/cm ²) @ Safe Distance
410.0 - 470.0	4.0	2.51	29.97	993.12	0.496	1.367	12.05	1.367
410.0 - 470.0	14.0	25.12	29.97	993.12	4.963	1.367	38.11	1.367
902.0 - 928.0	6.0	3.98	29.10	812.83	0.644	3.05	9.19	3.05

Note: for mobile or fixed location transmitters the minimum separation distance is 0.20m, even if calculations indicate the MPE distance to be less.

Based on the calculations above the minimum safe distance for the 14 dBi antenna gain is 39 cm.

Specification

Maximum Permissible Exposure Limits

FCC §1.1310 Limits for power density 300-1,500 MHz = f/300

(where f = frequency in MHz. * = Plane-wave equivalent power density)

410 MHz to 470 MHz: 1.367 mW/cm² and 902 MHz to 930 MHz 3.05 mW/cm²



575 Boulder Court
Pleasanton, California 94566, USA
Tel: +1 (925) 462 0304
Fax: +1 (925) 462 0306
www.micomlabs.com