

FCC 47 CFR MPE REPORT

ASUSTeK Computer Inc

MODULE-WIRELESS CHRG

Model Number: GST868003

FCC ID: MSQ-GST868003

Applicant:	ASUSTeK Computer Inc
Address:	1F, No.15, Lide Rd., Beitou, Taipei Taiwan
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R2603200
Date of Test:	Feb. 09, 2026 to Mar. 12, 2026
Date of Report:	Mar. 18, 2026

Applicant:	ASUSTeK Computer Inc		
Address:	1F, No.15, Lide Rd., Beitou, Taipei Taiwan		
Manufacturer:	ASUSTeK Computer Inc		
Address:	1F, No.15, Lide Rd., Beitou, Taipei Taiwan		
E.U.T:	MODULE-WIRELESS CHRG		
Model Number:	GST868003		
Power Supply:	DC 9V-16V, 2A		
Trade Name:	-----	Sample No.:	EST-260209045-001
Date of Receipt:	Feb. 09, 2026	Date of Test:	Feb. 09, 2026 to Mar. 12, 2026
Test Specification:	FCC CFR 47 Part 1.1307(b)&1.1310 KDB 680106 D01 RF Exposure Wireless Charging Apps v04r01		
Test Result:	The device described above is tested by EST Technology Co., Ltd. The measurement results were contained in this test report and EST Technology Co., Ltd. was assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT to be technically compliance with the FCC CFR 47 Part 1.1307(b)&1.1310 requirements. This report applies to above tested sample only and shall not be reproduced in part without written approval of EST Technology Co., Ltd. Date: Mar. 27, 2026		

Prepared by:

Reviewed by:

Approved by:

Zephyr Zhu

Seven Wang



Zephyr Zhu / Assistant

Seven Wang / Engineer

Iceman Hu / Manager

Other Aspects: None.

Abbreviations: OK/P=passed fail/F=failed n.a/N=not applicable E.U.T=equipment under tested

This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of EST Technology Co., Ltd. The statement of compliance in this report is based on the limit in the test standard, the measurement uncertainty is not considered.

1. Summary of test

1.1. Summary of test result

No.	Description of Test Item	FCC Standard Section	Results
1	Maximum Permissible Exposure	Part 1.1307(b)&1.1310	PASS

1.2. Test Mode

Test Item	Test Mode
Maximum Permissible Exposure	0w, 5w, 7.5w, 10w, 15w
Note: All modes have been tested. The report only reflects the worst case of 15W full load test data.	

1.3. Test Equipment List

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Electric and Magnetic Field Probe-Analyzer	Narda S.T.S./PMM	EHP-200A	EST-E106	June 10,25	June 9,26
Test Software	Narda	EHP200-TS	Rel 1.92	N/A	N/A
Note: Test uncertainty: ± 1.62 dB (H-field); ± 1.64 dB (E-field) at a level of confidence of 95%.					

1.4. Assistant equipment used for test

Item	Equipment	Brand	Model Name/Type No.	FCC ID	Series No.
1	Mobile Phone	-	HUAWEI P60 Pro	-	-

Item	Shielded Type	Ferrite Core	Length	Model Name/Type No.	Note
1	NO	NO	0.2m	-	DC Cable

2. Maximum Permissible Exposure


2.1. Limit

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

Note: f = frequency in MHz * = Plane-wave equivalent power density.

2.2. Test Setup



2.3. Test Procedure

- The test was performed on 360 degree turn table in anechoic chamber.
- The probe was placed at 20 cm surrounding, for test setup.
- The highest emission level was recorded and compared with limit as soon as measurement of each point; A, B, C, D, E were completed.


2.4. Test Result for Test setup :

E-field strength		
Frequency range (KHz)	111~205kHz	
Test Mode	No Load 0W	Full Load 15W
Position A (V/m)	0.297	0.354
Position B (V/m)	0.305	0.673
Position C (V/m)	0.312	1.012
Position D (V/m)	0.289	0.439
Position E (V/m)	0.307	0.463
Limits (V/m)	614	


H-field strength		
Frequency range (KHz)	111~205kHz	
Test Mode	No Load 0W	Full Load 15W
Position A (A/m)	0.036	0.089
Position B (A/m)	0.042	0.113
Position C (A/m)	0.035	0.114
Position D (A/m)	0.035	0.043
Position E (A/m)	0.034	0.070
Limits (A/m)	1.630	

3. Test photo

Position A



Position B




Position C



Position D



Position E



End of Test Report