

THIS DRAWING AND SPECIFICATIONS , HEREIN , ARE THE PROPERTY OF INVENTEC CORPORATION AND SHALL NOT BE REPRODUCED, COPIED, OR USED IN WHOLE OR IN PART AS THE BASIS FOR THE MANUFACTURE OR SALE OF ITEMS WITHOUT WRITTEN PERMISSION, COPYRIGHT © 2026 INVENTEC CORPORATION .

PART NO

6060B3963803

REV

A01

VARIATION

As show

LEGEND

4

3

2

1

出標樣式

46.0 mm

20.0 mm

3.0 mm

40.0 mm

5.0 mm

3.0 mm

Output direction

0.5 RX4

40 mm

20 mm

1.4~1.5 mm

Contains QCNFA765
FCC ID: MSQ-QCNFA765
IC: 3568A-QCNFA765
CCA121Y10040T2
R-C-QTI-QCNFA765
Wi-Fi 6E indoor use only
電波法に準拠
5.2/5.8/6 GHz
帯域内使用に限り
5.2 GHz帯域出力デ
ータ送信シス
テムの基地局又は
随上移動中
継局と通信する場合
など法令
003-230389 により
許可され
D220060003 た場合
を除く
15100-33280000

Black

Pantone 6106C

藍色框線不印出

5.2 mm

3.15 mm

4

3

2

1

4

3

2

1

REVISION HISTORY

DESIGNER	CHANGE NO.	INITIAL	DOC REV	DATE dd/mm/yyyy
			A	

卷芯要有以下資訊(Must be shown inside the reel)

IEC P/N

ASUS P/N

6060BXXXXXXXXXX

XXXXX-XXXXXXXXXX

離型紙後請印刷以下資訊(Must be shown on the liner)

Barcode內容同下方顯示文字
Barcode scanned as the text below.

IEC PN

圖紙版本(VER)

廠商代碼
Vendor code(Name)

6060BXXXXXXXXXX

V0

XXXX

151XX-XXXXXXXXXX

XXXX

ASUS PN

Vendor code(No.)

★注意：ASUS PN和Vendor code用英文半型“-”分開
Separate ASUS PN and Vendor Code with “-” (no space allowed)

NOTE:

(1) THE CIRCLE MARK DIMENSION IS THE KEY DIMENSION FOR REFERENCE.

(2) PART TO BE PACKAGED TO PREVENT DAMAGED IN SHIPPING AND HANDLING.

(3) OTHERS:ACCORDING TO IQC INSPECTION STANDARD OF INVENTEC (IF NOT SPECIFIED).

(4) MATERIAL:

A: 1.面材 Facestock (Code): 正永: (BW0128) 25#白色PET
2.表面處理TopCoat (Code) : 正永: (PPATM(T)(30)(N)) 霧P
3.膠性Adhesives Pattern : 平膠(flat)
or equivalent material.(the material spec as same as Q-Form spec)

B.ADHESIVE:NA

C.THICKNESS: 0.084mm(面材+膠材Facestock+adhesive)

D.RAW MATERIAL COLOR: WHITE

E.NEED UL CERTIFICATION: NA

(5) INK COLOR: 底色 (background color): Black C, 圖文 (graphics): Pantone 6106C灰字

(6) THERMAL TRANSFER RIBBON/ NEED UL CERTIFICATION:N/A

*Agency requirement: UL & cUL Recognized Component Marking and Labeling System (PGDQ2 or PGDQ8) or UL & cUL Recognized Component Printing Materials (PGJ12/PGJ18).

*Agency requirement: CSA Approved Manufacturer of Accepted Adhesive Type Name Plates.
CSA Identifier will be appear on the label (If the label is CSA approved).

(7) HSF PROPERTY: COMPLY iSupplier SYSTEM HSF PROPERTY ATTRIBUTE UP-TO-DATE VALUE.

(8) MUST CHECK WITH INVENTEC TO UPDATE “MANUFACTURE YEAR”
AT LEAST 3 MONTHS BEFORE THE NEXT ANNUAL.(內文有製造年份時需定義年份轉換規則)

Material	tolerance
Label W & H	±0.2mm
Label thickness	±0.02mm

Eraser Model	Usage Times	Weight	Length	Cleaning	Testing Standards
CS-10F rubber	1.2 cycles/sec 300 cycles	500g	5cm		1. Outline of printing is intact and not damaged and the substrate is not visible. 2. The substrate or Undercoating is not visible

Label Criteria						
check	Paste Location	Glue Type	Paste method	Peel off method	Test Criteria	Remark
	Carton	一般膠 General Glue	食指推平 Flatten with index finger	No	1. 不脫落No detachment 2. 不捲起No lift up 3. 氣泡在5*5cm 或以下面積範圍內，不超過兩個<5mm 直徑 Max 2 bubbles (<=5mm) allowed within 5×5 cm area or smaller	檢測結束 需靜置12hr Must rest for 12 hours after Storge testing completion
✓	Cover	as above	as above	No	as above	
		R膠 R Glue	食指推平 Flatten with index finger	90° at any corner	1. 不脫落No detachment 2. 不可殘膠 No glue residue (輕微可用3M推拭布推拭後無殘膠(light residue removable with 3M cloth is acceptable) 3. 氣泡在5*5cm 或以下面積範圍內，不超過兩個<5mm直徑 Max 2 bubbles (<=5mm) allowed within 5×5 cm area or smaller 4. 如呈浮貼狀態可再貼則為接受Lifted edges re-stickable: acceptable 5. 呈捲、曲、翹 狀則不予接受Rolled/warped/lifted: not acceptable	

MODEL

S5408Q

DESIGNER

Olivia Lan

MANAGER

Jane Lee

THIRD AHGLE PROJECTION

DO NOT SCALE DRAWING

LINEAR

mm

INCH

X

X.X

X.XX

CONFIDENTIAL

Inventec CORPORATION

TITLE

RF LB_XB665NF/QCNFA765/T99H294_MSQ
V1.0 COMBO 5G_BLK 40*20MM

DOCUMENT NUMBER

NUMBER

REV

VER

B

PS

6060-B39638-03-AI

A

0

SCALE: 1:1

UNIT:mm

SHEET:1OF1

FILE NAME

S5408Q_I-RF_15100-33280000_6060B3963803