

THIS DRAWING AND SPECIFICATIONS, HEREIN, ARE THE PROPERTY OF INVENTEC CORPORATION AND SHALL NOT BE REPRODUCED, COPIED, OR USED IN WHOLE OR IN PART AS THE BASIS FOR THE MANUFACTURE OR SALE OF ITEMS WITHOUT WRITTEN PERMISSION. COPYRIGHT © 2026 INVENTEC CORPORATION.

LEGEND

PART NO	REV	VARIATION
6060B3963803	A01	As show

NOTE:

- (1) THE CIRCLE MARK DIMENSION IS THE KEY DIMENSION FOR REFERENCE.
- (2) PART TO BE PACKAGED TO PREVENT DAMAGED IN SHIPPING AND HANDLING.
- (3) OTHERS: ACCORDING TO IQC INSPECTION STANDARD OF INVENTEC
(IF NOT SPECIFIED).
- (4) MATERIAL:

A: 1.面材 Facestock (Code): 正永: (BW0128) 25#白色PET
2.表面處理TopCoat (Code) : 正永: (PPATM(T)(30)(N)) 霧P
3.膠性Adhesives Pattern : 平膠(flat)
or equivalent material.(the material spec as same as Q-Form spec)

B.ADHESIVE:NA

C.THICKNESS: 0.084mm(面材+膠材Facestock+adhesive)

D.RAW MATERIAL COLOR: WHITE

E.NEED UL CERTIFICATION: NA

- (5) INK COLOR: 底色 (background color): Black C, 圖文 (graphics): Pantone 6106C灰字
(6) THERMAL TRANSFER RIBBON/ NEED UL CERTIFICATION:N/A

*Agency requirement: UL & cUL Recognized Component Marking and Labeling System (PGDQ2 or PGDQ8) or UL & cUL Recognized Component Printing Materials (PGJ12/PGJ18).

* Agency requirement: CSA Approved Manufacturer of Accepted Adhesive Type Name Plates. CSA Identifier will be appear on the label (If the label is CSA approved).

- (7) HSF PROPERTY: COMPLY iSupplier SYSTEM HSF PROPERTY ATTRIBUTE UP-TO-DATE VALUE.
(8) MUST CHECK WITH INVENTEC TO UPDATE "MANUFACTURE YEAR"
AT LEAST 3 MONTHS BEFORE THE NEXT ANNUAL.(內文有製造年份時需定義年份轉換規則)

	tolerance
Material	Dimension
Label W & H	±0.2mm
Label thickness	±0.02mm

Eraser Model	Usage Times	Weight	Length	Cleaning	Testing Standards
CS-10F rubber	1.2 cycles/sec 300 cycles	500g	5cm		1. Outline of printing is intact and not damaged and the substrate is not visible. 2. The substrate or Undercoating is not visible

Label Criteria						
check	Paste Location	Glue Type	Paste method	Peel off method	Test Criteria	Remark
	Carton	一般膠 General Glue	食指推平 Flatten with index finger	No	1. 不脫落 No detachment 2. 不起翹 No lift up 3. 氣泡在 5*5cm 或以下面積範圍內，不超過兩個 <5mm 直徑 Max 2 bubbles (<=5mm) allowed within 5x5 cm area or smaller	填滯結束 需靜置 12hr Must rest for 12 hours after Storge testing completion
✓	Cover	as above	as above	No	as above	
		R膠 R Glue	食指推平 Flatten with index finger	90° at any corner	1. 不脫落 No detachment 2. 不起殘膠 No glue residue (輕微可用 3M 濕拭布擦拭無殘膠 light residue removable with 3M cloth is acceptable) 3. 氣泡在 5*5cm 或以下面積範圍內，不超過兩個 <5mm 直徑 Max 2 bubbles (<=5mm) allowed within 5x5 cm area or smaller 4. 如呈浮貼狀需可再貼回則為接受 lifted edges re-stickable: acceptable 5. 呈捲、曲、皺 狀則不予接受 rolled/warped/lifted: not acceptable	

MODEL				S5408Q				InventecCORPORATION CONFIDENTIAL					
DESIGNER			D:17	TITLERF LB_XB665NF/QCNFA765/T99H294_MSQ V1.0 COMBO 5G_BLK 40*20MM									
Olivia Lan			M:06										
			Y:26										
MANAGER			D:17	DOCUMENT NUMBER									
Jane Lee			M:06										
			Y:26										
THIRD AHGLE PROJECTION		DO NOT SCALE DRAWING		SIZE		CODE		NUMBER		REV		VER	
B		PS		6060-B39638-03-AI		A		0					
SCALE: 1:1				UNIT:mm				SHEET:1OF1					
FILE NAME								S5408Q_I-RF_15100-33280000_6060B3963803					
LINEAR		X	X.X		X.XX								
mm													
INCH													

出標樣式




 Black
 Pantone 6106C

藍色框線不印出



Output direction

卷芯要有以下資訊(Must be shown inside the reel)



IEC P/N ← 6060BXXXXXXXXX
ASUS P/N ← XXXXX-XXXXXXXXXX

離型紙後請印刷以下資訊(Must be shown on the liner)

IEC PN 圖紙版本(VER) 廠商代碼
Vendor code(Name)

Barcode内容同下方顯示文字
Barcode scanned as
the text below.

IEC PN 圖紙版本(VER) 廠商代碼 Vendor code(Name)

6060BXXXXXX-V0-XXXX
151XX-XXXXXXXX-XXXX

ASUS PN Vendor code(No.)

★注意：ASUS PN和Vendor code用英文半型“-”分開
Separate ASUS PN and Vendor Code with “-” (no space allowed)

REVISION HISTORY

DESIGNER	CHANGE NO.	DOC REV	DATE
-	INITIAL	A	

4

3

2

1