

Label lcoation



1		2		3		4		5		6	
								Remark		Description	
								Editor		Date	
1. 以下内容由供应商印刷		2. 以下内容由工厂由在供应商印刷基础上打印									
38.5⁰_{-0.2} 24.5⁰_{-0.2} ASUS Wi-Fi AC Repeater Input: 100~240V~, 50/60Hz, 0.18A ASUSTek Computer Inc. Model: RP-AC51 FC Factory default setting: http://repeater.asus.com SSID(2.4GHz): ASUS_RPAC51 SSID(5GHz): ASUS_RPAC51_5G 1F, No. 15, Lide Rd., Beitou Dist., Taipei City 112, Taiwan ASUS COMPUTER GMBH HARKORT STR. 21-23, 40880 RATINGEN, GERMANY FCC ID: MSQ-RPAC4200 IC: 3568A-RPAC4200 CAN ICES-3(B)/NMB-3(B) Made in China PANTONE Cool Grey 9 C ASUS Wi-Fi AC Repeater Input: 100~240V~, 50/60Hz, 0.18A ASUSTek Computer Inc. Model: RP-AC51 H/W Ver.: A1 F/W Ver.: Vx.x.x.x MAC XXXXXXXXXXXXX SN YMIA42XXXXXX FC Factory default setting: http://repeater.asus.com SSID(2.4GHz): ASUS_RPAC51 SSID(5GHz): ASUS_RPAC51_5G 1F, No. 15, Lide Rd., Beitou Dist., Taipei City 112, Taiwan ASUS COMPUTER GMBH HARKORT STR. 21-23, 40880 RATINGEN, GERMANY FCC ID: MSQ-RPAC4200 IC: 3568A-RPAC4200 CAN ICES-3(B)/NMB-3(B) Made in China I为字母 编号规则: YMIA42XXXXXX IA42: 固定 Y: 年份 2010 年第一码为 " A " , 依此类推 2011=> B, 2012=> C 2029 => Z. (其中I,O,P,Q,U,V 不用) 再回到数字2030=> 0, ..., 2039=> 9 M: 月份 1~9代表1~9月, A:10月, B:11月, C:12月 XXXXXX: 000001 - 999999 (按生产流水号) MAC 位数及内容由ASUS提供, 由条码房分配 F/W Ver.: Vx.x.x.x为虚指, 见Agile系统软件表中客供软件发布申请单											