

1		2		3		4		5		6	
								Remark		Description	
								Editor		Date	
A										A	
B										B	
C										C	
D										D	
1		2		3		4		5		6	

0
-0.2
30.5 mm

1. 以下内容由供应商印刷：

0
-0.2
69.5 mm

ASUS

Input: DC12V --- 0.5A

Model Name: RT-N300

The device complies with Part 15 of the FCC Rules.
Operation is subject to the following two conditions:
(1) this device may not cause harmful interference, and
(2) this device must accept any interference received,
including interference that may cause undesired operation.
Factory Default Settings:
IP Address: 192.168.1.1
User Name: admin
Password: admin
FCC ID: MSQ-RT1901
IC: 3566A-RTN300
ASUSTek Computer Inc. Made in China

2. 以下内容由工厂在供应商印刷的基础上打印：

ASUS

Input: DC12V --- 0.5A

Model Name: RT-N300

The device complies with Part 15 of the FCC Rules.
Operation is subject to the following two conditions:
(1) this device may not cause harmful interference, and
(2) this device must accept any interference received,
including interference that may cause undesired operation.
Factory Default Settings:
IP Address: 192.168.1.1
User Name: admin
Password: admin
FCC ID: MSQ-RT1901
IC: 3566A-RTN300
ASUSTek Computer Inc. Made in China

F/W Ver.: Vx.x.x.x H/W Ver.: A
PIN Code XXXXXXXXXXXX
MAC XXXXXXXXXXXX

PIN Code

MAC

MAC 位数及内容见生产信息发布流程
PIN Code 位数及内容见生产信息发布流程
F/W Ver.: Vx.x.x.x 为虚指，位数及内容见生产信息发布流程

BARCODE: CODE 128

NOTES (技术要求)：

1. 黑色印刷，无边框, R1.5
(Black printing, no frame, R1.5)

2. 材料: 50# 亮白PET, 不过光膜, 过UV油墨, 背胶
(Material: 50# bright white PET, no film, UV coated, adhesive)

3. 原材料及后处理工艺均能满足我司《环保技术标准》要求。
(Raw materials and the corresponding post processing should meet requirements defined in the T&W Environmental Protection Technical Standards)

DIM	TOL±	△						CUSTOMER:		T&W 同维 SHANGHAI GONGJIN TELECOM TECHNOLOGY CO.,LTD.	
			C1	C2	C3	C4		ASUS			
RANGE							TITLE:		MODEL:		PART NO: 61100000XXXX
0~6	0.1	0.1	0.15	0.2	印刷盒底标贴		RT-N300				
6~30	0.2	0.3	0.4	0.5	UNITS	mm	VER	A0	DRAW	罗明	DATE: 150710
30~80	0.25	0.5	0.9	1.2	MAT'L	XXXX	SCALE	1:1	CHECK	苏健	
80~180	0.3	0.8	1.2	1.5	FINISH	N/A	SHEET	1 / 1	PDE	N/A	
180~315	0.5	1.3	1.8	3							
315~500	0.7	1.5	2.5	4							
500~800	0.9	1.8	3	5							
ANG.TOL±	0°~30°/0.1°		30°~60°/0.3°		60°~90°/0.5°						

