


FCC RADIO EXPOSURE TEST REPORT

FCC ID : MSQ-RTAC68UV2
Equipment : Wireless-AC1900 Dual Band Gigabit Router
Brand Name : ASUS
Model Name : RT-AC68U, RT-AC68R, RT-AC68W, RT-AC68P,
TM-AC1900, RT-AC1900, RT-AC68U V2,
RT-AC1900P
Applicant : ASUSTeK COMPUTER INC.
4F, No. 150, Li-Te Rd., Peitou, Taipei 112, Taiwan
Manufacturer (1) : Compal Networking (KunShan) Co., LTD.
No. 520, Nabbang Rd., Economic & Technical
Development Zone Kunshan, Jiangsu Province
China
Manufacturer (2) : Askey Technology (Jiangsu) Ltd.
1388, Jiao Tong Road, Wujiang Economic
Technological Development Area, Jiang Su
Province, P.R.C
Manufacturer (3) : Arcadyan Technology (Vietnam) Co., Ltd.
Ba Thien Industrial Park, Ba Hien commune, Binh
Xuyen district, Vinh Phuc Province, Viet Nam
Standard : 47 CFR Part 2.1091

The product was received on Oct. 16, 2019 , and testing was started from Oct. 16, 2019 and completed on Dec. 04, 2019. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR Part 2.1091 and shown compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this variant report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.


Approved by: Cliff Chang

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 EUT General Information	5
1.2 Table for Multiple Listing	5
1.3 Table for SKU information	5
1.4 Table for Class II Change.....	6
1.5 Testing Location	6
2 Maximum Permissible Exposure	7
2.1 Limit of Maximum Permissible Exposure	7
2.2 MPE Calculation Method.....	7
2.3 Calculated Result and Limit.....	8
Photographs of EUT v01	



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
2	-	Exposure evaluation	PASS	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Sam Chen

Report Producer: Wendy Pan



1 General Description

1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) VHT: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)
5GHz WLAN	5150-5250 5725-5850	5180-5240 5745-5825	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)

1.2 Table for Multiple Listing

The EUT has eight model names which are identical to each other in all aspects except for the following table:

Brand Name	Model Name	Description
ASUS	RT-AC68U	All the models are identical; the different model numbers served as marketing strategy.
	RT-AC68R	
	RT-AC68W	
	RT-AC68P	
	TM-AC1900	
	RT-AC1900	
	RT-AC68U V2	
	RT-AC1900P	

From the above models, model: RT-AC68U was selected as representative model for the test and its data was recorded in this report.

1.3 Table for SKU information

SKU 3 information			
Vendor	LAN port transformer (Model No.)	WAN port transformer (Model No.)	Spec
NET SWAPN(FCE)	FCE_NS773602	FCE_NS771802	DIP 10/100/1000 BASE-T



1.4 Table for Class II Change

This product is an extension of original one reported under Sporton project number: FA3D0426-09

Below is the table for the change of the product with respect to the original one.

Modifications	Performance Checking
1. Adding two adapters (Model: ADP-33AW Y and AD2088320) 2. Add a manufacturer and address: Arcadyan Technology (Vietnam) Co., Ltd. / Ba Thien Industrial Park, Ba Hien commune, Binh Xuyen district, Vinh Phuc Province, Viet Nam.	Do not affect the test results.
3. Update the test rule of 5GHz Band 4 to "15.407 (b)(4)(i)" from "15.407 (b)(4)(ii)".	WLAN 5GHz Band 4 MPE

Note: WLAN 2.4GHz and WLAN 5GHz Band 1 MPE test result was based on original report.

1.5 Testing Location

Testing Location		
☐	HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-327-0973
☒	JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

Test site Designation No. TW0006 with FCC.

Test site registered number IC 4086D with Industry Canada.



2 Maximum Permissible Exposure

2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Method

The MPE was calculated at 22 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



2.3 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)
2.4G;D1D	6.68	25.92	32.60	0.50	33.10	2.04174	22	0.33569	1.00000
5.8G;D1D	8.71	27.05	35.76	0.23	35.99	3.97192	22	0.65303	1.00000

Simultaneous Transmission Analysis Mode: WLAN 2.4GHz+WLAN 5GHz

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Ratio (S/Limit)
2.4G;D1D	6.68	25.92	32.60	0.50	33.10	2.04174	22	0.33569	1	0.33569
5.8;D1D	8.71	27.05	35.76	0.23	35.99	3.97192	22	0.65303	1	0.65303
									Sum Ratio	0.98872
									Ratio Limit	1

Note: The above antenna gain was declared by manufacturer.

————THE END————