

FCC SAR TEST REPORT

FCC ID : MSQ-RTL8852CE
Equipment : 11ax RTL8852CE Combo module
Brand Name : ASUS
Model Name : RTL8852CE
Applicant : ASUSTeK COMPUTER INC.
1F., No. 15, Lide Rd., Beitou Dist., Taipei City 112, Taiwan
Manufacturer : ASUSTeK COMPUTER INC.
1F., No. 15, Lide Rd., Beitou Dist., Taipei City 112, Taiwan
Standard : FCC 47 CFR Part 2 (2.1093)

The product was installed into Notebook PC/ASUS Expertbook (Brand Name: ASUS, Model Name: B5406FMA,B5456FMA) during test.

The product was received on May 26, 2026 and testing was started from Jun. 10, 2026 and completed on Aug. 13, 2026. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample provide by manufacturer and the test data has been evaluated in accordance with the test procedures given in 47 CFR Part 2.1093 and FCC KDB and has been pass the FCC requirement.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Laboratory, the test report shall not be reproduced except in full.



Approved by: Cona Huang / Deputy Manager



Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010



Table of Contents

1. Statement of Compliance	4
2. Guidance Applied.....	4
3. Equipment Under Test (EUT) Information.....	5
3.1 General Information	5
3.2 Sensor Triggering angle and power verification	7
4. RF Exposure Limits.....	11
4.1 Uncontrolled Environment.....	11
4.2 Controlled Environment.....	11
4.3 RF Exposure limit for above 6GHz.....	12
5. Specific Absorption Rate (SAR).....	13
5.1 Introduction	13
5.2 SAR Definition.....	13
6. System Description and Setup	14
6.1 Test Site Location.....	14
6.2 E-Field Probe.....	15
6.3 Data Acquisition Electronics (DAE)	15
6.4 Phantom.....	16
6.5 Device Holder.....	17
7. Measurement Procedures	18
7.1 Spatial Peak SAR Evaluation.....	18
7.2 Power Reference Measurement.....	19
7.3 Area Scan	19
7.4 Zoom Scan.....	20
7.5 Volume Scan Procedures.....	20
7.6 Power Drift Monitoring.....	20
8. Test Equipment List.....	21
9. System Verification.....	22
9.1 Tissue Verification	22
9.2 System Performance Check Results.....	23
9.1 PD System Performance Check Results.....	24
10. RF Exposure Positions.....	24
10.1 SAR Testing for Tablet.....	24
11. WiFi/Bluetooth Output Power (Unit: dBm)	25
12. Antenna Location	55
13. SAR Test Results	58
13.1 Body SAR	60
13.2 6GHz PD Test Result	63
13.3 Repeated SAR Measurement	64
14. Simultaneous Transmission Analysis	65
14.1 Body Exposure Conditions.....	65
14.2 SPLSR Evaluation and Analysis.....	66
15. Uncertainty Assessment	67
16. References.....	70
Appendix A. Plots of SAR System Performance Check	
Appendix B. Plots of PD System Performance Check	
Appendix C. Plots of High SAR Measurement	
Appendix D. Plots of High PD Measurement	
Appendix E. DASY Calibration Certificate	
Appendix F. Test Setup Photos	

[illegible]

1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) for ASUSTeK COMPUTER INC., 11ax RTL8852CE Combo module, RTL8852CE, are as follows.

Equipment Class	Frequency Band	Highest SAR Summary	
		Body (Separation: 0 mm)	Highest Body Simultaneous Transmission 1g SAR (W/kg)
		1g SAR (W/kg)	
DTS	2.4GHz WLAN	1.04	1.08
NII	5GHz WLAN	1.14	1.59
6CD	6GHz WLAN	1.14	1.59
DSS	Bluetooth	0.45	1.59
Frequency Band		Body Reported IPD (mW/cm ²)	
6CD	6GHz WLAN	0.50	
Date of Testing:		2026/06/10 ~ 2026/08/13	

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation and the FCC designation No. TW3786 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC test. This device is in compliance with Specific Absorption Rate (SAR) general population/uncontrolled exposure limits (1.6 W/kg for Partial-Body 1g SAR) specified in FCC 47 CFR part 2 (2.1093), Human Exposure to RF Radiation Limits (1.0 mW/cm²=10 W/m²) specified in FCC 47 CFR part 1.1310 and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013 and FCC KDB publications.

Reviewed by: Jason Wang
Report Producer: Paula Chen

2. Guidance Applied

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards, the below KDB standard may not including in the TAF code without accreditation.

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2013
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- FCC KDB 865664 D02 SAR Reporting v01r02
- FCC KDB 447498 D01 General RF Exposure Guidance v06
- FCC KDB 248227 D01 802.11 Wi-Fi SAR v02r02
- FCC KDB 616217 D04 SAR for laptop and tablets v01r02
- IEC/IEEE 62209-1528:2020
- SPEAG DASY6 System Handbook
- SPEAG DASY6 Application Note (Interim Procedure for Device Operation at 6GHz-10GHz)

3. Equipment Under Test (EUT) Information

3.1 General Information

Product Feature & Specification	
Equipment Name	11ax RTL8852CE Combo module
Brand Name	ASUS
Model Name	RTL8852CE
FCC ID	MSQ-RTL8852CE
Wireless Technology and Frequency Range	WLAN 2.4 GHz Band: 2400 MHz ~ 2483.5 MHz WLAN 5.2 GHz Band: 5150 MHz ~ 5250 MHz WLAN 5.3 GHz Band: 5250 MHz ~ 5350 MHz WLAN 5.6 GHz Band: 5470 MHz ~ 5725 MHz WLAN 5.8 GHz Band: 5725 MHz ~ 5850 MHz WLAN 5.9 GHz Band: 5850 MHz ~ 5895 MHz WLAN 6GHz Band: 5925 MHz ~ 6425 MHz, 6425 MHz ~ 6525 MHz, 6525 MHz ~ 6875 MHz, 6875 MHz ~ 7125 MHz Bluetooth: 2400 MHz ~ 2483.5 MHz
Mode	WLAN: 802.11a/b/g/n/ac/ax HT20/HT40/VHT20/VHT40/VHT80/VHT160/HE20/HE40/HE80/HE160 Bluetooth BR/EDR/LE
Remark: 1. This device is convertible type notebook PC, and there have Laptop and Tablet two usage way, when end user is used different mode which the device will according current mode to limit different maximum power. 2. The device has two samples: the LUX sample and the ADV sample. The LUX sample is used as the main test, and the ADV sample is spot-checked based on the worst-case results.	

Host Information	
Equipment Name	Notebook PC/ASUS Expertbook
Brand Name	ASUS
Model Name	B5406FMA,B5456FMA
Remark: All models are electrically identical (including circuitry, components, layout, antenna type and gain, and enclosure); the different model names are for marketing purposes only.	

WLAN Antenna Information									
1_main (Shenzhen Luxshare Acoustics Technology Ltd)	Ant. Type	PIFA	connector		2_aux (Shenzhen Luxshare Acoustics Technology Ltd)	Ant. Type	PIFA	connector	
	Model No.	RAN01-RY7200001				Model No.	RAN01-RY7200001		
	Peak Gain (dBi)_NB mode					Peak Gain (dBi)_NB mode			
	2400~2483.5MHz	1.8	5850~5925MHz	2.6		2400~2483.5MHz	2	5850~5925MHz	2
	5150~5250MHz	2.9	5925~6425MHz	2.2		5150~5250MHz	1	5925~6425MHz	2.2
	5250~5350MHz	2.1	6425~6525MHz	1.5		5250~5350MHz	1.9	6425~6525MHz	1.9
	5470~5725MHz	2.9	6525~6875MHz	1		5470~5725MHz	2.5	6525~6875MHz	1.7
	5725~5875MHz	2.4	6875~7125MHz	2.4		5725~5875MHz	2.2	6875~7125MHz	1.6
	Peak Gain (dBi)_PAD mode					Peak Gain (dBi)_PAD mode			
	2400~2483.5MHz	1.6	5850~5925MHz	1.5		2400~2483.5MHz	0.6	5850~5925MHz	0.5
	5150~5250MHz	1.7	5925~6425MHz	1.8		5150~5250MHz	1.7	5925~6425MHz	1.3
	5250~5350MHz	1.2	6425~6525MHz	1.6		5250~5350MHz	2.8	6425~6525MHz	1.7
	5470~5725MHz	1.6	6525~6875MHz	0.4		5470~5725MHz	1	6525~6875MHz	0.9
	5725~5875MHz	2.6	6875~7125MHz	0.8		5725~5875MHz	1.9	6875~7125MHz	1.3
3_main (Advanced Wireless & Antenna INC))	Ant. Type	PIFA	connector		4_aux (Advanced Wireless & Antenna INC))	Ant. Type	PIFA	connector	
	Model No.	RAN01-RY7200002				Model No.	RAN01-RY7200002		
	Peak Gain (dBi)_NB mode					Peak Gain (dBi)_NB mode			
	2400~2483.5MHz	0.6	5850~5925MHz	2.1		2400~2483.5MHz	0.7	5850~5925MHz	1.5
	5150~5250MHz	2	5925~6425MHz	1.4		5150~5250MHz	0.8	5925~6425MHz	2.2
	5250~5350MHz	1.3	6425~6525MHz	1		5250~5350MHz	1.5	6425~6525MHz	1.7
	5470~5725MHz	2.6	6525~6875MHz	0.7		5470~5725MHz	2.2	6525~6875MHz	1.4
	5725~5875MHz	1.9	6875~7125MHz	1.2		5725~5875MHz	1.5	6875~7125MHz	1.6
	Peak Gain (dBi)_PAD mode					Peak Gain (dBi)_PAD mode			
	2400~2483.5MHz	1.5	5850~5925MHz	1.46		2400~2483.5MHz	0.58	5850~5925MHz	0.47
	5150~5250MHz	1.6	5925~6425MHz	1.77		5150~5250MHz	1.59	5925~6425MHz	1.28
	5250~5350MHz	1.07	6425~6525MHz	1.51		5250~5350MHz	2.64	6425~6525MHz	1.62
	5470~5725MHz	1.54	6525~6875MHz	0.38		5470~5725MHz	0.88	6525~6875MHz	0.88
	5725~5875MHz	2.42	6875~7125MHz	0.76		5725~5875MHz	1.87	6875~7125MHz	1.22

Bluetooth Antenna Information				
2_aux (Shenzhen Luxshare Acoustics Technology Ltd)	Ant. Type	PIFA	Peak Gain	NB mode: 2 PAD mode: 0.6
	connector		Model No.	RAN01-RY7200001
4_aux (Advanced Wireless & Antenna INC))	Ant. Type	PIFA	Peak Gain	NB mode: 0.7 PAD mode: 0.58
	connector		Model No.	RAN01-RY7200002

3.2 Sensor Triggering angle and power verification

General Note:

- The following guidance should be applied to laptops/tablets that use Hall Effect or gravity sensors to detect lid angle for the purpose of power reduction:

Step 1: With the lid is in closed mode (0 degrees), open the screen in 10 degree steps until laptop mode is obtained
 Step 2: Lower the screen 5 degrees. Closed mode should be reobtained. If not keep lowering in 5 degree steps
 Step 3: Open the screen in 1 degree steps until laptop mode is reobtained
 Step 4: Continue opening the screen in 1 degree steps until at least 5 degrees past where laptop mode was obtained
 Step 5: Then continue opening the screen in 10 degree steps until tablet mode is obtained
 Step 6: Power measurements should be taken at each step
 Step 7: Reverse this procedure going from tablet mode back down to closed mode

when the screen angle is from 0 degree to 360 degree to 0 degree								
Screen angle (degree) v.s. power	Main Antenna							
	Wireless Band	WLAN2.4G	WLAN5.2G	WLAN5.3G	WLAN5.5G	WLAN5.8G	WLAN5.9G	
	Clamshell Mode	0	12.40	6.84	7.70	7.03	7.71	6.88
		1	12.40	6.84	7.70	7.03	7.71	6.88
		2	12.40	6.84	7.70	7.03	7.71	6.88
		3	12.40	6.84	7.70	7.03	7.71	6.88
		4	12.40	6.84	7.70	7.03	7.71	6.88
		5	12.40	6.84	7.70	7.03	7.71	6.88
		10	12.40	6.84	7.70	7.03	7.71	6.88
		20	12.40	6.84	7.70	7.03	7.71	6.88
		30	12.40	6.84	7.70	7.03	7.71	6.88
		40	12.40	6.84	7.70	7.03	7.71	6.88
		50	12.40	6.84	7.70	7.03	7.71	6.88
		60	12.40	6.84	7.70	7.03	7.71	6.88
		70	12.40	6.84	7.70	7.03	7.71	6.88
		80	12.40	6.84	7.70	7.03	7.71	6.88
		90	12.40	6.84	7.70	7.03	7.71	6.88
		100	12.40	6.84	7.70	7.03	7.71	6.88
		110	12.40	6.84	7.70	7.03	7.71	6.88
		120	12.40	6.84	7.70	7.03	7.71	6.88
		130	12.40	6.84	7.70	7.03	7.71	6.88
		140	12.40	6.84	7.70	7.03	7.71	6.88
		150	12.40	6.84	7.70	7.03	7.71	6.88
		160	12.40	6.84	7.70	7.03	7.71	6.88
	Tent / Stand Mode	170	12.40	6.84	7.70	7.03	7.71	6.88
		180	12.40	6.84	7.70	7.03	7.71	6.88
		186	12.40	6.84	7.70	7.03	7.71	6.88
		187	12.40	6.84	7.70	7.03	7.71	6.88
		188	12.40	6.84	7.70	7.03	7.71	6.88
		189	12.40	6.84	7.70	7.03	7.71	6.88
		190	12.40	6.84	7.70	7.03	7.71	6.88
		191	12.87	6.82	7.67	7.51	7.76	7.71
		192	12.87	6.82	7.67	7.51	7.76	7.71
		193	12.87	6.82	7.67	7.51	7.76	7.71
		194	12.87	6.82	7.67	7.51	7.76	7.71
		195	12.87	6.82	7.67	7.51	7.76	7.71
		200	12.87	6.82	7.67	7.51	7.76	7.71
		210	12.87	6.82	7.67	7.51	7.76	7.71
		220	12.87	6.82	7.67	7.51	7.76	7.71
		230	12.87	6.82	7.67	7.51	7.76	7.71
		240	12.87	6.82	7.67	7.51	7.76	7.71
		250	12.87	6.82	7.67	7.51	7.76	7.71
		260	12.87	6.82	7.67	7.51	7.76	7.71
		270	12.87	6.82	7.67	7.51	7.76	7.71
	Tablet Mode	280	12.87	6.82	7.67	7.51	7.76	7.71
		290	12.87	6.82	7.67	7.51	7.76	7.71
		300	12.87	6.82	7.67	7.51	7.76	7.71
		310	12.87	6.82	7.67	7.51	7.76	7.71
		320	12.87	6.82	7.67	7.51	7.76	7.71
		330	12.87	6.82	7.67	7.51	7.76	7.71
		336	12.87	6.82	7.67	7.51	7.76	7.71
		337	12.87	6.82	7.67	7.51	7.76	7.71
		338	12.87	6.82	7.67	7.51	7.76	7.71
		339	12.87	6.82	7.67	7.51	7.76	7.71
		340	12.87	6.82	7.67	7.51	7.76	7.71
		341	12.87	6.82	7.67	7.51	7.76	7.71
		342	12.87	6.82	7.67	7.51	7.76	7.71



FCC SAR TEST REPORT

Report No. : FA622608

		343	12.87	6.82	7.67	7.51	7.76	7.71
		344	12.87	6.82	7.67	7.51	7.76	7.71
		345	12.87	6.82	7.67	7.51	7.76	7.71
		350	12.87	6.82	7.67	7.51	7.76	7.71
		360	12.87	6.82	7.67	7.51	7.76	7.71
		350	12.87	6.82	7.67	7.51	7.76	7.71
		345	12.87	6.82	7.67	7.51	7.76	7.71
		344	12.87	6.82	7.67	7.51	7.76	7.71
		343	12.87	6.82	7.67	7.51	7.76	7.71
		342	12.87	6.82	7.67	7.51	7.76	7.71
		341	12.87	6.82	7.67	7.51	7.76	7.71
		340	12.87	6.82	7.67	7.51	7.76	7.71
	Tent / Stand Mode	339	12.87	6.82	7.67	7.51	7.76	7.71
		338	12.87	6.82	7.67	7.51	7.76	7.71
		337	12.87	6.82	7.67	7.51	7.76	7.71
		336	12.87	6.82	7.67	7.51	7.76	7.71
		330	12.87	6.82	7.67	7.51	7.76	7.71
		320	12.87	6.82	7.67	7.51	7.76	7.71
		310	12.87	6.82	7.67	7.51	7.76	7.71
		300	12.87	6.82	7.67	7.51	7.76	7.71
		290	12.87	6.82	7.67	7.51	7.76	7.71
		280	12.87	6.82	7.67	7.51	7.76	7.71
		270	12.87	6.82	7.67	7.51	7.76	7.71
		260	12.87	6.82	7.67	7.51	7.76	7.71
		250	12.87	6.82	7.67	7.51	7.76	7.71
		240	12.87	6.82	7.67	7.51	7.76	7.71
		230	12.87	6.82	7.67	7.51	7.76	7.71
		220	12.87	6.82	7.67	7.51	7.76	7.71
		200	12.87	6.82	7.67	7.51	7.76	7.71
		195	12.87	6.82	7.67	7.51	7.76	7.71
		194	12.87	6.82	7.67	7.51	7.76	7.71
		193	12.87	6.82	7.67	7.51	7.76	7.71
		192	12.87	6.82	7.67	7.51	7.76	7.71
		191	12.87	6.82	7.67	7.51	7.76	7.71
	Clamshell Mode	190	12.40	6.84	7.70	7.03	7.71	6.88
		189	12.40	6.84	7.70	7.03	7.71	6.88
		188	12.40	6.84	7.70	7.03	7.71	6.88
		187	12.40	6.84	7.70	7.03	7.71	6.88
		186	12.40	6.84	7.70	7.03	7.71	6.88
		180	12.40	6.84	7.70	7.03	7.71	6.88
		170	12.40	6.84	7.70	7.03	7.71	6.88
		160	12.40	6.84	7.70	7.03	7.71	6.88
		150	12.40	6.84	7.70	7.03	7.71	6.88
		140	12.40	6.84	7.70	7.03	7.71	6.88
		130	12.40	6.84	7.70	7.03	7.71	6.88
		120	12.40	6.84	7.70	7.03	7.71	6.88
		110	12.40	6.84	7.70	7.03	7.71	6.88
		100	12.40	6.84	7.70	7.03	7.71	6.88
		90	12.40	6.84	7.70	7.03	7.71	6.88
		80	12.40	6.84	7.70	7.03	7.71	6.88
		70	12.40	6.84	7.70	7.03	7.71	6.88
		60	12.40	6.84	7.70	7.03	7.71	6.88
		50	12.40	6.84	7.70	7.03	7.71	6.88
		40	12.40	6.84	7.70	7.03	7.71	6.88
		30	12.40	6.84	7.70	7.03	7.71	6.88
		20	12.40	6.84	7.70	7.03	7.71	6.88
		10	12.40	6.84	7.70	7.03	7.71	6.88
		5	12.40	6.84	7.70	7.03	7.71	6.88
		4	12.40	6.84	7.70	7.03	7.71	6.88
		3	12.40	6.84	7.70	7.03	7.71	6.88
		2	12.40	6.84	7.70	7.03	7.71	6.88
		1	12.40	6.84	7.70	7.03	7.71	6.88
		0	12.40	6.84	7.70	7.03	7.71	6.88



when the screen angle is from 0 degree to 360 degree to 0 degree								
Screen angle (degree) v.s. power	Aux Antenna							
	Wireless Band	WLAN2.4G	WLAN5.2G	WLAN5.3G	WLAN5.5G	WLAN5.8G	WLAN5.9G	
	Clamshell Mode	0	12.10	7.03	7.14	6.36	7.95	7.90
		1	12.10	7.03	7.14	6.36	7.95	7.90
		2	12.10	7.03	7.14	6.36	7.95	7.90
		3	12.10	7.03	7.14	6.36	7.95	7.90
		4	12.10	7.03	7.14	6.36	7.95	7.90
		5	12.10	7.03	7.14	6.36	7.95	7.90
		10	12.10	7.03	7.14	6.36	7.95	7.90
		20	12.10	7.03	7.14	6.36	7.95	7.90
		30	12.10	7.03	7.14	6.36	7.95	7.90
		40	12.10	7.03	7.14	6.36	7.95	7.90
		50	12.10	7.03	7.14	6.36	7.95	7.90
		60	12.10	7.03	7.14	6.36	7.95	7.90
		70	12.10	7.03	7.14	6.36	7.95	7.90
		80	12.10	7.03	7.14	6.36	7.95	7.90
		90	12.10	7.03	7.14	6.36	7.95	7.90
		100	12.10	7.03	7.14	6.36	7.95	7.90
		110	12.10	7.03	7.14	6.36	7.95	7.90
		120	12.10	7.03	7.14	6.36	7.95	7.90
		130	12.10	7.03	7.14	6.36	7.95	7.90
		140	12.10	7.03	7.14	6.36	7.95	7.90
		150	12.10	7.03	7.14	6.36	7.95	7.90
		160	12.10	7.03	7.14	6.36	7.95	7.90
		170	12.10	7.03	7.14	6.36	7.95	7.90
		180	12.10	7.03	7.14	6.36	7.95	7.90
		186	12.10	7.03	7.14	6.36	7.95	7.90
		187	12.10	7.03	7.14	6.36	7.95	7.90
		188	12.10	7.03	7.14	6.36	7.95	7.90
		189	12.10	7.03	7.14	6.36	7.95	7.90
		190	12.10	7.03	7.14	6.36	7.95	7.90
	Tent / Stand Mode	191	12.87	6.95	7.18	6.85	8.00	7.94
		192	12.87	6.95	7.18	6.85	8.00	7.94
		193	12.87	6.95	7.18	6.85	8.00	7.94
		194	12.87	6.95	7.18	6.85	8.00	7.94
		195	12.87	6.95	7.18	6.85	8.00	7.94
		200	12.87	6.95	7.18	6.85	8.00	7.94
		210	12.87	6.95	7.18	6.85	8.00	7.94
		220	12.87	6.95	7.18	6.85	8.00	7.94
		230	12.87	6.95	7.18	6.85	8.00	7.94
		240	12.87	6.95	7.18	6.85	8.00	7.94
		250	12.87	6.95	7.18	6.85	8.00	7.94
		260	12.87	6.95	7.18	6.85	8.00	7.94
		270	12.87	6.95	7.18	6.85	8.00	7.94
		280	12.87	6.95	7.18	6.85	8.00	7.94
		290	12.87	6.95	7.18	6.85	8.00	7.94
		300	12.87	6.95	7.18	6.85	8.00	7.94
		310	12.87	6.95	7.18	6.85	8.00	7.94
		320	12.87	6.95	7.18	6.85	8.00	7.94
		330	12.87	6.95	7.18	6.85	8.00	7.94
		Tablet Mode	336	12.87	6.95	7.18	6.85	8.00
	337		12.87	6.95	7.18	6.85	8.00	7.94
	338		12.87	6.95	7.18	6.85	8.00	7.94
	339		12.87	6.95	7.18	6.85	8.00	7.94
	340		12.87	6.95	7.18	6.85	8.00	7.94
	341		12.87	6.95	7.18	6.85	8.00	7.94
	342		12.87	6.95	7.18	6.85	8.00	7.94
	343		12.87	6.95	7.18	6.85	8.00	7.94
	344		12.87	6.95	7.18	6.85	8.00	7.94
	345		12.87	6.95	7.18	6.85	8.00	7.94
	350		12.87	6.95	7.18	6.85	8.00	7.94
	360		12.87	6.95	7.18	6.85	8.00	7.94
	Tent / Stand Mode	345	12.87	6.95	7.18	6.85	8.00	7.94
		344	12.87	6.95	7.18	6.85	8.00	7.94
		343	12.87	6.95	7.18	6.85	8.00	7.94
		342	12.87	6.95	7.18	6.85	8.00	7.94
		341	12.87	6.95	7.18	6.85	8.00	7.94



FCC SAR TEST REPORT

Report No. : FA622608

		336	12.87	6.95	7.18	6.85	8.00	7.94
		330	12.87	6.95	7.18	6.85	8.00	7.94
		320	12.87	6.95	7.18	6.85	8.00	7.94
		310	12.87	6.95	7.18	6.85	8.00	7.94
		300	12.87	6.95	7.18	6.85	8.00	7.94
		290	12.87	6.95	7.18	6.85	8.00	7.94
		280	12.87	6.95	7.18	6.85	8.00	7.94
		270	12.87	6.95	7.18	6.85	8.00	7.94
		260	12.87	6.95	7.18	6.85	8.00	7.94
		250	12.87	6.95	7.18	6.85	8.00	7.94
		240	12.87	6.95	7.18	6.85	8.00	7.94
		230	12.87	6.95	7.18	6.85	8.00	7.94
		220	12.87	6.95	7.18	6.85	8.00	7.94
		200	12.87	6.95	7.18	6.85	8.00	7.94
		195	12.87	6.95	7.18	6.85	8.00	7.94
		194	12.87	6.95	7.18	6.85	8.00	7.94
		193	12.87	6.95	7.18	6.85	8.00	7.94
		192	12.87	6.95	7.18	6.85	8.00	7.94
		191	12.87	6.95	7.18	6.85	8.00	7.94
	Clamshell Mode	190	12.10	7.03	7.14	6.36	7.95	7.90
		189	12.10	7.03	7.14	6.36	7.95	7.90
		188	12.10	7.03	7.14	6.36	7.95	7.90
		187	12.10	7.03	7.14	6.36	7.95	7.90
		186	12.10	7.03	7.14	6.36	7.95	7.90
		180	12.10	7.03	7.14	6.36	7.95	7.90
		170	12.10	7.03	7.14	6.36	7.95	7.90
		160	12.10	7.03	7.14	6.36	7.95	7.90
		150	12.10	7.03	7.14	6.36	7.95	7.90
		140	12.10	7.03	7.14	6.36	7.95	7.90
		130	12.10	7.03	7.14	6.36	7.95	7.90
		120	12.10	7.03	7.14	6.36	7.95	7.90
		110	12.10	7.03	7.14	6.36	7.95	7.90
		100	12.10	7.03	7.14	6.36	7.95	7.90
		90	12.10	7.03	7.14	6.36	7.95	7.90
		80	12.10	7.03	7.14	6.36	7.95	7.90
		70	12.10	7.03	7.14	6.36	7.95	7.90
		60	12.10	7.03	7.14	6.36	7.95	7.90
		50	12.10	7.03	7.14	6.36	7.95	7.90
		40	12.10	7.03	7.14	6.36	7.95	7.90
		30	12.10	7.03	7.14	6.36	7.95	7.90
		20	12.10	7.03	7.14	6.36	7.95	7.90
		10	12.10	7.03	7.14	6.36	7.95	7.90
		5	12.10	7.03	7.14	6.36	7.95	7.90
		4	12.10	7.03	7.14	6.36	7.95	7.90
		3	12.10	7.03	7.14	6.36	7.95	7.90
		2	12.10	7.03	7.14	6.36	7.95	7.90
		1	12.10	7.03	7.14	6.36	7.95	7.90
		0	12.10	7.03	7.14	6.36	7.95	7.90

4. RF Exposure Limits

4.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

4.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

1. Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

4.3 RF Exposure limit for above 6GHz

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Peak Spatially Averaged Power Density was evaluated over a circular area of 4cm² per interim FCC Guidance for near-field power density evaluations per October 2018 TCB Workshop notes

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

5. Specific Absorption Rate (SAR)

5.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

5.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg)

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

6. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:



- The DASY system in SAR Configuration is shown above
- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running windows software and the DASY software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

6.1 Test Site Location

The SAR measurement facilities used to collect data are within both Sporton Lab list below test site location are accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190 and 3786) and the FCC designation No. TW1190 and TW3786 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC test.

Laboratory	EMC & Wireless Communications Laboratory		Wensan Laboratory				
Test Site Location	TW1190		TW3786				
	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333		No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010				
Test Site No.	SAR01-HY	SAR03-HY	SAR08-HY	SAR09-HY	SAR15-HY	SAR18-HY	SAR21-HY
	SAR04-HY	SAR05-HY	SAR11-HY	SAR12-HY	SAR16-HY	SAR19-HY	SAR22-HY
	SAR06-HY	SAR10-HY	SAR13-HY	SAR14-HY	SAR17-HY	SAR20-HY	

6.2 E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG). The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

< ES3DV3 Probe >

Construction	Symmetric design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	4 MHz – 4 GHz; Linearity: ± 0.2 dB (30 MHz – 4 GHz)	
Directivity	± 0.2 dB in TSL (rotation around probe axis) ± 0.3 dB in TSL (rotation normal to probe axis)	
Dynamic Range	5 μ W/g – > 100 mW/g; Linearity: ± 0.2 dB	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 3.9 mm (body: 12 mm) Distance from probe tip to dipole centers: 3.0 mm	

< EX3DV4 Probe >

Construction	Symmetric design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	4 MHz – > 6 GHz Linearity: ± 0.2 dB (30 MHz – 6 GHz)	
Directivity	± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)	
Dynamic Range	10 μ W/g – > 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 2.5 mm (body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

6.3 Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.

The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.




Fig 5.1 Photo of DAE


6.4 Phantom

< SAM Twin Phantom >

Shell Thickness	2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm	
Filling Volume	Approx. 25 liters	
Dimensions	Length: 1000 mm; Width: 500 mm; Height: adjustable feet	
Measurement Areas	Left Hand, Right Hand, Flat Phantom	

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

< ELI Phantom >

Shell Thickness	2 ± 0.2 mm (sagging: < 1%)	
Filling Volume	Approx. 30 liters	
Dimensions	Major ellipse axis: 600 mm Minor axis: 400 mm	

The ELI phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with standard and all known tissue simulating liquids.

6.5 Device Holder

< Mounting Device for Hand-Held Transmitter >

In combination with the Twin SAM V5.0/V5.0c or ELI phantoms, the Mounting Device for Hand-Held Transmitters enables rotation of the mounted transmitter device to specified spherical coordinates. At the heads, the rotation axis is at the ear opening. Transmitter devices can be easily and accurately positioned according to IEC 62209-1, IEEE 1528, FCC, or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat). And upgrade kit to Mounting Device to enable easy mounting of wider devices like big smart-phones, e-books, small tablets, etc. It holds devices with width up to 140 mm.



Mounting Device for Hand-Held Transmitters



Mounting Device Adaptor for Wide-Phones

< Mounting Device for Laptops and other Body-Worn Transmitters >

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the mounting device in place of the phone positioned. The extension is fully compatible with the SAM Twin and ELI phantoms.



Mounting Device for Laptops

7. Measurement Procedures

The measurement procedures are as follows:

- (a) Configure the device RF transmitters to be in continuous transmission mode., at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

7.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

7.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

7.3 Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB0) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}	≤ 2 GHz: ≤ 15 mm $2 - 3$ GHz: ≤ 12 mm	$3 - 4$ GHz: ≤ 12 mm $4 - 6$ GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

7.4 Zoom Scan

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			≤ 2 GHz: ≤ 8 mm $2 - 3$ GHz: ≤ 5 mm*	$3 - 4$ GHz: ≤ 5 mm* $4 - 6$ GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	$3 - 4$ GHz: ≤ 4 mm $4 - 5$ GHz: ≤ 3 mm $5 - 6$ GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	$3 - 4$ GHz: ≤ 3 mm $4 - 5$ GHz: ≤ 2.5 mm $5 - 6$ GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	$3 - 4$ GHz: ≥ 28 mm $4 - 5$ GHz: ≥ 25 mm $5 - 6$ GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

7.5 Volume Scan Procedures

The volume scan is used to assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

7.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.

8. Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Last Cal.	Due Date
SPEAG	2450MHz System Validation Kit ⁽²⁾	D2450V2	736	Aug. 15, 2024	Aug. 12, 2027
SPEAG	2450MHz System Validation Kit	D2450V2	929	Nov. 12, 2025	Nov. 11, 2026
SPEAG	6500MHz System Validation Kit	D6.5GHzV2	1083	Oct. 22, 2025	Oct. 21, 2026
SPEAG	5GHz System Validation Kit ⁽²⁾	D5GHzV2	1171	Apr. 19, 2024	Apr. 16, 2027
SPEAG	5GHz System Validation Kit ⁽²⁾	D5GHzV2	1006	Oct. 15, 2024	Oct. 13, 2026
SPEAG	5G Verification Source	10GHz	1052	Oct. 13, 2025	Oct. 12, 2026
SPEAG	Data Acquisition Electronics	DAE4	1694	Oct. 15, 2025	Oct. 14, 2026
SPEAG	Data Acquisition Electronics	DAE4	699	Feb. 13, 2026	Feb. 12, 2027
SPEAG	Data Acquisition Electronics	DAE4	1805	May. 19, 2026	May. 18, 2027
SPEAG	Dosimetric E-Field Probe	EX3DV4	7785	Nov. 26, 2025	Nov. 25, 2026
SPEAG	Dosimetric E-Field Probe	EX3DV4	7590	Mar. 17, 2026	Mar. 16, 2027
SPEAG	Dielectric Probe Kit	DAK-3.5	1126	Sep. 16, 2025	Sep. 15, 2026
SPEAG	EUmmWV Probe Tip Protection	EUmmWV3	9424	Mar. 12, 2026	Mar. 11, 2027
Testo	Hygro meter	608-H1	45196600	Nov. 04, 2025	Nov. 03, 2026
Testo	Hygro meter	608-H1	45207528	Nov. 04, 2025	Nov. 03, 2026
R&S	BT Base Station	CBT	101136	Oct. 29, 2025	Oct. 28, 2026
SPEAG	Device Holder	N/A	N/A	N/A	N/A
Anritsu	Signal Generator	MG3710A	6201502524	Sep. 24, 2025	Sep. 23, 2026
Keysight	ENA Network Analyzer	E5071C	MY46104758	Oct. 14, 2025	Oct. 13, 2026
LINE SEIKI	Digital Thermometer	DTM3000-spezial	3690	Aug. 14, 2025	Aug. 13, 2026
Anritsu	Power Meter	ML2495A	1804003	Aug. 18, 2025	Aug. 17, 2026
Anritsu	Power Sensor	MA2411B	1726150	Aug. 18, 2025	Aug. 17, 2026
Anritsu	Spectrum Analyzer	MS2830A	6272625959	Aug. 14, 2025	Aug. 13, 2026
Mini-Circuits	Power Amplifier	ZVE-8G+	D120604	Oct. 17, 2025	Oct. 16, 2026
Mini-Circuits	Power Amplifier	ZHL-42W+	QA1344002	Oct. 17, 2025	Oct. 16, 2026
ATM	Dual Directional Coupler	C122H-10	P610410z-02	Note 1	
Warison	Directional Coupler	WCOU-10-50S-10	WR889BMC4B1	Note 1	
Woken	Attenuator 1	WK0602-XX	N/A	Note 1	
PE	Attenuator 2	PE7005-10	N/A	Note 1	
PE	Attenuator 3	PE7005- 3	N/A	Note 1	

General Note:

1. Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check source.
2. The dipole calibration interval can be extended to 3 years with justification. The dipoles are also not physically damaged, or repaired during the interval. The justification data in appendix C can be found which the return loss is < -20dB, within 20% of prior calibration, the impedance is within 5 ohm of prior calibration for each dipole.

9. System Verification

9.1 Tissue Verification

The tissue dielectric parameters of tissue-equivalent media used for SAR measurements must be characterized within a temperature range of 18°C to 25°C, measured with calibrated instruments and apparatuses, such as network analyzers and temperature probes. The temperature of the tissue-equivalent medium during SAR measurement must also be within 18°C to 25°C and within $\pm 2^\circ\text{C}$ of the temperature when the tissue parameters are characterized. The tissue dielectric measurement system must be calibrated before use. The dielectric parameters must be measured before the tissue-equivalent medium is used in a series of SAR measurements.

The liquid tissue depth was at least 15cm in the phantom for all SAR testing

The SPEAG Dasy Measurement system implement a SAR error compensation algorithm as documented in IEEE Std 1528-2013 to automatically compensate the measured SAR results for deviations between the measured and required tissue dielectric parameters, according to KDB 865664 D01 and IEC/IEEE 62209-1528, the tolerance for "Delta (σ)" and "Delta (ϵ_r)" can be relaxed to $\pm 10\%$

< Tissue Dielectric Parameter Check Results >

Frequency (MHz)	Liquid Temp (°C)	Conductivity (σ)	Permittivity (ϵ_r)	Conductivity Target (σ)	Permittivity Target (ϵ_r)	Delta (σ) (%)	Delta (ϵ_r) (%)	Limit (%)	Date
2450	22.5	1.827	40.605	1.80	39.2	1.50	3.58	± 10.0	2026-06-11
2450	22.1	1.87	41.4	1.80	39.2	3.89	5.61	± 10.0	2026-06-21
5250	22.5	4.621	35.566	4.71	36.0	-1.89	-1.21	± 10.0	2026-06-10
5250	22	4.63	36.6	4.71	36.0	-1.70	1.67	± 10.0	2026-06-20
5600	22	4.97	35.8	5.07	35.5	-1.97	0.85	± 10.0	2026-06-20
5800	22.5	5.249	34.539	5.27	35.3	-0.40	-2.16	± 10.0	2026-06-10
5800	22	5.31	35.7	5.27	35.3	0.76	1.13	± 10.0	2026-06-20
6500	22.5	6.15	34	6.07	34.5	1.32	-1.45	± 10.0	2026-06-18
6500	22.6	6.21	34.2	6.07	34.5	2.31	-0.87	± 10.0	2026-06-19
6500	22.3	6.04	32.2	6.07	34.5	-0.49	-6.67	± 10.0	2026-08-13

9.2 System Performance Check Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Test Site	Date	Frequency (MHz)	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 1g SAR (W/kg)	Targeted 1g SAR (W/kg)	Normalized 1g SAR (W/kg)	Deviation (%)
SAR13	2026-06-11	2450	50	D2450V2 - 736	EX3DV4 - SN7785	DAE4 Sn1694	2.5	51.4	50	-2.72
SAR14	2026-06-21	2450	50	D2450V2 - 929	EX3DV4 - SN7590	DAE4 Sn1805	2.64	53.3	52.8	-0.94
SAR13	2026-06-10	5250	50	D5GHzV2 - 1171	EX3DV4 - SN7785	DAE4 Sn1694	3.71	78.7	74.2	-5.72
SAR14	2026-06-20	5250	50	D5GHzV2 - 1006	EX3DV4 - SN7590	DAE4 Sn1805	3.78	80.6	75.6	-6.20
SAR14	2026-06-20	5600	50	D5GHzV2 - 1006	EX3DV4 - SN7590	DAE4 Sn1805	4.21	83.4	84.2	0.96
SAR13	2026-06-10	5800	50	D5GHzV2 - 1171	EX3DV4 - SN7785	DAE4 Sn1694	3.76	78.9	75.2	-4.69
SAR14	2026-06-20	5800	50	D5GHzV2 - 1006	EX3DV4 - SN7590	DAE4 Sn1805	4.17	80.6	83.4	3.47
SAR14	2026-06-18	6500	100	D6.5GHzV2 - 1083	EX3DV4 - SN7590	DAE4 Sn1805	32.3	302	323	6.95
SAR14	2026-06-19	6500	100	D6.5GHzV2 - 1083	EX3DV4 - SN7590	DAE4 Sn1805	32.2	302	322	6.62
SAR14	2026-08-13	6500	100	D6.5GHzV2 - SN1083	EX3DV4 - SN7590	DAE4 Sn1805	28.7	302	287	-4.97




Fig 8.3.1 System Performance Check Setup



Fig 8.3.2 Setup Photo

9.3 PD System Performance Check Results

The system was verified to be within ± 0.66 dB of the power density targets on the calibration certificate according to the test system specification in the user's manual and calibration facility recommendation. The 0.66 dB deviation threshold represents the expanded uncertainty for system performance checks using SPEAG's mmWave verification sources. The same spatial resolution and measurement region used in the source calibration was applied during the system check. The measured power density distribution of verification source was also confirmed through visual inspection to have no noticeable differences, both spatially (shape) and numerically (level) from the distribution provided by the manufacturer, per November 2017 TCBC Workshop Notes

Test Location	Frequency (GHz)	5G Verification Source	Probe S/N	DAE S/N	Distance (mm)	Measured 4 cm ² (W/m ²)	Targeted 4 cm ² (W/m ²)	Deviation (dB)	Date
SAR14	10G	10GHz_1052	EUmmWV4 - 9424	699	10mm	56	54	0.16	2026/6/23




Figure 4-3
System Verification Setup Photo

System Performance Check Setup

10. RF Exposure Positions

10.1 SAR Testing for Tablet

This device can be used also in full sized tablet exposure conditions, due to its size. Per FCC KDB 616217, the back surface and edges of the tablet should be tested for SAR compliance with the tablet touching the phantom. The SAR exclusion threshold in KDB 447498 D01v06 can be applied to determine SAR test exclusion for adjacent edge configurations. The closest distance from the antenna to an adjacent tablet edge is used to determine if SAR testing is required for the adjacent edges, with the adjacent edge positioned against the phantom and the edge containing the antenna positioned perpendicular to the phantom.

11. WiFi/Bluetooth Output Power (Unit: dBm)

General Note:

1. For each antenna, transmit power in SISO operation is larger than (or equal to) the power in MIMO operation, RF exposure compliance of MIMO mode can be deduced from the compliance simultaneous transmission of antennas operating in SISO mode.
2. Per KDB 248227 D01v02r02, the simultaneous SAR provisions in KDB publication 447498 should be applied to determine simultaneous transmission SAR test exclusion for WiFi MIMO. If the sum of 1g single transmission chain SAR measurements is $< 1.6\text{W/kg}$ and SAR peak to location ratio ≤ 0.04 , no additional SAR measurements for MIMO.
3. The maximum output power specified for production units are determined for all applicable 802.11 transmission modes in each standalone and aggregated frequency band. Maximum output power is measured for the highest maximum output power configuration(s) in each frequency band according to the default power measurement procedures. For "Not required", SAR Test reduction was applied from KDB 248227 guidance, Sec. 2.1, b), 1) when the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel in the initial test configuration, additional output power measurements were not necessary.
4. Per KDB 248227 D01v02r02, SAR test reduction is determined according to 802.11 transmission mode configurations and certain exposure conditions with multiple test positions. In the 2.4 GHz band, separate SAR procedures are applied to DSSS and OFDM configurations to simplify DSSS test requirements. For OFDM, in both 2.4 and 5 GHz bands, an initial test configuration must be determined for each standalone and aggregated frequency band, according to the transmission mode configuration with the highest maximum output power specified for production units to perform SAR measurements. If the same highest maximum output power applies to different combinations of channel bandwidths, modulations and data rates, additional procedures are applied to determine which test configurations require SAR measurement. When applicable, an initial test position may be applied to reduce the number of SAR measurements required for next to the ear, UMPC mini-tablet or hotspot mode configurations with multiple test positions.
5. For 2.4 GHz 802.11b DSSS, either the initial test position procedure for multiple exposure test positions or the DSSS procedure for fixed exposure position is applied; these are mutually exclusive. For 2.4 GHz and 5 GHz OFDM configurations, the initial test configuration is applied to measure SAR using either the initial test position procedure for multiple exposure test position configurations or the initial test configuration procedures for fixed exposure test conditions. Based on the reported SAR of the measured configurations and maximum output power of the transmission mode configurations that are not included in the initial test configuration, the subsequent test configuration and initial test position procedures are applied to determine if SAR measurements are required for the remaining OFDM transmission configurations. In general, the number of test channels that require SAR measurement is minimized based on maximum output power measured for the test sample(s).
6. For OFDM transmission configurations in the 2.4 GHz and 5 GHz bands, When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel for each frequency band.
7. DSSS and OFDM configurations are considered separately according to the required SAR procedures. SAR is measured in the initial test position using the 802.11 transmission mode configuration required by the DSSS procedure or initial test configuration and subsequent test configuration(s) according to the OFDM procedures. 18 The initial test position procedure is described in the following:
 - a. When the reported SAR of the initial test position is $\leq 0.4\text{ W/kg}$, further SAR measurement is not required for the other test positions in that exposure configuration and 802.11 transmission mode combinations within the frequency band or aggregated band.
 - b. When the reported SAR of the test position is $> 0.4\text{ W/kg}$, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is $\leq 0.8\text{ W/kg}$ or all required test position are tested.
 - c. For all positions/configurations, when the reported SAR is $> 0.8\text{ W/kg}$, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is $\leq 1.2\text{ W/kg}$ or all required channels are tested.
8. Per 201904 TCBC workshops, General principles of FCC KDB Publication 248227 D01 can be applied to determine the SAR Initial Test Configurations and test reduction for 802.11ax SAR testing. For the table below the 802.11ax maximum power is SU (non-OFDMA), and the SU maximum power also higher than RU (OFDMA)
9. In applying the test guidance, the IEEE 802.11 mode with the maximum output power (out of all modes) should be considered for testing
10. For modes with the same maximum output power, the guidance from section 5.3.2 a) of FCC KDB Publication 248227 D01 should be applied, with 802.11ax being considered as the highest 802.11 mode for the appropriate frequency bands
11. When SAR testing for 802.11ax is required
 - a. If the maximum output power is highest for OFDMA scenarios, choose the tone size with the maximum number of tones and the highest maximum output power
 - b. Otherwise, consider the fully allocated channel for SAR testing
 - c. When SAR testing is required on RU sizes less than the fully allocated channel, use the RU number closest to the middle of the channel, choosing the higher RU number when two RUs are equidistant to the middle of the channel



【2.4GHz WLAN_Main_Laptop】

			Main		
Mode	Channel	Frequency (MHz)	Average Power (dBm)	Tune-Up Limit	Duty Cycle %
802.11b 1Mbps	1	2412	12.21	12.50	99.67
	6	2437	12.24	12.50	
	11	2462	12.18	12.50	
	12	2467	12.17	12.50	
	13	2472	5.89	6.00	
802.11g 6Mbps	1	2412	Not Required	12.50	Not Required
	6	2437	Not Required	12.50	
	11	2462	Not Required	12.50	
	12	2467	Not Required	12.50	
	13	2472	Not Required	11.00	
802.11n-HT20 MCS0	1	2412	Not Required	12.50	Not Required
	6	2437	Not Required	12.50	
	11	2462	Not Required	12.50	
	12	2467	Not Required	12.50	
	13	2472	Not Required	6.00	
802.11n-HT40 MCS0	3	2422	Not Required	12.50	Not Required
	6	2437	Not Required	12.50	
	9	2452	Not Required	12.50	
	10	2457	Not Required	12.50	
	11	2462	Not Required	12.50	
802.11ac-VHT20 MCS0	1	2412	Not Required	12.50	Not Required
	6	2437	Not Required	12.50	
	11	2462	Not Required	12.50	
	12	2467	Not Required	12.50	
	13	2472	Not Required	6.00	
802.11ac-VHT40 MCS0	3	2422	Not Required	12.50	Not Required
	6	2437	Not Required	12.50	
	9	2452	Not Required	12.50	
	10	2457	Not Required	12.50	
	11	2462	Not Required	12.50	

**【2.4GHz WLAN_Main_Tablet】**

Mode	Channel	Frequency (MHz)	Main		
			Average Power (dBm)	Tune-Up Limit	Duty Cycle %
802.11b 1Mbps	1	2412	13.33	14.00	99.67
	6	2437	13.76	14.00	
	11	2462	13.74	14.00	
	12	2467	12.29	12.50	
	13	2472	5.98	6.00	
802.11g 6Mbps	1	2412	Not Required	14.00	Not Required
	6	2437	Not Required	14.00	
	11	2462	Not Required	14.00	
	12	2467	Not Required	14.00	
	13	2472	Not Required	10.50	
802.11n-HT20 MCS0	1	2412	Not Required	14.00	Not Required
	6	2437	Not Required	14.00	
	11	2462	Not Required	14.00	
	12	2467	Not Required	14.00	
	13	2472	Not Required	5.50	
802.11n-HT40 MCS0	3	2422	Not Required	14.00	Not Required
	6	2437	Not Required	14.00	
	9	2452	Not Required	14.00	
	10	2457	Not Required	14.00	
	11	2462	Not Required	13.00	
802.11ac-VHT20 MCS0	1	2412	Not Required	14.00	Not Required
	6	2437	Not Required	14.00	
	11	2462	Not Required	14.00	
	12	2467	Not Required	14.00	
	13	2472	Not Required	5.50	
802.11ac-VHT40 MCS0	3	2422	Not Required	14.00	Not Required
	6	2437	Not Required	14.00	
	9	2452	Not Required	14.00	
	10	2457	Not Required	14.00	
	11	2462	Not Required	13.00	

【2.4GHz WLAN_Aux_Laptop】

Mode	Channel	Frequency (MHz)	Aux		
			Average Power (dBm)	Tune-Up Limit	Duty Cycle %
802.11b 1Mbps	1	2412	12.28	12.50	99.51
	6	2437	12.20	12.50	
	11	2462	12.16	12.50	
	12	2467	12.25	12.50	
	13	2472	5.97	6.00	
802.11g 6Mbps	1	2412	Not Required	12.50	Not Required
	6	2437	Not Required	12.50	
	11	2462	Not Required	12.50	
	12	2467	Not Required	12.50	
	13	2472	Not Required	11.00	
802.11n-HT20 MCS0	1	2412	Not Required	12.50	Not Required
	6	2437	Not Required	12.50	
	11	2462	Not Required	12.50	
	12	2467	Not Required	12.50	
	13	2472	Not Required	6.00	
802.11n-HT40 MCS0	3	2422	Not Required	12.50	Not Required
	6	2437	Not Required	12.50	
	9	2452	Not Required	12.50	
	10	2457	Not Required	12.50	
	11	2462	Not Required	12.50	
802.11ac-VHT20 MCS0	1	2412	Not Required	12.50	Not Required
	6	2437	Not Required	12.50	
	11	2462	Not Required	12.50	
	12	2467	Not Required	12.50	
	13	2472	Not Required	6.00	
802.11ac-VHT40 MCS0	3	2422	Not Required	12.50	Not Required
	6	2437	Not Required	12.50	
	9	2452	Not Required	12.50	
	10	2457	Not Required	12.50	
	11	2462	Not Required	12.50	

**【2.4GHz WLAN_Aux_Tablet】**

Mode	Channel	Frequency (MHz)	Aux		
			Average Power (dBm)	Tune-Up Limit	Duty Cycle %
802.11b 1Mbps	1	2412	13.20	14.00	99.51
	6	2437	13.21	14.00	
	11	2462	13.11	14.00	
	12	2467	12.31	12.50	
	13	2472	5.84	6.00	
802.11g 6Mbps	1	2412	Not Required	14.00	Not Required
	6	2437	Not Required	14.00	
	11	2462	Not Required	14.00	
	12	2467	Not Required	14.00	
	13	2472	Not Required	10.50	
802.11n-HT20 MCS0	1	2412	Not Required	14.00	Not Required
	6	2437	Not Required	14.00	
	11	2462	Not Required	14.00	
	12	2467	Not Required	14.00	
	13	2472	Not Required	5.50	
802.11n-HT40 MCS0	3	2422	Not Required	14.00	Not Required
	6	2437	Not Required	14.00	
	9	2452	Not Required	14.00	
	10	2457	Not Required	14.00	
	11	2462	Not Required	13.00	
802.11ac-VHT20 MCS0	1	2412	Not Required	14.00	Not Required
	6	2437	Not Required	14.00	
	11	2462	Not Required	14.00	
	12	2467	Not Required	14.00	
	13	2472	Not Required	5.50	
802.11ac-VHT40 MCS0	3	2422	Not Required	14.00	Not Required
	6	2437	Not Required	14.00	
	9	2452	Not Required	14.00	
	10	2457	Not Required	14.00	
	11	2462	Not Required	13.00	

【2.4GHz WLAN_ MIMO_Laptop】

Mode	Channel	Frequency (MHz)	MIMO(Main)		MIMO(Aux)		MIMO		Duty Cycle %
			Average Power (dBm)	Tune-Up Limit	Average Power (dBm)	Tune-Up Limit	Average Power (dBm)	Tune-Up Limit	
802.11b 1Mbps	1	2412	Not Required	12.50	Not Required	12.50	Not Required	15.50	Not Required
	6	2437	Not Required	12.50	Not Required	12.50	Not Required	15.50	
	11	2462	Not Required	12.50	Not Required	12.50	Not Required	15.50	
	12	2467	Not Required	12.50	Not Required	12.50	Not Required	15.50	
	13	2472	Not Required	6.00	Not Required	6.00	Not Required	9.00	
802.11g 6Mbps	1	2412	Not Required	12.50	Not Required	12.50	Not Required	15.50	Not Required
	6	2437	Not Required	12.50	Not Required	12.50	Not Required	15.50	
	11	2462	Not Required	12.50	Not Required	12.50	Not Required	15.50	
	12	2467	Not Required	12.50	Not Required	12.50	Not Required	15.50	
	13	2472	Not Required	11.00	Not Required	11.00	Not Required	14.00	
802.11n-HT20 MCS0	1	2412	Not Required	12.50	Not Required	12.50	Not Required	15.50	Not Required
	6	2437	Not Required	12.50	Not Required	12.50	Not Required	15.50	
	11	2462	Not Required	12.50	Not Required	12.50	Not Required	15.50	
	12	2467	Not Required	12.50	Not Required	12.50	Not Required	15.50	
	13	2472	Not Required	6.00	Not Required	6.00	Not Required	9.00	
802.11n-HT40 MCS0	3	2422	Not Required	11.00	Not Required	11.00	Not Required	14.00	Not Required
	6	2437	Not Required	11.00	Not Required	11.00	Not Required	14.00	
	9	2452	Not Required	11.00	Not Required	11.00	Not Required	14.00	
	10	2457	Not Required	11.00	Not Required	11.00	Not Required	14.00	
	11	2462	Not Required	11.00	Not Required	11.00	Not Required	14.00	
802.11ac-VHT20 MCS0	1	2412	Not Required	12.50	Not Required	12.50	Not Required	15.50	Not Required
	6	2437	Not Required	12.50	Not Required	12.50	Not Required	15.50	
	11	2462	Not Required	12.50	Not Required	12.50	Not Required	15.50	
	12	2467	Not Required	12.50	Not Required	12.50	Not Required	15.50	
	13	2472	Not Required	6.00	Not Required	6.00	Not Required	9.00	
802.11ac-VHT40 MCS0	3	2422	Not Required	12.50	Not Required	12.50	Not Required	15.50	Not Required
	6	2437	Not Required	12.50	Not Required	12.50	Not Required	15.50	
	9	2452	Not Required	12.50	Not Required	12.50	Not Required	15.50	
	10	2457	Not Required	12.50	Not Required	12.50	Not Required	15.50	
	11	2462	Not Required	12.50	Not Required	12.50	Not Required	15.50	

**【2.4GHz WLAN_ MIMO_Tablet】**

Mode	Channel	Frequency (MHz)	MIMO(Main)		MIMO(Aux)		MIMO		Duty Cycle %
			Average Power (dBm)	Tune-Up Limit	Average Power (dBm)	Tune-Up Limit	Average Power (dBm)	Tune-Up Limit	
802.11b 1Mbps	1	2412	Not Required	14.00	Not Required	14.00	Not Required	17.00	Not Required
	6	2437	Not Required	14.00	Not Required	14.00	Not Required	17.00	
	11	2462	Not Required	14.00	Not Required	14.00	Not Required	17.00	
	12	2467	Not Required	12.50	Not Required	12.50	Not Required	15.50	
	13	2472	Not Required	6.00	Not Required	6.00	Not Required	9.00	
802.11g 6Mbps	1	2412	Not Required	14.00	Not Required	14.00	Not Required	17.00	Not Required
	6	2437	Not Required	14.00	Not Required	14.00	Not Required	17.00	
	11	2462	Not Required	14.00	Not Required	14.00	Not Required	17.00	
	12	2467	Not Required	14.00	Not Required	14.00	Not Required	17.00	
	13	2472	Not Required	10.50	Not Required	10.50	Not Required	13.50	
802.11n-HT20 MCS0	1	2412	Not Required	14.00	Not Required	14.00	Not Required	17.00	Not Required
	6	2437	Not Required	14.00	Not Required	14.00	Not Required	17.00	
	11	2462	Not Required	14.00	Not Required	14.00	Not Required	17.00	
	12	2467	Not Required	14.00	Not Required	14.00	Not Required	17.00	
	13	2472	Not Required	5.50	Not Required	5.50	Not Required	8.50	
802.11n-HT40 MCS0	3	2422	Not Required	12.50	Not Required	12.50	Not Required	15.50	Not Required
	6	2437	Not Required	12.50	Not Required	12.50	Not Required	15.50	
	9	2452	Not Required	12.50	Not Required	12.50	Not Required	15.50	
	10	2457	Not Required	12.50	Not Required	12.50	Not Required	15.50	
802.11ac-VHT20 MCS0	1	2412	Not Required	14.00	Not Required	14.00	Not Required	17.00	Not Required
	6	2437	Not Required	14.00	Not Required	14.00	Not Required	17.00	
	11	2462	Not Required	14.00	Not Required	14.00	Not Required	17.00	
	12	2467	Not Required	14.00	Not Required	14.00	Not Required	17.00	
	13	2472	Not Required	5.50	Not Required	5.50	Not Required	8.50	
802.11ac-VHT40 MCS0	3	2422	Not Required	14.00	Not Required	14.00	Not Required	17.00	Not Required
	6	2437	Not Required	14.00	Not Required	14.00	Not Required	17.00	
	9	2452	Not Required	14.00	Not Required	14.00	Not Required	17.00	
	10	2457	Not Required	14.00	Not Required	14.00	Not Required	17.00	
	11	2462	Not Required	13.00	Not Required	13.00	Not Required	16.00	

【5.2GHz WLAN_Main_Laptop】

Mode	Channel	Frequency (MHz)	Main		Duty Cycle %
			Average Power (dBm)	Tune-Up Limit	
802.11a 6Mbps	36	5180	Not Required	8.50	Not Required
	40	5200	Not Required	8.50	
	44	5220	Not Required	8.50	
	48	5240	Not Required	8.50	
802.11n-HT20 MCS0	36	5180	Not Required	8.50	Not Required
	40	5200	Not Required	8.50	
	44	5220	Not Required	8.50	
	48	5240	Not Required	8.50	
802.11n-HT40 MCS0	38	5190	Not Required	8.50	Not Required
	46	5230	Not Required	8.50	
802.11ac-VHT20 MCS0	36	5180	Not Required	8.50	Not Required
	40	5200	Not Required	8.50	
	44	5220	Not Required	8.50	
	48	5240	Not Required	8.50	
802.11ac-VHT40 MCS0	38	5190	Not Required	8.50	Not Required
	46	5230	Not Required	8.50	
802.11ac-VHT80 MCS0	42	5210	Not Required	8.50	Not Required
802.11ax-HE20 MCS0	36	5180	Not Required	8.50	Not Required
	40	5200	Not Required	8.50	
	44	5220	Not Required	8.50	
	48	5240	Not Required	8.50	
802.11ax-HE40 MCS0	38	5190	Not Required	8.50	Not Required
	46	5230	Not Required	8.50	
802.11ax-HE80 MCS0	42	5210	Not Required	8.50	Not Required

**【5.2GHz WLAN_Main_Tablet】**

Mode	Channel	Frequency (MHz)	Main		
			Average Power (dBm)	Tune-Up Limit	Duty Cycle %
802.11a 6Mbps	36	5180	Not Required	8.50	Not Required
	40	5200	Not Required	8.50	
	44	5220	Not Required	8.50	
	48	5240	Not Required	8.50	
802.11n-HT20 MCS0	36	5180	Not Required	8.50	Not Required
	40	5200	Not Required	8.50	
	44	5220	Not Required	8.50	
	48	5240	Not Required	8.50	
802.11n-HT40 MCS0	38	5190	Not Required	8.50	Not Required
	46	5230	Not Required	8.50	
802.11ac-VHT20 MCS0	36	5180	Not Required	8.50	Not Required
	40	5200	Not Required	8.50	
	44	5220	Not Required	8.50	
	48	5240	Not Required	8.50	
802.11ac-VHT40 MCS0	38	5190	Not Required	8.50	Not Required
	46	5230	Not Required	8.50	
802.11ac-VHT80 MCS0	42	5210	Not Required	8.50	Not Required
802.11ax-HE20 MCS0	36	5180	Not Required	8.50	Not Required
	40	5200	Not Required	8.50	
	44	5220	Not Required	8.50	
	48	5240	Not Required	8.50	
802.11ax-HE40 MCS0	38	5190	Not Required	8.50	Not Required
	46	5230	Not Required	8.50	
802.11ax-HE80 MCS0	42	5210	Not Required	8.50	Not Required

【5.2GHz WLAN_Aux_Laptop】

Mode	Channel	Frequency (MHz)	Aux		
			Average Power (dBm)	Tune-Up Limit	Duty Cycle %
802.11a 6Mbps	36	5180	Not Required	8.50	Not Required
	40	5200	Not Required	8.50	
	44	5220	Not Required	8.50	
	48	5240	Not Required	8.50	
802.11n-HT20 MCS0	36	5180	Not Required	8.50	Not Required
	40	5200	Not Required	8.50	
	44	5220	Not Required	8.50	
	48	5240	Not Required	8.50	
802.11n-HT40 MCS0	38	5190	Not Required	8.50	Not Required
	46	5230	Not Required	8.50	
802.11ac-VHT20 MCS0	36	5180	Not Required	8.50	Not Required
	40	5200	Not Required	8.50	
	44	5220	Not Required	8.50	
	48	5240	Not Required	8.50	
802.11ac-VHT40 MCS0	38	5190	Not Required	8.50	Not Required
	46	5230	Not Required	8.50	
802.11ac-VHT80 MCS0	42	5210	Not Required	8.50	Not Required
802.11ax-HE20 MCS0	36	5180	Not Required	8.50	Not Required
	40	5200	Not Required	8.50	
	44	5220	Not Required	8.50	
	48	5240	Not Required	8.50	
802.11ax-HE40 MCS0	38	5190	Not Required	8.50	Not Required
	46	5230	Not Required	8.50	
802.11ax-HE80 MCS0	42	5210	Not Required	8.50	Not Required

**【5.2GHz WLAN_Aux_Tablet】**

Mode	Channel	Frequency (MHz)	Aux		
			Average Power (dBm)	Tune-Up Limit	Duty Cycle %
802.11a 6Mbps	36	5180	Not Required	8.50	Not Required
	40	5200	Not Required	8.50	
	44	5220	Not Required	8.50	
	48	5240	Not Required	8.50	
802.11n-HT20 MCS0	36	5180	Not Required	8.50	Not Required
	40	5200	Not Required	8.50	
	44	5220	Not Required	8.50	
	48	5240	Not Required	8.50	
802.11n-HT40 MCS0	38	5190	Not Required	8.50	Not Required
	46	5230	Not Required	8.50	
802.11ac-VHT20 MCS0	36	5180	Not Required	8.50	Not Required
	40	5200	Not Required	8.50	
	44	5220	Not Required	8.50	
	48	5240	Not Required	8.50	
802.11ac-VHT40 MCS0	38	5190	Not Required	8.50	Not Required
	46	5230	Not Required	8.50	
802.11ac-VHT80 MCS0	42	5210	Not Required	8.50	Not Required
802.11ax-HE20 MCS0	36	5180	Not Required	8.50	Not Required
	40	5200	Not Required	8.50	
	44	5220	Not Required	8.50	
	48	5240	Not Required	8.50	
802.11ax-HE40 MCS0	38	5190	Not Required	8.50	Not Required
	46	5230	Not Required	8.50	
802.11ax-HE80 MCS0	42	5210	Not Required	8.50	Not Required

【5.2GHz WLAN_ MIMO_Laptop】

Mode	Channel	Frequency (MHz)	MIMO(Main)		MIMO(Aux)		MIMO		Duty Cycle %
			Average Power (dBm)	Tune-Up Limit	Average Power (dBm)	Tune-Up Limit	Average Power (dBm)	Tune-Up Limit	
802.11a 6Mbps	36	5180	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	40	5200	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	44	5220	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	48	5240	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11n-HT20 MCS0	36	5180	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	40	5200	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	44	5220	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	48	5240	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11n-HT40 MCS0	38	5190	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	46	5230	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11ac-VHT20 MCS0	36	5180	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	40	5200	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	44	5220	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	48	5240	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11ac-VHT40 MCS0	38	5190	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	46	5230	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11ac-VHT80 MCS0	42	5210	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
802.11ax-HE20 MCS0	36	5180	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	40	5200	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	44	5220	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	48	5240	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11ax-HE40 MCS0	38	5190	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	46	5230	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11ax-HE80 MCS0	42	5210	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required

**【5.2GHz WLAN_ MIMO_Tablet】**

Mode	Channel	Frequency (MHz)	MIMO(Main)		MIMO(Aux)		MIMO		Duty Cycle %
			Average Power (dBm)	Tune-Up Limit	Average Power (dBm)	Tune-Up Limit	Average Power (dBm)	Tune-Up Limit	
802.11a 6Mbps	36	5180	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	40	5200	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	44	5220	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	48	5240	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11n-HT20 MCS0	36	5180	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	40	5200	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	44	5220	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	48	5240	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11n-HT40 MCS0	38	5190	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	46	5230	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11ac-VHT20 MCS0	36	5180	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	40	5200	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	44	5220	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	48	5240	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11ac-VHT40 MCS0	38	5190	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	46	5230	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11ac-VHT80 MCS0	42	5210	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
802.11ax-HE20 MCS0	36	5180	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	40	5200	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	44	5220	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	48	5240	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11ax-HE40 MCS0	38	5190	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	46	5230	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11ax-HE80 MCS0	42	5210	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required

【5.3GHz WLAN_Main_Laptop】

Mode	Channel	Frequency (MHz)	Main		Duty Cycle %
			Average Power (dBm)	Tune-Up Limit	
802.11a 6Mbps	52	5280	Not Required	8.50	Not Required
	56	5280	Not Required	8.50	
	60	5300	Not Required	8.50	
	64	5320	Not Required	8.50	
802.11n-HT20 MCS0	52	5280	Not Required	8.50	Not Required
	56	5280	Not Required	8.50	
	60	5300	Not Required	8.50	
	64	5320	Not Required	8.50	
802.11n-HT40 MCS0	54	5270	8.38	8.50	95.76
	62	5310	8.45	8.50	
802.11ac-VHT20 MCS0	52	5280	Not Required	8.50	Not Required
	56	5280	Not Required	8.50	
	60	5300	Not Required	8.50	
	64	5320	Not Required	8.50	
802.11ac-VHT40 MCS0	54	5270	Not Required	8.50	Not Required
	62	5310	Not Required	8.50	
802.11ac-VHT80 MCS0	58	5290	8.29	8.50	91.86
802.11ac-VHT160 MCS0	50	5250	Not Required	6.50	Not Required
802.11ax-HE20 MCS0	52	5280	Not Required	8.50	Not Required
	56	5280	Not Required	8.50	
	60	5300	Not Required	8.50	
	64	5320	Not Required	8.50	
802.11ax-HE40 MCS0	54	5270	Not Required	8.50	Not Required
	62	5310	Not Required	8.50	
802.11ax-HE80 MCS0	58	5290	Not Required	8.50	Not Required
802.11ax-HE160 MCS0	50	5250	Not Required	7.00	Not Required

**【5.3GHz WLAN_Main_Tablet】**

Mode	Channel	Frequency (MHz)	Main		
			Average Power (dBm)	Tune-Up Limit	Duty Cycle %
802.11a 6Mbps	52	5260	Not Required	8.50	Not Required
	56	5280	Not Required	8.50	
	60	5300	Not Required	8.50	
	64	5320	Not Required	8.50	
802.11n-HT20 MCS0	52	5260	Not Required	8.50	Not Required
	56	5280	Not Required	8.50	
	60	5300	Not Required	8.50	
	64	5320	Not Required	8.50	
802.11n-HT40 MCS0	54	5270	7.88	8.50	95.76
	62	5310	8.45	8.50	
802.11ac-VHT20 MCS0	52	5260	Not Required	8.50	Not Required
	56	5280	Not Required	8.50	
	60	5300	Not Required	8.50	
	64	5320	Not Required	8.50	
802.11ac-VHT40 MCS0	54	5270	Not Required	8.50	Not Required
	62	5310	Not Required	8.50	
802.11ac-VHT80 MCS0	58	5290	7.86	8.50	91.86
802.11ac-VHT160 MCS0	50	5250	Not Required	6.50	Not Required
802.11ax-HE20 MCS0	52	5260	Not Required	8.50	Not Required
	56	5280	Not Required	8.50	
	60	5300	Not Required	8.50	
	64	5320	Not Required	8.50	
802.11ax-HE40 MCS0	54	5270	Not Required	8.50	Not Required
	62	5310	Not Required	8.50	
802.11ax-HE80 MCS0	58	5290	Not Required	8.50	Not Required
802.11ax-HE160 MCS0	50	5250	Not Required	7.00	Not Required

【5.3GHz WLAN_Aux_Laptop】

Mode	Channel	Frequency (MHz)	Aux		
			Average Power (dBm)	Tune-Up Limit	Duty Cycle %
802.11a 6Mbps	52	5260	Not Required	8.50	Not Required
	56	5280	Not Required	8.50	
	60	5300	Not Required	8.50	
	64	5320	Not Required	8.50	
802.11n-HT20 MCS0	52	5260	Not Required	8.50	Not Required
	56	5280	Not Required	8.50	
	60	5300	Not Required	8.50	
	64	5320	Not Required	8.50	
802.11n-HT40 MCS0	54	5270	8.22	8.50	95.91
	62	5310	8.41	8.50	
802.11ac-VHT20 MCS0	52	5260	Not Required	8.50	Not Required
	56	5280	Not Required	8.50	
	60	5300	Not Required	8.50	
	64	5320	Not Required	8.50	
802.11ac-VHT40 MCS0	54	5270	Not Required	8.50	Not Required
	62	5310	Not Required	8.50	
802.11ac-VHT80 MCS0	58	5290	8.25	8.50	91.59
802.11ac-VHT160 MCS0	50	5250	Not Required	6.50	Not Required
802.11ax-HE20 MCS0	52	5260	Not Required	8.50	Not Required
	56	5280	Not Required	8.50	
	60	5300	Not Required	8.50	
	64	5320	Not Required	8.50	
802.11ax-HE40 MCS0	54	5270	Not Required	8.50	Not Required
	62	5310	Not Required	8.50	
802.11ax-HE80 MCS0	58	5290	Not Required	8.50	Not Required
802.11ax-HE160 MCS0	50	5250	Not Required	7.00	Not Required

**【5.3GHz WLAN_Aux_Tablet】**

Mode	Channel	Frequency (MHz)	Aux		
			Average Power (dBm)	Tune-Up Limit	Duty Cycle %
802.11a 6Mbps	52	5260	Not Required	8.50	Not Required
	56	5280	Not Required	8.50	
	60	5300	Not Required	8.50	
	64	5320	Not Required	8.50	
802.11n-HT20 MCS0	52	5260	Not Required	8.50	Not Required
	56	5280	Not Required	8.50	
	60	5300	Not Required	8.50	
	64	5320	Not Required	8.50	
802.11n-HT40 MCS0	54	5270	8.22	8.50	95.91
	62	5310	8.41	8.50	
802.11ac-VHT20 MCS0	52	5260	Not Required	8.50	Not Required
	56	5280	Not Required	8.50	
	60	5300	Not Required	8.50	
	64	5320	Not Required	8.50	
802.11ac-VHT40 MCS0	54	5270	Not Required	8.50	Not Required
	62	5310	Not Required	8.50	
802.11ac-VHT80 MCS0	58	5290	8.25	8.50	91.59
802.11ac-VHT160 MCS0	50	5250	Not Required	6.50	Not Required
802.11ax-HE20 MCS0	52	5260	Not Required	8.50	Not Required
	56	5280	Not Required	8.50	
	60	5300	Not Required	8.50	
	64	5320	Not Required	8.50	
802.11ax-HE40 MCS0	54	5270	Not Required	8.50	Not Required
	62	5310	Not Required	8.50	
802.11ax-HE80 MCS0	58	5290	Not Required	8.50	Not Required
802.11ax-HE160 MCS0	50	5250	Not Required	7.00	Not Required

【5.3GHz WLAN_ MIMO_Laptop】

Mode	Channel	Frequency (MHz)	MIMO(Main)		MIMO(Aux)		MIMO		Duty Cycle %
			Average Power (dBm)	Tune-Up Limit	Average Power (dBm)	Tune-Up Limit	Average Power (dBm)	Tune-Up Limit	
802.11a 6Mbps	52	5260	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	56	5280	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	60	5300	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	64	5320	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11n-HT20 MCS0	52	5260	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	56	5280	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	60	5300	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	64	5320	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11n-HT40 MCS0	54	5270	7.20	8.50	8.50	8.50	10.91	11.50	95.91
	62	5310	8.10	8.50	7.63	8.50	10.88	11.50	
802.11ac-VHT20 MCS0	52	5260	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	56	5280	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	60	5300	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	64	5320	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11ac-VHT40 MCS0	54	5270	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	62	5310	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11ac-VHT80 MCS0	58	5290	8.50	8.50	8.21	8.50	11.37	11.50	91.59
802.11ac-VHT160 MCS0	50	5250	Not Required	6.50	Not Required	6.50	Not Required	9.50	Not Required
802.11ax-HE20 MCS0	52	5260	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	56	5280	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	60	5300	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	64	5320	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11ax-HE40 MCS0	54	5270	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	62	5310	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11ax-HE80 MCS0	58	5290	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
802.11ax-HE160 MCS0	50	5250	Not Required	7.00	Not Required	7.00	Not Required	10.00	Not Required



【5.3GHz WLAN_ MIMO_Tablet】

Mode	Channel	Frequency (MHz)	MIMO(Main)		MIMO(Aux)		MIMO		Duty Cycle %
			Average Power (dBm)	Tune-Up Limit	Average Power (dBm)	Tune-Up Limit	Average Power (dBm)	Tune-Up Limit	
802.11a 6Mbps	52	5260	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	56	5280	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	60	5300	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	64	5320	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11n-HT20 MCS0	52	5260	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	56	5280	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	60	5300	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	64	5320	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11n-HT40 MCS0	54	5270	7.20	8.50	8.50	8.50	10.91	11.50	95.91
	62	5310	8.10	8.50	7.63	8.50	10.88	11.50	
802.11ac-VHT20 MCS0	52	5260	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	56	5280	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	60	5300	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	64	5320	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11ac-VHT40 MCS0	54	5270	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	62	5310	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11ac-VHT80 MCS0	58	5290	8.50	8.50	8.21	8.50	11.37	11.50	91.59
802.11ac-VHT160 MCS0	50	5250	Not Required	6.50	Not Required	6.50	Not Required	9.50	Not Required
802.11ax-HE20 MCS0	52	5260	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	56	5280	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	60	5300	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	64	5320	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11ax-HE40 MCS0	54	5270	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	62	5310	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11ax-HE80 MCS0	58	5290	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
802.11ax-HE160 MCS0	50	5250	Not Required	7.00	Not Required	7.00	Not Required	10.00	Not Required



【5.5GHz WLAN_Main_Laptop】

			Main		
Mode	Channel	Frequency (MHz)	Average Power (dBm)	Tune-Up Limit	Duty Cycle %
802.11a 6Mbps	100	5500	Not Required	8.50	Not Required
	116	5580	Not Required	8.50	
	124	5620	Not Required	8.50	
	132	5660	Not Required	8.50	
	144	5720	Not Required	8.50	
802.11n-HT20 MCS0	100	5500	Not Required	8.50	Not Required
	116	5580	Not Required	8.50	
	124	5620	Not Required	8.50	
	132	5660	Not Required	8.50	
	144	5720	Not Required	8.50	
802.11n-HT40 MCS0	102	5510	Not Required	8.50	Not Required
	110	5550	Not Required	8.50	
	126	5630	Not Required	8.50	
	134	5670	Not Required	8.50	
	142	5710	Not Required	8.50	
802.11ac-VHT20 MCS0	100	5500	Not Required	8.50	Not Required
	116	5580	Not Required	8.50	
	124	5620	Not Required	8.50	
	132	5660	Not Required	8.50	
	144	5720	Not Required	8.50	
802.11ac-VHT40 MCS0	102	5510	Not Required	8.50	Not Required
	110	5550	Not Required	8.50	
	126	5630	Not Required	8.50	
	134	5670	Not Required	8.50	
	142	5710	Not Required	8.50	
802.11ac-VHT80 MCS0	106	5530	7.17	8.50	91.86
	122	5610	7.23	8.50	
	138	5690	7.33	8.50	
802.11ac-VHT160 MCS0	114	5570	6.93	8.50	86.12
802.11ax-HE20 MCS0	100	5500	Not Required	8.50	Not Required
	116	5580	Not Required	8.50	
	124	5620	Not Required	8.50	
	132	5660	Not Required	8.50	
	144	5720	Not Required	8.50	
802.11ax-HE40 MCS0	102	5510	Not Required	8.50	Not Required
	110	5550	Not Required	8.50	
	126	5630	Not Required	8.50	
	134	5670	Not Required	8.50	
	142	5710	Not Required	8.50	
802.11ax-HE80 MCS0	106	5530	Not Required	8.50	Not Required
	122	5610	Not Required	8.50	
	138	5690	Not Required	8.50	
802.11ax-HE160 MCS0	114	5570	Not Required	8.50	Not Required



【5.5GHz WLAN_Main_Tablet】

Mode	Channel	Frequency (MHz)	Main		
			Average Power (dBm)	Tune-Up Limit	Duty Cycle %
802.11a 6Mbps	100	5500	Not Required	8.50	Not Required
	116	5580	Not Required	8.50	
	124	5620	Not Required	8.50	
	132	5660	Not Required	8.50	
	144	5720	Not Required	8.50	
802.11n-HT20 MCS0	100	5500	Not Required	8.50	Not Required
	116	5580	Not Required	8.50	
	124	5620	Not Required	8.50	
	132	5660	Not Required	8.50	
	144	5720	Not Required	8.50	
802.11n-HT40 MCS0	102	5510	Not Required	8.50	Not Required
	110	5550	Not Required	8.50	
	126	5630	Not Required	8.50	
	134	5670	Not Required	8.50	
	142	5710	Not Required	8.50	
802.11ac-VHT20 MCS0	100	5500	Not Required	8.50	Not Required
	116	5580	Not Required	8.50	
	124	5620	Not Required	8.50	
	132	5660	Not Required	8.50	
	144	5720	Not Required	8.50	
802.11ac-VHT40 MCS0	102	5510	Not Required	8.50	Not Required
	110	5550	Not Required	8.50	
	126	5630	Not Required	8.50	
	134	5670	Not Required	8.50	
	142	5710	Not Required	8.50	
802.11ac-VHT80 MCS0	106	5530	7.67	8.50	91.86
	122	5610	7.73	8.50	
	138	5690	7.83	8.50	
802.11ac-VHT160 MCS0	114	5570	7.43	8.50	86.12
802.11ax-HE20 MCS0	100	5500	Not Required	8.50	Not Required
	116	5580	Not Required	8.50	
	124	5620	Not Required	8.50	
	132	5660	Not Required	8.50	
	144	5720	Not Required	8.50	
802.11ax-HE40 MCS0	102	5510	Not Required	8.50	Not Required
	110	5550	Not Required	8.50	
	126	5630	Not Required	8.50	
	134	5670	Not Required	8.50	
	142	5710	Not Required	8.50	
802.11ax-HE80 MCS0	106	5530	Not Required	8.50	Not Required
	122	5610	Not Required	8.50	
	138	5690	Not Required	8.50	
802.11ax-HE160 MCS0	114	5570	Not Required	8.50	Not Required



【5.5GHz WLAN_Aux_Laptop】

Mode	Channel	Frequency (MHz)	Aux		
			Average Power (dBm)	Tune-Up Limit	Duty Cycle %
802.11a 6Mbps	100	5500	Not Required	8.50	Not Required
	116	5580	Not Required	8.50	
	124	5620	Not Required	8.50	
	132	5660	Not Required	8.50	
	144	5720	Not Required	8.50	
802.11n-HT20 MCS0	100	5500	Not Required	8.50	Not Required
	116	5580	Not Required	8.50	
	124	5620	Not Required	8.50	
	132	5660	Not Required	8.50	
	144	5720	Not Required	8.50	
802.11n-HT40 MCS0	102	5510	Not Required	8.50	Not Required
	110	5550	Not Required	8.50	
	126	5630	Not Required	8.50	
	134	5670	Not Required	8.50	
	142	5710	Not Required	8.50	
802.11ac-VHT20 MCS0	100	5500	Not Required	8.50	Not Required
	116	5580	Not Required	8.50	
	124	5620	Not Required	8.50	
	132	5660	Not Required	8.50	
	144	5720	Not Required	8.50	
802.11ac-VHT40 MCS0	102	5510	Not Required	8.50	Not Required
	110	5550	Not Required	8.50	
	126	5630	Not Required	8.50	
	134	5670	Not Required	8.50	
	142	5710	Not Required	8.50	
802.11ac-VHT80 MCS0	106	5530	6.63	8.50	91.59
	122	5610	7.05	8.50	
	138	5690	6.90	8.50	
802.11ac-VHT160 MCS0	114	5570	6.65	8.50	86.54
802.11ax-HE20 MCS0	100	5500	Not Required	8.50	Not Required
	116	5580	Not Required	8.50	
	124	5620	Not Required	8.50	
	132	5660	Not Required	8.50	
	144	5720	Not Required	8.50	
802.11ax-HE40 MCS0	102	5510	Not Required	8.50	Not Required
	110	5550	Not Required	8.50	
	126	5630	Not Required	8.50	
	134	5670	Not Required	8.50	
	142	5710	Not Required	8.50	
802.11ax-HE80 MCS0	106	5530	Not Required	8.50	Not Required
	122	5610	Not Required	8.50	
	138	5690	Not Required	8.50	
802.11ax-HE160 MCS0	114	5570	Not Required	8.50	Not Required



【5.5GHz WLAN_Aux_Tablet】

Mode	Channel	Frequency (MHz)	Aux		
			Average Power (dBm)	Tune-Up Limit	Duty Cycle %
802.11a 6Mbps	100	5500	Not Required	8.50	Not Required
	116	5580	Not Required	8.50	
	124	5620	Not Required	8.50	
	132	5660	Not Required	8.50	
	144	5720	Not Required	8.50	
802.11n-HT20 MCS0	100	5500	Not Required	8.50	Not Required
	116	5580	Not Required	8.50	
	124	5620	Not Required	8.50	
	132	5660	Not Required	8.50	
	144	5720	Not Required	8.50	
802.11n-HT40 MCS0	102	5510	Not Required	8.50	Not Required
	110	5550	Not Required	8.50	
	126	5630	Not Required	8.50	
	134	5670	Not Required	8.50	
	142	5710	Not Required	8.50	
802.11ac-VHT20 MCS0	100	5500	Not Required	8.50	Not Required
	116	5580	Not Required	8.50	
	124	5620	Not Required	8.50	
	132	5660	Not Required	8.50	
	144	5720	Not Required	8.50	
802.11ac-VHT40 MCS0	102	5510	Not Required	8.50	Not Required
	110	5550	Not Required	8.50	
	126	5630	Not Required	8.50	
	134	5670	Not Required	8.50	
	142	5710	Not Required	8.50	
802.11ac-VHT80 MCS0	106	5530	7.13	8.50	91.59
	122	5610	7.55	8.50	
	138	5690	7.40	8.50	
802.11ac-VHT160 MCS0	114	5570	7.15	8.50	86.54
802.11ax-HE20 MCS0	100	5500	Not Required	8.50	Not Required
	116	5580	Not Required	8.50	
	124	5620	Not Required	8.50	
	132	5660	Not Required	8.50	
	144	5720	Not Required	8.50	
802.11ax-HE40 MCS0	102	5510	Not Required	8.50	Not Required
	110	5550	Not Required	8.50	
	126	5630	Not Required	8.50	
	134	5670	Not Required	8.50	
	142	5710	Not Required	8.50	
802.11ax-HE80 MCS0	106	5530	Not Required	8.50	Not Required
	122	5610	Not Required	8.50	
	138	5690	Not Required	8.50	
802.11ax-HE160 MCS0	114	5570	Not Required	8.50	Not Required



【5.5GHz WLAN_ MIMO_Laptop】

Mode	Channel	Frequency (MHz)	MIMO(Main)		MIMO(Aux)		MIMO		Duty Cycle %
			Average Power (dBm)	Tune-Up Limit	Average Power (dBm)	Tune-Up Limit	Average Power (dBm)	Tune-Up Limit	
802.11a 6Mbps	100	5500	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	116	5580	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	124	5620	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	132	5660	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	144	5720	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11n-HT20 MCS0	100	5500	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	116	5580	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	124	5620	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	132	5660	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	144	5720	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11n-HT40 MCS0	102	5510	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	110	5550	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	126	5630	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	134	5670	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	142	5710	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11ac-VHT20 MCS0	100	5500	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	116	5580	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	124	5620	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	132	5660	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	144	5720	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11ac-VHT40 MCS0	102	5510	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	110	5550	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	126	5630	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	134	5670	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	142	5710	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11ac-VHT80 MCS0	106	5530	8.49	8.50	7.75	8.50	11.15	11.50	91.59
	122	5610	7.61	8.50	8.45	8.50	11.06	11.50	
	138	5690	8.48	8.50	8.10	8.50	11.30	11.50	
802.11ac-VHT160 MCS0	114	5570	7.67	8.50	8.50	8.50	11.12	11.50	86.54
802.11ax-HE20 MCS0	100	5500	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	116	5580	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	124	5620	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	132	5660	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	144	5720	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11ax-HE40 MCS0	102	5510	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	110	5550	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	126	5630	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	134	5670	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	142	5710	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11ax-HE80 MCS0	106	5530	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	122	5610	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	138	5690	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11ax-HE160 MCS0	114	5570	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required



【5.5GHz WLAN_ MIMO_Tablet】

Mode	Channel	Frequency (MHz)	MIMO(Main)		MIMO(Aux)		MIMO		Duty Cycle %
			Average Power (dBm)	Tune-Up Limit	Average Power (dBm)	Tune-Up Limit	Average Power (dBm)	Tune-Up Limit	
802.11a 6Mbps	100	5500	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	116	5580	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	124	5620	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	132	5660	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	144	5720	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11n-HT20 MCS0	100	5500	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	116	5580	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	124	5620	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	132	5660	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	144	5720	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11n-HT40 MCS0	102	5510	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	110	5550	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	126	5630	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	134	5670	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	142	5710	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11ac-VHT20 MCS0	100	5500	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	116	5580	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	124	5620	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	132	5660	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	144	5720	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11ac-VHT40 MCS0	102	5510	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	110	5550	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	126	5630	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	134	5670	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	142	5710	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11ac-VHT80 MCS0	106	5530	8.26	8.50	7.50	8.50	10.91	11.50	91.59
	122	5610	7.38	8.50	8.50	8.50	10.99	11.50	
	138	5690	8.35	8.50	7.85	8.50	11.12	11.50	
802.11ac-VHT160 MCS0	114	5570	6.97	8.50	8.07	8.50	10.57	11.50	86.54
802.11ax-HE20 MCS0	100	5500	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	116	5580	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	124	5620	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	132	5660	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	144	5720	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11ax-HE40 MCS0	102	5510	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	110	5550	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	126	5630	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	134	5670	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	142	5710	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11ax-HE80 MCS0	106	5530	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required
	122	5610	Not Required	8.50	Not Required	8.50	Not Required	11.50	
	138	5690	Not Required	8.50	Not Required	8.50	Not Required	11.50	
802.11ax-HE160 MCS0	114	5570	Not Required	8.50	Not Required	8.50	Not Required	11.50	Not Required

**【5.8GHz WLAN_Main_Laptop】**

Mode	Channel	Frequency (MHz)	Main		
			Average Power (dBm)	Tune-Up Limit	Duty Cycle %
802.11a 6Mbps	149	5745	Not Required	10.50	Not Required
	157	5785	Not Required	10.50	
	165	5825	Not Required	10.50	
802.11n-HT20 MCS0	149	5745	Not Required	10.50	Not Required
	157	5785	Not Required	10.50	
	165	5825	Not Required	10.50	
802.11n-HT40 MCS0	151	5755	9.83	10.50	95.76
	159	5795	9.62	10.50	
802.11ac-VHT20 MCS0	149	5745	Not Required	10.50	Not Required
	157	5785	Not Required	10.50	
	165	5825	Not Required	10.50	
802.11ac-VHT40 MCS0	151	5755	Not Required	10.50	Not Required
	159	5795	Not Required	10.50	
802.11ac-VHT80 MCS0	155	5775	9.50	10.50	91.86
802.11ax-HE20 MCS0	149	5745	Not Required	10.50	Not Required
	157	5785	Not Required	10.50	
	165	5825	Not Required	10.50	
802.11ax-HE40 MCS0	151	5755	Not Required	10.50	Not Required
	159	5795	Not Required	10.50	
802.11ax-HE80 MCS0	155	5775	Not Required	10.50	Not Required

【5.8GHz WLAN_Main_Tablet】

Mode	Channel	Frequency (MHz)	Main		
			Average Power (dBm)	Tune-Up Limit	Duty Cycle %
802.11a 6Mbps	149	5745	Not Required	9.50	Not Required
	157	5785	Not Required	9.50	
	165	5825	Not Required	9.50	
802.11n-HT20 MCS0	149	5745	Not Required	9.50	Not Required
	157	5785	Not Required	9.50	
	165	5825	Not Required	9.50	
802.11n-HT40 MCS0	151	5755	9.33	9.50	95.76
	159	5795	9.45	9.50	
802.11ac-VHT20 MCS0	149	5745	Not Required	9.50	Not Required
	157	5785	Not Required	9.50	
	165	5825	Not Required	9.50	
802.11ac-VHT40 MCS0	151	5755	Not Required	9.50	Not Required
	159	5795	Not Required	9.50	
802.11ac-VHT80 MCS0	155	5775	9.44	9.50	91.86
802.11ax-HE20 MCS0	149	5745	Not Required	9.50	Not Required
	157	5785	Not Required	9.50	
	165	5825	Not Required	9.50	
802.11ax-HE40 MCS0	151	5755	Not Required	9.50	Not Required
	159	5795	Not Required	9.50	
802.11ax-HE80 MCS0	155	5775	Not Required	9.50	Not Required

**【5.8GHz WLAN_Aux_Laptop】**

Mode	Channel	Frequency (MHz)	Aux		
			Average Power (dBm)	Tune-Up Limit	Duty Cycle %
802.11a 6Mbps	149	5745	Not Required	10.50	Not Required
	157	5785	Not Required	10.50	
	165	5825	Not Required	10.50	
802.11n-HT20 MCS0	149	5745	Not Required	10.50	Not Required
	157	5785	Not Required	10.50	
	165	5825	Not Required	10.50	
802.11n-HT40 MCS0	151	5755	9.22	10.50	95.91
	159	5795	9.02	10.50	
802.11ac-VHT20 MCS0	149	5745	Not Required	10.50	Not Required
	157	5785	Not Required	10.50	
	165	5825	Not Required	10.50	
802.11ac-VHT40 MCS0	151	5755	Not Required	10.50	Not Required
	159	5795	Not Required	10.50	
802.11ac-VHT80 MCS0	155	5775	9.15	10.50	91.59
802.11ax-HE20 MCS0	149	5745	Not Required	10.50	Not Required
	157	5785	Not Required	10.50	
	165	5825	Not Required	10.50	
802.11ax-HE40 MCS0	151	5755	Not Required	10.50	Not Required
	159	5795	Not Required	10.50	
802.11ax-HE80 MCS0	155	5775	Not Required	10.50	Not Required

【5.8GHz WLAN_Aux_Tablet】

Mode	Channel	Frequency (MHz)	Aux		
			Average Power (dBm)	Tune-Up Limit	Duty Cycle %
802.11a 6Mbps	149	5745	Not Required	9.50	Not Required
	157	5785	Not Required	9.50	
	165	5825	Not Required	9.50	
802.11n-HT20 MCS0	149	5745	Not Required	9.50	Not Required
	157	5785	Not Required	9.50	
	165	5825	Not Required	9.50	
802.11n-HT40 MCS0	151	5755	9.22	9.50	95.91
	159	5795	9.02	9.50	
802.11ac-VHT20 MCS0	149	5745	Not Required	9.50	Not Required
	157	5785	Not Required	9.50	
	165	5825	Not Required	9.50	
802.11ac-VHT40 MCS0	151	5755	Not Required	9.50	Not Required
	159	5795	Not Required	9.50	
802.11ac-VHT80 MCS0	155	5775	9.15	9.50	91.59
802.11ax-HE20 MCS0	149	5745	Not Required	9.50	Not Required
	157	5785	Not Required	9.50	
	165	5825	Not Required	9.50	
802.11ax-HE40 MCS0	151	5755	Not Required	9.50	Not Required
	159	5795	Not Required	9.50	
802.11ax-HE80 MCS0	155	5775	Not Required	9.50	Not Required

**【5.8GHz WLAN_ MIMO_Laptop】**

Mode	Channel	Frequency (MHz)	MIMO(Main)		MIMO(Aux)		MIMO		Duty Cycle %
			Average Power (dBm)	Tune-Up Limit	Average Power (dBm)	Tune-Up Limit	Average Power (dBm)	Tune-Up Limit	
802.11a 6Mbps	149	5745	Not Required	10.50	Not Required	10.50	Not Required	13.50	Not Required
	157	5785	Not Required	10.50	Not Required	10.50	Not Required	13.50	
	165	5825	Not Required	10.50	Not Required	10.50	Not Required	13.50	
802.11n-HT20 MCS0	149	5745	Not Required	10.50	Not Required	10.50	Not Required	13.50	Not Required
	157	5785	Not Required	10.50	Not Required	10.50	Not Required	13.50	
	165	5825	Not Required	10.50	Not Required	10.50	Not Required	13.50	
802.11n-HT40 MCS0	151	5755	9.60	10.50	9.90	10.50	12.76	13.50	95.76
	159	5795	9.54	10.50	9.93	10.50	12.75	13.50	
802.11ac-VHT20 MCS0	149	5745	Not Required	10.50	Not Required	10.50	Not Required	13.50	Not Required
	157	5785	Not Required	10.50	Not Required	10.50	Not Required	13.50	
	165	5825	Not Required	10.50	Not Required	10.50	Not Required	13.50	
802.11ac-VHT40 MCS0	151	5755	Not Required	10.50	Not Required	10.50	Not Required	13.50	Not Required
	159	5795	Not Required	10.50	Not Required	10.50	Not Required	13.50	
802.11ac-VHT80 MCS0	155	5775	9.87	10.50	10.00	10.50	12.95	13.50	91.86
802.11ax-HE20 MCS0	149	5745	Not Required	10.50	Not Required	10.50	Not Required	13.50	Not Required
	157	5785	Not Required	10.50	Not Required	10.50	Not Required	13.50	
	165	5825	Not Required	10.50	Not Required	10.50	Not Required	13.50	
802.11ax-HE40 MCS0	151	5755	Not Required	10.50	Not Required	10.50	Not Required	13.50	Not Required
	159	5795	Not Required	10.50	Not Required	10.50	Not Required	13.50	
802.11ax-HE80 MCS0	155	5775	Not Required	10.50	Not Required	10.50	Not Required	13.50	Not Required

【5.8GHz WLAN_ MIMO_Tablet】

Mode	Channel	Frequency (MHz)	MIMO(Main)		MIMO(Aux)		MIMO		Duty Cycle %
			Average Power (dBm)	Tune-Up Limit	Average Power (dBm)	Tune-Up Limit	Average Power (dBm)	Tune-Up Limit	
802.11a 6Mbps	149	5745	Not Required	9.50	Not Required	9.50	Not Required	12.50	Not Required
	157	5785	Not Required	9.50	Not Required	9.50	Not Required	12.50	
	165	5825	Not Required	9.50	Not Required	9.50	Not Required	12.50	
802.11n-HT20 MCS0	149	5745	Not Required	9.50	Not Required	9.50	Not Required	12.50	Not Required
	157	5785	Not Required	9.50	Not Required	9.50	Not Required	12.50	
	165	5825	Not Required	9.50	Not Required	9.50	Not Required	12.50	
802.11n-HT40 MCS0	151	5755	8.60	9.50	8.90	9.50	11.76	12.50	95.76
	159	5795	8.54	9.50	8.93	9.50	11.75	12.50	
802.11ac-VHT20 MCS0	149	5745	Not Required	9.50	Not Required	9.50	Not Required	12.50	Not Required
	157	5785	Not Required	9.50	Not Required	9.50	Not Required	12.50	
	165	5825	Not Required	9.50	Not Required	9.50	Not Required	12.50	
802.11ac-VHT40 MCS0	151	5755	Not Required	9.50	Not Required	9.50	Not Required	12.50	Not Required
	159	5795	Not Required	9.50	Not Required	9.50	Not Required	12.50	
802.11ac-VHT80 MCS0	155	5775	8.87	9.50	9.00	9.50	11.95	12.50	91.86
802.11ax-HE20 MCS0	149	5745	Not Required	9.50	Not Required	9.50	Not Required	12.50	Not Required
	157	5785	Not Required	9.50	Not Required	9.50	Not Required	12.50	
	165	5825	Not Required	9.50	Not Required	9.50	Not Required	12.50	
802.11ax-HE40 MCS0	151	5755	Not Required	9.50	Not Required	9.50	Not Required	12.50	Not Required
	159	5795	Not Required	9.50	Not Required	9.50	Not Required	12.50	
802.11ax-HE80 MCS0	155	5775	Not Required	9.50	Not Required	9.50	Not Required	12.50	Not Required

**【5.9GHz WLAN UNII 4_Main_Laptop】**

Mode	Channel	Frequency (MHz)	Main		
			Average Power (dBm)	Tune-Up Limit	Duty Cycle %
802.11a 6Mbps	169	5845	Not Required	10.50	Not Required
	173	5865	Not Required	10.50	
	177	5885	Not Required	10.50	
802.11n-HT20 MCS0	169	5845	Not Required	10.50	Not Required
	173	5865	Not Required	10.50	
	177	5885	Not Required	10.50	
802.11n-HT40 MCS0	167	5835	Not Required	10.50	Not Required
	175	5875	Not Required	10.50	
802.11ac-VHT20 MCS0	169	5845	Not Required	10.50	Not Required
	173	5865	Not Required	10.50	
	177	5885	Not Required	10.50	
802.11ac-VHT40 MCS0	167	5835	Not Required	10.50	Not Required
	175	5875	Not Required	10.50	
802.11ac-VHT80 MCS0	171	5855	9.53	10.50	91.86
802.11ac-VHT160 MCS0	163	5815	9.67	10.50	86.12
802.11ax-HE20 MCS0	169	5845	Not Required	10.50	Not Required
	173	5865	Not Required	10.50	
	177	5885	Not Required	10.50	
802.11ax-HE40 MCS0	167	5835	Not Required	10.50	Not Required
	175	5875	Not Required	10.50	
802.11ax-HE80 MCS0	171	5855	Not Required	10.50	Not Required
802.11ax-HE160 MCS0	163	5815	Not Required	10.50	Not Required

【5.9GHz WLAN UNII 4_Main_Tablet】

Mode	Channel	Frequency (MHz)	Main		
			Average Power (dBm)	Tune-Up Limit	Duty Cycle %
802.11a 6Mbps	169	5845	Not Required	9.50	Not Required
	173	5865	Not Required	9.50	
	177	5885	Not Required	9.50	
802.11n-HT20 MCS0	169	5845	Not Required	9.50	Not Required
	173	5865	Not Required	9.50	
	177	5885	Not Required	9.50	
802.11n-HT40 MCS0	167	5835	Not Required	9.50	Not Required
	175	5875	Not Required	9.50	
802.11ac-VHT20 MCS0	169	5845	Not Required	9.50	Not Required
	173	5865	Not Required	9.50	
	177	5885	Not Required	9.50	
802.11ac-VHT40 MCS0	167	5835	Not Required	9.50	Not Required
	175	5875	Not Required	9.50	
802.11ac-VHT80 MCS0	171	5855	9.32	9.50	91.86
802.11ac-VHT160 MCS0	163	5815	9.11	9.50	86.12
802.11ax-HE20 MCS0	169	5845	Not Required	9.50	Not Required
	173	5865	Not Required	9.50	
	177	5885	Not Required	9.50	
802.11ax-HE40 MCS0	167	5835	Not Required	9.50	Not Required
	175	5875	Not Required	9.50	
802.11ax-HE80 MCS0	171	5855	Not Required	9.50	Not Required
802.11ax-HE160 MCS0	163	5815	Not Required	9.50	Not Required

**【5.9GHz WLAN UNII 4_Aux_Laptop】**

Mode	Channel	Frequency (MHz)	Aux		
			Average Power (dBm)	Tune-Up Limit	Duty Cycle %
802.11a 6Mbps	169	5845	Not Required	10.50	Not Required
	173	5865	Not Required	10.50	
	177	5885	Not Required	10.50	
802.11n-HT20 MCS0	169	5845	Not Required	10.50	Not Required
	173	5865	Not Required	10.50	
	177	5885	Not Required	10.50	
802.11n-HT40 MCS0	167	5835	Not Required	10.50	Not Required
	175	5875	Not Required	10.50	
802.11ac-VHT20 MCS0	169	5845	Not Required	10.50	Not Required
	173	5865	Not Required	10.50	
	177	5885	Not Required	10.50	
802.11ac-VHT40 MCS0	167	5835	Not Required	10.50	Not Required
	175	5875	Not Required	10.50	
802.11ac-VHT80 MCS0	171	5855	9.24	10.50	91.59
802.11ac-VHT160 MCS0	163	5815	9.00	10.50	86.54
802.11ax-HE20 MCS0	169	5845	Not Required	10.50	Not Required
	173	5865	Not Required	10.50	
	177	5885	Not Required	10.50	
802.11ax-HE40 MCS0	167	5835	Not Required	10.50	Not Required
	175	5875	Not Required	10.50	
802.11ax-HE80 MCS0	171	5855	Not Required	10.50	Not Required
802.11ax-HE160 MCS0	163	5815	Not Required	10.50	Not Required

【5.9GHz WLAN UNII 4_Aux_Tablet】

Mode	Channel	Frequency (MHz)	Aux		
			Average Power (dBm)	Tune-Up Limit	Duty Cycle %
802.11a 6Mbps	169	5845	Not Required	9.50	Not Required
	173	5865	Not Required	9.50	
	177	5885	Not Required	9.50	
802.11n-HT20 MCS0	169	5845	Not Required	9.50	Not Required
	173	5865	Not Required	9.50	
	177	5885	Not Required	9.50	
802.11n-HT40 MCS0	167	5835	Not Required	9.50	Not Required
	175	5875	Not Required	9.50	
802.11ac-VHT20 MCS0	169	5845	Not Required	9.50	Not Required
	173	5865	Not Required	9.50	
	177	5885	Not Required	9.50	
802.11ac-VHT40 MCS0	167	5835	Not Required	9.50	Not Required
	175	5875	Not Required	9.50	
802.11ac-VHT80 MCS0	171	5855	9.24	9.50	91.59
802.11ac-VHT160 MCS0	163	5815	9.08	9.50	86.54
802.11ax-HE20 MCS0	169	5845	Not Required	9.50	Not Required
	173	5865	Not Required	9.50	
	177	5885	Not Required	9.50	
802.11ax-HE40 MCS0	167	5835	Not Required	9.50	Not Required
	175	5875	Not Required	9.50	
802.11ax-HE80 MCS0	171	5855	Not Required	9.50	Not Required
802.11ax-HE160 MCS0	163	5815	Not Required	9.50	Not Required

**【5.9GHz WLAN UNII 4_ MIMO_Laptop】**

Mode	Channel	Frequency (MHz)	MIMO(Main)		MIMO(Aux)		MIMO		Duty Cycle %
			Average Power (dBm)	Tune-Up Limit	Average Power (dBm)	Tune-Up Limit	Average Power (dBm)	Tune-Up Limit	
802.11a 6Mbps	169	5845	Not Required	10.50	Not Required	10.50	Not Required	13.50	Not Required
	173	5865	Not Required	10.50	Not Required	10.50	Not Required	13.50	
	177	5885	Not Required	10.50	Not Required	10.50	Not Required	13.50	
802.11n-HT20 MCS0	169	5845	Not Required	10.50	Not Required	10.50	Not Required	13.50	Not Required
	173	5865	Not Required	10.50	Not Required	10.50	Not Required	13.50	
	177	5885	Not Required	10.50	Not Required	10.50	Not Required	13.50	
802.11n-HT40 MCS0	167	5835	Not Required	10.50	Not Required	10.50	Not Required	13.50	Not Required
	175	5875	Not Required	10.50	Not Required	10.50	Not Required	13.50	
802.11ac-VHT20 MCS0	169	5845	Not Required	10.50	Not Required	10.50	Not Required	13.50	Not Required
	173	5865	Not Required	10.50	Not Required	10.50	Not Required	13.50	
	177	5885	Not Required	10.50	Not Required	10.50	Not Required	13.50	
802.11ac-VHT40 MCS0	167	5835	Not Required	10.50	Not Required	10.50	Not Required	13.50	Not Required
	175	5875	Not Required	10.50	Not Required	10.50	Not Required	13.50	
802.11ac-VHT80 MCS0	171	5855	9.38	10.50	10.40	10.50	12.93	13.50	91.59
802.11ac-VHT160 MCS0	163	5815	9.40	10.50	10.00	10.50	12.72	13.50	86.54
802.11ax-HE20 MCS0	169	5845	Not Required	10.50	Not Required	10.50	Not Required	13.50	Not Required
	173	5865	Not Required	10.50	Not Required	10.50	Not Required	13.50	
	177	5885	Not Required	10.50	Not Required	10.50	Not Required	13.50	
802.11ax-HE40 MCS0	167	5835	Not Required	10.50	Not Required	10.50	Not Required	13.50	Not Required
	175	5875	Not Required	10.50	Not Required	10.50	Not Required	13.50	
802.11ax-HE80 MCS0	171	5855	Not Required	10.50	Not Required	10.50	Not Required	13.50	Not Required
802.11ax-HE160 MCS0	163	5815	Not Required	10.50	Not Required	10.50	Not Required	13.50	Not Required

【5.9GHz WLAN UNII 4_ MIMO_Tablet】

Mode	Channel	Frequency (MHz)	MIMO(Main)		MIMO(Aux)		MIMO		Duty Cycle %
			Average Power (dBm)	Tune-Up Limit	Average Power (dBm)	Tune-Up Limit	Average Power (dBm)	Tune-Up Limit	
802.11a 6Mbps	169	5845	Not Required	9.50	Not Required	9.50	Not Required	12.50	Not Required
	173	5865	Not Required	9.50	Not Required	9.50	Not Required	12.50	
	177	5885	Not Required	9.50	Not Required	9.50	Not Required	12.50	
802.11n-HT20 MCS0	169	5845	Not Required	9.50	Not Required	9.50	Not Required	12.50	Not Required
	173	5865	Not Required	9.50	Not Required	9.50	Not Required	12.50	
	177	5885	Not Required	9.50	Not Required	9.50	Not Required	12.50	
802.11n-HT40 MCS0	167	5835	Not Required	9.50	Not Required	9.50	Not Required	12.50	Not Required
	175	5875	Not Required	9.50	Not Required	9.50	Not Required	12.50	
802.11ac-VHT20 MCS0	169	5845	Not Required	9.50	Not Required	9.50	Not Required	12.50	Not Required
	173	5865	Not Required	9.50	Not Required	9.50	Not Required	12.50	
	177	5885	Not Required	9.50	Not Required	9.50	Not Required	12.50	
802.11ac-VHT40 MCS0	167	5835	Not Required	9.50	Not Required	9.50	Not Required	12.50	Not Required
	175	5875	Not Required	9.50	Not Required	9.50	Not Required	12.50	
802.11ac-VHT80 MCS0	171	5855	8.38	9.50	9.40	9.50	11.93	12.50	91.59
802.11ac-VHT160 MCS0	163	5815	8.40	9.50	9.00	9.50	11.72	12.50	86.12
802.11ax-HE20 MCS0	169	5845	Not Required	9.50	Not Required	9.50	Not Required	12.50	Not Required
	173	5865	Not Required	9.50	Not Required	9.50	Not Required	12.50	
	177	5885	Not Required	9.50	Not Required	9.50	Not Required	12.50	
802.11ax-HE40 MCS0	167	5835	Not Required	9.50	Not Required	9.50	Not Required	12.50	Not Required
	175	5875	Not Required	9.50	Not Required	9.50	Not Required	12.50	
802.11ax-HE80 MCS0	171	5855	Not Required	9.50	Not Required	9.50	Not Required	12.50	Not Required
802.11ax-HE160 MCS0	163	5815	Not Required	9.50	Not Required	9.50	Not Required	12.50	Not Required

**【6GHz WLAN_SP_Main_Laptop】**

Mode	Channel	Frequency (MHz)	Main		
			Average Power (dBm)	Tune-Up Limit	Duty Cycle %
802.11ax-HE20 MCS0	1	5955	Not Required	9.00	Not Required
	57	6235	Not Required	9.00	
	173	6815	Not Required	9.00	
802.11ax-HE40 MCS0	3	5965	Not Required	9.00	Not Required
	59	6245	Not Required	9.00	
	171	6805	Not Required	9.00	
802.11ax-HE80 MCS0	7	5985	8.55	9.00	92.24
	71	6305	8.88	9.00	
	167	6785	8.62	9.00	
802.11ax-HE160 MCS0	15	6025	8.73	9.00	87.34
	47	6185	8.51	9.00	
	143	6665	8.85	9.00	

【6GHz WLAN_LPI_Main_Laptop】

Mode	Channel	Frequency (MHz)	Main		
			Average Power (dBm)	Tune-Up Limit	Duty Cycle %
802.11ax-HE20 MCS0	1	5955	Not Required	7.50	Not Required
	57	6235	Not Required	7.00	
	113	6515	Not Required	7.00	
	173	6815	Not Required	7.00	
	233	7115	Not Required	7.50	
802.11ax-HE40 MCS0	3	5965	Not Required	9.00	Not Required
	59	6245	Not Required	9.00	
	107	6485	Not Required	9.00	
	171	6805	Not Required	9.00	
	227	7085	Not Required	10.50	
802.11ax-HE80 MCS0	7	5985	8.55	9.00	92.24
	71	6305	8.88	9.00	
	119	6545	8.92	9.00	
	167	6785	8.62	9.00	
	215	7025	9.51	10.50	
802.11ax-HE160 MCS0	15	6025	8.73	9.00	87.34
	47	6185	8.51	9.00	
	111	6505	8.81	9.00	
	143	6665	8.85	9.00	
	207	6985	10.38	10.50	

【6GHz WLAN_VLP_Main_Laptop】

Mode	Channel	Frequency (MHz)	Main		
			Average Power (dBm)	Tune-Up Limit	Duty Cycle %
802.11ax-HE20 MCS0	1	5955	Not Required	2.50	Not Required
	57	6235	Not Required	3.00	
	113	6515	Not Required	3.00	
	173	6815	Not Required	3.00	
	233	7115	Not Required	3.00	
802.11ax-HE40 MCS0	3	5965	Not Required	6.00	Not Required
	59	6245	Not Required	6.00	
	107	6485	Not Required	6.00	
	171	6805	Not Required	6.00	
	227	7085	Not Required	6.00	
802.11ax-HE80 MCS0	7	5985	Not Required	8.50	Not Required
	71	6305	Not Required	8.50	
	119	6545	Not Required	8.50	
	167	6785	Not Required	8.50	
	215	7025	Not Required	8.50	
802.11ax-HE160 MCS0	15	6025	Not Required	8.50	Not Required
	47	6185	Not Required	8.50	
	111	6505	Not Required	8.50	
	143	6665	Not Required	8.50	
	207	6985	Not Required	8.50	

**【6GHz WLAN_SP_Main_Tablet】**

Mode	Channel	Frequency (MHz)	Main		
			Average Power (dBm)	Tune-Up Limit	Duty Cycle %
802.11ax-HE20 MCS0	1	5955	Not Required	10.00	Not Required
	57	6235	Not Required	10.00	
	173	6815	Not Required	12.00	
802.11ax-HE40 MCS0	3	5965	Not Required	10.00	Not Required
	59	6245	Not Required	10.00	
	171	6805	Not Required	12.00	
802.11ax-HE80 MCS0	7	5985	9.55	10.00	92.24
	71	6305	9.51	10.00	
	167	6785	11.62	12.00	
802.11ax-HE160 MCS0	15	6025	9.75	10.00	87.34
	47	6185	9.55	10.00	
	143	6665	11.64	12.00	

【6GHz WLAN_LPI_Main_Tablet】

Mode	Channel	Frequency (MHz)	Main		
			Average Power (dBm)	Tune-Up Limit	Duty Cycle %
802.11ax-HE20 MCS0	1	5955	Not Required	7.50	Not Required
	57	6235	Not Required	7.00	
	113	6515	Not Required	7.00	
	173	6815	Not Required	7.00	
	233	7115	Not Required	7.50	
802.11ax-HE40 MCS0	3	5965	Not Required	10.00	Not Required
	59	6245	Not Required	10.00	
	107	6485	Not Required	10.00	
	171	6805	Not Required	10.00	
	227	7085	Not Required	10.50	
802.11ax-HE80 MCS0	7	5985	9.55	10.00	92.24
	71	6305	9.51	10.00	
	119	6545	9.28	11.50	
	167	6785	11.62	12.00	
	215	7025	11.51	12.00	
802.11ax-HE160 MCS0	15	6025	9.75	10.00	87.34
	47	6185	9.55	10.00	
	111	6505	11.42	11.50	
	143	6665	11.64	12.00	
	207	6985	11.89	12.00	

【6GHz WLAN_VLP_Main_Tablet】

Mode	Channel	Frequency (MHz)	Main		
			Average Power (dBm)	Tune-Up Limit	Duty Cycle %
802.11ax-HE20 MCS0	1	5955	Not Required	2.50	Not Required
	57	6235	Not Required	3.00	
	113	6515	Not Required	3.00	
	173	6815	Not Required	3.00	
	233	7115	Not Required	3.00	
802.11ax-HE40 MCS0	3	5965	Not Required	6.00	Not Required
	59	6245	Not Required	6.00	
	107	6485	Not Required	6.00	
	171	6805	Not Required	6.00	
	227	7085	Not Required	6.00	
802.11ax-HE80 MCS0	7	5985	Not Required	8.50	Not Required
	71	6305	Not Required	8.50	
	119	6545	Not Required	8.50	
	167	6785	Not Required	8.50	
	215	7025	Not Required	8.50	
802.11ax-HE160 MCS0	15	6025	Not Required	8.50	Not Required
	47	6185	Not Required	8.50	
	111	6505	Not Required	8.50	
	143	6665	Not Required	8.50	
	207	6985	Not Required	8.50	

**【6GHz WLAN_SP_Aux_Laptop】**

Mode	Channel	Frequency (MHz)	Aux		
			Average Power (dBm)	Tune-Up Limit	Duty Cycle %
802.11ax-HE20 MCS0	1	5955	Not Required	9.00	Not Required
	57	6235	Not Required	9.00	
	173	6815	Not Required	9.00	
802.11ax-HE40 MCS0	3	5965	Not Required	9.00	Not Required
	59	6245	Not Required	9.00	
	171	6805	Not Required	9.00	
802.11ax-HE80 MCS0	7	5985	8.38	9.00	94.24
	71	6305	8.30	9.00	
	167	6785	8.55	9.00	
802.11ax-HE160 MCS0	15	6025	8.67	9.00	87.72
	47	6185	8.70	9.00	
	143	6665	8.75	9.00	

【6GHz WLAN_LPI_Aux_Laptop】

Mode	Channel	Frequency (MHz)	Aux		
			Average Power (dBm)	Tune-Up Limit	Duty Cycle %
802.11ax-HE20 MCS0	1	5955	Not Required	7.50	Not Required
	57	6235	Not Required	7.00	
	113	6515	Not Required	7.00	
	173	6815	Not Required	7.00	
	233	7115	Not Required	7.50	
802.11ax-HE40 MCS0	3	5965	Not Required	9.00	Not Required
	59	6245	Not Required	9.00	
	107	6485	Not Required	9.00	
	171	6805	Not Required	9.00	
	227	7085	Not Required	10.50	
802.11ax-HE80 MCS0	7	5985	8.38	9.00	94.24
	71	6305	8.30	9.00	
	119	6545	8.03	9.00	
	167	6785	8.55	9.00	
	215	7025	9.40	10.50	
802.11ax-HE160 MCS0	15	6025	8.67	9.00	87.72
	47	6185	8.70	9.00	
	111	6505	8.85	9.00	
	143	6665	8.75	9.00	
	207	6985	10.25	10.50	

【6GHz WLAN_VLP_Aux_Laptop】

Mode	Channel	Frequency (MHz)	Aux		
			Average Power (dBm)	Tune-Up Limit	Duty Cycle %
802.11ax-HE20 MCS0	1	5955	Not Required	2.50	Not Required
	57	6235	Not Required	3.00	
	113	6515	Not Required	3.00	
	173	6815	Not Required	3.00	
	233	7115	Not Required	3.00	
802.11ax-HE40 MCS0	3	5965	Not Required	6.00	Not Required
	59	6245	Not Required	6.00	
	107	6485	Not Required	6.00	
	171	6805	Not Required	6.00	
	227	7085	Not Required	6.00	
802.11ax-HE80 MCS0	7	5985	Not Required	8.50	Not Required
	71	6305	Not Required	8.50	
	119	6545	Not Required	8.50	
	167	6785	Not Required	8.50	
	215	7025	Not Required	8.50	
802.11ax-HE160 MCS0	15	6025	Not Required	8.50	Not Required
	47	6185	Not Required	8.50	
	111	6505	Not Required	8.50	
	143	6665	Not Required	8.50	
	207	6985	Not Required	8.50	

**【6GHz WLAN_SP_Aux_Tablet】**

Mode	Channel	Frequency (MHz)	Aux		
			Average Power (dBm)	Tune-Up Limit	Duty Cycle %
802.11ax-HE20 MCS0	1	5955	Not Required	10.00	Not Required
	57	6235	Not Required	10.00	
	173	6815	Not Required	12.00	
802.11ax-HE40 MCS0	3	5965	Not Required	10.00	Not Required
	59	6245	Not Required	10.00	
	171	6805	Not Required	12.00	
802.11ax-HE80 MCS0	7	5985	9.75	10.00	92.24
	71	6305	9.88	10.00	
	167	6785	11.63	12.00	
802.11ax-HE160 MCS0	15	6025	9.08	10.00	87.72
	47	6185	9.18	10.00	
	143	6665	11.64	12.00	

【6GHz WLAN_LPI_Aux_Tablet】

Mode	Channel	Frequency (MHz)	Aux		
			Average Power (dBm)	Tune-Up Limit	Duty Cycle %
802.11ax-HE20 MCS0	1	5955	Not Required	7.50	Not Required
	57	6235	Not Required	7.00	
	113	6515	Not Required	7.00	
	173	6815	Not Required	7.00	
	233	7115	Not Required	7.50	
802.11ax-HE40 MCS0	3	5965	Not Required	10.00	Not Required
	59	6245	Not Required	10.00	
	107	6485	Not Required	10.00	
	171	6805	Not Required	10.00	
	227	7085	Not Required	10.50	
802.11ax-HE80 MCS0	7	5985	9.75	10.00	92.24
	71	6305	9.88	10.00	
	119	6545	10.35	11.50	
	167	6785	11.63	12.00	
	215	7025	10.98	12.00	
802.11ax-HE160 MCS0	15	6025	9.08	10.00	87.72
	47	6185	9.18	10.00	
	111	6505	11.28	11.50	
	143	6665	11.64	12.00	
	207	6985	11.66	12.00	

【6GHz WLAN_VLP_Aux_Tablet】

Mode	Channel	Frequency (MHz)	Aux		
			Average Power (dBm)	Tune-Up Limit	Duty Cycle %
802.11ax-HE20 MCS0	1	5955	Not Required	2.50	Not Required
	57	6235	Not Required	3.00	
	113	6515	Not Required	3.00	
	173	6815	Not Required	3.00	
	233	7115	Not Required	3.00	
802.11ax-HE40 MCS0	3	5965	Not Required	6.00	Not Required
	59	6245	Not Required	6.00	
	107	6485	Not Required	6.00	
	171	6805	Not Required	6.00	
	227	7085	Not Required	6.00	
802.11ax-HE80 MCS0	7	5985	Not Required	8.50	Not Required
	71	6305	Not Required	8.50	
	119	6545	Not Required	8.50	
	167	6785	Not Required	8.50	
	215	7025	Not Required	8.50	
802.11ax-HE160 MCS0	15	6025	Not Required	8.50	Not Required
	47	6185	Not Required	8.50	
	111	6505	Not Required	8.50	
	143	6665	Not Required	8.50	
	207	6985	Not Required	8.50	

**[6GHz WLAN_SP_ MIMO_Laptop]**

Mode	Channel	Frequency (MHz)	MIMO(Main)		MIMO(Aux)		MIMO		Duty Cycle %
			Average Power (dBm)	Tune-Up Limit	Average Power (dBm)	Tune-Up Limit	Average Power (dBm)	Tune-Up Limit	
802.11ax-HE20 MCS0	1	5955	Not Required	9.00	Not Required	9.00	Not Required	12.00	Not Required
	57	6235	Not Required	9.00	Not Required	9.00	Not Required	12.00	
	173	6815	Not Required	9.00	Not Required	9.00	Not Required	12.00	
802.11ax-HE40 MCS0	3	5965	Not Required	9.00	Not Required	9.00	Not Required	12.00	Not Required
	59	6245	Not Required	9.00	Not Required	9.00	Not Required	12.00	
	171	6805	Not Required	9.00	Not Required	9.00	Not Required	12.00	
802.11ax-HE80 MCS0	7	5985	Not Required	9.00	Not Required	9.00	Not Required	12.00	Not Required
	71	6305	Not Required	9.00	Not Required	9.00	Not Required	12.00	
	167	6785	Not Required	9.00	Not Required	9.00	Not Required	12.00	
802.11ax-HE160 MCS0	15	6025	8.54	9.00	8.12	9.00	11.35	12.00	87.72
	47	6185	7.18	9.00	8.95	9.00	11.16	12.00	
	143	6665	8.96	9.00	8.21	9.00	11.61	12.00	

[6GHz WLAN_LPI_ MIMO_Laptop]

Mode	Channel	Frequency (MHz)	MIMO(Main)		MIMO(Aux)		MIMO		Duty Cycle %
			Average Power (dBm)	Tune-Up Limit	Average Power (dBm)	Tune-Up Limit	Average Power (dBm)	Tune-Up Limit	
802.11ax-HE20 MCS0	1	5955	Not Required	1.00	Not Required	1.00	Not Required	4.00	Not Required
	57	6235	Not Required	0.50	Not Required	0.50	Not Required	3.50	
	113	6515	Not Required	1.00	Not Required	1.00	Not Required	4.00	
	173	6815	Not Required	1.00	Not Required	1.00	Not Required	4.00	
	233	7115	Not Required	1.50	Not Required	1.50	Not Required	4.50	
802.11ax-HE40 MCS0	3	5965	Not Required	4.00	Not Required	4.00	Not Required	7.00	Not Required
	59	6245	Not Required	4.00	Not Required	4.00	Not Required	7.00	
	107	6485	Not Required	4.50	Not Required	4.50	Not Required	7.50	
	171	6805	Not Required	4.00	Not Required	4.00	Not Required	7.00	
	227	7085	Not Required	4.50	Not Required	4.50	Not Required	7.50	
802.11ax-HE80 MCS0	7	5985	Not Required	7.00	Not Required	7.00	Not Required	10.00	Not Required
	71	6305	Not Required	6.50	Not Required	6.50	Not Required	9.50	
	119	6545	Not Required	6.50	Not Required	6.50	Not Required	9.50	
	167	6785	Not Required	6.50	Not Required	6.50	Not Required	9.50	
	215	7025	Not Required	7.00	Not Required	7.00	Not Required	10.00	
802.11ax-HE160 MCS0	15	6025	8.54	9.00	8.12	9.00	11.35	12.00	87.72
	47	6185	7.18	9.00	8.95	9.00	11.16	12.00	
	111	6505	8.14	9.00	9.00	9.00	11.60	12.00	
	143	6665	8.96	9.00	8.21	9.00	11.61	12.00	
	207	6985	9.20	9.50	8.13	9.50	11.71	12.50	

[6GHz WLAN_VLP_ MIMO_Laptop]

Mode	Channel	Frequency (MHz)	MIMO(Main)		MIMO(Aux)		MIMO		Duty Cycle %
			Average Power (dBm)	Tune-Up Limit	Average Power (dBm)	Tune-Up Limit	Average Power (dBm)	Tune-Up Limit	
802.11ax-HE20 MCS0	1	5955	Not Required	-3.00	Not Required	-3.00	Not Required	0.00	Not Required
	57	6235	Not Required	-3.00	Not Required	-3.00	Not Required	0.00	
	113	6515	Not Required	-3.50	Not Required	-3.50	Not Required	-0.50	
	173	6815	Not Required	-3.00	Not Required	-3.00	Not Required	0.00	
	233	7115	Not Required	-3.00	Not Required	-3.00	Not Required	0.00	
802.11ax-HE40 MCS0	3	5965	Not Required	0.00	Not Required	0.00	Not Required	3.00	Not Required
	59	6245	Not Required	0.00	Not Required	0.00	Not Required	3.00	
	107	6485	Not Required	0.00	Not Required	0.00	Not Required	3.00	
	171	6805	Not Required	0.00	Not Required	0.00	Not Required	3.00	
	227	7085	Not Required	0.00	Not Required	0.00	Not Required	3.00	
802.11ax-HE80 MCS0	7	5985	Not Required	2.50	Not Required	2.50	Not Required	5.50	Not Required
	71	6305	Not Required	2.50	Not Required	2.50	Not Required	5.50	
	119	6545	Not Required	2.50	Not Required	2.50	Not Required	5.50	
	167	6785	Not Required	2.50	Not Required	2.50	Not Required	5.50	
	215	7025	Not Required	2.50	Not Required	2.50	Not Required	5.50	
802.11ax-HE160 MCS0	15	6025	Not Required	2.50	Not Required	2.50	Not Required	5.50	Not Required
	47	6185	Not Required	2.50	Not Required	2.50	Not Required	5.50	
	111	6505	Not Required	2.50	Not Required	2.50	Not Required	5.50	
	143	6665	Not Required	2.50	Not Required	2.50	Not Required	5.50	
	207	6985	Not Required	2.50	Not Required	2.50	Not Required	5.50	

**【6GHz WLAN_SP_ MIMO_Tablet】**

Mode	Channel	Frequency (MHz)	MIMO(Main)		MIMO(Aux)		MIMO		Duty Cycle %
			Average Power (dBm)	Tune-Up Limit	Average Power (dBm)	Tune-Up Limit	Average Power (dBm)	Tune-Up Limit	
802.11ax-HE20 MCS0	1	5955	Not Required	10.00	Not Required	10.00	Not Required	13.00	Not Required
	57	6235	Not Required	10.00	Not Required	10.00	Not Required	13.00	
	173	6815	Not Required	12.00	Not Required	12.00	Not Required	15.00	
802.11ax-HE40 MCS0	3	5965	Not Required	10.00	Not Required	10.00	Not Required	13.00	Not Required
	59	6245	Not Required	10.00	Not Required	10.00	Not Required	13.00	
	171	6805	Not Required	12.00	Not Required	12.00	Not Required	15.00	
802.11ax-HE80 MCS0	7	5985	Not Required	10.00	Not Required	10.00	Not Required	13.00	Not Required
	71	6305	Not Required	10.00	Not Required	10.00	Not Required	13.00	
	167	6785	Not Required	12.00	Not Required	12.00	Not Required	15.00	
802.11ax-HE160 MCS0	15	6025	8.90	10.00	9.88	10.00	12.43	13.00	87.72
	47	6185	8.23	10.00	9.61	10.00	11.98	13.00	
	143	6665	10.85	12.00	11.37	12.00	14.13	15.00	

【6GHz WLAN_LPI_ MIMO_Tablet】

Mode	Channel	Frequency (MHz)	MIMO(Main)		MIMO(Aux)		MIMO		Duty Cycle %
			Average Power (dBm)	Tune-Up Limit	Average Power (dBm)	Tune-Up Limit	Average Power (dBm)	Tune-Up Limit	
802.11ax-HE20 MCS0	1	5955	Not Required	1.00	Not Required	1.00	Not Required	4.00	Not Required
	57	6235	Not Required	0.50	Not Required	0.50	Not Required	3.50	
	113	6515	Not Required	1.00	Not Required	1.00	Not Required	4.00	
	173	6815	Not Required	1.00	Not Required	1.00	Not Required	4.00	
	233	7115	Not Required	1.50	Not Required	1.50	Not Required	4.50	
802.11ax-HE40 MCS0	3	5965	Not Required	4.00	Not Required	4.00	Not Required	7.00	Not Required
	59	6245	Not Required	4.00	Not Required	4.00	Not Required	7.00	
	107	6485	Not Required	4.50	Not Required	4.50	Not Required	7.50	
	171	6805	Not Required	4.00	Not Required	4.00	Not Required	7.00	
	227	7085	Not Required	4.50	Not Required	4.50	Not Required	7.50	
802.11ax-HE80 MCS0	7	5985	Not Required	7.00	Not Required	7.00	Not Required	10.00	Not Required
	71	6305	Not Required	6.50	Not Required	6.50	Not Required	9.50	
	119	6545	Not Required	6.50	Not Required	6.50	Not Required	9.50	
	167	6785	Not Required	6.50	Not Required	6.50	Not Required	9.50	
	215	7025	Not Required	7.00	Not Required	7.00	Not Required	10.00	
802.11ax-HE160 MCS0	15	6025	8.43	9.50	9.26	9.50	11.88	12.50	87.72
	47	6185	7.34	9.00	8.54	9.00	10.99	12.00	
	111	6505	8.80	9.00	8.93	9.00	11.88	12.00	
	143	6665	8.44	9.50	8.70	9.50	11.58	12.50	
	207	6985	8.76	9.50	9.20	9.50	12.00	12.50	

【6GHz WLAN_VLP_ MIMO_Tablet】

Mode	Channel	Frequency (MHz)	MIMO(Main)		MIMO(Aux)		MIMO		Duty Cycle %
			Average Power (dBm)	Tune-Up Limit	Average Power (dBm)	Tune-Up Limit	Average Power (dBm)	Tune-Up Limit	
802.11ax-HE20 MCS0	1	5955	Not Required	-3.00	Not Required	-3.00	Not Required	0.00	Not Required
	57	6235	Not Required	-3.00	Not Required	-3.00	Not Required	0.00	
	113	6515	Not Required	-3.50	Not Required	-3.50	Not Required	-0.50	
	173	6815	Not Required	-3.00	Not Required	-3.00	Not Required	0.00	
	233	7115	Not Required	-3.00	Not Required	-3.00	Not Required	0.00	
802.11ax-HE40 MCS0	3	5965	Not Required	0.00	Not Required	0.00	Not Required	3.00	Not Required
	59	6245	Not Required	0.00	Not Required	0.00	Not Required	3.00	
	107	6485	Not Required	0.00	Not Required	0.00	Not Required	3.00	
	171	6805	Not Required	0.00	Not Required	0.00	Not Required	3.00	
	227	7085	Not Required	0.00	Not Required	0.00	Not Required	3.00	
802.11ax-HE80 MCS0	7	5985	Not Required	2.50	Not Required	2.50	Not Required	5.50	Not Required
	71	6305	Not Required	2.50	Not Required	2.50	Not Required	5.50	
	119	6545	Not Required	2.50	Not Required	2.50	Not Required	5.50	
	167	6785	Not Required	2.50	Not Required	2.50	Not Required	5.50	
	215	7025	Not Required	2.50	Not Required	2.50	Not Required	5.50	
802.11ax-HE160 MCS0	15	6025	Not Required	2.50	Not Required	2.50	Not Required	5.50	Not Required
	47	6185	Not Required	2.50	Not Required	2.50	Not Required	5.50	
	111	6505	Not Required	2.50	Not Required	2.50	Not Required	5.50	
	143	6665	Not Required	2.50	Not Required	2.50	Not Required	5.50	
	207	6985	Not Required	2.50	Not Required	2.50	Not Required	5.50	




< 2.4GHz Bluetooth >

【Bluetooth】

Mode	Channel	Frequency (MHz)	Aux		
			Average Power (dBm)	Tune-Up Limit	Duty Cycle %
BR / EDR 1Mbps	0	2402	11.64	12.00	76.93
	39	2441	11.89	12.00	
	78	2480	11.53	12.00	
BR / EDR 2Mbps	0	2402	Not Required	9.00	Not Required
	39	2441	Not Required	9.00	
	78	2480	Not Required	9.00	
BR / EDR 3Mbps	0	2402	Not Required	9.00	Not Required
	39	2441	Not Required	9.00	
	78	2480	Not Required	9.00	
LE 1Mbps	0	2402	Not Required	12.00	Not Required
	19	2440	Not Required	12.00	
	39	2480	Not Required	12.00	
LE 2Mbps	0	2402	Not Required	12.00	Not Required
	19	2440	Not Required	12.00	
	39	2480	Not Required	12.00	


General Note:

- For 2.4GHz Bluetooth SAR testing was selected 1Mbps due to its highest average power and duty cycle is 76.93% considered in SAR testing, and the duty cycle would be scaled to theoretical 83.3% in reported SAR calculation.



12. Antenna Location

<Tablet Mode>




Front View

The separation distance for antenna to edge :

Antenna	Top Edge (mm)	Right Edge (mm)	Bottom Edge (mm)	Left Edge (mm)
WLAN/BT Aux Antenna	224	145.2	10.8	134.5
WLAN Main Antenna	224	222.7	10.8	56.1

<Laptop Mode>



The separation distance for antenna to edge :

Antenna	To Bottom Side (mm)
WLAN Main Antenna	3.23
WLAN/BT Antenna	3.23

< SAR test exclusion table >
General Note:

1. The below table, when the distance is < 50 mm exclusion threshold is "Ratio", when the distance is > 50 mm exclusion threshold is "mW"
2. Maximum power is the source-based time-average power and represents the maximum RF output power among production units
3. Per KDB 447498 D01v06, for larger devices, the test separation distance of adjacent edge configuration is determined by the closest separation between the antenna and the user.
4. Per KDB 447498 D01v06, standalone SAR test exclusion threshold is applied; If the test separation distance is < 5mm, 5mm is used to determine SAR exclusion threshold.
5. Per KDB 447498 D01v06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR}$$
 - f(GHz) is the RF channel transmit frequency in GHz
 - Power and distance are rounded to the nearest mW and mm before calculation
 - The result is rounded to one decimal place for comparison
6. Per KDB 447498 D01v06, at 100 MHz to 6 GHz and for test separation distances > 50 mm, the SAR test exclusion threshold is determined according to the following
 - a) [Threshold at 50 mm in step 1) + (test separation distance - 50 mm) · (f(MHz)/150)] mW, at 100 MHz to 1500 MHz
 - b) [Threshold at 50 mm in step 1) + (test separation distance - 50 mm) · 10] mW at > 1500 MHz and ≤ 6 GHz

<Laptop Mode>

Exposure Position	Wireless Interface	BT Aux	2.4GHz WLAN Main	2.4GHz WLAN Aux	5/6GHz WLAN Main	5/6GHz WLAN Aux
	Calculated Frequency (MHz)	2480	2472	2472	5825	5825
	Maximum power (dBm)	12.0	12.5	12.5	10.5	10.5
	Maximum rated power(mW)	15.85	17.78	17.78	11.22	11.22
Bottom Face	Separation distance(mm)	3.2	3.2	3.2	3.2	3.2
	exclusion threshold	5.0	5.6	5.6	5.4	5.4
	Testing required?	Yes	Yes	Yes	Yes	Yes

<Tablet Mode>

Exposure Position	Wireless Interface	BT Aux	2.4GHz WLAN Main	2.4GHz WLAN Aux	5/6GHz WLAN Main	5/6GHz WLAN Aux
	Calculated Frequency (MHz)	2480	2472	2472	5825	5825
	Maximum power (dBm)	12.0	14.0	14.0	9.5	9.5
	Maximum rated power(mW)	15.85	25.12	25.12	8.91	8.91
Back	Separation distance(mm)	30.6	31.7	30.6	31.7	30.6
	exclusion threshold	0.8	1.2	1.3	0.7	0.7
	Testing required?	No	No	No	No	No
Right	Separation distance(mm)	145.2	222.7	145.2	222.7	145.2
	exclusion threshold	1047.0	1822.0	1047.0	1789.0	1014.0
	Testing required?	No	No	No	No	No
Left	Separation distance(mm)	134.5	56.1	134.5	56.1	134.5
	exclusion threshold	940.0	156.0	941.0	123.0	907.0
	Testing required?	No	No	No	No	No
Bottom	Separation distance(mm)	10.8	10.8	10.8	10.8	10.8
	exclusion threshold	2.3	3.7	3.7	2.0	2.0
	Testing required?	No	Yes	Yes	No	No
TOP	Separation distance(mm)	224.0	224.0	224.0	224.0	224.0
	exclusion threshold	1835.0	1835.0	1835.0	1802.0	1802.0
	Testing required?	No	No	No	No	No

13. SAR Test Results

General Note:

1. Per KDB 447498 D01v06, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - b. For SAR testing of WLAN signal with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)"
 - c. For WLAN/Bluetooth: Reported SAR(W/kg)= Measured SAR(W/kg)* Duty Cycle scaling factor * Tune-up scaling factor
2. Per KDB 447498 D01v06, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the *reported* 1-g or 10-g SAR for the mid-band or highest output power channel is:
 - ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
 - ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
 - ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz
3. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥ 0.8 W/kg.

WLAN Note:

1. Per KDB 248227 D01v02r02, for 2.4GHz 802.11g/n SAR testing is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.
2. Per KDB 248227 D01v02r02, WLAN5.2GHz SAR testing is not required for hotspot and body-worn condition when the WLAN5.3GHz band highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for WLAN5.2GHz band.
3. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
4. For all positions / configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions / configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.
5. For WLAN SAR testing was performed on single antenna RF power in SISO mode is larger or equal to the single antenna RF power in MIMO mode, and for RF exposure assessment of MIMO mode simultaneous transmission exclusion analysis was performed with SAR test results of each antenna in SISO mode.
6. Per KDB 248227 D01v02r02, the simultaneous SAR provisions in KDB publication 447498 should be applied to determine simultaneous transmission SAR test exclusion for WiFi MIMO. If the sum of 1g single transmission chain SAR measurements is < 1.6 W/kg and SAR peak to location ratio ≤ 0.04 , no additional SAR measurements for MIMO.
7. During SAR testing, the WLAN transmit signal was continuously monitored using a spectrum analyzer to ensure continuous and stable signal output throughout the measurement.

WLAN PD Note:

1. The WiFi 6E PD was performed according 2020 TCB workshop RF Exposure 5G RFX Policies Interim Procedures.
2. First, evaluate SAR using 6-7 GHz parameters per IEC/IEEE 62209-1528:2020 and evaluate incident PD using the mmw near-field probe and total-field/power-density reconstruction method.
3. Per Interim Procedures. The power density results were scaled according to IEC 62479:2010 for the portion of the measurement uncertainty > 30%. Total expanded uncertainty of 2.68 dB (85.4%) was used to determine the psPD measurement scaling factor
4. The manufacturer has confirmed that the devices tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
5. The WiFi 6E RF Exposure results are used for simultaneous transmission analysis with the other transmitters and total exposure ratio, the analysis can be found in this report section 14.
6. Absorbed power density (APD) using a 4cm² averaging area is reported based on SAR measurements.
7. Power density was calculated by repeated E-field measurements on two measurement planes separated by $\lambda/4$.
8. The device was configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools.
9. The measurement procedure consists of measuring the PD_{inc} at two different distances: 2 mm (compliance distance) and $\lambda/5$. The grid extents should be large enough to fully capture the transmitted energy. The grid step should be fine enough to demonstrate that the integrated Power Density iPD_n fulfill the criterion described below. Since iPD ratio between the two distances is ≥ -1 dB, the grid step (0.0625) was sufficient for determining compliance at d=2mm.

$$10 \cdot \log_{10} \frac{iPD_n(2mm)}{iPD_n(\lambda/5)} \geq -1$$

**13.1 Body SAR**

Plot No	Band	Mode	Test Position	Gap (mm)	Antenna	Power State	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-Up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	2.4GHz WLAN	802.11b 1Mbps	Bottom Side	0mm	Main	Laptop	6	2437	LUX	12.24	12.50	1.062	99.67	1.003	0.00	0.658	0.701
	2.4GHz WLAN	802.11b 1Mbps	Back	0mm	Main	Tablet	6	2437	LUX	13.76	14.00	1.057	99.67	1.003	-0.02	0.068	0.072
	2.4GHz WLAN	802.11b 1Mbps	Bottom	0mm	Main	Tablet	6	2437	LUX	13.76	14.00	1.057	99.67	1.003	-0.02	0.676	0.717
	2.4GHz WLAN	802.11b 1Mbps	Bottom Side	0mm	Main	Laptop	6	2437	ADV	12.24	12.50	1.062	99.67	1.003	0.11	0.934	0.995
	2.4GHz WLAN	802.11b 1Mbps	Bottom	0mm	Main	Tablet	6	2437	ADV	13.76	14.00	1.057	99.67	1.003	-0.18	0.860	0.912
	2.4GHz WLAN	802.11b 1Mbps	Bottom Side	0mm	Aux	Laptop	1	2412	LUX	12.28	12.50	1.052	99.51	1.005	-0.04	0.572	0.605
	2.4GHz WLAN	802.11b 1Mbps	Back	0mm	Aux	Tablet	6	2437	LUX	13.21	14.00	1.199	99.51	1.005	0.03	0.085	0.102
	2.4GHz WLAN	802.11b 1Mbps	Bottom	0mm	Aux	Tablet	6	2437	LUX	13.21	14.00	1.199	99.51	1.005	0.01	0.635	0.765
	2.4GHz WLAN	802.11b 1Mbps	Bottom Side	0mm	Aux	Laptop	1	2412	ADV	12.28	12.50	1.052	99.51	1.005	-0.02	0.658	0.696
01	2.4GHz WLAN	802.11b 1Mbps	Bottom	0mm	Aux	Tablet	6	2437	ADV	13.21	14.00	1.199	99.51	1.005	0.00	0.865	1.042
	2.4GHz WLAN	802.11b 1Mbps	Bottom	0mm	Aux	Tablet	1	2412	ADV	13.20	14.00	1.202	99.51	1.005	-0.15	0.684	0.826
	2.4GHz WLAN	802.11b 1Mbps	Bottom	0mm	Aux	Tablet	11	2462	ADV	13.11	14.00	1.227	99.51	1.005	-0.07	0.839	1.035
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom Side	0mm	Main	Laptop	58	5290	LUX	8.29	8.50	1.050	91.86	1.089	-0.08	0.627	0.717
	5GHz WLAN	802.11ac-VHT80 MCS0	Back	0mm	Main	Tablet	58	5290	LUX	7.86	8.50	1.159	91.86	1.089	0.08	0.093	0.117
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom	0mm	Main	Tablet	58	5290	LUX	7.86	8.50	1.159	91.86	1.089	0.15	0.654	0.825
	5GHz WLAN	802.11n-HT40 MCS0	Bottom	0mm	Main	Tablet	62	5310	LUX	8.45	8.50	1.012	95.76	1.044	0.12	0.675	0.713
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom Side	0mm	Main	Laptop	58	5290	ADV	8.29	8.50	1.050	91.86	1.089	-0.02	0.772	0.883
	5GHz WLAN	802.11n-HT40 MCS0	Bottom Side	0mm	Main	Laptop	62	5310	ADV	8.45	8.50	1.012	95.76	1.044	0.08	0.859	0.908
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom	0mm	Main	Tablet	58	5290	ADV	7.86	8.50	1.159	91.86	1.089	-0.01	0.706	0.891
	5GHz WLAN	802.11n-HT40 MCS0	Bottom	0mm	Main	Tablet	62	5310	ADV	8.45	8.50	1.012	95.76	1.044	0.14	0.729	0.770
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom Side	0mm	Aux	Laptop	58	5290	LUX	8.25	8.50	1.059	91.59	1.092	-0.12	0.607	0.702
	5GHz WLAN	802.11ac-VHT80 MCS0	Back	0mm	Aux	Tablet	58	5290	LUX	8.25	8.50	1.059	91.59	1.092	0.12	0.095	0.110
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom	0mm	Aux	Tablet	58	5290	LUX	8.25	8.50	1.059	91.59	1.092	-0.11	0.936	1.082
	5GHz WLAN	802.11n-HT40 MCS0	Bottom	0mm	Aux	Tablet	62	5310	LUX	8.41	8.50	1.021	95.91	1.043	0.07	0.837	0.891
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom Side	0mm	Aux	Laptop	58	5290	ADV	8.25	8.50	1.059	91.59	1.092	0.02	0.627	0.725
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom	0mm	Aux	Tablet	58	5290	ADV	8.25	8.50	1.059	91.59	1.092	-0.01	0.888	1.027
	5GHz WLAN	802.11n-HT40 MCS0	Bottom	0mm	Aux	Tablet	62	5310	ADV	8.41	8.50	1.021	95.91	1.043	0.02	0.812	0.865
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom Side	0mm	MIMO(Main)	Laptop	58	5290	LUX	8.50	8.50	1.000	91.59	1.092	0.03	1.000	1.092
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom Side	0mm	MIMO(Aux)	Laptop	58	5290	LUX	8.21	8.50	1.069	91.59	1.092	0.03	0.743	0.867
02	5GHz WLAN	802.11n-HT40 MCS0	Bottom Side	0mm	MIMO(Main)	Laptop	54	5270	LUX	7.20	8.50	1.349	95.91	1.043	0.09	0.809	1.138
	5GHz WLAN	802.11n-HT40 MCS0	Bottom Side	0mm	MIMO(Aux)	Laptop	54	5270	LUX	8.50	8.50	1.000	95.91	1.043	0.09	0.853	0.890
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom	0mm	MIMO(Main)	Tablet	58	5290	LUX	8.50	8.50	1.000	91.59	1.092	0.02	0.871	0.951
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom	0mm	MIMO(Aux)	Tablet	58	5290	LUX	8.21	8.50	1.069	91.59	1.092	0.02	0.930	1.086
	5GHz WLAN	802.11n-HT40 MCS0	Bottom	0mm	MIMO(Main)	Tablet	54	5270	LUX	7.20	8.50	1.349	95.91	1.043	0.16	0.759	1.068
	5GHz WLAN	802.11n-HT40 MCS0	Bottom	0mm	MIMO(Aux)	Tablet	54	5270	LUX	8.50	8.50	1.000	95.91	1.043	0.16	0.864	0.901
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom Side	0mm	MIMO(Main)	Laptop	58	5290	ADV	8.50	8.50	1.000	91.59	1.092	0.09	0.754	0.823
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom Side	0mm	MIMO(Aux)	Laptop	58	5290	ADV	8.21	8.50	1.069	91.59	1.092	0.09	0.703	0.821
	5GHz WLAN	802.11n-HT40 MCS0	Bottom Side	0mm	MIMO(Main)	Laptop	54	5270	ADV	7.20	8.50	1.349	95.91	1.043	0.11	0.695	0.978
	5GHz WLAN	802.11n-HT40 MCS0	Bottom Side	0mm	MIMO(Aux)	Laptop	54	5270	ADV	8.50	8.50	1.000	95.91	1.043	0.11	0.800	0.834
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom	0mm	MIMO(Main)	Tablet	58	5290	ADV	8.50	8.50	1.000	91.59	1.092	0.03	0.918	1.002
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom	0mm	MIMO(Aux)	Tablet	58	5290	ADV	8.21	8.50	1.069	91.59	1.092	0.03	0.642	0.749
	5GHz WLAN	802.11n-HT40 MCS0	Bottom	0mm	MIMO(Main)	Tablet	54	5270	ADV	7.20	8.50	1.349	95.91	1.043	0.05	0.751	1.057
	5GHz WLAN	802.11n-HT40 MCS0	Bottom	0mm	MIMO(Aux)	Tablet	54	5270	ADV	8.50	8.50	1.000	95.91	1.043	0.05	0.644	0.672
	5GHz WLAN	802.11ac-VHT160 MCS0	Bottom Side	0mm	Main	Laptop	114	5570	LUX	6.93	8.50	1.435	86.12	1.161	0.19	0.450	0.750
	5GHz WLAN	802.11ac-VHT160 MCS0	Back	0mm	Main	Tablet	114	5570	LUX	7.43	8.50	1.279	86.12	1.161	0.06	0.106	0.157
	5GHz WLAN	802.11ac-VHT160 MCS0	Bottom	0mm	Main	Tablet	114	5570	LUX	7.43	8.50	1.279	86.12	1.161	0.12	0.487	0.723
	5GHz WLAN	802.11ac-VHT160 MCS0	Bottom Side	0mm	Main	Laptop	114	5570	ADV	6.93	8.50	1.435	86.12	1.161	-0.01	0.589	0.981
	5GHz WLAN	802.11ac-VHT160 MCS0	Bottom Side	0mm	Main	Laptop	138	5690	ADV	7.33	8.50	1.309	91.86	1.089	0.01	0.635	0.905
	5GHz WLAN	802.11ac-VHT160 MCS0	Bottom	0mm	Main	Tablet	114	5570	ADV	7.43	8.50	1.279	86.12	1.161	0.04	0.625	0.928
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom	0mm	Main	Tablet	138	5690	ADV	7.83	8.50	1.167	91.86	1.089	-0.15	0.442	0.562
	5GHz WLAN	802.11ac-VHT160 MCS0	Bottom Side	0mm	Aux	Laptop	114	5570	LUX	6.65	8.50	1.531	86.54	1.156	-0.10	0.467	0.827
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom Side	0mm	Aux	Laptop	122	5610	LUX	7.05	8.50	1.396	91.59	1.092	0.01	0.436	0.665
	5GHz WLAN	802.11ac-VHT160 MCS0	Back	0mm	Aux	Tablet	114	5570	LUX	7.15	8.50	1.365	86.54	1.156	-0.09	0.065	0.103
	5GHz WLAN	802.11ac-VHT160 MCS0	Bottom	0mm	Aux	Tablet	114	5570	LUX	7.15	8.50	1.365	86.54	1.156	0.02	0.596	0.940
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom	0mm	Aux	Tablet	122	5610	LUX	7.55	8.50	1.245	91.59	1.092	0.16	0.462	0.628
	5GHz WLAN	802.11ac-VHT160 MCS0	Bottom Side	0mm	Aux	Laptop	114	5570	ADV	6.65	8.50	1.531	86.54	1.156	0.17	0.471	0.834
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom Side	0mm	Aux	Laptop	122	5610	ADV	7.05	8.50	1.396	91.59	1.092	-0.05	0.462	0.704
	5GHz WLAN	802.11ac-VHT160 MCS0	Bottom	0mm	Aux	Tablet	114	5570	ADV	7.15	8.50	1.365	86.54	1.156	-0.02	0.633	0.999
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom	0mm	Aux	Tablet	122	5610	ADV	7.55	8.50	1.245	91.59	1.092	-0.11	0.638	0.867
	5GHz WLAN	802.11ac-VHT160 MCS0	Bottom Side	0mm	MIMO(Main)	Laptop	114	5570	LUX	7.67	8.50	1.211	86.54	1.156	0.05	0.656	0.918
	5GHz WLAN	802.11ac-VHT160 MCS0	Bottom Side	0mm	MIMO(Aux)	Laptop	114	5570	LUX	8.50	8.50	1.000	86.54	1.156	0.05	0.612	0.707
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom Side	0mm	MIMO(Main)	Laptop	138	5690	LUX	8.48	8.50	1.005	91.59	1.092	0.11	0.504	0.553
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom Side	0mm	MIMO(Aux)	Laptop	138	5690	LUX	8.10	8.50	1.096	91.59	1.092	0.11	0.413	0.494
	5GHz WLAN	802.11ac-VHT160 MCS0	Bottom	0mm	MIMO(Main)	Tablet	114	5570	LUX	6.97	8.50	1.422	86.54	1.156	-0.08	0.542	0.891
	5GHz WLAN	802.11ac-VHT160 MCS0	Bottom	0mm	MIMO(Aux)	Tablet	114	5570	LUX	8.07	8.50	1.104	86.54	1.156	-0.08	0.689	0.879
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom	0mm	MIMO(Main)	Tablet	138	5690	LUX	8.35	8.50	1.035	91.59	1.092	0.05	0.672	0.760
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom	0mm	MIMO(Aux)	Tablet	138	5690	LUX	7.85	8.50	1.161	91.59	1.092	0.05	0.465	0.590
03	5GHz WLAN	802.11ac-VHT160 MCS0	Bottom Side	0mm	MIMO(Main)	Laptop	114	5570	ADV	7.67	8.50	1.211	86.54	1.156	0.10	0.811	1.135



FCC SAR TEST REPORT

Report No. : FA622608

	5GHz WLAN	802.11ac-VHT160 MCS0	Bottom Side	0mm	MIMO(Aux)	Laptop	114	5570	ADV	8.50	8.50	1.000	86.54	1.156	0.10	0.620	0.717
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom Side	0mm	MIMO(Main)	Laptop	138	5690	ADV	8.48	8.50	1.005	91.59	1.092	0.17	0.919	1.009
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom Side	0mm	MIMO(Aux)	Laptop	138	5690	ADV	8.10	8.50	1.096	91.59	1.092	0.17	0.452	0.541
	5GHz WLAN	802.11ac-VHT160 MCS0	Bottom	0mm	MIMO(Main)	Tablet	114	5570	ADV	6.97	8.50	1.422	86.54	1.156	0.01	0.535	0.879
	5GHz WLAN	802.11ac-VHT160 MCS0	Bottom	0mm	MIMO(Aux)	Tablet	114	5570	ADV	8.07	8.50	1.104	86.54	1.156	0.01	0.487	0.622
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom	0mm	MIMO(Main)	Tablet	138	5690	ADV	8.35	8.50	1.035	91.59	1.092	0.07	0.775	0.876
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom	0mm	MIMO(Aux)	Tablet	138	5690	ADV	7.85	8.50	1.161	91.59	1.092	0.07	0.381	0.483
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom Side	0mm	Main	Laptop	155	5775	LUX	9.50	10.50	1.259	91.86	1.089	-0.14	0.486	0.666
	5GHz WLAN	802.11ac-VHT80 MCS0	Back	0mm	Main	Tablet	155	5775	LUX	9.44	9.50	1.014	91.86	1.089	0.06	0.161	0.178
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom	0mm	Main	Tablet	155	5775	LUX	9.44	9.50	1.014	91.86	1.089	-0.14	0.657	0.725
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom Side	0mm	Main	Laptop	155	5775	ADV	9.50	10.50	1.259	91.86	1.089	0.04	0.679	0.931
	5GHz WLAN	802.11n-HT40 MCS0	Bottom Side	0mm	Main	Laptop	151	5755	ADV	9.83	10.50	1.167	95.76	1.044	-0.02	0.764	0.931
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom	0mm	Main	Tablet	155	5775	ADV	9.44	9.50	1.014	91.86	1.089	0.18	0.919	1.015
	5GHz WLAN	802.11n-HT40 MCS0	Bottom	0mm	Main	Tablet	159	5795	ADV	9.45	9.50	1.012	95.76	1.044	0.03	0.896	0.947
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom Side	0mm	Aux	Laptop	155	5775	LUX	9.15	10.50	1.365	91.59	1.092	0.11	0.411	0.613
	5GHz WLAN	802.11ac-VHT80 MCS0	Back	0mm	Aux	Laptop	155	5775	LUX	9.15	9.50	1.084	91.59	1.092	-0.02	0.103	0.122
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom	0mm	Aux	Tablet	155	5775	LUX	9.15	9.50	1.084	91.59	1.092	-0.05	0.572	0.677
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom Side	0mm	Aux	Laptop	155	5775	ADV	9.15	10.50	1.365	91.59	1.092	0.17	0.481	0.717
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom	0mm	Aux	Tablet	155	5775	ADV	9.15	9.50	1.084	91.59	1.092	0.00	0.710	0.840
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom Side	0mm	MIMO(Main)	Laptop	155	5775	LUX	9.87	10.50	1.156	91.86	1.089	0.13	0.473	0.595
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom Side	0mm	MIMO(Aux)	Laptop	155	5775	LUX	10.00	10.50	1.122	91.86	1.089	0.13	0.573	0.700
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom	0mm	MIMO(Main)	Tablet	155	5775	LUX	8.87	9.50	1.156	91.86	1.089	-0.07	0.700	0.881
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom	0mm	MIMO(Aux)	Tablet	155	5775	LUX	9.00	9.50	1.122	91.86	1.089	-0.07	0.895	1.094
	5GHz WLAN	802.11n-HT40 MCS0	Bottom	0mm	MIMO(Main)	Tablet	151	5755	LUX	8.60	9.50	1.230	95.76	1.044	0.16	0.633	0.813
	5GHz WLAN	802.11n-HT40 MCS0	Bottom	0mm	MIMO(Aux)	Tablet	151	5755	LUX	8.90	9.50	1.148	95.76	1.044	0.16	0.921	1.104
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom Side	0mm	MIMO(Main)	Laptop	155	5775	ADV	9.87	10.50	1.156	91.86	1.089	-0.17	0.717	0.903
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom Side	0mm	MIMO(Aux)	Laptop	155	5775	ADV	10.00	10.50	1.122	91.86	1.089	-0.17	0.588	0.718
	5GHz WLAN	802.11n-HT40 MCS0	Bottom Side	0mm	MIMO(Main)	Laptop	151	5755	ADV	9.60	10.50	1.230	95.76	1.044	-0.06	0.685	0.880
	5GHz WLAN	802.11n-HT40 MCS0	Bottom Side	0mm	MIMO(Aux)	Laptop	151	5755	ADV	9.90	10.50	1.148	95.76	1.044	-0.06	0.586	0.702
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom	0mm	MIMO(Main)	Tablet	155	5775	ADV	8.87	9.50	1.156	91.86	1.089	-0.17	0.807	1.016
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom	0mm	MIMO(Aux)	Tablet	155	5775	ADV	9.00	9.50	1.122	91.86	1.089	-0.17	0.704	0.860
04	5GHz WLAN	802.11n-HT40 MCS0	Bottom	0mm	MIMO(Main)	Tablet	151	5755	ADV	8.60	9.50	1.230	95.76	1.044	-0.12	0.889	1.142
	5GHz WLAN	802.11n-HT40 MCS0	Bottom	0mm	MIMO(Aux)	Tablet	151	5755	ADV	8.90	9.50	1.148	95.76	1.044	-0.12	0.733	0.879
	5GHz WLAN	802.11ac-VHT160 MCS0	Bottom Side	0mm	Main	Laptop	163	5815	LUX	9.67	10.50	1.211	86.12	1.161	0.16	0.426	0.599
	5GHz WLAN	802.11ac-VHT160 MCS0	Back	0mm	Main	Tablet	163	5815	LUX	9.11	9.50	1.094	86.12	1.161	0.03	0.112	0.142
	5GHz WLAN	802.11ac-VHT160 MCS0	Bottom	0mm	Main	Tablet	163	5815	LUX	9.11	9.50	1.094	86.12	1.161	0.06	0.619	0.786
	5GHz WLAN	802.11ac-VHT160 MCS0	Bottom Side	0mm	Main	Laptop	163	5815	ADV	9.67	10.50	1.211	86.12	1.161	-0.07	0.652	0.917
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom Side	0mm	Main	Laptop	171	5855	ADV	9.53	10.50	1.250	91.86	1.089	0.00	0.731	0.995
	5GHz WLAN	802.11ac-VHT160 MCS0	Bottom	0mm	Main	Tablet	163	5815	ADV	9.11	9.50	1.094	86.12	1.161	0.05	0.764	0.970
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom	0mm	Main	Tablet	171	5855	ADV	9.32	9.50	1.042	91.86	1.089	0.07	0.745	0.845
	5GHz WLAN	802.11ac-VHT160 MCS0	Bottom Side	0mm	Aux	Laptop	163	5815	LUX	9.00	10.50	1.413	86.54	1.156	0.11	0.459	0.750
	5GHz WLAN	802.11ac-VHT160 MCS0	Back	0mm	Aux	Tablet	163	5815	LUX	9.08	9.50	1.102	86.54	1.156	0.01	0.071	0.090
	5GHz WLAN	802.11ac-VHT160 MCS0	Bottom	0mm	Aux	Tablet	163	5815	LUX	9.08	9.50	1.102	86.54	1.156	-0.18	0.598	0.762
	5GHz WLAN	802.11ac-VHT160 MCS0	Bottom Side	0mm	Aux	Laptop	163	5815	ADV	9.00	10.50	1.413	86.54	1.156	0.10	0.446	0.729
	5GHz WLAN	802.11ac-VHT160 MCS0	Bottom	0mm	Aux	Tablet	163	5815	ADV	9.08	9.50	1.102	86.54	1.156	0.01	0.732	0.933
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom	0mm	Aux	Tablet	171	5855	ADV	9.24	9.50	1.062	91.59	1.092	0.05	0.792	0.918
	5GHz WLAN	802.11ac-VHT160 MCS0	Bottom Side	0mm	MIMO(Main)	Laptop	163	5815	LUX	9.40	10.50	1.288	86.54	1.156	0.12	0.482	0.718
	5GHz WLAN	802.11ac-VHT160 MCS0	Bottom Side	0mm	MIMO(Aux)	Laptop	163	5815	LUX	10.00	10.50	1.122	86.54	1.156	0.12	0.578	0.750
	5GHz WLAN	802.11ac-VHT160 MCS0	Bottom	0mm	MIMO(Main)	Tablet	163	5815	LUX	8.40	9.50	1.288	86.12	1.161	-0.18	0.494	0.739
	5GHz WLAN	802.11ac-VHT160 MCS0	Bottom	0mm	MIMO(Aux)	Tablet	163	5815	LUX	9.00	9.50	1.122	86.12	1.161	-0.18	0.746	0.972
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom	0mm	MIMO(Main)	Tablet	171	5855	LUX	8.38	9.50	1.294	91.59	1.092	-0.14	0.560	0.791
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom	0mm	MIMO(Aux)	Tablet	171	5855	LUX	9.40	9.50	1.023	91.59	1.092	-0.14	0.792	0.885
	5GHz WLAN	802.11ac-VHT160 MCS0	Bottom Side	0mm	MIMO(Main)	Laptop	163	5815	ADV	9.40	10.50	1.288	86.54	1.156	-0.03	0.633	0.942
	5GHz WLAN	802.11ac-VHT160 MCS0	Bottom Side	0mm	MIMO(Aux)	Laptop	163	5815	ADV	10.00	10.50	1.122	86.54	1.156	-0.03	0.565	0.733
05	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom Side	0mm	MIMO(Main)	Laptop	171	5855	ADV	9.38	10.50	1.294	91.59	1.092	-0.07	0.719	1.016
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom Side	0mm	MIMO(Aux)	Laptop	171	5855	ADV	10.40	10.50	1.023	91.59	1.092	-0.07	0.581	0.649
	5GHz WLAN	802.11ac-VHT160 MCS0	Bottom	0mm	MIMO(Main)	Tablet	163	5815	ADV	8.40	9.50	1.288	86.12	1.161	-0.14	0.668	0.999
	5GHz WLAN	802.11ac-VHT160 MCS0	Bottom	0mm	MIMO(Aux)	Tablet	163	5815	ADV	9.00	9.50	1.122	86.12	1.161	-0.14	0.584	0.761
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom	0mm	MIMO(Main)	Tablet	171	5855	ADV	8.38	9.50	1.294	91.59	1.092	-0.04	0.624	0.882
	5GHz WLAN	802.11ac-VHT80 MCS0	Bottom	0mm	MIMO(Aux)	Tablet	171	5855	ADV	9.40	9.50	1.023	91.59	1.092	-0.04	0.611	0.683



FCC SAR TEST REPORT

Report No. : FA622608

Plot No	Band	Mode	Test Position	Gap (mm)	Antenna	Power State	Ch.	Freq. (MHz)	Power Setting	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-Up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured APD (W/m ²)	Reported APD (W/m ²)
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom Side	0mm	Main	Laptop	207	6985	9.5	LUX	10.38	10.50	1.028	87.34	1.145	-0.03	0.651	0.766	3.270	3.849
	6GHz WLAN	802.11ax-HE160 MCS0	Back	0mm	Main	Tablet	207	6985	10.75	LUX	11.89	12.00	1.026	87.34	1.145	0.03	0.061	0.072	0.523	0.614
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom	0mm	Main	Tablet	207	6985	10.75	LUX	11.89	12.00	1.026	87.34	1.145	0.04	0.478	0.562	2.430	2.855
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom Side	0mm	Main	Laptop	15	6025	8.5	LUX	8.73	9.00	1.064	87.34	1.145	0.04	0.465	0.567	2.610	3.180
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom Side	0mm	Main	Laptop	47	6185	8.5	LUX	8.51	9.00	1.119	87.34	1.145	-0.03	0.460	0.589	2.460	3.152
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom Side	0mm	Main	Laptop	111	6505	8.5	LUX	8.81	9.00	1.045	87.34	1.145	0.05	0.458	0.548	2.340	2.800
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom Side	0mm	Main	Laptop	143	6665	9	LUX	8.85	9.00	1.035	87.34	1.145	-0.04	0.479	0.568	2.460	2.915
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom	0mm	Main	Tablet	15	6025	9.5	LUX	9.75	10.00	1.059	87.34	1.145	0.03	0.596	0.723	3.290	3.989
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom	0mm	Main	Tablet	47	6185	9.5	LUX	9.55	10.00	1.109	87.34	1.145	-0.02	0.466	0.592	2.440	3.098
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom	0mm	Main	Tablet	111	6505	11.5	LUX	11.42	11.50	1.019	87.34	1.145	0.01	0.587	0.685	3.210	3.745
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom	0mm	Main	Tablet	143	6665	11.5	LUX	11.64	12.00	1.086	87.34	1.145	0.07	0.469	0.583	2.530	3.146
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom Side	0mm	Main	Laptop	207	6985	9.5	ADV	10.38	10.50	1.028	87.34	1.145	0.13	0.806	0.949	4.020	4.732
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom Side	0mm	Main	Laptop	15	6025	8.5	ADV	8.73	9.00	1.064	87.34	1.145	0.08	0.653	0.796	3.600	4.386
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom Side	0mm	Main	Laptop	47	6185	8.5	ADV	8.51	9.00	1.119	87.34	1.145	0.01	0.767	0.983	4.120	5.279
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom Side	0mm	Main	Laptop	111	6505	8.5	ADV	8.81	9.00	1.045	87.34	1.145	0.19	0.780	0.933	4.040	4.834
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom Side	0mm	Main	Laptop	143	6665	9	ADV	8.85	9.00	1.035	87.34	1.145	-0.08	0.709	0.840	3.650	4.326
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom	0mm	Main	Tablet	15	6025	9.5	ADV	9.75	10.00	1.059	87.34	1.145	0.13	0.831	1.008	4.470	5.420
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom	0mm	Main	Tablet	47	6185	9.5	ADV	9.55	10.00	1.109	87.34	1.145	0.19	0.779	0.989	4.040	5.130
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom	0mm	Main	Tablet	111	6505	11.5	ADV	11.42	11.50	1.019	87.34	1.145	-0.16	0.902	1.052	4.100	4.784
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom	0mm	Main	Tablet	143	6665	11.5	ADV	11.64	12.00	1.086	87.34	1.145	0.07	0.621	0.772	3.240	4.029
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom	0mm	Main	Tablet	207	6985	10.75	ADV	11.89	12.00	1.026	87.34	1.145	0.02	0.622	0.731	3.180	3.736
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom Side	0mm	Aux	Laptop	207	6985	9	LUX	10.25	10.50	1.059	87.72	1.140	-0.14	0.434	0.524	2.280	2.753
	6GHz WLAN	802.11ax-HE160 MCS0	Back	0mm	Aux	Tablet	207	6985	11	LUX	11.66	12.00	1.081	87.72	1.140	-0.04	0.075	0.092	0.554	0.683
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom	0mm	Aux	Tablet	207	6985	11	LUX	11.66	12.00	1.081	87.72	1.140	0.01	0.780	0.961	4.270	5.262
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom Side	0mm	Aux	Laptop	15	6025	8.5	LUX	8.67	9.00	1.079	87.72	1.140	0.17	0.320	0.394	2.160	2.657
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom Side	0mm	Aux	Laptop	47	6185	8.5	LUX	8.70	9.00	1.072	87.72	1.140	-0.09	0.302	0.369	1.880	2.298
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom Side	0mm	Aux	Laptop	111	6505	8.5	LUX	8.85	9.00	1.035	87.72	1.140	0.11	0.386	0.455	2.260	2.667
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom Side	0mm	Aux	Laptop	143	6665	8.5	LUX	8.75	9.00	1.059	87.72	1.140	0.10	0.258	0.311	1.440	1.738
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom	0mm	Aux	Tablet	15	6025	9	LUX	9.08	10.00	1.236	87.72	1.140	0.01	0.486	0.685	2.510	3.537
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom	0mm	Aux	Tablet	47	6185	9	LUX	9.18	10.00	1.208	87.72	1.140	-0.02	0.433	0.596	2.280	3.140
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom	0mm	Aux	Tablet	111	6505	11.25	LUX	11.28	11.50	1.052	87.72	1.140	0.10	0.799	0.958	4.330	5.193
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom	0mm	Aux	Tablet	143	6665	11.5	LUX	11.64	12.00	1.086	87.72	1.140	0.01	0.691	0.855	3.540	4.383
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom Side	0mm	Aux	Laptop	207	6985	9	ADV	10.25	10.50	1.059	87.72	1.140	0.12	0.555	0.670	2.970	3.586
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom	0mm	Aux	Tablet	207	6985	11	ADV	11.66	12.00	1.081	87.72	1.140	0.07	0.876	1.080	4.570	5.632
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom	0mm	Aux	Tablet	15	6025	9	ADV	9.08	10.00	1.236	87.72	1.140	-0.05	0.619	0.872	3.190	4.495
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom	0mm	Aux	Tablet	47	6185	9	ADV	9.18	10.00	1.208	87.72	1.140	0.05	0.578	0.796	2.950	4.063
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom	0mm	Aux	Tablet	111	6505	11.25	ADV	11.28	11.50	1.052	87.72	1.140	0.00	0.836	1.003	4.280	5.133
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom	0mm	Aux	Tablet	143	6665	11.5	ADV	11.64	12.00	1.086	87.72	1.140	0.01	0.856	1.060	4.250	5.262
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom Side	0mm	MIMO(Main)	Laptop	207	6985	8.75	LUX	9.20	9.50	1.072	87.72	1.140	-0.05	0.666	0.814	3.450	4.216
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom Side	0mm	MIMO(Aux)	Laptop	207	6985	8.75	LUX	8.13	9.50	1.371	87.72	1.140	-0.05	0.568	0.888	3.170	4.955
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom Side	0mm	MIMO(Main)	Laptop	15	6025	8	LUX	8.54	9.00	1.112	87.72	1.140	-0.05	0.462	0.586	2.520	3.195
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom Side	0mm	MIMO(Aux)	Laptop	15	6025	8	LUX	8.12	9.00	1.225	87.72	1.140	0.08	0.397	0.554	2.310	3.226
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom Side	0mm	MIMO(Main)	Laptop	47	6185	8.25	LUX	7.18	9.00	1.521	87.72	1.140	-0.12	0.356	0.617	2.050	3.555
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom Side	0mm	MIMO(Aux)	Laptop	47	6185	8.25	LUX	8.95	9.00	1.012	87.72	1.140	-0.08	0.306	0.353	1.870	2.157
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom Side	0mm	MIMO(Main)	Laptop	111	6505	8.5	LUX	8.14	9.00	1.219	87.72	1.140	-0.14	0.432	0.600	2.430	3.377
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom Side	0mm	MIMO(Aux)	Laptop	111	6505	8.5	LUX	9.00	9.00	1.000	87.72	1.140	0.10	0.371	0.423	2.230	2.542
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom Side	0mm	MIMO(Main)	Laptop	143	6665	9.75	LUX	8.96	9.00	1.009	87.72	1.140	0.04	0.558	0.642	3.060	3.520
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom Side	0mm	MIMO(Aux)	Laptop	143	6665	9.75	LUX	8.21	9.00	1.199	87.72	1.140	-0.14	0.479	0.655	2.800	3.827
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom	0mm	MIMO(Main)	Tablet	207	6985	8.5	LUX	8.76	9.50	1.186	87.72	1.140	0.02	0.223	0.302	1.260	1.704
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom	0mm	MIMO(Aux)	Tablet	207	6985	8.5	LUX	9.20	9.50	1.072	87.72	1.140	0.02	0.349	0.427	1.970	2.407
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom	0mm	MIMO(Main)	Tablet	15	6025	8.5	LUX	8.90	10.00	1.288	87.72	1.140	0.05	0.558	0.819	2.950	4.332
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom	0mm	MIMO(Aux)	Tablet	15	6025	8.5	LUX	9.88	10.00	1.028	87.72	1.140	0.05	0.469	0.550	2.380	2.789
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom	0mm	MIMO(Main)	Tablet	47	6185	8.5	LUX	8.23	10.00	1.503	87.72	1.140	-0.11	0.415	0.711	2.140	3.667
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom	0mm	MIMO(Aux)	Tablet	47	6185	8.5	LUX	9.61	10.00	1.094	87.72	1.140	-0.11	0.348	0.434	1.730	2.158
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom	0mm	MIMO(Main)	Tablet	111	6505	8	LUX	8.80	9.00	1.047	87.72	1.140	0.06	0.226	0.270	1.270	1.516
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom	0mm	MIMO(Aux)	Tablet	111	6505	8	LUX	8.93	9.00	1.016	87.72	1.140	0.06	0.379	0.439	2.000	2.316
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom	0mm	MIMO(Main)	Tablet	143	6665	11	LUX	10.85	12.00	1.303	87.72	1.140	0.12	0.358	0.532	1.780	2.644
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom	0mm	MIMO(Aux)	Tablet	143	6665	11	LUX	11.37	12.00	1.156	87.72	1.140	0.12	0.540	0.712	2.780	3.664
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom Side	0mm	MIMO(Main)	Laptop	207	6985	8.75	ADV	9.16	9.50	1.081	87.72	1.140	0.04	0.743	0.916	3.670	4.523
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom Side	0mm	MIMO(Aux)	Laptop	207	6985	8.75	ADV	8.16	9.50	1.361	87.72	1.140	0.04	0.592	0.919	3.360	5.213
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom Side	0mm	MIMO(Main)	Laptop	15	6025	8	ADV	8.54	9.00	1.112	87.72	1.140	-0.01	0.545	0.691	2.650	3.359
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom Side	0mm	MIMO(Aux)	Laptop	15	6025	8	ADV	8.12	9.00	1.225	87.72	1.140	-0.01	0.396	0.553	3.010	4.203
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom Side	0mm	MIMO(Main)	Laptop	47	6185	8.25	ADV	7.18	9.00	1.521	87.72	1.140	0.09	0.575	0.997	3.350	5.809
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom Side	0mm	MIMO(Aux)	Laptop	47	6185	8.25	ADV	8.95									



FCC SAR TEST REPORT

Report No. : FA622608

	6GHz WLAN	802.11ax-HE160 MCS0	Bottom	0mm	MIMO(Aux)	Tablet	15	6025	8.5	ADV	9.88	10.00	1.028	87.72	1.140	-0.14	0.560	0.656	2.810	3.293
06	6GHz WLAN	802.11ax-HE160 MCS0	Bottom	0mm	MIMO(Main)	Tablet	47	6185	8.5	ADV	8.23	10.00	1.503	87.72	1.140	-0.05	0.665	1.139	3.230	5.534
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom	0mm	MIMO(Aux)	Tablet	47	6185	8.5	ADV	9.61	10.00	1.094	87.72	1.140	-0.05	0.558	0.696	2.640	3.293
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom	0mm	MIMO(Main)	Tablet	111	6505	8	ADV	8.72	9.00	1.067	87.72	1.140	-0.03	0.316	0.384	1.450	1.764
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom	0mm	MIMO(Aux)	Tablet	111	6505	8	ADV	8.76	9.00	1.057	87.72	1.140	-0.03	0.448	0.540	2.280	2.747
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom	0mm	MIMO(Main)	Tablet	143	6665	11	ADV	10.85	12.00	1.303	87.72	1.140	0.10	0.526	0.781	2.500	3.714
	6GHz WLAN	802.11ax-HE160 MCS0	Bottom	0mm	MIMO(Aux)	Tablet	143	6665	11	ADV	11.37	12.00	1.156	87.72	1.140	0.10	0.793	1.045	3.910	5.153

【Bluetooth SAR】

Plot No	Band	Mode	Test Position	Gap (mm)	Antenna	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-Up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	Bluetooth	1Mbps	Bottom Side	0mm	Aux	39	2441	LUX	11.89	12.00	1.026	76.93	1.083	0.09	0.150	0.167
07	Bluetooth	1Mbps	Bottom Side	0mm	Aux	39	2441	ADV	11.89	12.00	1.026	76.93	1.083	-0.09	0.406	0.451
	Bluetooth	1Mbps	Back	0mm	Aux	39	2441	LUX	11.89	12.00	1.026	76.93	1.083	0.00	0.050	0.056
	Bluetooth	1Mbps	Bottom	0mm	Aux	39	2441	LUX	11.89	12.00	1.026	76.93	1.083	-0.06	0.350	0.389
	Bluetooth	1Mbps	Bottom	0mm	Aux	39	2441	ADV	11.89	12.00	1.026	76.93	1.083	-0.04	0.352	0.391

13.2 6GHz PD Test Result

Band	Mode	Test Position	Gap (mm)	Antenna	Ch.	Freq. (MHz)	Average Power (dBm)	Grid Step (A)	iPDn	iPD ratio (≥ -1)	Normal psPD (W/m ²)	Total psPD (W/m ²)
WLAN6GHz	802.11ax-HE160 MCS0	Bottom	2mm	Main	15	6025	9.75	0.0625	0.587	-0.63870811	1.54	2.18
WLAN6GHz	802.11ax-HE160 MCS0	Bottom	10mm	Main	15	6025	9.75	0.25	0.68	-0.63870811	0.913	0.938
WLAN6GHz	802.11ax-HE160 MCS0	Bottom	2mm	Main	207	6985	12.16	0.0625	1.12	0.038950439	1.75	2.62
WLAN6GHz	802.11ax-HE160 MCS0	Bottom	8.59mm	Main	207	6985	12.16	0.25	1.11	0.038950439	0.832	0.872

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Grid Step (A)	Scaling Factor for Measurement Uncertainty	Power Drift (dB)	Normal psPD (W/m ²)	Scaled Normal psPD (W/m ²)	Total psPD (W/m ²)	Scaled Total psPD (W/m ²)
Laptop																			
	WLAN6GHz	802.11ax-HE160 MCS0	Bottom Side	2mm	Main	47	6185	8.51	9.00	1.119	87.34	1.145	0.0625	1.5535	0.17	1.47	2.93	1.6	3.19
	WLAN6GHz	802.11ax-HE160 MCS0	Bottom Side	2mm	Aux	207	6985	10.25	10.50	1.059	87.72	1.140	0.0625	1.5535	0.17	1.73	3.25	1.92	3.60
Tablet																			
	WLAN6GHz	802.11ax-HE160 MCS0	Bottom	2mm	Main	15	6025	9.75	10.00	1.059	87.34	1.145	0.0625	1.5535	-0.15	1.54	2.90	2.18	4.11
01	WLAN6GHz	802.11ax-HE160 MCS0	Bottom	2mm	Aux	207	6985	12.16	12.50	1.081	87.72	1.140	0.0625	1.5535	-0.15	1.75	3.35	2.62	5.02

13.3 Repeated SAR Measurement

No.	Band	Mode	Test Position	Gap (mm)	Antenna	Power State	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-Up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Ratio
1st	2.4GHz WLAN	20M_802.11b 1Mbps	Bottom Side	0.0	Main	Laptop	6	2437	ADV	12.24	12.50	1.062	99.67	1.003	0.11	0.934	0.995	—
2nd	2.4GHz WLAN	20M_802.11b 1Mbps	Bottom Side	0.0	Main	Laptop	6	2437	ADV	12.24	12.50	1.062	99.67	1.003	0.05	0.917	0.977	1.02
1st	5.3GHz WLAN	80M_802.11ac-VHT80 MCS0	Bottom Side	0.0	MIMO	Laptop	58	5290	LUX	8.50	8.50	1.000	91.59	1.092	0.03	1.000	1.092	—
2nd	5.3GHz WLAN	80M_802.11ac-VHT80 MCS0	Bottom Side	0.0	MIMO	Laptop	58	5290	LUX	8.50	8.50	1.000	91.59	1.092	0.02	0.987	1.078	1.01
1st	5.5GHz WLAN	80M_802.11ac-VHT80 MCS0	Bottom Side	0.0	MIMO	Laptop	138	5690	ADV	8.48	8.50	1.005	91.59	1.092	0.17	0.919	1.009	—
2nd	5.5GHz WLAN	80M_802.11ac-VHT80 MCS0	Bottom Side	0.0	MIMO	Laptop	138	5690	ADV	8.48	8.50	1.005	91.59	1.092	0.03	0.910	0.999	1.01
1st	5.8GHz WLAN	40M_802.11n-HT40 MCS0	Bottom	0.0	MIMO	Tablet	151	5755	LUX	8.90	9.50	1.148	95.76	1.044	0.16	0.921	1.104	—
2nd	5.8GHz WLAN	40M_802.11n-HT40 MCS0	Bottom	0.0	MIMO	Tablet	151	5755	LUX	8.90	9.50	1.148	95.76	1.044	0.01	0.920	1.103	1.00
1st	6GHz WLAN	160M_802.11ax-HE160 MCS0	Bottom	0.0	Main	Tablet	111	6505	ADV	11.42	11.50	1.019	87.34	1.145	-0.16	0.902	1.052	—
2nd	6GHz WLAN	160M_802.11ax-HE160 MCS0	Bottom	0.0	Main	Tablet	111	6505	ADV	11.42	11.50	1.019	87.34	1.145	-0.08	0.869	1.014	1.04

General Note:

1. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is $\geq 0.8\text{W/kg}$.
2. Per KDB 865664 D01v01r04, if the ratio among the repeated measurement is ≤ 1.2 and the measured SAR $< 1.45\text{W/kg}$, only one repeated measurement is required.
3. The ratio is the difference in percentage between original and repeated *measured SAR*.
4. All measurement SAR result is scaled-up to account for tune-up tolerance and is compliant.

14. Simultaneous Transmission Analysis

NO.	Simultaneous Transmission Configurations	Body
1.	WLAN2.4GHz Ant Main + WLAN5/6GHz Ant Aux	Yes
2.	WLAN2.4GHz Ant Aux + WLAN5/6GHz Ant Main	Yes
3.	WLAN5/6GHz Ant Main+ WLAN5/6GHz Ant Aux + Bluetooth Ant Aux	Yes

General Note:

1. The Scaled SAR summation is calculated based on the same configuration and test position.
2. Per KDB 447498 D01v06, simultaneous transmission SAR is compliant if,
 - i) Scalar SAR summation < 1g 1.6W/kg or 10g 4.0W/kg.
 - ii) SPLSR = $(SAR1 + SAR2)^{1.5} / (\text{min. separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$, where (x1, y1, z1) and (x2, y2, z2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.
 - iii) If SPLSR ≤ 0.04 for 1g SAR, ≤ 0.1 for 10g SAR, simultaneously transmission SAR measurement is not necessary.
 - iv) Simultaneously transmission SAR measurement, and the reported multi-band 1g SAR < 1.6W/kg or 10g SAR < 4.0W/kg.
 - v) Simultaneously transmission SAR measurement, and the reported multi-band SAR < 1.6W/kg.
 - vi) The SPLSR calculated results please refer to section 14.2.

14.1 Body Exposure Conditions

Exposure Position	1	2	3	4	5	1+4	2+3	1+4	SPLSR	2+3	SPLSR
	WLAN2.4GHz Ant Main 1g SAR (W/kg)	WLAN2.4GHz Ant Aux 1g SAR (W/kg)	WLAN5/6GHz Ant Main 1g SAR (W/kg)	WLAN5/6GHz Ant Aux 1g SAR (W/kg)	Bluetooth Ant Aux 1g SAR (W/kg)	Summed 1g SAR (W/kg)	Summed 1g SAR (W/kg)	Case No.		Case No.	
Bottom Side at 0mm	0.995	0.696	0.995	0.834	0.451	1.829	1.691	Case 1	0.03	Case 2	0.03
Back at 0mm	0.072	0.102	0.178	0.122	0.056	0.194	0.280				
Bottom at 0mm	0.912	1.042	1.015	1.082	0.391	1.994	2.057	Case 4	0.03	Case 5	0.04

Exposure Position	1	2	3	4	1+4	2+4	1+2+4	3+4
	5/6GHz WLAN Main 1g SAR (W/kg)	5/6GHz WLAN Aux 1g SAR (W/kg)	5/6GHz WLAN MIMO 1g SAR (W/kg)	Bluetooth Aux 1g SAR (W/kg)	Summed 1g SAR (W/kg)	Summed 1g SAR (W/kg)	Summed 1g SAR (W/kg)	Summed 1g SAR (W/kg)
Bottom Side at 0mm	0.995	0.834	1.138	0.451	1.446	1.285		1.589
Back at 0mm	0.178	0.122		0.056	0.234	0.178	0.356	
Bottom at 0mm	1.015	1.082	1.142	0.391	1.406	1.473		1.533

14.2 SPLSR Evaluation and Analysis

General Note:

1. $SPLSR = (SAR_1 + SAR_2)^{1.5} / (\text{min. separation distance, mm})$. If $SPLSR \leq 0.04$, simultaneously transmission SAR measurement is not necessary

Case 1	Band	Position	SAR (W/kg)	Gap	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
				(mm)	X	Y	Z				
	WLAN2.4GHz Ant Main	Bottom Side	0.995	0	106.7	-77.9	-177	73.9	1.83	0.03	Not required
	WLAN5/6GHz Ant Aux		0.834	0	109	-4	-177				
Case 2	Band	Position	SAR (W/kg)	Gap	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
				(mm)	X	Y	Z				
	WLAN2.4GHz Ant Aux	Bottom Side	0.696	0	105.5	-9.5	-177	67.8	1.69	0.03	Not required
	WLAN5/6GHz Ant Main		0.995	0	107.8	-77.3	-177				
Case 4	Band	Position	SAR (W/kg)	Gap	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
				(mm)	X	Y	Z				
	WLAN2.4GHz Ant Main	Bottom	0.912	0	-6	91	-177	81.2	1.99	0.03	Not required
	WLAN5/6GHz Ant Aux		1.082	0	0	10	-177				
Case 5	Band	Position	SAR (W/kg)	Gap	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
				(mm)	X	Y	Z				
	WLAN2.4GHz Ant Aux	Bottom	1.042	0	0	6.4	-177	76.2	2.06	0.04	Not required
	WLAN5/6GHz Ant Main		1.015	0	-2.9	82.5	-177				

Test Engineer : Chris Yang

15. Uncertainty Assessment

Declaration of Conformity:

The test results with all measurement uncertainty excluded is presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

The component of uncertainty may generally be categorized according to the methods used to evaluate them. The evaluation of uncertainty by the statistical analysis of a series of observations is termed a Type A evaluation of uncertainty. The evaluation of uncertainty by means other than the statistical analysis of a series of observation is termed a Type B evaluation of uncertainty. Each component of uncertainty, however evaluated, is represented by an estimated standard deviation, termed standard uncertainty, which is determined by the positive square root of the estimated variance.

A Type A evaluation of standard uncertainty may be based on any valid statistical method for treating data. This includes calculating the standard deviation of the mean of a series of independent observations; using the method of least squares to fit a curve to the data in order to estimate the parameter of the curve and their standard deviations; or carrying out an analysis of variance in order to identify and quantify random effects in certain kinds of measurement.

A type B evaluation of standard uncertainty is typically based on scientific judgment using all of the relevant information available. These may include previous measurement data, experience, and knowledge of the behavior and properties of relevant materials and instruments, manufacture's specification, data provided in calibration reports and uncertainties assigned to reference data taken from handbooks. Broadly speaking, the uncertainty is either obtained from an outdoor source or obtained from an assumed distribution, such as the normal distribution, rectangular or triangular distributions indicated in table below.

Uncertainty Distributions	Normal	Rectangular	Triangular	U-Shape
Multi-plying Factor ^(a)	1/k ^(b)	1/√3	1/√6	1/√2

(a) standard uncertainty is determined as the product of the multiplying factor and the estimated range of variations in the measured quantity

(b) κ is the coverage factor

Standard Uncertainty for Assumed Distribution

The combined standard uncertainty of the measurement result represents the estimated standard deviation of the result. It is obtained by combining the individual standard uncertainties of both Type A and Type B evaluation using the usual "root-sum-squares" (RSS) methods of combining standard deviations by taking the positive square root of the estimated variances.

Expanded uncertainty is a measure of uncertainty that defines an interval about the measurement result within which the measured value is confidently believed to lie. It is obtained by multiplying the combined standard uncertainty by a coverage factor. Typically, the coverage factor ranges from 2 to 3. Using a coverage factor allows the true value of a measured quantity to be specified with a defined probability within the specified uncertainty range. For purpose of this document, a coverage factor two is used, which corresponds to confidence interval of about 95 %. The DASY uncertainty Budget is shown in the following tables.

The judgment of conformity in the report is based on the measurement results excluding the measurement uncertainty.

Applicable for SAR Measurements:

Uncertainty Budget (4 MHz - 10 GHz range)							
Error Description	Uncertainty Value (±%)	Probability	Divisor	(Ci) 1g	(Ci) 10g	Standard Uncertainty (1g) (±%)	Standard Uncertainty (10g) (±%)
Measurement System							
Probe Calibration	18.60	N	2	1	1	9.3	9.3
Axial Isotropy	4.70	R	1.732	0.7	0.7	1.9	1.9
Hemispherical Isotropy	9.60	R	1.732	0.7	0.7	3.9	3.9
Linearity	4.70	R	1.732	1	1	2.7	2.7
Modulation Response	4.68	R	1.732	1	1	2.7	2.7
System Detection Limits	1.00	R	1.732	1	1	0.6	0.6
Boundary Effects	2.00	R	1.732	1	1	1.2	1.2
Readout Electronics	0.30	N	1	1	1	0.3	0.3
Response Time	0.00	R	1.732	1	1	0.0	0.0
Integration Time	2.60	R	1.732	1	1	1.5	1.5
RF Ambient Noise	3.00	R	1.732	1	1	1.7	1.7
RF Ambient Reflections	3.00	R	1.732	1	1	1.7	1.7
Probe Positioner	0.40	R	1.732	1	1	0.2	0.2
Probe Positioning	6.70	R	1.732	1	1	3.9	3.9
Post-processing	4.00	R	1.732	1	1	2.3	2.3
Test Sample Related							
Device Holder	3.60	N	1	1	1	3.6	3.6
Test sample Positioning	3.03	N	1	1	1	3.0	3.0
Power Scaling	0.00	R	1.732	1	1	0.0	0.0
Power Drift	5.00	R	1.732	1	1	2.9	2.9
Phantom and Setup							
Phantom Uncertainty	7.60	R	1.732	1	1	4.4	4.4
SAR correction	0.00	R	1.732	1	0.84	0.0	0.0
Liquid Conductivity Repeatability	0.03	N	1	0.78	0.77	0.0	0.0
Liquid Conductivity (target)	5.00	R	1.732	0.78	0.77	2.3	2.2
Liquid Conductivity (mea.)	2.50	R	1.732	0.78	0.77	1.1	1.1
Temp. unc. - Conductivity	3.68	R	1.732	0.78	0.77	1.7	1.6
Liquid Permittivity Repeatability	0.02	N	1	0.23	0.26	0.0	0.0
Liquid Permittivity (target)	5.00	R	1.732	0.23	0.26	0.7	0.8
Liquid Permittivity (mea.)	2.50	R	1.732	0.23	0.26	0.3	0.4
Temp. unc. - Permittivity	0.84	R	1.732	0.23	0.26	0.1	0.1
Combined Std. Uncertainty						14.5%	14.2%
Coverage Factor for 95 %						K=2	K=2
Expanded STD Uncertainty						29.0%	28.4%

Applicable for Power Density Measurements:

Error Description	Uncertainty Value (±dB)	Probability	Divisor	(Ci)	Standard Uncertainty (±dB)
Probe Calibration	0.49	N	1	1	0.49
Probe correction	0.00	R	1.732	1	0.00
Frequency response (BW ≤ 1 GHz)	0.20	R	1.732	1	0.12
Sensor cross coupling	0.00	R	1.732	1	0.00
Isotropy	0.50	R	1.732	1	0.29
Linearity	0.20	R	1.732	1	0.12
Probe scattering	0.00	R	1.732	1	0.00
Probe positioning offset	0.30	R	1.732	1	0.17
Probe positioning repeatability	0.04	R	1.732	1	0.02
Sensor mechanical offset	0.00	R	1.732	1	0.00
Probe spatial resolution	0.00	R	1.732	1	0.00
Field impedance dependance	0.00	R	1.732	1	0.00
Amplitude and phase drift	0.00	R	1.732	1	0.00
Amplitude and phase noise	0.04	R	1.732	1	0.02
Measurement area truncation	0.00	R	1.732	1	0.00
Data acquisition	0.03	N	1	1	0.03
Sampling	0.00	R	1.732	1	0.00
Field reconstruction	2.00	R	1.732	1	1.15
Forward transformation	0.00	R	1.732	1	0.00
Power density scaling	0.00	R	1.732	1	0.00
Spatial averaging	0.10	R	1.732	1	0.06
System detection limit	0.04	R	1.732	1	0.02
Uncertainty terms dependent on the DUT and environmental factors					
Probe coupling with DUT	0.00	R	1.732	1	0.0
Modulation response	0.40	R	1.732	1	0.2
Integration time	0.00	R	1.732	1	0.0
Response time	0.00	R	1.732	1	0.0
Device holder influence	0.10	R	1.732	1	0.1
DUT alignment	0.00	R	1.732	1	0.0
RF ambient conditions	0.04	R	1.732	1	0.0
Ambient reflections	0.04	R	1.732	1	0.0
Immunity / secondary reception	0.00	R	1.732	1	0.0
Drift of the DUT		R	1.732	1	
Combined Std. Uncertainty					1.34
Expanded STD Uncertainty (95%)					2.68

16. References

- [1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [2] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- [3] IEEE Std. 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", Sep 2013
- [4] FCC KDB 248227 D01 v02r02, "SAR Guidance for IEEE 802.11 (WiFi) Transmitters", Oct 2015.
- [5] FCC KDB 447498 D01 v06, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", Oct 2015
- [6] FCC KDB 616217 D04 v01r02, "SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers", Oct 2015
- [7] FCC KDB 865664 D01 v01r04, "SAR Measurement Requirements for 100 MHz to 6 GHz", Aug 2015.
- [8] FCC KDB 865664 D02 v01r02, "RF Exposure Compliance Reporting and Documentation Considerations" Oct 2015.
- [9] IEC/IEEE 62209-1528:2020, "Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Part 1528: Human models, instrumentation, and procedures (Frequency range of 4 MHz to 10 GHz)", Oct. 2020
- [10] SPEAG DASY6 System Handbook
- [11] SPEAG DASY6 Application Note (Interim Procedure for Device Operation at 6GHz-10GHz)