FCC RF Test Report

APPLICANT	:	ASUSTeK COMPUTER INC.
EQUIPMENT	:	ASUS Tablet
BRAND NAME	:	ASUS
MODEL NAME	:	T100 Chi
FCC ID	:	MSQ-T100CHI
STANDARD	:	FCC Part 15 Subpart C §15.247
CLASSIFICATION	:	(DTS) Digital Transmission System

The product was received on Oct. 21, 2014 and testing was completed on Dec. 01, 2014. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager

Testing Laboratory
1190

SPORTON INTERNATIONAL INC.
No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

TABLE OF CONTENTS

REVISION HISTORY **3**

SUMMARY OF TEST RESULT **4**

1 GENERAL DESCRIPTION **5**

1.1 Applicant 5
1.2 Manufacturer 5
1.3 Product Feature of Equipment Under Test 5
1.4 Product Specification subjective to this standard 6
1.5 Modification of EUT 6
1.6 Testing Location 7
1.7 Applicable Standards 7

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **8**

2.1 Carrier Frequency and Channel 8
2.2 Pre-Scanned RF Power 9
2.3 Test Mode 10
2.4 Connection Diagram of Test System 11
2.5 Support Unit used in test configuration and system 12
2.6 EUT Operation Test Setup 12
2.7 Measurement Results Explanation Example 12

3 TEST RESULT **13**

3.1 6dB and 99% Bandwidth Measurement 13
3.2 Peak Output Power Measurement 15
3.3 Power Spectral Density Measurement 18
3.4 Conducted Band Edges and Spurious Emission Measurement 21
3.5 Radiated Band Edges and Spurious Emission Measurement 34
3.6 AC Conducted Emission Measurement 38
3.7 Antenna Requirements 42

4 LIST OF MEASURING EQUIPMENT **44**

5 UNCERTAINTY OF EVALUATION **45**

APPENDIX A. TEST RESULT OF RADIATED TEST RESULTS

APPENDIX B. SETUP PHOTOGRAPHS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR4O2114C	Rev. 01	Initial issue of report	Dec. 15, 2014

SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	RSS-210 A8.2(a)	6dB Bandwidth	≥ 0.5MHz	Pass	-
3.1	-	RSS-Gen 4.6.1	99% Bandwidth	-	Pass	-
3.2	15.247(b)	RSS-210 A8.4	Power Output Measurement	≤ 30dBm	Pass	-
3.3	15.247(e)	RSS-210 A8.2(b)	Power Spectral Density	≤ 8dBm/3kHz	Pass	-
3.4	15.247(d)	RSS-210 A8.5	Conducted Band Edges	≤ 20dBc	Pass	-
			Conducted Spurious Emission		Pass	-
3.5	15.247(d)	RSS-210 A8.5	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 4.91 dB at 2483.520 MHz
0	15.207	RSS-Gen 7.2.4	AC Conducted Emission	15.207(a)	Pass	Under limit 11.00 dB at 14.814 MHz
3.7	15.203 & 15.247(b)	RSS-210 A8.4	Antenna Requirement	N/A	Pass	-

1 General Description

1.1 Applicant

ASUSTeK COMPUTER INC.
4F, No. 150, LI-TE RD., PEITOU, TAIPEI 112, TAIWAN

1.2 Manufacturer

1. **TECH-COM (SHANGHAI) COMPUTER CO., LTD.**
   68 SANZHUANG RD, SONGJIANG EXPORT PROCESSING ZONE, SHANGHAI 201613, CHINA

2. **WISTRON INFOCOMM (SUNSHAN) CO., LTD.**
   FIRST AVE, KUNSHAN INTEGRATED FREE TRADE ZONE, KUNSHAN, JIANGSU, CHINA

3. **WISTRON INFOCOMM (CHONGQING) CO., LTD.**
   18-9 BAOHONG AVENUE WANGJIA SUB-DISTRICT YUBEI DISTRICT CHONGQING 401120 CHINA

4. **COTEK ELECTRONICS (SUZHOU) CO., LTD.**
   288 MAYUN RD, NEW DISTRICT SUZHOU, JIANGSU 215011, CHINA

5. **TECH-FRONT (CHONGQING) COMPUTER CO., LTD.**
   18 ZONGBAO ROAD, SHAPINGBA DISTRICT, CHONGQING, CHINA

6. **DIGITEK (CHONGQING) LTD**
   B01, SECTION C, AIRPORT FUNCTION ZONE, LIANGLU CUNTAN FREE TRADE PORT AREA, YUBEI DISTRICT CHONGQING CITY, CHINA

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	ASUS Tablet
Brand Name	ASUS
Model Name	T100 Chi
FCC ID	MSQ-T100CHI
EUT supports Radios application	WLAN 11b/g/n HT20 WLAN 11a/n HT20/HT40 Bluetooth v4.0 EDR/LE
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification subjective to this standard

<table>
<tr><th colspan="2">Product Specification subjective to this standard</th></tr>
<tr><td>Tx/Rx Channel Frequency Range</td><td>802.11b/g/n : 2412 MHz ~ 2462 MHz</td></tr>
<tr><td>Maximum Output Power to antenna</td><td>802.11b : 19.62 dBm (0.0916 W)
802.11g : 23.42 dBm (0.2198 W)
802.11n HT20 : 24.92 dBm (0.3105 W)</td></tr>
<tr><td>99% Occupied Bandwidth</td><td>802.11b : 11.50MHz
802.11g : 17.15MHz
802.11n HT20 : 18.00MHz</td></tr>
<tr><td>Antenna Type</td><td><Ant 1>
802.11b/g/n : PIFA Antenna type with gain 1.60 dBi
<Ant 2>
802.11b/g/n : PIFA Antenna type with gain 1.57 dBi</td></tr>
<tr><td>Type of Modulation</td><td>802.11b : DSSS (DBPSK / DQPSK / CCK)
802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)</td></tr>
<tr><td>Antenna Function for Transmitter</td><td>
<table>
<tr><th></th><th>Chain
Port 0
Ant. 1</th><th>Chain
Port 1
Ant. 2</th></tr>
<tr><td>802.11 b</td><td>V</td><td>-</td></tr>
<tr><td>802.11 g</td><td>V</td><td>-</td></tr>
<tr><td>802.11 n
MIMO</td><td>V</td><td>V</td></tr>
</table>
</td></tr>
</table>

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	**Sporton Site No.**	
	TH02-HY	CO05-HY

Note: The test site complies with ANSI C63.4 2009 requirement.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No. 13-1&14-1, Lane 19, Wen 33rd St. Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-318-0787/+886-3-318-0792 FAX: +886-3-318-0287	
Test Site No.	**Sporton Site No.**	**FCC Registration No.**
	03CH09-HY	213289

Note: The test site complies with ANSI C63.4 2009 requirement.

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02
- FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ANSI C63.10-2009

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.

2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.

The final configuration from all the combinations and the worst-case data rates were investigated by measuring the maximum power across all the data rates and modulation modes under section 2.2.

Based on the worst configuration found above, the RF power setting is set individually to meet FCC compliance limit for the final conducted and radiated tests shown in section 2.3.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437		

2.2 Pre-Scanned RF Power

Preliminary tests were performed in different data rate and data rate associated with the highest power were chosen for full test shown in the following tables.

<Ant. 1>

802.11b				
Data Rate (MHz)	**1M bps**	**2M bps**	**5.5M bps**	**11M bps**
Peak Power (dBm)	**19.62**	19.60	19.56	19.47

802.11g								
Data Rate (MHz)	**6M bps**	**9M bps**	**12M bps**	**18M bps**	**24M bps**	**36M bps**	**48M bps**	**54M bps**
Peak Power (dBm)	**23.42**	23.23	22.98	22.73	22.68	22.55	22.97	22.92

MIMO <Ant. 1+2>

2.4GHz 802.11n HT20								
Data Rate (MHz)	**MCS8**	**MCS9**	**MCS10**	**MCS11**	**MCS12**	**MCS13**	**MCS14**	**MCS15**
Peak Power (dBm)	**24.92**	24.42	24.75	24.90	24.73	24.80	24.25	24.59

Note: MIMO Ant. 1+2 is a calculated result from sum of the power MIMO Ant. 1 and MIMO Ant. 2.

2.3 Test Mode

Final results of test modes, data rates and test channels are shown as following table.

Test Cases				
	Test Items	Mode	Data Rate	Test Channel
Conducted TCs	6dB and 99% BW Power Spectral Density	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	6.5 Mbps	1/6/11
	Output Power	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	6.5 Mbps	1/6/11
	Conducted Band Edge	802.11b	1 Mbps	1/11
		802.11g	6 Mbps	1/11
		802.11n HT20	6.5 Mbps	1/11
	Conducted Spurious Emission	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	6.5 Mbps	1/6/11
Radiated TCs	Radiated Band Edge	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	6.5 Mbps	1/6/11
	Radiated Spurious Emission	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	6.5 Mbps	1/6/11

Test Cases	
AC Conducted Emission	Mode 1 :WLAN (2.4GHz) Link + Bluetooth Link + MPEG4 + Camera + H Patten + HDMI Cable + Earphone + USB HD + SD Card + Docking

2.4 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>



2.5 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	D-Link	DIR-628	KA2DIR628A2	N/A	Unshielded, 1.8 m
2.	USB3.0 HD	Pqi	H568V	FCC DoC	Shielded, 0.5 m	N/A
3.	iPod Earphone	Apple	N/A	Verification	Unshielded, 1.0 m	N/A
4.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A

2.6 EUT Operation Test Setup

For WLAN function, programmed RF utility, “cmd” installed in the notebook make the EUT provide functions like channel selection and power level for continuous transmitting and receiving signals.

2.7 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 4.2 + 10 = 14.2 (dB)

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v03r02.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) = 1MHz and set the Video bandwidth (VBW) = 3MHz.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Test Band :	2.4GHz	Temperature :	21~25℃
Test Engineer :	Osolemio Chang	Relative Humidity :	51~54%

Mod.	Data Rate	N_{TX}	Channel	Freq. (MHz)	99% Bandwidth (MHz)		6dB Bandwidth (MHz)		6dB Bandwidth Min. Limit (MHz)	Pass/Fail
					Ant. 1	Ant. 2	Ant. 1	Ant. 2		
11b	1Mbps	1	1	2412	11.50	-	8.08	-	0.5	Pass
11b	1Mbps	1	6	2437	11.50	-	8.08	-	0.5	Pass
11b	1Mbps	1	11	2462	11.50	-	8.56	-	0.5	Pass
11g	6Mbps	1	1	2412	17.15	-	15.72	-	0.5	Pass
11g	6Mbps	1	6	2437	17.15	-	16.04	-	0.5	Pass
11g	6Mbps	1	11	2462	17.15	-	15.72	-	0.5	Pass
HT20	MCS0	2	1	2412	17.95	17.95	15.84	16.32	0.5	Pass
HT20	MCS0	2	6	2437	17.95	17.95	15.78	16.36	0.5	Pass
HT20	MCS0	2	11	2462	17.95	18.00	15.72	16.32	0.5	Pass

Minimum 6dB Bandwidth



Date: 1.DEC.2014 21:10:59

Maximum 99% Occupied Bandwidth



Date: 1.DEC.2014 22:34:53

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Peak Output Power Measurement

3.2.1 Limit of Peak Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna with directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v03r02.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.
5. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Test Band :	2.4GHz	Temperature :	21~25℃
Test Engineer :	Osolemio Chang	Relative Humidity :	51~54%

Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	Peak Conducted Power (dBm)			Max. Limit (dBm)		DG (dBi)		Pass/Fail
					Ant. 1	Ant. 2	SUM	Ant. 1	Ant. 2	Ant. 1	Ant. 2	
11b	1Mbps	1	1	2412	19.62	-	-	30.00	30.00	1.60	1.57	Pass
11b	1Mbps	1	6	2437	19.35	-		30.00	30.00	1.60	1.57	Pass
11b	1Mbps	1	11	2462	19.06	-		30.00	30.00	1.60	1.57	Pass
11g	6Mbps	1	1	2412	23.42	-		30.00	30.00	1.60	1.57	Pass
11g	6Mbps	1	6	2437	22.88	-		30.00	30.00	1.60	1.57	Pass
11g	6Mbps	1	11	2462	22.25	-		30.00	30.00	1.60	1.57	Pass
HT20	MCS0	2	1	2412	21.84	21.97	24.92	30.00		4.60		Pass
HT20	MCS0	2	6	2437	21.81	21.83	24.83	30.00		4.60		Pass
HT20	MCS0	2	11	2462	21.25	21.87	24.58	30.00		4.60		Pass

Note: Measured power (dBm) has offset with cable loss.

3.2.6 Test Result of Average output Power (Reporting Only)

Test Band :	2.4GHz	Temperature :	21~25℃
Test Engineer :	Osolemio Chang	Relative Humidity :	51~54%

Mod.	Data Rate	N_{TX}	Channel	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)		
					Ant. 1	Ant. 2	Ant. 1	Ant. 2	Sum Power
11b	1Mbps	1	1	2412	0.04	-	16.34	-	-
11b	1Mbps	1	6	2437	0.04	-	15.95	-	
11b	1Mbps	1	11	2462	0.04	-	15.72	-	
11g	6Mbps	1	1	2412	0.25	-	13.78	-	
11g	6Mbps	1	6	2437	0.25	-	12.88	-	
11g	6Mbps	1	11	2462	0.25	-	12.51	-	
HT20	MCS0	2	1	2412	0.42	0.42	12.41	12.95	15.70
HT20	MCS0	2	6	2437	0.42	0.42	12.24	12.64	15.45
HT20	MCS0	2	11	2462	0.42	0.42	11.91	12.60	15.28

Note: Measured power (dBm) has offset with cable loss and duty factor.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

   If measurements performed using method (2) plus 10 log (N) exceeds the emission limit, the test should choose method (1) before declaring that the device fails the emission limit.

   Method (1): Measure and sum the spectra across the outputs.

   The total final Power Spectral Density is from a device with 2 transmitter outputs. The spectrum measurements of the individual outputs are all performed with the same span and number of points, the spectrum value in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 to obtain the value for the first frequency bin of the summed spectrum.

   Method (2): Measure and add 10 log (N) dB, where N is the number of outputs. (N=2)

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Test Band :	2.4GHz	Temperature :	21~25℃
Test Engineer :	Osolemio Chang	Relative Humidity :	51~54%

Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	Peak Power Density (dBm/3kHz)			Max. Limit (dBm/3kHz)		DG (dBi)		Pass/Fail
					Ant. 1	Ant. 2	Worst +10log(2)	Ant. 1	Ant. 2	Ant. 1	Ant. 2	
11b	1Mbps	1	1	2412	-6.01	-	-	8.00	8.00	1.60	1.57	Pass
11b	1Mbps	1	6	2437	-6.00	-		8.00	8.00	1.60	1.57	Pass
11b	1Mbps	1	11	2462	-6.69	-		8.00	8.00	1.60	1.57	Pass
11g	6Mbps	1	1	2412	-11.89	-		8.00	8.00	1.60	1.57	Pass
11g	6Mbps	1	6	2437	-10.76	-		8.00	8.00	1.60	1.57	Pass
11g	6Mbps	1	11	2462	-11.45	-		8.00	8.00	1.60	1.57	Pass
HT20	MCS0	2	1	2412	-13.26	-11.82	-8.81	8.00		4.60		Pass
HT20	MCS0	2	6	2437	-12.82	-12.65	-9.64	8.00		4.60		Pass
HT20	MCS0	2	11	2462	-12.50	-12.33	-9.32	8.00		4.60		Pass

Note: Measured power density (dBm) has offset with cable loss.

Worst Case Power Density (dBm/3kHz)



Date: 1.DEC.2014 21:18:42

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Number of TX = 1, Ant. 1 (Measured)

Number of TX	1	**Ant. :**	1
Test Mode :	802.11b	**Temperature :**	21~25℃
Test Band :	2.4GHz Low	**Relative Humidity :**	51~54%
Test Channel :	01	**Test Engineer :**	Osolemio Chang

WLAN 802.11b Channel 01

100kHz PSD reference Level



Date: 1.DEC.2014 21:13:05

Low Channel Plot



Date: 1.DEC.2014 21:13:22

Spurious Emission 30MHz~3GHz



Date: 1.DEC.2014 21:14:42

Spurious Emission 2GHz~25GHz



Date: 1.DEC.2014 21:15:00

Number of TX :	1	**Ant. :**	1
Test Mode :	802.11b	**Temperature :**	21~25℃
Test Band :	2.4GHz Mid	**Relative Humidity :**	51~54%
Test Channel :	06	**Test Engineer :**	Osolemio Chang

WLAN 802.11b Channel 06

100kHz PSD reference Level



Date: 1.DEC.2014 21:20:21

Spurious Emission 30MHz~3GHz



Date: 1.DEC.2014 21:22:27

Spurious Emission 2GHz~25GHz



Date: 1.DEC.2014 21:22:45

Number of TX :	1	**Ant. :**	1
Test Mode :	802.11b	**Temperature :**	21~25℃
Test Band :	2.4GHz High	**Relative Humidity :**	51~54%
Test Channel :	11	**Test Engineer :**	Osolemio Chang

WLAN 802.11b Channel 11

100kHz PSD reference Level



Date: 1.DEC.2014 21:27:41

High Channel Plot



Date: 1.DEC.2014 21:32:11

Spurious Emission 30MHz~3GHz



Date: 1.DEC.2014 21:33:52

Spurious Emission 2GHz~25GHz



Date: 1.DEC.2014 21:34:10

Number of TX :	1	**Ant. :**	1
Test Mode :	802.11g	**Temperature :**	21~25℃
Test Band :	2.4GHz Low	**Relative Humidity :**	51~54%
Test Channel :	01	**Test Engineer :**	Osolemio Chang

WLAN 802.11g Channel 01

100kHz PSD reference Level



Date: 1.DEC.2014 21:49:11

Low Channel Plot



Date: 1.DEC.2014 21:50:00

Spurious Emission 30MHz~3GHz



Date: 1.DEC.2014 21:50:50

Spurious Emission 2GHz~25GHz



Date: 1.DEC.2014 21:51:08

Number of TX :	1	**Ant. :**	1
Test Mode :	802.11g	**Temperature :**	21~25℃
Test Band :	2.4GHz Mid	**Relative Humidity :**	51~54%
Test Channel :	06	**Test Engineer :**	Osolemio Chang

WLAN 802.11g Channel 06

100kHz PSD reference Level



Date: 1.DEC.2014 21:59:28

Spurious Emission 30MHz~3GHz



Date: 1.DEC.2014 21:59:57

Spurious Emission 2GHz~25GHz



Date: 1.DEC.2014 22:00:15

Number of TX :	1	**Ant. :**	1
Test Mode :	802.11g	**Temperature :**	21~25℃
Test Band :	2.4GHz High	**Relative Humidity :**	51~54%
Test Channel :	11	**Test Engineer :**	Osolemio Chang

WLAN 802.11g Channel 11

100kHz PSD reference Level



Date: 1.DEC.2014 22:05:38

High Channel Plot



Date: 1.DEC.2014 22:06:02

Spurious Emission 30MHz~3GHz



Date: 1.DEC.2014 22:06:28

Spurious Emission 2GHz~25GHz



Date: 1.DEC.2014 22:06:46

Number of TX = 2, Ant. 1 (Measured)

Number of TX :	2	**Ant. :**	1
Test Mode :	802.11n HT20	**Temperature :**	21~25℃
Test Band :	2.4GHz Low	**Relative Humidity :**	51~54%
Test Channel :	01	**Test Engineer :**	Osolemio Chang

WLAN 802.11n HT20 Channel 01

100kHz PSD reference Level



Date: 1.DEC.2014 22:15:21

Low Channel Plot



Date: 1.DEC.2014 22:15:55

Spurious Emission 30MHz~3GHz



Date: 1.DEC.2014 22:18:11

Spurious Emission 2GHz~25GHz



Date: 1.DEC.2014 22:18:29

Number of TX :	2	**Ant. :**	1
Test Mode :	802.11n HT20	**Temperature :**	21~25℃
Test Band :	2.4GHz Mid	**Relative Humidity :**	51~54%
Test Channel :	06	**Test Engineer :**	Osolemio Chang

WLAN 802.11n HT20 Channel 06

100kHz PSD reference Level



Date: 1.DEC.2014 22:22:38

Spurious Emission 30MHz~3GHz



Date: 1.DEC.2014 22:23:59

Spurious Emission 2GHz~25GHz



Date: 1.DEC.2014 22:24:17

Number of TX :	2	**Ant. :**	1
Test Mode :	802.11n HT20	**Temperature :**	21~25℃
Test Band :	2.4GHz High	**Relative Humidity :**	51~54%
Test Channel :	11	**Test Engineer :**	Osolemio Chang

WLAN 802.11n HT20 Channel 11

100kHz PSD reference Level



Date: 1.DEC.2014 22:28:14

High Channel Plot



Date: 1.DEC.2014 22:28:34

Spurious Emission 30MHz~3GHz



Date: 1.DEC.2014 22:29:16

Spurious Emission 2GHz~25GHz



Date: 1.DEC.2014 22:29:34

Number of TX = 2, Ant. 2 (Measured)

Number of TX :	2	**Ant. :**	2
Test Mode :	802.11n HT20	**Temperature :**	21~25℃
Test Band :	2.4GHz Low	**Relative Humidity :**	51~54%
Test Channel :	01	**Test Engineer :**	Osolemio Chang

WLAN 802.11n HT20 Channel 01

100kHz PSD reference Level



Date: 1.DEC.2014 22:46:12

Low Channel Plot



Date: 1.DEC.2014 22:46:31

Spurious Emission 30MHz~3GHz



Date: 1.DEC.2014 22:47:01

Spurious Emission 2GHz~25GHz



Date: 1.DEC.2014 22:47:19

Number of TX :	2	**Ant. :**	2
Test Mode :	802.11n HT20	**Temperature :**	21~25℃
Test Band :	2.4GHz Mid	**Relative Humidity :**	51~54%
Test Channel :	06	**Test Engineer :**	Osolemio Chang

WLAN 802.11n HT20 Channel 06

100kHz PSD reference Level



Date: 1.DEC.2014 22:38:14

Spurious Emission 30MHz~3GHz



Date: 1.DEC.2014 22:41:49

Spurious Emission 2GHz~25GHz



Date: 1.DEC.2014 22:42:07

Number of TX :	2	**Ant. :**	2
Test Mode :	802.11n HT20	**Temperature :**	21~25℃
Test Band :	2.4GHz High	**Relative Humidity :**	51~54%
Test Channel :	11	**Test Engineer :**	Osolemio Chang

WLAN 802.11n HT20 Channel 11

100kHz PSD reference Level



Date: 1.DEC.2014 22:33:26

High Channel Plot



Date: 1.DEC.2014 22:33:46

Spurious Emission 30MHz~3GHz



Date: 1.DEC.2014 22:34:14

Spurious Emission 2GHz~25GHz



Date: 1.DEC.2014 22:34:31

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedure

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
   (1) Span shall wide enough to fully capture the emission being measured;
   (2) Set RBW=100 kHz for f < 1 GHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
   (3) Set RBW = 1 MHz, VBW= 3MHz for f ≥ 1 GHz for peak measurement.
   For average measurement:
   - VBW = 10 Hz, when duty cycle is no less than 98 percent.
   - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

Antenna	Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting
1	802.11b	99.04	-	-	10Hz
1	802.11g	94.5	2060	0.49	1kHz
1+2	2.4GHz 802.11n HT20 for Ant 1	90.83	990	1.01	3kHz
1+2	2.4GHz 802.11n HT20 for Ant 2	90.83	990	1.01	3kHz

3.5.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix A of this report.

3.5.7 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix A of this report.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dBμV)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



AMN = Artificial mains network (LISN)
AE = Associated equipment
EUT = Equipment under test
ISN = Impedance stabilization network

3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	**Temperature :**	20~22℃
Test Engineer :	Kai-Chun Chu	**Relative Humidity :**	46~48%
Test Voltage :	120Vac / 60Hz	**Phase :**	Line
Function Type :	WLAN (2.4GHz) Link + Bluetooth Link + MPEG4 + Camera + H Patten + HDMI Cable + Earphone + USB HD + SD Card + Docking		



Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.190000	49.5	Off	L1	19.5	14.5	64.0
0.254000	41.6	Off	L1	19.5	20.0	61.6
0.326000	37.6	Off	L1	19.5	22.0	59.6
0.518000	34.6	Off	L1	19.5	21.4	56.0
3.054000	33.4	Off	L1	19.6	22.6	56.0
10.134000	41.3	Off	L1	19.7	18.7	60.0
13.918000	43.1	Off	L1	19.8	16.9	60.0
14.926000	43.7	Off	L1	19.9	16.3	60.0
15.510000	42.7	Off	L1	19.9	17.3	60.0

Final Result : Average

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.190000	35.1	Off	L1	19.5	18.9	54.0
0.254000	31.6	Off	L1	19.5	20.0	51.6
0.326000	29.5	Off	L1	19.5	20.1	49.6
0.518000	25.9	Off	L1	19.5	20.1	46.0
3.054000	21.5	Off	L1	19.6	24.5	46.0
10.134000	29.9	Off	L1	19.7	20.1	50.0
13.918000	35.2	Off	L1	19.8	14.8	50.0
14.926000	36.0	Off	L1	19.9	14.0	50.0
15.510000	35.5	Off	L1	19.9	14.5	50.0

Test Mode :	Mode 1	**Temperature :**	20~22℃
Test Engineer :	Kai-Chun Chu	**Relative Humidity :**	46~48%
Test Voltage :	120Vac / 60Hz	**Phase :**	Neutral
Function Type :	WLAN (2.4GHz) Link + Bluetooth Link + MPEG4 + Camera + H Patten + HDMI Cable + Earphone + USB HD + SD Card + Docking		



Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.190000	47.4	Off	N	19.5	16.6	64.0
0.262000	41.8	Off	N	19.5	19.6	61.4
0.934000	33.0	Off	N	19.5	23.0	56.0
2.502000	32.4	Off	N	19.5	23.6	56.0
9.694000	44.0	Off	N	19.7	16.0	60.0
13.142000	45.6	Off	N	19.8	14.4	60.0
14.006000	47.8	Off	N	19.8	12.2	60.0
14.814000	49.0	Off	N	19.9	11.0	60.0
15.702000	45.8	Off	N	19.9	14.2	60.0

Final Result : Average

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.190000	33.9	Off	N	19.5	20.1	54.0
0.262000	29.4	Off	N	19.5	22.0	51.4
0.934000	23.7	Off	N	19.5	22.3	46.0
2.502000	23.6	Off	N	19.5	22.4	46.0
9.694000	33.4	Off	N	19.7	16.6	50.0
13.142000	36.7	Off	N	19.8	13.3	50.0
14.006000	38.2	Off	N	19.8	11.8	50.0
14.814000	38.9	Off	N	19.9	11.1	50.0
15.702000	35.4	Off	N	19.9	14.6	50.0

3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting Antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the Antenna exceeds 6 dBi. The use of a permanently attached Antenna or of an Antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

For CDD and beamforming transmissions, directional gain is calculated as

$$DirectionalGain = 10 \cdot \log\left[\frac{\sum_{j=1}^{N_{SS}}\left\{\sum_{k=1}^{N_{ANT}} g_{j,k}\right\}^2}{N_{ANT}}\right]$$

where

Each antenna is driven by no more than one spatial stream;

N_{SS} = the number of independent spatial streams of data;

N_{ANT} = the total number of antennas

$g_{j,k} = 10^{G_k/20}$ if the kth antenna is being fed by spatial stream j, or zero if it is not;

G_k is the gain in dBi of the kth antenna.

The EUT supports CDD mode and beamforming.

The power and PSD limit should be modified if the directional gain of EUT is over 6 dBi,

The directional gain “DG” is calculated as following table.

	Ant. 1 (dBi)	Ant. 2 (dBi)	DG for Power (dBi)	DG for PSD (dBi)	Power Limit Reduction (dB)	PSD Limit Reduction (dB)
2.4 GHz	1.60	1.57	4.60	4.60	0.00	0.00

Power Limit Reduction = DG(Power) – 6dBi, (min = 0)

PSD Limit Reduction = DG(PSD) – 6dBi, (min = 0)

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz~40GHz	Jun. 09, 2014	Nov. 26, 2014 ~ Dec. 01, 2014	Jun. 08, 2015	Conducted (TH02-HY)
Power Meter	Anritsu	ML2495A	1036004	300MHz~40GHz	Aug. 09, 2014	Nov. 26, 2014 ~ Dec. 01, 2014	Aug. 08, 2015	Conducted (TH02-HY)
Power Sensor	Anritsu	MA2411B	1027253	300MHz~40GHz	Aug. 09, 2014	Nov. 26, 2014 ~ Dec. 01, 2014	Aug. 08, 2015	Conducted (TH02-HY)
EMI Test Receiver	Agilent	N9038A	MY53290053	20Hz to 26.5GHz	Jan. 08, 2014	Nov. 28, 2014 ~ Nov. 29, 2014	Jan. 07, 2015	Radiation (03CH09-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Jul. 28, 2014	Nov. 28, 2014 ~ Nov. 29, 2014	Jul. 27, 2016	Radiation (03CH09-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170251	15GHz- 40GHz	Oct. 02, 2014	Nov. 28, 2014 ~ Nov. 29, 2014	Oct. 01, 2015	Radiation (03CH09-HY)
Double Ridged Guide Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1241	1GHz ~ 18GHz	Apr. 16, 2014	Nov. 28, 2014 ~ Nov. 29, 2014	Apr. 15, 2015	Radiation (03CH09-HY)
Bilog Antenna	TESEQ	CBL 6111D	37059	30MHz ~ 1GHz	Jan. 23, 2014	Nov. 28, 2014 ~ Nov. 29, 2014	Jan. 22, 2015	Radiation (03CH09-HY)
Preamplifier	EMEC	EM01M06G	60584	100MHz ~ 6GHz	Jul. 15, 2014	Nov. 28, 2014 ~ Nov. 29, 2014	Jul. 14, 2015	Radiation (03CH09-HY)
Preamplifier	EMCI	EMC051845	SN980048	1GHz ~ 18GHz	Jul. 17, 2014	Nov. 28, 2014 ~ Nov. 29, 2014	Jul. 16, 2015	Radiation (03CH09-HY)
Preamplifier	MITEQ	JS44-18004000-33-8P	1840917	18GHz~40GHz	Jun. 09, 2014	Nov. 28, 2014 ~ Nov. 29, 2014	Jun. 08, 2015	Radiation (03CH09-HY)
Preamplifier	Sonoma-Instrument	310 N	187282	10MHz~1GHz	Apr. 28, 2014	Nov. 28, 2014 ~ Nov. 29, 2014	Apr. 27, 2015	Radiation (03CH09-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100057	9kHz~40GHz	Oct. 17, 2014	Nov. 28, 2014 ~ Nov. 29, 2014	Oct. 16, 2015	Radiation (03CH09-HY)
Turn Table	ChainTek	T-200S	1308028	0~360 deg	N/A	Nov. 28, 2014 ~ Nov. 29, 2014	N/A	Radiation (03CH09-HY)
Antenna Mast	ChainTek	MBS-400	1308049	1m~4m	N/A	Nov. 28, 2014 ~ Nov. 29, 2014	N/A	Radiation (03CH09-HY)
EMI Test Receiver	Rohde & Schwarz	ESCS 30	100356	9kHz ~ 2.75GHz	Nov. 12, 2014	Nov. 26, 2014	Nov. 11, 2015	Conduction (CO05-HY)
LISN (for auxiliary equipment)	Rohde & Schwarz	ENV216	100081	9kHz ~ 30MHz	Dec. 12, 2013	Nov. 26, 2014	Dec. 11, 2014	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz ~ 30MHz	Dec. 04, 2013	Nov. 26, 2014	Dec. 03, 2014	Conduction (CO05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Nov. 26, 2014	N/A	Conduction (CO05-HY)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.26

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.7