

Appendix D. SAR Test Setup Photos


Head Exposure Condition



Right Cheek, Test Separation 0 mm



Right Tilted, Test Separation 0 mm



Left Cheek, Test Separation 0 mm



Left Tilted, Test Separation 0 mm



**Left Cheek with AeroActive cooler,
Test Separation 0 mm**

Hotspot Exposure Condition



Front, Test Separation 10 mm



Back, Test Separation 10 mm



Left Side, Test Separation 10 mm



Right Side, Test Separation 10 mm



Top Side, Test Separation 10 mm



Bottom Side, Test Separation 10 mm



**Left Side with AeroActive cooler,
Test Separation 10 mm**

Body-worn Exposure Condition



Front, Test Separation 15 mm



Back, Test Separation 15 mm



**Back with AeroActive cooler,
Test Separation 15 mm**

Product Specific 10g SAR



Front, Test Separation 0 mm




Back, Test Separation 0 mm



Left Side, Test Separation 0 mm



Right Side, Test Separation 0 mm



Top Side, Test Separation 0 mm




Bottom Side, Test Separation 0 mm



**Back with AeroActive cooler,
Test Separation 0 mm**

Antenna Location



Antenna	Support Band
Antenna 0	GSM: 850<TX/RX> WCDMA: B5 <TX/RX> LTE: B5/12/17/26/71 <TX/RX> NR: n5/n12/n26/n71 <TX/RX>
Antenna 1	GSM: 1900<TX/RX> WCDMA: B2/4<TX/RX> LTE: B2/4/7/25/30/66/38/41 <TX/RX> NR: n2/n7/n25/n30/n66/n41 <TX/RX>
Antenna 2	WCDMA: B2/4/5<TX/RX> LTE: B2/4/5/7/12/17/25/26/30/66/71/38/41 <TX/RX> NR: n2/n5/n7/n12/n25/n30/n26/n66/n71/n41 <TX/RX>
Antenna 4	WLAN 2.4GHz/5GHz/6GHz/Bluetooth chain 1 <TX/RX>
Antenna 5	WLAN 2.4GHz/5GHz/6GHz/Bluetooth chain 0 <TX/RX>
Antenna 6	WLAN 2.4GHz/5GHz/6GHz/Bluetooth chain 1 <TX/RX>
Antenna 7	LTE: B2/4/25/30/66/48 <TX/RX> NR: n2/n25/n30/n38/n41/n48/n66/n77 <TX/RX>
Antenna 8	LTE: B48<TX/RX> NR: n38/n41/n48/n77 <TX/RX>
Antenna 9	LTE: B48<TX/RX> NR: n48/n77 <TX/RX>
Antenna 10	LTE: B48<TX/RX> NR: n48/n77 <TX/RX>
NFC Antenna	NFC<TX/RX>

Distance of the Antenna to the EUT surface/edge						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
Antenna 0	≤ 25mm	≤ 25mm	>25mm	≤ 25mm	≤ 25mm	≤ 25mm
Antenna 1	≤ 25mm	≤ 25mm	>25mm	≤ 25mm	>25mm	≤ 25mm
Antenna 2	≤ 25mm	≤ 25mm	≤ 25mm	>25mm	>25mm	≤ 25mm
Antenna 4	≤ 25mm	≤ 25mm	≤ 25mm	>25mm	≤ 25mm	>25mm
Antenna 5	≤ 25mm	≤ 25mm	>25mm	>25mm	≤ 25mm	>25mm
Antenna 6	≤ 25mm	≤ 25mm	≤ 25mm	>25mm	>25mm	≤ 25mm
Antenna 7	≤ 25mm	≤ 25mm	≤ 25mm	>25mm	>25mm	≤ 25mm
Antenna 8	≤ 25mm	≤ 25mm	>25mm	>25mm	>25mm	≤ 25mm
Antenna 9	≤ 25mm	≤ 25mm	>25mm	≤ 25mm	>25mm	≤ 25mm
Antenna 10	≤ 25mm	≤ 25mm	≤ 25mm	>25mm	≤ 25mm	>25mm
NFC Antenna	≤ 25mm	≤ 25mm	≤ 25mm	>25mm	≤ 25mm	>25mm

Positions for SAR tests; Hotspot mode						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
Antenna 0	Yes	Yes	No	Yes	Yes	Yes
Antenna 1	Yes	Yes	No	Yes	No	Yes
Antenna 2	Yes	Yes	Yes	No	No	Yes
Antenna 4	Yes	Yes	Yes	No	Yes	No
Antenna 5	Yes	Yes	No	No	Yes	No
Antenna 6	Yes	Yes	Yes	No	No	Yes
Antenna 7	Yes	Yes	Yes	No	No	Yes
Antenna 8	Yes	Yes	No	No	No	Yes
Antenna 9	Yes	Yes	No	Yes	No	Yes
Antenna 10	Yes	Yes	Yes	No	Yes	No
NFC Antenna	Yes	Yes	Yes	No	Yes	No

Note: Referring to KDB 941225 D06 v02r01, when the overall device length and width are ≥ 9cm*5cm, the test distance is 10 mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge.