FCC RADIO TEST REPORT

FCC ID	:	**MSQI001D**
Equipment	:	**ASUS Phone(Mobile Phone)**
Brand Name	:	**ASUS**
Model Name	:	**ASUS_I001D** **ASUS_I001DC**
Applicant	:	**ASUSTeK COMPUTER INC.** **4F, No. 150, LI-TE RD., PEITOU, TAIPEI, TAIWAN**
Manufacturer	:	**Guangdong Enok Communication Co., Ltd.** **No. 137, 139, Lixiang Road., Songmushan Village, Dalang Town, Dongguan City, Guangdong Province, China**
Standard	:	**FCC Part 15 Subpart C §15.247**

The product was received on Mar. 13, 2019 and testing was started from May 15, 2019 and completed on Jul. 01, 2019. We, SPORTON INTERNATIONAL INC., EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Jones Tsai

Approved by: Jones Tsai

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)

Table of Contents

History of this test report **3**
Summary of Test Result **4**
1 General Description **5**
1.1 Product Feature of Equipment Under Test 5
1.2 Modification of EUT 5
1.3 Testing Location 6
1.4 Applicable Standards 6
2 Test Configuration of Equipment Under Test **7**
2.1 Carrier Frequency Channel 7
2.2 Test Mode 8
2.3 Connection Diagram of Test System 9
2.4 Support Unit used in test configuration and system 9
2.5 EUT Operation Test Setup 9
2.6 Measurement Results Explanation Example 10
3 Test Result **11**
3.1 6dB and 99% Bandwidth Measurement 11
3.2 Output Power Measurement 18
3.3 Power Spectral Density Measurement 19
3.4 Conducted Band Edges and Spurious Emission Measurement 26
3.5 Radiated Band Edges and Spurious Emission Measurement 35
3.6 AC Conducted Emission Measurement 39
3.7 Antenna Requirements 41
4 List of Measuring Equipment **42**
5 Uncertainty of Evaluation **44**
Appendix A. Conducted Test Results
Appendix B. AC Conducted Emission Test Result
Appendix C. Radiated Spurious Emission
Appendix D. Radiated Spurious Emission Plots
Appendix E. Duty Cycle Plots
Appendix F. Setup Photographs

History of this test report

Report No.	Version	Description	Issued Date
FR931316B	01	Initial issue of report	Jul. 08, 2019

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Reporting only	-
3.2	15.247(b)(3)	Peak Output Power	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	Pass	Under limit 6.16 dB at 89.400 MHz
3.6	15.207	AC Conducted Emission	Pass	Under limit 4.49 dB at 13.560MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	Pass	-

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Wii Chang

Report Producer: Ann Lee

1 General Description

1.1 Product Feature of Equipment Under Test

GSM/CDMA/WCDMA/LTE, Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n/ac, Wi-Fi 5GHz 802.11a/n/ac, FM Receiver, NFC, and GNSS.

Product Specification subjective to this standard	
Antenna Type	WWAN: PIFA Antenna WLAN **<Ant. 0>:** PIFA Antenna **<Ant. 1>:** PIFA Antenna **<Ant. 2>:** PIFA Antenna **<Ant. 3>:** PIFA Antenna Bluetooth: PIFA Antenna GPS / Glonass / BDS / Galileo: PIFA Antenna NFC: Loop Antenna FM: Using Earphone as Antenna

<Sample Information>

Sample	Sample 1	Sample 2	Sample 3	Sample 4	Sample 5
Confi	8G/256GB	12G/512GB	12G/512GB	12G/128GB	12G/256GB
LCD+ Touch module	TIANMA/TA066VVHM01-00 ON CELL	TIANMA/TA066VVHM01-00 ON CELL	TIANMA/TA066VVHM01-00 ON CELL	TIANMA/TA066VVHM01-00 ON CELL	TM/TA066VVHM01-00 2.0 ON CELL
Front Camera 24M	AZUREWAVE/AM-9BF8N01-A	SUNWIN/SWCG572Y0DAB-VA	AZUREWAVE/AM-9BF8N01-A	SUNWIN/SWCG572Y0DAB-VA	SUNWIN/SWCG572Y0DAB-VA
Rear Camera 48M	OFILM/OSS1588	LUXVISIONS/9BAL02P3	OFILM/OSS1588	PRIMAX/50-704J1ASC8	LUXVISIONS/9BAL02P3
Finger print	ACE TW/9105-260002101	ACE TW/9105-260002101	ACE TW/9105-260002101	ACE TW/9105-260002101	ACE TW/9105-260002101
BATT	SCUD/C11P1901	SCUD/C11P1901	SCUD/C11P1901	SCUD/C11P1901	SCUD/C11P1901
CPU	QUALCOMM 893MPSP/SM-8150-1-893BMPSP-TR-03-0-AB	QUALCOMM 893MPSP/SM-8150-1-893BMPSP-TR-03-0-AB	QUALCOMM 893MPSP/SM-8150-1-893BMPSP-TR-03-0-AB	QUALCOMM 893MPSP/SM-8150-1-MPSP893-TR-03-0-AC	QUALCOMM 893MPSP/SM-8150-5-MPSP893-TR-03-0-AC
DDR	SAMSUNG/K3UH7H70AM-AGCL	SAMSUNG/K3UHAHA0AM-AGCL	SAMSUNG/K3UHAHA0AM-AGCL	SAMSUNG/K3UHAHA0AM-AGCL	SAMSUNG/K3UHAHA0AM-AGCL
UFS	Samsung/KLUEG8U1EA-B0C1	Samsung/KLUFG8R1EM-B0C1	Samsung/KLUFG8R1EM-B0C1	SAMSUNG KLUDG4UHDB-B2D1	HYNIX/H28S9O302BMR

1.2 Modification of EUT

No modifications are made to the EUT during all test items.

1.3 Testing Location

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory	
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	**Sporton Site No.**	
	TH05-HY	CO05-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	**Sporton Site No.**
	03CH011-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW0007

1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05r02
- FCC KDB 414788 D01 Radiated Test Site v01r01
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-

2.2 Test Mode

a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Camera Mode: Z plane for 1Mbps with bottom port for Ant. 3, X plane for 2Mbps with bottom port for Ant. 3; Calling and Gaming Mode: Z plane for 1Mbps and 2Mbps with bottom port for Ant. 0) were recorded in this report.

b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	**Data Rate / Modulation**
	Bluetooth – LE / GFSK
Conducted Test Cases	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps
Radiated Test Cases	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps
AC Conducted Emission	Mode 1 : GSM 850 Idle + Bluetooth Link + WLAN (2.4GHz) Link + X Mode + Aura Sync + NFC On + MPEG4 (Color Bar) + Earphone 3 + Inbox 1 (Charging from AC Adapter via USB Cable) + Fan on (Max.) + SIM 1 for Sample 3
Remark: For Radiated Test Cases, the tests were performed with Earphone 1 and Sample 3	

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	Bluetooth Earphone	Sony Ericsson	MW600	PY700A2029	N/A	N/A
3.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	ASUS	Unshielded, 1.8 m
4.	Notebook	DELL	Latitude E6320	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
5.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A
6.	Earphone 3	ASUS	EA010	FCC DoC	Unshielded, 1.2 m	N/A

2.5 EUT Operation Test Setup

The RF test items, utility “QRCT Version3.0.271.0” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 5.4dB and 20dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 5.4 + 20 = 25.4 (dB)

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) ≥ 3 * RBW.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

<1Mbps>

6 dB Bandwidth Plot on Channel 00



Date: 20.MAY.2019 05:12:34

6 dB Bandwidth Plot on Channel 19



Date: 20.MAY.2019 05:16:11

6 dB Bandwidth Plot on Channel 39



Date: 20.MAY.2019 05:19:13

<2Mbps>

6 dB Bandwidth Plot on Channel 00



Date: 20.MAY.2019 05:23:33

6 dB Bandwidth Plot on Channel 19



Date: 20.MAY.2019 05:27:23

6 dB Bandwidth Plot on Channel 39



Date: 20.MAY.2019 05:34:53

3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

<1Mbps>

99% Bandwidth Plot on Channel 00



Date: 20.MAY.2019 05:14:26

99% Occupied Bandwidth Plot on Channel 19



Date: 20.MAY.2019 05:18:05

99% Occupied Bandwidth Plot on Channel 39



Date: 20.MAY.2019 05:21:08

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

<2Mbps>

99% Bandwidth Plot on Channel 00



Date: 20.MAY.2019 05:26:04

99% Occupied Bandwidth Plot on Channel 19



Date: 20.MAY.2019 05:33:50

99% Occupied Bandwidth Plot on Channel 39



Date: 20.MAY.2019 05:37:35

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT was connected to the power meter by RF cable and attenuator.
3. The path loss was compensated to the results for each measurement.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.3.6 Test Result of Power Spectral Density Plots (100kHz)

<1Mbps>

PSD 100kHz Plot on Channel 00



Date: 20.MAY.2019 05:13:08

PSD 100kHz Plot on Channel 19



Date: 20.MAY.2019 05:16:43

PSD 100kHz Plot on Channel 39



Date: 20.MAY.2019 05:19:53

<2Mbps>

PSD 100kHz Plot on Channel 00



Date: 20.MAY.2019 05:24:34

PSD 100kHz Plot on Channel 19



Date: 20.MAY.2019 05:32:29

PSD 100kHz Plot on Channel 39



Date: 20.MAY.2019 05:35:33

3.3.7 Test Result of Power Spectral Density Plots (3kHz)

<1Mbps>

PSD 3kHz Plot on Channel 00



Date: 20.MAY.2019 05:12:51

PSD 3kHz Plot on Channel 19



Date: 20.MAY.2019 05:16:28

PSD 3kHz Plot on Channel 39



Date: 20.MAY.2019 05:19:36

<2Mbps>

PSD 3kHz Plot on Channel 00



Date: 20.MAY.2019 05:23:52

PSD 3kHz Plot on Channel 19



Date: 20.MAY.2019 05:27:44

PSD 3kHz Plot on Channel 39



Date: 20.MAY.2019 05:35:10

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.

3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

3.4.3 Test Procedure

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges Plots

<1Mbps>

Low Band Edge Plot on Channel 00



Date: 20.MAY.2019 05:13:23

High Band Edge Plot on Channel 39



Date: 20.MAY.2019 05:20:08

<2Mbps>

Low Band Edge Plot on Channel 00



Date: 20.MAY.2019 05:24:48

High Band Edge Plot on Channel 39



Date: 20.MAY.2019 05:35:56

3.4.6 Test Result of Conducted Spurious Emission Plots

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps

GFSK Channel 00



Date: 20.MAY.2019 05:13:41

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps

GFSK Channel 00



Date: 20.MAY.2019 05:13:59

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19



Date: 20.MAY.2019 05:17:28

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19



Date: 20.MAY.2019 05:17:43

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39



Date: 20.MAY.2019 05:20:29

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39



Date: 20.MAY.2019 05:20:44

Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 00



Date: 20.MAY.2019 05:25:08

Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 00



Date: 20.MAY.2019 05:25:34

Conducted Spurious Emission Plot on Bluetooth LE 2Mbps

GFSK Channel 19



Date: 20.MAY.2019 05:33:01

Conducted Spurious Emission Plot on Bluetooth LE 2Mbps

GFSK Channel 19



Date: 20.MAY.2019 05:33:19

Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 39



Date: 20.MAY.2019 05:36:55

Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 39



Date: 20.MAY.2019 05:37:09

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

See list of measuring equipment of this test report.

3.5.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
   (1) Span shall wide enough to fully capture the emission being measured;
   (2) Set RBW=100 kHz for f < 1 GHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
   (3) Set RBW = 1 MHz, VBW= 3MHz for f ≥ 1 GHz for peak measurement.
   For average measurement:
   - VBW = 10 Hz, when duty cycle is no less than 98 percent.
   - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

3.5.7 Duty Cycle

Please refer to Appendix E.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.6.2 Measuring Instruments

See list of measuring equipment of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.

3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz, VSWR : 2.5:1 max	Jul. 16, 2018	May 22, 2019~ Jun. 07, 2019	Jul. 15, 2019	Radiation (03CH11-HY)
Amplifier	SONOMA	310N	187312	9kHz~1GHz	Dec. 04, 2018	May 22, 2019~ Jun. 07, 2019	Dec. 03, 2019	Radiation (03CH11-HY)
Bilog Antenna	TESEQ	CBL 6111D&N-6-06	35414&AT-N0602	30MHz~1GHz	Oct. 13, 2018	May 22, 2019~ Jun. 07, 2019	Oct. 12, 2019	Radiation (03CH11-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1326	1GHz ~ 18GHz	Oct. 30, 2018	May 22, 2019~ Jun. 07, 2019	Oct. 29, 2019	Radiation (03CH11-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Nov. 22, 2018	May 22, 2019~ Jun. 07, 2019	Nov. 21, 2019	Radiation (03CH11-HY)
Preamplifier	Keysight	83017A	MY53270080	1GHz~26.5GHz	Nov. 14, 2018	May 22, 2019~ Jun. 07, 2019	Nov. 13, 2020	Radiation (03CH11-HY)
Spectrum Analyzer	Keysight	N9010A	MY54200486	10Hz ~ 44GHz	Oct. 19, 2018	May 22, 2019~ Jun. 07, 2019	Oct. 18, 2019	Radiation (03CH11-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1~4m	N/A	May 22, 2019~ Jun. 07, 2019	N/A	Radiation (03CH11-HY)
Turn Table	EMEC	TT 2000	N/A	0~360 Degree	N/A	May 22, 2019~ Jun. 07, 2019	N/A	Radiation (03CH11-HY)
Preamplifier	Jet-Power	JPA0118-55-303	1710001800055007	1GHz~18GHz	Apr. 01, 2019	May 22, 2019~ Jun. 07, 2019	Mar. 31, 2020	Radiation (03CH11-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170584	18GHz- 40GHz	Dec. 05, 2018	May 22, 2019~ Jun. 07, 2019	Dec. 04, 2019	Radiation (03CH11-HY)
EMI Test Receiver	Keysight	N9038A (MXE)	MY54130085	N/A	Nov. 01, 2018	May 22, 2019~ Jun. 07, 2019	Oct. 31, 2019	Radiation (03CH11-HY)
Software	Audix	E3 6.2009-8-24	RK-001042	N/A	N/A	May 22, 2019~ Jun. 07, 2019	N/A	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4PE	9kHz-30MHz	Mar. 13, 2019	May 22, 2019~ Jun. 07, 2019	Mar. 12, 2020	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY2859/2	30MHz-40GHz	Mar. 13, 2019	May 22, 2019~ Jun. 07, 2019	Mar. 12, 2020	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4PE	30M-18G	Mar. 13, 2019	May 22, 2019~ Jun. 07, 2019	Mar. 12, 2020	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY4274/2	30MHz-40GHz	Mar. 13, 2019	May 22, 2019~ Jun. 07, 2019	Mar. 12, 2020	Radiation (03CH11-HY)
Filter	Wainwright	WLK4-1000-1530-8000-40SS	SN11	1G Low Pass	Sep. 16, 2018	May 22, 2019~ Jun. 07, 2019	Sep. 17, 2019	Radiation (03CH11-HY)
Filter	Wainwright	WHKX12-2700-3000-18000-60SS	SN3	2.7G High Pass	Sep. 17, 2018	May 22, 2019~ Jun. 07, 2019	Sep. 16, 2019	Radiation (03CH11-HY)

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Sensor	DARE	RPR3006W	16I00054SNO10	10MHz~6GHz	Dec. 19, 2018	May 15, 2019~ Jul. 01, 2019	Dec. 18, 2019	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100057	9kHz-40GHz	Nov. 21, 2018	May 15, 2019~ Jul. 01, 2019	Nov. 20, 2019	Conducted (TH05-HY)
Switch Box & RF Cable	EM	EMSW18	SW1070903	N/A	Dec. 19, 2018	May 15, 2019~ Jul. 01, 2019	Dec. 18, 2019	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jun. 14, 2019	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Nov. 12, 2018	Jun. 14, 2019	Nov. 11, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 14, 2018	Jun. 14, 2019	Nov. 13, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 09, 2018	Jun. 14, 2019	Nov. 08, 2019	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Jun. 14, 2019	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Dec. 31, 2018	Jun. 14, 2019	Dec. 30, 2019	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Dec. 31, 2018	Jun. 14, 2019	Dec. 30, 2019	Conduction (CO05-HY)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.2

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.2

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.5

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.2

Appendix A. Test Result of Conducted Test Items

Test Engineer:	CreedWu	Temperature:	21~25	°C
Test Date:	2019/5/15 ~ 2019/07/01	Relative Humidity:	51~54	%

<For 1Mbps>

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.028	0.668	0.50	Pass
BLE	1Mbps	1	19	2440	1.028	0.668	0.50	Pass
BLE	1Mbps	1	39	2480	1.030	0.664	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	10.00	30.00	-1.87	8.13	36.00	Pass
BLE	1Mbps	1	19	2440	8.30	30.00	-1.87	6.43	36.00	Pass
BLE	1Mbps	1	39	2480	9.30	30.00	-1.87	7.43	36.00	Pass

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	10.32	-4.49	-1.87	8.00	Pass
BLE	1Mbps	1	19	2440	8.41	-6.34	-1.87	8.00	Pass
BLE	1Mbps	1	39	2480	9.22	-5.64	-1.87	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

Test Engineer:	CreedWu	Temperature:	21~25	°C
Test Date:	2019/5/15 ~ 2019/07/01	Relative Humidity:	51~54	%

<For 2Mbps>

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE5.0	2Mbps	1	0	2402	2.040	1.152	0.50	Pass
BLE5.0	2Mbps	1	19	2440	2.044	1.144	0.50	Pass
BLE5.0	2Mbps	1	39	2480	2.044	1.152	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE5.0	2Mbps	1	0	2402	10.00	30.00	-1.87	8.13	36.00	Pass
BLE5.0	2Mbps	1	19	2440	8.20	30.00	-1.87	6.33	36.00	Pass
BLE5.0	2Mbps	1	39	2480	9.30	30.00	-1.87	7.43	36.00	Pass

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE5.0	2Mbps	1	0	2402	10.30	-7.94	-1.87	8.00	Pass
BLE5.0	2Mbps	1	19	2440	8.47	-9.84	-1.87	8.00	Pass
BLE5.0	2Mbps	1	39	2480	9.23	-9.12	-1.87	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

Appendix B. AC Conducted Emission Test Results

Test Engineer :	Jimmy Chang	**Temperature :**	22.7~23.4℃
		Relative Humidity :	52~53%

EUT Information

Report NO :	931316
Test Mode :	Mode 1
Test Voltage :	120Vac/60Hz
Phase :	Line



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.168000	---	30.79	55.06	24.27	L1	OFF	19.5
0.168000	47.35	---	65.06	17.71	L1	OFF	19.5
0.174750	---	37.60	54.73	17.13	L1	OFF	19.5
0.174750	54.27	---	64.73	10.46	L1	OFF	19.5
0.186000	---	36.97	54.21	17.24	L1	OFF	19.5
0.186000	53.55	---	64.21	10.66	L1	OFF	19.5
0.190500	---	31.31	54.02	22.71	L1	OFF	19.5
0.190500	48.85	---	64.02	15.17	L1	OFF	19.5
0.251250	---	23.64	51.72	28.08	L1	OFF	19.5
0.251250	27.22	---	61.72	34.50	L1	OFF	19.5
3.867000	---	25.36	46.00	20.64	L1	OFF	19.7
3.867000	27.60	---	56.00	28.40	L1	OFF	19.7
13.560000	---	44.63	50.00	5.37	L1	OFF	20.0
13.560000	55.51	---	60.00	4.49	L1	OFF	20.0
22.749000	---	26.35	50.00	23.65	L1	OFF	20.3
22.749000	28.02	---	60.00	31.98	L1	OFF	20.3

EUT Information

Report NO :	931316
Test Mode :	Mode 1
Test Voltage :	120Vac/60Hz
Phase :	Neutral



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.172500	---	34.94	54.84	19.90	N	OFF	19.5
0.172500	52.02	---	64.84	12.82	N	OFF	19.5
0.181500	---	37.69	54.42	16.73	N	OFF	19.5
0.181500	51.68	---	64.42	12.74	N	OFF	19.5
0.188250	---	33.71	54.11	20.40	N	OFF	19.5
0.188250	50.02	---	64.11	14.09	N	OFF	19.5
0.258000	---	25.72	51.50	25.78	N	OFF	19.5
0.258000	37.53	---	61.50	23.97	N	OFF	19.5
0.350250	---	25.10	48.96	23.86	N	OFF	19.5
0.350250	34.43	---	58.96	24.53	N	OFF	19.5
1.029750	---	22.33	46.00	23.67	N	OFF	19.6
1.029750	23.28	---	56.00	32.72	N	OFF	19.6
4.710750	---	24.79	46.00	21.21	N	OFF	19.7
4.710750	25.74	---	56.00	30.26	N	OFF	19.7
13.560000	---	40.99	50.00	9.01	N	OFF	20.1
13.560000	55.16	---	60.00	4.84	N	OFF	20.1
23.460000	---	27.04	50.00	22.96	N	OFF	20.4
23.460000	29.26	---	60.00	30.74	N	OFF	20.4

Appendix C. Radiated Spurious Emission

Test Engineer :	Hao Hsu, FU Chen, Ken Wu, Troye Hsieh	Temperature :	23.2~24.2°C
		Relative Humidity :	53~60%

<Camera Mode>

2.4GHz 2400~2483.5MHz

BLE 1Mbps (Band Edge @ 3m)

BLE Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
3		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2367.12	53.38	-20.62	74	42.88	27.53	16.61	33.64	100	66	P	H
		2315.67	43.27	-10.73	54	32.64	27.74	16.55	33.66	100	66	A	H
	*	2402	101.27	-	-	90.85	27.4	16.65	33.63	100	66	P	H
	*	2402	100.59	-	-	90.17	27.4	16.65	33.63	100	66	A	H
		2356.305	53.59	-20.41	74	43.06	27.57	16.6	33.64	238	88	P	V
		2355.78	43.45	-10.55	54	32.91	27.58	16.6	33.64	238	88	A	V
	*	2402	100.81	-	-	90.39	27.4	16.65	33.63	238	88	P	V
	*	2402	100.33	-	-	89.91	27.4	16.65	33.63	238	88	A	V
BLE CH 19 2440MHz		2381.36	53.1	-20.9	74	42.63	27.47	16.63	33.63	129	67	P	H
		2372.24	43.48	-10.52	54	32.99	27.51	16.62	33.64	129	67	A	H
	*	2440	99.83	-	-	89.43	27.32	16.69	33.61	129	67	P	H
	*	2440	99.29	-	-	88.89	27.32	16.69	33.61	129	67	A	H
		2492.32	52.77	-21.23	74	42.31	27.3	16.75	33.59	129	67	P	H
		2488.4	43.37	-10.63	54	32.92	27.3	16.74	33.59	129	67	A	H
		2348.24	52.87	-21.13	74	42.31	27.61	16.59	33.64	266	89	P	V
		2384.88	43.49	-10.51	54	33.03	27.46	16.63	33.63	266	89	A	V
	*	2440	99.32	-	-	88.92	27.32	16.69	33.61	266	89	P	V
	*	2440	98.78	-	-	88.38	27.32	16.69	33.61	266	89	A	V
		2494.56	52.99	-21.01	74	42.53	27.3	16.75	33.59	266	89	P	V
		2492.8	43.5	-10.5	54	33.04	27.3	16.75	33.59	266	89	A	V

BLE Ant. 3	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 39 2480MHz	*	2480	101.9	-	-	91.47	27.3	16.73	33.6	107	66	P	H
	*	2480	101.13	-	-	90.7	27.3	16.73	33.6	107	66	A	H
		2498.28	53.03	-20.97	74	42.57	27.3	16.75	33.59	107	66	P	H
		2483.72	43.57	-10.43	54	33.13	27.3	16.74	33.6	107	66	A	H
	*	2480	100.33	-	-	89.9	27.3	16.73	33.6	261	101	P	V
	*	2480	99.78	-	-	89.35	27.3	16.73	33.6	261	101	A	V
		2497.88	52.89	-21.11	74	42.43	27.3	16.75	33.59	261	101	P	V
		2484.08	43.3	-10.7	54	32.86	27.3	16.74	33.6	261	101	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

2.4GHz 2400~2483.5MHz

BLE 1Mbps (Harmonic @ 3m)

BLE Ant. 3	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		4804	37.55	-36.45	74	54.61	31.1	11	59.16	100	0	P	H
		4804	37.55	-36.45	74	54.61	31.1	11	59.16	100	0	P	V
BLE CH 19 2440MHz		4880	37.84	-36.16	74	54.92	31.04	11.06	59.18	100	0	P	H
		7320	41.28	-32.72	74	50.26	36.54	13.65	59.17	100	0	P	H
		4880	37.33	-36.67	74	54.41	31.04	11.06	59.18	100	0	P	V
		7320	41.12	-32.88	74	50.1	36.54	13.65	59.17	100	0	P	V
BLE CH 39 2480MHz		4960	37.71	-36.29	74	54.47	31.32	11.11	59.19	100	0	P	H
		7440	40.61	-33.39	74	49.63	36.48	13.62	59.12	100	0	P	H
		4960	37.26	-36.74	74	54.02	31.32	11.11	59.19	100	0	P	V
		7440	40.57	-33.43	74	49.59	36.48	13.62	59.12	100	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

2.4GHz 2400~2483.5MHz

BLE 2Mbps (Band Edge @ 3m)

BLE Ant. 3	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		2334.99	54.46	-19.54	74	43.87	27.66	16.58	33.65	304	43	P	H
		2322.6	45.48	-8.52	54	34.86	27.71	16.56	33.65	304	43	A	H
	*	2402	99.07	-	-	88.65	27.4	16.65	33.63	304	43	P	H
	*	2402	97.56	-	-	87.14	27.4	16.65	33.63	304	43	A	H
		2352.945	53.49	-20.51	74	42.94	27.59	16.6	33.64	100	96	P	V
		2313.57	45.06	-8.94	54	34.42	27.75	16.55	33.66	100	96	A	V
	*	2402	96.88	-	-	86.46	27.4	16.65	33.63	100	96	P	V
	*	2402	95.65	-	-	85.23	27.4	16.65	33.63	100	96	A	V
BLE CH 19 2440MHz		2350.46	52.77	-21.23	74	42.22	27.6	16.59	33.64	303	74	P	H
		2368.24	45.09	-8.91	54	34.59	27.53	16.61	33.64	303	74	A	H
	*	2440	98.28	-	-	87.88	27.32	16.69	33.61	303	74	P	H
	*	2440	96.95	-	-	86.55	27.32	16.69	33.61	303	74	A	H
		2494.4	53.83	-20.17	74	43.37	27.3	16.75	33.59	303	74	P	H
		2483.62	44.85	-9.15	54	34.41	27.3	16.74	33.6	303	74	A	H
		2311.4	53.19	-20.81	74	42.55	27.75	16.55	33.66	106	96	P	V
		2366.84	45	-9	54	34.5	27.53	16.61	33.64	106	96	A	V
	*	2440	97.23	-	-	86.83	27.32	16.69	33.61	106	96	P	V
	*	2440	95.82	-	-	85.42	27.32	16.69	33.61	106	96	A	V
		2486.91	53.07	-20.93	74	42.62	27.3	16.74	33.59	106	96	P	V
		2494.05	44.98	-9.02	54	34.52	27.3	16.75	33.59	106	96	A	V

BLE Ant. 3	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 39 2480MHz	*	2480	101.92	-	-	91.49	27.3	16.73	33.6	296	74	P	H
	*	2480	98.81	-	-	88.38	27.3	16.73	33.6	296	74	A	H
		2483.6	55.02	-18.98	74	44.58	27.3	16.74	33.6	296	74	P	H
		2488.32	45.28	-8.72	54	34.83	27.3	16.74	33.59	296	74	A	H
	*	2480	99.47	-	-	89.04	27.3	16.73	33.6	100	95	P	V
	*	2480	98.06	-	-	87.63	27.3	16.73	33.6	100	95	A	V
		2483.68	53.03	-20.97	74	42.59	27.3	16.74	33.6	100	95	P	V
		2493.52	44.86	-9.14	54	34.4	27.3	16.75	33.59	100	95	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

2.4GHz 2400~2483.5MHz

BLE 2Mbps (Harmonic @ 3m)

BLE Ant. 3	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		4804	37.49	-36.51	74	54.55	31.1	11	59.16	100	0	P	H
		4804	38.07	-35.93	74	55.13	31.1	11	59.16	100	0	P	V
BLE CH 19 2440MHz		4880	37.58	-36.42	74	54.66	31.04	11.06	59.18	100	0	P	H
		7320	41.95	-32.05	74	50.93	36.54	13.65	59.17	100	0	P	H
		4880	37.26	-36.74	74	54.34	31.04	11.06	59.18	100	0	P	V
		7320	41.77	-32.23	74	50.75	36.54	13.65	59.17	100	0	P	V
BLE CH 39 2480MHz		4960	37.76	-36.24	74	54.52	31.32	11.11	59.19	100	0	P	H
		7440	41.2	-32.8	74	50.22	36.48	13.62	59.12	100	0	P	H
		4960	37.72	-36.28	74	54.48	31.32	11.11	59.19	100	0	P	V
		7440	41.08	-32.92	74	50.1	36.48	13.62	59.12	100	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Emission below 1GHz

2.4GHz BLE (LF)

BLE Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
3		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BLE LF		89.4	37.34	-6.16	43.5	53.83	14.55	1.29	32.33	100	0	P	H
		174.99	35.32	-8.18	43.5	50.65	15.07	1.86	32.26	-	-	P	H
		241.95	33.72	-12.28	46	46.56	17.25	2.12	32.21	-	-	P	H
		855.8	32.84	-13.16	46	31.11	29.23	4.08	31.58	-	-	P	H
		955.9	34.08	-11.92	46	29.76	30.83	4.33	30.84	-	-	P	H
		969.2	34.35	-19.65	54	29.71	30.98	4.37	30.71	-	-	P	H
		48.09	30.19	-9.81	40	46.6	15.04	0.92	32.37	-	-	P	V
		53.49	33.57	-6.43	40	52.34	12.63	0.97	32.37	100	0	P	V
		114.24	30.92	-12.58	43.5	44.94	16.87	1.42	32.31	-	-	P	V
		863.5	32.23	-13.77	46	30.38	29.29	4.1	31.54	-	-	P	V
		910.4	32.69	-13.31	46	30.71	29.02	4.21	31.25	-	-	P	V
		971.3	34.91	-19.09	54	30.25	30.97	4.38	30.69	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

<Calling and Gaming Mode>

2.4GHz 2400~2483.5MHz

BLE 1Mbps (Band Edge @ 3m)

BLE Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
0		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2338.35	53.16	-20.84	74	42.58	27.65	16.58	33.65	127	131	P	H
		2343.285	43.26	-10.74	54	32.7	27.63	16.58	33.65	127	131	A	H
	*	2402	99.74	-	-	89.32	27.4	16.65	33.63	127	131	P	H
	*	2402	99.29	-	-	88.87	27.4	16.65	33.63	127	131	A	H
		2362.71	53.82	-20.18	74	43.3	27.55	16.61	33.64	327	1	P	V
		2349.48	43.41	-10.59	54	32.86	27.6	16.59	33.64	327	1	A	V
	*	2402	102.67	-	-	92.25	27.4	16.65	33.63	327	1	P	V
	*	2402	102.12	-	-	91.7	27.4	16.65	33.63	327	1	A	V
BLE CH 19 2440MHz		2313.2	52.75	-21.25	74	42.11	27.75	16.55	33.66	132	119	P	H
		2330.16	43.26	-10.74	54	32.66	27.68	16.57	33.65	132	119	A	H
	*	2440	96.12	-	-	85.72	27.32	16.69	33.61	132	119	P	H
	*	2440	95.53	-	-	85.13	27.32	16.69	33.61	132	119	A	H
		2496.4	52.91	-21.09	74	42.45	27.3	16.75	33.59	132	119	P	H
		2490	43.44	-10.56	54	32.99	27.3	16.74	33.59	132	119	A	H
		2380.08	52.92	-21.08	74	42.44	27.48	16.63	33.63	360	2	P	V
		2368.08	43.57	-10.43	54	33.07	27.53	16.61	33.64	360	2	A	V
	*	2440	100.19	-	-	89.79	27.32	16.69	33.61	360	2	P	V
	*	2440	99.62	-	-	89.22	27.32	16.69	33.61	360	2	A	V
		2492.72	52.53	-21.47	74	42.07	27.3	16.75	33.59	360	2	P	V
		2490.08	43.21	-10.79	54	32.76	27.3	16.74	33.59	360	2	A	V

BLE Ant. 0	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 39 2480MHz	*	2480	97.06	-	-	86.63	27.3	16.73	33.6	106	118	P	H
	*	2480	96.26	-	-	85.83	27.3	16.73	33.6	106	118	A	H
		2499.68	53.11	-20.89	74	42.65	27.3	16.75	33.59	106	118	P	H
		2483.64	43.61	-10.39	54	33.17	27.3	16.74	33.6	106	118	A	H
	*	2480	100.66	-	-	90.23	27.3	16.73	33.6	310	1	P	V
	*	2480	100.15	-	-	89.72	27.3	16.73	33.6	310	1	A	V
		2483.6	53.41	-20.59	74	42.97	27.3	16.74	33.6	310	1	P	V
		2484.44	43.57	-10.43	54	33.13	27.3	16.74	33.6	310	1	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

2.4GHz 2400~2483.5MHz

BLE 1Mbps (Harmonic @ 3m)

BLE Ant. 0	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		4804	36.77	-37.23	74	53.83	31.1	11	59.16	100	0	P	H
		4804	37.08	-36.92	74	54.14	31.1	11	59.16	100	0	P	V
BLE CH 19 2440MHz		4880	37.92	-36.08	74	55	31.04	11.06	59.18	100	0	P	H
		7320	45.18	-28.82	74	54.16	36.54	13.65	59.17	100	0	P	H
		4880	37.55	-36.45	74	54.63	31.04	11.06	59.18	100	0	P	V
		7320	43.88	-30.12	74	52.86	36.54	13.65	59.17	100	0	P	V
BLE CH 39 2480MHz		4960	38.47	-35.53	74	55.23	31.32	11.11	59.19	100	0	P	H
		7440	45.08	-28.92	74	54.1	36.48	13.62	59.12	100	0	P	H
		4960	39.1	-34.9	74	55.86	31.32	11.11	59.19	100	0	P	V
		7440	43.49	-30.51	74	52.51	36.48	13.62	59.12	100	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE Ant. 0	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		2347.905	54.11	-19.89	74	43.55	27.61	16.59	33.64	224	37	P	H
		2390	45.1	-8.9	54	34.65	27.44	16.64	33.63	224	37	A	H
	*	2402	103.01	-	-	92.59	27.4	16.65	33.63	224	37	P	H
	*	2402	101.72	-	-	91.3	27.4	16.65	33.63	224	37	A	H
													H
													H
		2327.115	53.19	-20.81	74	42.58	27.69	16.57	33.65	249	86	P	V
		2327.325	45.18	-8.82	54	34.57	27.69	16.57	33.65	249	86	A	V
	*	2402	102.58	-	-	92.16	27.4	16.65	33.63	249	86	P	V
	*	2402	101.23	-	-	90.81	27.4	16.65	33.63	249	86	A	V
BLE CH 19 2440MHz		2336.04	52.64	-21.36	74	42.05	27.66	16.58	33.65	224	31	P	H
		2313.22	45.15	-8.85	54	34.51	27.75	16.55	33.66	224	31	A	H
	*	2440	100.66	-	-	90.26	27.32	16.69	33.61	224	31	P	H
	*	2440	99.2	-	-	88.8	27.32	16.69	33.61	224	31	A	H
		2496.5	53.28	-20.72	74	42.82	27.3	16.75	33.59	224	31	P	H
		2498.88	44.8	-9.2	54	34.34	27.3	16.75	33.59	224	31	A	H
		2316.02	53.03	-20.97	74	42.4	27.74	16.55	33.66	195	283	P	V
		2344.58	45.31	-8.69	54	34.75	27.62	16.59	33.65	195	283	A	V
	*	2440	98.37	-	-	87.97	27.32	16.69	33.61	195	283	P	V
	*	2440	97.17	-	-	86.77	27.32	16.69	33.61	195	283	A	V
		2500	52.44	-21.56	74	41.98	27.3	16.75	33.59	195	283	P	V
		2483.97	45.16	-8.84	54	34.72	27.3	16.74	33.6	195	283	A	V

BLE Ant. 0	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 39 2480MHz	*	2480	100.99	-	-	90.56	27.3	16.73	33.6	212	35	P	H
	*	2480	99.37	-	-	88.94	27.3	16.73	33.6	212	35	A	H
		2483.64	54.33	-19.67	74	43.89	27.3	16.74	33.6	212	35	P	H
		2483.52	45.13	-8.87	54	34.69	27.3	16.74	33.6	212	35	A	H
	*	2480	98.21	-	-	87.78	27.3	16.73	33.6	198	268	P	V
	*	2480	96.96	-	-	86.53	27.3	16.73	33.6	198	268	A	V
		2483.84	52.98	-21.02	74	42.54	27.3	16.74	33.6	198	268	P	V
		2488.48	44.96	-9.04	54	34.51	27.3	16.74	33.59	198	268	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Emission below 1GHz

2.4GHz BLE (LF)

BLE Ant. 0	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
2.4GHz BLE LF		31.89	21.35	-18.65	40	29.75	23.18	0.79	32.37	-	-	P	H
		89.67	34.39	-9.11	43.5	50.83	14.6	1.29	32.33	100	0	P	H
		177.42	32.23	-11.27	43.5	47.68	14.93	1.88	32.26	-	-	P	H
		861.4	31.99	-14.01	46	30.14	29.3	4.1	31.55	-	-	P	H
		895.7	32.17	-13.83	46	30.35	29.01	4.18	31.37	-	-	P	H
		950.3	34.43	-11.57	46	30.42	30.59	4.31	30.89	-	-	P	H
		53.49	33.28	-6.72	40	52.05	12.63	0.97	32.37	100	0	P	V
		67.8	33.14	-6.86	40	52.54	11.83	1.12	32.35	-	-	P	V
		245.46	30.75	-15.25	46	43.16	17.66	2.14	32.21	-	-	P	V
		939.8	32.99	-13.01	46	29.74	29.94	4.29	30.98	-	-	P	V
		964.3	34.02	-19.98	54	29.44	30.99	4.35	30.76	-	-	P	V
		980.4	34.14	-19.86	54	29.49	30.86	4.4	30.61	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

Note symbol

*	**Fundamental Frequency** which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is **over limit** line.
P/A	**P**eak or **A**verage
H/V	**H**orizontal or **V**ertical

A calculation example for radiated spurious emission is shown as below:

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) =

Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.

Appendix D. Radiated Spurious Emission Plots

Test Engineer :	Hao Hsu, FU Chen, Ken Wu, Troye Hsieh	**Temperature :**	23.2~24.2°C
		Relative Humidity :	53~60%

Note symbol

-L	**Low channel location**
-R	**High channel location**

<Camera Mode>

2.4GHz 2400~2483.5MHz

BLE 1Mbps (Band Edge @ 3m)

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH00 2402MHz	
3	Horizontal	Fundamental
Peak		
Avg.		

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH00 2402MHz	
3	Vertical	Fundamental
Peak		
Avg		

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - L	
3	Horizontal	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 931316	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 931316
Avg.	 Site : 03CH11-HY Condition : AVG_BE_54 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 931316	 Site : 03CH11-HY Condition : AVG_54 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 931316

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - R	
3	Horizontal	Fundamental
Peak		Left blank
Avg.		Left blank

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - L	
3	Vertical	Fundamental
Peak		
Avg.		

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - R	
3	Vertical	Fundamental
Peak		Left blank
Avg.		Left blank

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH39 2480MHz	
3	Horizontal	Fundamental
Peak		
Avg.		

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH39 2480MHz	
3	Vertical	Fundamental
Peak		
Avg.		

2.4GHz 2400~2483.5MHz

BLE 1Mbps (Harmonic @ 3m)

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BLE CH00 2402MHz	
3	Horizontal	Vertical
Peak Avg.		

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BLE CH19 2440MHz	
3	Horizontal	Vertical
Peak Avg.		

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BLE CH39 2480MHz	
3	Horizontal	Vertical
Peak		

2.4GHz 2400~2483.5MHz

BLE 2Mbps (Band Edge @ 3m)

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH00 2402MHz	
3	Horizontal	Fundamental
Peak		
Avg.		

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH00 2402MHz	
3	Vertical	Fundamental
Peak		
Avg		

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - L	
3	Horizontal	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 931316	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 931316
Avg.	 Site : 03CH11-HY Condition : AVG_BE_54 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 931316	 Site : 03CH11-HY Condition : AVG_54 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 931316

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - R	
3	Horizontal	Fundamental
Peak		Left blank
Avg.		Left blank

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - L	
3	Vertical	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 9120D-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 931316	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 931316
Avg.	 Site : 03CH11-HY Condition : AVG_BE_54 3m HORN 9120D-HF VERTICAL : RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 931316	 Site : 03CH11-HY Condition : AVG_54 3m HORN 9120D-HF VERTICAL : RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 931316

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - R	
3	Vertical	Fundamental
Peak		Left blank
Avg.		Left blank

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH39 2480MHz	
3	Horizontal	Fundamental
Peak		
Avg.		

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH39 2480MHz	
3	Vertical	Fundamental
Peak		
Avg.		

2.4GHz 2400~2483.5MHz

BLE 2Mbps (Harmonic @ 3m)

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BLE CH00 2402MHz	
3	Horizontal	Vertical
Peak Avg.	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 931316	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 931316

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BLE CH19 2440MHz	
3	Horizontal	Vertical
Peak Avg.		

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BLE CH39 2480MHz	
3	Horizontal	Vertical
Peak	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 931316	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 931316

Emission below 1GHz

2.4GHz BLE (LF)

BLE	2.4GHz 2400~2483.5MHz	
ANT	BLE LF	
3	Horizontal	Vertical
QP / Peak		

<Calling and Gaming Mode>

2.4GHz 2400~2483.5MHz

BLE 1Mbps (Band Edge @ 3m)

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH00 2402MHz	
0	Horizontal	Fundamental
Peak		
Avg.		

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH00 2402MHz	
0	Vertical	Fundamental
Peak		
Avg		

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - L	
0	Horizontal	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 931316	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 931316
Avg.	 Site : 03CH11-HY Condition : AVG_BE_54 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 931316	 Site : 03CH11-HY Condition : AVG_54 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 931316

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - R	
0	Horizontal	Fundamental
Peak		Left blank
Avg.		Left blank

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - L	
0	Vertical	Fundamental
Peak		
Avg.		

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - R	
0	Vertical	Fundamental
Peak		Left blank
Avg.		Left blank

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH39 2480MHz	
0	Horizontal	Fundamental
Peak		
Avg.		

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH39 2480MHz	
0	Vertical	Fundamental
Peak		
Avg.		

2.4GHz 2400~2483.5MHz

BLE 1Mbps (Harmonic @ 3m)

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BLE CH00 2402MHz	
0	Horizontal	Vertical
Peak Avg.	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 931316	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 931316

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BLE CH19 2440MHz	
0	Horizontal	Vertical
Peak Avg.		

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BLE CH39 2480MHz	
0	Horizontal	Vertical
Peak	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 931316	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 931316

2.4GHz 2400~2483.5MHz

BLE 2Mbps (Band Edge @ 3m)

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH00 2402MHz	
0	Horizontal	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 931316	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 931316
Avg.	 Site : 03CH11-HY Condition : AVG_BE_54 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 931316	 Site : 03CH11-HY Condition : AVG_54 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 931316

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH00 2402MHz	
0	Vertical	Fundamental
Peak		
Avg		

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - L	
0	Horizontal	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 931316	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 931316
Avg.	 Site : 03CH11-HY Condition : AVG_BE_54 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 931316	 Site : 03CH11-HY Condition : AVG_54 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 931316

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - R	
0	Horizontal	Fundamental
Peak		Left blank
Avg.		Left blank

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - L	
0	Vertical	Fundamental
Peak		
Avg.		

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - R	
0	Vertical	Fundamental
Peak		Left blank
Avg.		Left blank

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH39 2480MHz	
0	Horizontal	Fundamental
Peak		
Avg.		

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH39 2480MHz	
0	Vertical	Fundamental
Peak		
Avg.		

Emission below 1GHz

2.4GHz BLE (LF)

BLE	2.4GHz 2400~2483.5MHz	
ANT	BLE LF	
0	Horizontal	Vertical
QP / Peak		

Appendix E. Duty Cycle Plots

Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting	Duty Factor(dB)
Bluetooth –LE for 1Mbps	61.62	390.19	2.56	3kHz	2.10
Bluetooth –LE for 2Mbps	32.05	200.00	5.00	10kHz	4.94

<1Mbps>



Date: 15.MAY.2019 22:23:29

<2Mbps>



Date: 1.JUL.2019 11:05:25